



A Survey of Techniques for Predicting Earthquake Ground Motions for Engineering Purposes

John Douglas, Hideo Aochi

► To cite this version:

John Douglas, Hideo Aochi. A Survey of Techniques for Predicting Earthquake Ground Motions for Engineering Purposes. *Surveys in Geophysics*, 2008, 29 (3), pp.187-220. 10.1007/s10712-008-9046-y . hal-00557625

HAL Id: hal-00557625

<https://brgm.hal.science/hal-00557625>

Submitted on 19 Jan 2011

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

**1 A survey of techniques for predicting earthquake ground
2 motions for engineering purposes**

3 John Douglas & Hideo Aochi

4

5 Received: date / Accepted: date

6 Abstract Over the past four or five decades many advances have been made in earth-
7 quake ground-motion prediction and a variety of procedures have been proposed. Some
8 of these procedures are based on explicit physical models of the earthquake source,
9 travel-path and recording site while others lack a strong physical basis and seek only
10 to replicate observations. In addition, there are a number of hybrid methods that seek
11 to combine benefits of different approaches. The various techniques proposed have their
12 adherents and some of them are extensively used to estimate ground motions for engi-
13 neering design purposes and in seismic hazard research. These methods all have their
14 own advantages and limitations that are not often discussed by their proponents.

15 The purposes of this article are to: summarise existing methods and the most
16 important references, provide a family tree showing the connections between different
17 methods and, most importantly, to discuss the advantages and disadvantages of each
18 method.

19 **Keywords** earthquake · earthquake scenario · seismic hazard assessment · strong
20 ground motion · ground-motion prediction

21 **1 Introduction**

22 The accurate estimation of the characteristics of the ground shaking that occurs during
23 damaging earthquakes is vital for efficient risk mitigation in terms of land-use planning
24 and the engineering design of structures to adequately withstand these motions. This
25 article has been provoked by a vast, and rapidly growing, literature on the development
26 of various methods for ground-motion prediction. In total, this article surveys roughly
27 two dozen methods proposed in the literature. Only about half are commonly in use
28 today. Some techniques are still in development and others have never been widely
29 used due to their limitations or lack of available tools, constraints on input parameters
30 or data for their application.

31 Earthquake ground-motion estimation that transforms event parameters, e.g. mag-
32 nitude and source location, to site parameters, either time-histories of ground motions
33 or strong-motion parameters (e.g. peak ground acceleration, PGA, or response spectral
34 displacement) is a vital component within seismic hazard assessment be it probabilistic
35 or deterministic (scenario-based). Ground-motion characteristics of interest depend on
36 the structure or effects being considered (e.g. McGuire 2004). At present, there are a
37 number of methods being used within research and engineering practice for ground-
38 motion estimation; however, it is difficult to understand how these different procedures
39 relate to each another and to appreciate their strengths and weaknesses. Hence, the
40 choice of which technique to use for a given task is not easy to make. The purpose of
41 this article is to summarise the links between the different methods currently in use

42 today and to discuss their advantages and disadvantages. The details of the methods
43 will not be discussed here; these can be found within the articles cited. Only a brief
44 description, list of required input parameters and possible outputs are given. The au-
45 dience of this article includes students and researchers in engineering seismology but
46 also seismic hazard analysts responsible for providing estimates for engineering projects
47 and earthquake engineers seeking to understand limits on the predictions provided by
48 hazard analyses. Numerous reviews of ground-motion simulation techniques have been
49 published (e.g. Aki 1982; Shinozuka 1988; Anderson 1991; Erdik and Durukal 2003)
50 but these have had different aims and scopes to this survey.

51 Only methods that can be used to estimate ground motions of engineering signifi-
52 cance are examined here, i.e. those motions from earthquakes with moment magnitude
53 M_w greater than 5 at source-to-site distances less than 100 km for periods between 0 to
54 4 s (but extending to permanent displacements for some special studies). In addition,
55 focus is given to the estimation of ground motions at flat rock sites since it is common
56 to separate the hazard at the bedrock from the estimation of site response (e.g. Dowrick
57 1977) and because site response modelling is, itself, a vast topic (e.g. Heuze et al 2004).
58 Laboratory models, including foam models (e.g. Archuleta and Brune 1975), are not
59 included because it is difficult to scale up to provide engineering predictions from such
60 experiments.

61 Section 2 summarises the different procedures that have been proposed within
62 a series of one-page tables (owing to the vast literature in this domain, only brief
63 details can be given) and through a diagram showing the links between the methods.
64 The problem of defining an earthquake scenario is discussed in Section 3. Section 4 is
65 concerned with the testing of methods using observations. The article concludes with
66 a discussion of how to select the most appropriate procedure for a given task.


67 **2 Summaries of different procedures**

68 As described by Ólafsson et al (2001) there are basically two approaches to the con-
69 struction of models for the prediction of earthquake ground motions: the mathematical
70 approach, where a model is analytically based on physical principles, and the experi-
71 mental one, where a mathematical model, which is not necessarily based on physical
72 insight, is fitted to experimental data. In addition, there are hybrid approaches com-
73 bining elements of both philosophies. Earthquakes are so complex that physical insight
74 alone is currently not sufficient to obtain a reasonable model. Ólafsson et al (2001)
75 term those models that only rely on measured data ‘black-box’ models.

76 Figure 1 summarises the links between the different methods described in Tables 1
77 to 22. Each table briefly: 1) describes the method; 2) lists the required input parameters
78 (bold for those parameters that are invariably used, italic for parameters that are
79 occasionally considered and normal font for those parameters that are often implicitly,
80 but not often explicitly, considered) and the outputs that can be reliably obtained; 3)
81 lists a maximum of a dozen key references (preference is given to: the original source
82 of the method, journal articles that significantly developed the approach and review
83 articles) including studies that test the approach against observations; 4) lists the
84 tools that are easily available to apply approach (public domain programs with good
85 documentation help encourage uptake of a method¹); 5) gives the rough level of use
86 of the technique in practice and in research; and finally 6) summarises the advantages
87 and disadvantages/limitations of the method. The following sections introduce each of
88 the four main types of methods.

¹ Some of the programs for ground-motion prediction are available for download from the ORFEUS Seismological Software Library (<http://www.orfeus-eu.org/Software/softwarelib.html>).

Fig. 1 Summary of the approximate date when a method was developed on the x-axis, links to other approaches and the level of detail of the scenario modelled on the y-axis. Boxes indicate those methods that are often used in research and/or practice.



89 2.1 Empirical methods

90 The three methods described in this section are closely based on strong ground motion
91 observations. Such empirical techniques are the most straightforward way to predict
92 ground motions in future earthquakes and they are based on the assumption that
93 shaking in future earthquakes will be similar to that observed in previous events. The
94 development of these methods roughly coincided with the recording of the first strong-
95 motion records in the 1930s but they continue to be improved. Empirical methods
96 remain the most popular procedure for ground-motion prediction, especially in engi-
97 neering practice. Tables 1 to 3 summarise the three main types of empirical methods.

98 [Table 1 about here.]

99 [Table 2 about here.]

100 [Table 3 about here.]

101 2.2 Black-box methods

102 This section describes four methods (Tables 4 to 7) that can be classified as black-box
103 approaches because they do not seek to accurately model the underlying physics of
104 earthquake ground motion but simply to replicate certain characteristics of strong-
105 motion records. They are generally characterised by simple formulations with a few
106 input parameters that modify white noise so that it more closely matches earthquake
107 shaking. These methods were generally developed in the 1960s and 1970s for engineer-
108 ing purposes to fill gaps in the small observational datasets then available. With the
109 great increase in the quantity and quality of strong-motion data and the development
110 of powerful techniques for physics-based ground-motion simulation, this family of pre-

111 diction techniques has become less important although some of the procedures are still
112 used in engineering practice.

113 [Table 4 about here.]

114 [Table 5 about here.]

115 [Table 6 about here.]

116 [Table 7 about here.]

117 2.3 Physics-based methods

118 Although this class of methods was simply called the ‘mathematical approach’ by
119 Ólafsson et al (2001), the recent advances in the physical comprehension of the dynamic
120 phenomena of earthquakes and in the simulation technology means that we prefer the
121 name ‘physics-based methods’. These techniques often consist of two stages: simulation
122 of the generation of seismic waves (through fault rupture) and simulation of wave
123 propagation. Due to this separation it is possible to couple the same source model with
124 differing wave propagation approaches or different source models with the same wave
125 propagation code (e.g. Aochi and Douglas 2006). In this survey emphasis is placed on
126 wave propagation techniques.

127 Source models that have been used extensively for ground-motion prediction include
128 theoretical works by: Haskell (1969), Brune (1970, 1971), Papageorgiou and Aki (1983),
129 Gusev (1983), Joyner (1984), Zeng et al (1994) and Herrero and Bernard (1994). Such
130 insights are introduced into prescribed earthquake scenarios, called ‘kinematic’ source
131 models. It is well known that the near-source ground motion is significantly affected by
132 source parameters, such as the point of nucleation on the fault (hypocentre), rupture

velocity, slip distribution over the fault and the shape of the slip function (e.g. Miyake et al 2003; Mai and Beroza 2003; Tinti et al 2005; Ruiz et al 2007). This aspect is difficult to take into account in empirical methods. Recently it has become possible to introduce a complex source history numerically simulated by pseudo- or fully-dynamic modelling (e.g. Guatteri et al 2003, 2004; Aochi and Douglas 2006; Ripperger et al 2008) into the prediction procedure. Such dynamic simulations including complex source processes have been shown to successfully simulate previous large earthquakes, such as the 1992 Landers event (e.g. Olsen et al 1997; Aochi and Fukuyama 2002). This is an interesting and on-going research topic but we do not review them in this article.

All of the physics-based deterministic methods convolve the source function with synthetic Green's functions (the Earth's response to a point-source double couple) to produce the motion at ground surface. Erdik and Durukal (2003) provide a detailed review of the physics behind ground-motion modelling and show examples of ground motions simulated using different methods. Tables 8 to 18 summarise the main types of physics-based procedures classified based on the method used to calculate the synthetic seismograms in the elastic medium for a given earthquake source. Most of these are based on theoretical concepts introduced in the 1970s and 1980s and intensively developed in the past decade when significant improvements in the understanding of earthquake sources and wave propagation (helped by the recording of near-source ground motions) were coupled with improvements in computer technology to develop powerful computational capabilities. Some of these methods are extensively used for research purposes and for engineering projects of high-importance although most of them are rarely used in general engineering practice due to their cost and complexity.

[Table 8 about here.]

157 [Table 9 about here.]

158 [Table 10 about here.]

159 [Table 11 about here.]

160 [Table 12 about here.]

161 [Table 13 about here.]

162 [Table 14 about here.]

163 [Table 15 about here.]

164 [Table 16 about here.]

165 [Table 17 about here.]

166 [Table 18 about here.]

167 2.4 Hybrid methods

168 To benefit from the advantages of two (or more) different approaches and to overcome
169 some of their disadvantages a number of hybrid methods have been proposed. These
170 are summarised in Tables 19 to 22. These techniques were developed later than the
171 other three families of procedures, which are the bases of these methods. Since their de-
172 velopment, mainly in the 1980s and 1990s, they have been increasingly used, especially
173 for research purposes. Their uptake in engineering practice has been limited until now,
174 although they seem to be gaining in popularity due to the engineering requirement for
175 broadband time-histories, e.g. for soil-structure interaction analyses.

176 [Table 19 about here.]

177 [Table 20 about here.]

178 [Table 21 about here.]

179 [Table 22 about here.]

180 **3 Earthquake scenario**

181 Before predicting the earthquake ground motions that could occur at a site it is nec-
182 essary to define an earthquake scenario or scenarios, i.e. earthquake(s) that need(s)
183 to be considered in the design (or risk assessment) process for the site. The methods
184 proposed in the literature to define these scenarios (e.g. Dowrick 1977; Hays 1980; Re-
185 iter 1990; Anderson 1997a; Bazzurro and Cornell 1999; Bommer et al 2000) are not
186 discussed here. In this section the focus is on the level of detail required to define a
187 scenario for different ground-motion prediction techniques, which have varying degrees
188 of freedom. In general, physics-based (generally complex) methods require more pa-
189 rameters to be defined than empirical (generally simple) techniques. As the number
190 of degrees of freedom increases sophisticated prediction techniques can model more
191 specific earthquake scenarios, but it becomes difficult to constrain the input parame-
192 ters. The various methods consider different aspects of the ground-motion generation
193 process to be important and set (either explicitly or implicitly) different parameters
194 to default values. However, even for methods where a characteristic can be varied it is
195 often set to a standard value due to a lack of knowledge. In fact, when there is a lack
196 of knowledge (epistemic uncertainty) the input parameters should be varied within a
197 physically-realistic range rather than fixed to default values. Care must be taken to
198 make sure that parameters defining a scenario are internally consistent. For example,

199 asperity size and asperity slip contrast of earthquake ruptures are generally inversely
200 correlated (e.g. Bommer et al 2004).

201 The basic parameters required to define a scenario for almost all methods are mag-
202 nitude and source-to-site distance (note that, as stated in Section 1, hazard is generally
203 initially computed for a rock site and hence site effects are not considered here). In
204 addition, other gross source characteristics, such as the style-of-faulting mechanism,
205 are increasingly being considered. An often implicit general input variable for simple
206 techniques is ‘seismotectonic regime’, which is explicitly accounted for in more com-
207 plex approaches through source and path modelling. In this article, we assume that
208 kinematic source models (where the rupture process is a fixed input) are used for
209 ground-motion simulations. Dynamic source modelling (where the rupture process is
210 simulated by considering stress conditions) is a step up in complexity from kinematic
211 models and it remains mainly a research topic that is very rarely used for generating
212 time-histories for engineering design purposes. Dynamic rupture simulations have the
213 advantage over kinematic source models in proposing various possible rupture scenar-
214 ios of different magnitudes for a given seismotectonic situation (e.g. Anderson et al
215 2003; Aochi et al 2006). However, it is still difficult to tune the model parameters for
216 practical engineering purposes (e.g. Aochi and Douglas 2006) (see Section 2.3 for a
217 discussion of dynamic source models).

218 Many factors (often divided into source, path and site effects) have been observed
219 to influence earthquake ground motions, e.g.: earthquake magnitude (or in some ap-
220 proaches epicentral macroseismic intensity), faulting mechanism, source depth, fault
221 geometry, stress drop and direction of rupture (directivity); source-to-site distance,
222 crustal structure, geology along wave paths, radiation pattern and directionality; and
223 site geology, topography, soil-structure interaction and nonlinear soil behaviour. The

combination of these different, often inter-related, effects leads to dispersion in ground motions. The varying detail of the scenarios (i.e. not accounting for some factors while modelling others) used for the different techniques consequently leads to dispersion in the predictions. The unmodelled effects, which can be important, are ignored and consequently predictions from some simple techniques (e.g. empirical ground-motion models) contain a bias due to the (unknown) distribution of records used to construct the model with respect to these variables (e.g. Douglas 2007). There is more explicit control in simulation-based procedures. Concerning empirical ground-motion models McGuire (2004) says that ‘only variables that are known and can be specified *before* an earthquake should be included in the predictive equation. Using what are actually random properties of an earthquake source (properties that might be known *after* an earthquake) in the ground motion estimation artificially reduces the apparent scatter, requires more complex analysis, and may introduce errors because of the added complexity.’

In empirical methods the associated parameters that cannot yet be estimated before the earthquake, e.g. stress drop and details of the fault rupture, are, since observed ground motions are used, by definition, within the range of possibilities. Varying numbers of these parameters need to be chosen when using simulation techniques, which can be difficult. On the other hand, only a limited and unknown subset of these parameters are sampled by empirical methods since not all possible earthquakes have been recorded. In addition, due to the limited number of strong-motion records from a given region possible regional dependence of these parameters cannot usually be accounted for by empirical procedures since records from a variety of areas are combined in order to obtain a sufficiently large dataset.

248 Various prediction methods account for possible regional dependence (e.g. Douglas
249 2007) in different ways. Methods based on observed ground motions implicitly hope
250 that the strong-motion records capture the complete regional dependence and that the
251 range of possible motions is not underestimated. However, due to limited databanks
252 it is not often possible to only use records from small regions of interest; data from
253 other areas usually need to be imported. Physics-based methods explicitly model re-
254 gional dependence through the choice of input parameters, some of which, e.g. crustal
255 structure, can be estimated from geological information or velocimetric (weak-motion)
256 data, while others, e.g. stress parameters, can only be confidently estimated based
257 on observed strong-motion data from the region. If not available for a specific region
258 parameters must be imported from other regions or a range of possible values assumed.

259 Although this article does not discuss site effects nor their modelling, it is important
260 that the choice of which technique to use for a task is made considering the potential
261 use of the ground-motion predictions on rock for input to a site response analysis. For
262 example, predictions from empirical methods are for rock sites whose characteristics
263 (e.g. velocity and density profiles and near-surface attenuation) are limited by the ob-
264 servational database available and therefore the definition of rock cannot, usually, be
265 explicitly defined by the user; however, approximate adjustments to unify predictions
266 at different rock sites can be made (e.g. Cotton et al 2006). In addition, the character-
267 istics of the rock sites within observational databases are generally poorly known (e.g.
268 Cotton et al 2006) and therefore the rock associated with the prediction is ill-defined.
269 In contrast, physics-based techniques generally allow the user to explicitly define the
270 characteristics of the rock site and therefore more control is available. The numerical
271 resolution of each method puts limits on the velocities and thicknesses of the suffi-
272 ciently layers that can be treated. Black-box approaches generally neglect site effects

273 and, when they do, the parameters for controlling the type of site to use are, as in
274 empirical techniques, constrained based on (limited) observational databases.

275 **4 Testing of methods**

276 Predicted ground motions should be compared to observations for the considered site,
277 in terms of amplitude, frequency content, duration, energy content and more difficult
278 to characterise aspects, such as the ‘look’ of the time-histories. This verification of the
279 predictions is required so that the ground-motion estimates can be used with confi-
280 dence in engineering and risk analyses. Such comparisons take the form of either point
281 comparisons for past earthquakes (e.g. Aochi and Madariaga 2003), visually checking
282 a handful of predictions and observations in a non-systematic way, or more general
283 routine validation exercises, where hundreds of predictions and observations are statis-
284 tically compared to confirm that the predictions are not significantly biased and do not
285 display too great a scatter (a perfect fit between predictions and observations is not
286 expected, or generally possible, when making such general comparisons) (e.g. Atkinson
287 and Somerville 1994; Silva et al 1999; Douglas et al 2004). In a general comparison it
288 is also useful to check the correlation coefficients between various strong-motion pa-
289 rameters (e.g. PGA and relative significant duration, RSD) to verify that they match
290 the correlations commonly observed (Aochi and Douglas 2006).

291 For those techniques that are based on matching a set of strong-motion intensity
292 parameters, such as the elastic response spectral ordinates, it is important that the
293 fit to non-matched parameters is used to verify that they are physically realistic, i.e.
294 to check the internal consistency of the approach. For example, black-box techniques
295 that generate time-histories to match a target elastic response spectrum can lead to

296 time-histories with unrealistic displacement demand and energy content (Naeim and
297 Lew 1995).

298 A potentially useful approach, although one that is rarely employed, is to use a
299 construction set of data to calibrate a method and then an independent validation set
300 of data to test the predictions. Using such a two-stage procedure will demonstrate that
301 any free parameters tuned during the first step do not need further modifications for
302 other situations. Such a demonstration is important when there is a trade-off between
303 parameters whereby various choices can lead to similar predicted ground motions for
304 a given scenario.

305 One problem faced by all validation analysis is access to all the required independent
306 parameters, such as local site conditions, in order that the comparisons are fair. If a
307 full set of independent variables is not available then assumptions need to be made,
308 which can lead to uncertainty in the comparisons. For example, Boore (2001), when
309 comparing observations from the Chi-Chi earthquake to shaking predicted by various
310 empirical ground-motion models, had to make assumptions on site classes due to poor
311 site information for Taiwanese stations. These assumptions led to a lack of precision
312 in the level of over-prediction of the ground motions.

313 Until recently most comparisons between observations and predictions were visual
314 or based on simple measures of goodness-of-fit, such as: the mean bias and the overall
315 standard deviation sometimes computed using a maximum-likelihood approach (Spu-
316 dich et al 1999). Scherbaum et al (2004) develop a statistical technique for ranking
317 various empirical ground-motion models by their ability to predict a set of observed
318 ground motions. Such a method could be modified for use with other types of pre-
319 dictions. However, the technique of Scherbaum et al (2004) relies on estimates of the
320 scatter in observed motions, which are difficult to assess for techniques based on ground-

321 motion simulation, and the criteria used to rank the models would probably require
322 modification if applied to other prediction techniques. Assessment of the uncertainty
323 in simulations requires considering all sources of dispersion: modelling (differences be-
324 tween the actual physical process and the simulation), random (detailed aspects of the
325 source and wave propagation that cannot be modelled deterministically at present)
326 and parametric (uncertainty in source parameters for future earthquakes) (Abraham-
327 son et al 1990). The approach developed by Abrahamson et al (1990) to split total
328 uncertainty into these different components means that the relative importance of dif-
329 ferent source parameters can be assessed and hence aids in the physical interpretation
330 of ground-motion uncertainty.

331 In addition to this consideration of different types of uncertainty, work has been
332 undertaken to consider the ability of a simulation technique to provide adequate pre-
333 dictions not just for a single strong-motion intensity parameter but many. Anderson
334 (2004) proposes a quantitative measure of the goodness-of-fit between synthetic and
335 observed accelerograms using ten different criteria that measure various aspects of the
336 motions, for numerous frequency bands. This approach could be optimized to require
337 less computation by adopting a series of strong-motion parameters that are poorly
338 correlated (orthogonal), and hence measure different aspects of ground motions, e.g.
339 amplitude characterised by PGA and duration characterised by RSD. A goodness-of-fit
340 approach based on the time-frequency representation of seismograms, as opposed to
341 strong-motion intensity parameters as in the method of Anderson (2004), is proposed
342 by Kristeková et al (2006) to compare ground motions simulated using different com-
343 puter codes and techniques. Since it has only recently been introduced this procedure
344 has yet to become common but it has the promise to be a useful objective strategy for
345 the validation of simulation techniques by comparing predicted and observed motions

346 and also by internal comparisons between methods. Some comprehensive comparisons
347 of the results from numerical simulations have been made in the framework of recent
348 research projects and workshops (e.g. Day et al 2005; Chaljub et al 2007b)

349 If what is required from a method is a *set* of ground motions that include the
350 possible variability in shaking at a site from a given event then it is important to
351 use a method that introduces some randomness into the process (e.g. Pousse et al
352 2006) to account for random and parametric uncertainties. For example, results from
353 physically-based simulation techniques will not reproduce the full range of possible
354 motions unless a stochastic element is introduced into the prediction, through the
355 source or path. However, if what is required from a technique is the ability to give
356 the closest prediction to an observation then this stochastic element is not necessarily
357 required.

358 **5 Synthesis and conclusions**

359 Dowrick (1977) notes that ‘[a]s with other aspects of design the degree of detail entered
360 into selecting dynamic input [i.e. ground-motion estimates] will depend on the size
361 and vulnerability of the project’. This is commonly applied in practice where simple
362 methods (GMPEs, representative accelerograms or black-box methods) are applied for
363 lower importance and less complex projects whereas physics-based techniques are used
364 for high importance and complex situations (although invariably in combination with
365 simpler methods). Methods providing time-histories are necessary for studies requiring
366 non-linear engineering analyses, which are becoming increasingly common. Dowrick
367 (1977) believes that ‘because there are still so many imponderables in this topic only
368 the simpler methods will be warranted in most cases’. However, due to the significant

369 improvements in techniques, knowledge, experience and computing power this view
370 from the 1970s is now less valid. Simple empirical ground-motion estimates have the
371 advantage of being more defensible and are more easily accepted by decision makers
372 due to their close connection to observations. Simulations are particularly important in
373 regions with limited (or non-existent) observational databanks and also for site-specific
374 studies, where the importance of different assumptions on the input parameters can
375 be studied. However, reliable simulations require good knowledge of the propagation
376 media and they are often computationally expensive.

377 One area where physics-based forward modelling breaks down is in the simulation
378 of high-frequency ground motions where the lack of detail in source (e.g. heterogeneities
379 of the rupture process) and path (e.g. scattering) models means high frequencies are
380 poorly predicted. Hanks and McGuire (1981) state that ‘[e]vidently, a realistic charac-
381 terization of high-frequency strong ground motion will require one or more stochastic
382 parameters that can account for phase incoherence.’ In contrast, Aki (2003) believes
383 that ‘[a]ll these new results suggest that we may not need to consider frequencies higher
384 than about 10 Hz in Strong Motion Seismology. Thus, it may be a viable goal for strong
385 motion seismologists to use entirely deterministic modeling, at least for path and site
386 effects, before the end of the 21st century.’

387 The associated uncertainties within ground-motion prediction remain high despite
388 many decades of research and increasingly sophisticated techniques. The unchanging
389 level of aleatory uncertainties within empirical ground-motion estimation equations
390 over the past thirty years are an obvious example of this (e.g. Douglas 2003). However,
391 estimates from simulation methods are similarly affected by large (and often unknown)
392 uncertainties. These large uncertainties oblige earthquake engineers to design structures
393 with large factors of safety that may not be required.

394 The selection of the optimum method for ground-motion estimation depends on
395 what data is available for assessing the earthquake scenario, resources available and
396 experience of the group. Currently the choice of method used for a particular study is
397 generally controlled by the experience and preferences of the worker and the tools and
398 software available to them rather than it being necessarily selected based on what is
399 most appropriate for the project.

400 There are still a number of questions concerning ground-motion prediction that
401 need to be answered. These include the following: possible regional dependence of
402 ground motions (e.g. Douglas 2007), the effect of rupture complexity on near-source
403 ground motion (e.g. Aochi and Madariaga 2003), the spatial variability of shaking (e.g.
404 Goda and Hong 2008) and the determination of upper bounds on ground motions (e.g.
405 Strasser et al 2008). All these questions are difficult to answer at present due to the
406 lack of near-source strong-motion data from large earthquakes in many regions (little
407 near-source data exists outside the western USA, Japan and Taiwan). Therefore, there
408 is a requirement to install, keep operational and improve, e.g. in terms of spatial density
409 (Trifunac 2007), strong-motion networks in various parts of the world. In addition, the
410 co-location of accelerometers and high-sample-rate instruments using global navigation
411 satellite systems (e.g. the Global Positioning System, GPS) could help improve the
412 prediction of long-period ground motions (e.g. Wang et al 2007).

413 In addition to the general questions mentioned above, more specific questions re-
414 lated to ground-motion prediction can be posed, such as: what is the most appropriate
415 method to use for varying quality and quantity of input data and for different seismo-
416 tectonic environments? how can the best use be made of the available data? how can
417 the uncertainties associated with a given method be properly accounted for? how can
418 the duration of shaking be correctly modelled? These types of questions are rarely ex-

419 plicitly investigated in articles addressing ground-motion prediction. In addition, more
420 detailed quantitative comparisons of simulations from different methods for the same
421 scenario should be conducted through benchmarks.

422 Over time the preferred techniques will tend to move to the top of Figure 1 (more
423 physically based approaches requiring greater numbers of input parameters) (e.g. Field
424 et al 2003) since knowledge of faults, travel paths and sites will become sufficient to
425 constrain input parameters. Such predictions will be site-specific as opposed to the
426 generic estimations commonly used at present. Due to the relatively high cost and
427 difficulty of ground investigations, detailed knowledge of the ground subsurface are
428 likely to continue to be insufficient for fully numerical simulations for high-frequency
429 ground motions, which require data on 3D velocity variations at a scale of tens of
430 metres. In the distant future when vast observational strong-motion databanks exist
431 including records from many well-studied sites and earthquakes, more sophisticated
432 versions of the simplest empirical technique, that of representative accelerograms, could
433 be used where selections are made not just using a handful of scenario parameters but
434 many, in order to select ground motions from scenarios close to that expected for a
435 study area.

436 **Acknowledgements** The design of the diagram in this article has benefited from advice
437 contained in the book by Tufte (2006). Some of the work presented in this article was funded
438 by the ANR project ‘Quantitative Seismic Hazard Assessment’ (QSHA). The rest was funded
439 by internal BRGM research projects. We thank the rest of the BRGM Seismic Risks unit for
440 numerous discussions on the topics discussed in this article. Finally, we thank two anonymous
441 reviewers for their careful and detailed reviews, which led to significant improvements to this
442 article.

 443 **References**

- 444 Abrahamson N, Atkinson G, Boore D, Bozorgnia Y, Campbell K, Chiou B, Idriss IM, Silva W,
 445 Youngs R (2008) Comparisons of the NGA ground-motion relations. *Earthquake Spectra*
 446 24(1):45–66, DOI 10.1193/1.2924363
- 447 Abrahamson NA, Shedlock KM (1997) Overview. *Seismological Research Letters* 68(1):9–23
- 448 Abrahamson NA, Somerville PG, Cornell CA (1990) Uncertainty in numerical strong mo-
 449 tion predictions. In: *Proceedings of the Fourth U.S. National Conference on Earthquake*
 450 *Engineering*, vol 1, pp 407–416
- 451 Aki K (1982) Strong motion prediction using mathematical modeling techniques. *Bulletin of*
 452 *the Seismological Society of America* 72(6):S29–S41
- 453 Aki K (2003) A perspective on the history of strong motion seismology. *Physics of the Earth*
 454 *and Planetary Interiors* 137:5–11
- 455 Aki K, Larner KL (1970) Surface motion of a layered medium having an irregular interface
 456 due to incident plane SH waves. *Journal of Geophysical Research* 75(5):933–954
- 457 Aki K, Richards PG (2002) *Quantitative Seismology*. University Science Books, Sausalito,
 458 California, USA
- 459 Akkar S, Bommer JJ (2006) Influence of long-period filter cut-off on elastic spectral displace-
 460 *ments*. *Earthquake Engineering and Structural Dynamics* 35(9):1145–1165
- 461 Ambraseys NN (1974) The correlation of intensity with ground motion. In: *Advancements in*
 462 *Engineering Seismology in Europe*, Trieste
- 463 Ambraseys NN, Douglas J, Sigbjörnsson R, Berge-Thierry C, Suhadolc P, Costa G, Smit PM
 464 (2004a) Dissemination of European Strong-Motion Data, volume 2. In: *Proceedings of*
 465 *Thirteenth World Conference on Earthquake Engineering*, paper no. 32
- 466 Ambraseys NN, Smit P, Douglas J, Margaris B, Sigbjörnsson R, Ólafsson S, Suhadolc P, Costa
 467 G (2004b) Internet site for European strong-motion data. *Bollettino di Geofisica Teorica*
 468 *ed Applicata* 45(3):113–129
- 469 Anderson G, Aagaard BT, Hudnut K (2003) Fault interactions and large complex earthquakes
 470 in the Los Angeles area. *Science* 302(5652):1946–1949, DOI 10.1126/science.1090747
- 471 Anderson JG (1991) Strong motion seismology. *Reviews of Geophysics* 29:700–720, part 2

-
- 472 Anderson JG (1997a) Benefits of scenario ground motion maps. *Engineering Geology* 48(1–
473 2):43–57
- 474 Anderson JG (1997b) Nonparametric description of peak acceleration above a subduction
475 thrust. *Seismological Research Letters* 68(1):86–93
- 476 Anderson JG (2004) Quantitative measure of the goodness-of-fit of synthetic seismograms. In:
477 Proceedings of Thirteenth World Conference on Earthquake Engineering, paper no. 243
- 478 Aochi H, Douglas J (2006) Testing the validity of simulated strong ground motion from the
479 dynamic rupture of a finite fault, by using empirical equations. *Bulletin of Earthquake
480 Engineering* 4(3):211–229, DOI 10.1007/s10518-006-0001-3
- 481 Aochi H, Fukuyama E (2002) Three-dimensional nonplanar simulation of the 1992 Landers
482 earthquake. *Journal of Geophysical Research* 107(B2), DOI 10.1029/2000JB000061
- 483 Aochi H, Madariaga R (2003) The 1999 Izmit, Turkey, earthquake: Nonplanar fault structure,
484 dynamic rupture process, and strong ground motion. *Bulletin of the Seismological Society
485 of America* 93(3):1249–1266
- 486 Aochi H, Cushing M, Scotti O, Berge-Thierry C (2006) Estimating rupture scenario like-
487 lihood based on dynamic rupture simulations: The example of the segmented Middle
488 Durance fault, southeastern France. *Geophysical Journal International* 165(2):436–446,
489 DOI 10.1111/j.1365-246X.2006.02842.x
- 490 Aoi S, Fujiwara H (1999) 3D finite-difference method using discontinuous grids. *Bulletin of the
491 Seismological Society of America* 89(4):918–930
- 492 Apse RJ, Luco JE (1983) On the Green's functions for a layered half-space. Part II. *Bulletin
493 of the Seismological Society of America* 73(4):931–951
- 494 Archuleta RJ, Brune JN (1975) Surface strong motion associated with a stick-slip event in
495 a foam rubber model of earthquakes. *Bulletin of the Seismological Society of America*
496 65(5):1059–1071
- 497 Atkinson GM (2001) An alternative to stochastic ground-motion relations for use in seismic
498 hazard analysis in eastern North America. *Seismological Research Letters* 72:299–306
- 499 Atkinson GM, Boore DM (2006) Earthquake ground-motion prediction equations for eastern
500 North America. *Bulletin of the Seismological Society of America* 96(6):2181–2205, DOI
501 10.1785/0120050245

-
- 502 Atkinson GM, Silva W (2000) Stochastic modeling of California ground motion. *Bulletin of*
503 *the Seismological Society of America* 90(2):255–274
- 504 Atkinson GM, Somerville PG (1994) Calibration of time history simulation methods. *Bulletin*
505 *of the Seismological Society of America* 84(2):400–414
- 506 Atkinson GM, Sonley E (2000) Empirical relationships between modified Mercalli intensity
507 and response spectra. *Bulletin of the Seismological Society of America* 90(2):537–544
- 508 Baker JW, Cornell CA (2006) Spectral shape, epsilon and record selection. *Earthquake Engi-*
509 *neering and Structural Dynamics* 35(9):1077–1095, DOI 10.1002/eqe.571
- 510 Bao HS, Bielak J, Ghattas O, Kallivokas LF, O'Hallaron DR, Shewchuk JR, Xu JF (1998)
511 Large-scale simulation of elastic wave propagation in heterogeneous media on parallel
512 computers. *Computer Methods in Applied Mechanics and Engineering* 152(1–2):85–102
- 513 Bazzurro P, Cornell CA (1999) Disaggregation of seismic hazard. *Bulletin of the Seismological*
514 *Society of America* 89(2):501–520
- 515 Beresnev IA, Atkinson GM (1998) FINSIM: A FORTRAN program for simulating stochastic
516 acceleration time histories from finite faults. *Seismological Research Letters* 69:27–32
- 517 Berge C, Gariel JC, Bernard P (1998) A very broad-band stochastic source model used for
518 near source strong motion prediction. *Geophysical Research Letters* 25(7):1063–1066
- 519 Beyer K, Bommer JJ (2007) Selection and scaling of real accelerograms for bi-directional load-
520 ing: A review of current practice and code provisions. *Journal of Earthquake Engineering*
521 11(S1):13–45, DOI 10.1080/13632460701280013
- 522 Bommer JJ, Acevedo AB (2004) The use of real earthquake accelerograms as input to dynamic
523 analysis. *Journal of Earthquake Engineering* 8(Special issue 1):43–91
- 524 Bommer JJ, Alarcón JE (2006) The prediction and use of peak ground velocity. *Journal of*
525 *Earthquake Engineering* 10(1):1–31
- 526 Bommer JJ, Ruggeri C (2002) The specification of acceleration time-histories in seismic design
527 codes. *European Earthquake Engineering* 16(1):3–17
- 528 Bommer JJ, Scott SG, Sarma SK (2000) Hazard-consistent earthquake scenarios. *Soil Dynam-*
529 *ics and Earthquake Engineering* 19(4):219–231
- 530 Bommer JJ, Abrahamson NA, Strasser FO, Pecker A, Bard PY, Bungum H, Cotton F, Fäh
531 D, Sabetta F, Scherbaum F, Studer J (2004) The challenge of defining upper bounds on

- 532 earthquake ground motions. *Seismological Research Letters* 75(1):82–95
- 533 Boore DM (1973) The effect of simple topography on seismic waves: Implications for the
534 accelerations recorded at Pacoima Dam, San Fernando valley, California. *Bulletin of the*
535 *Seismological Society of America* 63(5):1603–1609
- 536 Boore DM (1983) Stochastic simulation of high-frequency ground motions based on seismo-
537 logical models of the radiated spectra. *Bulletin of the Seismological Society of America*
538 73(6):1865–1894
- 539 Boore DM (2001) Comparisons of ground motions from the 1999 Chi-Chi earthquake with
540 empirical predictions largely based on data from California. *Bulletin of the Seismological*
541 *Society of America* 91(5):1212–1217
- 542 Boore DM (2003) Simulation of ground motion using the stochastic method. *Pure and Applied*
543 *Geophysics* 160(3–4):635–676, DOI 10.1007/PL00012553
- 544 Boore DM (2005) SMSIM — Fortran programs for simulating ground motions from earth-
545 quakes: Version 2.3 — A revision of OFR 96-80-A. Open-File Report 00-509, United States
546 Geological Survey, modified version, describing the program as of 15 August 2005 (Version
547 2.30).
- 548 Bouchon M (1981) A simple method to calculate Green's functions for elastic layered media.
549 *Bulletin of the Seismological Society of America* 71(4):959–971
- 550 Bouchon M, Sánchez-Sesma FJ (2007) Boundary integral equations and boundary elements
551 methods in elastodynamics. In: *Advances in Geophysics: Advances in wave propagation in*
552 *heterogeneous Earth*, vol 48, Academic Press, London, UK, chap 3, pp 157–189
- 553 Brune JN (1970) Tectonic stress and the spectra of seismic shear waves from earthquakes.
554 *Journal of Geophysical Research* 75(26):4997–5009
- 555 Brune JN (1971) Correction. *Journal of Geophysical Research* 76(20):5002
- 556 Bycroft GN (1960) White noise representation of earthquake. *Journal of The Engineering*
557 *Mechanics Division, ASCE* 86(EM2):1–16
- 558 Campbell KW (1986) An empirical estimate of near-source ground motion for a major,
559 $m_b = 6.8$, earthquake in the eastern United States. *Bulletin of the Seismological Soci-*
560 *ety of America* 76(1):1–17

- 561 Campbell KW (2002) A contemporary guide to strong-motion attenuation relations. In: Lee
562 WHK, Kanamori H, Jennings PC, Kisslinger C (eds) International Handbook of Earth-
563 quake and Engineering Seismology, Academic Press, London, chap 60
- 564 Campbell KW (2003) Prediction of strong ground motion using the hybrid empirical method
565 and its use in the development of ground-motion (attenuation) relations in eastern North
566 America. *Bulletin of the Seismological Society of America* 93(3):1012–1033
- 567 Campbell KW (2007) Validation and update of hybrid empirical ground motion (attenuation)
568 relations for the CEUS. Tech. rep., ABS Consulting, Inc. (EQECAT), Beaverton, USA,
569 award number: 05HQGR0032
- 570 Cancani A (1904) Sur l'emploi d'une double échelle sismique des intensités, empirique et ab-
571 solue. *Gerlands Beitr z Geophys* 2:281–283, not seen. Cited in Gutenberg and Richter
572 (1942).
- 573 Chaljub E, Komatitsch D, Vilotte JP, Capdeville Y, Valette B, Festa G (2007a) Spectral-
574 element analysis in seismology. In: *Advances in Geophysics: Advances in wave propagation*
575 in heterogeneous Earth, vol 48, Academic Press, London, UK, chap 7, pp 365–419
- 576 Chaljub E, Tsuno S, Bard PY, Cornou C (2007b) Analyse des résultats d'un benchmark
577 numérique de prédiction du mouvement sismique dans la vallée de Grenoble. In: 7ème
578 Colloque National AFPS 2007, in French
- 579 Chen M, Hjörleifsdóttir V, Kientz S, Komatitsch D, Liu Q, Maggi A, Savage B, Strand L, Tape
580 C, Tromp J (2008) SPECFEM 3D: User manual version 1.4.3. Tech. rep., Computational
581 Infrastructure for Geodynamics (CIG), California Institute of Technology (USA); Univer-
582 sity of Pau (France), URL <http://www.gps.caltech.edu/jtromp/research/downloads.html>
- 583 Chen XF (2007) Generation and propagation of seismic SH waves in multi-layered media
584 with irregular interfaces. In: *Advances in Geophysics: Advances in wave propagation in*
585 *heterogeneous Earth*, vol 48, Academic Press, London, UK, chap 4, pp 191–264
- 586 Cotton F, Scherbaum F, Bommer JJ, Bungum H (2006) Criteria for selecting and adjusting
587 ground-motion models for specific target regions: Application to central Europe and rock
588 sites. *Journal of Seismology* 10(2):137–156, DOI 10.1007/s10950-005-9006-7
- 589 Dalguer LA, Irikura K, Riera JD (2003) Simulation of tensile crack generation by three-
590 dimensional dynamic shear rupture propagation during an earthquake. *Journal of Geo-*

- 591 physical Research 108(B3), article 2144
- 592 Dan K, Watanabe T, Tanaka T, Sato R (1990) Stability of earthquake ground motion synthe-
593 sized by using different small-event records as empirical Green's functions. Bulletin of the
594 Seismological Society of America 80(6):1433–1455
- 595 Day SM, Bradley CR (2001) Memory-efficient simulation of anelastic wave propagation. Bul-
596 letin of the Seismological Society of America 91(3):520–531
- 597 Day SM, Bielak J, Dreger D, Graves R, Larsen S, Olsen KB, Pitarka A (2005) Tests of 3D elas-
598 todynamic codes. Final report for Lifelines Project 1A03, Pacific Earthquake Engineering
599 Research Center, University of California, Berkeley, USA
- 600 Dormy E, Tarantola A (1995) Numerical simulation of elastic wave propagation using a finite
601 volume method. Journal of Geophysical Research 100(B2):2123–2133
- 602 Douglas J (2003) Earthquake ground motion estimation using strong-motion records: A review
603 of equations for the estimation of peak ground acceleration and response spectral ordinates.
604 Earth-Science Reviews 61(1–2):43–104
- 605 Douglas J (2007) On the regional dependence of earthquake response spectra. ISET Journal
606 of Earthquake Technology 44(1):71–99
- 607 Douglas J, Suhadolc P, Costa G (2004) On the incorporation of the effect of crustal struc-
608 ture into empirical strong ground motion estimation. Bulletin of Earthquake Engineering
609 2(1):75–99
- 610 Douglas J, Bungum H, Scherbaum F (2006) Ground-motion prediction equations for southern
611 Spain and southern Norway obtained using the composite model perspective. Journal of
612 Earthquake Engineering 10(1):33–72
- 613 Dowrick DJ (1977) Earthquake Resistant Design – A Manual For Engineers and Architects.
614 John Wiley & Sons, Ltd.
- 615 Erdik M, Durukal E (2003) Simulation modeling of strong ground motion. In: Earthquake
616 Engineering Handbook, CRC Press LLC, chap 6
- 617 Esteva L, Rosenblueth E (1964) Espectros de temblores a distancias moderadas y grandes.
618 Boletin Sociedad Mexicana de Ingenieria Sismica 2:1–18, in Spanish.
- 619 Faccioli E, Maggio F, Paolucci R, Quarteroni A (1997) 2D and 3D elastic wave propagation
620 by a pseudo-spectral domain decomposition method. Journal of Seismology 1(3):237–251

- 621 Field EH, Jordan TH, Cornell CA (2003) OpenSHA: A developing community-modeling envi-
622 ronment for seismic hazard analysis. *Seismological Research Letters* 74(4):406–419
- 623 Florsch N, Fäh D, Suhadolc P, Panza GF (1991) Complete synthetic seismograms for high-
624 frequency multimode SH-waves. *Pure and Applied Geophysics* 136:529–560
- 625 Frankel A (1995) Simulating strong motions of large earthquakes using recordings of small
626 earthquakes: The Loma Prieta mainshock as a test case. *Bulletin of the Seismological
627 Society of America* 85(4):1144–1160
- 628 Frankel A, Clayton RW (1986) Finite-difference simulations of seismic scattering — Implica-
629 tions for the propagation of short-period seismic-waves in the crust and models of crustal
630 heterogeneity. *Journal of Geophysical Research* 91(B6):6465–6489
- 631 Gallovič F, Brokešová J (2007) Hybrid k -squared source model for strong ground motion
632 simulations: Introduction. *Physics of the Earth and Planetary Interiors* 160(1):34–50, DOI
633 10.1016/j.pepi.2006.09.002
- 634 Goda K, Hong HP (2008) Spatial correlation of peak ground motions and response spectra.
635 *Bulletin of the Seismological Society of America* 98(1):354–365, DOI 10.1785/0120070078
- 636 Graves RWJ (1996) Simulating seismic wave propagation in 3D elastic media using staggered-
637 grid finite differences. *Bulletin of the Seismological Society of America* 86(4):1091–1106
- 638 Guatteri M, Mai PM, Beroza GC, Boatwright J (2003) Strong ground motion prediction
639 from stochastic-dynamic source models. *Bulletin of the Seismological Society of America*
640 93(1):301–313, DOI 10.1785/0120020006
- 641 Guatteri M, Mai PM, Beroza GC (2004) A pseudo-dynamic approximation to dynamic rup-
642 ture models for strong ground motion prediction. *Bulletin of the Seismological Society of
643 America* 94(6):2051–2063, DOI 10.1785/0120040037
- 644 Gusev AA (1983) Descriptive statistical model of earthquake source radiation and its appli-
645 cation to an estimation of short-period strong motion. *Geophysical Journal of the Royal
646 Astronomical Society* 74:787–808
- 647 Gutenberg G, Richter CF (1942) Earthquake magnitude, intensity, energy, and acceleration.
648 *Bulletin of the Seismological Society of America* 32(3):163–191
- 649 Guzman RA, Jennings PC (1976) Design spectra for nuclear power plants. *Journal of The
650 Power Division, ASCE* 102(2):165–178

-
- 651 Hadley DM, Helmberger DV (1980) Simulation of strong ground motions. Bulletin of the
652 Seismological Society of America 70(2):617–630
- 653 Hancock J, Watson-Lamprey J, Abrahamson NA, Bommer JJ, Markatis A, McCoy E, Mendis
654 R (2006) An improved method of matching response spectra of recorded earthquake ground
655 motion using wavelets. Journal of Earthquake Engineering 10(Special issue 1):67–89
- 656 Hancock J, Bommer JJ, Stafford PJ (2008) Numbers of scaled and matched accelerograms
657 required for inelastic dynamic analyses. Earthquake Engineering and Structural Dynamics
658 DOI 10.1002/eqe.827, in press
- 659 Hanks TC (1979) b values and $\omega^{-\gamma}$ seismic source models: Implications for tectonic stress
660 variations along active crustal fault zones and the estimation of high-frequency strong
661 ground motion. Journal of Geophysical Research 84(B5):2235–2242
- 662 Hanks TC, McGuire RK (1981) The character of high-frequency strong ground motion. Bulletin
663 of the Seismological Society of America 71(6):2071–2095
- 664 Hartzell S, Leeds A, Frankel A, Williams RA, Odum J, Stephenson W, Silva S (2002) Sim-
665 ulation of broadband ground motion including nonlinear soil effects for a magnitude 6.5
666 earthquake on the Seattle fault, Seattle, Washington. Bulletin of the Seismological Society
667 of America 92(2):831–853
- 668 Hartzell SH (1978) Earthquake aftershocks as Green's functions. Geophysical Research Letters
669 5(1):1–4
- 670 Haskell NA (1969) Elastic displacements in the near-field of a propagating fault. Bulletin of
671 the Seismological Society of America 59(2):865–908
- 672 Hays WW (1980) Procedures for estimating earthquake ground motions. Geological Survey
673 Professional Paper 1114, US Geological Survey
- 674 Heaton TH, Helmberger DV (1977) A study of the strong ground motion of the Borrego Moun-
675 tain, California, earthquake. Bulletin of the Seismological Society of America 67(2):315–330
- 676 Herrero A, Bernard P (1994) A kinematic self-similar rupture process for earthquakes. Bulletin
677 of the Seismological Society of America 84(4):1216–1228
- 678 Hershberger J (1956) A comparison of earthquake accelerations with intensity ratings. Bulletin
679 of the Seismological Society of America 46(4):317–320

-
- 680 Heuze F, Archuleta R, Bonilla F, Day S, Doroudian M, Elgamal A, Gonzales S, Hoehler
681 M, Lai T, Lavallee D, Lawrence B, Liu PC, Martin A, Matesic L, Minster B, Mellors
682 R, Oglesby D, Park S, Riemer M, Steidl J, Vernon F, Vucetic M, Wagoner J, Yang Z
683 (2004) Estimating site-specific strong earthquake motions. *Soil Dynamics and Earthquake*
684 *Engineering* 24(3):199–223, DOI 10.1016/j.soildyn.2003.11.002
- 685 Hisada Y (2008) Broadband strong motion simulation in layered half-space using stochastic
686 Green's function technique. *Journal of Seismology* 12(2):265–279, DOI 10.1007/s10950-
687 008-9090-6
- 688 Housner GW (1947) Characteristics of strong-motion earthquakes. *Bulletin of the Seismological*
689 *Society of America* 37(1):19–31
- 690 Housner GW (1955) Properties of strong-ground motion earthquakes. *Bulletin of the Seismo-*
691 *logical Society of America* 45(3):197–218
- 692 Housner GW, Jennings PC (1964) Generation of artificial earthquakes. *Journal of The Engi-*
693 *neering Mechanics Division, ASCE* 90:113–150
- 694 Irikura K, Kamae K (1994) Estimation of strong ground motion in broad-frequency band based
695 on a seismic source scaling model and an empirical Green's function technique. *Annali di*
696 *Geofisica XXXVII(6):1721–1743*
- 697 Jennings PC, Housner GW, Tsai NC (1968) Simulated earthquake motions. Tech. rep., Earth-
698 *quake Engineering Research Laboratory, California Institute of Technology, Pasadena, Cal-*
699 *fornia, USA*
- 700 Joyner WB (1984) A scaling law for the spectra of large earthquakes. *Bulletin of the Seismo-*
701 *logical Society of America* 74(4):1167–1188
- 702 Joyner WB, Boore DM (1986) On simulating large earthquake by Green's function addition
703 of smaller earthquakes. In: Das S, Boatwright J, Scholtz CH (eds) *Earthquake Source*
704 *Mechanics, Maurice Ewing Series 6, vol 37, American Geophysical Union, Washington,*
705 *D.C., USA*
- 706 Joyner WB, Boore DM (1988) Measurement, characterization, and prediction of strong ground
707 motion. In: *Proceedings of Earthquake Engineering & Soil Dynamics II, Geotechnical Di-*
708 *sion, ASCE, pp 43–102*

- 709 Jurkevics A, Ulrych TJ (1978) Representing and simulating strong ground motion. *Bulletin of*
710 *the Seismological Society of America* 68(3):781–801
- 711 Kaka SI, Atkinson GM (2004) Relationships between instrumental ground-motion parameters
712 and modified Mercalli intensity in eastern North America. *Bulletin of the Seismological*
713 *Society of America* 94(5):1728–1736
- 714 Kamae K, Irikura K, Pitarka A (1998) A technique for simulating strong ground motion using
715 hybrid Green's functions. *Bulletin of the Seismological Society of America* 88(2):357–367
- 716 Kanamori H (1979) A semi-empirical approach to prediction of long-period ground motions
717 from great earthquakes. *Bulletin of the Seismological Society of America* 69(6):1645–1670
- 718 Käser M, Iske A (2005) ADER schemes on adaptive triangular meshes for scalar conservations
719 laws. *Journal of Computational Physics* 205(2):486–508
- 720 Kaul MK (1978) Spectrum-consistent time-history generation. *Journal of The Engineering*
721 *Mechanics Division, ASCE* 104(ME4):781–788
- 722 Kennett BLN, Kerry NJ (1979) Seismic waves in a stratified half-space. *Geophysical Journal*
723 *of the Royal Astronomical Society* 57:557–583
- 724 Kohrs-Sansorny C, Courboulex F, Bour M, Deschamps A (2005) A two-stage method for
725 ground-motion simulation using stochastic summation of small earthquakes. *Bulletin of*
726 *the Seismological Society of America* 95(4):1387–1400, DOI 10.1785/0120040211
- 727 Koketsu K (1985) The extended reflectivity method for synthetic near-field seismograms. *Jour-*
728 *nal of the Physics of the Earth* 33:121–131
- 729 Komatitsch D, Martin R (2007) An unsplit convolutional perfectly matched layer improved at
730 grazing incidence for the seismic wave equation. *Geophysics* 72(5):SM155–SM167
- 731 Komatitsch D, Tromp J (1999) Introduction to the spectral element method for three-
732 dimensional seismic wave propagation. *Geophysical Journal International* 139(3):806–822
- 733 Komatitsch D, Vilotte JP (1998) The spectral element method: An efficient tool to simulate
734 the seismic response of 2D and 3D geological structures. *Bulletin of the Seismological*
735 *Society of America* 88(2):368–392
- 736 Komatitsch D, Liu Q, Tromp J, Süss P, Stidham C, Shaw JH (2004) Simulations of ground
737 motion in the Los Angeles basin based upon the spectral-element method. *Bulletin of the*
738 *Seismological Society of America* 94(1):187–206

- 739 Krishnan S, Ji C, Komatitsch D, Tromp J (2006) Case studies of damage to tall steel moment-
740 frame buildings in southern California during large San Andreas earthquakes. *Bulletin of
741 the Seismological Society of America* 96(4A):1523–1537, DOI 10.1785/0120050145
- 742 Kristeková M, Kristek J, Moczo P, Day SM (2006) Misfit criteria for quantitative comparison
743 of seismograms. *Bulletin of the Seismological Society of America* 96(5):1836–1850, DOI
744 10.1785/0120060012
- 745 Lee VW, Trifunac MD (1985) Torsional accelerograms. *Soil Dynamics and Earthquake Engi-
746 neering* 4(3):132–139
- 747 Lee VW, Trifunac MD (1987) Rocking strong earthquake accelerations. *Soil Dynamics and
748 Earthquake Engineering* 6(2):75–89
- 749 Lee Y, Anderson JG, Zeng Y (2000) Evaluation of empirical ground-motion relations in south-
750 ern California. *Bulletin of the Seismological Society of America* 90(6B):S136–S148
- 751 Levander AR (1988) Fourth-order finite-difference P-SV seismograms. *Geophysics* 53(11):1425–
752 1436
- 753 LeVeque RJ (2002) Finite Volume Methods for Hyperbolic Problems. Cambridge University
754 Press, Cambridge, UK
- 755 Luco JE, Apsel RJ (1983) On the Green's functions for a layered half-space. Part I. *Bulletin
756 of the Seismological Society of America* 73(4):909–929
- 757 Lysmer J, Drake LA (1972) A finite element method for seismology. In: Bolt BA (ed) *Methods
758 in Computational Physics*, Academic Press Inc., New York, USA
- 759 Ma S, Archuleta RJ, Page MT (2007) Effects of large-scale surface topography on ground
760 motions as demonstrated by a study of the San Gabriel Mountains, Los Angeles,
761 California. *Bulletin of the Seismological Society of America* 97(6):2066–2079, DOI
762 10.1785/0120070040
- 763 Mai PM, Beroza GC (2003) A hybrid method for calculating near-source, broadband seis-
764 mograms: Application to strong motion prediction. *Physics of the Earth and Planetary
765 Interiors* 137(1–4):183–199, DOI 10.1016/S0031-9201(03)00014-1
- 766 Maupin V (2007) Introduction to mode coupling methods for surface waves. In: *Advances
767 in Geophysics: Advances in wave propagation in heterogeneous Earth*, vol 48, Academic
768 Press, London, UK, chap 2, pp 127–155

-
- 769 McGuire RK (2004) Seismic Hazard and Risk Analysis. *Earthquake Engineering Research*
770 Institute (EERI), Oakland, California, USA
- 771 Miyake H, Iwata T, Irikura K (2003) Source characterization for broadband ground-motion
772 simulation: Kinematic heterogeneous source model and strong motion generation area. *Bul-*
773 *letin of the Seismological Society of America* 93(6):2531–2545, DOI 10.1785/0120020183
- 774 Moczo P, Kristek J, Galis M, Pazak P, Balazovjech M (2007a) The finite-difference and finite-
775 element modeling of seismic wave propagation and earthquake motion. *Acta Physica Slo-*
776 *vaca* 57(2):177–406
- 777 Moczo P, Robertsson JOA, Eisner L (2007b) The finite-difference time-domain method for
778 modeling of seismic wave propagation. In: *Advances in Geophysics: Advances in wave*
779 *propagation in heterogeneous Earth*, vol 48, Academic Press, London, UK, chap 8, pp
780 421–516
- 781 Montaldo V, Kiremidjian AS, Thráinsson H, Zonno G (2003) Simulation of the Fourier phase
782 spectrum for the generation of synthetic accelerograms. *Journal of Earthquake Engineering*
783 7(3):427–445
- 784 Mora P, Place D (1994) Simulation of the frictional stick-slip instability. *Pure and Applied*
785 *Geophysics* 143(1–3):61–87
- 786 Motazedian D, Atkinson GM (2005) Stochastic finite-fault modeling based on a dynamic cor-
787 *ner frequency. Bulletin of the Seismological Society of America* 95(3):995–1010, DOI
788 10.1785/0120030207
- 789 Mukherjee S, Gupta VK (2002) Wavelet-based generation of spectrum-compatible time-
790 histories. *Soil Dynamics and Earthquake Engineering* 22(9–12):799–804
- 791 Murphy JR, O'Brien LJ (1977) The correlation of peak ground acceleration amplitude with
792 seismic intensity and other physical parameters. *Bulletin of the Seismological Society of*
793 *America* 67(3):877–915
- 794 Naeim F, Lew M (1995) On the use of design spectrum compatible time histories. *Earthquake*
795 *Spectra* 11(1):111–127
- 796 Nau RF, Oliver RM, Pister KS (1982) Simulating and analyzing artificial nonstationary earth-
797 *quake ground motions. Bulletin of the Seismological Society of America* 72(2):615–636

- 798 Ólafsson S, Sigbjörnsson R (1995) Application of ARMA models to estimate earthquake
799 ground motion and structural response. *Earthquake Engineering and Structural Dynamics*
800 24(7):951–966
- 801 Ólafsson S, Remseth S, Sigbjörnsson R (2001) Stochastic models for simulation of strong
802 ground motion in Iceland. *Earthquake Engineering and Structural Dynamics* 30(9):1305–
803 1331
- 804 Olsen K, Madariaga R, Archuleta RJ (1997) Three-dimensional dynamic simulation of the
805 1992 Landers earthquake. *Science* 278:834–838
- 806 Olsen KB, Day SM, Minster JB, Cui Y, Chourasia A, Faerman M, Moore R, Maechling P,
807 Jordan T (2006) Strong shaking in Los Angeles expected from southern San Andreas
808 earthquake. *Geophysical Research Letters* 33(L07305), DOI 10.1029/2005GL025472
- 809 Oprsal I, Zahradník J (2002) Three-dimensional finite difference method and hybrid mod-
810 eling of earthquake ground motion. *Journal of Geophysical Research* 107(B8), DOI
811 10.1029/2000JB000082
- 812 Ordaz M, Arboleda J, Singh SK (1995) A scheme of random summation of an empirical
813 Green's function to estimate ground motions from future large earthquakes. *Bulletin of*
814 *the Seismological Society of America* 85(6):1635–1647
- 815 Panza GF (1985) Synthetic seismograms: The Rayleigh waves modal summation. *Journal of*
816 *Geophysics* 58:125–145
- 817 Panza GF, Suhadolc P (1987) Complete strong motion synthetics. In: Bolt BA (ed) *Seismic*
818 *strong motion synthetics*, Academic Press, Orlando, pp 153–204
- 819 Papageorgiou AS, Aki K (1983) A specific barrier model for the quantitative description of
820 inhomogeneous faulting and the prediction of strong ground motion. Part I. Description
821 of the model. *Bulletin of the Seismological Society of America* 73(3):693–702
- 822 Pavic R, Koller MG, Bard PY, Lacave-Lachet C (2000) Ground motion prediction with the
823 empirical Green's function technique: an assessment of uncertainties and confidence level.
824 *Journal of Seismology* 4(1):59–77
- 825 Pitarka A, Irikura K, Iwata T, Sekiguchi H (1998) Three-dimensional simulation of the near-
826 fault ground motion for the 1995 Hyogo-ken Nanbu (Kobe), Japan, earthquake. *Bulletin*
827 *of the Seismological Society of America* 88(2):428–440

- 828 Pitarka A, Somerville P, Fukushima Y, Uetake T, Irikura K (2000) Simulation of near-fault
829 strong-ground motion using hybrid Green's functions. *Bulletin of the Seismological Society*
830 of America 90(3):566–586
- 831 Place D, Mora P (1999) The lattice solid model to simulate the physics of rocks and earth-
832 quakes: Incorporation of friction. *Journal of Computational Physics* 150(2):332–372
- 833 Pousse G, Bonilla LF, Cotton F, Margerin L (2006) Non stationary stochastic simulation of
834 strong ground motion time histories including natural variability: Application to the K-net
835 Japanese database. *Bulletin of the Seismological Society of America* 96(6):2103–2117, DOI
836 10.1785/0120050134
- 837 Power M, Chiou B, Abrahamson N, Bozorgnia Y, Shantz T, Roblee C (2008) An overview of
838 the NGA project. *Earthquake Spectra* 24(1):3–21, DOI 10.1193/1.2894833
- 839 Reiter L (1990) *Earthquake Hazard Analysis: Issues and Insights*. Columbia University Press,
840 New York
- 841 Ripperger J, Mai PM, Ampuero JP (2008) Variability of near-field ground motion from dy-
842 namic earthquake rupture simulations. *Bulletin of the Seismological Society of America*
843 98(3):1207–1228, DOI 10.1785/0120070076
- 844 Ruiz J, Baumont D, Bernard P, , Berge-Thierry C (2007) New approach in the kinematic k^2
845 source model for generating physical slip velocity functions. *Geophysical Journal Interna-*
846 *tional* 171(2):739–754, DOI 10.1111/j.1365-246X.2007.03503.x
- 847 Sabetta F, Pugliese A (1996) Estimation of response spectra and simulation of nonstationary
848 earthquake ground motions. *Bulletin of the Seismological Society of America* 86(2):337–352
- 849 Scherbaum F, Cotton F, Smit P (2004) On the use of response spectral-reference data for
850 the selection and ranking of ground-motion models for seismic-hazard analysis in regions
851 of moderate seismicity: The case of rock motion. *Bulletin of the Seismological Society of*
852 *America* 94(6):2164–2185, DOI 10.1785/0120030147
- 853 Scherbaum F, Cotton F, Staedtke H (2006) The estimation of minimum-misfit stochastic
854 models from empirical ground-motion prediction equations. *Bulletin of the Seismological*
855 *Society of America* 96(2):427–445, DOI 10.1785/0120050015
- 856 Shi B, Brune JN (2005) Characteristics of near-fault ground motions by dynamic thrust fault-
857 ing: Two-dimensional lattice particle approaches. *Bulletin of the Seismological Society of*

-
- 858 America 95(6):2525–2533, DOI 10.1785/0120040227
- 859 Shinozuka M (1988) Engineering modeling of ground motion. In: Proceedings of Ninth World
860 Conference on Earthquake Engineering, vol VIII, pp 51–62
- 861 Shome N, Cornell CA, Bazzurro P, Carballo JE (1998) Earthquakes, records and nonlinear
862 responses. *Earthquake Spectra* 14(3):469–500
- 863 Silva W, Gregor N, Darragh B (1999) Near fault ground motions. Tech. rep., Pacific Engineer-
864 ing and Analysis, El Cerrito, USA, PG&E PEER — Task 5.A
- 865 Silva WJ, Lee K (1987) State-of-the-art for assessing earthquake hazards in the United States;
866 report 24: WES RASCAL code for synthesizing earthquake ground motions. Miscellaneous
867 Paper S-73-1, US Army Corps of Engineers
- 868 Sokolov V, Wald DJ (2002) Instrumental intensity distribution for the Hector Mine, Califor-
869 nia, and the Chi-Chi, Taiwan, earthquakes: Comparison of two methods. *Bulletin of the*
870 *Seismological Society of America* 92(6):2145–2162
- 871 Souriau A (2006) Quantifying felt events: A joint analysis of intensities, accelerations and
872 dominant frequencies. *Journal of Seismology* 10(1):23–38, DOI 10.1007/s10950-006-2843-1
- 873 Spudich P, Xu L (2003) Software for calculating earthquake ground motions from finite faults
874 in vertically varying media. In: IASPEI Handbook of Earthquake and Engineering Seis-
875 mology, Academic Press, Amsterdam, The Netherlands, chap 85.14, pp 1633–1634
- 876 Spudich P, Joyner WB, Lindh AG, Boore DM, Margaris BM, Fletcher JB (1999) SEA99: A
877 revised ground motion prediction relation for use in extensional tectonic regimes. *Bulletin*
878 *of the Seismological Society of America* 89(5):1156–1170
- 879 Strasser FO, Bommer JJ, Abrahamson NA (2008) Truncation of the distribution of ground-
880 motion residuals. *Journal of Seismology* 12(1):79–105, DOI 10.1007/s10950-007-9073-z
- 881 Swanger HJ, Boore DM (1978) Simulation of strong-motion displacements using surface-wave
882 modal superposition. *Bulletin of the Seismological Society of America* 68(4):907–922
- 883 Takeo M (1985) Near-field synthetic seismograms taking into account the effects of anelastic-
884 ity: The effects of anelastic attenuation on seismograms caused by a sedimentary layer.
885 Meteorology & Geophysics 36(4):245–257
- 886 Tavakoli B, Pezeshk S (2005) Empirical-stochastic ground-motion prediction for eastern
887 North America. *Bulletin of the Seismological Society of America* 95(6):2283–2296, DOI

- 888 10.1785/0120050030
- 889 Tinti E, Fukuyama E, Piatanesi A, Cocco M (2005) A kinematic source-time function compati-
- 890 ble with earthquake dynamics. *Bulletin of the Seismological Society of America* 95(4):1211–
- 891 1223, DOI 10.1785/0120040177
- 892 Trifunac MD (1971) A method for synthesizing realistic strong ground motion. *Bulletin of the*
- 893 *Seismological Society of America* 61(6):1739–1753
- 894 Trifunac MD (1976) Preliminary analysis of the peaks of strong earthquake ground motion
- 895 – dependence of peaks on earthquake magnitude, epicentral distance, and recording site
- 896 conditions. *Bulletin of the Seismological Society of America* 66(1):189–219
- 897 Trifunac MD (1990) Curvograms of strong ground motion. *Journal of The Engineering Me-*
- 898 *chanics Division, ASCE* 116:1426–32
- 899 Trifunac MD (2007) Recording strong earthquake motion — Instruments, recording strategies
- 900 and data processing. *Tech. Rep. CE 07-03, Department of Civil Engineering, University*
- 901 *of Southern California*
- 902 Trifunac MD, Brady AG (1975) On the correlation of seismic intensity scales with the peaks of
- 903 recorded strong ground motion. *Bulletin of the Seismological Society of America* 65(1):139–
- 904 162
- 905 Tuft E (2006) *Beautiful Evidence*. Graphics Press, Cheshire, Connecticut, USA
- 906 Tumarkin A, Archuleta R (1994) Empirical ground motion prediction. *Annali di Geofisica*
- 907 XXXVII(6):1691–1720
- 908 Vanmarcke EH (1979) Representation of earthquake ground motion: Scaled accelerograms and
- 909 equivalent response spectra. *State-of-the-Art for Assessing Earthquake Hazards in the*
- 910 *United States 14, Miscellaneous Paper S-73-1, U.S. Army Corps of Engineers, Vicksburg,*
- 911 *Mississippi, USA*
- 912 Vanmarcke EH, Gasparini DA (1976) Simulated earthquake motions compatible with pre-
- 913 scribed response spectra. *Tech. Rep. R76-4, Dept. of Civil Engineering, Massachusetts*
- 914 *Inst. of Technology, Cambridge, USA*
- 915 Virieux J, Madariaga R (1982) Dynamic faulting studied by a finite difference method. *Bulletin*
- 916 *of the Seismological Society of America* 72(2):345–369

-
- 917 Wald DJ, Quitoriano V, Heaton TH, Kanamori H (1999) Relationships between peak ground
918 acceleration, peak ground velocity, and modified Mercalli intensity in California. *Earth-*
919 *quake Spectra* 15(3):557–564
- 920 Wang GQ, Boore DM, Tang G, Zhou X (2007) Comparisons of ground motions from col-
921 located and closely-spaced 1-sample-per-second Global Positioning System (GPS) and
922 accelerograph recordings of the 2003, M6.5 San Simeon, California, earthquake in the
923 Parkfield Region. *Bulletin of the Seismological Society of America* 97(1B):76–90, DOI
924 10.1785/0120060053
- 925 Wang R (1999) A simple orthonormalization method for stable and efficient computation of
926 Green's functions. *Bulletin of the Seismological Society of America* 89(3):733–741
- 927 Watson-Lamprey J, Abrahamson N (2006) Selection of ground motion time series and limits
928 on scaling. *Soil Dynamics and Earthquake Engineering* 26(5):477–482
- 929 Wennerberg L (1990) Stochastic summation of empirical Green's functions. *Bulletin of the*
930 *Seismological Society of America* 80(6):1418–1432
- 931 Wong HL, Trifunac MD (1978) Synthesizing realistic ground motion accelerograms. Tech. Rep.
932 CE 78-07, Department of Civil Engineering, University of Southern California
- 933 Woodhouse JH (1974) Surface waves in a laterally varying layered structure. *Geophysical*
934 *Journal of the Royal Astronomical Society* 37:461–490
- 935 Zeng T, Anderson JG, Yu G (1994) A composite source model for computing realistic synthetic
936 strong ground motions. *Geophysical Research Letters* 21(8):725–728
- 937 Zeng Y, Anderson JG (1995) A method for direct computation of the differential seismogram
938 with respect to the velocity change in a layered elastic solid. *Bulletin of the Seismological*
939 *Society of America* 85(1):300–307

940 List of Tables

941 1	Method of representative accelerograms	39
942 2	Method of empirical ground-motion models (ground-motion prediction 943 equations, GMPEs)	40
944 3	Methods based on macroseismic intensity-ground-motion correlations .	41
945 4	Methods based on stationary black-box simulations	42
946 5	Methods based on non-stationary black-box simulations	43
947 6	Methods based on autoregressive/moving average (ARMA) simulations .	44
948 7	Methods based on spectrum-matching simulations	45
949 8	Methods based on physics-based stochastic models	46
950 9	Methods based on physics-based extended stochastic models	47
951 10	Method based on group-velocity dispersion curves	48
952 11	Semi-analytical methods	49
953 12	Finite difference methods (FDM)	50
954 13	Finite element methods (FEM)	51
955 14	Spectral element methods (SEM)	52
956 15	Methods based on modal summation	53
957 16	Lattice particle method	54
958 17	Finite volume method	55
959 18	Methods based on ray theory	56
960 19	Methods based on empirical Green's functions (EGF) (classic)	57
961 20	Methods based on empirical Green's functions (stochastic)	58
962 21	Hybrid stochastic-empirical method	59
963 22	Hybrid numerical methods	60

Table 1 Method of representative accelerograms

Description of method		
Input parameters	Outputs	Key references
Magnitude, distance, design response spectrum, seismic regime, source depth, style-of-faulting	Scaled (modified) natural accelerogram reliable up to 1–4 s for analogue or 10 s for digital (Akkar and Bommer 2006)	Guzman and Jennings (1976), Dowrick (1977), Campbell (1986), Joyner and Boore (1988), Shome et al (1998), Bommer et al (2000), Bommer and Ruggeri (2002), Bommer and Acevedo (2004), Baker and Cornell (2006), Watson-Lamprey and Abrahamson (2006), Beyer and Bommer (2007), Hancock et al (2008)
Available tools	Used in research	Used in practice
Various websites (e.g. Ambraseys et al 2004b) and CD ROMs (e.g. Ambraseys et al 2004a) providing accelerograms; RSP-MATCH2005 (Hancock et al 2006); RASCAL (Silva and Lee 1987); WAVGEN (Mukherjee and Gupta 2002)	Often	Very often although they are rarely called ‘representative accelerograms’.
Advantages	Disadvantages/limitations	
Rapid; straightforward; many available records from Internet sites and CD ROM collections; can account for effects (e.g. near-field pulses) that are not well modelled by other methods; well established; since the ground motions have occurred in the past, they are physically possible; more easily understood and accepted by decision makers since based on observations; only requires standard scenario characteristics; includes ground-motion variability; can provide triaxial time-histories consistent with observed correlations between components.	Still lack of near-source records from large events (hence difficult to know if observations are well representative of the true range of possible motions or sampling artifact); difficult to find records to match scenario characteristics in addition to magnitude and distance; small databases for most regions (outside California and Japan); often implicit assumption is that host and target regions have similar characteristics (or that strong motions are not dependent on region); difficult to ascertain whether certain records are applicable elsewhere due to particular site or source effects; scaling can have significant impact on results of dynamic analyses.	

Table 2 Method of empirical ground-motion models (ground-motion prediction equations, GMPEs)

Description of method		
A databank of accelerograms and metadata from a region are collated and processed. Strong-motion intensity parameters (e.g. PGA) are computed for these accelerograms. Regression analysis is performed using a handful of source, path and site independent variables and the intensity parameter as the dependent variable. Less popular variants consist of the development of tables, graphs or neural nets for prediction purposes. The developed models are evaluated for a given scenario and the results are commonly weighted.		
Input parameters	Output parameters	Key references
Magnitude, near-distance, near-surface site characteristics, style-of-faulting, source depth, seismic regime, gross source characteristics, deep geology	Strong-motion intensity parameters (e.g. PGA, PGV, PGD , response spectral ordinates, duration, other parameters)	Esteva and Rosenblueth (1964), Trifunac (1976), Joyner and Boore (1988), Abrahamson and Shedlock (1997), Anderson (1997b), Lee et al (2000), Campbell (2002), Douglas (2003), Scherbaum et al (2004), Bommer and Alarcón (2006), Power et al (2008), Abrahamson et al (2008)
Available tools	Used in research	Used in practice
Various websites (e.g. Ambraseys et al 2004b) and CD ROMs (e.g. Ambraseys et al 2004a) providing accelerograms; various spreadsheets and computer codes for evaluating models and for regression analysis; OpenSHA (Field et al 2003)	Very often	Very often
Advantages	Disadvantages/limitations	
Rapid; well established; can be simply and easily applied without having to set up lots of simulations (hence useful for regional PSHA); only requires standard scenario characteristics; more easily understood and accepted by decision makers since based on observations; easy to develop new GMPEs; includes ground-motion variability; can model different causes of variability (e.g. inter-event, inter-site and record-to-record variation).	Output is strong-motion parameter rather than time-history; strong-motion parameter is not always useful for sophisticated engineering analyses; still lack of near-source records from large events (hence difficult to know if observations are well representative of the true range of possible motions or sampling artifact); small databanks for most regions (outside California and Japan); often implicit assumption is that host and target regions have similar characteristics (or that strong motions are not dependent on region); applies to a generic (mainly unknown) situation so cannot account for site-specific conditions; never sure of having the correct functional form; observed data smoothed due to large scatter in observations; requires lots of records to derive models; at edges of dataspace predictions poorly constrained; physically basis of coefficients is not always clear; ground motions from small and large events scale differently with magnitude and distance hence difficult to use weak records to predict strong motions; debate over preference for global, regional or local models; large epistemic uncertainty, mainly due to limited data.	

Table 3 Methods based on macroseismic intensity-ground-motion correlations

Description of method		
Input parameters	Outputs	Key references
Macroseismic site intensity, seismotectonic regime, source depth, <i>magnitude</i> , distance	Strong-motion intensity parameters (e.g. PGA, PGV, <i>PGD</i> , response spectral ordinates, duration, other parameters)	Cancani (1904), Gutenberg and Richter (1942), Hershberger (1956), Ambraseys (1974), Trifunac and Brady (1975), Murphy and O'Brien (1977), Campbell (1986), Wald et al (1999), Atkinson and Sonley (2000), Sokolov and Wald (2002), Kaka and Atkinson (2004), Souriau (2006)
Available tools	Used in research	Used in practice
None known	Rarely	Occasionally
Advantages	Disadvantages/limitations	
Rapid; straightforward; more easily understood and accepted by decision makers since based on observations; only requires standard scenario characteristics; includes ground-motion variability; historical earthquake catalogues often defined only in terms of macroseismic intensities hence less conversions required than other techniques; does not require strong-motion data if adopt data/model from another region; easier to apply ground-motion estimates for risk evaluation if vulnerability functions defined in terms of macroseismic intensity.	Output is strong-motion parameter rather than time-history; strong-motion parameter not always useful for sophisticated engineering analyses; often implicit assumption is that host and target regions have similar characteristics (or that strong motions are not dependent on region); weak statistical dependence (lack of clear physical relationship) between ground-motion parameters and intensity; intensities in catalogues are subjective and can be associated with large inaccuracies; few reliable usable correlations between intensity and different strong-motion parameters because there are many intensity scales, intensity assessment can be country-dependent and lack of intensity data from close to accelerograph stations; many intensity relationships derived using isoseismal contours, which leads to positive bias in estimated motions; applies to a generic (mainly unknown) situation so cannot account for site-specific conditions; never sure of having the correct functional form; observed data smoothed due to large scatter in observations; requires lots of records to derive correlations; at edges of dataspace predictions poorly constrained; physically basis of coefficients not always clear; ground motions from small and large events scale differently with magnitude and distance hence difficult to use weak records to predict strong motions; debate over preference for global, regional or local models; large epistemic uncertainty, mainly due to limited data.	

Table 4 Methods based on stationary black-box simulations

Description of method		
This type of method was developed to fill in gaps in early observational databanks, particularly, for large earthquakes. White noise (sum of cosines with random time delays) is modified by filtering in the frequency domain to obtain acceleration time-histories that conform to the observed main characteristics of earthquake ground motions.		
Input parameters	Outputs	Key references
Magnitude, distance, near-surface site characteristics, source depth, seismotectonic regime	Artifical acceleration time-histories reliable from 0 to about 2 s	Housner (1947), Housner (1955), Bycroft (1960), Housner and Jennings (1964), Jennings et al (1968), Dowrick (1977)
Available tools	Used in research	Used in practice
None known	Very rarely	Very rarely
Advantages	Disadvantages/limitations	
Rapid; straightforward; provides as many independent time-histories for a scenario as required; includes consideration of ground-motion variability; time-histories adequate for examining elastic response of lightly-damped structures; well-suited for analytic solutions and Monte Carlo simulations of structural response; do not require knowledge of source, path and site.	Do not generally involve rigorous considerations of the physics of the earthquakes; not appropriate for modelling smaller earthquake motions or for use in studies where the less intense but longer tails of accelerograms are thought to be significant, e.g. liquefaction studies; does not consider non-stationarity in time and frequency domains of earthquake ground motions; true ground-motion variability can be underestimated; frequency content not realistic; not accurate close to source where non-stationarity important; for generic scenario; too many cycles in ground motions; energy content of motions not realistic.	

Table 5 Methods based on non-stationary black-box simulations

Description of method		
White noise is modified by filtering in the frequency domain and then it is multiplied by an envelope function in the time domain. Also can account for non-stationarity in frequency domain and a consideration of phase. Frequency content and envelope function developed using equations developed through regression analysis of observational data.		
Input parameters	Outputs	Key references
Magnitude, distance, near-surface site characteristics, style-of-faulting, source depth, seismotectonic regime	Artifical acceleration time-histories reliable from 0 to about 4s (e.g. Sabetta and Pugliese 1996)	Sabetta and Pugliese (1996), Montaldo et al (2003), Pousse et al (2006)
Available tools	Used in research	Used in practice
Program of Pousse et al (2006)	Occasionally	Rarely
Advantages	Disadvantages/limitations	
Rapid; straightforward; only requires a handful of input parameters; close link to observations; provides as many independent time-histories for a scenario as required; includes consideration of ground-motion variability; accounts for non-stationarity in time and frequency domains; do not require knowledge of source, path and site.	Do not generally involve rigorous considerations of the physics of the earthquakes; require good databanks to constrain empirical parameters; true ground-motion variability can be underestimated.	

Table 6 Methods based on autoregressive/moving average (ARMA) simulations

Description of method		
Input parameters	Outputs	Key references
Magnitude, distance, near-surface site characteristics, seismotectonic regime, source depth	Artificial acceleration time-histories reliable from 0 to about 2 s	Jurkevics and Ulrych (1978), Nau et al (1982), Ólafsson and Sigbjörnsson (1995) Ólafsson et al (2001)
Available tools	Used in research	Used in practice
None known	Rarely	Very rarely
Advantages	Disadvantages/limitations	
Rapid; nonparametric method to compute acceleration envelopes so does not rely on assumed envelope shape; provides as many independent time-histories for a scenario as required; includes consideration of ground-motion variability; well-suited for Monte Carlo simulations of structural response; ARMA models only need a handful of coefficients to give a good statistical fit to time histories; do not require knowledge of source, path and site.	Do not generally involve rigorous considerations of the physics of the earthquakes; true ground-motion variability can be underestimated; not commonly used so poorly known; requires observational data to constrain input parameters; assumes that the strong-motion phase can be modelled as a locally stationary stochastic process; does not give reliable estimate outside range of data.	

Table 7 Methods based on spectrum-matching simulations

Description of method		
Input parameters	Outputs	Key references
Elastic response spectrum, duration of strong shaking	Artificial acceleration time-histories reliable from 0 to about 2 s	Kaul (1978), Vanmarcke (1979), Naeim and Lew (1995),
Available tools	Used in research	Used in practice
SIMQKE (Vanmarcke and Gasparini 1976), various updates and numerous similar codes	Occasionally	Often
Advantages	Disadvantages/limitations	
Rapid; straightforward; provides time-histories whose elastic response spectra exactly match design spectrum; only requires an elastic response spectrum as input; commonly used in past so well established; do not require knowledge of source, path and site; easy-to-use software freely available.	Do not generally involve rigorous considerations of the physics of the earthquakes; true ground-motion variability can be underestimated; too many cycles in ground motions; energy content of motions not realistic; velocity and displacement time-histories not realistic.	

Table 8 Methods based on physics-based stochastic models

Description of method		
Input parameters	Outputs	Key references
Source spectral amplitude, geometric decay rates, anelastic attenuation, local site amplification and attenuation, source spectral shape, source duration, path duration	Ground-motion time-histories reliable from 0 to about 2 s	Hanks (1979), Hanks and McGuire (1981), Boore (1983), Silva et al (1999), Atkinson and Somerville (1994), Boore (2003), Atkinson and Boore (2006)
Available tools	Used in research	Used in practice
SMSIM (Boore 2005), RASCAL (Silva and Lee 1987) and numerous similar codes	Often	Occasionally
Advantages	Disadvantages/limitations	
Rapid; good predictions for short-period motions; useful for regions lacking observational data from damaging earthquakes because the parameters required can be estimated using data from standard seismological networks; input parameters have physical meaning hence link between physics and ground motions; realistic looking time-histories; acts as a link between engineering and seismological approaches.	Long-period motions can be poorly estimated since generally only for S waves; does not generate three-component seismograms with physically-expected coherency; does not account for phase effects due to propagating rupture or wave propagation and, therefore, may not be reliable in near-source region; uncertainty in shape of source spectra for moderate and large events; variability only taken into account by the random generation of the phase; frequency content is stationary with time hence late-arriving surface waves and attenuated shear waves are not modelled; for generic scenario and not a specific source, path and site.	

Table 9 Methods based on physics-based extended stochastic models

Description of method		
Input parameters	Outputs	Key references
Source spectral amplitude, fault location and size, rupture history, geometric decay rates, anelastic attenuation, local site amplification and attenuation, source spectral shape, source duration, path duration	Ground-motion time-histories reliable from 0 to about 4 s	See Table 8, Beresnev and Atkinson (1998), Atkinson and Silva (2000), Motazedian and Atkinson (2005)
Available tools	Used in research	Used in practice
FINSIM (Beresnev and Atkinson 1998), EXSIM (Motazedian and Atkinson 2005)	Occasionally	Rarely
Advantages	Disadvantages/limitations	
Rapid; good predictions for short-period motions; useful for regions lacking observational data from damaging earthquakes because most parameters required can be estimated using data from standard seismological networks; input parameters have physical meaning hence link between physics and ground motions; good predictions for near-source regions; realistic looking time-histories.	Uncertainty in shape of source spectra for moderate and large events.	

Table 10 Method based on group-velocity dispersion curves

Description of method		
Input parameters	Outputs	Key references
Magnitude (or epicentral macroseismic intensity), dis- tance, velocity and density profile of site, style-of-faulting, source depth, seismotectonic regime	Ground-motion time-histories re- liable from 0 to about 4 s	Trifunac (1971), Wong and Trifunac (1978), Lee and Trifunac (1985), Lee and Trifunac (1987), Trifunac (1990)
Available tools	Used in research	Used in practice
SYNACC (Wong and Trifunac 1978)	Rarely	Very rarely
Advantages	Disadvantages/limitations	
Rapid; accounts for non-stationary of time-histories; can be used to generate strain, curvatures and rotation (torsion and rocking) components of motion con- sistent with translation components; ac- counts for detailed site characteristics; in- cludes some variability in ground motions; combines aspects of empirical and physics- based techniques; does not require detailed source description; seismograms have real- istic appearance.	Medium structure limited to stratified lay- ers; requires detailed velocity and density profile for site; no large-scale validation exercise conducted; not widely used and therefore not widely accepted by commu- nity; approach is strictly only valid for surface waves; for generic source; mainly based on observations at deep alluvium sites.	

Table 11 Semi-analytical methods

Description of method		
Solve the elastodynamic equation, complying with the boundary conditions of the free surface, continuity of wave field across each interface and bonded motion at infinity, for a layered homogeneous and isotropic elastic medium over a half-space with an earthquake point source buried inside. The solution is usually derived using the generalized reflection and transmission matrix method, which excludes the growing exponential terms. The solution is computed in the frequency domain and then converted to the time domain. This easily allows the introduction of frequency-dependent attenuation parameters (e.g. quality factor) independently for P and S waves.		
Input parameters	Outputs	Key references
Source location, velocity and density profiles of layered medium, source mechanism, quality factor of medium	Ground-motion time-histories reliable for a frequency range defined by number of discrete frequencies or wavenumbers	Aki and Larner (1970), Kennett and Kerry (1979), Bouchon (1981), Apsel and Luco (1983), Luco and Apsel (1983), Koketsu (1985), Takeo (1985), Zeng and Anderson (1995), Wang (1999), Aki and Richards (2002), Bouchon and Sánchez-Sesma (2007), Chen (2007)
Available tools	Used in research	Used in practice
Many authors freely provide their codes on demand; COMPSYN (Spudich and Xu 2003).	Often	Often
Advantages	Disadvantages/limitations	
Numerically accurate over wide range of frequencies; useful for inverse problems; seismograms have realistic appearance; more rapid than typical FDM; more accurate than typical FDM; stable technique for layers of thicknesses from ms to kms; valid for a wide range of frequencies; can account for material attenuation; widely used in different fields of seismology; can provide static deformation field; can give theoretical Green's function for a unit source so for arbitrary source (finite source with complex source time function) synthetic waveforms can be generated through convolution.	Medium structure often limited to stratified elastic layers; time consuming to calculate motions at many points.	

Table 12 Finite difference methods (FDM)

Description of method		
Directly solve the differential equation of elastic or (viscoelastic) wave propagation in a medium. The volume is discretized, usually by equally-spaced grids, but some intelligent ways of using unstructured grids have also been proposed. Finite fault sources are usually (except when dynamically modelling the rupture process along the fault plane) treated as a series of point sources in the form of double couple forces or stress gluts corresponding to a seismic moment. As for other pure numerical methods, anelastic attenuation can be approximated as a damping factor in the elastic medium but more realistically it is necessary to solve the visco-elastic equations. To simulate an unbounded medium, such as the Earth, some absorbing boundary conditions should be introduced at the edges of the model space so as to avoid artificial wave reflections. Both these aspects are still research topics.		
Input parameters	Outputs	Key references
Source location, time function and mechanism, velocity and density profiles of layered medium, quality factor of medium	Ground-motion time-histories reliable for low frequencies in heterogeneous model corresponding to grid spacing (normally one wavelength needs 5–10 spatial grid points)	Boore (1973), Virieux and Madariaga (1982), Frankel and Clayton (1986), Levander (1988), Graves (1996), Olsen et al (1997), Pitarka et al (1998), Aoi and Fujiwara (1999), Day and Bradley (2001), Oprsal and Zahradník (2002), Olsen et al (2006), Komatitsch and Martin (2007), Moczo et al (2007b)
Available tools	Used in research	Used in practice
Many authors freely provide their codes on demand, e.g. http://geo.mff.cuni.cz/~io/	Often	Occasionally
Advantages	Disadvantages/limitations	
Can treat any heterogeneous medium; can allow volumetric visualization of wave propagation without increasing number of numerical calculations; rapid computer development in 1990s means that large calculations are easy for practical applications; most efficient of all purely numerical methods; complex geometry more easy to model; can also treat any anisotropy and/or anelastic media.	Not better than semi-analytical methods with respect to numerical accuracy; numerical dispersion; shows best performance for structured grids; not good at treating sharp interfaces with strong contrasts (e.g. internal layering and topography); gridding does not always correspond to material interfaces, which means that elastic properties attributed to each grid point is usually an average value thereby limiting the accuracy of the method in heterogeneous media.	

Table 13 Finite element methods (FEM)

Description of method		
Solve the variational, or weak form, of the equations of wave propagation with low-order polynomial bases in the framework of unstructured elements. This leads to a linear system of equations in matrix form. Normally the tensors are not diagonal and therefore the unknown solution vectors have to be numerically inverted from these equations.		
Input parameters	Outputs	Key references
Source location, time function and mechanism, velocity and density profiles of layered medium, mesh, quality factor of medium	Ground-motion time-histories reliable for a frequency defined by element spacing	Lysmer and Drake (1972), Bao et al (1998), Ma et al (2007), Moczo et al (2007a)
Available tools	Used in research	Used in practice
Mostly commercial codes	Rarely	Rarely
Advantages	Disadvantages/limitations	
Can treat any heterogeneous medium; can allow volumetric visualization of wave propagation without increasing number of numerical calculations; complex geometry more easy to model; parallelization of computer codes possible; meshing can be made consistent with material interfaces, which improves accuracy of method (see Table 12).	Numerical dispersion; very numerically expensive; parallelization usually difficult because of domain participation and matrix; complicated meshing is a big task that must be completed before application of FEM code.	

Table 14 Spectral element methods (SEM)

Description of method		
Solve the variational, or weak form, of the equations of wave propagation with high-order basic functions for unstructured elements. It is an integrated formulation of classical FEM (Table 13). This approach is becoming popular for the simulation of ground motions from large earthquakes and for motions affected by basin structures.		
Input parameters	Outputs	Key references
Source location, time function and mechanism; velocity and density profiles of layered medium; mesh, quality factor of medium	Ground-motion time-histories reliable for a frequency defined by element spacing and order of basic functions	Faccioli et al (1997), Komatitsch and Vilotte (1998), Komatitsch and Tromp (1999), Komatitsch et al (2004), Krishnan et al (2006), Chaljub et al (2007a)
Available tools	Used in research	Used in practice
SPECFEM3D (Chen et al 2008)	Occasionally	Very rarely
Advantages	Disadvantages/limitations	
See Table 13; compared to FEM calculation is faster thanks to diagonal matrix; can use larger elements thanks to higher-order basic functions compared to FEM.	Much more numerically expensive than FDM but less expensive than FEM; simple structured elements generally preferred.	

Table 15 Methods based on modal summation

Description of method		
For a wave field in a limited area only consisting of wave-trains propagating away from the source, the surface-wave formulation is adequate. Lateral heterogeneity can also be treated as coupling of local modes.		
Input parameters	Outputs	Key references
Source location, time function and mechanism, velocity and density profiles of layered medium, quality factor of medium	Ground-motion time-histories reliable for low frequencies in heterogeneous model defined by used mode frequencies	Woodhouse (1974), Swanger and Boore (1978), Panza (1985), Panza and Suhadolc (1987), Florsch et al (1991), Douglas et al (2004), Maupin (2007)
Available tools	Used in research	Used in practice
Some authors freely provide their codes on demand	Occasionally	Rarely
Advantages	Disadvantages/limitations	
Useful when surface waves dominate, e.g. at long periods and moderate distances; widely used for teleseismic studies so efficient programs exist; the dispersion parameters and eigenfunctions need only be computed once for time-domain synthesis for any type and depth of source, at any azimuth and any distance; time-domain synthesis simple and rapid; useful for interpretation of relative importance of source depth and site response; easy to extend point source solutions to extended sources; number of layers not a practical limitation; useful for inverse problems.	Only reliable when epicentral distance is greater than focal depth; only gives an approximation (of unknown accuracy) of the total motion; not suitable when no surface layers.	

Table 16 Lattice particle method

Description of method		
Instead of solving differential equation in continuous medium simulate physical interaction between particles on a discrete lattice. Depending on the physical description and numerical discretization this method is also known as: lattice solid model, discrete element method or distinct element method.		
Input parameters	Outputs	Key references
Source location, time function and mechanism, velocity and density profiles of layered medium, mesh, quality factor of medium	Ground-motion time-histories reliable for low frequencies in heterogeneous model corresponding to a large number of elements	Mora and Place (1994), Place and Mora (1999), Dalguer et al (2003), Shi and Brune (2005)
Available tools	Used in research	Used in practice
None known	Very rarely	Very rarely
Advantages	Disadvantages/limitations	
Applicable for complex hydro-dynamical problems that cannot be described as a system of continuous mediums; accurate for compressive waves.	Complex calculation; less accurate for shear waves; numerically expensive.	

Table 17 Finite volume method

Description of method		
Transform the differential equation into a conservative formulation inside a discrete volume. This leads to an integral equation different from those of FEM and SEM; however, for certain simple cases the method corresponds to FDM or FEM.		
Input parameters	Outputs	Key references
Source location, time function and mechanism, velocity and density profiles of layered medium, mesh, quality factor of medium	Ground-motion time-histories reliable for a frequency defined by element spacing	Dormy and Tarantola (1995), LeVeque (2002), Käser and Iske (2005)
Available tools	Used in research	Used in practice
None known	Very rarely	Very rarely
Advantages	Disadvantages/limitations	
Can correctly treat the material interfaces; suitable for unstructured meshes; can be more accurate than FDM.	Higher-order approximation numerically costly; numerical efforts much heavier than FDM.	

Table 18 Methods based on ray theory

Description of method		
Input parameters	Outputs	Key references
Source location, time function and mechanism, velocity and density profiles of layered medium, quality factor of medium	Ground-motion time-histories reliable for low frequencies depending on heterogeneities	Heaton and Helmberger (1977), Atkinson and Somerville (1994)
Available tools	Used in research Often	Used in practice Rarely
Some authors freely provide their codes on demand; ISOSYN (Spudich and Xu 2003).		
Advantages	Disadvantages/limitations	
Economical, especially for high frequencies where the contribution of surface waves is small; arrival of different phases accurately modelled; attenuation function derived from focal depth and crustal structure and therefore more appropriate when empirical attenuation information lacking; provides insight through analysis of crustal conditions controlling details of observed ground motions and also the effects of focal depth on attenuation.	Not efficient when many layers; cannot easily account for attenuation; time-histories not realistic because scattering not included; low frequencies better predicted than high frequencies.	

Table 19 Methods based on empirical Green's functions (EGF) (classic)

Description of method		
Input parameters	Outputs	Key references
Recorded accelerogram(s) of small event(s) (1-3 magnitude units smaller than modelled event) in the source region of the modelled earthquake, basic fault model, source-to-site distances	Ground-motion time-histories reliable from 0 to 1–10 s, depending on quality of EGF(s)	Hartzell (1978), Kanamori (1979), Hadley and Helmberger (1980), Dan et al (1990), Irikura and Kamae (1994), Tumarkin and Archuleta (1994), Frankel (1995), Kamae et al (1998), Pavic et al (2000).
Available tools	Used in research	Used in practice
None known	Often	Rarely
Advantages	Disadvantages/limitations	
Computation is rapid; EGFs already contain all the information about the path and local site effects; does not explicitly compute the wave path or site effects (since captured within the time-histories from the small earthquake); simulated motions are closely based on observations; ground motions look realistic.	Only possible where appropriate records of small events from the source area recorded at sites of interest are available (rare for source areas of future large earthquakes); EGF(s) must have same focal mechanism(s) as modelled earthquake; many (poorly constrained) degrees of freedom therefore large epistemic uncertainties in results; strictly only for site(s) with available EGF(s); signal-to-noise ratio of Green's function limits long-period estimation; event should be able to be considered as a point source; difficult to match the source characteristics since the stress drops of small and large earthquakes may be different; valid up to the corner frequency of EGF(s); debate over correct method to sum the EGFs; results can have strong dependence on choice of EGF(s); does not account for nonlinear site effects (not a problem if predicting at rock sites).	

Table 20 Methods based on empirical Green's functions (stochastic)

Description of method		
Input parameters	Outputs	Key references
Recorded accelerogram(s) of small event(s) (1-3 magnitude units smaller than modelled event) in the source region of the modelled earthquake, magnitude, stress drop source-to-site distance	Ground-motion time-histories reliable from 0 to 1-10 s, depending on quality of EGF(s)	See Table 19, Joyner and Boore (1986), Wennerberg (1990), Ordaz et al (1995), Kohrs-Sansorny et al (2005)
Available tools	Used in research	Used in practice
None known	Often	Rarely
Advantages	Disadvantages/limitations	
Rapid; far fewer degrees-of-freedom than classic EGF approach; simulates a multitude of rupture processes; variability in simulated ground motions; see Table 19.	Source-to-site distance must be greater than source dimensions therefore not for near-source region since assumes point source and hence does not model directivity; see Table 19.	

Table 21 Hybrid stochastic-empirical method

Description of method		
A stochastic model (Table 8) is constructed for a target region (e.g. from existing literature). Stochastic models are estimated for existing empirical ground-motion models (for different host regions) for response spectra by finding models that lead to the minimum misfit between predicted response spectra from empirical and stochastic models. Response spectra are predicted for various magnitudes and distances (and other independent variables) by the empirical ground-motion models and then are multiplied by the ratio between the response spectrum predicted by the stochastic models for the target and host regions. These response spectral ordinates are then regressed to develop hybrid stochastic-empirical ground-motion models for the target region.		
Input parameters	Outputs	Key references
Magnitude, distance, near-surface site characteristics, style-of-faulting, seismotectonic regimes of host and target regions, source depth, gross source characteristics, deep geology, Source spectral amplitude, geometric decay rates, anelastic attenuation, local site amplification and attenuation, source spectral shape, source duration, path duration	Strong-motion intensity amplitude parameters (e.g. PGA, PGV, PGD and response spectral ordinates)	See Tables 2 and 8, Atkinson (2001), Campbell (2003), Tavakoli and Pezeshk (2005), Douglas et al (2006), Scherbaum et al (2006), Campbell (2007)
Available tools	Used in research	Used in practice
CHEEP (Douglas et al 2006)	Occasionally	Rarely
Advantages	Disadvantages/limitations	
See Tables 2 and 8.	See Tables 2 and 8; difficult to assess true variability of derived models; not yet validated by observations.	

Table 22 Hybrid numerical methods

Description of method		
High frequencies from one method and low frequencies from another method to get hybrid synthetic ground motions (after used matched filters to combine the two approaches) that are then used to simulate motions from large earthquakes. This approach is taken since smaller scale heterogeneity in the Earth (source, propagation path and site) is difficult to deterministically identify and our knowledge in each method is limited. Those who propose EGF or stochastic methods (e.g. Tables 8, 9, 19 and 20) to generate high frequencies assume relatively simple earthquake source description, whereas those who use semi-analytical or numerical methods (see Tables 11, 12 and 13) up to high frequencies adopt complex descriptions of the earthquake source, which have been greatly developed in the past decade. There are numerous combinations proposed in the literature.		
Input parameters	Outputs	Key references
See tables for the two methods comprising the hybrid approach	See tables for the two methods comprising the hybrid approach	Berge et al (1998), Kamae et al (1998), Pitarka et al (2000), Hartzell et al (2002), Mai and Beroza (2003), Gallovič and Brokešová (2007), Hisada (2008)
Available tools	Used in research	Used in practice
No ready-to-use code is known to exist	Occasionally	Occasionally
Advantages	Disadvantages/limitations	
Practical for a wide range of frequencies; reduces computation time considerably; works for near-source region; can handle complex propagation media because crustal phases and surface waves evaluated with complete Green's functions; can statistically adjust the frequency content of ground motion to that desired; see tables for the two methods comprising the hybrid approach.	Combination of two sets of simulation results is not always easy; not evident how to obtain triaxial time-histories with correct correlation between components; not evident that velocity and displacement time-histories are realistic, especially in the time domain, due to the lack of causality of phase; see tables for the two methods comprising the hybrid approach.	