



**HAL**  
open science

## Innovative process routes for a high-quality concrete recycling in the aggregates and cement industries

Kathy Bru, Yannick Menard, Solène Touzé, Alain Le Moign, Jean Eric Poirier, Gilles Ruffié, Fabrice Bonnaudin, Frédéric von Der Weid

► **To cite this version:**

Kathy Bru, Yannick Menard, Solène Touzé, Alain Le Moign, Jean Eric Poirier, et al.. Innovative process routes for a high-quality concrete recycling in the aggregates and cement industries. SARDINIA 2011 - Thirteenth International Waste Management and Landfill Symposium, Oct 2011, Cagliari, Italy. pp.1. hal-00594306

**HAL Id: hal-00594306**

**<https://brgm.hal.science/hal-00594306>**

Submitted on 1 Dec 2011

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# INNOVATIVE PROCESS ROUTES FOR A HIGH-QUALITY CONCRETE RECYCLING IN THE AGGREGATES AND CEMENT INDUSTRIES

Y. MENARD<sup>a</sup>, K. BRU<sup>a</sup>, S TOUZE<sup>a</sup>, A. LEMOIGN<sup>b</sup>, J.E. POIRIER<sup>c</sup>, G. RUFFIE<sup>d</sup>, F. BONNAUDIN<sup>d</sup>, F. VON DER WEID<sup>e</sup>

<sup>a</sup> *BRGM, Environment and process division, Orleans, France*

<sup>b</sup> *Picheta, Recycling and remediation division, Pierrelaye, France*

<sup>c</sup> *COLAS, Campus scientifique et technique, Magny-les-Hameaux, France*

<sup>d</sup> *IMS, PESSAC, France*

<sup>e</sup> *SELFRAG AG, Kerzers, Switzerland*

**SUMMARY:** This study presents alternative methods for the processing of concrete. The mechanical stresses needed for the embrittlement of the mortar matrix and further selective crushing of concrete were generated by either electric impulses or microwaves heating. Tests were carried out on lab-made concrete samples representative of concrete waste from revolving drum and on concrete waste collected on a French demolition site. The results obtained so far show that both techniques can be used to weaken concrete samples and to enhance aggregate selective liberation during crushing and grinding. Electric pulses treatment seems to appear more efficient, more robust and less energy consuming (1 to 3 kWh t<sup>-1</sup>) than microwave treatment (10 to 40 kWh t<sup>-1</sup>) but it can only be applied on samples in water leading to a major drawback for recycling aggregates or cement paste in the cement production process.