



HAL
open science

On the bending and tension of thermoelastic shells undergoing phase transitions

Victor A. Eremeyev, Wojciech Pietraszkiewicz

► **To cite this version:**

Victor A. Eremeyev, Wojciech Pietraszkiewicz. On the bending and tension of thermoelastic shells undergoing phase transitions. PAMM, 2009, 9 (1), pp.305-306. hal-00835654

HAL Id: hal-00835654

<https://hal.science/hal-00835654>

Submitted on 19 Jun 2013

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

On the bending and tension of thermoelastic shells undergoing phase transitions

Victor A. Eremeyev^{1,2,*} and Wojciech Pietraszkiewicz^{1,**}

¹ Institute of Fluid-Flow Machinery of the Polish Academy of Sciences, ul. Gen. J. Fiszerza 14, 80-952 Gdańsk, Poland

² South Scientific Center of RASci and South Federal University, 8a, Milchakov St. 8a, 344090 Rostov on Don, Russian Federation

Applying the general non-linear theory of shells undergoing phase transitions, we derive the balance equations along the singular surface curve modelling the phase interface in the shell. From the integral forms of balance laws of linear momentum, angular momentum, and energy as well as the entropy inequality we obtain the local static balance equations along the curvilinear phase interface. We also derive the thermodynamic condition allowing one to determine the interface position on the deformed shell midsurface. The theoretical model is illustrated by the example of thin circular cylindrical shell made of two-phase material subjected to tensile forces and bending couples at the shell boundary. The elastic solution reveals the existence of the hysteresis loop whose size depends upon values of several loading parameters.

1 Introduction

Phase transition (PT) phenomenon in continuous media originally described by Gibbs in 1875–1878, see [1], was developed in a number of papers summarised in several recent books, for example in [2–5]. In this approach one assumes existence of the sharp phase interface being a sufficiently regular surface dividing different material phases. The position and motion of the phase interface itself is among the most discussed issues in the field. In the literature many model one-dimensional (1D) problems were analysed theoretically, numerically and experimentally which adequately described behaviour of bars, rods, and beams made of martensitic materials.

The non-linear equilibrium conditions of elastic shells undergoing PT of martensitic type were formulated in [6–8] within the dynamically and kinematically exact theory of shells presented in [9–11]. In this shell theory the translation vector \mathbf{u} and rotation tensor \mathbf{Q} fields are the only independent variables. By analogy to the 3D case, the two-phase shell was regarded as the Cosserat surface consisting of two material phases divided by a sufficiently smooth surface curve. Existence of such a curve was confirmed by several experiments on thin-walled samples.

2 Basic relations

The two-dimensional (2D) local laws of shell thermomechanics can be derived by direct and exact through-the-thickness integration of global 3D balances of forces, moments, energy and the entropy inequality, see [6–8]. After appropriate transformations the resulting 2D local Lagrangian laws in $M \setminus \mathcal{C}$ become

$$\begin{aligned} Div_s \mathbf{N} + \mathbf{f} &= \mathbf{0}, \quad Div_s \mathbf{M} + ax(\mathbf{N}\mathbf{F}^T - \mathbf{F}\mathbf{N}^T) + \mathbf{c} = \mathbf{0}, \\ \rho \frac{d\varepsilon}{dt} &= \rho(q^+ + q^- + q_{\Pi}) - Div_s \mathbf{q} + \mathbf{N} \bullet \mathbf{E}^\circ + \mathbf{M} \bullet \mathbf{K}^\circ, \\ \rho \frac{d\psi}{dt} &\leq \rho \eta \frac{dT}{dt} + \mathbf{N} \bullet \mathbf{E}^\circ + \mathbf{M} \bullet \mathbf{K}^\circ + Grad_s \left(\frac{1}{T} \right) \cdot \mathbf{q} + \rho q^+ \left(1 - \frac{T}{T_{ext}^+} \right) + \rho q^- \left(1 - \frac{T}{T_{ext}^-} \right), \end{aligned} \quad (1)$$

where \mathbf{f} , \mathbf{c} are the resultant surface force and couple vector fields acting on $N \setminus \mathcal{D}$, but measured per unit area of $M \setminus \mathcal{C}$, M and N are the shell midsurfaces in the undeformed and deformed placements, respectively, $\mathcal{C} \subset M$ and $\mathcal{D} \subset N$ are the curvilinear phase interfaces, $(\mathbf{N}, \mathbf{M}) \in E \otimes T_x M$ the surface tangential stress resultant and stress couple tensors of the first Piola-Kirchhoff type, $\mathbf{F} = Grad_s \mathbf{y}$ the surface deformation gradient, $\mathbf{F} \in E \otimes T_x M$, $ax(\dots)$ the axial vector associated with the skew tensor (\dots) , $(\mathbf{E}^\circ, \mathbf{K}^\circ) \in E \otimes T_x M$ the corotational derivatives of the shell strain measures work-conjugate to (\mathbf{N}, \mathbf{M}) , and Div_s the surface divergence operator on M . Additionally, ε and η are the surface internal energy and entropy densities, ρ the undeformed surface mass density, q^\pm the heat influx densities through the upper (+) and lower (–) shell faces, q_{Π} the internal surface heat supply density, \mathbf{q} the surface heat influx vector, T the through-the-thickness average temperature, T_{ext}^+ and T_{ext}^- temperatures of the external media surrounding the shell from above and below, and $\psi = \varepsilon - T\eta$ the surface free energy density. For constitutive equations of thermoelastic and thermoviscoelastic shells see [8].

* Corresponding author E-mail: eremeyev.victor@gmail.com.

** e-mail: pietrasz@imp.gda.pl

We use the kinetic equation, describing motion of the phase interface for all quasistatic processes, in the form

$$V = -\mathcal{F}(\boldsymbol{\nu} \cdot \llbracket \mathbf{C} \rrbracket \boldsymbol{\nu}), \quad \mathbf{C} = \rho\psi \mathbf{A} - \mathbf{N}^T \mathbf{F} - \mathbf{M}^T \mathbf{K}, \quad (2)$$

where \mathcal{F} is the non-negative definite kinetic function depending on the jump of \mathbf{C} at \mathcal{C} , i.e. $\mathcal{F}(\zeta) \geq 0$ for $\zeta > 0$, the expression $\llbracket \dots \rrbracket = (\dots)_B - (\dots)_A$ means the jump at \mathcal{C} , $\boldsymbol{\nu}$ the surface unit vector externally normal to ∂M , V the exterior normal velocity of the phase curve \mathcal{C} , $\mathbf{A} = \mathbf{1} - \mathbf{n} \otimes \mathbf{n}$, and $\mathbf{1}$ the 3D unit tensor.

We assume $\mathcal{F}(\zeta)$ in the form

$$\mathcal{F}(\zeta) = \begin{cases} \frac{k(\zeta - \zeta_0)}{1 + a(\zeta - \zeta_0)} & \zeta \geq \zeta_0, \\ 0 & -\zeta_0 < \zeta < \zeta_0, \\ \frac{k(\zeta + \zeta_0)}{1 - a(\zeta + \zeta_0)} & \zeta \leq -\zeta_0. \end{cases} \quad (3)$$

Here ζ_0 describes the effects associated with nucleation of the new phase and action of the surface tension, a is a parameter describing the limit value of the phase transition velocity, and k is a positive kinetic factor.

3 Bending and tension of elastic thin-walled tube

As an example, we discuss the thin circular cylindrical shell of length L , radius R , and thickness h made of material undergoing phase transition. The phase interface \mathcal{C} is given by $z = \ell$. The tube is extended by forces P and bent by couples m uniformly distributed at the right shell boundary. The two-phase solution is presented in Fig. 1.




Fig. 1 Shape of the thin-walled two-phase tube after phase transition (magnified).

The proposed 2D model allows one to take into account several additional factors such as solutions of the boundary layer type or more differentiated ways of loading and unloading.

Acknowledgements

The first author was supported by the Russian Foundation of Basic Research with the grants No 07-01-00525 and No 09-01-00459, while the second author by the Polish Ministry of Science and Higher Education with the grant No N501 0073 33.

References

- [1] J. W. Gibbs, On the equilibrium of heterogeneous substances, in: The Collected Works of J. Willard Gibbs, (Longmans, Green & Co, New York, 1928), pp. 55–353.
- [2] K. Bhattacharya, Microstructure of Martensite: Why It Forms and How It Gives Rise to the Shape-Memory Effect (Oxford University Press, Oxford, 2003).
- [3] R. Abeyaratne and J. K. Knowles, Evolution of Phase Transitions: A Continuum Theory (Cambridge University Press, Cambridge, 2006).
- [4] D. C. Lagoudas (ed.), Shape Memory Alloys: Modeling and Engineering Applications (Springer, Berlin, 2008).
- [5] A. Berezovski, J. Engelbrecht, and G. A. Maugin, Numerical Simulation of Waves and Fronts in Inhomogeneous Solids (World Scientific, New Jersey et al., 2008).
- [6] V. A. Eremeyev and W. Pietraszkiewicz, Journal of Elasticity **74**(1), 67–86 (2004).
- [7] W. Pietraszkiewicz, V. A. Eremeyev, and V. Konopińska, ZAMM **87**(2), 150–159 (2007).
- [8] V. A. Eremeyev and W. Pietraszkiewicz, Archives of Mechanics **61**(1), 41–67 (2009).
- [9] A. Libai and J. Simmonds, The Nonlinear Theory of Elastic Shells, 2nd edition (Cambridge University Press, Cambridge, 1998).
- [10] J. Chrościelewski, J. Makowski, and W. Pietraszkiewicz, Statyka i dynamika powłok wielopłatowych: Nieliniowa teoria i metoda elementów skończonych (Wydawnictwo IPPT PAN, Warszawa, 2004).
- [11] V. A. Eremeyev and L. M. Zubov, Mechanics of Elastic Shells (in Russian) (Nauka, Moscow, 2008).