Axisymmetric formulation for boundary integral equation methods in scalar potential problems

Laurent Krähenbühl, Alain Nicolas

► To cite this version:

Laurent Krähenbühl, Alain Nicolas. Axisymmetric formulation for boundary integral equation methods in scalar potential problems. IEEE Transactions on Magnetics, 1983, 19 (6), pp.2364 - 2366. 10.1109/TMAG.1983.1062872 . hal-00414086

HAL Id: hal-00414086

<https://hal.science/hal-00414086>

Submitted on 8 Sep 2009

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

AXISYMMETRIC FORMULATION FOR BOUNDARY INTEGRAL EQUATION METHODS IN SCALAR POTENTIAL PROBLEMS

by L. KRAHENBUHL and A. NICOLAS

Abstract : Axisymmetric geometries often appear in electromagnetic device studies. The authors present an original formulation for Boundary Integral Equation methods in scalar potential problems. This technique requires only 2D boundary in the r-z plane and evaluation of the equations only on those boundaries.

INTRODUCTION

Scalar potential problems are described by Laplace's equation :

$$\Delta\psi = 0 \quad (1)$$

in the general 3D space.

When the geometry is an axisymmetric there are two possibilities :

- use cylindrical coordinates, express equation (1) in this set of coordinates and note that each quantity is invariant in the azimuthal direction

Laplace equation becomes :

$$\frac{\partial^2 \psi}{\partial z^2} + \frac{\partial^2 \psi}{\partial r^2} + \frac{1}{r} \cdot \frac{\partial \psi}{\partial r} = 0 \quad (2)$$

Boundary Integral Equations have to be developed with operator :

$$\frac{\partial^2}{\partial z^2} + \frac{\partial^2}{\partial r^2} + \frac{1}{r} \cdot \frac{\partial}{\partial r}$$

This gives complicated expressions.

- the second method we propose to develop is to express the BIE in 3D space and to integrate all the invariant quantities analytically before solving the equations.

AXISYMMETRIC FORMULATION

In a 3D space Laplace equation is transformed into BIE equation :

$$c.\psi = \iint_{\partial R} \left(\psi \cdot \frac{\partial G}{\partial n} - \epsilon \cdot \frac{\psi}{\mu_i} \cdot G \right) ds - \iint_{\partial R} H_{0n} \cdot G \cdot ds \quad (3)$$

as shown in previous publications [1].

When ψ , ψ and H_{0n} are constant along one part of the boundary ∂R , partial integration of functions G and $\partial G / \partial n$ along that direction can be made. As an example it can be shown that partial integration of 3D Green's function

$$G = \frac{1}{4\pi r} \quad (4)$$

over a straight line gives 2D Green's function :

$$G_{2D} = -\frac{1}{2\pi} \cdot \log r \quad (5)$$

The authors are with
Departement d'Electrotechnique - ERA 908
Ecole Centrale de Lyon - BP 163
69131 ECULLY CEDEX - FRANCE

In axisymmetric geometry physical quantities keep constant values on circular lines : Green's function G and derivative function $\partial G / \partial n$ have to be integrated on circles.

By this way a 2D Boundary Integral Equation can be generated in the r-z plane, similar to those in x-y plane [4].

$$c.\psi = \int_{\partial R} \left(\psi \cdot G'_{ax} - \epsilon \cdot \frac{\psi}{\mu_i} \cdot G_{ax} \right) \cdot dl - \int_{\partial R} H_{0n} \cdot G_{ax} \cdot dl \quad (6)$$

It can be noticed that G_{ax} gives the potential of a uniform charge distribution on a circle. Classical development [2] can be applied to obtain function G_{ax} :

$$G_{ax} = \oint_{\text{circle}} G \cdot dl = \int_{\text{circle}} \frac{R \cdot d\theta}{4\pi \sqrt{D^2 - 2R \cdot \rho \cdot (1 + \cos \theta)}} = \frac{R}{\pi \cdot D} K(k^2) \quad (7)$$

$$k = 2\sqrt{R \cdot \rho} / D \quad (8)$$

where :

K : complete elliptic integral of the first kind

[3]

ρ , R , D : as shown on Fig. 1

Function G'_{ax} is obtained by a similar development :

$$G'_{ax} = \oint \frac{\partial G}{\partial n} \cdot dl \quad (9)$$

$$= -\frac{\cos \alpha}{2\pi D} K(k^2) + \frac{1}{2\pi D} \cdot [D \cdot \cos \alpha - 2R \cdot \cos(\alpha - \gamma)] \cdot E(k^2)$$

with

E : complete elliptic integral of the second kind.

α , γ , D' : as shown on Fig. 1

Figure 1

FLUX DENSITY CALCULATION

The induced magnetic field in a point P of the region R :

$$\vec{H}_i = -\text{grad } \varphi \quad (10)$$

can be computed directly by integration of φ and ψ on the boundary δR :

$$\vec{H}_i = - \int_{\delta R} \left[\varphi \cdot \vec{\text{grad}} G'_{ax} - \left(\epsilon \frac{\phi}{\mu_r} + H_{on} \right) \cdot \vec{\text{grad}} G_{ax} \right] \cdot d\vec{l} \quad (11)$$

with

$$\frac{dG_{ax}}{d\rho} = \frac{R}{\pi D} \left(-\frac{R+\rho}{D^2} \cdot K + \frac{dK}{dk} \cdot \frac{dk}{d\rho} \right) \quad (12)$$

$$\frac{dG_{ax}}{dz} = \frac{R}{\pi D} \left(-\frac{z}{D^2} \cdot K + \frac{dK}{dk} \cdot \frac{dk}{dz} \right) \quad (13)$$

$$\frac{dG'_{ax}}{d\rho} = -\frac{\cos \alpha}{2 \cdot R} \cdot \frac{dG_{ax}}{d\rho} \quad (14)$$

$$+ \frac{D \cdot \cos \alpha - 2 \cdot R \cdot \cos(\alpha - \gamma)}{2 \cdot \pi \cdot D^{1/2}} \cdot \left(\frac{dE}{dk} \frac{dk}{d\rho} + \frac{2 \cdot (R-\rho)}{D^{1/2}} \cdot E \right) + \frac{1}{2 \cdot \pi \cdot D D^{1/2}} \cdot \left[(\rho - R) \cdot \cos \alpha + \frac{2 \cdot R}{D} (R + \rho) \cdot \cos(\alpha - \gamma) \right] \cdot E$$

$$\frac{dG'_{ax}}{dz} = -\frac{\cos \alpha}{2 \cdot R} \cdot \frac{dG_{ax}}{dz} \quad (15)$$

$$+ \frac{D \cdot \cos \alpha - 2 \cdot R \cdot \cos(\alpha - \gamma)}{2 \cdot \pi \cdot D^{1/2}} \cdot \left(\frac{dE}{dk} \frac{dk}{dz} - \frac{2 \cdot z}{D^{1/2}} \cdot E \right) + \frac{1}{2 \cdot \pi \cdot D D^{1/2}} \cdot \left[z \cdot \cos \alpha - 2 \cdot R (\sin \alpha - \frac{z}{D} \cdot \cos(\alpha - \gamma)) \right] \cdot E$$

$$\frac{dK}{dk} = \frac{1}{k} \cdot \left(\frac{E}{1-k^2} - K \right) \quad (16)$$

$$\frac{dE}{dk} = \frac{1}{k} \cdot (E - K) \quad (17)$$

$$\frac{dk}{dz} = -\frac{z \cdot k^3}{4 \cdot R \cdot \rho} \quad (18)$$

$$\frac{dk}{d\rho} = \frac{k}{2 \cdot \rho} - \frac{k^3}{4} \cdot \frac{R+\rho}{R \cdot \rho} \quad (19)$$

$$K = K(k^2) \quad E = E(k^2)$$

It must be noticed that these expressions depend on the same functions K and E as G'_{ax} and G'_{ax} .

When the point P is on the boundary, a more simple expression can be used :

$$\vec{H}_i = - \left(\epsilon \frac{\phi}{\mu_r} + H_{on} \right) \cdot \vec{n} - \frac{\delta \varphi}{\delta \vec{t}} \cdot \vec{t} \quad (20)$$

an equivalent result is obtained in this way. However computing time is less important in this case.

NUMERICAL DEVELOPMENT

Numerical calculation of integrals K and E can be done in several ways :

- numerical integration ;
- asymptotic development [3] ;
- tabulation and interpolation.

As these integrals have to be computed a large number of times, the third solution appears to be the most convenient.

Function E is always regular, but K becomes singular when $r_{PQ} \rightarrow 0$. This singularity is similar to $\text{Log}(r)$ singularity, and Gaussian quadrature formulae with weight function $\text{Log}(t)$ are well matched for evaluation of the integral (6) of function K.

This development is now applied in PHIAx program, using classical techniques [1], [4].

NUMERICAL RESULT

The analytical solution is known for a ferromagnetic sphere in a constant field [5]. We have chosen this example to test the method.

The sphere is discretised into 4 finite elements of second order (fig. 2). The accuracy of the solution on the boundary is better than 0.4 % on the potential and 1. % on the normal flux density (fig. 3).

Fig. 2 : Finite element discretisation of the sphere.

Point	Potential			Flux density		
	Phiax progr.	Analit. value		Phiax progr.	Analit. value	
1	3.8808	3.8823	.4%	5.8881	5.8823	1.1%
2	3.5859	3.5868	.3%	5.4369	5.4346	.4%
3	2.7441	2.7452	.3%	4.1628	4.1595	.6%
4	1.4853	1.4857	.1%	2.2517	2.2511	.1%
5	.1E-04	0.	.04%	.4E-05	0.	

Fig.3 : Solution on the boundary.

The values of potential and flux density for 6 external points are also presented with comparison to analytical values (fig. 4). The points 6 and 7 are very near the boundary and the integration errors increase.

The same integrals give the angular factor "C" ($|4|$; eq. (6)). So this coefficient becomes a "goodness factor" of the method and allows the definition of a forbidden area around the boundary where potential and magnetic field cannot be computed.

Point	Potential					
	Phi _{ax}	Analit.				
	progr.	value				
3	2.7441	2.7452				
6	2.5948	2.6114				
7	2.4736	2.4402				
8	2.1434	2.1447				
9	1.8999	1.8998				
10	1.6938	1.6946				
11	1.3715	1.3726				

Point	H _p		H _z		Rel. error	
	Phi _{ax}	Analit.	Phi _{ax}	Analit.	on 'c'	
	progr.	value	progr.	value	see eq. (6)	
3	2.9138	2.9118	0.9731	0.9706		
6	-2.0787	2.7014	-3.9932	0.9005	7.5%	X
7	2.9622	2.4402	1.3445	0.8134	11.2%	X
8	2.0131	2.0107	0.6744	0.6702	1.2%	
9	1.6701	1.6763	0.5522	0.5588	<1%	
10	1.4101	1.4122	0.4691	0.4707		
11	1.0284	1.0295	0.3427	0.3431		

Fig.4 : Potential and flux density on the straight line $\mathcal{D}$.

X points in the forbidden area.

CONCLUSION

The method we developed and exposed is the complementary to the BIE programs already existing in 2D and 3D. It solves a large set of problems at a low computing cost and needs a very short geometry description time. With PHI2D, PHI3D and now this PHIAX packages it is possible to solve with the BIE method all magnetostatic or electrostatic problems.

REFERENCES

- [1] ANCELLE B. : "Emploi de la méthode des équations intégrales de frontière et mise en oeuvre de la CAO dans les calculs des systèmes électromagnétiques" PH. D. Thesis - Grenoble 1979.
- [2] DURAND : "Electrostatique" - tome 1, Masson, Paris
- [3] ABRAMOWITZ M. and STEGUN I.A. : "Handbook of mathematical functions". Dover Publication.
- [4] KRAHENBUHL L. and NICOLAS A. : "Efficient techniques for boundary equations method for potential problems". Compumag 83.
- [5] DURAND : "Magnétostatique" - Masson, Paris.