A Linear Time-Varying Controller for Synchronization of LÜ Chaotic Systems With One Input

Antonio Loria

► To cite this version:

Antonio Loria. A Linear Time-Varying Controller for Synchronization of LÜ Chaotic Systems With One Input. IEEE Transactions on Circuits and Systems I: Regular Papers, 2009, 56 (08), pp.674 - 678. 10.1109/TCSII.2009.2025624 . hal-00447345

HAL Id: hal-00447345

<https://hal.science/hal-00447345>

Submitted on 14 Jan 2010

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

A Linear Time-Varying Controller for Synchronization of Lü Chaotic Systems With One Input

Antonio Loria

Abstract—This brief addresses the problem of synchronization of two Lü chaotic systems. As opposed to nonlinear Lyapunov-based controllers, which are designed with the aim of rendering the derivative of a Lyapunov function negative along trajectories of the closed-loop system, control design exploits the natural stability properties of the system. The proof relies not only on basic Lyapunov stability theory but also on other concepts, such as persistency of excitation. The contribution with respect to other works is to show that *one* control input is enough to force synchronization; moreover, the controllers are *linear time varying*.

Index Terms—Chaotic systems, control, nonlinear oscillators, synchronization.

I. INTRODUCTION

MASTER-SLAVE synchronization continues to attract the attention of research communities. For example, the utility of popular techniques such as observer-based synchronization (cf. [2] and [5]) is reiterated by experiment validation as feasible solutions for secure telecommunication (cf. [4]). In that context, see also [6] for a brief paper on the synchronization of Lü systems (which are the subject of this brief) in the context of code-division multiple access.

This brief addresses the problem of controlled master-slave synchronization for the so-called Lü chaotic oscillator (cf. [9]); this problem was successively solved via nonlinear Lyapunov-based control in [10] and [11], in the former using three control inputs and in the latter using two control inputs. In both references, control is nonlinear and designed with the aim of rendering the derivative of a quadratic Lyapunov function negative definite, which is a standard procedure in control theory.

Our controllers are designed, following engineering intuition (basic “filtering signal” ideas) and a fundamental concept from stability and control theory named *persistency of excitation* (cf. [1]). Roughly, the latter is the property of a signal by which a certain *average* is strictly positive. For illustration, consider the context of electrical circuits, particularly a standard (serial) RC circuit¹ with variable resistance $R(t)$, which may be zero for “large” periods of time. During such intervals, it is clear that passive element R becomes lossless, i.e., energy dissipation is lost. At intervals over which $R = 0$ becomes larger, energy

is stored “longer” in the capacitor element. For energy to be dissipated (on average), it seems reasonable to impose a maximum interval length over which $R \approx 0$ or, in other words, that $R(t)$ has a strictly positive *minimum* “average” value. This idea, which is formally captured in the property of persistency of excitation, is our main steering intuition to show that the controlled synchronization of two Lü chaotic oscillators may be achieved with *one linear time-varying* control input. This is our main contribution with respect to existing literature.

The remainder of this brief consists of the main results (cf. Section II), and stability proofs are given in Section III.

II. MAIN RESULTS

A. Problem Formulation

The Lü chaotic system is given by (cf. [9])

$$\dot{x}_m = \beta x_m - y_m z_m + c \quad (1a)$$

$$\dot{y}_m = -a y_m + x_m z_m \quad (1b)$$

$$\dot{z}_m = -b z_m + x_m y_m. \quad (1c)$$

Unless otherwise specified, it is conventionally assumed that the constant parameters β , a , and b are strictly positive and that $c \in \mathbb{R}$. We assume that system (1) freely “moves” about, so it is called the master system. The synchronization problem is to design a controller (u_1, u_2, u_3) such that the trajectories of the slave system

$$\dot{x}_s = \beta x_s - y_s z_s + c + u_1 \quad (2a)$$

$$\dot{y}_s = -a y_s + x_s z_s + u_2 \quad (2b)$$

$$\dot{z}_s = -b z_s + x_s y_s + u_3 \quad (2c)$$

asymptotically follow those of the master, i.e., it is desired that

$$\begin{aligned} \lim_{t \rightarrow \infty} |x_s - x_m| &= 0 \\ \lim_{t \rightarrow \infty} |y_s - y_m| &= 0 \\ \lim_{t \rightarrow \infty} |z_s - z_m| &= 0. \end{aligned} \quad (3)$$

This problem was solved via Lyapunov-based nonlinear control in [10] and [11]. In the latter, it is shown that two control inputs are enough to produce synchronization: In particular, the authors propose two controllers that exponentially synchronize the systems with either $u_2 = 0$ or $u_3 = 0$. Control input u_1 is used in both references to compensate for the term βx_s , $\beta > 0$, which induces instability. In the case where y_s and z_s are different from zero, a term of undefined sign is added to (2a); hence, the latter may be regarded as an unstable system with a nonvanishing disturbance (cf. [7]), which is expected to be unstable. Both [10] and [11] rely on canceling unstable terms; however, canceling unstable “poles” is, in general, undesirable due to parametric uncertainty. In this brief, it is shown that

Manuscript received November 16, 2008; revised March 17, 2009. First published July 14, 2009; current version published August 14, 2009. This paper was recommended by Associate Editor B. Jean-Pierre.

The author is with the Centre National de la Recherche Scientifique, Laboratoire des Signaux et Systèmes, 91192 Gif sur Yvette, France (e-mail: loria@lss.supelec.fr).

Color versions of one or more of the figures in this paper are available online at <http://ieeexplore.ieee.org>.

Digital Object Identifier 10.1109/TCSII.2009.2025624

¹With the current through the resistor as input and the capacitor voltage as output.

the systems may be synchronized with $u_1 = 0$ for appropriate choices of u_2 or u_3 . That is, it is shown that synchronization can be achieved with one control input: hence, either $u_1 = u_2 = 0$ or $u_1 = u_3 = 0$. Moreover, the controller is designed by exploiting and not dismantling the system's natural structure.

To put the main results into perspective, the synchronization error dynamics is first written. To that end, define

$$e_1 := x_s - x_m \quad e_2 := y_s - y_m \quad e_3 := z_s - z_m. \quad (4)$$

Then, subtracting (1) from (2), we obtain

$$\dot{e}_1 = \beta e_1 - y_s e_3 - z_m e_2 + u_1 \quad (5a)$$

$$\dot{e}_2 = -a e_2 + z_m e_1 + x_s e_3 + u_2 \quad (5b)$$

$$\dot{e}_3 = -b e_3 + x_s e_2 + e_1 y_m + u_3. \quad (5c)$$

The synchronization problem is solved if and only if it is ensured that $\lim_{t \rightarrow \infty} e_i(t) = 0$ for all i . Beyond a mere convergence property, one may seek the stronger property of asymptotic stability of $e = 0$.² A yet stronger property is *exponential* stability, which is proven in [10] and [11] using Lyapunov's direct method and *at least* two control inputs including u_1 .

B. Solution

Set $u_1 \equiv 0$. We start by posing some evidently abusive assumptions with the sole purpose of illustrating the idea of our control approach; formal statements are made later.

Step 1) In order to circumvent the inherent instability of (5a) with $u_1 \equiv 0$, either e_2 or e_3 is regarded as a virtual control input. For instance, with e_3 being a control input (the same reasoning is valid for e_2), let $e_3 := k_2 y_s e_1$, where k_2 is a control gain, and let $e_2 = 0$. Then, (5a) reads

$$\dot{e}_1 = \beta e_1 - k_2 y_s(t)^2 e_1. \quad (6)$$

The term $-k_2 y_s^2$ is nonpositive; hence, $-k_2 y_s^2 e_1$ is considered to be a stabilizing term used to compensate for the destabilizing term βe_1 with $\beta > 0$. For instance, it is clear that if y_s is constant, it suffices to pick $k_2 > \beta/y_s^2$ to make the origin $e_1 = 0$ of (6) exponentially stable. Yet, in the context of chaotic systems, it certainly does not make sense to assume that y_s is constant; moreover, most typically, $y_s(t) = 0$ for certain values of t since it corresponds to the trajectory of the slave system. For those instances, infinite gain is seemingly needed. However, it reasonably may be assumed that the set of times t such that $y_s(t) = 0$ are isolated points or, at least, that $y_s(t) \neq 0$ for intervals of time of a minimal length. Then, it is said that y_s has the property of *persistence of excitation*, which is comparable to an "average value" and is mathematically written as follows (cf. [1] and [8]):

Definition 1: The locally integrable function $\varphi : \mathbb{R}_{\geq 0} \rightarrow \mathbb{R}$ is said to be persistently exciting (PE) if there exist positive numbers μ and Δ such that

$$\int_t^{t+\Delta} \varphi(s)^2 ds \geq \mu > 0 \quad \forall t \geq 0. \quad (7)$$

²Convergence and asymptotic stability are different properties that are sometimes mistakenly taken for synonyms (cf. [7]).

Fig. 1. (a) Graph of (top) $\varphi(t)^2 - 0.5$ and (bottom) corresponding $x(t)$. (b) Graph of (top) $\varphi(t)^2 - 0.25$ and (bottom) corresponding $x(t)$.

It has been well known for many years (cf. [1]) that the origin of $\dot{x} = -\varphi(t)^2 x$ is exponentially stable if and only if $\varphi(t)$ is PE.³ The rationale of this statement may be understood with the following example: Let $\varphi(t) = 0$ for all $t \in (2i, 2i + 2]$, with $i > 0$ being odd, and $\varphi(t) = 1$ for all $t \in (2i, 2i + 2]$, with i being even. Then, $\dot{x}(t) = -x(t)$ on intervals where i is even and $x(t)$ exponentially decays, whereas $x(t) = \text{const}$ on intervals for odd values of i . See that $x(t)$ exponentially decays as $t \rightarrow \infty$. Consider now the system $\dot{x} = -[\varphi(t)^2 - \beta]x$ with $\beta > 0$. Provided that $\beta < 1$, over the intervals where $\varphi(t)^2 > \beta$, solution $x(t)$ decays exponentially fast with rate $1 - \beta$; during the complementary intervals, $|x(t)|$ exponentially increases with a rate equal to β . Graphically (cf. Fig. 1), one can see that the system's trajectories exponentially decay to zero if $\beta < 0.5$.

The previous example may be put in the context of the RC circuit previously evoked by considering $\varphi(t)^2$ as the value of the variable resistance and β as a constant supply that keeps the circuit from dissipating energy, so that the capacitor does not discharge. Note that, for simplicity, the "operating point" is zero, but this is assumed without loss of generality. We formalize the previous reasoning in the following technical lemma:

Lemma 1: Consider the system

$$\dot{x} = -\varphi(t)x, \quad \varphi(t) := [a(t) - b], \quad x \in \mathbb{R} \quad (8)$$

where $a(t) \geq 0$ is globally Lipschitz and bounded; $b > 0$; and there exist positive numbers μ_m , μ_M , and Δ such that

$$\mu_m \geq \int_t^{t+\Delta} \varphi(s) ds \geq \mu_m > 0 \quad \forall t \geq 0. \quad (9)$$

Then, the origin of (8) is exponentially stable for suitable values of μ_m , Δ , and b .

The proof is included in Section III. Roughly, as it may be inferred from the previous discussion and Fig. 1, it is required that μ_m and Δ be sufficiently large; this implicitly requires that $a(t)$ be sufficiently PE and b be "relatively small."

Note that (6) is of the form (8), with $x = e_1$, $a(t) := k_2 y_s(t)^2$, and $b = \beta$. From Lemma 1, it readily follows that, if y_s is PE (which holds if the slave system has a chaotic behavior), k_2 is sufficiently large, and β is "small," the origin of (6) is globally exponentially stable.

Step 2) The previous arguments rely on the assumption that $e_3 = k_2 y_s(t) e_1$. Hence, a controller that asymptotically makes $e_3 \rightarrow k_2 y_s(t) e_1$ must be designed under

³If, in addition, φ is bounded and globally Lipschitz.

the restriction of using only *one* control input. Consider (first) $u_2 \equiv 0$ and

$$u_3 = -ke_3 + k_2 y_s(t) e_1, \quad k, k_2 > 0. \quad (10)$$

The choice of u_3 is motivated by the observation that, with $e_2 \equiv e_1 \equiv 0$, the e_3 dynamics has the form

$$e_3(t) = \frac{1}{p + [k + b]} k_2 y_s(t) e_1(t) \quad p := \frac{d}{dt} \quad (11)$$

i.e., the e_3 dynamics may be regarded as a low-pass filter with cutting frequency at $k + b$. In other words, for sufficiently large k , the “input” $k_2 y_s(t) e_1(t)$ is recovered at the filter’s output, up to a gain.

Step 3) In summary, the closed-loop system is

$$\begin{bmatrix} \dot{e}_1 \\ \dot{e}_2 \end{bmatrix} = \begin{bmatrix} -[k_2 y_s^2 - \beta] & -z_m \\ z_m & -a \end{bmatrix} \begin{bmatrix} e_1 \\ e_2 \end{bmatrix} + \begin{bmatrix} -y_s \\ x_s \end{bmatrix} e_3 \quad (12a)$$

$$e_3(t) = \frac{1}{p + [k + b]} k_2 y_s(t) e_1(t) + [y_m \quad x_s] \begin{bmatrix} e_1 \\ e_2 \end{bmatrix}. \quad (12b)$$

Roughly speaking, the system in (12a) is seen as a stable system with input e_3 , whereas the “filter” system (12b) is also a stable system with additive “perturbation” $[e_1 \ e_2]^T$. A *small-gain* argument (cf. [3]) suffices to ensure the stability of the interconnected system; roughly, it is required that the respective terms multiplying the inputs are not too “large” relative to the stabilizing terms of the “nominal” systems. These intuitive arguments are recovered in Proposition 1; the proof is presented in Section III.

Proposition 1: Consider system (5) in closed loop with $u_2 \equiv 0$ and u_3 , as in (10). Then, for sufficiently large gains k and k_2 , the origin of the closed-loop system is globally exponentially stable if $y_s(t)$ is PE with sufficiently large μ_m and Δ .

Following the same train of thought that leads to Proposition 1, let us now explore the case when $u_3 \equiv 0$ and use u_2 as control input. In this case, e_2 in (5a) is seen as the virtual control input: If $e_3 = 0$ and $e_2 = k_4 z_m e_1$, with $k_4 > 0$, (5a) reads

$$\dot{e}_1 = -[k_4 z_m(t)^2 - \beta] e_1 \quad (13)$$

which is of the form (8); hence, by Lemma 1, the origin $e_1 = 0$ of (13) is exponentially stable for an appropriate choice of k_4 and PE $z_m(t)$ with sufficiently large μ_m and Δ . With this in mind, define

$$u_2 = -k_4 e_2 - 2x_s e_3 + k_2 z_m(t) e_1, \quad k_2, k_4 > 0. \quad (14)$$

Thus, the closed-loop equation of (5b) with (13) becomes

$$\dot{e}_2 = -[a + k_4] e_2 + [k_2 + 1] z_m(t) e_1 - x_s e_3. \quad (15)$$

Disregarding the term $-x_s e_3$, (15) may be rewritten as a low-pass filter with input $[k_2 + 1] z_m e_1$ and cutting frequency at $a + k_4$, which may be set at will, i.e.,

$$e_2(t) = \frac{1}{p + [a + k_4]} [k_2 + 1] z_m(t) e_1(t), \quad p := \frac{d}{dt}. \quad (16)$$

Proposition 2: Consider system (5) in closed loop with $u_3 \equiv 0$ and u_2 , as in (14). Then, for sufficiently large k_2 and k_4 , the origin of the closed-loop system is globally exponentially stable if $z_m(t)$ is PE with sufficiently large μ_m and Δ .

Fig. 2. Graphs of error trajectories $e(t)$ using control u_3 given by (10).

Fig. 3. Graph of the numerical approximation of $F(t) := \int_t^{t+\Delta} [y_s(s)^2 - \beta] ds$ for $t \in [0, 100 - \Delta]$ under control u_3 ; $\Delta = 4s$ and $\hat{\mu}_m := \min_{t \in [0, 100 - \Delta]} \{F(t)\} = 10.4393$.

It is worth emphasizing that controller u_2 uses full master state feedback, whereas controller u_3 uses partial-state or output feedback (measurement of z_m and x_m only).

C. Simulations

We have tested the performance of controllers (10) and (14) in simulations using SIMULINK or MATLAB. The simulation is run for 100 s using a third-order approximation algorithm and an integration step of $1e^{-4}$. The initial conditions are

$$\begin{aligned} x_s(0) &= 5 & y_s(0) &= -5 & z_s(0) &= 1 \\ x_m(0) &= 3 & y_m(0) &= -20 & z_m(0) &= 2 \end{aligned}$$

and the parameters are selected, so that the systems describe a chaotic behavior: $a = -10$, $b = -4$, $c = 0$, and $\beta = 2.8571$. For the controller (10), the gains are set to $k = 200$ and $k_2 = 1$. The results are shown in Figs. 2 and 3.

In the former, the synchronization errors exponentially tending to zero are shown; in the latter, the numerical integration of $[y_s(s)^2 - \beta]$ is depicted. Note that the PE condition may be verified only numerically since it must be verified for all $t \geq 0$: Let $\{\bar{y}_s(t_j)\}$ be an ordered array of points such that $\bar{y}_s(t_j) = y(t)$ for all $t \in [0, 100]$ such that $t = t_j \in \{0, 1e^{-4}, 2e^{-4}, \dots, 100\}$, i.e., $\{\bar{y}_s(t_j)\}$ is the array of points generated by the numerical integration routine with a step of 0.1 ms. To lighten the computational burden, let

$$F(t) := \int_t^{t+4} [y_s(\tau)^2 - \beta] d\tau \quad \forall t \in [0, 100]$$

by $F(t_k)$, where $\{t_k\} := \{0, 0.1, 0.2, \dots, 96\}$

$$F(t_k) := \sum_{t_j=10^4 t_k}^{(t_k+4)10^4} [\bar{y}_s(t_j)^2 - \beta], \quad k \in \{1, 2, \dots, 9600\}; \quad t_j \in \mathbb{Z} \quad (17)$$

Fig. 4. Graphs of error trajectories $e(t)$ using control u_2 given by (14). Fig. 5. Graph of the numerical approximation of $F(t) := \int_t^{t+\Delta} [z_m(s)^2 - \beta] ds$ for $t \in [0, 100 - \Delta]$ under control u_2 ; $\Delta = 4s$ and $\hat{\mu}_m := \min_{t \in [0, 100 - \Delta]} \{F(t)\} = 19.60618$.

i.e., define a subsequence of 9600 points $\{t_k\}$ from the sequence $\{t_j\}$, $j \in \mathbb{Z}_{\geq 0}$, $j \leq 10^6$, generated via the integration routine. This comes to computing 9600 sums of 4×10^4 terms each, as opposed to $1e^6$ at the expense of resolution but not of accuracy. The minimal value of $F(t_k)$ gives an estimate of the PE bound μ_m ; in this particular example, it is $\hat{\mu}_m = 10.439$ (see Fig. 3).

In a second run of simulations, the controller u_2 defined in (14) was tested under similar conditions. The results are shown in Figs. 4 and 5. As for the previous case, error trajectories $e_i(t)$ (cf. Fig. 4) and the graph of $F(t_k)$, defined in (17) albeit replacing y_s with z_m , are shown. In Fig. 4, the 3-D attractor for the slave system is shown.

Note that, in both Figs. 2 and 4, the short transients are comparable to those under nonlinear cancellation control with two inputs (cf. [11]) and with three inputs (cf. [10]).

III. PROOFS

Proof of Lemma 1: Let $\varphi_M > 0$ be such that $|\varphi(t)| \leq \varphi_M$ for all t , and define

$$V_1(x) = \left(\frac{1}{2} + \varphi_M\right) x^2 \quad V_2(t, x) := -\int_t^\infty \varphi(\tau) x^2 e^{t-\tau} d\tau. \quad (18)$$

(Note that V_2 is reminiscent of a convolution integral.) Hence

$$V_2(t, x) \leq -\int_t^{t+\Delta} \varphi(\tau) x^2 e^\Delta d\tau \leq -\mu_m e^\Delta x^2.$$

We also remark that

$$\int_t^\infty \varphi(\tau) e^{t-\tau} d\tau \leq \varphi_M \int_t^\infty e^{t-\tau} d\tau = \varphi_M.$$

Thus, $V_2 \geq -\varphi_M x^2$, and $V_1 + V_2$ is positive definite. Now, evaluating the total time derivative of V_1 along the trajectories

of (8) yields $\dot{V}_1 = -[2\varphi_M + 1]\varphi(t)x^2$, whereas the time derivative of V_2 satisfies

$$\dot{V}_2 = \varphi(t)x^2 + \int_t^\infty 2x^2 \varphi(\tau) \varphi(t) e^{t-\tau} d\tau + V_2. \quad (19)$$

Using $|\varphi(t)| \leq \varphi_M$, it is concluded that the integral term in (19) is bounded by $2|V_2|\varphi_M$, so $\dot{V}_1 + \dot{V}_2 \leq -2\varphi_M \varphi(t)x^2 + 2|V_2|\varphi_M - \mu_m e^\Delta x^2$; therefore, using $|V_2| \leq \varphi_M x^2$ yields

$$\dot{V}_1 + \dot{V}_2 \leq -[\mu_m e^\Delta - 4\varphi_M^2] x^2$$

which is negative definite if $\mu_m e^\Delta \geq 4\varphi_M^2$, which holds for sufficiently large μ_m and Δ . (Note, however, that this is a conservative bound.) Lastly, it is verified that, on the one hand, $|\varphi(\tau)| \leq \varphi_M$ and, on the other hand, (9) must hold by assumption. Hence, it is required that

$$\mu_m \leq \int_t^{t+\Delta} \varphi(\tau) d\tau \leq \varphi_M \Delta$$

which holds only if $\mu_m \leq \varphi_M \Delta$. The latter holds for sufficiently large Δ .

Proof of Proposition 1: Define $e_{3d} := k_2 y_s e_1$ and $\tilde{e}_3 := e_3 - e_{3d}$. Then, the closed-loop equations (5), with $u_1 = u_2 = 0$, and (10) are

$$\dot{e}_1 = -[k_2 y_s(t)^2 - \beta] e_1 - z_m e_2 - y_s \tilde{e}_3 \quad (20a)$$

$$\dot{e}_2 = -a e_2 + z_m e_1 + x_s e_3 \quad (20b)$$

$$\dot{e}_3 = -[k + b] e_3 + x_s e_2 + [y_m + k_2 y_s] e_1. \quad (20c)$$

Next, a dynamic equation for $\tilde{e}_3$ is derived, i.e.,

$$\begin{aligned} \dot{\tilde{e}}_3 &= -(k + b)(\tilde{e}_3 + e_{3d}) + [y_m \ x_s] \begin{bmatrix} e_1 \\ e_2 \end{bmatrix} + k_2 y_s e_1 \\ &\quad - k_2 \dot{y}_s e_1 - k_2 y_s [- (k_2 y_s^2 - \beta) e_1 - z_m e_2 - y_s \tilde{e}_3] \\ &= -[k + b] \tilde{e}_3 - [k + b] e_{3d} + y_m e_1 + x_s e_2 + k_2 y_s e_1 \\ &\quad - k_2 \dot{y}_s e_1 + k_2 y_s [k_2 y_s^2 - \beta] e_1 + k_2 z_m y_s e_2 + k_2 y_s^2 \tilde{e}_3. \end{aligned}$$

Using $e_{3d} = k_2 y_s e_1$ and regrouping terms yield

$$\begin{aligned} \dot{\tilde{e}}_3 &= -[k + b] \tilde{e}_3 + e_1 [y_m + k_2 y_s - k_2 \dot{y}_s - k_2(k + b) y_s] \\ &\quad + e_{3d} [k_2 y_s^2 - \beta] + e_2 [x_s + z_m y_s] + y_s^2 \tilde{e}_3. \end{aligned}$$

Using $e_{3d} = e_3 - \tilde{e}_3$ results in

$$\begin{aligned} \dot{\tilde{e}}_3 &= -[k + b - \beta] \tilde{e}_3 + e_3 [k_2 y_s^2 - \beta] + e_2 [x_s + y_s z_m] \\ &\quad + e_1 [y_m - k_2(k + b) y_s + k_2 y_s - k_2 \dot{y}_s]. \end{aligned} \quad (21)$$

Define $\Psi(t)^\top := [\psi_1(t) \ \psi_2(t) \ \psi_3(t)]$, with $\psi_1(t) := y_m(t) + k_2[y_s(1 - k + b) - \dot{y}_s]$, $\psi_2(t) := x_s(t) + y_s(t)z_m(t)$, and $\psi_3(t) := k_2 y_s(t)^2 - \beta$. Then

$$\dot{\tilde{e}}_3 = -(k + b - \beta) \tilde{e}_3 + \Psi(t)^\top e, \quad e^\top := [e_1 \ e_2 \ e_3]. \quad (22)$$

Let $e_{12}^\top := [e_1 \ e_2]$ and $V_{12}(t, e_{12}) := V_1(e_1) + V_2(t, e_1) + 0.5e_2^2$, where V_1 and V_2 are defined in (18) and $V_3 := 0.5e_3^2$. Following the proof of Lemma 1 leads to

$$\begin{aligned} \dot{V}_{12} + \dot{V}_3 &\leq -[\mu_m e^\Delta - 4\varphi_M^2] e_1^2 - a e_2^2 - [k + b] e_3^2 + 2e_2 e_3 x_s \\ &\quad + [y_m + k_2 y_s] e_1 e_3 + [4\varphi_M + 1] |y_s| |\tilde{e}_3| |e_1| \\ &\quad + 4\varphi_M |e_1| |e_2| |z_m| \end{aligned}$$

where the equality

$$\frac{\partial V_{12}}{\partial e_1} = \left[2\varphi_M + 1 - 2 \int_t^\infty \varphi(\tau) e^{t-\tau} d\tau \right] e_1 \leq [4\varphi_M + 1] |e_1|$$

was used. Define $\tilde{V}_3 := 0.5\tilde{e}_3^2$. Then,

$$\dot{\tilde{V}}_3 = -[k + b - \beta]\tilde{e}_3^2 + \Psi(t)^\top e \tilde{e}_3.$$

Finally, define $\kappa := [4\varphi_M + 1]|y_s|$ and $\mathcal{V} := \gamma V_{12} + V_3 + \tilde{V}_3$, with $\gamma \propto (k + b)$; its total time derivative satisfies

$$2\dot{\mathcal{V}} \leq [e^\top \tilde{e}_3]^\top D \begin{bmatrix} e \\ \tilde{e}_3 \end{bmatrix} - \gamma [\mu_m e^\Delta - 4\varphi_M^2] e_1^2 - a\gamma e_2^2 - [k + b] e_3^2$$

$$D := \begin{bmatrix} -\gamma(\mu_m e^\Delta - 4\varphi_M^2) & 4\gamma\varphi_M|z_m| & (y_m + k_2 y_s) & \gamma\kappa + \psi_1 \\ 4\gamma\varphi_M|z_m| & -a\gamma & x_s & \psi_2 \\ (y_m + k_2 y_s) & x_s & -[k + b] & \psi_3 \\ \gamma\kappa + \psi_1 & \psi_2 & \psi_3 & -[k + b - \beta] \end{bmatrix}.$$

Since the off-diagonal elements of matrix D are bounded,⁴ D may be made negative definite for sufficiently large values of design parameters μ_m , Δ , k , and k_2 , so $\dot{\mathcal{V}}$ is negative definite. ♦♦♦

Proof of Proposition 2: The proof follows similar guidelines. In this case, with $\tilde{e}_2 = e_2 - e_{2d}$ and $e_{2d} = k_2 z_m e_1$, the closed-loop equations (5) with (14) and $u_3 = 0$ yield

$$\dot{e}_1 = -[k_2 z_m(t)^2 - \beta] e_1 - z_m \tilde{e}_2 - y_s e_3 \quad (23a)$$

$$\dot{e}_2 = -[k_4 + a] e_2 + z_m(k_2 + 1) e_1 - x_s e_3 \quad (23b)$$

$$\dot{e}_3 = -b e_3 + x_s e_2 + e_1 y_m. \quad (23c)$$

Following somewhat lengthy but direct computations, as to obtain $\dot{\tilde{e}}_3$ in the proof of Proposition 1 leads to

$$\dot{\tilde{e}}_2 = -[k_4 + a - \beta]\tilde{e}_2 - [x_s - k_2 z_m y_s] e_3 + (k_2 z_m^2 - \beta) e_2 - [(k_4 + a)k_2 z_m - (k_2 + 1)z_m + \dot{z}_m] e_1.$$

Define $e_{12}^\top := [e_1 \ e_2]$, and consider function $V_{12}(t, e_1) := V_1(e_1) + V_2(t, e_1)$. Let z_m be (sufficiently) PE, so that $(k_2 z_m^2 - \beta)$ is also PE⁵ with μ_m and Δ . The total time derivative using (23a) satisfies

$$\dot{V}_{12} \leq -[\mu_m e^\Delta - 4\varphi_M^2] e_1^2 + [6\varphi_m + 1] (|e_3 y_s| + |z_m \tilde{e}_2|) |e_1|.$$

Next, define $V_{23}(e_{23}) := 0.5|e_{23}|^2$. We have

$$\dot{V}(e_{23}) \leq -(k_4 + a) e_2^2 - b e_3^2 + |e_1| (|z_m| |e_2| + |y_m| |e_3|).$$

Collecting terms yields

$$\dot{V}_{12} + \dot{V}_{23} \leq \frac{1}{2} \begin{bmatrix} |e_1| \\ |e_2| \\ |e_3| \end{bmatrix}^\top M_\lambda \begin{bmatrix} |e_1| \\ |e_2| \\ |e_3| \end{bmatrix} + (6\varphi_m + 1) |z_m| |e_1| |\tilde{e}_2|$$

$$M_\lambda := \begin{bmatrix} -\lambda(\mu_m e^\Delta - 4\varphi_M^2) & |z_m| & |y_m| + |y_s|(6\varphi_m + 1) \\ |z_m| & -(k_4 + a) & 0 \\ |y_m| + |y_s|(6\varphi_m + 1) & 0 & -b \end{bmatrix}$$

with $\lambda \in (0, 1]$. Matrix M_λ is negative definite if

$$\lambda(\mu_m e^\Delta - 4\varphi_M^2)(k_4 + a)b > (k_4 + a)(6\varphi_m + 1)^2 + z_m^2 y_m^2 b$$

⁴This may be shown under the assumption that the slave system operates in the chaotic regime, in *open loop*.

⁵Correspondingly, it is required that β is relatively small, i.e., that a PE signal remains PE under the addition of a small constant is a well-known property of PE functions.

which holds for sufficiently large μ_m and Δ for any fixed λ . Let $\lambda \in (0, 1)$, $\lambda \approx 1$, $c := \lambda_{\min}(M_\lambda)$ (the smallest eigenvalue of M_λ) and $\gamma > 0$. Define $\mathcal{V}(e, \tilde{e}) := V_{12}(e_1) + V_{23}(e_{23}) + 0.5\gamma\tilde{e}_2^2$ and $\Psi := [\psi_1 \ \psi_2 \ \psi_3]^\top$, with $\psi_1 := -[(k_4 + a)k_2 z_m - z_m + \dot{z}_m]$, $\psi_2 := (k_2 z_m^2 - \beta)$, and $\psi_3 := -[x_s - k_2 z_m y_s]$. Then

$$2\dot{\mathcal{V}} \leq -c|e|^2 - [k_4 + a - \beta]\gamma\tilde{e}_2^2$$

$$- \begin{bmatrix} |e| \\ \tilde{e}_2 \end{bmatrix}^\top \begin{bmatrix} c & \gamma|\Psi| \\ \gamma|\Psi| & \frac{1}{2}\gamma[k_4 + a - \beta] \end{bmatrix} \begin{bmatrix} |e| \\ \tilde{e}_2 \end{bmatrix}$$

$$- \begin{bmatrix} e_1 \\ \tilde{e}_2 \end{bmatrix}^\top \begin{bmatrix} (1-\lambda)(\mu_m e^\Delta - 4\varphi_M^2) & (6\varphi_m + 1)|z_m| \\ (6\varphi_m + 1)|z_m| & \frac{1}{2}\gamma[k_4 + a - \beta] \end{bmatrix} \begin{bmatrix} e_1 \\ \tilde{e}_2 \end{bmatrix}$$

$$\times \begin{bmatrix} e_1 \\ \tilde{e}_2 \end{bmatrix}.$$

The last two terms on the right-hand side of the preceding expression are nonpositive if

$$[k_4 + a - \beta]c \geq 2\gamma|\Psi|^2$$

$$[k_4 + a - \beta]\gamma(1 - \lambda)(\mu_m e^\Delta - 4\varphi_M^2) \geq (6\varphi_m + 1)^2 z_m^2.$$

Both inequalities are satisfied for sufficiently small γ and sufficiently large k_4 , a , μ_m , and Δ .

We conclude that $\mathcal{V}$ is negative definite. Moreover, since $\mathcal{V}$ satisfies lower and upper quadratic bounds of the norm of $[e \ \tilde{e}_2]$, global exponential stability follows. ♦♦♦

IV. CONCLUSION

We have shown that master-slave synchronization of Lü chaotic oscillators is achievable with *one* control input. Moreover, our control laws are linear time varying. Further research is targeted at solving the problem under parameter uncertainty, i.e., using adaptive control.

REFERENCES

- [1] B. O. Anderson, "Exponential stability of linear equations arising in adaptive identification," *IEEE Trans. Autom. Control*, vol. AC-22, no. 1, pp. 83–88, Feb. 1977.
- [2] E. Cherrier, M. Boutayeb, and J. Ragot, "Observers-based synchronization and input recovery for a class of nonlinear chaotic models," *IEEE Trans. Circuits Syst. I, Reg. Papers*, vol. 53, no. 9, pp. 1977–1988, Sep. 2006.
- [3] G. Escobar, M. Hernández-Gómez, and P. R. Martínez-Montejano, "A repetitive-based controller for a power factor precompensator," *IEEE Trans. Circuits Syst. I, Reg. Papers*, vol. 54, no. 9, pp. 1968–1976, Sep. 2007.
- [4] M. L'Hernault, J.-P. Barbot, and A. Ouslimani, "Feasibility of analog realization of a sliding-mode observer: Application to data transmission," *IEEE Trans. Circuits Syst. I, Reg. Papers*, vol. 55, no. 2, pp. 614–624, Mar. 2008.
- [5] G.-P. Jiang, W. X. Zheng, W. K.-S. Tang, and G. Chen, "Integral-observer-based chaos synchronization," *IEEE Trans. Circuits Syst. II, Exp. Briefs*, vol. 53, no. 2, pp. 110–114, Feb. 2006.
- [6] K. Kemih and M. Benslama, "Synchronized chaotic Lü system in CDMA satellite communication using genetic algorithm," in *Proc. ICDT*, 2006, pp. 33–37.
- [7] H. Khalil, *Nonlinear Systems*, 3rd ed. New York: Prentice-Hall, 2002.
- [8] A. Loría and A. Zavala, "Adaptive tracking control of chaotic systems with applications to synchronization," *IEEE Trans. Circuits Syst. I, Reg. Papers*, vol. 54, no. 9, pp. 2019–2029, Sep. 2007.
- [9] J. Lü, G. Chen, and D. Cheng, "A new chaotic system and beyond: The generalized Lorenz-like system," *Int. J. Bifurc. Chaos*, vol. 14, no. 5, pp. 1507–1537, May 2004.
- [10] J. H. Park, "Chaos synchronization of a chaotic system via nonlinear control," *Chaos Solitons Fractals*, vol. 25, no. 3, pp. 579–584, Aug. 2005.
- [11] Q. Zhang and J. Lu, "Chaos synchronization of a new chaotic system via nonlinear control," *Chaos Solitons Fractals*, vol. 37, no. 1, pp. 175–179, Jul. 2008.