Human-Robot Interaction in the MORSE Simulator

Séverin Lemaignan, Gilberto Echeverria, Michael Karg, Jim Mainprice,
Alexandra Kirsch, Rachid Alami

► To cite this version:

Séverin Lemaignan, Gilberto Echeverria, Michael Karg, Jim Mainprice, Alexandra Kirsch, et al..
Human-Robot Interaction in the MORSE Simulator. Human-Robot Interaction Conference (HRI
2012), Mar 2012, Boston, United States. 2p. hal-00667026

HAL Id: hal-00667026

<https://hal.science/hal-00667026>

Submitted on 6 Feb 2012

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Human-Robot Interaction in the MORSE Simulator

Séverin Lemaignan^{1,2,3}, Gilberto Echeverría^{1,2}, Michael Karg³
Jim Mainprice^{1,2}, Alexandra Kirsch³, Rachid Alami^{1,2}

{slemaign, gechever, jmainpri, rachid}@laas.fr, {kargm, kirsch}@in.tum.de

¹CNRS-LAAS ; 7 avenue du colonel Roche, F-31077 Toulouse, France

²Université de Toulouse; UPS, INSA, INP, ISAE ; LAAS ; F-31077 Toulouse, France

³IAS; Technical University of Munich ; Karlstr. 45 ; D-80333 Munich, Germany

ABSTRACT

Over the last two years, the Modular OpenRobots Simulation Engine (MORSE) project¹ went from a simple extension plugged on the Blender's *Game Engine* to a full-fledged simulation environment for academic robotics. Driven by the requirements of several of its developers, tools dedicated to Human-Robot interaction simulation have taken a prominent place in the project. This late breaking report discusses some of the recent additions in this domain, including the immersive experience provided by the integration of the Kinect device as input controller. We also give an overview of the experiences we plan to complete in the coming months.

Categories and Subject Descriptors

I.2.9 [Computing Methodologies]: Artificial Intelligence—Robotics

General Terms

Experimentation, Human Factor

Keywords

Simulation, Human-Robot Interaction

1. THE MORSE SIMULATOR

The Modular OpenRobots Simulation Engine (MORSE) [2] is a open-source tool developed for robotics research. It is a domain independent simulator, where virtual robots can interact with a 3D environment, using sensors and actuators that behave in the same way as their counterparts in the real world. MORSE relies on the advanced 3D (OpenGL shaders) and physics simulation (BULLET physics engine) capabilities of the Blender *Game Engine*, a real-time 3D runtime integrated to the open-source Blender modeling toolkit. This allows for semi-realistic simulation of complex environments.

The MORSE components (sensors and actuators) exchange data with the robotics software via middleware bindings, using a *Software In The Loop* (SAIL) architecture. Middleware supported in the current version include ROS and

¹<http://morse.openrobots.org>

Figure 1: The experimental setup with the human avatar controlled from a Kinect.

YARP, as well as a socket-based raw protocol. This design allows in principle to use the same software in both the real robots and the simulator. Instructions given to the robot are interpreted in the simulator to provide the control of actuators, such as the motion of the robot and its arms. The data from simulated sensors is sent back through the middlewares, *e.g.* exporting the images from cameras, or the positions of the robot, human and other objects of interest.

MORSE provides support for several classes of robots *out of the box*, and allows for easy customization of those, either by composing individual sensors and actuators with empty robot structures directly in the MORSE interface, or through a Python-based script language that permits to conveniently describe robots and simulation scenarii.

Other experiments using simulation have been carried to gather data for HRI [1]. However, these do not involve the actual robot software, and it is another human who takes the role of the robot.

2. HRI SPECIFIC FEATURES

A new *human avatar* has been recently added to the MORSE assets. It provides a first-person immersive experience: when started, one can take the role of the human and control it via the keyboard, a WiiMote or, as another recent addition to the simulator, through a Kinect device (Fig. 1).

When in first-person mode, the user can interact in several ways with the environment. He/she can pick and release objects, can open drawers and cupboards. As any other object,

Figure 2: Example of integration in a software architecture: MORSE transparently replaces the real robot.

the avatar physically interacts (collision detection) with the surrounding furnitures. MORSE exports the position and posture of the avatar as a global joint state to be used by the real software components of the robot.

MORSE also offers a special sensor that exports abstracted informations of objects visible to the robot (called the *semantic camera*). This sensor typically exports the name, type (glass, table, bottle, etc.), color and location of objects. Since human-robot interaction often involves semantic-rich environments, this abstract sensor simplifies the experiments on such scenarii, by avoiding the added complexity of processing camera images to detect the objects of interest and exploiting the inherent knowledge of the simulated world.

3. CURRENT AND FUTURE EXPERIMENTS

Due to its nature, MORSE offers two main advantages compared to experiments on a real robot: light-weight deployment and repeatability. MORSE is already used for human-robot interaction in two laboratories, at the LAAS-CNRS, Toulouse, France, and at the Technical University of Munich, Germany.

Integration in the LAAS cognitive architecture: Figure 2 presents the current integration of MORSE in the LAAS' software architecture. In particular, both the human posture and the object features are integrated with SPARK [5], a module dedicated to geometric and temporal reasoning. This module is a key component providing a base of facts such as objects' relative placements, visibility and reachability by the agents present in the scene. It additionally provides a stable state of the world to the motion planners.

Human-Aware Motion Planning: The human avatar is being used to evaluate human-aware navigation planners at Munich TU. It enables developers to find and avoid errors before running on real robots. A simulated human tracker updates the position of the human and passes it to the robotic middleware. A video is available here: <http://vimeo.com/31257264>.

Interaction with Natural Language: Relying on the abstract sensors provided by MORSE, we plan to repro-

duce in simulation the results of a previous experiment [4] involving interactive verbal disambiguation. Natural language understanding relies on a dedicated language parsing and grounding module called DIALOGS, which is fed by a symbolic knowledge base build as a ontology server [3].

4. SUMMARY

We have presented the developments leading to an interactive experimental setup for Human-Robot Interaction. The development of particular functionalities of the robot architecture, especially those involving a quick response to changes in the environment induced by the human presence, will directly benefit from the HRI simulation capabilities provided by MORSE.

5. REFERENCES

- [1] S. Chernova, N. DePalma, E. Morant, and C. Breazeal. Crowdsourcing human-robot interaction: Application from virtual to physical worlds. In *20th IEEE International Symposium in Robot and Human Interactive Communication*, 2011.
- [2] G. Echeverria, N. Lassabe, A. Degroote, and S. Lemaignan. Modular openrobots simulation engine: MORSE. In *Proceedings of the IEEE ICRA*, 2011.
- [3] S. Lemaignan, R. Ros, E. A. Sisbot, R. Alami, and M. Beetz. Grounding the interaction: Anchoring situated discourse in everyday human-robot interaction. *International Journal of Social Robotics*, pages 1–19, 2011.
- [4] R. Ros, S. Lemaignan, E. A. Sisbot, R. Alami, J. Steinwender, K. Hamann, and F. Warneken. Which one? grounding the referent based on efficient human-robot interaction. In *19th IEEE International Symposium in Robot and Human Interactive Communication*, 2010.
- [5] E. Sisbot, R. Ros, and R. Alami. Situation assessment for human-robot interaction. In *20th IEEE International Symposium in Robot and Human Interactive Communication*, 2011.