



The Flasher Manager Benchmarks

Hélène Collavizza, Nguyen Le Vinh, Olivier Ponsini, Michel Rueher, Antoine Rollet

► To cite this version:

Hélène Collavizza, Nguyen Le Vinh, Olivier Ponsini, Michel Rueher, Antoine Rollet. The Flasher Manager Benchmarks. 2012. hal-00720921

HAL Id: hal-00720921

<https://hal.science/hal-00720921>

Preprint submitted on 26 Jul 2012

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

The *Flasher Manager* Benchmarks

Hélène Collavizza Le Vinh Nguyen Olivier Ponsini
Michel Rueher Antoine Rollet

Abstract

This technical report provides all the source code of the *Flasher Manager* as well as of the test programs. The *Flasher Manager* is an industrial application from a car manufacturer that is embedded as a C program in a car computer. The benchmarks are based on four safety properties specified by the *Flasher Manager* designers.

1 The *Flasher Manager* application

The *Flasher Manager* application [1] is a real time industrial application from a car manufacturer that was provided by **Geensoft / Dassault Systems**¹. The *Flasher Manager* application was designed and simulated using the *Simulink* platform. Its specification was given by Geensoft and consists of four main properties. The *Flasher Manager* is concretely embedded as a C program in a car computer. This application is challenging for software verification: its complexity comes from the size of the C function generated from the *Simulink* module and from the number of clock cycles required for verifying each property. These benchmarks have been used to compare the performances of different bounded model-checkers and solvers [1].

2 The *Flasher Manager* Benchmarks

The following files are provided:

- **f1.c**: C code of the *Flasher Manager* module (function **f1**)
- **p1.c**: C code for checking property 1
- **p2.c**: C code for checking property 2
- **p3a.c**: C code for checking property 3a
- **p3b.c**: C code for checking property 3b
- **p4.c**: C code for checking property 4

¹See <http://www.geensoft.com/en>

- `simulink1.pdf`: an overview of the *Flasher Manager Simulink* circuit
- `simulink2.pdf`: a detailed view of the *Flasher Manager Simulink* circuit

References

- [1] H. Collavizza, L. V. Nguyen, O. Ponsini, M. Rueher and A. Rollet. *Constraint-Based BMC: A Backjumping Strategy*. To appear in International Journal on Software Tools for Technology Transfer (STTT). <http://hal.archives-ouvertes.fr/hal-00635417>