Constraint scores for semi-supervised feature selection: A comparative study

Mariam Kallakech, Philippe Biela, Ludovic Macaire, Denis Hamad

► To cite this version:

Mariam Kallakech, Philippe Biela, Ludovic Macaire, Denis Hamad. Constraint scores for semi-supervised feature selection: A comparative study. Pattern Recognition Letters, 2011, 32 (5), pp.656-665. 10.1016/j.patrec.2010.12.014 . hal-00732484

HAL Id: hal-00732484

<https://hal.science/hal-00732484>

Submitted on 14 Sep 2012

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Constraint scores for semi-supervised feature selection: A comparative study

Mariam Kalakech^{a,b}, Philippe Biela^{a,b}, Ludovic Macaire^b, Denis Hamad^c

^a*Hautes Etudes d'Ingénieur, 13 rue de Toul, F-59046, Lille, France*

^b*LAGIS FRE CNRS 3303, Université de Lille 1 Nord de France, Bâtiment P2, Cité Scientifique, F-59655 Villeneuve d'Ascq, France*

^c*LISIC, ULCO, 50, rue Ferdinand Buisson, F-62228 Calais, France*

Abstract

Recent feature selection scores using pairwise constraints (must-link and cannot-link) have shown better performances than the unsupervised methods and comparable to the supervised ones. However, these scores use only the pairwise constraints and ignore the available information brought by the unlabeled data. Moreover, these constraint scores strongly depend on the given must-link and cannot-link subsets built by the user. In this paper, we address these problems and propose a new semi-supervised constraint score that uses both pairwise constraints and local properties of the unlabeled data. Experimental results show that this new score is less sensitive to the given constraints than the previous scores while providing similar performances. *Keywords:* Feature selection, Pairwise constraints, Kendall's coefficient, Constraint scores, Laplacian score, Fisher score

1. Introduction

In machine learning and pattern recognition applications, the processing of high dimensional data requires large computation time and capacity storage. Though, it leads to poor performances when the dimensionality to sample size ratio is high. To improve performances, the sample dimensionality is reduced thanks to feature extraction or selection schemes (Liu and Motoda (1998); Yu and Liu (2003)). Let us notice that feature extraction transforms the original input space into a new low dimensional space by combining the initial features, while feature selection retains the most relevant ones in order to build a low dimensional feature space.

Data samples can be either unlabeled or labeled, leading to the development of unsupervised and supervised feature selection techniques. Unsupervised feature selection measures the feature capacity of keeping the intrinsic data structure in order to evaluate its relevance (Dy and Brodley (2004)). Supervised feature selection consists in evaluating feature relevance by measuring the correlation between the feature and class labels (Yu and Liu (2004)).

Supervised feature selection requires sufficient labeled data samples in order

19 to provide a discriminating feature space. However, the sample labeling pro-
20 cess by the human user is fastidious and expensive. That is the reason why in
21 many real applications, we have huge unlabeled data and small labeled sam-
22 ples. To deal with this "lack labeled-sample problem", recent semi-supervised
23 feature selection schemes have been developed by Zhao et al. (Zhao and Liu
24 (2007a); Zhao and Liu (2007b)). They propose a semi-supervised feature
25 relevance criterion which takes into account both unlabeled data and labeled
26 samples. Unfortunately, this score requires to define the classifier step in
27 order to compare the initial labels of the samples and those provided by the
28 classifier (Ng et al. (2001)).

29 Beside class labels, there is another kind of user supervision information
30 called the pairwise constraints (Bar-Hillel et al. (2005)). It consists to simply
31 specify whether a pair of data samples must be regrouped together (must-
32 link constraints) or cannot be regrouped together (cannot-link constraints).
33 Zhang et al. (Zhang et al. (2008)) propose to evaluate the feature relevance
34 by scores which only take into account these constraints. Zhao et al. de-
35 fine another score which uses both the pairwise constraints defined by the
36 user and the unlabeled nearest neighbors of the samples (Zhao et al. (2008)).
37 However, this score considers the neighbors of each sample without explicitly

38 taking into account its local density property.

39 These authors have experimentally shown that the features selected thanks
40 to these constraint-based scores, may provide results which are compara-
41 ble with those given by supervised approaches. Unfortunately, these scores
42 strongly depend on the given constraint subsets built by the user. So, when
43 the user slightly modifies the constraint subset, the feature scores may also
44 change.

45
46 In this paper, we first present a review of the feature selection scores. We
47 then propose a semi-supervised score which uses both pairwise constraints
48 and the local properties of the unlabeled data. We experimentally demon-
49 strate that this score, thanks to the contribution of the unlabeled data, is
50 less sensitive to constraint changes than the classical constraint scores, while
51 providing satisfying classification results.

52 Previous works compare the performances of the feature scores by consider-
53 ing the accuracy rates obtained by a classifier operating in the selected fea-
54 ture space. In order to measure the sensitiveness of the scores to constraint
55 changes, we could estimate the dispersion of accuracy rates with respect to
56 different subsets of constraints. Though, this evaluation depends on the be-

havior of the used classifier. So, we propose to only examine the dispersion of the feature ranks provided by the examined scores thanks to the Kendall's coefficient (Grzegorzewski (2006)).

The paper is organized as follows. In section 2, we review different supervised and unsupervised feature selection scores. Then, we introduce the spectral semi-supervised score in section 3. Recent constraint scores are detailed in section 4 and our semi-supervised constraint score is presented in section 5. In section 6, we study the relationships between the constraints given by the user and the feature ranks obtained by the different scores. Comparative experimental results are provided in section 7 in order to assess the efficiency of our semi-supervised constraint score.

2. Supervised and unsupervised feature selection

Given a dataset of n samples defined in a d -dimensional feature space, let us denote $\mathcal{X} = (x_{ir})$ $i = 1, \dots, n$; $r = 1, \dots, d$; the associated data matrix where x_{ir} is the r^{th} feature value of the i^{th} data. Each of the n rows of the matrix $\mathcal{X}$ represents a data sample $x_i = (x_{i1}, \dots, x_{id}) \in \mathbb{R}^d$, while each of the d columns of $\mathcal{X}$ defines the feature values $f_r = (x_{1r}, \dots, x_{nr})^T \in \mathbb{R}^n$.

74 2.1. Supervised feature selection

75 The principle of supervised feature selection consists in examining the
76 correlation between projected data samples and their class labels on each
77 feature axis. It looks for features on which the classes are compact and far
78 from each others. For this purpose, one uses the well known Fisher criterion
79 to evaluate the feature relevance (Bishop (1996)).

80 By considering the sample coordinates on the feature f_r , each class ω , $\omega=1$,
81 ..., c , populated with n_ω labeled samples is characterized by its mean $\mu_{\omega r}$ and
82 its variance $\sigma_{\omega r}^2$. Moreover, let us denote μ_r the mean of all data samples on
83 the feature f_r .

84 The Fisher score F_r used to evaluate the relevance of the feature f_r is defined
85 by:

$$F_r = \frac{\sum_{\omega=1}^c n_\omega (\mu_{\omega r} - \mu_r)^2}{\sum_{\omega=1}^c n_\omega \sigma_{\omega r}^2}. \quad (1)$$

86 In order to select the most relevant features, they are sorted according to the
87 decreasing order of their Fisher score F_r .

88 2.2. Unsupervised feature selection

89 Unsupervised feature selection consists in evaluating the relevance of each
90 feature by examining the dispersion of the data samples projected on its axis.
91 A feature is considered as being relevant when the data samples projected
92 on this feature axis are scattered as much as possible.
93 So, the variance score V_r is used to evaluate the relevance of the feature f_r :

$$V_r = \frac{1}{n} \sum_{i=1}^n (x_{ir} - \mu_r)^2. \quad (2)$$

94 The features are sorted according to the decreasing order of V_r , in order
95 to select the most relevant ones.

96

97 Rather than measuring the data dispersion along a feature axis, one ex-
98 amines the local properties of the data. The basic idea is to assume that
99 the input data pairwise distances are preserved in the relevant feature space.
100 So, similar samples have to be close when they are projected on a relevant
101 feature axis.

102 According to the spectral graph theory (von Luxburg. (2007)), data samples
103 $x_i, i = 1, \dots, n$ are represented by n nodes in a graph structure. The edge
104 between two connected nodes i and j is weighted by a similarity level defined

105 by:

$$s_{ij} = \exp \left(-\frac{\|x_i - x_j\|^2}{2t^2} \right), \quad (3)$$

106 where $\|x_i - x_j\|^2$ represents the squared euclidean distance between x_i
 107 and x_j in the d -dimensional initial feature space (von Luxburg. (2007)). The
 108 parameter t has to be tuned in order to represent the local dispersion of the
 109 data (Zelink-Manor and Perona (2005)).

110 The weights of the graph are represented by a similarity matrix S ($n \times n$).
 111 From S , we calculate the Laplacian matrix defined as $L = D - S$, where D
 112 ($n \times n$) is the diagonal matrix, $D_{ii} = \sum_{j=1}^n s_{ij}$. It is interesting to note that
 113 the degree D_{ii} of a node i can be considered as a local density measure at x_i .

114

115 In an unsupervised context, He et al. assume that the projections (coor-
 116 dinates) of similar data on the examined feature axis have to be as close as
 117 possible (He et al. (2005)). They propose to compute the Laplacian score L_r
 118 of a feature f_r as:

$$L_r = \frac{\sum_{ij} (x_{ir} - x_{jr})^2 s_{ij}}{\sum_i (x_{ir} - \bar{f}_r) D_{ii}}. \quad (4)$$

119 It is easy to demonstrate that:

$$L_r = \frac{\tilde{f}_r^T L \tilde{f}_r}{\tilde{f}_r^T D \tilde{f}_r} \quad (5)$$

120

121 where $\tilde{f}_r = f_r - \bar{f}_r$ and $\bar{f}_r = \frac{\sum_{i=1}^n x_{ir} D_{ii}}{\sum_{i=1}^n D_{ii}}$.

122 By considering D_{ii} as a density probability measure, $\bar{f}_r$ is the weighted fea-
123 ture average.

124 In order to select relevant features, they are sorted according to the ascend-
125 ing order of L_r .

126 He et al. have experimentally demonstrated that the classifier operating in
127 the feature space selected by the Laplacian score L_r , outperforms the classi-
128 fier operating in the feature space selected by the variance score V_r . Indeed,
129 L_r takes into account the locality structure of the data samples.

130 3. Semi-supervised feature selection

131 In many applications, we have huge unlabeled and a few labeled data
132 samples. Indeed, labeling all the data samples by the user is time consuming
133 and fastidious. In that context, the labeled data subset is usually too small
134 to carry sufficient information for the supervised selection while unsupervised

135 approaches ignore this label information which could be yet interesting for
136 feature selection.

137 That is the reason why more interest has been addressed for a new challenge
138 in feature selection called "small labeled-sample problem". Semi-supervised
139 feature selection methods bring slutions by considering both labeled and un-
140 labeled data subsets.

141 Zhao et al. propose to couple the Laplacian score with normalized mutual
142 information (NMI) in order to introduce a new semi-supervised feature se-
143 lection score (Zhao and Liu (2007a); Zhao and Liu (2007c)). This score
144 compares the initial labels of the data samples with the labels provided by a
145 classifier operating with the examined feature f_r . It is defined as:

$$M_r = \alpha \frac{\sum_{ij} (x_{ir} - x_{jr})^2 s_{ij}}{\sum_i (x_{ir} - \bar{f}_r) D_{ii}} + (1 - \alpha) \left(1 - NMI \left(\hat{f}_r, y \right) \right). \quad (6)$$

146 where $\hat{f}_r$ is the cluster indicator of the samples generated by the classifier and
147 y is the initial class label vector (Zhao and Liu (2007a)). The first term of
148 equation (6) calculates the Laplacian score of the feature f_r , while the second
149 term estimates the corresponding classification error of $\hat{f}_r$ according to the
150 labeled data. The term α is a regularization parameter set to 0.1 by (Zhao
151 and Liu (2007a)), in order to favor the contribution of the labeled data. That

152 is the reason why the selected features by using equation (6) mainly depend
 153 on the labeling decision achieved by the classifier.

154 4. Constraint scores

155 The prior knowledge about the data can be represented according to two
 156 different ways: class labels and pairwise constraints. Class labels require
 157 to have detailed information about the classes and to precisely indicate the
 158 label of each data sample. Pairwise constraints simply mention for some
 159 pairs of data samples that they are similar, i.e. must be regrouped together
 160 (must-link constraints), or that they are dissimilar, i.e. cannot be regrouped
 161 together (cannot-link constraints).

162 The user has to build the subset $\mathcal{M}$ of must-link constraints and the subset
 163 $\mathcal{C}$ of cannot-link constraints defined as:

$$164 \mathcal{M} = \{(x_i, x_j), \text{ such as } x_i \text{ and } x_j \text{ must be linked}\}.$$

$$165 \mathcal{C} = \{(x_i, x_j), \text{ such as } x_i \text{ and } x_j \text{ cannot be linked}\}.$$

166 The cardinals of these subsets are usually much lower than the number $\binom{n}{2}$
 167 of all possible pairwise constraints.

168 These pairwise constraints are easier to be obtained by the user than the
 169 class labels. They simply formalize that two data samples belong or not to

170 the same class without detailed information about the classes in presence.
 171 Indeed, labeled data samples can be transformed into must-link and cannot-
 172 link constraints but not vice versa. It consists in putting must-link constraint
 173 between two data samples which share the same label and cannot-link con-
 174 straint between two data samples sharing different labels.

175 Zhang et al. have recently proposed a constraint feature selection scheme
 176 which uses only a subset of must-link and cannot-link constraints (Zhang
 177 et al. (2008)).

178 In the context of the spectral theory (von Luxburg. (2007)), two specific
 179 graphs are built:

- 180 • The must-link graph $G^{\mathcal{M}}$ where a connection is established between
 181 two nodes i and j if there is a must-link constraint between their cor-
 182 responding samples (nodes) x_i and x_j .
- 183 • The cannot-link graph $G^{\mathcal{C}}$ where a connection is established between
 184 two nodes i and j if there is a cannot-link constraint between their
 185 corresponding samples (nodes) x_i and x_j .

186 The connection weights between two nodes of the graphs $G^{\mathcal{M}}$ and $G^{\mathcal{C}}$ are
 187 respectively stored by the similarity matrices $S^{\mathcal{M}}$ ($n \times n$) and $S^{\mathcal{C}}$ ($n \times n$),

188 and are given by:

189 $s_{ij}^{\mathcal{M}} =$

$$\begin{cases} 1 & \text{if } (x_i, x_j) \in \mathcal{M} \text{ or } (x_j, x_i) \in \mathcal{M} \\ 0 & \text{otherwise,} \end{cases} \quad (7)$$

190

191 $s_{ij}^{\mathcal{C}} =$

$$\begin{cases} 1 & \text{if } (x_i, x_j) \in \mathcal{C} \text{ or } (x_j, x_i) \in \mathcal{C} \\ 0 & \text{otherwise.} \end{cases} \quad (8)$$

192 The matrices $S^{\mathcal{M}}$ and $S^{\mathcal{C}}$ are used to define the constraint Laplacian
 193 matrices $L^{\mathcal{M}} = D^{\mathcal{M}} - S^{\mathcal{M}}$ and $L^{\mathcal{C}} = D^{\mathcal{C}} - S^{\mathcal{C}}$, where $D^{\mathcal{M}}$ and $D^{\mathcal{C}}$ are the
 194 degree matrices defined by $D_{ii}^{\mathcal{M}} = \sum_{j=1}^n s_{ij}^{\mathcal{M}}$ and $D_{ii}^{\mathcal{C}} = \sum_{j=1}^n s_{ij}^{\mathcal{C}}$.

195 In order to measure the constraint preserving ability of the feature f_r , Zhang
 196 et al. define two constraint scores C_r^1 and C_r^2 :

$$C_r^1 = \frac{\sum_{ij} (x_{ir} - x_{jr})^2 s_{ij}^{\mathcal{M}}}{\sum_{ij} (x_{ir} - x_{jr})^2 s_{ij}^{\mathcal{C}}} = \frac{f_r^T L^{\mathcal{M}} f_r}{f_r^T L^{\mathcal{C}} f_r}, \quad (9)$$

197

198

$$\begin{aligned}
C_r^2 &= \sum_{ij} (x_{ir} - x_{jr})^2 s_{ij}^{\mathcal{M}} - \lambda \sum_{ij} (x_{ir} - x_{jr})^2 s_{ij}^{\mathcal{C}} \\
&= f_r^T L^{\mathcal{M}} f_r - \lambda f_r^T L^{\mathcal{C}} f_r,
\end{aligned} \tag{10}$$

199 where λ is a regularization parameter used to balance the contribution of
 200 the two constraints terms of C_r^2 . Must-link constraints are favored by setting
 201 $0 < \lambda < 1$.

202 The lower these two scores are, the more relevant the feature is. Zhang et al.
 203 have experimentally shown that the features selected by C^1 and C^2 provide
 204 similar performances when λ is well balanced.

205 **5. Constraint scores for semi-supervised feature selection**

206 The scores presented in section 4 use only the available constraints and
 207 do not take into account the unlabeled data contribution. Zhao et al. define
 208 another score which uses both unlabeled data and pairwise constraints in
 209 order to retrieve both locality properties and discriminating structures in
 210 the data samples (Zhao et al. (2008)). They build a new graph $G^{\mathcal{W}}$ which
 211 connects samples having high probability of sharing the same label:

- 212 • $G^{\mathcal{W}}$ is the within-class graph: two nodes i and j are connected if (x_i, x_j)
 213 or (x_j, x_i) belongs to $\mathcal{M}$, or if the two samples are unlabeled but they

214 are sufficiently close to each other (by using the k -nearest neighbor
 215 graph)

216 The edges in the graphs $G^{\mathcal{W}}$ are weighted by using the similarity matrix $S^{\mathcal{W}}$
 217 ($n \times n$) and are expressed as:

218 $s_{ij}^{\mathcal{W}} =$

219

$$\left\{ \begin{array}{l} \gamma \text{ if } (x_i, x_j) \in \mathcal{M} \text{ or } (x_j, x_i) \in \mathcal{M} \\ 1 \text{ if } x_i \text{ or } x_j \text{ is unlabeled} \\ \text{but node } i \in KNN(j) \text{ or node } j \in KNN(i) \\ 0 \text{ otherwise} \end{array} \right. \quad (11)$$

220 where γ is a constant parameter which has been empirically set to 100 in
 221 (Zhao et al. (2008)).

222 Zhao et al. introduce a Laplacian score, called the locality sensitive discrim-
 223 inant analysis score and defined as:

$$C_r^3 = \frac{\sum_{i,j} (x_{ir} - x_{jr})^2 s_{ij}^{\mathcal{W}}}{\sum_{i,j} (x_{ir} - x_{jr})^2 s_{ij}^{\mathcal{C}}} = \frac{f_r^T L^{\mathcal{W}} f_r}{f_r^T L^{\mathcal{C}} f_r}, \quad (12)$$

224 where $L^{\mathcal{W}} = D^{\mathcal{W}} - S^{\mathcal{W}}$, $D^{\mathcal{W}}$ being the degree matrix defined by $D_{ii}^{\mathcal{W}} =$
 225 $\sum_{j=1}^n s_{ij}^{\mathcal{W}}$. This score implicitly takes into account the unlabeled data but
 226 favors pairs of must-link data by assigning them high weights in the matrix
 227 $S^{\mathcal{W}}$. Moreover, the similarity matrix $S^{\mathcal{W}}$ represents the links between the
 228 k -nearest neighbors of the data by binary weighting them. By mainly con-
 229 sidering the must-link constraints, C^3 is very close to C^2 , and both neglect
 230 the unlabeled data samples.

231 Though, taking into account the unlabeled data samples should catch the
 232 data structure and make less sensitive a feature score against the given con-
 233 straint subset. That leads us to propose another semi-supervised constraint
 234 score which is less sensitive to the constraints chosen by the user. Given the
 235 matrices S , $S^{\mathcal{M}}$ and $S^{\mathcal{C}}$, the semi-supervised constraint score is defined as :

$$C_r^4 = \frac{\tilde{f}_r^T L \tilde{f}_r}{\tilde{f}_r^T D \tilde{f}_r} \cdot \frac{f_r^T L^{\mathcal{M}} f_r}{f_r^T L^{\mathcal{C}} f_r}. \quad (13)$$

236 The proposed score C_r^4 is the simple product between the Laplacien score
 237 L_r (see equation (4)) processed with the unlabeled data and the constraint
 238 score C_r^1 (see equation (9)) defined by Zhang:

$$C_r^4 = L_r \cdot C_r^1, \quad (14)$$

239 So, it takes into account both the unlabeled data thanks to L_r and the
240 available constraints thanks to C_r^1 in order to evaluate the relevance of the
241 feature f_r . As for the other scores, the features are ranked in ascending order
242 according to score C^4 in order to select the most relevant ones.

243 6. Constraint subset influence in feature selection process

244 The constraint scores introduced above evaluate the relevance of the fea-
245 tures based on the must-link and cannot-link constraints. However, these
246 scores strongly depend on the given constraint subsets $\mathcal{M}$ and $\mathcal{C}$. Indeed,
247 changing the subset of available constraints could lead to a large change in
248 the feature ranks and so, in the selected features. To illustrate this problem,
249 we examine the following toy example.

250 6.1. Toy example

251 Let us consider four 3-dimensional data samples:

252 $A(-3, -1, 1)$; $B(-3, 1, 1)$; $C(-1, -1, 1)$ and $D(1, -3, -1)$.

253 A , B and C belong to the first class whereas D is assigned to the second
254 class. We can see that the feature f_3 is the single feature which corresponds
255 to the class label (1 for the first class, -1 for the second class). So, an efficient

256 feature selection algorithm should identify the feature f_3 as the most relevant
257 one.

258 Let us consider that the user builds one single must-link constraint and one
259 single cannot-link constraint from the labeled samples. The constraint scores
260 introduced in sections 4 and 5 are used to rank the 3 features based on these
261 constraints.

262 The different feature ranks are shown in table 1. Pairs $\{(A,B)\}$, $\{(A,C)\}$ and
263 $\{(B,C)\}$ are the single must-link constraints that can be built from the data
264 samples. Pairs $\{(A,D)\}$, $\{(B,D)\}$ and $\{(C,D)\}$ are the single cannot-link
265 constraints that can be also built from the data samples. So, there are 9
266 constraint combinations which correspond to 9 cells in table 1. The first, the
267 second, the third and the fourth row of each cell represent the ranks of the 3
268 features given by C^1 , C^2 (α is fixed to 0.1 as suggested by the authors), C^3
269 and C^4 scores, respectively. The sign '=' between two features means that
270 their scores are equal.

271 For example, let us examine the cell which corresponds to the must-link
272 constraint $\{(A,C)\}$ and the cannot-link constraint $\{(B,D)\}$. Scores C^1 and
273 C^4 select the features f_2 and f_3 as the best features. and the feature f_1 as the
274 third feature. Scores C^2 and C^3 sort feature f_2 as the best feature, feature

f_3 as the second feature and feature f_1 as the third feature.

$\mathcal{C}/\mathcal{M}$		$\{(A,B)\}$	$\{(A,C)\}$	$\{(B,C)\}$
$\{(A,D)\}$	C^1	$\mathbf{f_3 = f_1, f_2}$	$\mathbf{f_3 = f_2, f_1}$	$\mathbf{f_3, f_1, f_2}$
	C^2	$\mathbf{f_1, f_3, f_2}$	$f_3 = f_2, f_1$	f_3, f_1, f_2
	C^3	f_1, f_3, f_2	$\mathbf{f_3, f_2, f_1}$	f_3, f_1, f_2
	C^4	$f_3 = f_1, f_2$	$f_3 = f_2, f_1$	f_3, f_1, f_2
$\{(B,D)\}$	C^1	$f_3 = f_1, f_2$	$f_3 = f_2, f_1$	$\mathbf{f_3, f_1 = f_2}$
	C^2	f_1, f_3, f_2	$\mathbf{f_2, f_3, f_1}$	$f_3, f_1 = f_2$
	C^3	f_1, f_3, f_2	f_2, f_3, f_1	f_3, f_2, f_1
	C^4	$f_3 = f_1, f_2$	$f_3 = f_2, f_1$	f_3, f_1, f_2
$\{(C,D)\}$	C^1	$f_3 = f_1, f_2$	$f_3 = f_2, f_1$	$f_3, f_1 = f_2$
	C^2	$f_3 = f_1, f_2$	$f_3 = f_2, f_1$	$f_3, f_1 = f_2$
	C^3	f_3, f_1, f_2	f_3, f_2, f_1	f_3, f_2, f_1
	C^4	$f_3 = f_1, f_2$	$f_3 = f_2, f_1$	f_3, f_1, f_2

Table 1: Feature ranks by semi-supervised scores using the chosen constraints.

275

276 First, table 1 shows that the feature f_3 is always ranked as the first
 277 feature by C^1 and C^4 whatever the given constraint subset. C^2 and C^3 do
 278 not retain feature f_3 as the first feature three times. This table also shows

279 that 7 different ranks (indicated in bold in table 1) of the 3 features are
 280 obtained by comparing each of the 4 examined scores for the 9 constraint
 281 combinations. This simple example clearly shows that the features ranks
 282 deduced from these scores strongly depend on the chosen constraints. So, we
 283 propose to measure how the feature ranks vary with respect to the subset of
 284 constraints.

285 6.2. Kendall's coefficient

286 The performances of the examined scores are generally compared by mea-
 287 suring the accuracy rates obtained from well classified data projected on the
 288 selected features. To measure the dependence of the scores on the given
 289 constraint subsets, we could estimate the disparity of the accuracy rates ob-
 290 tained with different constraint subsets. This evaluation requires to define a
 291 labeling decision step, such as k -nearest neighbor classifier, which operates in
 292 the selected feature space. Since this decision step influences the quality of
 293 classification, the comparison between the score performances may depend
 294 on the used classifier.

295 We prefer to examine only the feature ranks deduced from the scores, so that
 296 our study is not corrupted by the decision step. More precisely, we study the

297 concordance between feature ranks when the constraint subset changes.

298

299 Given the sample set $\mathcal{X} = (x_1, \dots, x_n)$ and the associated class label of each
 300 data sample, we randomly pick up a subset $\mathcal{S}_q$ of pairwise constraints ($\mathcal{S}_q =$
 301 $\mathcal{M}_q \cup \mathcal{C}_q$). Then, we rank the d features f_r , according to the different con-
 302 straint scores C_r^* detailed in sections 4 and 5 ($* = 1, 2, 3, 4$).

303 Let us denote R_{qr}^* the rank of the feature f_r when the score C_r^* considers the
 304 constraint subset $\mathcal{S}_q$. In order to evaluate the influence of constraint subset,
 305 the feature selection is run p times. For a score C^* , the ranks of the d features
 306 obtained with the p different subsets $\mathcal{S}_q$ are represented by the matrix R^*
 307 ($p \times d$):

308

$$309 \quad R^* = \begin{bmatrix} R_{11}^* & R_{12}^* & \dots & R_{1d}^* \\ R_{21}^* & R_{22}^* & \dots & R_{2d}^* \\ \dots & \dots & \dots & \dots \\ R_{p1}^* & R_{p2}^* & \dots & R_{pd}^* \end{bmatrix}$$

310

311 The q^{th} row of R^* represents the d feature ranks by using the subset $\mathcal{S}_q$
 312 ($q = 1, \dots, p$) while the r^{th} column represents the ranks of the feature f_r by
 313 using the p different constraint subsets. Therefore, each row of R^* is a per-

314 mutation of the d feature ranks which depends on the available constraint
 315 subset S_q .

316 We use the Kendall's coefficient to measure the concordance or agreement
 317 between the feature ranks with p constraint subsets (Grzegorzewski (2006)).
 318 The Kendall's coefficient K^* takes into account the different rows of the
 319 matrix R^* and is defined as (Siegel and Castellan (1988)):

$$K^* = \frac{12\Delta^*}{p^2(d^3 - d) - p\tau^*}, \quad (15)$$

320 where $\Delta^* = \sum_{r=1}^d (R_r^* - \bar{R}^*)^2$, $R_r^* = \sum_{q=1}^p R_{qr}^*$, $\bar{R}^* = \frac{1}{d} \sum_{r=1}^d R_r^*$ and $\tau^* =$
 321 $\sum_{v=1}^m (\tau_v^{*3} - \tau_v^*)$

322 The term τ_v^* is the number of tied ranks in each of the m groups of ties in
 323 R^* . The sum τ^* is computed over all the groups of ties found in all p rows
 324 of the table R^* .

325 The Kendall's coefficient which measures the dispersion Δ^* of the feature
 326 ranks, ranges from 0 (no agreement) to 1 (complete agreement).

327 6.3. Kendall's coefficient for the toy example

328 Let us examine the toy example of section 6.1. We propose to compute
 329 the Kendall's coefficient from table 1 in order to measure the concordance of

the feature ranks obtained by each examined constraint score. The Kendall's coefficients K^1 (see eq. (9)), K^2 (see eq. (10)), K^3 (see eq. (12)) and K^4 (see eq. (13)) are respectively 0.4325, 0.2258, 0.3333 and 0.4333.

These low values reflect the dependence of the feature ranks on the available constraints subsets.

This example shows that the Kendall's coefficient K^4 of C^4 is slightly higher than the other ones. The objective of this simple example, with low sample population, is not to compare the Kendall's coefficient of the different scores, but to arise that the selected features depend on the given constraint subset. This conclusion concurs with that of Sun et al. (Suna and Zhang (2010)).

7. Comparative experimental results

In this section, we first measure the sensitivity of the scores against the given constraints. So, we compare the Kendall's coefficient obtained by the tested scores (C^1 , C^2 , C^3 , C^4).

We also compare the performances obtained by a classifier operating in the feature space selected by C^4 score and those obtained with the classical feature selection methods: Fisher score (supervised), Laplacian score (unsupervised), C^1 , C^2 (constraint scores) and C^3 (semi-supervised constraint

348 score).

349 *7.1. Examined databases*

350 For this purpose, our experiments are achieved with six well known and
351 largely used benchmark databases, and more precisely the 'Wine', 'Image
352 segmentation' and 'Vehicle' databases from the UCI repository (Blake et al.
353 (1998)), the face database 'ORL' (Samaria and Hartert (1994)) and the
354 two gene expression databases, i.e., 'Colon Cancer'(Alon et al. (1999)) and
355 'Leukemia'(Golub et al. (1999)). These databases have been retained since
356 the features are numeric and since the label information of each data sample
357 is clearly defined.

358 In our experiments, we first normalize the features between 0 and 1, so that
359 different features have the same scale. For each dataset, we follow an Holdout
360 partition and choose the first half of samples from each class as the training
361 data and the remaining data for testing.

362 *7.2. Results on UCI datasets and ORL database*

363 First, we achieve experiments on 3 UCI datasets and the the 'ORL' face
364 database. Here is a brief description of the four considered databases:

365 • **'Wine' database**

366 This database contains 178 13-dimensional data ($d=13$) regrouped into
367 3 classes having 59, 71 and 48 instances, respectively. We randomly
368 select 30, 36 and 24 data samples from each class to build the training
369 data. The remaining data are organized as the test data subset.

370 • **'Image segmentation' database**

371 This database contains 210 19-dimensional data ($d=19$) regrouped into
372 7 classes, each class having 30 instances. We randomly select 15 data
373 samples from each class to build the training data and the remaining
374 data constitute the test data subset.

375 • **'Vehicle' database**

376 This database contains 846 18-dimensional data ($d=18$) regrouped into
377 4 classes, having 212, 217, 218 and 199 instances, respectively. We
378 randomly select 106, 109, 109 and 100 data samples from each class to
379 build the training data.

380 • **'ORL' database**

381 The 'ORL' database (Olivetti Research Laboratory) contains a set of
382 face images representing 40 distinct subjects. There are 10 different

Figure 1: Sample face images from the ORL database (2 subjects).

383 images per subject, so that the database contains 400 images. For each
 384 subject, the images have been acquired according to different condi-
 385 tions: lighting, facial expressions (open / closed eyes, smiling / not
 386 smiling) and facial details (glasses / no glasses) (see figure 1).

387 In our experiments, original images have been normalized (in scale and
 388 orientation) so that the two eyes are aligned at the same horizontal
 389 position. Then, the facial areas have been cropped in order to build
 390 images of size 32×32 pixels. Thus, each image can be represented by
 391 a 1024-dimensional sample data. The gray level of each pixel is quan-
 392 tified with 256 levels.

393 We randomly select 5 images from each class (subject) to build the
 394 training data. The remaining data are organized as the test data sub-
 395 set.

396 7.2.1. Kendall's coefficient results

397 In our experiments, the feature selection is performed on the training data
 398 and features are ranked according to the different scores. At each feature se-
 399 lection run q , $q=1, \dots, p$, we simulate the generation of pairwise constraints
 400 as follow: we randomly select pairs of samples from the training data and
 401 create must-link or cannot-link constraints depending on whether the under-
 402 lying classes of the two samples are the same or different. We iterate this
 403 scheme until we obtain $\frac{\text{card}(S_q)}{2}$ must-link constraints and $\frac{\text{card}(S_q)}{2}$ cannot-link
 404 constraints.

405 This operation is repeated over $p = 100$ runs in order to measure the
 406 Kendall's coefficients K^1 , K^2 , K^3 and K^4 .

407 We achieve experiments for different cardinals of S_q ranging from 4 (2 must-
 408 link and 2 cannot-link) to 40 constraints as Zhang et al. do.

409 Figure 2 shows the Kendall's coefficients K^1 , K^2 , K^3 and K^4 calculated
 410 over $p = 100$ runs for different numbers of constraints. At each run, the
 411 same given constraint subset is of course considered by the four tested cri-
 412 teria. The low values of K^1 , K^2 , K^3 and K^4 show clearly that the selected
 413 features using C^1 , C^2 , C^3 and C^4 depend on the constraint subsets.

414 By examining the different curves of figure 2, we see that the different coeffi-

(a) 'Wine'.

(b) 'Image segmentation'.

(c) 'Vehicle'.

(d) 'ORL'.

Figure 2: Kendall's coefficient for different number S_q of constraints on the four databases.

415 cients K^1 , K^2 , K^3 and K^4 increase with the number $card(S_q)$ of constraints.

416 The higher the number $card(\mathcal{S}_q)$ of constraints is, the more complete the su-

417 pervision information is. Ideed, when $card(\mathcal{S}_q)$ is high, the semi-supervised

418 learning context tends to become a supervised learning context. That ex-

419 plains why the agreement of feature ranks increases when $card(\mathcal{S}_q)$ increases

420 in the different curves of figure 2.

421 We can also notice that K^4 has the highest values for the different cardinals

422 of constraint subsets in the four databases. This shows that our score C^4 is

423 less sensitive to the must-link and cannot-link constraints built by the user

424 than the classical scores.

425 We also observe that the values of the Kendall's coefficients on the 'ORL'
426 database are lower than those obtained with the other databases. Indeed,
427 the number of features extracted from the 'ORL' database (1024 features) is
428 bigger than that of the other databases.

429 Zhao and Zhang have experimentally shown that by picking-up a small num-
430 ber $card(\mathcal{S}_q)$ of constraints, their scores allow to select the features which
431 carry a good discriminating power. Figure 2 shows that, between two differ-
432 ent runs, the feature ranks change, and so the selected features change when
433 $card(\mathcal{S}_q)$ is low. So, the quality of data discrimination would strongly vary
434 with respect to the chosen constraint subsets.

435 7.2.2. Comparison of the performances

436 We also compare the performances obtained by the nearest neighbor clas-
437 sifier which operates in the feature space selected thanks to the considered
438 supervised, unsupervised and semi-supervised feature scores.

439 The classification accuracies of the test data are used to evaluate the perfor-
440 mance of each criterion.

441 As for measuring the Kendall's coefficients, the rates of good classification

(a) 'Wine'.

(b) 'Image segmentation'.

(c) 'Vehicle'.

(d) 'ORL'.

Figure 3: Accuracy vs. different number of selected features on the four datasets. 10 pairwise constraints including 5 must-link and 5 cannot link are used.

442 are averaged over $p = 100$ runs with different generations of constraints.
 443 Figure 3 shows the plots of accuracy vs. the desired number of selected fea-
 444 tures on the 'Wine' 3(a), 'Image segmentation' 3(b), 'Vehicle' 3(c) and 'ORL'
 445 3(d) databases, respectively when $\text{card}(\mathcal{S}_q)$ is set to 10 .
 446 From figure 3 , we can see that the classification rates obtained with con-
 447 straint scores (C^1 , C^2 , C^3 and C^4) range between those obtained with the un-
 448 supervised method (Laplacian score) and those obtained with the supervised
 449 method (Fisher score). Since $\text{card}(\mathcal{S}_q)$ is set to 10, these semi-supervised
 450 scores use a bit more supervision information than Laplacian score, but much
 451 fewer than Fisher Score.
 452 So, these results confirm that a classification scheme reaches higher per-
 453 formance thanks to a supervised learning than thanks to a semi-supervised
 454 learning. They also confirm that taking into account a few constraints allows
 455 to improve classification results, compared with the unsupervised learning.
 456 However, the curves of C^1 , C^2 , C^3 and C^4 are confused in figure 3. It is also
 457 difficult to compare the performances of these scores since they are averaged
 458 over 100 runs with different generations of constraints.

459 That leads us to compare these scores while examining their accuracies
 460 at each of the 100 runs. For a fixed number of selected features, in each of

$card(S_q) / T$	T^1	T^2	T^3	T^4
4 constraints	198	238	219	180
10 constraints	195	210	185	162
40 constraints	180	299	168	136

Table 2: The rank sums of the different semi-supervised criteria for different number S_q of constraints on the 'wine' database.

$card(S_q) / T$	T^1	T^2	T^3	T^4
4 constraints	208	228	168	179
10 constraints	228	210	154	183
40 constraints	184	177	153	146

Table 3: The rank sums of the different semi-supervised criteria for different number S_q of constraints on the 'image' database.

461 the 100 runs, we propose to rank the 4 criteria in descending order of their
 462 accuracy. Let us denote $rank_q^*$ the rank of the criterion C^* at the run q .
 463 This rank takes the values 1, 2, 3 or 4. At each run q , the method having
 464 the highest accuracy is ranked as 1 and the method with the lowest accuracy
 465 value, is ranked as 4. Methods with the same accuracy have the same rank.
 466 We calculate a rank sum T^* for each semi-supervised constraint score as
 467 follow:

$card(S_q) / T$	T^1	T^2	T^3	T^4
4 constraints	237	239	232	219
10 constraints	271	246	189	240
40 constraints	290	240	208	207

Table 4: The rank sums of the different semi-supervised criteria for different number S_q of constraints on the 'vehicle' database.

$card(S_q) / T$	T^1	T^2	T^3	T^4
4 constraints	194	212	311	200
10 constraints	185	189	250	196
40 constraints	190	202	300	203

Table 5: The rank sums of the different semi-supervised criteria for different number S_q of constraints on the 'ORL' database.

$$T^* = \sum_{q=1}^{100} rank_q^*, \quad (16)$$

468 where $*$ is 1, 2, 3 or 4 corresponding to the score C^1 , C^2 , C^3 or C^4 respectively.

469 The method with the lowest rank sum is considered as being the score which
470 provides the best results.

471 For the 'Wine', 'Image segmentation', 'Vehicle' and 'ORL' databases, the
472 accuracy of each of the 4 semi-supervised criteria seems to be stable when

the number of desired features is higher than 6, 5, 8 and 300, respectively (see figure 3). So, we propose to calculate the rank total of each of the semi-supervised criteria by considering the 6 first selected features for the 'Wine database', the 5 first selected features for the 'Image segmentation' database, the 8 first selected features for the 'Vehicle' database and the 300 first selected ones for the 'ORL' database .

Tables 2, 3, 4 and 5 show the rank sum T^* for different numbers S_q of constraints (4, 10 and 40). Each cell indicates the rank sum of the tested score with the considered number of constraints. From these tables, we can clearly see that T^1 , T^2 , T^3 and T^4 are very close. The features selected thanks to C^4 provide accuracy rates comparable with those obtained by the features selected by C^1 , C^2 and C^3 . Indeed, our score provides the lowest rank sum T (indicated in bold) for 6 times over the 12 rows of tables 2, 3, 4 and 5.

7.3. Results on gene expression databases

In this subsection, several experiments are carried out on two gene expression databases, i.e., 'Colon Cancer'(Alon et al. (1999)) and 'Leukemia'(Golub et al. (1999)).

491 • **'Colon Cancer'**

492 This database contains the expression of 2000 genes measured on 62
493 tissues (40 tumors and 22 normals). We randomly select 20 and 11 data
494 samples from each class to build the training data. The remaining data
495 are organized as the test data subset.

496 • **'Leukemia'**

497 This database contains information on gene-expression in samples from
498 human acute myeloid (AML) and acute lymphoblastic leukemias (ALL).
499 From the originally measured 6817 probe sets we removed genes that
500 were not present in at least one sample so a total of 5147 genes are
501 used in the experiments.

502 Because Leukemia has a predefined partition of the objects into train-
503 ing (27 ALL and 11 AML) and testing (20 ALL and 14 AML) subsets,
504 the ensembles on this dataset are performed on the predefined training
505 and testing sets.

506 Figure 4 shows the Kendall's coefficients K^1 , K^2 , K^3 and K^4 calculated over
507 $p = 100$ runs for different numbers of constraints on the 'Colon Cancer' and
508 the 'Leukemia' databases. As for the previous databases, K^4 has the high-

(a) 'Colon Cancer'.

(b) 'Leukemia'.

Figure 4: Kendall's coefficient for different number S_q of constraints on the 'Colon Cancer' and the 'Leukemia' databases.

est values for the different cardinals of constraint subsets in these two gene
 expression databases. This confirm the fact that our score C^4 is less sensi-
 tive to the must-link and cannot-link constraints built by the user than the
 classical scores. Moreover, since the number of features is very high, 2000
 for the Colon Cancer database and 5147 for the leukemia one, we can notice
 that the gap between K^4 on a hand and K^1 , K^2 and K^3 on the other hand
 is higher on these databases than the previous ones (a voir).

Figure 5 shows the plots for accuracy vs. different numbers of selected fea-
 tures on Colon Cancer and Leukemia databases. $card(S_q)$ here is set to 60
 as Sun et al. do (Suna and Zhang (2010)), so 60 pairwise constraints in-
 cluding 30 must-link and 30 cannot-link are used. From figure 5, we can
 see that the classification rates obtained with constraint scores (C1, C2,

(a) 'Colon Cancer'.

(b) 'Leukemia'.

Figure 5: Accuracy vs. different number of selected features on the gene expression-databases. 60 pairwise constraints including 30 must-link and 30 cannot link are used.

521 C3 and C4) range between those obtained with the unsupervised method
522 (Laplacian score) and those obtained with the supervised method (Fisher
523 score). These semi-supervised constraint scores even outperforms the super-
524 vised Fisher score on the 'Colon Cancer' database for a number of selected
features more than 1050.

$card(S_q) / T$	T^1	T^2	T^3	T^4
4 constraints	148	195	235	158
10 constraints	156	242	203	153
40 constraints	169	286	153	138
60 constraints	157	271	149	144

Table 6: The rank sums of the different semi-supervised criteria for different number S_q of constraints on the 'Colon Cancer' database.

525

526 Tables 6 and 7 show the rank sum T^* for different numbers S_q of constraints
527 (4, 10, 40 and 60) on the 'Colon Cancer' and the 'Leukemia' databases re-
528 spectively. The rank total of each of the semi-supervised criteria is calculated
529 considering the half of the original features of each of the gene expression
530 databases (see(Suna and Zhang (2010))).

531 From these tables, we can see that, for the 'Colon Cancer' database, our
532 score provides the lowest rank sum T (indicated in bold) for 3 times over the

$card(S_q) / T$	T^1	T^2	T^3	T^4
4 constraints	184	240	194	182
10 constraints	176	276	150	134
40 constraints	170	196	148	118
60 constraints	186	198	168	126

Table 7: The rank sums of the different semi-supervised criteria for different number S_q of constraints on the 'Leukemia' database.

533 4 rows of table 6. For the 'Leukemia database', our score provides the lowest
534 rank sum T (indicated in bold) for the different numbers of constraints (4,
535 10, 40 and 60). These results improve the fact that the features selected
536 thanks to C_4 provide accuracy rates comparable with those obtained by the
537 features selected by C_1 , C_2 and C_3 .

538 Furthermore, figure 6 shows the plot for accuracy under fixed number of se-
539 lected features (half of the number of original features) vs. different numbers
540 of pairwise constraints on the gene expression databases. For almost all the
541 number of constraints, our score C_4 achieves higher accuracy than C_1 , C_2
542 and C_3 .

(a) 'Colon Cancer'.

(b) 'Leukemia'.

Figure 6: Accuracy vs. different number of pairwise constraints (for C_1 , C_2 , C_3 and C_4) on the gene expression databases. The desired number of selected features is half of the number of original features

8. Conclusion

Constraint scores which use pairwise constraints for semi-supervised feature selection have shown good performances of classification. Unfortunately, these scores depend on the subset of constraints built by the user since they do not take into account the information provided by the unlabeled data. In this paper, we propose a new semi-supervised constraint score that considers both the pairwise constraints and the local properties of the unlabeled data. Moreover, we study the relationships between the features selected by the constraint scores and the constraints chosen by the user. We measure the sensitiveness of the scores to constraint changes by the Kendall's coefficient.

553 To the best of our knowledge, this is the first work that studies the influence
554 of the constraint subsets change on the features selected by the constraint
555 scores.

556 Experimental results on three UCI datasets and a face database show that
557 the proposed score is less sensitive to the constraint changes while selecting
558 features that provide satisfying classification results.

559 **References**

560 Alon, U., Barkai, N., Notterman, D., Gishdagger, K., Ybarradagger, S.,
561 Mackdagger, D., Levine, A., 1999. Broad patterns of gene expression re-
562 vealed by clustering analysis of tumor and normal colon tissues probed by
563 oligonucleotide arrays. *Proceedings of the National Academy of Science of*
564 *the USA* 96 (12), 745–6750.

565 Bar-Hillel, A., Hertz, T., Shental, N., Weinshall, D., 2005. Learning a maha-
566 lanobis metric from equivalence constraints. *Journal of Machine Learning*
567 *Research*, 937–965.

568 Bishop, C., Jan. 1996. *Neural Networks for Pattern Recognition*. Oxford
569 University Press, USA.

- 570 Blake, C., Keogh, E., Merz, C., 1998. UCI repository of machine learning
571 databases. <http://www.ics.uci.edu/ml/MLRepository.html>.
- 572 Dy, J., Brodley, C., 2004. Feature selection for unsupervised learning. *Journal*
573 *of Machine Learning Research* 5, 845–889.
- 574 Golub, T. R., Slonim, D. K., Tamayo, P., Huard, C., Gaasenbeek, M.,
575 Mesirov, J. P., Coller, H., Loh, M. L., Downing, J. R., Caligiuri, M. A.,
576 Bloomfield, C. D., 1999. Molecular classification of cancer: class discovery
577 and class prediction by gene expression monitoring. *Science* 286, 531–537.
- 578 Grzegorzewski, P., 2006. The coefficient of concordance for vague data. *Com-*
579 *putational Statistics and Data Analysis* 51 (1), 314–322.
- 580 He, X., Cai, D., Niyogi, P., Dec. 2005. Laplacian score for feature selection.
581 In: *Proceedings of the Advances in Neural Information Processing Systems*
582 *(’NIPS 05’)*. Vancouver, British Columbia, Canada.
- 583 Liu, H., Motoda, H., Aug. 1998. Feature extraction construction and selection
584 a data mining perspective, 1st Edition. Springer.
- 585 Ng, A., Jordan, M., Weiss, Y., Dec. 2001. On spectral clustering: Analysis

586 and an algorithm. In: Proceedings of the Advances in Neural Information
587 Processing Systems ('NIPS 01'). Canada, pp. 849–856.

588 Samaria, F., Hartert, A., 1994. Parameterisation of a stochastic model for
589 human face identification. In: Proceedings of the Second IEEE Workshop
590 on Applications of Computer Vision 'ACV 94'. Sarasota, Florida, pp. 138–
591 142.

592 Siegel, S., Castellan, N., 1988. Nonparametric statistics for the behavioral
593 sciences, 2nd Edition. McGraw-Hill, New York.

594 Suna, D., Zhang, D., Jun. 2010. Bagging constraint score for feature selection
595 with pairwise constraints. Pattern Recognition 43, 2106–2118.

596 von Luxburg., U., 2007. A tutorial on spectral clustering. Statistics and Com-
597 puting 17 (4), 395–416.

598 Yu, L., Liu, H., 2003. Feature selection for high-dimensional data: A fast
599 correlation-based filter solution. Vol. 6. pp. 856–863.

600 Yu, L., Liu, H., 2004. Efficient feature selection via analysis of relevance and
601 redundancy. Journal of Machine Learning Research 5, 1205–1224.

602 Zelink-Manor, L., Perona, P., Dec. 2005. Self-tuning spectral clustering. In:

603 Proceedings of the Advances in Neural Information Processing Systems
604 'ANIPS 05'. Vancouver, British Columbia, Canada, pp. 1601–1608.

605 Zhang, D., Chen, S., Zhou, Z., Oct. 2008. Constraint score: A new filter
606 method for feature selection with pairwise constraints. *Pattern Recognition*
607 (41), 1440–1451.

608 Zhao, J., Lu, K., He, X., 2008. Locality sensitive semi-supervised feature
609 selection. *Neurocomputing* 71 (10-12), 1842–1849.

610 Zhao, Z., Liu, H., Apr. 2007a. Semi-supervised feature selection via spectral
611 analysis. In: *Proceedings of the SIAM International Conference on Data*
612 Mining 'ICDM 07'. Minneapolis.

613 Zhao, Z., Liu, H., 2007b. Semi-supervised feature selection via spectral anal-
614 ysis. Tech. rep., Computer Science and Engineering (CSE) Department,
615 Ari-zona State University (ASU).

616 Zhao, Z., Liu, H., Aug. 2007c. Spectral feature selection for supervised and
617 unsupervised learning. In: *Proceedings of the 24th international conference*
618 on Machine learning 'ICML 07'. ACM, Corvalis, Oregon, pp. 1151–1157.