

Constrained spherical deconvolution on signal and ODF values

Eleftherios Garyfallidis, Samuel St-Jean, Michael Paquette, Pierrick Coupé, Maxime Descoteaux

▶ To cite this version:

Eleftherios Garyfallidis, Samuel St-Jean, Michael Paquette, Pierrick Coupé, Maxime Descoteaux. Constrained spherical deconvolution on signal and ODF values. IEEE International Symposium on Biomedical Imaging (ISBI 2013), Apr 2013, United States. pp.17. hal-00829328

HAL Id: hal-00829328

https://hal.science/hal-00829328

Submitted on 3 Jun 2013

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Constrained spherical deconvolution on signal and ODF values

Eleftherios Garyfallidis*, Samuel St-Jean*, Michael Paquette*, Pierrick Coupé[†], Maxime Descoteaux*

* Sherbrooke Connectivity Imaging Lab (SCIL), Computer Science department, Université de Sherbrooke, Sherbrooke, Canada

† CNRS, Laboratoire Bordelais de Recherche en Informatique, Bordeaux, France

For the purpose of the ISBI HARDI reconstruction challenge 2013 and for the categories DTI and HARDI acquisitions, we reconstructed the diffusion datasets using two well established methods: a) Spherical Deconvolution Transform (SDT) [1], [2] and b) Constrained Spherical Deconvolution (CSD) [3].

The SDT is a sharpening operation which transforms the smooth diffusion ODF into a sharper fiber ODF. The method is inspired by CSD [3] with, the main difference that the CSD is applied directly to the initial signal and the SDT directly to the ODF.

The idea here is that an ODF, for example the analytical Q-ball ODF ψ_{QBI} , can be formed by the convolution between the single fiber diffusion ODF kernel R and the true fiber ODF ψ_{SDT} .

$$\psi_{QBI}(\mathbf{u}) = \int_{|w|=1} R(\mathbf{u} \cdot \mathbf{w}) \psi_{SDT}(\mathbf{w}) dw$$
 (1)

Therefore, the deconvolution of ψ_{QBI} can recover a sharper ψ_{SDT} . We can derive the formula for the ψ_{SDT} using symmetrized spherical harmonics.

$$\psi_{SDT}(\mathbf{u}) = \sum_{j=1}^{R} 2\pi P_{l_j}(0) \frac{c_j}{f_j} Y_j(\mathbf{u})$$
 (2)

For the derivation and explanation of the formula see [1].

The deconvolution that we used here is a fast converging iterative process. Usually, taking 5 to 10 iterations for convergence. The main choice to be considered both for SDT and CSD is the estimation of the single fiber response function R. We assume that R is derived from a prolate tensor. The eigenvalues of this tensor are estimated from the voxels with FA > 0.7. In Tab. 1 we show for the trainings sets that the estimated eigenvalues can change considerably (values scaled by 1000).

R estimation	DTI	HARDI
SNR 10	$\lambda_1 = 17.7, \lambda_2 = 4.1$	$\lambda_1 = 13.6, \lambda_2 = 3.8$
SNR 30	$\lambda_1 = 18.3, \lambda_2 = 3.7$	$\lambda_1 = 16.6, \lambda_2 = 3.8$

TABLE I

In order to deal with the high levels of noise, the diffusion weighted (DW) datasets for SNR 10 and 20 were denoised with the adaptive nonlocal means [4] using a rician noise model. As proposed in [5], each DW images were processed independently. The DW dataset with SNR 30 was left intact and no further denoising was performed.

In order to find the best parameters for the methods described here we created a connectivity matrix after generating deterministic streamlines from the ODFs of the training set. We finally selected the parameters which minimized the number of missing and false bundles in the training set and used those with the test data. In Fig.1 we see results from an ROI from slice Y=22 of the testing dataset reconstructed with CSD in A and C and with SDT in B and D. The




Fig. 1. ROI [14:24, 22, 23:33] of the denoised test dataset (SNR 10) provided by the organizers of the HARDI reconstruction challenge 2013. A) CSD DTI, B) SDT DTI, C) CSD HARDI, D) SDT HARDI.

spherical harmonic order used for the DTI datasests was 6 and for HARDI 8 both for CSD and SDT. In Fig. 1 we observe that SDT performed better in the DTI category but CSD performed slightly better the HARDI category as it managed to resolve more crossing fibers. For the challenge we submitted all results with ODFs saved as spherical harmonic coefficients of order 8. The source code for the methods described in this paper is available at dipy.org.

REFERENCES

- M. Descoteaux, R. Deriche, T. R. Knösche, and A. Anwander, "Deterministic and probabilistic tractography based on complex fibre orientation distributions," *IEEE Transactions in Medical Imaging*, vol. 28, pp. 269–286, Febuary 2009.
- [2] M. Descoteaux, High Angular Resolution Diffusion MRI: from Local Estimation to Segmentation and Tractography. PhD thesis, University of Nice-Sophia Antipolis, 2008.
- [3] J.-D. Tournier, F. Calamante, and A. Connelly, "Robust determination of the fibre orientation distribution in diffusion mri: Non-negativity constrained super-resolved spherical deconvolution," *NeuroImage*, vol. 35, no. 4, pp. 1459–1472, 2007.
- [4] J. V. Manjón, P. Coupé, L. Martí-Bonmatí, D. L. Collins, and M. Robles, "Adaptive non-local means denoising of mr images with spatially varying noise levels," *Journal of Magnetic Resonance Imaging*, vol. 31, no. 1, pp. 192–203, 2010.
- [5] M. Descoteaux, N. Wiest-Daesslé, S. Prima, C. Barillot, and R. Deriche, "Impact of rician adapted non-local means filtering on hardi," in *Medical Image Computing and Computer-Assisted Intervention (MICCAI)*, vol. 5242, pp. 122–130, 2008.