Control of the moisture content of growing media by time domain reflectometry (TDR)

Philippe Morel, Jean-Charles Michel

► To cite this version:

Philippe Morel, Jean-Charles Michel. Control of the moisture content of growing media by time domain reflectometry (TDR). *Agronomie*, 2004, 24 (5), pp.275-279. 10.1051/agro:2004023 . hal-00886034

HAL Id: hal-00886034

<https://hal.science/hal-00886034>

Submitted on 1 Jan 2004

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Control of the moisture content of growing media by time domain reflectometry (TDR)

Philippe MOREL*, Jean-Charles MICHEL

UMR A 462 SAGAH (Sciences Agronomiques Appliquées à l'Horticulture), INRA-INH-Université d'Angers, 42 rue Georges Morel, BP 57, 49171 Beaucouzé Cedex, France

(Received 24 June 2003; accepted 7 May 2004)

Abstract – The irrigation of pot crops requires considerable follow-up because the autonomy of the water reserve of the growing medium is low in relation to plant water requirements. Computerised systems for irrigation management are therefore under investigation. Time domain reflectometry (TDR) was used on different peat-based mixtures to which perlite or composted bark were added in volumetric ratios of 0, 25, 50, 75 and 100%. Calibration equations (linear or polynomial) established between the water content and dielectric constant were obtained for each mixture. Their precision is highly satisfactory ($R^2 > 0.95$), except for the mixture with 100% perlite. However, this method requires an equation per growing medium. We therefore attempted to establish a general formula that could be applied to binary peat-based mixtures. We tested second-order polynomial calibration equations, a function of the dielectric constant measured as well as the volume percent of complementary material added to the peat (bark or perlite). The precision of these equations is excellent for all mixtures ($R^2 > 0.96$). For all practical purposes, this approach would considerably simplify the use of TDR for computerised irrigation management because it would introduce only a limited number of parametric equations into the irrigation system.

irrigation management / TDR / pot crop / growing medium

1. INTRODUCTION

Irrigation management for pot crops is delicate because the quantity of water available to the plant is low as a result of the limited volume of the growing medium explored by roots. The water content of the growing medium varies rapidly, ranging from a value close to saturation after irrigation to a dryness level that is sufficient to cause the plant to wilt after several hours of evapotranspiration. The reverse phenomenon is observed with oxygen content at the level of the roots, where it may become and remain very low after irrigation if the climatic demand is limited, leading to a high risk of oxygen deficiency.

Water supply management and, as a result, the supply of air, is therefore crucial in a soilless culture. The measurement of water potential of the growing medium by tensiometry has been used with success over the last few years [3, 7]. However, this method has met with reticence among professionals. One of the reasons for its lack of popularity is the relative complexity of its installation (from the probe to the electro-valve of irrigation) as well as the fragility of the tensiometer itself. The use of sturdier equipment would therefore remove one of the problems standing in the way of the development of these techniques.

Fairly recent research [4, 8] has shown the advantages of Time Domain Reflectometry (TDR) for directly measuring the

soil water content. The principle of this technique is to measure the apparent dielectric permittivity of the soil (constant K_a), using a metal probe with an electromagnetic wave train running through it. The transmission time of these waves in the guide is a function of the length of the rods in the guide as well as of the dielectric constant of the material in which the probe is located. This constant depends on the type of matter (organic or mineral) as well and, above all, on its water content. Therefore, there is a direct relationship between the water content of the matter and the dielectric constant measured. The equation that determines this relationship is a polynomial according to Topp et al. [8], whereas it is linear for Ledieu et al. [4], where the calibration coefficients of these equations depend on the type of soil and especially on its organic matter content.

However, these equations are not directly applicable to growing media which often contain high proportions of organic matter. This has led different authors to look for the calibration equations the most well-suited to different materials. Among them, the work of Pépin et al. [6] on peat, Anisko et al. [1] on sand, composted bark and peat (alone or in a mixture), and Kipp and Kaarsemaker [2] on rockwool and granular material (perlite, coir dust and pumice stone), deserve special mention. For each type of material, specific equations were determined with excellent regression coefficients.

* Corresponding author: morel@angers.inra.fr

The use of TDR to determine the water content of a growing medium seems possible on this type of material, provided that its calibration equation is known. However, in practice, the application of this method is more delicate than it would appear since growing media are often mixtures of several very different materials with variable volume percents. It is difficult to imagine the necessity of determining a specific calibration equation for each mixture. Therefore, the aim of our work was to see if calibration equations could be developed to include the measurement of K_a as well as the volume percent of complementary material added to the peat and if the user's task could be simplified by simply indicating the type of mixture and the percent of the components, in the event that these formulas were included in the irrigation system.

2. MATERIALS AND METHODS

2.1. Laboratory measurements

In order to obtain reliable and reproducible moisture content measurements, samples were prepared according to the standardised European method, NF EN 13041 [9]. This method especially guarantees initial wetting and packing of the homogeneous growing medium. After preparation, each sample (cylinder of 100 mm in diameter and 100 mm in height) was subjected to increasing water potentials (−1, −2, −3, −4, −5, −7.5, −10, −15, −17.5 and −20 kPa) on a suction table. The water content for each potential was estimated for three replications by weighing. In two other replications, an 8-cm-long TDR probe was introduced into the growing medium cylinder and kept in place throughout the entire trial. These probes were linked, via a multiplexer, to a device that served both as a wave transmitter and as a data acquisition centre at the same time (Trase 6050X1 from Soil Moisture Equipment Corp., Ca., USA). The values of the corresponding dielectric constant K_a were also recorded at the same time as samples were taken to measure water content.

Measurements were made on different mixtures of *Sphagnum* peat, maritime pine bark and perlite (Tab. I). The peat, with a granulometry of approximately 10 mm, came from the Baltic States. The bark, provided by the 'Terreaux de France- Faliénor' Company (Vivry, France), was composted and had a granulometry of less than or equal to 10 mm.

2.2. Models of adjustment for calibration curves

Calibration curves were calculated for each material on the basis of real moisture content and K_a taken from media placed on a vacuum table. Three regression models were used to evaluate the moisture content θ of the growing medium from K_a , two of which are commonly found in scientific literature:

- the polynomial equation of Topp et al. [8]

$$\theta = \alpha_0 + \alpha_1 K_a + \alpha_2 K_a^2 + \alpha_3 K_a^3$$

- the linear equation of Ledieu et al. [4]

$$\theta = \beta_0 + \beta_1 \sqrt{K_a}.$$

Table I. Mixtures used for measuring moisture content and K_a .

% of perlite and bark in mixture	Perlite	Composted bark
0	PER0	BARK0
25	PER25	BARK25
50	PER50	BARK50
75	PER75	BARK75
100	PER100	BARK100

We would like to propose a third model, linear, simpler and not mentioned in the literature, but which deserves to be evaluated since it may be advantageous to the relatively narrow potential interval used (−1 to −20 kPa) in the event that irrigation management by TDR is developed on growing media. This linear equation is solely a function of K_a :

$$\theta = \gamma_0 + \gamma_1 K_a$$

K_a is the apparent dielectric permittivity of the growing medium, and $\alpha_0, \alpha_1, \alpha_2, \alpha_3, \beta_0, \beta_1, \gamma_0, \gamma_1$ are adjustment parameters.

3. RESULTS

3.1. Calibration curves specific to the different mixtures

Tables II, III and IV give the coefficient values for the three equation models and the nine growing media tested. They also indicate the precision of these equations by the corresponding determination coefficient R^2 . For most of the growing media, the polynomial equation gives very representative values of the real moisture content, with R^2 greater than 98%. Only the one applied to 100% perlite was a little less reliable. The linear equation of the Ledieu type [4] is also acceptable (R^2 greater than 0.96 in most of the cases), although it is a little less accurate, especially for mixtures with perlite. The simple linear equation also provides good results. For practical applications in soilless culture, these simpler models could therefore be used.

3.2. Calibration curves determined by type of mixture

The preceding equations are highly representative of each mixture but they also reveal the strong influence of the composition of the mixture on K_a . As can be seen in Figures 1 and 2, incorporating perlite or bark, even in limited quantities (25%), leads to a major deviation from the curve. Therefore, for a K_a value of 25, for example, the moisture content is 51% for the peat but 60.5% for the mixture with 25% perlite and 66% with 25% bark. It is therefore clear that the user of a given growing medium who wants to use TDR to manage irrigation must know the exact characteristic equation of his mixture or run the risk of obtaining inaccurate results.

A more relevant solution would be to introduce complementary data into the model, making it possible to take the content

Table II. Calibration coefficients for a polynomial type of equation – 8-cm probe placed vertically – 10 measurements per mixture.

	Equation model $\theta = \alpha_0 + \alpha_1 K_a + v_2 K_a^2 + \alpha_3 K_a^3$				
	α_0	α_1	α_2	α_3	R ²
Peat 100%	19.601	1.169	0.007	−0.0001	0.9977
Bark 25%	30.225	−0.863	0.156	−0.003	0.9970
Bark 50%	−22.979	7.549	−0.223	0.003	0.9614
Bark 75%	38.673	−1.382	0.203	−0.004	0.9970
Bark 100%	77.659	−12.906	1.278	−0.035	0.9903
Perlite 25%	−4.596	5.496	−0.222	0.004	0.9929
Perlite 50%	17.819	1.617	−0.018	0.001	0.9949
Perlite 75%	10.571	3.315	−0.166	0.007	0.9847
Perlite 100%	10.955	3.515	−0.163	0.007	0.9333

Table III. Calibration coefficients for a linear type of equation (function of $\sqrt{K_a}$) – 8-cm probe placed vertically – 10 measurements per mixture.

	Calibration coefficients		
	$\theta = \beta_0 + \beta_1 \sqrt{K_a}$		
	β_0	β_1	R ²
Peat 100%	-9.003	12.137	0.9966
Bark 25%	-27.526	18.602	0.9928
Bark 50%	-22.035	18.207	0.9572
Bark 75%	-9.811	15.721	0.9916
Bark 100%	-4.573	14.697	0.9695
Perlite 25%	-22.616	16.875	0.9638
Perlite 50%	-6.578	12.988	0.9662
Perlite 75%	-2.895	11.778	0.9782
Perlite 100%	1.691	10.607	0.8680

Table IV. Calibration coefficients for a linear type of equation (function of K_a) – 8-cm probe placed vertically – 10 measurements per mixture.

	Calibration coefficients		
	$\theta = \gamma_0 + \gamma_1 K_a$		
	γ_0	γ_1	R^2
Peat 100%	22.779	1.092	0.9889
Bark 25%	12.620	2.096	0.9958
Bark 50%	17.793	2.006	0.9445
Bark 75%	21.425	1.937	0.9960
Bark 100%	22.375	1.985	0.9563
Perlite 25%	12.494	1.982	0.9849
Perlite 50%	14.989	1.890	0.9876
Perlite 75%	13.481	2.078	0.9843
Perlite 100%	13.970	2.270	0.8547

Calculated moisture content (%) **Figure 1.** Relationship between calculated θ and K_a for mixtures with bark. The obtained equations are highly representative of each mixture, but incorporated bark leads to a major deviation of the curve.

of material other than peat into account. It would thus be necessary for the user to introduce two simple data items into his irrigation programme (material and volume percent) instead of

Calculated moisture content (%) **Figure 2.** Relationship between calculated θ and K_a for mixtures with perlite. The obtained equations are highly representative of each mixture, but incorporated perlite leads to a major deviation of the curve.

Table V. Calibration coefficients for a third-order polynomial equation, a function of K_a and of the percent of perlite or bark (P) – 50 measurements per mixture.

Equation model $\theta = \theta_0 + \alpha_1 K_a + \alpha_2 K_a^2 + \alpha_3 K_a^3 + \alpha_4 P + \alpha_5 P^2 + \alpha_6 P^3$		
Coefficients	Mixtures with perlite	Mixtures with bark
α_0	4.052	-6.879
α_1	2.499	3.488
α_2	-0.024	-0.047
α_3	$6.91 \cdot 10^{-5}$	$2.37 \cdot 10^{-4}$
α_4	0.418	0.464
α_5	-0.007	-0.0046
α_6	$4.07 \cdot 10^{-5}$	$1.77 \cdot 10^{-5}$
R^2	0.999	0.981

Table VI. Calibration coefficients for a second-order polynomial equation, a function of K_a and of the percent of perlite or bark (P) – 50 measurements per mixture.

Equation model $\theta = \alpha_0 + \alpha_1 K_a + \alpha_2 K_a^2 + \alpha_3 P + \alpha_4 P^2$		
Coefficients	Mixtures with perlite	Mixtures with bark
α_0	6.089	-0.653
α_1	2.343	2.797
α_2	-0.017	-0.024
α_3	0.191	0.367
α_4	-0.0011	-0.002
R^2	0.984	0.957

introducing the regression coefficients for each mixture. We therefore looked for a simple relationship between θ and K_a , on the one hand, and the percent of perlite or bark in the mixture, on the other. Second- and third-order polynomial equations were tested. Tables V and VI give the results of these tests, with the corresponding R^2 determination coefficients.

R^2 is greater than 0.98 with perlite, regardless of whether the equation is second or third-order. The small difference observed between second- and third-order equations led us to choose the simplest, as can be easily seen in Figure 3.

The results for mixtures with bark are a little less precise but remain satisfactory because R^2 is close to 0.96 in the two models. As in the case of perlite, the small difference observed between the second- and third-order equations led us to choose the simplest one. Figure 4 confirms the close correlation between the real moisture content and the moisture content calculated from a second-order polynomial equation.

4. DISCUSSION

The results obtained in the laboratory confirm that it is possible to obtain a very good estimate of the water content of a growing medium from the measurement of the dielectric con-

Calculated moisture content (%) **Figure 3.** Linear regression between real moisture contents and calculated moisture contents according to a second-degree polynomial equation, as a function of K_a and the percent of perlite ($y = 0.9845x + 0.5866$ with $R^2 = 0.98$). Note the very close correlation between the real and calculated moistures.**Calculated moisture content (%)** **Figure 4.** Linear regression between real moisture contents and calculated moisture contents according to a second-degree polynomial equation, as a function of K_a and the percent of bark ($y = 0.9575x + 2.1337$ with $R^2 = 0.96$). The correlation between the real and calculated moistures is satisfactory but a little less close than for perlite.

stant K_a , by using a specific calibration equation for each growing medium. For moisture ranges commonly found in growing media (between -1 and -20 kPa), linear and second- and third-order polynomials provide good results. This similarity of results between the different models can certainly be explained by the low amplitude of water potential variation in soilless systems (between -1 and -15 kPa in most cases) and water content, which always remains high (greater than 20% of the volume).

However, we also clearly demonstrated that the type of material had a strong influence on the value of K_a , independent of the water content. Even for totally organic materials such as peat/bark mixtures, differences in moisture content for the same value of K_a may be as high as 20%, depending on the volume percent of each component. This strong sensitivity to the type of mixture may stand in the way of its development as a method for irrigation management. Generally speaking, growing media are usually a mixture of different materials. It is

therefore not possible to propose a specific calibration equation for each of them. This is why we tried to simplify the user's task by seeing if it was possible to find a single equation for mixtures made up of two materials, a case frequently encountered in cultivation practices. Therefore, K_a is a factor in this equation as is the percent of complementary material added to the peat. On peat-based mixtures that contain increasing quantities of perlite and composted maritime pine bark, a second-order polynomial equation provides a totally satisfactory estimate of the moisture content. It is therefore valid to introduce the volume percent of perlite or bark into the calibration equation.

5. CONCLUSION

This work showed it is possible to measure precisely the moisture of a growing medium by TDR using a specific calibration equation (for each mixture) or a general formula (second-order polynomial calibration equations, a function of the dielectric constant K_a and the volume percent of complementary material added to the peat). From a practical point of view, the use of TDR to manage irrigation would be simpler because the horticulturist would only need to provide the type of complementary material added to the peat and its volume percent since the computer would already have the corresponding calibration equation in its database. But one question still remains: what is the validity of these calibration equations based on measurements made in the laboratory, for use under growing conditions? We must question their long-term reliability, knowing that the characteristics of an organic growing medium can change over a period of time. A recent experiment, carried out with four different substrates on a *Chrysanthemum* $\times$ *grandiflorum* cultivation [5], showed the reliability of general calibration equations; but the length of growing time was short in this trial (only 13 weeks) and the growing media evolved very

little during the cultivation. Therefore, experiments with longer growth cycles (several months) will be necessary to validate this method, before it is possibly used for computerised irrigation management of different pot or container crops.

Acknowledgements: The authors would like to thank Gilles Guillemain and Odile Douillet for their contribution to tests and analyses made within the framework of this study, and Mrs Wagman for the English translation of the text.

REFERENCES

- [1] Anisko T., NeSmith D.S., Lindstrom O.M., Time domain reflectometry for measuring water content of organic media in containers, *HortSci.* 29 (1994) 1511–1513.
- [2] Kipp J.A., Kaarsemaker S.C., Calibration of time domain reflectometry water content measurements in growing media, *Acta Hortic.* 401 (1995) 49–55.
- [3] Lachurie J., Morel P., Gestion de l'irrigation à partir des paramètres du substrat, in: ASTREDHOR, L'irrigation en pépinière hors-sol, Paris, 1999, pp. 39–52.
- [4] Ledieu J., de Ridder P., de Clerck P., Dautrebande S., A method of measuring soil moisture by time domain reflectometry, *J. Hydrol.* 88 (1986) 319–328.
- [5] Morel P., Guillemain G., Mesure de la teneur en eau de différents substrats par TDR en culture de chrysanthème en pot, *P.H.M. Rev. Hortic.* 450 (2003) 36–41.
- [6] Pépin S., Plamondon A.P., Stein J., Peat water content measurement using time domain reflectometry, *Can. J. Forest Res.* 22 (1992) 534–540.
- [7] Rivière L.M., Morel Ph., Loiseau M., Laury J.C., Mesure du potentiel hydrique des substrats de plantes en pots au moyen de tensiomètres, *P.H.M. Rev. Hortic.* 316 (1991) 33–39.
- [8] Topp G.C., Davis J.L., Annan A.P., Electromagnetic determination of soil water content: measurements in coaxial transmission lines, *Water Resour. Res.* 16 (1980) 574–582.
- [9] NF EN 13041. Soil improvers and growing media – Determination of physical properties – Dry bulk density, air volume, water volume, shrinkage value and total pore space, AFNOR (2000).