



Influence of the variations in the main micro-climatic factors of the fattening pig house

C. Texier, B. de La Farge, R. Granier

► To cite this version:

C. Texier, B. de La Farge, R. Granier. Influence of the variations in the main micro-climatic factors of the fattening pig house. *Annales de zootechnie*, 1979, 28 (3), pp.353-353. hal-00887896

HAL Id: hal-00887896

<https://hal.science/hal-00887896>

Submitted on 11 May 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

— The digestive disorders (diarrhoea) following weaning can be largely limited through the control of the climatic conditions, the utilization of slatted floor and especially a discontinuous batch management allowing the cleaning, disinfection and non-utilization of the rooms between each passage of animals.

Influence of the variations in the main micro-climatic factors of the fattening pig house

C. TEXIER, B. DE LA FARGE, R. GRANIER

*I.T.P., Service Bâtiment Environnement,
149, rue de Bercy, 75595 Paris Cedex 12
I.T.P., Service Bâtiment et Environnement,
34, bd de la Gare, 31079 Toulouse Cedex
I.T.P., Station Expérimentale, Les Cabrières,
12200 Villefranche-de-Rouergue (France)*

The experimental building used was a fattening pig house of the Danish type divided into 4 identical rooms with a capacity of 32-40 pigs each. Every room was fitted with a dynamic ventilation system (pressure above atmospheric) with rates ranging between 50 and 740 m³/h/pig and a heating system by radiation whose capacity ranged from 100 to 260 millithermies/hour/pig.

By means of an automatic regulator (I.T.P.(*) patent) it was possible at any moment to obtain different ambient conditions from one room to another.

The climatic data were recorded continuously until the slaughtering of the first group of animals.

Six trials were made from 1976 to 1978 from which the following conclusions can be drawn:

— optimum ambient conditions are obtained at high temperatures (at least 20 p. 100 at the resultant dry temperature),

— association of a low ventilation rate (30 m³/hour/pig) and a high air velocity (2.5 m/s) leads to the best growth performance,

— the feeding level should be taken into account when choosing the ambient conditions as *ad libitum* fed pigs are less susceptible to climatic variations than restricted animals.

Deodorization of pig manure in the piggery

B. LEFÈVRE, Michèle HEDUIT

*C.T.G.R.E.F., Division Qualité des Eaux, Pêche et Pisciculture,
14, avenue de St-Mandé, 75012 Paris
G.I.D.A./I.T.P., 149, rue de Bercy, 75595 Paris Cedex 12*

The aim of this study was to test the efficiency of a treatment of manure deodorization by two air-injectors blowing directly in the dunging gutter of the piggery.

Two fattening periods were observed. In the first one the ventilation times varied from 12.5 p. 100 (5.2 kg. O₂/day) to 50 p. 100 working (20.9 kg O₂/day). In the second batch, from 50 p. 100 to 100 p. 100.

(*) I.T.P. : Institut Technique du Porc.