

# Structure and hydrogeochemical functioning of a sparkling natural mineral water system from a multidisciplinary approach: a case study from southern France

Jean-Christophe Maréchal, Patrick Lachassagne, Bernard Ladouche, Benoît Dewandel, Sandra Lanini, Paul Le Strat, Emmanuelle Petelet-Giraud

▶ **To cite this version:**

Jean-Christophe Maréchal, Patrick Lachassagne, Bernard Ladouche, Benoît Dewandel, Sandra Lanini, et al.. Structure and hydrogeochemical functioning of a sparkling natural mineral water system from a multidisciplinary approach: a case study from southern France. Hydrogeology Journal, 2014, 22 (1), pp.47-68. 10.1007/s10040-013-1073-1 . hal-00944206

**HAL Id: hal-00944206**
**https://brgm.hal.science/hal-00944206**

Submitted on 10 Feb 2014

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Structure andhydrogeochemicalfunctioningof a sparkling natural mineral water system determined usinga multidisciplinary approach: a case study from southern France

JC. Maréchal[1], P. Lachassagne[2], B. Ladouche[1], B. Dewandel[1], S. Lanini[1], P. Le Strat[3], E. Petelet-Giraud[1]

[1] BRGM -1039, rue de Pinville - 34000 Montpellier, France; http://www.brgm.fr.jc.marechal@brgm.fr

[2] Danone Waters - Evian Volvic World Sources - BP 87, 11 av.Général Dupas - 74503 Evian-les-Bains Cedex, France. patrick.lachassagne@danone.com

[3]19, chemin du champ Juvénal - 34170 Castelnau-le-Lez, France

## ABSTRACT

Natural mineral waters (NMW), often used to produce bottled water, are of high socio-economic interest and need appropriatemanagement to ensure the sustainability of the resource. A complex sparkling NMW system at La Salvetat, southern France, was investigatedusing a multidisciplinary approach. Geological and geophysical investigations, pumping test analyses, time-series signal processing, hydrogeochemical and isotopic data (both stable and radiogenic), and numerical modelling provided complementary information on the geometry, hydrodynamic characteristics and functioning of this mineral system.The conceptual model consists of a compartmentalizedreservoir characterized by twosubvertical,parallel deeply-rootedhydraulically independent permeable structures that arefed by deep $CO_2$-rich crustal fluids.The non-mineralized shallowaquifer system corresponds to a fissured layer within the weathered zone that is recharged by leakage from the overlying saprolite. This surficial aquifer responds rapidly to recharge (40-80 days), whereas the deep system's response to recharge is much longer (up to 120 days). This research demonstrates the need for multidisciplinary

approaches and modelling (quantity, hydrochemistry) for understanding complex NMW systems. This knowledge is already being applied by the bottling company that manages the resource at La Salvetat, and would be useful for conceptualizing other NMW sites.

Keywords:thermal conditions, $CO_2$, fractured rock, natural mineral water, France

**NOTE TO COPYEDITOR – PLEASE INSERT THE FOLLOWING BELOW THE RECEIVED/ACCEPTED DATE AND ABOVE THE AUTHOR CONTACT DETAILS:**

Published in the theme issue 'Hydrogeology of Shallow Thermal Systems'

## 1. INTRODUCTION

Sparkling natural mineral waters, and more generally natural mineral waters (NMW), often used to produce bottled water, are of socio-economic interest. In order to sustain these resources, appropriate management is needed that is well informed by local hydrogeological understanding.

Hydrothermal systems comprise the following three main geological components: water, heat and permeability(Clemente and Villadolid-Abrigo 1993; Lachassagne et al. 2009). Sparklingnaturalmineral water systems comprise water, $CO_2$ and permeability so water and gas can flow and rise to the land's surface. Geogenic $CO_2$may originate from three sources: metamorphism of carbonate rocks in the Earth (Kerrick and Caldeira 1998), transformation of organic matter during oil, gas and coal formation (Battani et al. 2000), or degassing of the mantle(Shipton et al. 2005). Consequently, in most cases, $CO_2$ is of deep origin. In crystalline rocks, deep fractures create the required permeability to bring the $CO_2$ to the surface, often as springs. At a relatively shallow depth (tens to hundreds of meters), these structures also constitute the drilling targets for safely abstracting the NMW. Therefore, the identification of the

geometry, hydrodynamic properties, extent(both laterally and with depth), and thickness of such permeable structures are the key factors for correctly understanding, tapping, managing, and protecting the mineral water system.

In crystalline rocks, the hydrodynamic properties of shallow (0-100 m) aquifers, and their relationships with weathering processes are now well characterized, with comprehensive conceptual models (Dewandel et al. 2006; Dewandel et al. 2011; Lachassagne et al. 2011). Deeper, nuclear waste storage projects have achieved very precise characterization of the (low permeability) fractured network of crystalline rocks, but in areas specifically chosen to avoid deep fracturing (Gustafson et al. 2009; Morosini and Rhen 2000). Thus, it appears that the precise characterization of deep permeable structures is very rare, and often based on conjecture and/or uncertain assumptions.This research is devoted to characterizing such complex NMW structures.

Another objective of the research was to show that such complex natural mineral water systems require multidisciplinary approaches, combining several techniques, in order to propose an appropriateprecise, realistic and robust conceptual model to tackle this complexity. The approach used combines geological, geophysical, hydrodynamic and times series analysis, hydrogeochemical and isotopic data, and a comprehensive numerical model in order to characterize and simulate the permeable reservoir of a NMW system in crystalline rocks. This approach is applied to the La Salvetatsparklingnatural mineral water system in southern France which is bottled.The knowledge about the structure and functioning of this mineral water system is of high interest for the bottling company for the development, sustainable management and protection of its spring. Developing a realistic conceptualization for a well characterized site is also of broad interest in order to inspire conceptualizations of other NMW sites.

## 2. STUDY AREA

75 The sparkling water spring at La Salvetat (Hérault region, southern France) has been
76 known at least since the Middle Ages, particularly by the Santiago de Compostella pilgrims who
77 rested and bathed at the Rieumajou spring. The spring has been operated for NMW bottling by
78 the Danone group (Evian Volvic World Sources, Danone Waters France) since the early 1990s,
79 and is now, together with forestry and traditional mountain agriculture, one of the key drivers of
80 the local economy and employment. This NMW spring emerges in a bedrock region composed
81 primarily of metamorphic rockswithout obvious visible tectonic structures at the surface. The field
82 is located south of the Ravègehydropower lake dam within the large south eastern France $CO_2$
83 region (an area where numerous carbonate-rich springs occur), which is part of the larger $CO_2$
84 Alpine foreland (Blavoux and Dazy 1990).The reservoir is currently exploited by six wells (B1,
85 R1, R2, R3, R5 and R6, **Erreur ! Source du renvoi introuvable.**). Observation boreholes (R4
86 inoperative well, P1, P3, MLC2, ML3, Pz1 to 7) are used for reservoir monitoring. Recently, five
87 new cored 200 m-long exploration boreholes were drilled (HF1 to HF5). The data from numerous
88 older wells, now closed, are also available.

89 The local climate is predominantly Mediterranean with a strong mountainous
90 ("Cévenole") influence. During the 1993-2008 period, the mean annual rainfall was 1,444 mm
91 with a mean annual potential evapotranspiration of 806 mm. A reservoir model(Ladouche et al.,
92 BRGM, unpublished data, 2013), calibrated using the daily time series of shallow aquifer water
93 table fluctuations (water supply Port well) and runoff (at the 48 $km^2$AgoutRiver crystalline
94 watershed scale), provides estimates of effective rainfall (920 mm/yr), recharge to the shallow
95 aquifer (169 mm/yr) and runoff (751 mm/yr).

96 ## 3. METHODOLOGY

97 The multidisciplinary approach, implemented to characterize the permeable reservoir of
98 La Salvetat NMW field, comprised four stages. The first involved a detailed geological study
99 (lithology, weathering, sequence stratigraphy, structural geology, fissure and

fractureidentification) and a field hydrogeological study. The geological approach combined a pole-dipole geophysical survey(14 mostly north-south profiles with an investigation depth of about 120 m totaling about 16.5 km performed in 2011 - Figure 1), and geological field investigation, involvinga comprehensive survey of the outcrops and their comparisonto local lithotypes to complement the 1:50000 scale BRGM geological map (Demange et al. 1995). The geological field investigation also comprised the geological reinterpretation of all available cores (11 boreholes), cuttings (3 boreholes), and existing geological logs for thoseboreholes where the cuttings and cores were no longer available, along with macroscopic and microscopic (thin section) analysis. In the studied area (Fig. 1), due to the weathering, the outcrops are small in size (less than a few square meters), and mostly restricted to granite veins that appear to be less weathered than the nearby geological formations. There the fracturing is mostly linked to weathering processes.

The field hydrogeological approach was primarily focused on characterizing the springs (fresh water and NMW), particularly during the La Raviègelake's low water-level period.To characterize the hydrodynamic properties of the aquifer, pumping tests and interference tests between production wells wereanalyzed. The interpretation of pumping tests in crystalline aquifers is a difficult task, as groundwater flow can be fractionalized (Black 1994), ie. controlled by the hydraulic conductivity of fractures, fracturedensity and orientation, their relationship with the low-hydraulic-conductivity blocks or matrix (Maréchal et al. 2004), and the geometry of the faults or intrusive bodies acting as permeable or impervious structures (Dewandel et al. 2011). To reveal the various aspects of the hydrogeological properties of such a complex hydrogeological system, and particularly the geometry of fractured zones tapped by NMW pumping wells, careful attention was paid to diagnosing the test responses prior to modelling with an analytical solution. Diagnoses were based on the analysis of derivative drawdown curves on log-log plots, which allows flow-regime identification (Ehlig-Economides 1988; Renard et al. 2009). According to the results of the diagnosis, suitable analytical models for partitioned(Nind

126 1965) or leaky aquifers (Hantush 1960)wereused in order to calculate the hydrodynamic and
127 geometric parameters of the aquifer.

128 The hydrogeological processes were characterised using a signal processing method
129 applied to the rainfall, piezometric level and fluid electrical conductivity time series. The functions
130 used (autocorrelation and cross-correlation) and their corresponding mathematical expressions
131 have been described by several authors (Mangin 1984). An analysis methodology was also
132 developed in this study to extract recharge information from the measured signal, disturbed,
133 amongst others factors, by pumping, thereby providing quantitative information on the recharge
134 rate and the dynamics of its transfer function. Piezometric and electrical conductivity variations
135 (O: system output) were explained by considering the input variables likely to influence the
136 system. This involved describing a Multiple Input Single Output (MISO) system(Kothyari and
137 Singh 1999). The calculations were performed using the Tempo software with a one-day time
138 step (Pinault et al. 2001).

139 Water chemistry and isotopic tracing (stable isotopes of water, strontium)were used in
140 order to constrain the hydrochemicalmechanisms and to understand the origin of the mineral
141 waters system. The pH, temperature and electrical conductivity were measured onsite on raw
142 water samples. Samples for cation, trace metallic element and Sr isotope determination were
143 filtered through 0.45 µm Millipore membrane filters and acidified (with ultrapure $HNO_3$ to pH<2).
144 Anions were determined by ion chromatography;cations and trace elements by ICP-MS. The
145 measurement uncertainties for major and trace elements are 5 and 10%, respectively. Oxygen
146 ($^{18}O$) and hydrogen (D) isotope measurements were done with a standardized method, using a
147 Finnigan MAT 252 mass spectrometer with a precision of ±0.1‰ vs SMOW for $\delta^{18}O$ and ±0.8‰
148 for δD. The $^{18}O/^{16}O$ ratio is reported as δ deviation (per mil) of this ratio in the sample from that
149 of the V-SMOW standard.Isotopic compositions are reported in the usual δ-scale in ‰. Analysis
150 of the $\delta^{13}C$ composition of the $CO_2$wasdoneby mass spectrometry with a precision of 0.1 ‰. The
151 $^{13}C/^{12}C$ ratio is expressed in per mil notation relative to standard V-PDB. In addition,strontium

isotope analyses on the main rocks and mineral phases were performed to better understand water-rock interactions.The objective was to define the isotopic signatures for strontium ($^{87}Sr/^{86}Sr$) in the main rocks comprising the La Salvetat reservoir in order to interpret the origin and variations in the isotopic strontium ratio in the sparklingNMW field. Chemical purification of Sr (~3 µg) was done using an ion-exchange column (Sr-Spec) before mass analysis according to a method adapted from(Pin and Bassin 1992), with total blank <1 ng for the entire chemical procedure. After chemical separation, around 150 ng of Sr was loaded onto a tungsten filament with a tantalum activator and analysed with a Finnigan MAT 262 multi-collector mass spectrometer. The $^{87}Sr/^{86}Sr$ ratios were normalized to $^{86}Sr/^{88}Sr$ ratio of 0.1194. An average internal precision of $\pm 10 \times 10^{-6}$ (2σm) was obtained and the reproducibility of the $^{87}Sr/^{86}Sr$ ratio measurements was tested by repeated analyses of the NBS987 standard, for which a mean value of $0.710230 \pm 18 \times 10^{-6}$(2σ, n=12) was obtained.

To determine the theoretical isotopic signature of water interacting with a given rock, a theoretical dissolution model must be used (Bullen et al. 1997). Such a dissolution model has been developed (Negrel et al. 2001) assuming that most of the Sr released by weathering comes from the following three main minerals: plagioclase, K-feldspar and biotite. Model parameters are: (i) Sr content in the main mineral phases (plagioclase, K-feldspar and biotite), (ii) their isotopic Sr composition ($^{87}Sr/^{86}Sr$), (iii) the proportion of each of these minerals in the studied rock and, (iv) the weatherability of each of these minerals(Petelet Giraud et al. 2003). The total rock sample and separate minerals were analysed for Rb and Sr content and $^{87}Sr/^{86}Sr$ isotopic ratio. The separation of K-feldspars, plagioclases and biotitewas performed by particle-size (on the 50-400 µmfraction), densimetric (K-feldspars, plagioclases and part of biotite) and magnetic separation (rest of biotite). The nature of the plagioclases was analysed by electronic microprobing: they can be classified as oligoclase (An90-70Ab10-30) and andesine (An30-50Ab70-50). Calcite separation in the Cipolin marble sample (R6 149.1) was performed by rock

177 stripping (thin sections and hand samples) using a microgrinder. The results of these dissolution
178 models were then compared to the water samples from the wells to explain their origin.
179 Finally a hydrodynamic and reactive hydrogeochemicalnumerical model was developed
180 to dynamically simulate the functioning of theNMWsystem. It was used to integrate all the
181 information provided by the multidisciplinary study, and to validate the conceptual model. The
182 modelling method selected is the networked reservoir and chemical reactor methodology (Collon
183 et al. 2002). It is based on the main assumption that piezometric levels and chemical
184 concentrations are uniform within each reservoir. The system modelled is then described by a
185 set of ordinary coupled differential equations translating water storage and chemical elements in
186 each of the variable volume reactors. The water-rock interactions were taken into account by
187 introducing aqueous phase chemical kinetics for certain reactive chemical elements. The
188 relevance of the model to reflect the system studied lies in the choice of the number of
189 reservoirs, the way they are connected, the laws chosen to describe the water and matter
190 exchanged amongst the reservoirs, and the choice of the reactive chemical elements and the
191 related chemical kinetics.

192 ## 4. RESULTS

193 ### 4.1. GEOLOGICAL STRUCTURE OF THE MINERAL WATER SYSTEM

194 The detailed geological approach confirmedthe overall high quality of the 1:50000
195 geological mapping (Demange et al. 1995) in the Rieumajou spring area. The main
196 lithotypeswere observed in the field and their distributions were well contoured, at least at the
197 scale of the map. The bedrock inLa Salvetat area is mostly composed of intensely folded and
198 foliated metamorphic rocks derived from a sedimentary sequenceoverlying a more ancient
199 granitic substratum. In the mineral spring area, this series exposes, from South to North, a
200 conformable succession, from bottom (South) to top (North) (**Erreur ! Source du renvoi**

**introuvable.**): (i) the Larnorthogneiss derived from a Cadomian granite metamorphosed during the Hercynian orogeny, and weathered prior to being covered by sediments and prior to being further metamorphosed; (ii) a Cambrian sedimentary sequence lying unconformably on the metamorphosed granite, and consisting of fourmain geological formations:

1)a50 to 100 m thick schist-quartzite Puech-Plô grey gneiss composed of ancient, coalescent anddetritic deltas aligned perpendicularly at contact between the ancient basement and the paleo sedimentary series;

2)a20 to 30 m thick quartzo-feldspathicMurat gneiss, a metamorphosed volcanic-sedimentary formation (conglomerates, leptynites) infilling the lowest points between the paleodeltas;

3)amore than 100 m thick Nagesparagneiss rich in calcic levels: plagioclase-rich gneiss, gneiss with calcic silicates and Cipolin marbles. This series is a prograding-retrograding platform which, in top partsis mostly carbonated. It shows a typical klupfelian carbonated deposit profile which provides a distal deeper facies, probably located at the south towards a coastal proximal located at the north with the following geological facies: clay-rich siltites, carved agrading alternations from a subsiding bay, coastal prograding alternations, tidal dunes, beach, and intertidal stromatolites. The analysis of the sedimentary signal shows that this carbonated platform series is transgressive on the Puech-Plô and the Larn Gneiss formations. In several wells, this series is duplicated with first (near the surface) the inverted series, and then the normal one. Moreover, the resulting inversion line (and also the series) is folded.

4) Late hercinian granite and pegmatite intrusive veins (tourmaline leucocratic granite and pegmatite).

225 The foliation is mostly N050 to 090°E (Figure 2). The units dip at 70 to 80° South to North;
226 consequently, these geological formations are considered to be deeply rooted and are still
227 crosscut in the boreholes at depths greater than 200 m.

228 The main outcome of the detailed geological mapping concerned the granite veins. The
229 authors of the 1:50000 geological map inferred that these veins resulted from the partial melting
230 of the other lithological units during metamorphism, and consequently, that they are conformable
231 (same dip) with the main foliation of the lithological units and effectively are sills “invading” the
232 other lithological units. However, the field survey clearly showed that the granite is much
233 younger and occurs as subvertical,N110 to N160°E oriented veins that are meters to tens of
234 meters thick and tens to hundreds of meters long. These veins are not conformable with the
235 other rocks as they cross-cut all the other lithologies (Figure 2).

236 These formations are deeply weathered with an up to 30 m thick cover of unconsolidated
237 saprolite. Differential weathering has resulted in higher relief granite veins (with several
238 outcrops), whereas the Nages formation rocks outcrop only very locally. As a consequence, in
239 the spring area, the outcrops are quite poor and do not allowperforming a detailed structural
240 analysis. As far as faults can be identified on cores, the drillings crosscut several fracture zones
241 which mostly seem to be dilational(no compressive tectoglyphs). Several fractures comprise
242 breccias that in places are cemented with calcite and/or silica and can show signs of
243 hydrothermal activity. It was possible to characterize the orientation and dip of 15open or
244 mineralized fractures observed on the cores. These fractures were oriented,using the foliation
245 measured in the well as a geometric reference. The following main results were obtained:
246 fracture orientationin the wells is mostly N100-110°E (n = 9), and then N130-140°E (n = 3), and
247 N020-030°E (n = 3).

248 Electrical profiles (survey lines shown in Fig. 1) clearly reveal the depth of the weathering profile.
249 Typically, the electrical resistivity isbelow 1000 Ω.m within the first 50 m below ground surface
250 (Figure 3). There is a sharp resistivity contrast at approximately 50 m, where the resistivity

increases to more than 5000 Ω.m,which can be followed within most of the Nages formation in Fig. 3 (M profile from X = 160 to 550 m and C profile from X = 120 to 340 m, and X = 600 to 840 m). In these profiles, the thickest granite and pegmatite veins appear as more resistant (higher electrical resistivity) bodies within the low resistivity weathering profile (X = 480 m on the M profile). However, apart from this result about some granite veins, the electrical profiles do not provide unambiguous information about the lithology, notably below the weathering profile. The electrical profiles also reveal enhanced weathering (or past hydrothermalism) along some lithological contacts, particularly the southern Puech-Plô/Murat and Nages contact (subvertical, about 150 m wide - locally much wider - 50 to 70 Ω.m structure that can be followed on most of the North-South electrical profiles; Fig. 3 - M profile from X = 90 to 155 m and C profile from X = 60 m to 120 m). The most interesting results from the geophysical survey are the deep (more than 100 to 120 m) subvertical conductive structures (locally down to about 10 Ω.m, but more frequently between 150 and 200 Ω.m; Fig. 3 - M profile from X = 550 m and C profile from X = 340 to 480 m). These structures are 30 to more than 50 m wide, are oriented N100-110°E, and coincide with the fractured zones in wells producing NMW (see the dotted blue curves on Figure 2). One of these structures, the southern one, identified on five North-South electrical profiles, seems to link the R4 area (West) at least to HF4 and B1 wells (East). The second structure, the northern one, only identified on two profiles due to the presence of the lake (which limited the geophysical measurements), links the area of R5 (West) with the HF2 area (East). These structures (HF2, HF4 boreholes) and some other conductive anomalies (HF1, HF3, HF5 boreholes) were targeted during the last drilling campaign, and only the HF2 and HF4 boreholes successfully tapped permeable NMW bearing fracture zones in the “southern” and “northern” structures.

### 4.2. PRELIMINARY HYDRODYNAMIC APPROACH

The synthesis of blowing discharge measurements performed during down-hole-hammer drilling shows that the fissured zone of the Puech-Plô formation is much less productive than the Nagesformation, with mean discharges 3 to 4 times lower. The productivity of the Nages formation is nearly nil within the saprolite (first 20 to 30 meters below ground surface) and is relatively higher within the underlying30 - 40 m thick fissured zone. Productivity is nil within the deeper unweathered rock, except where the borehole crosscuts a deep NMW bearing fracture.

Piezometric measurements available from the wells tapping the NMW bearing fractures show two East-West slight piezometric depressions corresponding to the two structures identified from geological and geophysical data (Figure 1). These depressions appear to be related to the natural flow within the mineral aquifer and to the pumping in the wells. The first piezometric depression extends from R4 to R1 (pumping in R1, R2, R3). The second one corresponds to R5 and R6 pumping. Most of the formerly flowing or still-existing NMW springs appear to be located at the intersection between the two East-West structures and the topographical low points (**Erreur ! Source du renvoi introuvable.** and **Erreur ! Source du renvoi introuvable.**). One main locationis West of each structure, at their lowest topographical point. The second one is a small North-South valley in the vicinity of R1 and R2 wells where the main NMW spring was located. There is no significant NMW outflow in the HF4-B1 area, which is interpreted as a consequence of the low permeability of the geological cover in this valley, as piezometric levels in the mineral aquifer in that area are aboveground level. Consequently, from these data, it can be inferred that the natural mineral water may have flowed naturally (i) upwards and then westward from the B1 area toward the main NMW spring (between R1 and R2) and then to R4, and (ii) from R5 (or even from HF2) to the springs located east of R6.

### 4.3. HYDRODYNAMIC PARAMETERS AND AQUIFER STRUCTURE FROM PUMPING TESTS

Data from 30pumping tests, a few hours to several monthsin duration, and performed on ten of the Rieumajou area wells were interpreted to establish interferences between the wells,

and to evaluate the geometry of the permeable formations and their hydrodynamic parameters. Except well R5,in which thescreened part mainly crosscuts a granite vein, all others are sited within the Nages gneiss. The tests were performed between 1990 and 2011 at the time of well drilling. During the pumping tests, water level changes in nearby wells and piezometers were also observed.

One example of a 10-day pumping test performed on well R4 in 2010 is presented (**Erreur ! Source du renvoi introuvable.**). R4 is 63.3 m deep and screened between 46.2 and 57.0 m into the NMW bearing fractures. The derivative curve is complex, but illustratesvarious typical flow regimes (**Erreur ! Source du renvoi introuvable.**):

- from the beginning of the test to 20 minutes duration describes the wellbore storage effect,
- from 20 to 50 minutes, the flat trend of the derivative curveis typical of infinite radial flow from which aquifer transmissivity can be calculated ($T=5.4x10^{-4}$ $m^2/s$),
- from 50 to 400 minutes, the derivative curve tends to a ½ slope, and the drawdown reaches two parallel no-flow boundaries,
- from 400 to about 6,000 minutes, the derivative curve follows a unit slope typical of bounded aquifers (at least two additional no-flow boundaries),
- finally, from 6,000 minutes to the end of the test, drawdown tends to stabilize, and the decrease of the derivative suggests leakage from shallow aquifers. Such a leakage effect was only observed in this well.

This diagnostic shows that R4 is located in a bounded aquifer, theboundaries of which are close to the well (between 50 and 400 minutes). In addition, the aquifer is connected to another aquifer (most probably the shallow aquifer) by leakage: consequently, this well is not exploited, as pumping might induce shallow aquifer water inflow. This test was interpreted using a rectangular aquifer model with seepage (Hantush 1960)with four orthogonal no-flow

boundaries, wellbore storage effect and well skin(**Erreur ! Source du renvoi introuvable.** - black curves). The evaluated aquifer surface is 0.09 $km^2$ (about 400 m length by 200 m wide).

Test diagnosis and modelling were carried outto interpret the 29 other pumping tests, the main results of which are summarized in **Erreur ! Source du renvoi introuvable.**andTable *1*.In summary, the interference tests clearly demonstrate that the site is partitioned into two approximately East-West direction compartments: a northern one (R5 and R6) and a southern one (R1-R2-R3-R4-P3-DAC). This result is supported by most of the test diagnoses. It is also highly consistent with the geophysical and piezometricdata.Diagnostic and pumpingtest modelling also provide information about the aquifer geometry. The southern compartment is characterized by a permeable (fractured) zone, about 0.1 $km^2$area (200x400 m approximately) and oriented ina near East-West direction (N105°E). Its eastern limit,however,is not well constrained. Its transmissivity is about 3 $x10^{-4}$ $m^2/s$ and is relatively constant from one well to another. Its storativity is about 5x $10^{-4}$. The northern compartment is also elongated in a near East-West direction and is probably smaller than the southern one; however, pumping tests were not long enough to reach all the boundaries. Transmissivity is similar to that of the southern compartment, but storativity is less, 2x $10^{-5}$.

Two of the pumping tests, at B1 and HF4, could not demonstrate any interference despite seeming to belong,geometrically and geologically, to the eastern continuation of the southern compartment. Nevertheless, interferences show that the two wells belong to the same fractured system (“B1” compartment). HF4 yieldeda high transmissivity (8x $10^{-3}$ $m^2/s$)corresponding to a zone a few meters wide. The geometry of compartment B1 is not well constrained, but from pumping tests,two parallel no-flow boundaries are reached relatively late after the start of the pumping (3 000 min). This leads to the interpretation of an apparently (depending on assumption on S) very large fractured zone (about 800 m wide); the orientation of this fractured zone was not constrained by the modelling of the pumping tests, but it was by the

351 geophysical data.As discussed below (section '*Multiple input single output'*), the piezometric time
352 series analysis confirms that the HF4-B1 compartment is the eastern prolongation of the R4-R1
353 compartment.

354 Several pumping tests show evidence of partial penetration (Table *1*), suggesting that the
355 fractured zone extends muchdeeper than the bottom of the wells, which generally do not exceed
356 100 to 120 m depth.

357 ### 4.4. HYDROGEOLOGICAL FUNCTIONING OF THE SYSTEM FROM TIME SERIES ANALYSIS

358 #### 4.4.1. PRELIMINARY DESCRIPTION OF HYDROLOGICAL TIME SERIES

359 Flow rate variations in the pumping wells (**Erreur ! Source du renvoi introuvable.**b)
360 generally follow the same pattern, i.e., because of the constraints dictated by NMW production,
361 flow rates are all increased or loweredsynchronously. Very few periods exist in which differential
362 flow rate variation is available.

363 Piezometry trends measured at R5 in the northern compartment show a correlation with
364 lake water level, which, according to dam management records, is low during the winter energy
365 production season and high in summer during the tourist season. For R6, time series are too
366 short to provide a basis for conclusion. The head in the aquifer is thus affected by the surface
367 hydraulic head imposed by the lake surface. At daily time scale, piezometric fluctuations at R5
368 are impacted by pumping but it is not possible to identify whether this is only due to pumping at
369 R5 or also at neighbouring wells. The very short-termpiezometric fluctuationsare due to the high
370 quadratic (non-linear) head losses in the R5 well visible in 2004 and 2008-2009 when pumping
371 rates are variable. Piezometricvariabilitytherefore appears to be essentially controlled by
372 pumping rates and by variations in the lake water level, while piezometric variations linked to
373 rainfall (recharge) appear to be negligible on short- and mid-timeframes(several days to several
374 weeks).

375 Piezometric trends in wells located to the South (R1, R2 and R3) do not appear to be
376 influenced by water level variations in the La Raviègelake. Piezometric trends at R1 and R2 are
377 very comparable, which confirms the existence of a hydraulic link between the two wells.
378 Piezometric time series for R3 also show similar trends to those measured at R1 and R2. The
379 piezometric variations appear to be controlled by pumping rate variations. Here again, these
380 piezometric variations are primarily linked to high quadratic head losses. In a similar way to R5,
381 piezometric variations induced by recharge are hidden in the short- (several days) and mid-
382 timeframes(several weeks) by variations induced by pumping.
383 For several years after being putinto operation (see R5, R6 and B1 because R1, R2, R3
384 data were not recorded for the first years of service), all wells show an initial decrease in
385 electrical conductivity (EC) over a period spanning several years (**Erreur ! Source du renvoi**
386 **introuvable.**). EC then becomes relatively stable and shows variations with a shorter
387 wavelength. Annual fluctuations inECat R5 are in the rangeof 100 µS/cm; the annual
388 amplitudeappears to be relatively synchronous with lake level variations: maximum EClevels
389 correspond to high water levels in the lake. Short-term pumping variations do not cause a
390 significant variation in the EC of pumped water. The gradual increase in pumping rates at R5 in
391 2009 (from 1 to 1.8 $m^3$/h), and again in 2010 (up to approximately 1.9 $m^3$/h), seems to causea
392 decrease in EC, as it did when the well was put into production (with R6 being put into
393 production in 2009, overall pumping in this compartment reached nearly 4 $m^3$/h as of 2010). In
394 the other wells (R1, R2, R3 and B1), theEC does not appear to be controlled by lake water level
395 fluctuations. Long-term oscillations observed in B1, R1 and R2 are explained below.

396 4.4.2. CROSS CORRELATION ANALYSIS

397 Cross-correlation analysis involved three input variables: rainfall (P), lake water level ($H_{Lake}$)
398 and the aggregate flow rates at wells (Qx+Qy). Output includedpiezometry (H-well) or water
399 mineralisation - EC, which is primarily controlled by $HCO_3$ and calcium content (**Erreur ! Source**

400 **du renvoi introuvable.**a, b and c). Rainfall-piezometry cross-correlograms (**Erreur ! Source du**
401 **renvoi introuvable.**a) are very noisy and show very low cross-correlation coefficients (<0.1)
402 indicating that the rainfall signal is highly filtered/dampened by the system. Maximum correlation
403 is observed for offsets ranging from 80-120 days. The shape of rainfall-piezometry cross-
404 correlograms provides an approximation of recharge impulse response; it is indicative of
405 hydraulic transfer within a weakly diffusive system. The end of the recharge impulse response
406 occurs at an offset of approximately 250 days. The memory effect (inertia) of the hydrosystem
407 cannot be assessed using the piezometric time series autocorrelogramas the wells' piezometry
408 is over-affected by other influences.Correlation of piezometry and ECwith lake water levels is
409 high for wells R5 and R6. Maximum lake - piezometry correlation in R5 is 0.6 for an offset of 0
410 days (**Erreur ! Source du renvoi introuvable.**b) (fast pressure transfer). Lake level –EC
411 correlation in R5 is not as high with a maximum of 0.13 for an offset ranging from 15 to 30 days:
412 EC increases when the lake level increases. For the other wells (R1, R2 and R3), no correlation
413 is observedbetween piezometry and lake level (diagrams not shown). Likewise, the ECof water
414 pumped from these wells is not correlated with fluctuations in the La Raviège lake level.
415 Logically, the correlation between pumping rate and measured piezometry is negative
416 (**Erreur ! Source du renvoi introuvable.**b) due, among other factors, to thelarge quadratic well
417 head losses. The cross-correlogram between the pumping rate (QR5) and ECin R5 (**Erreur !**
418 **Source du renvoi introuvable.**c) shows an inverse correlation.

419 ### 4.4.3. MULTIPLE INPUT SINGLE OUTPUT

420 The qualitative description of piezometric trends, water ECmonitoring and cross-correlation
421 analysis indicate that the variations linked to rainfall recharge are low-amplitudecompared to
422 other factors (La Raviège Lake levels for R5 and R6 and/or pumping rate). A multiple input
423 single output (MISO)deconvolutionanalysis wastherefore undertaken to highlight and better
424 characterize the recharge mode.

*In this model (see the example for well R1 -* ***Erreur ! Source du renvoi introuvable.****), the aim was to reproduce the output (piezometry) from three inputs: (1) recharge, (2) R1 well discharge rate,and (3) aggregate discharge rate other than from well R1 (ΣQ= QB1+QR2+QR3); QB1 being added in order to check the hypothesis that the B1 eastern compartment is the prolongation of the R4-R1 compartment. Calculation of piezometricimpulse response was capped at a value of 256 days, corresponding to an approximate duration of recharge impulse response in pressure transfer (****Erreur ! Source du renvoi introuvable.****a). The model reproducessatisfactorily the piezometric trends observed at well R1 with a Nash criterion(Nash and Sutcliffe 1970) equal to 0.79 (****Erreur ! Source du renvoi introuvable.****a) with the relative contributions of the various components shown in* ***Erreur ! Source du renvoi introuvable.****c, d and e. Average contributions for R1 and those calculated for the other wells using the MISO method are summarized in*

Table *2*. In R1, thevariation linked to rechargereaches 4.6 m, compared to nearly 9.5 m for pumping in R1, and nearly 14.4 m for aggregate discharge (ΣQ). Consequently, it is this last variable that mainly controls the long term changes in piezometry. The sensitivity analysis performed on QB1 demonstrates the hydraulic connection of the R4-R1 and HF4-B1 compartments, and thus confirms the geophysical and geological interpretation.

On the basis of the MISO deconvolution results (Figures8c, d and e), information related to the recharge process was extracted for each of the wells investigated. The cross-correlation analysis between rainfall and extracted recharge signal (water level (H) series deconvoluted from pumping effects using the MISO approach) is presented in**Erreur ! Source du renvoi introuvable.**. The piezometric response to the rechargeprocess is fast in the fissured horizon (Port well), with a maximum pressure transfer response of approximately 40-80 days after a rechargeevent (Figure 9a). The deep system's response to rechargeis much longer for well B1 (about 120 days) and wells R1 and R2 (around 100 days). The shape of the impulse response is indicative ofpressure transfer within a weakly diffusive system that can be attributed to: (i) the

low permeability saprolite, (ii) the Nagesstratiformfissured zone, and (iii) the very low permeability of the underlying unfractured bedrock for the NMW wells. The response gap between B1 and R1/R2 (around 20 days) appears to be consistent considering the local geological structure: the B1 aquifer structure may be “confined” by the overlying impervious granite vein, and the water-bearing structure at the origin of the Rieumajou springlocated between R1 and R2 may enhance the relationship between the deep fractures and the fissured horizon in surface.The responses of wells R3 and R5 are bimodal (**Erreur ! Source du renvoi introuvable.**b) with first a fast response and then a delayed response similarto the one observed on the other wells (B1, R1, R2) and a slightly faster response. The responsessuggest that these wells are better connected (pressure transfer) to the subsurface formations.

The MISO approach was also used to describe mineralisation trends (EC)in water. It can be used to track the deep component of the system, as $HCO_3$ content is linked to $CO_2$ of deep origin.An example of a deconvolution result is given for well R1 (**Erreur ! Source du renvoi introuvable.**b). As described previously, three inputs were considered: (1) pumping time series for well R1 (QR1), (2) aggregate discharge rate at the other wells ($\Sigma Q$ = QB1+QR2+QR3), and (3) recharge time series corresponding to the recharge time series previously deconvolutedfrompiezometric data. Calculation of mineralisation impulse response was assumed at amaximum value of 512 days, as the duration of mass transfer is intuitively longer thanthat of pressure transfer (256 days).The mineralisation trend at borehole R1 is reproduced satisfactorily with the MISO approach (Figure 8b, Nash = 0.75). Increased pumping rates (compared to mean pumping rate) cause a decrease in mineralisation. Variations in pumping rates in R1 generate changes in mineralisation ($\Delta$) in the range of -20 µS/cm at largetemporal scale (Figure 8d). Increases in other pumping rates ($\Sigma Q$) also result in decreased mineralisation (**Erreur ! Source du renvoi introuvable.**e). Thiscumulative pumping ($\Sigma Q$) plays a significant role in mineralisation trends, which once again confirms that wells R1, R2, R3 and B1 are

476 hydraulically connected and, additionally, are connected to the same deep, $CO_2$–rich water
477 reservoir. Recharge induces an increase in mineralisation with a long-term cumulative
478 effect(**Erreur ! Source du renvoi introuvable.**c): the succession of several wet cycles in 1994,
479 1995 and 1996 (1668 mm, 1637 mm and 2412 mm rainfall,respectively) generates a greater
480 mineralisation delta ($\Delta = +60$ µS/cm) than dry cycles in 2001 (932 mm) and 2005 (1145 mm),
481 ($\Delta < +10$ µS/cm a year). These results indicate that intensive recharge events do not result in a
482 dilution of the mineral waterby surface water. Instead, recharge events result in an increase in
483 water mineralization because of increased pressure on the deeper parts of the system. This
484 behaviour relative to recharge is similar to the one revealed for lake level increase.

485 ### 4.5. WATER-ROCK INTERACTION FROM HYDROCHEMISTRY AND ISOTOPE ANALYSIS

486 From the hydrogeochemical viewpoint (Table 3), the reservoir waters are characterised by
487 acalciumbicarbonatefacies(300 to 1200 mg/l of $HCO_3$) typical of the “deep component” and by
488 significant silica content (50 to 90 mg/l). The NMWtherefore representsa fairly specific facies
489 with typical basement water-rock interaction markers. The traditional indicators of high
490 temperature water-rock interaction (Millot and Négrel, 2007) are low in concentration (low
491 sodium content [<7 mg/l], and very low lithium [<0.1 mg/l] and boron [<0.15 mg/l] contents). The
492 NMW has a low chloride content (a few mg/l), this element being characteristic of the shallow
493 componentand mainly due to rainfall.

494 The carbon isotopic signature of $\delta^{13}C$ from the gaseous $CO_2$ ($\delta^{13}C$ ranges from – 5.6‰ to -
495 7.8‰) clearly demonstrates its mantle origin according to Deines(1970) andBlavoux et al.
496 (1982). In the $\delta^2H$ vs $\delta^{18}O$graph(**Erreur ! Source du renvoi introuvable.**), the water samples
497 are located between the global meteoric water line (Craig 1961), which globally represents
498 Atlantic origin rainfall, and the local meteoric water line determined for the Hérault
499 region(Ladouche et al. 2009), affected by air masses from the Mediterranean. The graph does
500 not highlight isotopic exchange phenomena, such as exchange with gaseous $CO_2$ or with rock

501 silicates at high temperature. The waters sampled in the shallow aquifer that were recharged at
502 about 700 m a.s.l.are slighly more enriched in heavy isotopes compared to the NMW from the
503 wells, which suggests recharge at a slightly higher elevation: 800 ± 50 m a.s.l. with a -0.3 ‰/100
504 m gradient (Ladouche et al. 2009),but that is nevertheless compatible with a local recharge. A
505 paleoclimatic effect does not have to be factored in to explainthe depleted
506 isotopicsignaturesfrom wells B1 and HF4.Tritium data areexplained as a result of mixing
507 between old tritium-free water (deep sparklingwater) and recent water (post 1952) with an
508 exponential flow model (Malozewski and Zuber 1982), in which the distribution function of the
509 transit time of water in the shallow aquifer is exponential.Tritium content in well F1 (1991) and in
510 well R3 (1997 and 2010) may be explained by amixture of 80% old water (prior to early 1950s)
511 and 20% recent water, resulting in a mean transit time of more than 50 years.
512
513 The dominant aquifer lithology is Nages gneiss which is cross-cut by subvertical granite
514 intrusions (**Erreur ! Source du renvoi introuvable.**). To conduct strontium isotope analysis,
515 three rock samples from the Nages formation were selected from cores taken in well R6 and
516 three granite samples from well R5 cores and a nearby outcrop of a granite vein (**Erreur !**
517 **Source du renvoi introuvable.**). The results of water-rock interaction modelling for the granites
518 and Nages gneiss (Table 4) show that, for the R6 sample (76 m depth), the absence of K-
519 feldspar minerals in the model results in a $^{87}Sr/^{86}Sr$ value of 0.71064 in the water at equilibrium,
520 very close to the plagioclase value (0.710379). For the other R6 sample (96.9 m depth), the
521 absence of plagioclase results in a highercomputed value (0.71975) of the $^{87}Sr/^{87}Sr$ ratio in the
522 water at the equilibriumwith the rock. The theoretical dissolution model was not applied to the R6
523 sample (149.1 m depth–Cipolin marble) as the model is not applicable to carbonate rocks. The
524 analyses were performed on the whole rock (Cipolin) as well as on the calcite that is present in
525 light and dark layers. This Cipolin has the lowestSr isotopic composition of all the rocks
526 measured in the La Salvetat system. The isotopic composition of the calcite (0.708567), which

constitutes 69% of the light grey rock, has an isotopic signature that is fairly similar to that of the total rock. The residual calcite (calcite not yet dissolved) in dark beds is somewhat more radiogenic (0.709179).

The Srisotope ($^{87}Sr/^{86}Sr$) signature in water sampled from the wells ranges between 0.708956 and 0.709121 (Table 3).Compared to theoretical values calculated above for waters in equilibrium with the various rock types, the results clearly show that pumped waters haveSrisotope ($^{87}Sr/^{86}Sr$) signatures comparable to those measured in the Cipolin (R6, 149.1 m). The well waters are much less radiogenic than the waters calculated to be in equilibrium with the intrusive granites and spotted gneiss (R6, 96.9). The calcium bicarbonate facies of sparkling mineral waters is therefore acquired on contact with the Cipolins of the Nages formation.

# 5. NUMERICAL MODELLING

## 5.1. MODEL ARCHITECTURE

A model was developed for the South compartment exploited by wells R3, R2, R1, HF4 and B1. The compartmentwas modelledwith two superimposed aquifer levels: a shallow reservoir and five deeper reservoirs, one for each production well (**Erreur ! Source du renvoi introuvable.**). The physical laws describing the various flows exchanged within this network of six reservoirs were selected on the basis of the conclusions of the multidisciplinary study. Thus, taking the piezometric data and location of the springs into account, it wasascertained that flow between the five reservoirs representing the deep aquifer is directed from the area around borehole HF4 towards the others (respectively towards the east (B1) and the west (F1, R2, R3…) and reproduces the NMW discharge measured beforeexploitation began on the site. Horizontal flow generated by the head difference between the reservoirs is described in the model by a Darcy-type law. Vertical flow from the shallow reservoir towards the deep reservoirs is assumed proportional to the head difference in order to reproduce the leakage phenomenon

revealed by some hydraulic tests. Lastly, analysis has shown that, before the site was exploited, natural springs and shallow groundwater could be highly mineralised locally due to inflow of deep NMW into the shallow aquifers. To reproduce this mineralization, the deep reservoirswere forced to empty into the shallow reservoir according to a decreasing exponential (emptying time 5 to 10 days depending on the reservoir) whichterminates below a certain piezometric threshold.

A “soil” module in the model calculates the partitioning of rainwater into evapotranspiration, runoff, and infiltration according to the Thornthwaite classical model. Runoff flows towards the La RavièGeLake outside the modelled system. Infiltration comprises two components, with given chemical composition. The first component has a “shallow” type geochemical signature and is imposed asinput to the shallow reservoir. The chemical composition of water is not calculated by the model but rather is a boundary condition, constant over time. In order to reproduce the observed inflow of NMW in the shallow aquifer (reservoir), this boundaryconditionwasspatialized. Consequently, the chemical composition of water in the shallow reservoir could vary from one reservoir to the other. Thus, a composition C1 (Figure 11) is imposed for transfers from the shallow reservoir feeding R1, R2 and R3 reservoirs, and a more mineralised composition C2 is imposed as input for feeding B1 and HF4. This conceptualization allows for reproduction of a higher chemical inertia of B1 and HF4 wells as compared to R1, R2 and R3.The second component feeding the deep reservoirs is the deep geochemical signature C3.All these imposed compositions are chosen among available results of surface or deep water analyses.These two components are imposed at the reservoir input with a time lag relative to the rainfall that generated them. This is used to introduce inertia into the model on the basis of a maximum lag of 80 to 130 days as highlighted bytime series analysis.

The chemical composition of the water in each of the five reservoirs iscalculated by the model according toa mixing processdue to flow exchangebetween the reservoirs.Water-rock geochemical reactions are also taken into account where necessary. The chemical heterogeneous reactions that produceor consume calcium, carbon and silica in aqueous phase

577 aredescribed by first-order kinetic laws. The other chemical elements are considered non-
578 reactive.

579 The model was numerically transposed using Matlab and Simulink© software with a one-
580 day time step. The physical parameters of the modelwere determined according to the results of
581 the multidisciplinary study. In this way, the dimensions of the five deep reservoirs are such that
582 they form a deeply-rooted, lens-shaped structure 50 m wide and 600 m long. As defined by the
583 model, these reservoirs are unconfined. An effective porosity of 1%, a classical value in the
584 shallow weathered-fractured zone of crystalline rocks (Marechal et al. 2006; Maréchal et al.
585 2004), leads, at an equivalent water head, to a body of water of the same order of magnitude as
586 that stored in the natural confined aquifer (storage coefficient estimated at $5x10^{-4}$) including wells
587 R3, R2, R1, HF4 and B1. The reservoir time constants are fitted so that, without pumping, flow is
588 within anorder of magnitude of the estimated discharge of natural springs before
589 production,mainly to the west (R3) and to a much lower extent to the east (B1). In order to
590 estimate the other model parameters, time series of production discharge, daily piezometric data
591 and weekly chemical analyses are available on a 10 to 22 years period. A long transient period
592 was needed for initialization because, owing to the inertia of the hydrogeological system, the
593 observed system is never in a stationary regime. The area of the upper reservoir's catchment
594 zone was determined during fitting, at 0.6 $km^2$. This value is in agreement with the $^{18}O$ data and
595 the physical geography of the site, and corresponds to 3/4 of the surface catchment area. Lastly,
596 to most accurately reflect the concentrations of chemical species observed in the water from the
597 different wells, the chemical reactivity of calcium, carbon and silica wereconsidered. For the
598 other chemical elements considered by the model, the perfect tracer hypothesis is acceptable
599 (i.e. the chemical speciesare considered un-reactive).

600 ## 5.2. SIMULATION

The calculated water levels were compared to the piezometric levels measured (corrected for quadratic head loss) over the calibration period (1991-2012) after initialisation. The results obtained at wells R1 and R2, which benefit from the longest observation period,are given for illustration purposes in **Erreur ! Source du renvoi introuvable.**. The high amplitude fluctuations observed (and simulated) over the period 1994-1998 are linked to high precipitation periods. The year 1996 is an atypical year with 2,412 mm of precipitation, while the annual mean is 1,370 mm over the period 1987-2011.The model alsoreproduces satisfactorily long-term concentration dynamics (**Erreur ! Source du renvoi introuvable.**). The annual fluctuations are consistent with the observations. In particular, the model correctly forecasts increased concentrations following a series of rainy years (**Erreur ! Source du renvoi introuvable.**). However, in the short-term, the model lacks inertia and does not sufficiently absorb fluctuations compared to reality.

Once fitted, the numerical model was used to explore how the system functions and to verify the consistency of the conceptual model with the entire set of observations. For instance, in its natural state (without pumping), the discharge from the reservoirs approximates 60 $m^3$/day for R1 and R2, and 10 $m^3$/day for B1. These values match the estimated discharge from natural springs before exploitation in each area. In its natural state, the shallow reservoir mainly feeds the deep reservoir HF4 (which receives 45% of flow from the shallow reservoir), followed by R1 and R2 (20% each). These flow differences induce pressure differentials between the deep reservoirs, which induce flow from HF4 towards B1 (to the east) and from HF4 to R1 (to the west), and from R2 towards R3. Modelling therefore allows one to rule out that sector B1-HF4 may not be hydraulically connected to the western part of the aquifer. From the geochemical standpoint, 50% of flow feeding reservoirs B1 and R1 correspond to highly mineralised water (deep geochemical signature), versus 30% in HF4 and R2.

## 6. DISCUSSION

626 The absence of connectivitybetween the North and South compartments (piezometry,
627 interference between wells), and their contrasting hydrodynamic functioning demonstrate the
628 existence of two permeable bodies oriented E-W (N100-110°E) (**Erreur ! Source du renvoi**
629 **introuvable.**a and b). This orientation is consistent with the major extensional structures related
630 to the alpine orogeny, which resulted from the Miocene opening of the western Mediterranean.
631 Furthermore, signal treatment and modelling demonstrated the continuity of the southern
632 compartment towards the East until at least B1 well. These hydraulic data agree with the
633 geological structure deduced from the geophysics and calibrated against the geological data
634 from the wellsand the basic data such as topography, location of NMW springs, and piezometry.
635 The geology alone, however, was not clearenough to be demonstrative.Based on these findings,
636 it appears that the granite veins do not explain the permeability of the La Salvetat mineral
637 aquifer. Water mineralisation is primarily acquired at depth on contact with the Cipolin
638 marbleswhich must,consequently,be deeply rooted, while the granites form fairly thin local veins,
639 which are not deeply rooted.Analysis of pumping and interferencetests between production
640 wells, in addition to the structure (two distinct permeable bodies) and the characterization of their
641 hydrodynamic parameters,highlights the existence of three major hydraulicboundary conditions.
642 First, the presence of a leakage effect forseveral wells, correlated with the existence of a
643 discontinuous aquifer in the stratiformfissured layer, shows that it is drained *per descensum* by
644 leakage into the deep fractures intersected by the wells. In this type of crystalline rock, this
645 aquifer corresponds to the middle part of the weathering profile formed by a fissured layer in the
646 Nages gneiss, itself supplied through leakage from overlying weathered products (saprolite). The
647 relationship between the deep aquifertapped by the wells and this aquiferis confirmed by the
648 hydrochemistry and, above all, by the numerical model, which requires this type of vertical
649 exchange to correctly reproduce piezometric trends and the water chemical composition.
650 Second, no-flow boundary conditions show that the deep fractures drain a spatially closed
651 aquifer with a width (North-South) of about 50 to 200 m (pumping tests, geophysics) and a

length of about600 meters (West to East, from R4 at least to B1) whichis realistic considering the pumping test and modelling data. Well data (discrete water bearing structures separated by impermeable formations) show that within thissubvertical fractured strip, only a small part of the volume (about onepercent in volume) is fractured and permeable.

Third, the partial penetration of the wells is confirmed by modelling which requires at least a depth of 600 meters for each reservoir to account for the high inertia of the mineral system, most of the pumped water flowing upward from this great depth. This suggests that each permeable structure is very deeply rooted with a fissured zone along main faults. Both these two faults appear to be tension joints. Data currently available do not provide a basis for determining whether other joints exist further North or South. In addition, the availablegeophysics does not suggest it. Nevertheless, new drillings are scheduled at the eastern tip of the southern structure (East of B1) in order to check its potential eastern continuation.

Another similar structure in the Nages gneiss gives rise to a mineral spring (Font Rouge),6 km west of the investigation site with a similar hydrochemicalcomposition.It is the only such springwithin a radius of about 50 km around La Salvetat. Thus, such permeable structures are not common. They cannot be identified only by simple means (lineament analysis, for instance). Such fractures are mostly revealed by NMW outflowwhere they cross-cut a topographical low. Other similar fractures not cross-cutting a topographical low probably exist, but they are not identifiable at the surface by a NMW spring.

Signal processing on piezometric and geochemical data logically shows the existence of two types of groundwater flow: (i) a “fast” recharge corresponding to local flow path (40-80 days), within the non-mineralizedshallowaquifer of the fissured layer, and (ii) the increase of the NMW component hydraulic head (80-130days) itself resulting in an increase in mineralisation. High water levels in the shallow aquifer (related to rainfall or to lake level variations) give rise to an increase in the mineral component. The inertia of the system is such that several successive wet years induce a continuous increase in this mineral component. Modelling also shows that R3

(and particularly R4) is apparently not directly supplied by the deep permeable structure,but results from mixing between overflow from mineral water coming from the East (B1, HF4, R1, R2) and ancient waters (without tritium) from the shallow fissuredaquifer. Additional modelling of the northern compartment (R6, R5, HF2) scheduled for the second phase of the project will undoubtedly fine-tune this conceptual model, particularly the possible relationships between the two systems through the fissured layer, and the recharge evaluation.

This investigation showed the importance of characterising initial flow conditions (and geochemistry) before the system went into production in order to understand how these hydrothermal systems function. In fact, these elements were essentialfor reliably fitting the hydrodynamic model.Such a characterization should systematically be performed in detail prior to beginning to pump in a NMW system. The study also illustratesthe need for suitable analytical models for modelling pumping tests where it is necessary to consider, among other parameters, the anisotropy in hydraulic conductivity of a faulted zone, and the partial penetration of wells within such a faulted aquifer. This could be particularly helpful for better characterization of the B1 compartment to improve the system geometry, and also to better constrain the depth of the fracture or, at least, if it is very deep, to assess it. In fact, it is probable that at B1 the far no-flow boundaries appear very late after the start of the pumping because of such a very strong anisotropy of the pumped fractured zone, and also as a consequence of the very deep root of the fractured zone.

## 7. CONCLUSION

A detailed characterization of a complex NMW systemat La Salvetat (France)was made possible through the use of a combination of techniques. Twoneighbouringfractured zones in the Nages gneiss constitute the main pathways for deep $CO_2$ and NMW to riseto the land's surface. Geological investigations, pumping test analysis, time series signal processing, hydrogeochemicaland isotopes approaches, and numerical modelling provided complementary

703 information on the geometry and hydrodynamic characteristics of the permeable structure, and
704 on the functioning of this mineral system.This applied research investigation demonstrates the
705 need of multidisciplinary approaches and modelling (quantity, quality) as a tool for understanding
706 complex NMW systems. Only through a combination of evidences, each obtained from one
707 discipline, which on its owndid not lend sufficient insight, was it possible to build a representative
708 conceptual model. This model then alloweddetermining, with an acceptable degree of certainty,
709 the geometry of the permeable structureat the origin of the mineral system, whereas most
710 classical studies, mainly based only on a structural geology approach, do not generally exhibit
711 this degree of reliability and are merely speculative.The multidisciplinary approach also allowed
712 a more thorough understanding of the hydrodynamic and hydrogeochemical functioning of the
713 system, from a rather great depth (a few hundred meters) to the surface. This knowledge about
714 the structure and functioning of such a sparkling NMW system is of interest as it may provide a
715 conceptual model that could be used atother NMW sites.The knowledge of the system is also of
716 high interest for the bottling company that is already applying it for the sustainable management
717 of the spring, to program additional hydrogeological surveysaimed at increasing the available
718 resource, and to implement protectionpolicies on its watershed. It also opens up perspectives for
719 a complete spatializeddeterministic 3-D modelling of such complex hydrosystems.

720 ## 8. ACKNOWLEDGMENTS

721 This study was conducted under a research agreement between Evian Volvic World Sources
722 (Danone Waters France) and BRGM. The constructive reviews of the Guest Editor and three
723 anonymous reviewers were highly appreciated.

724 ## 9. REFERENCES

725 Battani A, Sarda P, Prinzhofer A (2000) Basin scale natural gas source, migration and trapping traced by
726 noble gases and major elements: the Pakistan Indus basin. Earth and Planetary Science Letters
727 181: 229-249 doi: 10.1016/s0012-821x(00)00188-6

728 Black JH (1994) Hydrogeology of fractured rocks - a question of uncertainty about geometry. Applied
729 Hydrogeology 2: 56-70 doi: 10.1007/s100400050049
730 Blavoux B, Dazy J (1990) Characterization of a CO2 province in the Southeastern basin of France.
731 Hydrogéologie 4: 241-252
732 Bullen TD, White AF, Blum AE, Harden JW, Schulz MS (1997) Chemical weathering of a soil
733 chronosequence on granitoid alluvium; II, Mineralogic and isotopic constraints on the behavior
734 of strontium. Geochimica et Cosmochimica Acta 61: 291-306 doi: 10.1016/S0016-
735 7037(96)00344-4
736 Clemente WC, Villadolid-Abrigo FL (1993) The Bulalo geothermal field, Philippines: reservoir
737 characteristics and response to production. Geothermics 22: 381-394 doi: 10.1016/0375-
738 6505(93)90026-J
739 Collon P, Fabriol R, Vaute L, Pinault JL, Bues M (2002) Modelling changes in sulphate concentration in
740 discharge water from the abandoned iron mine of SaizeraisSWEMP 2002 - International
741 Symposium on Environmental issues and Waste Management in Energy and Mineral Production
742 7th edn, Cagliari.
743 Craig H (1961) Isotopic Variations in Meteoric Waters. Science 133: 1702-1703 doi:
744 10.1126/science.133.3465.1702
745 Demange M, Guérangé-Lozes J, Guérangé B (1995) Carte géol. France (1/50 000) feuille Lacaune
746 (Geological map of France - sheet Lacaune) BRGM, Orléans, pp. Notice explicative par M.
747 Demange, J. Guérangé-Lozes, B. Guérangé et coll. .
748 Dewandel B, Lachassagne P, Wyns R, Marechal JC, Krishnamurthy NS (2006) A generalized 3-D geological
749 and hydrogeological conceptual model of granite aquifers controlled by single or multiphase
750 weathering. Journal of Hydrology 330: 260-284 doi: 10.1016/j.jhydrol.2006.03.026
751 Dewandel B, Lachassagne P, Zaidi FK, Chandra S (2011) A conceptual hydrodynamic model of a geological
752 discontinuity in hard rock aquifers: Example of a quartz reef in granitic terrain in South India.
753 Journal of Hydrology 405: 474-487 doi: 10.1016/j.jhydrol.2011.05.050
754 Ehlig-Economides C (1988) Use of the pressure derivative for diagnosing pressure-transient behavior. J.
755 Pet. Technol: 1280–1282 doi: 10.2118/18594-PA
756 Gustafson G, Gylling B, Selroos J-O (2009) The Aespoe Task Force on groundwater flow and transport of
757 solutes: bridging the gap between site characterization and performance assessment for
758 radioactive waste disposal in fractured rocks. Hydrogeology Journal 17: 1031-1033 doi:
759 10.1007/s10040-008-0419-6
760 Hantush MS (1960) Aquifer tests on partially penetrating wells. Journal of Geophysical Research 65:
761 2495-2495
762 Kerrick DM, Caldeira K (1998) Metamorphic CO2 degassing from orogenic belts. Chemical Geology 145:
763 213-232 doi: 10.1016/s0009-2541(97)00144-7
764 Kothyari UC, Singh VP (1999) A multiple-input single-output model for flow forecasting. Journal of
765 Hydrology 220: 12-26 doi: 10.1016/S0022-1694(99)00055-4
766 Lachassagne P, Maréchal J, Sanjuan B (2009) Hydrogeological model of a high-energy geothermal field
767 (Bouillante area, Guadeloupe, French West Indies). Hydrogeology Journal 17: 1589-1606 doi:
768 10.1007/s10040-009-0486-3
769 Lachassagne P, Wyns R, Dewandel B, Lachassagne P, Wyns R, Dewandel B, P. L, et al. (2011) The fracture
770 permeability of Hard Rock Aquifers is due neither to tectonics, nor to unloading, but to
771 weathering processes. Terra Nova 23: 145-161 doi: 10.1111/j.1365-3121.2011.00998.x
772 Ladouche B, Aquilina L, Dörfliger N (2009) Chemical and isotopic investigation of rainwater in Southern
773 France (1996-2002): Potential use as input signal for karst functioning investigation. Journal of
774 Hydrology 367: 15-15 doi: 10.1016/j.jhydrol.2009.01.012

775 Mangin A (1984) The Use of Autocorrelation and Spectral Analyses to Obtain a Better Understanding of
776 Hydrological Systems (Pour une Meilleure Connaissance des Systemes Hydrologiques a Partir des
777 Analyses Corelatoire et Spectrale). Journal of Hydrology 67: 25-43
778 Marechal JC, Dewandel B, Ahmed S, Galeazzi L, Zaidi FK (2006) Combined estimation of specific yield and
779 natural recharge in a semi-arid groundwater basin with irrigated agriculture. Journal of
780 Hydrology 329: 281-293 doi: 10.1016/j.jhydrol.2006.02.022
781 Maréchal JC, Dewandel B, Subrahmanyam K (2004) Use of hydraulic tests at different scales to
782 characterize fracture network properties in the weathered-fractured layer of a hard rock aquifer.
783 Water Resources Research 40 doi: 10.1029/2004wr003137
784 Morosini M, Rhen I (2000) Hydrogeological characterization of fractured rock for Sweden's nuclear waste
785 storage. Proceedings of the ... IAH Congress on Groundwater... 30: 785-789
786 Nash JE, Sutcliffe JV (1970) River flow forecasting through conceptual models part I — A discussion of
787 principles. Journal of Hydrology 10: 282-290 doi: http://dx.doi.org/10.1016/0022-
788 1694(70)90255-6
789 Negrel P, Casanova J, Aranyossy J-F (2001) Strontium isotope systematics used to decipher the origin of
790 groundwaters sampled from granitoids; the Vienne case (France). Chemical Geology 177: 287-
791 308 doi: 10.1016/S0009-2541(00)00414-9
792 Nind T (1965) Influences of absolute and partial hydrologic barriers on pump test results. Canadian
793 Journal of Earth Sciences 2: 309-323 doi: doi:10.1139/e65-025
794 Petelet Giraud E, Negrel P, Casanova J (2003) Variability of Sr-87/Sr-86 in water draining granite revealed
795 after a double correction for atmospheric and anthropogenic inputs. HYDROLOGICAL SCIENCES
796 JOURNAL JOURNAL DES SCIENCES HYDROLOGIQUES 48: 729-742
797 Pin C, Bassin C (1992) Evaluation of a strontium specific extraction chromatographic method for isotopic
798 analysis in geological materials. Analytica Chimica Acta 269: 249-255 doi: 10.1016/0003-
799 2670(92)85409-Y
800 Pinault J-L, Plagnes V, Aquilina L, Bakalowicz M (2001) Inverse modeling of the hydrological and the
801 hydrochemical behavior of hydrosystems: Characterization of karst system functioning. Water
802 Resources Research 37: 2191-2204 doi: 10.1029/2001WR900018
803 Renard P, Glenz D, Mejias M (2009) Understanding diagnostic plots for well-test interpretation.
804 Hydrogeology Journal 17: 589-600 doi: 10.1007/s10040-008-0392-0
805 Shipton ZK, Evans JP, Dockerill B, Heath J, Williams A, Kirchener D, Kolesar PT (2005) Natural leaking CO2-
806 charged systems as analogs for failed geologic storage reservoirs. In: Benson SM (ed) Carbon
807 dioxide capture for storage in deep geological formations:699–712.

808

809 **Tables**

810 Table 1: Summary of pumping test results

811

| PW | Geol | No. of Tests | OW | Diagnostic feature | Analytical model | *T* or *T1* ($m^2/s$) | *S* | Distance to boundary (m) | *T2* ($m^2/s$) |
|---|---|---|---|---|---|---|---|---|---|
| R1 | N | 3 | R2, DAC, P1 | Partitioned aquifer, PP | Hantush (1961); Nind (1965) | $2.3 \times 10^{-4}$ | $5.1 \times 10^{-4}$ | 180 | $4.5 \times 10^{-4}$ |
| R2 | N | 2 | R1, DAC, | Partitioned aquifer | Nind (1965) | $2.3 \times 10^{-4}$ | $5.2 \times 10^{-4}$ | 180 | $4.7 \times 10^{-4}$ |

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | | | P1 | | | | | | |
| R3 | N | 2 | R1, R2 | Partitioned aquifer | Nind (1965) | $2.4 \times 10^{-4}$ | $5.7 \times 10^{-4}$ | 300 | $2.6 \times 10^{-5}$ |
| R4 | N | 3 | MLC2, ML3, P3 | Bounded aquifer with leakage | 4 orthogonal no-flow boundaries + leakage | $5.4 \times 10^{-4}$ | $5.0 \times 10^{-4}$ | 100, 100, 140, 260 | - |
| R5 | G | 2 | R6* | Partitioned aquifer (PP) | Hantush (1961); Nind (1965) | $5.0 \times 10^{-4}$ | $4.0 \times 10^{-5}$ | Not evaluated | - |
| R6 | N | 10 | R5* | Partitioned aquifer | Nind (1965) | $1.8 \times 10^{-4}$ | $1.3 \times 10^{-5}$ | 450 | $9.3 \times 10^{-4}$ |
| DAC | N | 1 | R1, R2 | Homogeneous aquifer | Theis (1935) | $1.4 \times 10^{-4}$ | $3.9 \times 10^{-4}$ | - | - |
| P3 | N | 1 | R3, R4 | Bounded aquifer | 4 orthogonal no-flow boundaries | $5.0 \times 10^{-4}$ | $8.3 \times 10^{-4}$ | 70, 70, 70, 70 | - |
| B1 | N | 4 | - | Channelized flow | 2 parallel no-flow boundaries | $9.0 \times 10^{-5}$ | - | 400, 400 | - |
| HF4 | N | 2 | B1 | Channelized flow | 2 parallel no-flow boundaries | $8.7 \times 10^{-3}$ | $4.0 \times 10^{-4}$ | 30, 30 | - |

PW pumping well; OW observation well; T – transmissivity (in case of partitioned aquifer: T1 - transmissivity of the local aquifer where the PW is drilled and T2 – transmissivity of the aquifer beyond the boundary); S – storativity. Geology: N – Nages and G – granite; PP: Partial penetration;*no reaction of other wells

Table 2: Relative contributions of hydrological time series to the water level in five production wells

| | | Mean Relative Contributions | | | |
|---|---|---|---|---|---|
| Well | Depth of well screening (m) | Recharge (%) *[maximum amplitude]* | Discharge at the well (%) *[maximum amplitude]* | Discharge of the other wells (%) *[maximum amplitude]* | Raviège Lake level(%) *[maximum amplitude]* |
| R1 | 60-87 | 13% *[4.6 m]* | 37% *[9.5 m]* | 50% *[14.4 m]* | No contribution |
| B1 | 111-121 | 39% *[3.1 m]* | 61% *[4.9 m]* | - | No contribution |
| R2 | 45-101 | 12% *[2.2 m]* | 44% *[5 m]* | 54% *[8.4 m]* | No contribution |
| R3 | 41.9-44 | 8% *[1.8 m]* | 87% *[5.5 m]* | 5% *[1.6 m]* | No contribution |
| R5 | 73-130 | 8% *[1 m]* | 42% *[6 m]* | - | 50% *[7 m]* |

Table 3 : Major cations and anions (Na, K, Mg, Ca, Cl, $HCO_3$, $SO_4$, and $SiO_2$ in mg/L), trace elements (Li, B, Sr, Fe, Mn and Ba in µg/L), stable isotopes of the water molecule ($\delta^2H$ and $\delta^{18}O$), tritium, stable isotopes ($\delta^{13}C$) of the dissolved $CO_2$ and $^{87}Sr/^{86}Sr$ ratios

| | Well | B1 | R5 | R3 | R6 | R1 | R2 | HF4 |
|---|---|---|---|---|---|---|---|---|
| | Date (dd/mm/yy) | 10/09/10 | 10/09/10 | 10/09/10 | 10/09/10 | 10/09/10 | 10/09/10 | 14/09/11 |
| pH | | 5.8 | 6.2 | 6.4 | 6.2 | 6.1 | 5.9 | 5.81 |
| EC | µS/cm | 1645 | 884 | 477 | 588 | 1076 | 816 | 1460 |
| Temp | °C | 14.7 | 14.0 | 15.1 | 14.1 | 14.0 | 14.3 | 13.0 |
| $SiO_2$ | mg/l | 81.0 | 91.3 | 61.5 | 80.4 | 74.9 | 71.5 | 96.8 |
| $Na^+$ | mg/l | 6.6 | 4.8 | 4.5 | 3.4 | 5.3 | 4.4 | 7.1 |
| $K^+$ | mg/l | 2.9 | 2.0 | 2.3 | 1.5 | 2.4 | 2.3 | 2.9 |
| $Ca^{2+}$ | mg/l | 374 | 176 | 137 | 112 | 222 | 162 | 373 |
| $Mg^{2+}$ | mg/l | 15.6 | 9.5 | 7.0 | 4.8 | 10.5 | 7.5 | 15.4 |
| $Cl^-$ | mg/l | 3.7 | 4.2 | 4.1 | 4.2 | 4.5 | 5.1 | 3.4 |
| $HCO^{3-}$ | mg/l | 1186 | 561 | 289 | 358 | 681 | 544 | 1192 |
| $SO_4^{2-}$ | mg/l | 9.0 | 20.3 | 9.0 | 7.4 | 43.6 | 7.9 | 8.5 |
| $NO_3^-$ | mg/l | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 |
| $NH_4^+$ | mg/l | 0.14 | 0.07 | <0.05 | <0.05 | 0.05 | 0.19 | |
| $F^-$ | mg/l | 0.3 | 0.4 | 0.3 | 0.4 | 0.3 | 0.4 | 0.3 |
| Fe(tot) | µg/l | 14500 | 8430 | 5230 | 5790 | 11400 | 7660 | 48024 |
| Mn(tot) | µg/l | 1581 | 581 | 458 | 455 | 843 | 568 | 1722 |
| Ba | µg/l | 12.47 | 11.35 | 7.58 | 8.19 | 7.33 | 7.27 | 50.1 |
| $B^-$ | µg/l | 59.4 | 24 | 32.1 | 16.2 | 36.1 | 39.6 | 10.4 |
| $Li^+$ | µg/l | 28.3 | 21.5 | 16.9 | 13.1 | 21.2 | 16.9 | 21.9 |
| $Sr^{2+}$ | µg/l | 1910 | 914 | 780 | 601 | 1210 | 868 | 1718 |
| $^{87}Sr/^{86}Sr$ | | 0.708985 | 0.709048 | 0.709121 | 0.708963 | 0.709018 | 0.709024 | 0.708956 |
| $2\sigma$ for $^{87}Sr/^{86}Sr(m)$ | | 0.000008 | 0.000008 | 0.000009 | 0.000008 | 0.000007 | 0.000008 | 0.000009 |
| $\delta D$ | ‰ | -46.0 | -44.5 | -45.3 | -45.3 | -45.2 | -45.1 | -48 |
| $\delta^{18}O$ | ‰ | -7.3 | -7.1 | -7.2 | -7.1 | -7.2 | -7.2 | -7.5 |
| $^3H$ | UT | 2 | 2 | <1 | 2 | 3 | 2 | 3 |

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| 2σ for $^{3}H$(m) | | 1 | 1 | | 1 | 1 | 1 | 1 |
| $d^{13}C$ ($CO_{2g}$) | ‰ | -5.6 | -6.7 | -7.8 | -7.8 | -6.6 | -6.4 | |

831

832

833 Table 3(continued)

| | | P3 | MLC1 | R4 | HF1 | HF2 | HF3 | HF5 |
|---|---|---|---|---|---|---|---|---|
| | | 08/09/10 | 08/09/10 | 13/09/10 | 13/12/11 | 27/12/11 | 15/09/11 | 13/12/11 |
| pH | | 6.77 | 6.89 | 6.64 | 7.20 | 6.50 | 7.23 | 7.80 |
| EC | µS/cm | 232 | 132 | 718 | 126 | 863 | | 179 |
| Temp | °C | | | | 14.0 | | 11.7 | 14.0 |
| $SiO_2$ | mg/l | 10.4 | 13.9 | 35.6 | 19.5 | 39.0 | 15.4 | 10.2 |
| $Na^+$ | mg/l | 4.7 | 3.8 | 4.7 | 4.9 | 8.7 | 3.7 | 3.4 |
| $K^+$ | mg/l | 1.0 | 1.0 | 1.7 | 2.8 | 2.5 | 0.8 | 1.5 |
| $Ca^{2+}$ | mg/l | 40 | 22 | 182 | 38 | 203 | 26 | 30 |
| $Mg^{2+}$ | mg/l | 2.4 | 1.5 | 6.7 | 3.2 | 11.6 | 1.5 | 2.5 |
| $Cl^-$ | mg/l | 18.5 | 7.5 | 7.9 | 3.0 | 3.0 | 4.0 | 6.5 |
| $HCO_3^-$ | mg/l | 107 | 76 | 542 | 79 | 686 | 82 | 106 |
| $SO_4^{2-}$ | mg/l | 3.5 | 3.0 | 9.5 | 5.5 | 5.5 | 2.0 | 2.5 |
| $NO_3^-$ | mg/l | 14.5 | 1.6 | 0.4 | 0.40 | 3.6 | 1.6 | 5.30 |
| $NH_4^+$ | mg/l | | | | | <0.02 | | |
| $F^-$ | mg/l | | | | <0.1 | | <0.1 | <0.1 |
| Fe(tot) | µg/l | 1.5 | 4 | 194 | | 0.60 | 24 | |
| Mn(tot) | µg/l | 0.3 | 0.5 | 180 | 374 | 0.10 | 13.5 | 18 |
| Ba | µg/l | 7 | 7.5 | 14 | 12.5 | 17 | 4.1 | 6.5 |
| B- | µg/l | <20 | 30 | <20 | <20 | | 3.0 | <20 |
| $Li^+$ | µg/l | 1.5 | 1.5 | 21.0 | 5.5 | 29.0 | 1.7 | 3.5 |
| $Sr^{2+}$ | µg/l | 301 | 157 | 1201 | 397 | 1370 | 307 | 286 |
| $^{87}Sr/^{86}Sr$ | | 0.708933 | 0.709473 | 0.708840 | | | 0.709012 | |
| 2σ for $^{87}Sr/^{86}Sr$ (m) | | 0.000009 | 0.000009 | 0.000009 | | | 0.000009 | |
| δD | ‰ | -45.2 | -42.9 | -44.5 | | | -46.5 | |
| $\delta^{18}O$ | ‰ | -7.2 | -6.9 | -7.0 | | | -7.2 | |
| $^{3}H$ | UT | 3 | 3 | 2 | | | | |
| 2σ for $^{3}H$(m) | | 1 | 1 | 1 | | | | |

834 σ: standard deviation

835

836

837

*Table 4:* Strontium (Sr) and rubidium (Rb) data on rock samples

| Formation | Sample (depth) | Mineral | Rb (ppm) | Rb* (ppm) | Sr (ppm) | Sr* (ppm) | $^{87}Sr/^{86}Sr$ | $^{87}Sr/^{86}Sr$ W-model |
|---|---|---|---|---|---|---|---|---|
| Granite | Granite 8 (outcrop) | TR | 271 | - | 76 | - | 0.755219 | 0.76116 |
| | | P+Q | 135 | 271 | 46 | 92 | 0.748866 | |
| | | K-F | 532 | - | 104 | - | 0.773991 | |
| | | B | 609 | - | 10 | - | 1.390815 | |
| Granite | R5 (102.8 m) | TR | 373 | - | 48 | - | 0.799635 | 0.80615 |
| | | P+Q | 219 | 547 | 34 | 84 | 0.784069 | |
| | | K-F | 530 | - | 76 | - | 0.793338 | |
| | | B | 1807 | - | 10 | | 2.805149 | |
| Granite (pegmatite) | R5 (117.4 m) | TR | 451 | - | 28 | - | 0.897886 | 0.88075 |
| | | P+Q | 273 | 414 | 20 | 30 | 0.872317 | |
| | | K-F | 959 | - | 45 | - | 0.959064 | |
| Nages gneiss | R6 (76 m) | TR | 94 | - | 471 | - | 0.712446 | 0.71064 |
| | | P+Q | 21 | 54 | 886 | 2816 | 0.710379 | |
| | | K-F | 264 | - | 160 | - | 0.729277 | |
| Nages gneiss | R6 (96.9 m) | TR | 157 | - | 241 | - | 0.717688 | 0.71975 |
| | | K-F | 222 | - | 592 | - | 0.713817 | |
| | | B | 206 | - | 193 | - | 0.72217 | |
| | | C | 117 | - | 168 | - | 0.71759 | |
| Cipolin marble | R6 (149.1 m) | TR | 34 | - | 1937 | - | 0.708719 | - |
| | | C1 | 14 | - | 2283 | - | 0.708567 | |
| | | C2 | 89 | - | 1834 | - | 0.709179 | |

TR: total rock sample; P+Q: plagioclase + quartz; K-F: K-feldspar ; B: biotite; C: calcite; C1: light calcite; C2: dark calcite.

Rb* and Sr* contents are corrected from the quartz proportion of the sample.

$^{87}Sr/^{86}Sr$ W-model means the $^{87}Sr/^{86}Sr$ of water in theoretical equilibrium with the rock