Modelling of the gas-liquid partitioning of aroma compounds during wine alcoholic fermentation and prediction of aroma losses

Sumallika Morakul, Jean-Roch Mouret, Nicole Pamela, Cristian Trelea, Jean-Marie Sablayrolles, Violaine Athes

► To cite this version:

Sumallika Morakul, Jean-Roch Mouret, Nicole Pamela, Cristian Trelea, Jean-Marie Sablayrolles, et al.. Modelling of the gas-liquid partitioning of aroma compounds during wine alcoholic fermentation and prediction of aroma losses. *Process Biochemistry*, 2011, 46 (5), pp.1125-1131. 10.1016/j.procbio.2011.01.034 . hal-01003250

HAL Id: hal-01003250

<https://hal.science/hal-01003250>

Submitted on 12 Jul 2017

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

**Modelling of the gas-liquid partitioning of aroma compounds during wine alcoholic
fermentation and prediction of aroma losses**

Sumallika Morakul^a, Jean-Roch Mouret^a, Pamela Nicolle^b, Ioan Cristian Trelea^c, Jean-
Marie Sablayrolles^a, Violaine Athes^{c*}

^a INRA, UMR 1083, 2 Place Viala, F-34060 Montpellier Cedex 1, France

^b INRA, UE 999, F-11430 Gruissan, France

^c AgroParisTech, INRA, UMR 782, F-78850 Thiverval–Grignon, France

*Corresponding author

Tel. : + 33 1 30 81 53 83

Fax. : +33 1 30 81 55 97

e-mail : vathes@grignon.inra.fr

ABSTRACT

A model was elaborated to quantify the gas-liquid partitioning of four of the most important volatile compounds produced during winemaking fermentations, namely isobutanol, ethyl acetate, isoamyl acetate and ethyl hexanoate. Analyses of constant rate fermentations demonstrated that the partitioning was not influenced by the CO₂ production rate and was a function of only the must composition and the temperature. The parameters of the model were identified in fermentations run at different temperatures, including anisothermal conditions. The prediction of the partition coefficient (k_i) by the model was very accurate for isobutanol, isoamyl acetate and ethyl hexanoate. The technological potential of the model was confirmed by using it to calculate the losses of volatiles in the gas phase during fermentation and comparing them with experimental data. Up to 70% of the produced volatile compounds were lost. The difference between observed losses and losses estimated from predicted k_i values never exceeded 3%.

Keywords: gas-liquid transfer, online GC measurement, wine, aroma, dynamic modelling

1. Introduction

The synthesis of higher alcohols and esters during fermentation makes an important contribution to wine quality and the control of the production of these volatile compounds is one of the major ways to control the organoleptic characteristics of wine. The higher alcohols are undesirable at high concentrations, but in smaller quantities they are thought to contribute positively to overall wine quality. Esters have a significant effect on the fruity flavour in wine. The esters making the largest olfactory impact are ethyl acetate, isoamyl acetate, isobutyl acetate, ethyl hexanoate and 2- phenylethyl acetate [1]. Varietal aromas —volatile compounds derived from non-volatile precursors in the grape which are released by the yeast during fermentation, such as thiols— also play an essential role in wine aroma but they are usually present at very low concentrations and are therefore more difficult to quantify.

The concentrations of volatiles at the end of fermentation depend primarily on their synthesis by the yeasts but may also be significantly modified by losses into the exhausted CO₂. Therefore, understanding and modelling the transfer of aroma compounds between the gas and liquid phases would be extremely useful, and the calculation of balances differentiating the microbiological process of production and the physicochemical process of transfer into the exhausted CO₂ is central to this issue. The online monitoring of volatile compounds in the tank headspace, as recently proposed by Mouret et al. [2], allows online estimation of volatile concentrations in fermenting musts, provided that reliable models for gas-liquid partitioning are available for all phases of the fermentation process. Finally, such models could subsequently be coupled to predictive models of volatile compound synthesis, based on knowledge of the biochemical pathways involved. Indeed, some authors have already proposed such models in beer making conditions [3-5].

Several models have been developed to quantify the transfer of volatile molecules between aqueous solutions and gas phases [6-8]. However, none of them is directly applicable to winemaking conditions. Indeed, unlike the conditions considered in these established models, the concentrations of volatile molecules, as well as the overall composition of the fermenting must, are continuously changing during alcoholic fermentations. Another difference is the production and release of CO₂, bubbles of which increase the transfer from the liquid to the gas, by stripping. Finally, only 3 molecules (isobutyl acetate, acetaldehyde and ethyl acetate) out of 21 were of interest in wine fermentations.

Several authors have studied flavour release in the context of oenology but mostly focused on the partitioning properties of volatiles in final wines [9-11] and did not consider their behaviour during fermentation. Recently, Morakul et al. [12] evaluated the effect of the matrix changes (mainly corresponding to the consumption of sugar and the production of ethanol) and of the temperature on gas-liquid partitioning in model conditions simulating fermenting musts. Ferreira et al. [13] assessed volatile compound losses due to the CO₂ production and showed that up to 80% of some molecules could be blown off; however, the experimental conditions used in [13] were not completely representative of the fermentation conditions, because changes in the matrix composition were not considered and the stripping rate was much higher than usually observed in winemaking.

In this paper, the objective was to develop a model of the evolution of the partition coefficient between the gas and liquid phases of four major volatile molecules, (ethyl acetate, isoamyl acetate, ethyl hexanoate and isobutanol) in winemaking fermentations. The partition coefficient k_i is expressed as the ratio between the mass concentration of the compound in the gas phase [C_i^{gas} in mg/L] and that in the liquid phase [C_i^{liq} in mg/L] at equilibrium.

The work was focused on these four molecules because they are representative of higher alcohol and ester families. Isobutanol is one of the major fusel alcohols whose concentrations

in wines are several tens of mg/L. It is synthesized by the yeasts from amino acids, in particular valine, and from keto-acids. As most higher alcohols are weakly volatile, its partition coefficient (k_i), expressed as a mass concentration ratio, at 25°C in grape musts is around 6.8×10^{-4} [12]. Despite its high concentration in the liquid phase, it is often below its perception threshold in gas [1]. Ethyl acetate, isoamyl acetate, and ethyl hexanoate are well known for their contribution to the fruity aroma of wines [14]. Their concentrations in wines are usually low (20 - 60 mg/L for ethyl acetate and less than 10 mg/L for isoamyl acetate and ethyl hexanoate) but nevertheless always above their perception thresholds [1]. The k_i values at 25°C in grape musts are around 1.0×10^{-2} for ethyl acetate, 2.9×10^{-2} for isoamyl acetate and 4.5×10^{-2} for ethyl hexanoate [12].

After assessing the effects of the main factors involved, and in particular the impact of stripping by CO₂, the model for the prediction of the partition coefficient (k_i) was developed and then validated in different winemaking situations. The model was then used to estimate the losses of volatile compounds in several winemaking situations.

2. Material and methods

2.1. Fermentations

2.1.1. Yeast strains

The *Saccharomyces cerevisiae* strains EC1118 and K1 were used. These commercial wine yeasts are produced as active dry yeast by Lallemand SA. Each fermentation tank was inoculated with 0.2 g/L of active dry yeast previously rehydrated for 30 minutes at 35 °C.

2.1.2. Musts

Various grape musts from the South of France were used. They were flash-pasteurised and stored under sterile conditions. Their sugar concentrations were between 180-200 g/L and their assimilable nitrogen concentrations were 40, 120, 140 and 240 mg/L.

2.1.3. Tanks

Fermentations were run at pilot scale in stainless steel tanks. The tanks contained 90 L of must and the headspace represented 30% of the total volume.

2.1.4. Control of fermentation

The CO₂ released was automatically and continually measured with a gas mass flow meter and the rate of CO₂ production (dCO₂/dt) was calculated with a high level of precision. The fermentations were controlled in different ways:

(i) Constant rate fermentations (CRF): to control the stripping effect, constant rate fermentations were run at 20°C. In these experiments, the rate of CO₂ production was kept constant by a feedback control **system** involving the addition of ammoniacal nitrogen via a peristaltic pump (Ismatec Reglo) [15].

(ii) Isothermal fermentations (IF): the temperature was maintained at a constant value (20 and 30°C), with a precision of 0.1°C.

(iii) Anisothermal fermentations (AF): the temperature was regulated according to the CO₂ production, which is proportional to the sugar degradation, with a slope of 0.2°C/(g/L) of evolved CO₂. This evolution of temperature simulated anisothermal conditions observed in industrial-size tanks when the temperature rises freely until the final setpoint is reached [16]. Two anisothermal fermentations were run between 15 and 30°C, thus covering the maximum range of temperatures used in winemaking. Another fermentation was conducted between 20

and 30°C, simulating a common temperature profile for red winemaking. All parameters and control conditions for the fermentation experiments in this study are summarized in **Table 1**.

2.2 Analysis of volatile compounds

2.2.1. Online measurements in the gas

The gas was pumped at a flow rate of 14 mL/min from the tank headspace through a heated transfer line and concentrated in a cold trap (Tenax TM) for 6 min (desorption at 160°C for 1 min), and injected into a ZBWax (60 m × 0.32 mm × 0.5 µm, Phenomenex Inc.). The injector was kept at 200°C. Helium was used as the carrier gas at a constant pressure of 120 kPa. The oven temperature program was 38°C for 3 min, 3°C/min up to 65°C, then 6°C/min to 160°C, held for 5 min, then 8°C/min up to 230°C and held for 5 min. A flame ionisation detector (FID) was used at 260°C.

The on-line GC system was calibrated by using a Sonimix 6000C1 (LNI Schmidlin SA). This equipment generates standard gases by dilution from standard gas bottles or permeation tubes. Standard gas bottles (Air Product) containing 4004, 85.1 and 100 mmol/Kmol of ethyl acetate (CAS number 141-78-6), isoamyl acetate (CAS number 123-92-2) and isobutanol (CAS number 78-83-1), respectively, were used. A permeation tube with a permeation rate of 4831 ng/min at 45°C (LNI Schmidlin SA) was used to calibrate ethyl hexanoate (CAS number 123-66-0) concentration. The permeation tube was placed in an oven at 45°C, and diluted with air at 51 mL/min.

2.2.2. Measurements in the liquid

NaCl (1 g) was added to 3 mL of the fermentation sample in a 20 mL vial. To standardise the equilibrium conditions between the liquid and the headspace, the ethanol concentration in

the vial was adjusted to 11% by adding 2 mL of a mixture of 12 g/L tartaric acid solution diluted either in water or a ethanol/ water mix (30% v/v). Fifty µL of 4-Methylpentan-2-ol at a concentration 3 g/L was added to the vial as an internal standard. The sample vial was heated and agitated for 5 min at 50°C in a headspace autosampler HT200 equipped with a gastight syringe, preheated to 60°C. One mL of headspace gas was analysed by using a HP6890 GC coupled with a FID detector. The injector temperature was 240°C. The GC oven was equipped with a BP20 column (30 m × 0.53 mm × 1.0 µm, SGE). H₂ was used as the carrier gas at a constant flow rate of 4.8 mL/min. The oven temperature programme was 40°C for 3 min, 3°C/min to 80°C, 15°C/min to 160°C held for 1 min, then 30°C/min to 220°C and then held at 220°C for 2 min. The detector was set at 250°C. Peak areas were acquired with Agilent Chemstation software.

2.3. Determinations of gas-liquid partition coefficients (k_i)

The gas-liquid partition coefficients (k_i) during fermentation were followed by dividing the volatile concentrations in the tank headspace by the concentrations in the liquid at various times. Several k_i were also determined in samples taken at different stages of fermentation by using the Phase Ratio Variation (PRV) method in static conditions as previously described [12, 17].

2.4. Modelling

The equations of the mathematical model (listed in the section Results) were implemented in a program written under Matlab 7 (The Matworks Inc., Natick, MA). The parameters were identified by nonlinear regression under Matlab, using the Statistic Toolbox.

3. Results and discussion

3.1. Model development

3.1.1. Effects of CO₂ stripping and of must composition

Morakul et al. [12] used synthetic solutions with increasing ethanol concentrations and decreasing sugar concentrations to simulate the evolution of the composition of must during fermentation. They showed that the gas-liquid partition coefficients (k_i) of higher alcohols and esters continuously decreased as the composition of a model wine fermentation medium changed because the sugar induces ‘salting out’ of volatile compounds (at the beginning of a fermentation) whereas the ethanol increases their solubility, and thereby decreases their volatility. The authors also observed a decrease of the relative gas-liquid ratio of these molecules during fermentation. However, the ratios were expressed in arbitrary units and could not be directly compared to the values of k_i obtained in synthetic solutions, without any release of CO₂.

To complete this previous preliminary study, the first aim of the present work was to clarify the effect of stripping on gas-liquid partitioning of aroma compounds. The stripping effect is complex because, in usual fermentations, both the rate of CO₂ production and other factors vary throughout the fermentation process. The problems associated with this complexity were overcome by controlling the rate of CO₂ release. The effect of stripping was indeed isolated by running defined fermentations, in which the rate of CO₂ production was kept constant by perfusion of ammoniacal nitrogen controlled. By modifying the amount of assimilable nitrogen initially present in the must i.e. 40 mg/L or 120 mg/L (no addition or addition of 80 mg/L of ammoniacal nitrogen), it was possible to set up two fermentations

(CRF-0.3 and CRF-0.6) in which the rates of CO₂ production were kept constant at 0.3 g /L.h and 0.6 g /L.h respectively. The rate of CO₂ production was regulated between 10 and 85% of the fermentation progress. Fig. 1 compares the evolution of the CO₂ production rate (i) in these two fermentations and in (ii) an isothermal fermentation at 20°C, without any control of the CO₂ production rate (IF-20-B).

Changes in gas-liquid concentration ratios of ethyl acetate, isoamyl acetate, ethyl hexanoate and isobutanol were compared in these three different fermentation conditions. They were also compared to the values of k_i calculated by the static headspace PRV method in samples taken during fermentation. In these samples, k_i was measured at equilibrium, in the absence of CO₂ release. **Fig. 2** shows the results obtained for isobutanol and isoamyl acetate, the following observations being also valid for the other volatile molecules (data not shown). A very remarkable result was that (i) almost identical decreases in k_i with increasing ethanol concentration were observed whatever the CO₂ production rate and (ii) values of the partition coefficients were close to those obtained at equilibrium without any CO₂ release. It can therefore be concluded that stripping did not significantly change the gas-liquid partitioning of aroma compounds during fermentation and that the two phases always remained at equilibrium throughout the process in spite of the CO₂ flux.

Therefore, at constant temperature, the values of k_i which reflect changes in the gas-liquid partitioning of aroma compounds in fermenting musts only result from changes in the composition of the liquid phase, that is the decreasing sugar concentration and increasing ethanol concentration.

Consequently, at constant temperature, the evolution of k_i can be written as follows:

$$k_i = A \times E + B \quad (\text{Equation 1})$$

where A and B are constants depending on the considered compound i , and E is the ethanol concentration (g/L) in the liquid phase, which is proportional to the sugar consumption and

CO₂ production. E is therefore representative of the whole matrix effect corresponding to the modification of the ethanol and sugar concentrations.

3.1.2 Effect of temperature

Gas-liquid partitioning not only depends on the composition of the liquid phase; it is also strongly affected by the temperature. For a constant medium composition, the Clausius-Clapeyron law is usually applied to the changes in partition coefficient (k_i) with temperature [19]:

$$-\frac{d(\ln k_i)}{d(1/T)} = \frac{\Delta H_{vap}}{R} \quad \text{or} \quad \ln k_i = C - \frac{\Delta H_{vap}}{R \times T} \quad (\text{Equation 2})$$

Where ΔH_{vap} is the phase change enthalpy of the volatile compound expressed in J/mol, T is the absolute temperature (K), R is the perfect gas constant (8.413 J/mol.K) and C is a constant.

Nevertheless, Morakul et al. [12] showed that, in synthetic media, the value of the parameter ΔH_{vap} is not constant. For example, the ΔH_{vap} of isobutanol was 71.4 kJ/mol in a synthetic medium simulating a grape juice and 37.8 kJ/mol in a synthetic medium simulating a wine. As a consequence, the effect of the temperature on the gas-liquid partitioning not only depends on the temperature but is also a function of the composition of the liquid phase. So, the classical Clausius-Clapeyron expression was modified to introduce the dependence of the values C and ΔH_{vap} on the medium composition:

$$\ln k_i = D1 + D2 \times E - \frac{D3 + D4 \times E}{R \times T} \quad (\text{Equation 3})$$

Where T is the absolute temperature and D1, D2, D3 and D4 are constants. To give a clearer physical meaning to the parameters of the model, we modified the previous equation by including a reference temperature (T_{ref}), so the model expression became:

$$\ln k_i = F1 + F2 \times E - \frac{F3 + F4 \times E}{R} \left(\frac{1000}{T} - \frac{1000}{T_{ref}} \right) \quad (\text{Equation 4})$$

Where T is the **current absolute** temperature, T_{ref} corresponds to the absolute reference temperature, i.e 293 K (20°C) in this study and F1, F2, F3 and F4 are constants. F1 is the logarithm of the partition coefficient ($\ln k_i$) at the reference temperature in the initial must ($E = 0$). F2 represents the sensitivity of the partition coefficient to medium composition at the reference temperature. F3 corresponds to the value of ΔH_{vap} in the initial must ($E = 0$), ΔH_{vap} giving the sensitivity of k_i to changes in temperature. F4 represents the sensitivity of ΔH_{vap} to changes in medium composition, described here as the ethanol concentration. The arbitrary factor 1000 was introduced for numerical convenience, to have numeric parameter values (F1-F4) of order of one. This generally favours reliable identification with nonlinear regression software. This factor can be of course absorbed into the values of F3 and F4.

The mathematical expression detailed in Equation 4 was then used in the subsequent steps to model the evolution of the k_i values for ethyl acetate, isoamyl acetate, ethyl hexanoate and isobutanol throughout the wine fermentation as a function both of the ethanol production and of the temperature.

3.2 Model identification

Model parameters in Equation 4 were determined **simultaneously** by nonlinear regression based on the values of the k_i (in concentration ratio) obtained from three experiments (i) isothermal fermentation at 20°C (IF-20-A) (ii) isothermal fermentation at 30°C (IF-30) and (iii) anisothermal fermentations between 15 and 30°C (**AF-15-30**). All k_i measurements (**41 values, including 14 from IF-20-A, 11 from IF-30 and 16 from AF-15-30**) were used to determine the parameters F1-F4 together with their standard **errors** (**Table 2**).

The estimated values of $F1$ were consistent with the values of $\ln k_i$ measured by the PRV method [12] in static conditions in the must at the beginning of fermentation (-5.11, -3.94, -3.68 and -7.72 for ethyl acetate, isoamyl acetate, ethyl hexanoate and isobutanol, respectively). Among the volatile compounds studied, ethyl hexanoate had the highest $\ln k_i$ consistent with the higher volatility of this compound whereas isobutanol, which had a lower value of $\ln k_i$, is always less volatile than esters.

$F2$ values were negative, indicating that k_i decreased as the ethanol concentration increased. The most negative value indicates the greatest sensitivity of k_i to the changes in liquid composition. Ethyl hexanoate was the molecule most affected by the liquid composition ($F2 = -1.39 \times 10^{-2}$) and ethyl acetate and isobutanol were less sensitive with $F2$ values of -2.90×10^{-3} and -4.10×10^{-3} , respectively. This sensitivity is seemingly related to the hydrophobicity of the molecule. Indeed, the hydrophobicity constant values ($\text{Log}K_{ow}$ at 25°C), i.e. 0.76, 0.73, 2.25 and 2.83, for isobutanol, ethyl acetate, isoamyl acetate and ethyl hexanoate, respectively (SRC Interactive PhysProp database, Syracuse), are in the same order as $F2$.

The values of $F3$ representing the sensitivity of k_i to the temperature, were compared to previously reported ΔH_{vap} values [12]. The ΔH_{vap} was 39, 39.4, 67.5 and 71.4 kJ/mol for ethyl acetate, isoamyl acetate, ethyl hexanoate and isobutanol, respectively. Although the values are in the same order of magnitude as our $F3$ values, there are differences of about 20% for isoamyl acetate, ethyl hexanoate and isobutanol. These differences between $F3$ and ΔH_{vap} may be a consequence of the differences in the matrix used, as the $F3$ values were identified using the natural must whereas ΔH_{vap} were calculated using a synthetic medium which contained only sugar and weak acids to simulate the must at the start of the fermentation. The difference between $F3$ and ΔH_{vap} for ethyl acetate is higher than 40%, and this might be due to an atypical behaviour of this compound. Indeed, temperature had little influence on the

value of k_i of ethyl acetate and therefore, it is difficult to determine precisely the values of F3 and F4.

A sensitivity analysis of the model was conducted to assess the effect and the relative importance of the model parameters. Average conditions ($T=25^{\circ}\text{C}$ and ethanol concentration $E=45\text{g/L}$) were selected and each parameter (F1-F4) was arbitrarily increased by 30%. As expected, parameter F1 (directly related to the partition value) had the higher sensitivity, comprised between 64% for ethyl hexanoate and 92% for isobutanol. Its knowledge is thus the most important for accurately predicting k_i . The second most important parameter (between 10 and 16% sensitivity) was F3, confirming the usually reported fact that temperature has a significant effect on volatility. The effect of the medium composition expressed via F2 was similar (between 4% for ethyl acetate and 17% for ethyl hexanoate). Finally, parameter F4 was found to have some effect only for ethyl acetate (4%), and less than 1% for the other compounds studied; this is consistent with the model identification results indicating that a significantly different from zero value of F4 could only be determined for ethyl acetate.

3.3. Model validation

After parameter identification, the variation of k_i as a function of ethanol concentration and temperature, according to equation 4, was plotted. **Fig. 3** shows the plot for fermentations used for parameter identification and **Fig. 4** that for independent fermentations: (i) isothermal fermentation at 20°C (IF-20-B) and (ii) anisothermal fermentation between 20 and 30°C (AF-20-30).

The mean relative error between model prediction values and the measured values was calculated as follows:

$$\varepsilon = \frac{1}{n} \sum \frac{|k_{ij}^{measured} - k_{ij}^{predicted}|}{k_{ij}^{measured}} \times 100\% \quad (\text{Equation 5})$$

Where n is the number of k_i measurements used for model validation. **Table 3** indicates that (i) the average differences between the experimental and the calculated values were less than 10% for isoamyl acetate, ethyl hexanoate and isobutanol and (ii) the precision of the k_i estimations was comparable for data from experiments not used for parameter identification. These results demonstrate the value of the model to predict k_i with a good accuracy for these 3 compounds. The prediction was much less satisfactory for ethyl acetate with differences up to 33%, due to an atypical behaviour of this compound.

One of the main reasons why predicting k_i is valuable is that it allows calculation of the concentrations of volatiles in the gas phase from measurements in the liquid, and the reverse. It is therefore possible to calculate the global production by adding the volatile concentration in the liquid to the amount lost in the gas phase (Equation 6):

$$Losses = \frac{\int_0^{t_{end}} C^{gas}(t) \times Q(t) \times dt}{C^{liq}(t_{end}) + \int_0^{t_{end}} C^{gas}(t) \times Q(t) \times dt} \times 100\% \quad (\text{Equation 6})$$

Where t is the current time (h), t_{end} is the final time (h), $C^{gas}(t)$ is the concentration of volatile compound in the gas phase at time t expressed in mg/L of CO₂, $Q(t)$ is the CO₂ specific flow rate at time t expressed in (L of CO₂/L of must)/h and C^{liq} is the total concentration of the volatile compound in the must at the end of the fermentation (mg/L of must).

The relative amount of volatiles lost, i.e the ratio of losses to total production, is of particular technological interest. **Table 4** compares measured (using concentrations in the gas) and predicted (using k_i values and concentrations in the liquid) loss values. The predicted losses were very close to the values measured, illustrating the accuracy of the model. The

amounts of lost volatile in the gas phase varied with the volatility of the compounds: it was negligible in the case of isobutanol but was 70% for ethyl hexanoate at 30°C.

4. Conclusion

The gas-liquid partitioning of the main aroma compounds produced during winemaking fermentations, namely isobutanol, isoamyl acetate, ethyl hexanoate and to a lesser extent ethyl acetate, was accurately predicted by the model. The model, based on the effects of changes to the matrix and temperature during fermentation, allowed estimation of the partition coefficient (k_i) with less than 10% error, except for ethyl acetate. The benefits of predicting k_i include allowing the calculation of the total production of the volatile compounds from a single measure (concentration in the gas or in the liquid phase). This is particularly advantageous in the case of on-line monitoring of the main aroma compounds in the gas, as described by Mouret et al. [2]. The ability to calculate the total production and to differentiate between the amounts remaining in the liquid and those lost in the CO₂ are major issues for improving our understanding of yeast metabolism and optimising fermentation control. From a microbiological point of view, the total amount produced needs to be considered whereas, from a technological point of view, the concentration remaining in the wine is more important. For some molecules, such as isobutanol, the losses in the gas are negligible but for more volatile compounds, in particular esters, such losses can represent a very significant proportion of the total production. Minimising these losses, by optimizing the fermentation control, particularly the temperature profile, is a significant challenge. The objective is to find the best compromise between fermentation kinetics and aroma production. The development of metabolic models predicting the synthesis of aroma compounds [20], in combination with

the model of gas-liquid partitioning and with a kinetic model [21] represents a complex but very promising prospect.

Acknowledgements

This research was funded by the European Union Seventh Framework Programme (FP7/2007-2013), under grant no. KBBE-212754.

References

- [1] Swiegers JH, Bartowsky EJ, Henschke PA, Pretorius IS. Yeast and bacterial modulation of wine aroma and flavour. Aust J Grape Wine Res 2005; 11: 139-173.
- [2] Mouret J-R, Nicolle P, Angenieux M, Aguera E, Perez M, Sablayrolles J-M. On-line measurement of 'quality markers' during winemaking fermentations. International Intervitis Interfructa Congress, March 24-26, 2010, Stuttgart, Germany.
- [3] Gee DA, Ramirez WF. A flavour model for beer fermentation. J Inst Brew 1994; 100: 321-329.
- [4] Trelea IC, Latrille E, Landaud S, Corrieu G. Reliable estimation of the key variables and of their rates of change in alcoholic fermentation. Bioprocess Biosyst Eng 2001; 24: 227-237.
- [5] Trelea IC, Titica M, Corrieu G. Dynamic optimisation of the aroma production in brewing fermentation. J Process Control 2004; 14: 1-16.
- [6] Banavara DS, Rabe S, Krings U, Berger RG. Modeling dynamic flavor release from water. J Agric Food Chem 2002; 50: 6448-6452.
- [7] Marin M, Baek I, Taylor AJ. Volatile release from aqueous solutions under dynamic headspace dilution conditions. J Agric Food Chem 1999; 47: 4750-4755.

399 [8] Nahon DF, Harrison M, Roozen JP. Modeling flavor release from aqueous sucrose
400 solutions, using mass transfer and partition coefficients. *J Agric Food Chem* 2000; 48: 1278-
401 1284.

402 [9] Robinson AL, Ebeler SE, Heymann H, Boss PK, Solomon PS, Trengove RD. Interactions
403 between wine volatile compounds and grape and wine matrix components influence aroma
404 compound headspace partitioning. *J Agric Food Chem* 2009; 57: 10313-10322.

405 [10] Tsachaki M, Gady A-L, Kalopesas M, Linforth RST, Athes V, Marin M, Taylor AJ.
406 Effect of ethanol, temperature, and gas flow rate on volatile release from aqueous solutions
407 under dynamic headspace dilution conditions. *J Agric Food Chem* 2008; 56: 5308-5315.

408 [11] Tsachaki M, Linforth RST, Taylor AJ. Aroma release from wines under dynamic
409 conditions. *J Agric Food Chem* 2009; 57: 6976-6981.

410 [12] Morakul S, Athes V, Mouret J-R, Sablayrolles J-M. Comprehensive study of the
411 evolution of gas-liquid partitioning of aroma compounds during wine alcoholic fermentation.
412 *J Agric Food Chem* 2010; 58: 10219-10225.

413 [13] Ferreira V, Pena C, Escudero A, Cacho J. Losses of volatile compounds during
414 fermentation. *Z Lebensm-Unters Forsch* 1996; 202: 318-323.

415 [14] Francis IL, Newton JL. Determining wine aroma from compositional data. *Aust J Grape*
416 *Wine Res* 2005; 11: 114-126.

417 [15] Manginot C, Sablayrolles JM, Roustan JL, Barre P. Use of constant rate alcoholic
418 fermentations to compare the effectiveness of different nitrogen sources added during the
419 stationary phase. *Enzyme Microb Technol* 1997; 20: 373-380.

420 [16] Sablayrolles JM, Barre P. Kinetics of alcoholic fermentation under anisothermal
421 conditions.2. Prediction from the kinetics under isothermal conditions. *Am J Enol Vitic* 1993;
422 44: 134-138.

423 [17] Athes V, Pena y Lillo M, Bernard C, Perez-Correa R, Souchon I. Comparison of
424 experimental methods for measuring infinite dilution volatilities of aroma compounds in
425 water/ethanol mixtures. J Agric Food Chem 2004; 52: 2021-2027.

426 [18] El Haloui N, Picque D, Corrieu G. Alcoholic fermentation in winemaking: On-line
427 measurement of density and carbon dioxide evolution. J Food Eng 1988; 8: 17-30.

428 [19] Meynier A, Garillon A, Lethuaut L, Genot C. Partition of five aroma compounds
429 between air and skim milk, anhydrous milk fat or full-fat cream. Lait 2003; 83: 223-235.

430 [20] Charnomordic B, David R, Dochain D, Hilgert N, Mouret J-R, Sablayrolles J-M, Vande
431 Wouwer A. Two modelling approaches of winemaking: first principle and metabolic
432 engineering. Math Comp Model Dyn 2010; 16: 535 - 553.

433 [21] Malherbe S, Fromion V, Hilgert N, Sablayrolles, J-M. Modeling the effects of
434 assimilable nitrogen and temperature on fermentation kinetics in enological conditions.
435 Biotechnol and Bioeng 2004; 86: 261-272.

436

Figure captions

Fig 1-1. Evolution of the CO_2 production rate as a function of ethanol concentration, for a standard fermentation IF-20-B (...), and for constant rate fermentations at CO_2 production rates of 0.3 g/L.h CRF-0.3 (+) and 0.6 g/L.h CRF-0.6 (— —) and assimilable nitrogen concentration added to control the CO_2 production rate (—). Initial assimilable nitrogen concentrations in the musts: 240, 40 and 120 mg/L. Temperature: 20°C.

Fig 2. Changes in gas-liquid ratio (k_i) as a function of ethanol concentration for isoamyl acetate (A) and isobutanol (B); standard fermentation IF-20-A (×), constant rate fermentation at 0.3 g/L.h CRF-0.3 (□) and constant rate fermentation at 0.6 g/L.h CRF-0.6 (Δ). Comparison with k_i measured in static conditions by the PRV method (◇). Temperature: 20°C.

Fig 3. Comparison of predicted and measured k_i for isoamyl acetate (B) and isobutanol (C) in fermentations run at different fermentation temperatures (A) for model identification. (B) and (C) show predicted (...) and measured (□) k_i during an isothermal fermentation at 20°C (IF-20-A); predicted (—), measured (●) k_i during an anisothermal fermentation run between 15-30°C (AF-15-30); predicted (—), measured (×) k_i during an isothermal fermentation at 30°C (IF-30).

Fig 4. Comparison of predicted and measured values for k_i for isoamyl acetate (B) and isobutanol (C) in fermentations run at different fermentation temperatures (A) for model validation. (B) and (C) show predicted (...) and measured (□) k_i during an isothermal fermentation at 20°C (IF-20-B); predicted (—), measured (●) k_i during an anisothermal fermentation run between 20-30°C (AF-20-30). The (A) graph shows temperature profiles for the two fermentation runs IF-20-B and AF-20-30.

Table 1. Experimental conditions of the fermentation trials, used for model identification and for model validation.

Fermentations	Initial assimilable nitrogen (mg/L)	Regulated temperature (°C)	Identification / validation
Constant rate fermentations (CRF) ^a			
1) CRF-0.3	40	20	
2) CRF-0.6	120	20	
Isothermal fermentations (IF) ^b			
3) IF-20-A	140	20	Model identification
4) IF-20-B	240	20	Model validation
5) IF-30	240	30	Model identification
Anisothermal fermentations (AF) ^c			
6) AF-15-30	140	15 to 30	Model identification
7) AF-20-30	140	20 to 30	Model validation

^aThe rate of CO₂ production was kept constant at 0.3 and 0.6 g/L.h by addition of ammoniacal nitrogen

^bThe temperature during fermentation was regulated at the indicated constant values

^cThe fermentation temperature was increased by 0.2°C per g/L of CO₂ produced

Table 2. Numerical values for the model parameters identified from Equation 4 and given with their standard error.

Parameter	Ethyl acetate	Isoamyl acetate	Ethyl hexanoate	Isobutanol
F1 (-)	-6.11 ± 0.07	-3.98 ± 0.03	-3.09 ± 0.31	-8.45 ± 0.03
F2 (g/L)	-2.9×10 ⁻³ ± 1.2×10 ⁻³	-9.6×10 ⁻³ ± 0.5×10 ⁻³	-1.39×10 ⁻² ± 0.06×10 ⁻²	-4.1×10 ⁻³ ± 0.5×10 ⁻³
F3 (kJ/mol ^l)	71 ± 9	49± 4	55 ± 4	53 ± 4
F4 (kJ mol/g.L)	-4.4×10 ⁻¹ ± 1.5×10 ⁻¹	-1.7×10 ⁻³ ± 59×10 ⁻³ *	8.6×10 ⁻² ± 6.1×10 ⁻² *	6.4×10 ⁻³ ± 60×10 ⁻³ *

* A standard error leading to the value zero being included in the 95% confidence interval means that the parameter is not significantly different from zero.

1
2

Table 3. Mean relative errors (%) between predicted and measured k_i calculated according to equation 5, with n: number of k_i measurements per fermentation.

Fermentations	Ethylacetate		Isoamylacetate		Ethyl hexanoate		Isobutanol	
	%	n	%	n	%	n	%	n
Fermentations used for model identification								
Anisothermal 15-30°C	12.8	16	4.13	16	4.1	16	3.28	16
Isothermal at 20°C	13.5	14	5.15	14	6.5	14	6.23	14
Isothermal at 30°C	14.5	11	3.47	10	7.0	12	4.63	12
Mean	13.5		4.25		5.7		4.65	
Independent fermentations used for model validation only								
Anisothermal 20-30°C	17.2	11	9.07	11	6.6	11	7.94	11
Isothermal at 20°C	32.8	10	5.77	10	4.2	10	4.92	10
Mean	24.7		7.42		5.4		6.50	

3

1 **Table 4. Volatile** compound losses (%). Comparison of predicted* (pred.) and measured**
2 (meas.) values for losses, in %.

Experiments	Ethyl acetate		Isoamyl acetate		Ethyl hexanoate		Isobutanol	
	pred.	meas.	pred.	meas.	pred.	meas.	pred.	meas.
Anisothermal 15-30°C	7.48	6.87	33.3	33.7	54.2	54.3	0.66	0.65
Isothermal at 20°C	5.86	6.02	25.2	25.6	44.6	44.4	0.55	0.54
Isothermal at 30°C	13.6	13.0	44.1	42.2	70.9	71.0	1.33	1.33
Anisothermal 20-30°C	10.5	12.5	45.0	46.7	66.3	64.7	0.93	1.01
Isothermal at 20°C	5.59	8.73	27.1	26.2	46.2	45.3	0.63	0.63

3 *Predicted losses were calculated from k_i values and concentrations of the volatiles in the
4 liquid.

5 **Measured losses were calculated from concentrations of the volatiles in the gas.

Figure1

Fig 1

Fig 2.

Fig 3

Fig 4.