Micromechanical modelling of internal erosion

Stéphane Bonelli, Didier Marot

► To cite this version:

Stéphane Bonelli, Didier Marot. Micromechanical modelling of internal erosion. European Journal of Environmental and Civil Engineering, 2011, 15 (8), pp.1207-1224. 10.3166/EJECE.15.1207-1224 . hal-01007039

HAL Id: hal-01007039

<https://hal.science/hal-01007039>

Submitted on 12 Dec 2018

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Micromechanical modeling of internal erosion

Stéphane Bonelli* — **Didier Marot****

** Cemagref, Unité de Recherche Ouvrages Hydrauliques
3275, route de Cézanne, CS 400061, F-13182 Aix-en-Provence Cedex 5
stephane.bonelli@cemagref.fr*

*** GeM UMR CNRS 6183, Institut de Recherche en génie civil et mécanique
Université de Nantes, IUT de Saint-Nazaire
58, rue Michel Ange, BP 420, F-44606 Saint-Nazaire Cedex
didier.marot@univ-nantes.fr*

ABSTRACT. Suffusion is the internal erosion process by which finer soil particles are detached from the solid matrix, and transported through constrictions by seepage flow. At the macroscopic scale, this is a bulk erosion process and corresponds to a source term in the mass balance equations. This paper constitutes a step towards bridging the gap between the counter intuitive bulk erosion model and our intuition that erosion is essentially an interfacial process. We suggest that a framework within suffusion can be viewed as a clay/water interface erosion at the microscopic scale. The coefficient of surface erosion appears to be a relevant parameter for the suffusion bulk erosion law. The comparison between the results of the present modeling study and previously published experimental data supports the validity of our approach.

RÉSUMÉ. La suffusion est le processus d'érosion interne de détachement de particules fines de sol, et de transport de ces particules par écoulement d'eau entre les particules les plus grosses. A l'échelle macroscopique, ce phénomène est une érosion de volume, et il est représenté par un terme source dans les équations de conservation de la masse. Notre intuition est que l'érosion est un phénomène intrinsèquement interfacial. Ce travail vise à comprendre ce paradoxe apparent. Nous proposons un cadre de travail qui permet de considérer la suffusion comme une érosion d'interface argile/eau à l'échelle microscopique. Le coefficient d'érosion de surface apparaît comme un paramètre pertinent de la loi d'érosion de volume de suffusion. La comparaison entre les résultats de cette modélisation et des résultats expérimentaux publiés confirme la pertinence de notre approche.

KEYWORDS: internal erosion, suffusion, interfacial erosion, homogenization.

MOTS-CLÉS: érosion interne, suffusion, érosion interfaciale, homogénéisation.

1. Introduction

Erosion is the removal of material caused by the eroding power of the flow and is essentially an interfacial process. Suffusion (or suffosion) is an internal erosion process by which finer soil particles are detached from the solid matrix and transported through pore constrictions by seepage flow. The term suffusion (L. suffossio, from suffodere, to dig under) was introduced by Pavlov in 1898. The internal instability that results from suffusion gives rise to a wide range of hazards including piping and sinkholes (Fell and Fry, 2007; Gutiérrez *et al.*, 2008).

Two scales must be considered: a micro-scale defined at the level of the pore constrictions, and a macro-scale corresponding to the Representative Elementary Volume (REV). The REV is typically a laboratory sample, or a spatial integration point in the Finite Element Method (*e.g.* a Gauss point).

The process of bulk erosion may be considered at the macro-scale as a transition from solid-like to fluid-like behaviour. This transition is smooth, and usually described by using a three-phase model (solid, fluid and fluidized solid). These three phases interact while being constrained by the balance equations. For the sake of clarity, the equations are written here in one-dimensionnal evolution and dilute suspension flow as follows (Papamichos *et al.*, 2001; Papamichos and Vardoulakis, 2005; Papamichos, 2010; Wan and Wang, 2004):

$$\frac{\partial \phi}{\partial t} = \frac{r}{\rho_{Clay}} \text{ (solid mass balance equation)} \quad [1]$$

$$\frac{\partial q}{\partial X} = 0 \text{ (pore-fluid mass balance equation)} \quad [2]$$

$$-\frac{\partial p}{\partial X} = F \text{ (pore-fluid momentum balance equation)} \quad [3]$$

$$F = \frac{\eta_w}{\kappa} q \text{ (Darcy constitutive law)} \quad [4]$$

In these equations, ϕ is the porosity, ρ_{Clay} is the eroded material density, q is the seepage velocity, p is the water pressure, F represents the mechanical interaction between the pore-fluid and the solid matrix, η_w is the water viscosity and κ is the geometric permeability.

The term r is introduced into the mass balance Equation [1] to describe the detachment of particles via an erosion law. The description of suffusion at the macroscopic scale therefore corresponds to a bulk erosion process. The erosion constitutive law is introduced as usual by phenomenological analysis, at the macroscale.

Few attempts have been made to relate macroscopic and microscopic quantities in a multi-scale description of the suffusion process. This paper is intended as a further step in this direction, on the basis of the results published by Bouddour *et al.* (1996). What follows is not a program aimed at reformulating the theory of suffusion as a whole based on homogenization, rather attention focuses explicitly on the goal of bridging the gap between the counter intuitive bulk erosion model and our intuition that erosion is essentially an interfacial process.

2. Description of the representative elementary volume

Let us consider a representative elementary volume Ω (REV) of a soil partitioned into three disjoint regions $\Omega = \Omega_{Pore} \cup \Omega_{Clay} \cup \Omega_{Sand}^s$ (Figure 1):

i) a connected meso-pore domain Ω_{Pore} of boundary $\Gamma_{Pore} = \partial\Omega_{Pore}$, with volume fraction ϕ and specific surface S_{Pore}

$$\phi = \frac{|\Omega_{Pore}|}{|\Omega|}, \quad S_{Pore} = \frac{|\Gamma_{Pore}|}{|\Omega_{Pore}|} \quad [5]$$

ii) a clay matrix domain Ω_{Clay} of volume fraction of boundary $\Gamma_{Clay} = \partial\Omega_{Clay}$, with volume fraction ϕ_V and specific surface S_{Clay}

$$\phi_V = \frac{|\Omega_{Clay}|}{|\Omega|}, \quad S_{Clay} = \frac{|\Gamma_{Clay}|}{|\Omega_{Clay}|} \quad [6]$$

iii) a sand grain domain Ω_{Sand}^s of volume fraction of boundary $\Gamma_{Sand} = \partial\Omega_{Sand}$, with porosity ϕ_{Sand} and specific surface S_{Sand}

$$1 - \phi_{Sand} = \frac{|\Omega_{Sand}^s|}{|\Omega|}, \quad S_{Sand} = \frac{|\Gamma_{Sand}|}{|\Omega_{Sand}^s|} \quad [7]$$

The meso-pore domain contains an incompressible two-phase flow of water and clay particles, assumed to be a dilute suspension (density ρ_w , viscosity η_w). The clay matrix, which is considered as a continuum, consists of two phases: water, and clays particles Ω_{Clay}^s (volume fraction $1 - \phi_{Clay} = |\Omega_{Clay}^s| / |\Omega_{Clay}|$).

Here, the superscript s in Ω_{Sand}^s and Ω_{Clay}^s denotes the solid constituent, and not the solid phase. For the clay domain, the solid phase Ω_{Clay} is the sum of the solid constituent Ω_{Clay}^s and the micro-pores, saturated by water. All solid constituents are of density ρ_s . The sand grains are homogeneous and impervious. The clay matrix

density is $\rho_{Clay} = (1 - \phi_{Clay})\rho_s + \phi_{Clay}\rho_w$. From Figure 1, we infer the important connection:

$$\varphi_V = \phi_{sand} - \phi \quad [8]$$

The porosity $\phi + \varphi_V\phi_{Clay}$ can be divided into macro-porosity ϕ corresponding to the meso-pore domain, and micro-porosity ϕ_{Clay} in the clay matrix. This description accounts for two observation scales:

- (i) local (microscopic) scale, which is associated with the characteristic size of heterogeneities (clay aggregates, sand grains, meso-pores);
- (ii) the macroscopic scale, which corresponds to entire soil layers and is most important for practical purposes.

The scale corresponding to clay particles and micro-pores in the clay matrix is not considered. This type of heterogeneous soil is similar to the classical double-porosity model for modelling flow in fractured porous media, developed in the early 1960s. However, while the meso-pore domain makes up only a small percentage of the total pore volume, it transmits a major portion of the flow through the REV, and the fluid exchange between the clay matrix and the meso-pore domain can be neglected.

We assume that the soil is a clayey sand (Revil and Cathles, 1999; Revil *et al.*, 2002), and that the size of the meso-pores is much greater than the size of the micro-pores. Therefore, $\varphi_V < \phi_{Sand}$ and the sand matrix is connected while the clay matrix may not be.

We assume that erosion occurs only at the interface $\Gamma_{Clay} \cap \Gamma_{Pore}$ of the clay matrix and the meso-pore domain (sand grains are not erodible) (Figure 2). The erosion process is therefore external to the clay matrix, and does not affect its porosity ϕ_{Clay} , nor its density ρ_{Clay} .

Figure 1. Relative proportions of each constituent for a sand-clay mixture in the clayey sand domain

As illustrated in Figure 3, suffusion may occur when $0 < \phi_V < \phi_{sand}$, whereas no suffusion occurs when $\phi_V = 0$ (no clay) or $\phi_V = \phi_{Sand}$ (the pore constrictions are too small).

3. Microscopic equations of Stokes flow with interfacial erosion

The mechanical state is such that effective stresses and matrix deformations are negligible. Physico-chemical effects (like dissolution or deposition) are not considered. The porosities ϕ_{Sand} and ϕ_{Clay} are thus constant. The Reynolds number is small and inertia is neglected.

We take $a(\mathbf{x})$ to denote any quantity a varying at the micro-scale. The Stokes equations for the pore flow within Ω_{Pore} are:

$$\underbrace{\nabla \cdot \mathbf{u} = 0}_{\text{Fluid mass balance equation}} \quad \text{in } \Omega_{Pore} \quad [9]$$

$$\underbrace{\nabla \cdot \mathbf{T} = 0}_{\text{Fluid momentum balance equation}} \quad \text{in } \Omega_{Pore} \quad [10]$$

$$\underbrace{\mathbf{T} = -p\mathbf{I} + 2\eta_w \mathbf{D}(\mathbf{u}), \quad \mathbf{D}(\mathbf{u}) = \frac{1}{2}(\nabla \mathbf{u} + {}^T \nabla \mathbf{u})}_{\text{Fluid constitutive law}} \quad \text{in } \Omega_{Pore} \quad [11]$$

The jump equations on the sand/water interface are

$$\underbrace{\mathbf{u} \cdot \mathbf{n} = 0}_{\text{Total mass jump equation}} \quad \text{on } \Gamma_{Sand} \cap \Gamma_{Pore} \quad [12]$$

$$\underbrace{[\![\mathbf{T} \cdot \mathbf{n}]\!]}_{\text{Momentum jump equation}} = 0 \quad \text{on } \Gamma_{Sand} \cap \Gamma_{Pore} \quad [13]$$

The jump equations on the clay/water interface are (Bonelli and Brivois, 2006; Brivois *et al.*, 2007)

$$\underbrace{[\![\rho(\mathbf{w} - \mathbf{u}) \cdot \mathbf{n}]\!]}_{\text{Total mass jump equation}} = 0 \quad \text{on } \Gamma_{Clay} \cap \Gamma_{Pore} \quad [14]$$

$$\underbrace{[\![\rho \mathbf{u}(\mathbf{w} - \mathbf{u}) \cdot \mathbf{n}]\!]}_{\text{Momentum jump equation}} = -[\![\mathbf{T} \cdot \mathbf{n}]\!] \quad \text{on } \Gamma_{Clay} \cap \Gamma_{Pore} \quad [15]$$

Figure 2. *Schematic of the suffusion process viewed as the surface erosion of the clay matrix*

Figure 3. *Occurrence of suffusion in a clayey sand*

In these equations, $\mathbf{u}$ is the mass-weighted average velocity, $\mathbf{T}$ the Cauchy stress tensor, p the pressure, $\mathbf{n}$ the normal unit vector of Γ_{Pore} , $\mathbf{w}$ the velocity of Γ_{Pore} , and $\llbracket a \rrbracket$ the jump of any physical variable a across Γ_{Pore} . The total flux of eroded material (both particles and water) crossing Γ_{Pore} is $\dot{m} = \rho_{Clay} \mathbf{w} \cdot \mathbf{n}$.

Shear induced interfacial erosion is usually described with threshold laws such as (Ariathurai, 1986; Knapen, 2007; Partheniades, 1965; Zhu, 2001):

$$\dot{m} = k_{er} H\tau - \tau_c \text{ on } \Gamma_{Clay} \cap \Gamma_{Pore} \quad [16]$$

where τ_c (Pa) is the threshold stress, k_{er} (s/m) is the coefficient of surface erosion, $H[\bullet]$ is the Heaviside step function, $\tau = \|\boldsymbol{\tau}\|$ is the tangential shear stress at the interface, with $\boldsymbol{\tau} = [\mathbf{I} - \mathbf{n} \otimes \mathbf{n}] \cdot \mathbf{T} \cdot \mathbf{n}$.

An additional (and usual) constitutive assumption on the interface is that all tangential velocities are assumed to be continuous across Γ_{Pore} , implying the continuity of $\boldsymbol{\tau}$ across Γ_{Pore} :

$$[[\mathbf{u}_T]] = 0, \quad \mathbf{u}_T = [\mathbf{I} - \mathbf{n} \otimes \mathbf{n}] \cdot \mathbf{u} \text{ on } \Gamma_{Pore} \quad [17]$$

4. Inferring a suffusion law by means of spatial averaging

The complete set of Equations [9]-[17] has been previously used to study different systems by means of periodic homogenization (Bouddour *et al.*, 1996). Under the dilute flow assumption, the system obtained is formally similar to Equations [1]-[4]. Bouddour *et al.* (1996) established that the global volume flux of eroded material r Equation [1] is related to the local surface flux $\dot{m}$ Equation [16] of eroded material as follows:

$$\frac{1}{|\Omega|} \int_{\Gamma_{Pore}} \dot{m} d\Gamma = r \quad [18]$$

The surface of eroded material is

$$\Gamma_{er} = \{\mathbf{x} \in \Gamma_{Pore} \cap \Gamma_{Clay} / \tau(\mathbf{x}) > \tau_c(\mathbf{x})\} \quad [19]$$

Equation [18] involves the spatial average of the stress $\tau - \tau_c$ on Γ_{er} . As Γ_{er} depends on τ , this spatial average is not straightforward. The threshold stress τ_c is not considered, as the average of a local threshold law involving local stresses is known not to be a threshold law involving the average of the local stresses. We propose a first order approximation leading to:

$$\int_{\Gamma_{Pore}} H\tau - \tau_c d\Gamma = \frac{|\Gamma_{er}|}{|\Gamma_{Pore}|} \int_{\Gamma_{Pore}} \tau d\Gamma \quad [20]$$

In order to model the average shear stress on Γ_{Pore} , let $|\Delta P / L| \mathbf{e}$ the macroscopic pressure gradient denoted by $\partial p / \partial X$ in Equation [3], with magnitude $|\Delta P / L|$ and orientation $\mathbf{e}$ ($\|\mathbf{e}\| = 1$). This is the leading term of the microscopic Stokes flow, as the microscopic balance equation is $\nabla \cdot \mathbf{T} = |\Delta P / L| \mathbf{e}$. As p in Equation [11] now denotes only the pressure fluctuation, this gives the well-known result:

$$\frac{1}{|\Omega|} \int_{\Gamma_{Pore}} 2\eta_w \mathbf{D}(\mathbf{u}) \cdot \mathbf{n} d\Gamma = \phi \left| \frac{\Delta P}{L} \right| \mathbf{e} \quad [21]$$

The local (viscous) shear stress is defined as follows (Bouddour *et al.*, 1996):

$$2\eta_w \mathbf{D}(\mathbf{u}) \cdot \mathbf{n} = \xi \left| \frac{\Delta P}{L} \right|, \quad \xi_i = \left(\frac{\partial K_{ip}}{\partial x_q} + \frac{\partial K_{qp}}{\partial x_i} \right) e_p n_q \quad [22]$$

where $\mathbf{K}$ is the microscopic geometric permeability tensor. The volume average of $\mathbf{K}$ gives the macroscopic permeability tensor. Equation [21] shows that the spatial average of ξ is equal to $\phi \mathbf{e}$, which gives:

$$\left\| \frac{1}{|\Omega|} \int_{\Gamma_{Pore}} \xi d\Gamma \right\| = \phi \quad [23]$$

The spatial average of τ is more complicated:

$$\frac{1}{|\Omega|} \int_{\Gamma_{Pore}} \tau d\Gamma = \varsigma \phi \left| \frac{\Delta P}{L} \right| \quad [24]$$

$$\varsigma = \frac{\int_{\Gamma_{Pore}} \|\xi_T\| d\Gamma}{\left\| \int_{\Gamma_{Pore}} \xi d\Gamma \right\|} = \frac{1}{|\Omega_{Pore}|} \int_{\Gamma_{Pore}} \|\xi_T\| d\Gamma \quad [25]$$

$$\xi_T = [\mathbf{I} - \mathbf{n} \otimes \mathbf{n}] \cdot \xi \text{ on } \Gamma_{Pore} \quad [26]$$

Thorough analysis performed by means of numerical simulations (Golay *et al.*, 2010; Golay *et al.*, 2011), which is not detailed here for conciseness, shows that the normal component of the viscous stress vector on Γ is usually several orders of magnitude lower than the tangential component ($2\eta_w |\mathbf{n} \cdot \mathbf{D}(\mathbf{u}) \cdot \mathbf{n}| \ll \tau$). At the first order we can consider that $\|\xi_T\| \approx \|\xi\|$, and that $\varsigma \geq 1$.

The orientation of the microscopic velocity is given by $\mathbf{u} \propto \mathbf{K} \cdot \mathbf{e}$ as $\mathbf{u} = -\eta_w^{-1} \mathbf{K} \cdot \mathbf{e} |\Delta P / L|$ (Bouddour *et al.*, 1996). If this microscopic velocity has mostly the same direction as the macroscopic pressure gradient ($\mathbf{u} \propto \mathbf{e}$), then the use of Equation [22] shows that $\varsigma \approx 1$ (considering that $\|\xi_T\| \approx \|\xi\|$). This situation can be viewed as an isotropic behaviour with weak inhomogeneities and low tortuosity.

In reality, the porous domain of a soil comprises a mixture of pores of different shapes and orientations. This porous domain is modified by the microscopic erosion process. Suffusion is likely to induce anisotropy, but permeability anisotropy is also likely to affect the suffusion process. The quantity ς accounts for the relationship

between the local permeability gradient and the global pressure gradient. This parameter certainly plays a role in describing the strong coupling between the evolution of the microstructure due to erosion, and the macroscopic suffusion law.

We take i_w to denote the hydraulic gradient:

$$i_w = \frac{1}{\gamma_w} \left| \frac{\Delta P}{L} \right| \quad [27]$$

where $\gamma_w = \rho_w g$ is the water specific weight. Assuming a constant coefficient of erosion k_{er} , Equation [18] is re-written as follows:

$$r = \gamma_w k_{er} \phi \zeta \frac{|\Gamma_{er}|}{|\Gamma_{Pore}|} i_w \quad [28]$$

The macroscopic volume erosion appears here to be driven by the global pressure gradient, and not by the seepage velocity, as earlier suggested by Einstein (1937) and Sakthivadivel *et al.* (1966). In addition, the suffusion process and the evolution of the permeability anisotropy are coupled. Modelling this coupling phenomenon is, however, beyond the scope of this paper. For the sake of simplicity, we assume that ζ is a constant.

A model for $|\Gamma_{er}| / |\Gamma_{Pore}|$ is now introduced.

5. Modeling the evolution of internal surfaces

The dimensionless quantity $|\Gamma_{er}| / |\Gamma_{Pore}|$ can be split as follows:

$$\frac{|\Gamma_{er}|}{|\Gamma_{Pore}|} = \frac{|\Gamma_{Clay} \cap \Gamma_{Pore}|}{|\Gamma_{Pore}|} \frac{|\Gamma_{er}|}{|\Gamma_{Clay} \cap \Gamma_{Pore}|} \quad [29]$$

From the identity

$$|\Gamma_{Clay}| = |\Gamma_{Clay} \cap \Gamma_{Pore}| + |\Gamma_{Clay} \cap \Gamma_{Sand}| \quad [30]$$

we obtain

$$\frac{|\Gamma_{Clay} \cap \Gamma_{Pore}|}{|\Gamma_{Pore}|} = \frac{|\Gamma_{Clay}|}{|\Gamma_{Pore}|} - \alpha \frac{|\Gamma_{Sand}|}{|\Gamma_{Pore}|} \quad [31]$$

where

$$\alpha = \frac{|\Gamma_{Clay} \cap \Gamma_{Sand}|}{|\Gamma_{Sand}|} \quad [32]$$

Inserting the identity

$$|\Gamma_{Pore}| = |\Gamma_{Clay}| + |\Gamma_{Sand}| - 2|\Gamma_{Clay} \leftrightarrow \Gamma_{Sand}| \quad [33]$$

into Equation [32] yields

$$\alpha = \frac{1}{2} \left(1 + \frac{|\Gamma_{Clay}|}{|\Gamma_{Sand}|} - \frac{|\Gamma_{Pore}|}{|\Gamma_{Sand}|} \right) \quad [34]$$

Now inserting this result into Equation [31] gives

$$\frac{|\Gamma_{Clay} \cap \Gamma_{Pore}|}{|\Gamma_{Pore}|} = \frac{|\Gamma_{Clay}| + |\Gamma_{Pore}| - |\Gamma_{Sand}|}{2|\Gamma_{Pore}|} \quad [35]$$

From Equations [5], [6], [7] and [35] we finally obtain

$$\frac{|\Gamma_{Clay} \cap \Gamma_{Pore}|}{|\Gamma_{Pore}|} = \frac{S_{Clay}\phi_V + S_{Pore}\phi - S_{Sand}(1 - \phi_{Sand})}{2S_{Pore}\phi} \quad [36]$$

We now assume that a domain surface area scales with the corresponding domain volume raised to the power of 2/3. This is a simple surface/volume scaling: for example, the surface of a sphere scales with its volume with this exponent. The expressions $S_{Clay}\phi_V$ and $S_{Pore}\phi$ can therefore be modelled as follows:

$$\frac{S_{Clay}\phi_V}{S_{Clay}^0\phi_V^0} = \frac{\Gamma_{Clay}}{\Gamma_{Clay}^0} = \left(\frac{\Omega_{Clay}}{\Omega_{Clay}^0} \right)^{2/3} = \left(\frac{\phi_V}{\phi_V^0} \right)^{2/3} \quad [37]$$

$$\frac{S_{Pore}\phi}{S_{Pore}^0\phi^0} = \frac{\Gamma_{Pore}}{\Gamma_{Pore}^0} = \left(\frac{\Omega_{Pore}}{\Omega_{Pore}^0} \right)^{2/3} = \left(\frac{\phi}{\phi^0} \right)^{2/3} = \left(\frac{\phi_{Sand} - \phi_V}{\phi_{Sand} - \phi_V^0} \right)^{2/3} \quad [38]$$

Here, the superscript 0 in any quantity a^0 denotes the initial value of a .

From Equations [5], [6], [7] and [33] we obtain:

$$S_{Pore}\phi = S_{Clay}\phi_V + S_{Sand}(1 - \phi_{Sand})(1 - 2\alpha) \quad [39]$$

The quantity α of Equation [32] must be equal to zero if $\phi_V = 0$ ($\Gamma_{Clay} = \emptyset$). By using Equations [38] and [39], we infer the identity:

$$S_{Pore}^0(\phi^0)^{1/3}(\phi_{Sand})^{2/3} = S_{Sand}(1 - \phi_{Sand}) \quad [40]$$

By using Equation [40], Equations [37] and [38] can now be written as follows:

$$S_{Clay} \phi_V = S_{Sand} (1 - \phi_{Sand}) \left(\frac{\phi_V}{\phi_{Sand}} \right)^{2/3} \quad [41]$$

$$S_{Pore} \phi = S_{Sand} (1 - \phi_{Sand}) \left(1 - \frac{\phi_V}{\phi_{Sand}} \right)^{2/3} \quad [42]$$

Inserting the above results into Equation [36] finally yields:

$$\frac{|\Gamma_{Clay} \cap \Gamma_{Pore}|}{|\Gamma_{Pore}|} = \frac{\left(\frac{\phi_V}{\phi_{Sand}} \right)^{2/3} + \left(1 - \frac{\phi_V}{\phi_{Sand}} \right)^{2/3} - 1}{2 \left(1 - \frac{\phi_V}{\phi_{Sand}} \right)^{2/3}} \quad [43]$$

For the sake of simplicity, we retain a first order approximation:

$$\frac{|\Gamma_{Clay} \cap \Gamma_{Pore}|}{|\Gamma_{Pore}|} = \frac{1}{2} \left(\frac{\phi_V}{\phi_{Sand}} \right)^{2/3} \quad [44]$$

A model for $|\Gamma_{er}| / |\Gamma_{Clay} \cap \Gamma_{Pore}|$ is now introduced. In the erosion process of the enlargement of a pipe (Bonelli *et al.*, 2006; Bonelli and Brivois, 2008), the limitation of the amount of eroded material is a structural piece of information (it may be the earth-dam height for example). For suffusion, the situation is entirely different. This time the amount of eroded material (the clay) is limited, and depends on the hydraulic gradient, as established by experimental results (Bendahmane *et al.*, 2006; Bendahmane *et al.*, 2008; Sterpi, 2003). Parameter $|\Gamma_{er}|$ appears to be the relevant quantity accounting for this material information. Consequently, we assume that the surface fraction of eroded material $|\Gamma_{er}|$ scales with the clay volume fraction as follows:

$$\frac{|\Gamma_{er}|}{|\Gamma_{Clay} \cap \Gamma_{Pore}|} = H[\phi_V - \phi_V^{stop}] \left[1 - \left(\frac{\phi_V^{stop}}{\phi_V} \right)^{2/3} \right] \quad [45]$$

The final clay volume fraction ϕ_V^{stop} is assumed to depend on the hydraulic gradient:

$$\phi_V^{stop} = \phi_V^0 \left(\frac{i_c^0}{i_c^0 + i_w} \right)^{3/2} \quad [46]$$

The parameter i_c^0 is a phenomenological parameter which is not explicitly connected to the local threshold τ_c . It is a threshold hydraulic gradient to stop

erosion, as erosion stops if $\varphi_V = \varphi_V^{stop}$. It is also a threshold hydraulic gradient for the onset of erosion, as erosion occurs if

$$i_w > i_c^0 \left[\left(\frac{\varphi_V^0}{\varphi_V} \right)^{2/3} - 1 \right] \quad [47]$$

5. Parametric analysis

We consider a homogeneous sample, and we assume dilute flow and no deposition or clogging. As a result, the pore-fluid viscosity and the geometric permeability are homogenous. The pressure gradient is therefore homogeneous. The system Equations [1] and [2] (balance equations) and [28]-[46] (erosion constitutive law) leads to the following differential equation:

$$\begin{cases} \frac{d}{d\tilde{t}} \tilde{\varphi}_V = - \frac{\tilde{i}_w (\tilde{\phi}_{sand} - \tilde{\varphi}_V)}{\tilde{\phi}_{sand}^{2/3}} \left[\tilde{\varphi}_V^{2/3} - \frac{1}{1 + \tilde{i}_w} \right] \\ \tilde{\varphi}_V(0) = 1 \end{cases} \quad [48]$$

In Equation [48], $\tilde{\varphi}_V$ is the dimensionless clay volume fraction, $\tilde{\phi}_{sand}$ the dimensionless sand porosity, and $\tilde{i}_w$ the dimensionless hydraulic gradient defined as follows:

$$\tilde{\varphi}_V = \frac{\varphi_V}{\varphi_V^0}, \quad \tilde{\phi}_{sand} = \frac{\phi_{sand}}{\varphi_V^0}, \quad \tilde{i}_w = \frac{i_w}{i_c^0} \quad [49]$$

The dimensionless time $\tilde{t}$ is defined by means of a characteristic time of erosion t_{er} :

$$\tilde{t} = \frac{t}{t_{er}}, \quad t_{er} = \frac{2\rho_{Clay}}{\varsigma \rho_w g i_c^0 k_{er}} \quad [50]$$

This characteristic time is the main result of this work: it is established here that the global pressure gradient for suffusion plays the same role as the pressure drop $\Delta p / L$ in a pipe of length L , where a similar characteristic time has been defined (Bonelli *et al.*, 2006; Bonelli and Brivois, 2008).

The effects of varying the dimensionless hydraulic gradient $\tilde{i}_w$ are shown in Figure 4 for $\tilde{\phi}_{sand} = 1 / 0.99$, and Figure 5 for $\tilde{\phi}_{sand} = 2$. Figure 6 and Figure 7 show the effects of varying the initial dimensionless amount of clay $\tilde{\phi}_{sand}$ for $\tilde{i}_w = 1$, and $\tilde{i}_w = 10$ respectively.

For a given clayey sand (i_c^0, k_{er}), the model captures two important aspects:

- the greater the initial clay volume fraction φ_V^0 , the slower the erosion;
- the greater the hydraulic mechanical state i_w , the faster the erosion.

Figure 3. Effects of varying $\tilde{i}_w$ on $\tilde{\varphi}_V$ for $\tilde{\phi}_{sand} = 1 / 0.99$

Figure 4. Effects of varying $\tilde{i}_w$ on $\tilde{\varphi}_V$ for $\tilde{\phi}_{sand} = 2$

Figure 5. Effects of varying $\tilde{\phi}_{sand}$ on $\tilde{\varphi}_V$ for $\tilde{i}_w = 1$

Figure 6. Effects of varying $\tilde{\phi}_{sand}$ on $\tilde{\phi}_V$ for $\tilde{i}_w = 10$

6. Comparison with experimental results

The suffusion law is now compared with previously published data, giving the mass fraction of eroded material as a function of time for several hydraulic gradients (Sterpi, 2003).

The mass fraction of eroded material is a function of the clay volume fraction as follows:

$$\mu(t) = \frac{(1 - \phi_{clay}) [\phi_V^0 - \phi_V(t)]}{(1 - \phi_{clay}) \phi_V^0 + (1 - \phi_{sand})} \quad [51]$$

Table 1 summarizes the parameters of the suffusion equation. Parameters ϕ_{sand} and ϕ_V^0 were inferred from Sterpi (2003), while a characteristic value of ϕ_{clay} was chosen as this value was not available.

Equation [46] suggests that it is possible to estimate the parameter i_c^0 from the total amount of eroded material in a given test, if at least equilibrium is attained, which was not the case in the available data (Sterpi, 2003). The results of the identification are mean values and standard deviations for i_c^0 and k_{er} .

It is notable that although most of the research on suffusion has been directed towards the threshold stress, the rate of erosion is at least equally as important. This rate of erosion appears to be primarily driven by t_{er} Equation [50], which is essentially affected by the coefficient of surface erosion k_{er} . For piping erosion, k_{er} was found to range from 10^{-6} s/m to 10^{-3} s/m for fine-grained soils (Bonelli *et al.*, 2006; Bonelli and Brivois, 2008).

Table 1. Numerical values of the parameters

ϕ_{sand}	Sand porosity	0.49	
ϕ_{clay}	Clay porosity	0.60	
ϕ_V^0	Initial clay volume fraction	38%	
ρ_w	Water density	1 000	kg.m ⁻³
ρ_{Clay}	Clay saturated density	1 688	kg.m ⁻³
ζ	Anisotropy and tortuosity	2	
g	Gravitational constant	9.81	m.s ⁻²
k_{er}	Coefficient of erosion	$4.33 \times 10^{-5} \pm 0.30 \times 10^{-5}$	s.m ⁻¹
i_c^0	Threshold hydraulic gradient	2.95 ± 0.64

Figure 6. Suffusion tests with a constant pressure drop, mass fraction of eroded clay is shown as a function of time, test results (symbols, (Sterpi, 2003)) versus model results (continuous lines)

The coefficient of erosion is about 10^{-5} s/m. This is a low value, which corresponds to a slow erodable soil for surface erosion (Bonelli *et al.*, 2006; Bonelli and Brivois, 2008). This finding is consistent with previous experimental results: internal erosion rates have been found to be smaller than surface erosion rates (Reddi *et al.*, 2000).

Figure 6 gives the increase in the mass fraction of eroded material as a function of time. The data are well-described by our model over the full range of hydraulic gradients explored.

7. Conclusion

Erosion, which is the removal of material caused by the eroding power of the flow, is essentially an interfacial process. The objective of this work was to understand the bulk erosion process, which is counter intuitive at the pore scale, as an interfacial erosion process.

By means of homogenization reasoning, the macroscopic volume flux of eroded material is related to the microscopic surface flux of eroded material, at the clay water interface. This surface erosion is considered as shear stress driven. The macroscopic volume erosion is therefore driven by the global pressure gradient. In addition, the coefficient of clay surface erosion appears to be a relevant parameter to describe the kinetics of the suffusion process.

The total clay/water interface and the eroded clay/water interface are related to the clay volume fraction. The amount of erodable clay is related to the hydraulic gradient. Comparisons with published experimental results show that this model gives good results over the full range of hydraulic gradients explored.

This paper was not intended to propose a new suffusion law, or to reformulate the theory of suffusion as a whole based on homogenization. Other important phenomena should be considered in a more comprehensive model of internal erosion: permeability anisotropy induced by microstructure erosion, particle transport and filtration, deposition and clogging, two-phase seepage flow, concentrated flow, and dissolution and physico-chemical effects.

Acknowledgements

This project is sponsored by the Région Provence Alpes Côte d'Azur, the French National Research Agency under grant 0594C0115 (ANR-ERINOH), and the French Institute for Applied Research and Experimentation in Civil Engineering (IREX).

8. References

- Ariathurai R., Arulanandan K., "Erosion rates of cohesive soils", *Journal of the Hydraulics Division ASCE*, vol. 104, n° 2, 1986, p. 279-283.
- Bendahmane F., Marot D., Alexis A., "Parametric study of suffusion and backward erosion", *Journal of Geotechnical and Geoenvironmental Engineering (ASCE)*, vol. 134, n° 1, 2008, p. 57-67.

- Bonelli S., Brivois O., Borghi R., Benahmed N., “On the modelling of piping erosion”, *Comptes Rendus de Mécanique*, vol. 8-9, n° 334, 2006, p. 555-559.
- Bonelli S., Brivois O., “The scaling law in the hole erosion test with a constant pressure drop”, *International Journal for Numerical and Analytical Methods in Geomechanics*, vol. 32, 2006, p. 1573-1595.
- Bouddour A., Auriault J.-L., Mhamdi-Alaoui M., “Erosion and deposition of solid particles in porous media: Homogenization analysis of a formation damage”, *Transport in Porous Media*, vol. 25, n° 2, 1996, p. 121-146.
- Brivois O., Bonelli S., Borghi R., “Soil erosion in the boundary layer flow along a slope: a theoretical study”, *European Journal of Mechanics /B Fluids*, vol. 26, 2007, p. 707-719.
- Einstein H.A., *Der Geschiebetrieb als wahrschein- lichkeits Problem*, Mitt. d. Versuchsanstalt f. Wasserbau, Eidg. T. H., Zurich, 1937.
- Fell R., Fry J.-J. (edt), *Internal Erosion of Dams and Their Foundations*, Taylor & Francis, London, 2007.
- Golay F., Lachouette D., Bonelli S., Seppecher P., “Interfacial erosion: A three-dimensional numerical model”, *C.R. Mecanique*, vol. 338, n° 6, 2010, p. 333-337.
- Golay F., Lachouette D., Bonelli S., Seppecher P., “Numerical modelling of interfacial soil erosion with viscous incompressible flows”, *Comput. Methods Appl. Mech. Engrg*, vol. 200, 2011, p. 383-391.
- Gutiérrez F., Guerrero J., Lucha P., “A genetic classification of sinkholes illustrated from evaporite paleokarst exposures in Spain”, *Environmental Geology*, vol. 53, n° 5, 2008, p. 993-1006.
- Knapen A., Poesen J., Govers G., Gyssels G., Nachtergaele J., “Resistance of soils to concentrated flow erosion: A review”, *Earth-Science Reviews*, vol. 80, 2007, p. 75-109.
- Marot D., Bendahmane F., Rosquoët F., Alexis A., “Internal flow effects on isotropic confined sand-clay mixtures”, *Soil & Sediment Contamination, an International Journal*, vol. 18, n° 3, 2008, p. 294-306.
- Papamichos E., Vardoulakis I., Tronvoll J., Skjaerstein A., “Volumetric sand production model and experiment”, *International Journal for Numerical and Analytical Methods in Geomechanics*, vol. 25, 2001, p. 789-808.
- Papamichos E., Vardoulakis I., “Sand erosion with a porosity diffusion law”, *Computers and Geotechnics*, vol. 32, 2005, p. 47-58.
- Papamichos E., “Erosion and multiphase flow in porous media”, *International Journal of Geotechnical and Geoenvironmental Engineering*, vol. 14, n° 8-9, 2010, p. 1129-1154.
- Partheniades E., “Erosion and deposition of cohesive soils”, *Journal of the Hydraulics Division ASCE*, vol. 91, 1965, p. 105-139.
- Pavlov A.P., “About relief of plains and its change under the influence of subsurface and surface water”, *Geosciences*, vol. 5, n° 34, 1898, p. 91-147.

- Reddi L.N., Lee I.-M., Bonala M.V.S., “Comparison of internal and surface erosion using flow pump tests on a sand-kaolinite mixture”, *Geotechnical Testing Journal*, vol. 23, n° 1, 2000, p. 116-122.
- Revil A., Cathles L.M., “Permeability of shaly sands”, *Water Resources Research*, vol. 35, n° 3, 1999, p. 651-662.
- Revil A., Grauls D., Brévar O., “Mechanical compaction of sand/clay mixtures”, *Journal of Geophysical Research*, vol. 107, n° B11, 2002, p. 1-15.
- Sakthivadivel R., Irmay S., *A review of filtration*, thesis HEL 15-4, University of California, Berkley, 1966.
- Sterpi D., “Effects of the erosion and transport of fine particles due to seepage flow”, *International Journal of Geomechanics*, vol. 3, n° 1, 2003, p. 111-122.
- Wan R.G., Wang J., “Analysis of sand production in unconsolidated oil sand using a coupled erosional-stress-deformation model”, *Journal of Canadian Petroleum Technology*, vol. 43, n° 2, 2004, p. 47-52.
- Zhu J.C., Gantzer C.J., Anderson S.H., Peyton R.L., Albert E.E., “Comparison of concentrated-flow detachment equations for low shear stress”, *Soil & Tillage Research*, vol. 61, 2001, p. 203-212.