Turbulent non-uniform flows in straight compound open-channels

Sébastien Proust, J.N. Fernandes, Y. Peltier, J.B. Leal, N. Rivière, A.H. Cardoso

► To cite this version:

Sébastien Proust, J.N. Fernandes, Y. Peltier, J.B. Leal, N. Rivière, et al.. Turbulent non-uniform flows in straight compound open-channels. *Journal of Hydraulic Research*, 2013, 51 (6), pp.656-667. 10.1080/00221686.2013.818586 . hal-01122551

HAL Id: hal-01122551

<https://hal.science/hal-01122551>

Submitted on 4 Mar 2015

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

1 Turbulent non-uniform flows in straight compound open-channels

2 SEBASTIEN PROUST (IAHR Member), Research fellow, IRSTEA, UR HHLY, Hydrology-
3 Hydraulics Research Unit, 5 rue de la Doua, 69100 Villeurbanne, France

4 *Email: sebastien.proust@irstea.fr (Corresponding Author)*

5 JOAO N. FERNANDES (IAHR Member), Ph.D, CEHIDRO and Hydraulics and
6 Environment Department, National Laboratory for Civil Engineering, Lisbon, 1700-066,
7 Portugal

8 *Email: jnfernandes@lnec.pt*

9 YANN PELTIER (IAHR Member), Ph. D., IRSTEA, UR HHLY, Hydrology-Hydraulics
10 Research Unit, 5 rue de la Doua, 69100 Villeurbanne, France

11 *Email: yann.peltier90@gmail.com*

12 JOAO B. LEAL (IAHR Member), Research fellow, CEHIDRO and Department of Civil
13 Engineering, Faculdade de Ciencias e Tecnologia, New University of Lisbon, Caparica, 2829-
14 516, Portugal

15 *Email: jleal@fct.unl.pt*

16 NICOLAS RIVIERE (IAHR Member), Professor, LMFA, Université de Lyon, INSA de
17 Lyon, 20 av. A. Einstein, 69621 France

18 *Email: nicolas.riviere@insa-lyon.fr*

19 ANTONIO H. CARDOSO (IAHR Member), Professor, CEHIDRO and DECivil, Instituto
20 Superior Tecnico, Universidade Técnica de Lisboa, Lisbon, 1049-001, Portugal

21 *Email: antonio.cardoso@ist.utl.pt*

22
23

24 ABSTRACT

25 The reported experimental study assesses the effect of non-uniformity of flow on the momentum flux
26 in straight compound channels. Two flumes were used, featuring vertical and sloping banks. Starting
27 with uniform flow condition, various imbalances in the upstream discharge distribution were
28 introduced. This resulted in a time-averaged lateral flow and an advective transport of momentum,
29 which interacted with the shear-layer turbulence generated by the compound geometry. To investigate
30 this interaction, the three contributions to transverse momentum flux (depth-averaged flow, shear-layer
31 turbulence and dispersive term of spanwise velocity) are assessed. The first two contributions were
32 strengthened by the sloping banks, while the third becomes important for the case of the vertical bank.
33 With a lateral flow towards the main channel, the first contribution rises at the expense of the second.
34 With a lateral flow towards the floodplain, the first two contributions have the same order of
35 magnitude, and the Boussinesq approach is invalidated.

36 Keywords: compound open channel flow; laboratory studies; non-uniform flow; transverse
37 momentum flux; turbulent mixing layers;

38 1. Introduction

39 River floods are characterized by overbank flows in compound open-channels. A
40 compound channel consists of a main channel and one or two floodplains. The variation in
41 depth and roughness across the section generates transversally sheared flows. Under uniform
42 flow conditions, these flows are characterized by large-scale, coherent vortices that develop at
43 the boundary between the main channel and the floodplain (herein called sub-sections). These
44 macro-vortices enable the two parallel flows to exchange momentum, affecting the river
45 conveyance (*e.g.* Sellin 1964, Knight and Shiono 1990, Tominaga and Nezu 1991,
46 Nezu *et al.* 1999).

47 Overbank flows are frequently non-uniform. Non-uniformity may be the result of
48 flow unsteadiness, but non-uniform steady flows are also observed in prismatic geometries
49 when (i) a backwater effect is caused by the downstream boundary condition for sub-critical
50 flows or when (ii) the upstream velocity distribution is far from equilibrium. This last flow
51 configuration was considered in the present work to investigate turbulent non-uniform
52 compound channel flows.

53 The motivation for this study stems from the fact that a change in cross-sectional
54 shape, bottom slope and/or roughness occurs upstream from a prismatic reach, which
55 necessarily leads to an upstream imbalance in the velocity distribution between the sub-
56 sections. Three examples of flow configurations observed in natural streams are shown in
57 Fig. 1: (a) diverging or (b) converging floodplains upstream from a prismatic reach; and (c)
58 prismatic reach with a longitudinal transition in the hydraulic roughness on the floodplains.
59 The flow deficit that was observed over diverging floodplains by Bousmar *et al.* (2006) leads
60 to a flow redistribution from the main channel towards the floodplain along the prismatic
61 reach. By contrast, the flow excess on converging floodplains (Bousmar *et al.* 2004 and
62 Proust *et al.* 2006) results in a decelerating flow over the floodplains of the prismatic reach.

The third example is inspired by Vermaas *et al.* (2011), who experimentally studied the influence of a lateral increase in hydraulic roughness on an initially uniform flow in a single channel. A lateral mass exchange was observed from the decelerating flow over the rougher bed to the accelerating flow over the smoother bed. With a similar lateral change in roughness across a compound geometry, the third case shown in Fig. 1(c) features a lateral flow towards the main channel.

Bousmar *et al.* (2005) was one of the first studies dealing with steady flows in prismatic compound channels with an upstream imbalance in the velocity distribution. The streamwise evolution of the discharge distribution between the sub-sections was examined in three laboratory flumes. The lateral mass exchange was found to be a slow process acting on longitudinal distances ranging from $8 \times B_f$ to $35 \times B_f$ (B_f being the width of one floodplain). Using the same data, Proust *et al.* (2010) focused on the energy losses and showed that the streamwise profile of the total head was different from one sub-section to another.

In the two previously mentioned works, the turbulent quantities were not measured. In the present work, we investigated the interaction between the time-averaged transverse flow caused by the longitudinal non-uniformity and the shear-layer turbulence generated by the compound geometry. We estimated the three contributions to transverse momentum flux, namely the depth-averaged lateral Reynolds shear stress, a dispersive term of spanwise velocity over the depth, and the momentum flux by the depth-averaged velocity components. Specific attention was given to the vertical interface between the sub-sections, since it plays an important role in 1D (Bousmar and Zech 1999) or 1D+ numerical modelling (Proust *et al.* 2009, 2010). In particular, the validity of the Boussinesq approach is analysed.

The experiments were carried out in two flumes, presenting vertical and sloping banks. These two different geometries enable the assessment of the effect of the bank slope on the mass and momentum exchanges. Each data set is composed of a uniform flow and non-uniform flow cases, which are produced by an imbalance in the upstream discharges. An excess or a deficit in floodplain inflow were both investigated.

2. Experimental procedure

2.1. The two laboratory flumes

The experiments were performed in two compound channel flumes located at the Laboratory of Fluid Mechanics and Acoustics (LMFA), Lyon, France, and at the National Laboratory of Civil Engineering (LNEC), Lisbon, Portugal. The schematic top views and cross-sections of the flumes are shown in Fig. 2. The LMFA flume is 8 m long, 1.2 m wide, and is made of PVC with a bottom slope of 1.8 mm/m. The cross-section was asymmetrical, composed of a rectangular main channel and a floodplain, with a bank full height, h_b , of

53 mm. The LNEC flume is 10 m long, 2 m wide, and made of polished concrete with a bottom slope of 1.1 mm/m. The symmetrical cross-section was composed of two floodplains and one trapezoidal main channel with a bank slope of 45° and a height, h_b , of 100 mm. The Manning roughness was 0.0091 m^{-1/3}/s and 0.0092 m^{-1/3}/s, at LMFA and LNEC, respectively. These values were obtained by isolating one sub-section from another with a moveable vertical wall.

Following the recommendations of Bousmar *et al.* (2005), independent inlets for the main channel and for the floodplains were used in both flumes (see Fig. 2), and the discharges were measured with independent electromagnetic flow meters (uncertainty of 0.2 L/s to 0.3 L/s). To adjust water levels, independent downstream tailgates (one per sub-section) were used in each flume.

A Cartesian coordinate system is used in which x , y and z refer to the longitudinal, lateral and vertical directions, respectively (see Fig. 2), and u , v , w refer to the components of instantaneous velocity. The system origin is defined as: $x = 0$ at the inlet cross-section; $y = 0$ at the sidewall of the right-hand floodplain; and at a given x station, elevation z is measured from the bed of the main channel.

2.2. Measurement of velocity and water level

In both flumes, velocity was measured with a 10 MHz micro ADV (Vectrino+), equipped with a two-dimensional side-looking probe. The sampling volume was a 7 mm long cylinder with 6 mm diameter. The acquisition time was 3 min at each measurement position, with a sampling rate of 100 Hz. With 18,000 samples, the convergence of first and second statistical moments of the velocity components was ensured and the error on Reynolds shear stress is expected to be ±3% according to Chanson *et al.* (2007). The flow was seeded with 10 µm hollow glass spheres to get a signal-to-noise ratio higher than 20 dB as recommended by McLelland and Nicholas (2000). The ADV data were despiked using the phase-space thresholding technique of Goring and Nikora (2002), and correlations lower than 70% were excluded from the time-series.

To correct errors of misalignment of the ADV probe with respect to the longitudinal direction, the pitch angle was slightly modified during the post-processing. A single correction angle was used for each measured cross-section. At LMFA, the depth-averaged spanwise velocity, V_d , was assumed to be zero in the measuring volume that was nearest the main channel sidewall (5 mm from the wall). At LNEC, the value of V_d was minimized both on the main channel centreline and at the last measured position that was located 50 mm from the floodplain sidewall. The correction angle is in the range ±0.5° in both flumes, and it was

accounted for when computing local time-averaged velocity and Reynolds stresses, as recommended by Roy *et al.* (1996) and Peltier *et al.* (2013b).

The measuring cross-sections were located at downstream distances $x = 2.5, 4.5$ and 6.5 m at LMFA, and at $x = 1.1, 3.0, 5.0$ and 7.5 m at LNEC. The velocity measuring grids are shown in Fig. 2, with 43 to 45 lateral positions and with up to 10 vertical positions (interface between the sub-sections). At LMFA, velocity was also measured at $x = 5.5$ m at floodplain edge. In both flumes, the flow rate computed from the integration of the velocity field was within 97 to 100% of the values measured by the flow meters.

Water levels were measured with an ultrasonic sensor (uncertainty of ± 0.2 mm) at LMFA, and with a point gauge (uncertainty of ± 0.3 mm) at LNEC.

2.3. Flow conditions

Uniform flow conditions were used as a reference situation. In both flumes, the relative flow depth, $D_r = h_f / h_m$, was chosen to be 0.3. As shown in Fig. 2, h_f is the mean flow depth on the floodplain and h_m is the mean flow depth in the main channel (outside the side-sloped region at LNEC). The flow is considered uniform when both the flow depth and the depth-averaged streamwise velocity, U_d , are constant along x -direction (see sections 4.1 and 4.4). To obtain a constant flow depth all along the flume, both the height of the downstream tailgates and the upstream discharge distribution were adjusted. Then, the uniform flow was disturbed by varying the upstream discharges, but keeping the total flow rate and the height of the tailgates unchanged. Let us consider the variation in the floodplain discharge, Q_f , with respect to uniform flow conditions:

$$\Delta Q_f(x) = \frac{Q_f(x) - Q_f^u(x)}{Q_f^u(x)} \times 100 \quad (1)$$

where superscript u refers to uniform flow. The inflow conditions, which are defined by $\Delta Q_f(x=0)$, are reported in the first column in Table 1. The total flow rate Q is 27.4 L/s and 80.6 L/s, at LMFA and LNEC, respectively. For each flow rate Q , two or three excesses and one deficit in floodplains inflow were investigated (+19%, +38%, +53% and -19%).

To compare the non-uniform flows at position x with the uniform flow of same total discharge, Q , a non-uniformity parameter, N , was defined as:

$$N(x) = \frac{U_m(x) - U_f(x)}{U_m^u(x) - U_f^u(x)} \quad (2)$$

where U_m and U_f are the mean velocities in the main channel and floodplain, respectively. A time-averaged transverse flow from the floodplain to the main channel implies that $N < 1$.

The values of parameters N , D_r , U_f , U_m , and h_f , which were measured in the most upstream measuring section, are also shown in Table 1. The cases +53% at LMFA and +38% at LNEC feature a small or nil upstream velocity difference, $U_m - U_f$, as observed at the outlet of an abrupt contraction of the floodplain by Proust *et al.* (2006). The deficit of -19% corresponds to flow conditions at the outlet of a diverging compound channel (see Fig. 1). This table also presents the Froude numbers in the sub-sections, F_f , and F_m , ($F_i = U_i / \sqrt{gR_i}$, where $i = m$ or f , and R_i is the hydraulic radius in one sub-section). Regarding the Reynolds numbers in a sub-section ($R_i = 4U_i R_i / \nu$, with ν = kinematic viscosity), $R_f \in [6 \times 10^4 - 1.1 \times 10^5]$, and $R_m \in [2.4 \times 10^5 - 3.4 \times 10^5]$ at LNEC, and $R_f \in [2.5 \times 10^4 - 4.2 \times 10^4]$, $R_m \in [1.2 \times 10^5 - 1.6 \times 10^5]$ at LMFA. Considering the equivalent sand roughness, k_s , in both flumes (1.5×10^{-6} mm at LMFA, and 1.5×10^{-4} mm at LNEC), all flow cases in both sub-sections are hydraulically smooth at LMFA, or transitional flow at LNEC, according to the corrected Moody diagram (French 1985).

3. Theoretical background

3.1. Lateral exchange of streamwise momentum

Under uniform flow conditions, an important issue is to identify the contributions of turbulent diffusion and of secondary flows to the transverse momentum flux (see *e.g.* Shiono and Knight 1991, van Prooijen *et al.* 2005, Kara *et al.* 2012). Under non-uniform flow conditions, another source of transverse momentum flux has to be taken into account, i.e. the advective transport of momentum by the bulk flow. In the present paper, these three contributions to the lateral exchange of streamwise momentum were accounted for using a depth-averaged approach.

The time average of the depth-averaged lateral exchange of streamwise momentum yields:

$$\overline{1/h \int_0^h -\rho u v dz} = -1/h \int_0^h \rho \overline{u'v'} dz - 1/h \int_0^h \rho \overline{u} \overline{v} dz \quad (3)$$

where h is the local flow depth, $(\overline{\quad})$ the time-averaging operator, ρ , the fluid density, u and v , the instantaneous longitudinal and lateral velocities, $\overline{u}$ and $\overline{v}$, the time-averaged longitudinal and lateral velocities, and u' and v' , the fluctuations of the velocity components about the averaged values.

193 The first term on the right-hand side of Eq. (3) is the depth-averaged lateral Reynolds
194 shear stress, denoted T_{xy} :

$$195 \quad T_{xy} = 1/h \int_0^h -\rho \overline{u'v'} dz \quad (4)$$

196 The second term on the right-hand side of Eq. (3) is the lateral exchange of
197 streamwise momentum by the time-averaged flow, denoted M_{xy} :

$$198 \quad M_{xy} = -1/h \int_0^h \rho \overline{uv} dz = -\rho U_d V_d - 1/h \int_0^h \rho \overline{u} (\overline{v} - V_d) dz \quad (5)$$

199 where U_d and V_d are the depth-averaged, time-averaged longitudinal and lateral velocity.

200 According to Eq. (5), the term M_{xy} is the sum of the advective transport of momentum
201 by the depth-averaged flow and of a dispersive term of spanwise velocity $\overline{v}$ over the depth,
202 denoted $-\rho \overline{u} (\overline{v} - V_d) \Big|_d$ in the following. Under uniform flow conditions, the velocity V_d is nil,
203 but the depth-averaged value of $\overline{uv}$ can be different from zero due to secondary currents.

204 3.2. The Boussinesq approach

205 The Boussinesq assumption was validated for uniform compound channel flows, *e.g.*
206 by Shiono and Knight (1991) or van Prooijen *et al.* (2005). If gradients $\partial V_d / \partial x$ and $\partial \overline{v} / \partial x$
207 are negligible compared to $\partial U_d / \partial y$ and $\partial \overline{u} / \partial y$, respectively, a local transverse eddy
208 viscosity, ε_{xy} , and a depth-averaged transverse eddy viscosity, $\varepsilon_{xy} \Big|_d$ can be defined as:

$$209 \quad -\overline{u'v'} = \varepsilon_{xy} \frac{\partial \overline{u}}{\partial y} \quad (6)$$

$$210 \quad T_{xy} / \rho = \varepsilon_{xy} \Big|_d \frac{\partial U_d}{\partial y} \quad (7)$$

211 We will also investigate in this paper, if the Boussinesq approach is still relevant
212 when the flow is non-uniform.

213 4. Results

214 4.1. Relative flow depth

215 The longitudinal variation in relative flow depth, D_r , is shown in Fig. 3(a) for the
216 various floodplain inflows $\Delta Q_f(x=0)$. The relative flow depth is constant along both

flumes when the flow is uniform. The analysis of non-uniform flows shows that the cases with an excess in the floodplains inflow tend towards the uniform relative flow depth more rapidly than the cases with a deficit in the floodplains inflow. Considering runs +19% and –19% that are symmetric in terms of floodplains inflow relative to uniform flow, the profile of D_r for run –19% is further from the uniform flow profile along the two flumes.

Figure 3(a) also shows that the relative flow depth, D_r , increases from run –19% to run +53%, *i.e.* when the velocity difference between the sub-sections, $U_m - U_f$, decreases. The largest variation in D_r was observed in the first measuring section: the discrepancy from uniform relative flow depth ranges from –4% to +8% at LNEC, and from –6% to +8% at LMFA (see data of D_r in Table 1).

4.2. Velocity difference between sub-sections

Figure 3(b) shows the longitudinal variation in the non-uniformity parameter, N (see Eq. (2)). The N -profiles prove that a time-averaged transverse flow occurs between the sub-sections until the most downstream measuring section for each non-uniform case in both flumes. The length of the flumes is not sufficient so that any of the non-uniform cases reaches equilibrium ($N = 1$).

Figures 3(a) and 3(b) show that the relative flow depth, D_r , tends to equilibrium more rapidly than the N -parameter. In the LNEC flume at $x/B_f = 10.7$, the discrepancy from uniform relative flow depth ranges from –2% to +1%, while the parameter N significantly varies from 0.49 to 1.25. When using dimensional variables, this means that several velocity differences between the sub-sections can be obtained with the same flow depth. In accordance with Bousmar *et al.* (2005), this shows that using constant water depth as the unique criterion of flow uniformity can lead to erroneous results.

4.3. Depth-averaged transverse flow

The lateral distribution of time-averaged and depth-averaged spanwise velocity, V_d , is shown in Fig. 4 at $x/B_f = 5.6$ and 4.3 at LMFA and LNEC, respectively. This velocity is scaled by the bulk velocity under uniform flow conditions, $U_A^u = Q/A^u$. When the flow is non-uniform, the transverse flow is not laterally uniform. In both flumes, the highest values of $|V_d|$ are observed on the floodplains near the vertical interface between sub-sections, and irrespective of the N -parameter. Beyond $y/B_f = 1$, $|V_d|$ decreases in the main channel. At LMFA, this decrease is sharp owing to low values of local spanwise velocity, $\bar{v}$, below the bank full height, h_b . At LNEC, the sloping bank ensures a smoother decrease in $|V_d|$ between the top and the bottom of the bank.

250 4.4. Mixing layer width

251 The depth-averaged streamwise velocity, U_d , is shown in Fig. 5 in the most
252 downstream measuring sections. At LMFA, a local decrease is observed near the centreline
253 position in the main channel, irrespective of the direction and magnitude of the transverse
254 flow. This decrease is the result of marked counter-rotating secondary flows that will be
255 analysed further in section 4.5.

256 Let us consider a moving average with three consecutive values of U_d , such that the
257 changes in this average are lower than 1 cm/s (uncertainty on velocity measurement). We can
258 define two local plateaux of U_d and two associated velocities U_{d1} and U_{d2} , which are located
259 out of the shear-layer on the floodplain and in the main channel, respectively (shown in Fig. 5
260 for $N > 1$). In LMFA, U_{d2} is, therefore, located on the left-hand side of the local decrease in
261 velocity.

262 Similarly to Pope (2000) for unbounded mixing layers, we can define the lateral
263 location $y_\alpha(x)$ for $0 < \alpha < 1$ such that depth-averaged velocity, U_d , can be defined as:

$$264 \quad U_d(x, y_\alpha(x)) = U_{d1} + \alpha(U_{d2} - U_{d1}) \quad (8)$$

265 and consider a characteristic width of the mixing layer $\delta(x)$ as

$$266 \quad \delta(x) = y_{0.9}(x) - y_{0.1}(x) \quad (9)$$

267 with $y_\alpha = 0$ at the sidewall of the right-hand floodplain (see Fig. 2)

268 The longitudinal variations in the scaled width, δ/B_f , and the scaled position, $y_{0.1}/B_f$,
269 are shown in Fig. 6 for seven flow cases. Additional values of δ are displayed for the uniform
270 flow at LMFA (nine measuring sections). They were obtained from U_d -profiles that were
271 measured by Peltier *et al.* (2013a) with identical flow conditions in the same flume. With the
272 uniform flows in Fig. 6(a), after a phase of growth along the x -direction, the width of the
273 mixing layer δ reaches a constant value at $x/B_f = 5.6$ and 4.3, at LMFA and LNEC,
274 respectively. Beyond these two downstream positions: (i) the mixing layer is self-sustained
275 owing to the topographical forcing of the 2-stage channel (Jirka 2001); and (ii) the flow can
276 rigorously be considered as uniform since no significant transverse flow occurs across the
277 flumes (see Fig. 4).

278 It can be seen in Fig. 6(b) that for cases with an excess in floodplain flow, the lateral
279 boundary of the mixing layer, $y_{0.1}$, is increasingly moved towards the main channel with an
280 increase in the floodplain inflow. The high spanwise velocities near $y/B_f = 1$ on floodplain
281 side (see Fig. 4) are responsible for the displacement of the shear layer. With case +53% at
282 LMFA or case +38% at LNEC, the lateral position, $y_{0.1}$, is displaced into the main channel
283 until the most downstream measuring section. As shown in Fig. 6(a), this results in a

significant decrease in the mixing layer width, δ , relative to uniform flow case. The lateral displacement of the layer is constrained by the presence of the main channel sidewall at LMFA or the symmetry axis at LNEC, and by the high speed flow in the main channel of both flumes. For example, with the case +19% at LMFA, the flow that is the closest to equilibrium ($N = 0.88$ at $x/B_f = 8.1$ in Fig. 3(b)), a 30% decrease is observed relative to the mixing layer width of the uniform flow.

With cases -19%, the mixing layer in both flumes laterally spreads onto the floodplains in the downstream direction (see $y_{0,l}$ in Fig. 6(b)), with a linear evolution.

These changes in the lateral position, $y_{0,l}$ and the mixing layer width were also observed by Peltier *et al.* (2013a) in the LMFA flume with a transverse embankment set on the floodplain. With the same total flow rate $Q = 24.7$ L/s, and with a 50cm-long embankment, the width δ is zero close to the embankment owing to very large transverse flows.

4.5. Time-averaged streamwise velocity

Under uniform flow conditions, preliminary measurements of the vertical profiles of the time-averaged streamwise velocity $\bar{u}$ were carried out along the centreline position in the main channel, every $\Delta x = 0.5$ m or 1 m. The vertical distribution of $\bar{u}$ stops evolving from downstream positions $x/B_f = 6.8$ at LMFA, and 8.6 at LNEC flume, with a log-law in the inner region. Figure 7 shows the cross-sectional distribution of $\bar{u}$, scaled by U_A^u , in the last measuring sections, at $x/B_f = 8.1$ and 10.7, at LMFA and LNEC, respectively. In the main channel of LMFA flume, the presence of two counter-rotating secondary flows can be inferred from the inflection of the contours of velocity $\bar{u}$, upwards near the centreline position and downwards in the corners. In the results from LNEC, the presence of secondary flows is not so clear, despite of a similar aspect ratio B_m/h_b . As stated by Ikeda and McEwan (2009) for uniform flows, the presence of a vertical bank and a vertical sidewall strengthen secondary currents in comparison to the sloping banks of the LNEC flume. The present data set shows the maintenance of secondary currents cells when the flow is gradually varied. However, Fig. 7(a) and Fig. 5 (top plot) show that the region of local deficit in velocity is shifted towards the main channel sidewall by a mass transfer coming from the floodplain, i.e. for $N < 1$. Comparing cases $N = 1$ and $N = 0.64$, the local decrease in velocity U_d in Fig. 5 (top plots) is displaced from $y/B_f = 1.2$ to 1.25, i.e. of 4 cm (10% of the main channel width).

In both flumes, in spite of the wide range of variation in the non-uniformity parameter N , the general pattern of primary velocity $\bar{u}$ is weakly affected by the transverse flow in the most downstream measuring section. However, some local changes can be observed close to the interface between sub-sections. At LNEC, near $y/B_f = 1$, the contours of $\bar{u}$ for the cases

– 19% and +38% clearly differ, depending on the direction of the transverse flow. At LMFA, the contours of $\bar{u}$ near the floodplain edge in the main channel are inclined where the floodplain flow gets into the faster flow (compare $N = 1$ to $N = 0.64$)

4.6. Lateral Reynolds shear stress

Figure 8 shows the lateral distribution of depth-averaged lateral Reynolds shear stress, T_{xy} , at $x/B_f = [8.1, 10.7]$, at LMFA and LNEC, respectively. Comparing Fig. 8 to Fig. 5 indicates, at least from a qualitative point of view, a link between the lateral distributions of T_{xy} and of the streamwise velocity U_d . The shear layer turbulence appears to be locally induced by the streamwise velocity field. The Boussinesq assumption, which was validated for uniform compound channel flows, could still be valid for non-uniform flows in both flumes. The link between T_{xy} and lateral gradient $\partial U_d / \partial y$ is clear, irrespective of the N -value. For $N < 1$, the shear stress T_{xy} is negligible as velocity U_d is constant across the whole floodplain. For $N > 1$, the region of high shear stress T_{xy} coincides with the region of high gradients $\partial U_d / \partial y$, between $y/B_f = 0.7$ and 1.0 in both flumes. In addition, the negative values of gradient $\partial U_d / \partial y$ that are related to the secondary currents and to the sidewall effect in the main channel at LMFA lead to negative values of T_{xy} .

Figure 9 shows the cross-sectional distribution of lateral Reynolds shear stress $-\rho \overline{u'v'}$, scaled by $\rho(U_m - U_f)^2$, as the velocity difference $U_m - U_f$ is the natural source of the shear-layer turbulence. All cases feature a marked 2D pattern of $-\rho \overline{u'v'}$ across the section. Under uniform flow conditions, the region of high Reynolds stress extends below the bank full level in both flumes. This is more pronounced in the LNEC flume. Since the aspect ratio B_m/h_b and the velocity difference are comparable in both flumes, the sloping bank appears to be responsible for a higher turbulent diffusion at LNEC. Under non-uniform flow conditions, the cross-sectional pattern of Reynolds stress is highly altered by the time-averaged transverse flow in the most downstream measuring sections of both flumes.

In the presence of a transverse flow towards the main channel ($N < 1$), different flow characteristics are observed depending upon whether the main channel is rectangular or trapezoidal. As mass exchange progressively increases at LMFA from $N = 0.88$ to $N = 0.64$, the high shear region is laterally stretched towards the main channel sidewall. The highest shear region remains located at the floodplain edge (see also Fig. 8), while a second local maximum detaches from the floodplain edge and is horizontally shifted towards the main channel sidewall (to $\approx y/B_f = 1.1$ for $N = 0.64$). The region of negative values of Reynolds stress associated with the local deficit in velocity is also displaced in the same direction. Simultaneously, the high shear region in the main channel is increasingly extended in the

vertical direction from $N = 0.88$ to $N = 0.64$, highlighting the interaction between the transverse plunging flow and the shear-layer turbulence. At LNEC, as the transverse flow increases, the high shear region is first horizontally displaced towards the main channel ($N = 0.76$), and then vertically towards the sloping bank for $N = 0.49$. With this latter flow, the farthest from equilibrium in Fig. 9, the high shear region is stretched towards the bottom of the slope by the transverse plunging flow and a second region of shear is produced near the centre of the main channel, as observed at LMFA.

In the case of a transverse flow towards the floodplains ($N > 1$), different flow conditions are also observed in both flumes, although the velocity difference, $U_m - U_f$, is comparable with $N = 1.31$ and 1.25 . The lateral Reynolds shear stresses are significantly higher at LNEC than at LMFA from $y/B_f = 0.7$ to 1.1 (see also Fig. 8). This is particularly noticeable (i) below the bank full level, and (ii) within the near-surface layer on the floodplain. Since the lateral gradients $\partial U_d / \partial y$ shown in Fig. 5 are lower at LNEC than at LMFA, an increase of depth-averaged transverse eddy viscosity (see Equation 7 in section 3.2) is observed in this flume. Hence, in comparison with the vertical bank, the sloping bank enhances the shear-layer turbulence when the flow is uniform and when mass is transferred onto the floodplains.

4.7. Momentum flux at floodplain edge

As previously said, an accurate estimate of the transverse momentum flux at floodplain edge ($y/B_f = 1$) is required for 1D or 1D+ modelling. In this section, we investigate this momentum flux at comparable distances x/B_f in both flumes, *i.e.* 6.8 and 7.1 at LMFA and LNEC, respectively. Figure 10 shows the three contributions to this flux, namely the depth-averaged lateral Reynolds shear stress T_{xy} , the advective transport term $-\rho U_d V_d$ and the depth averaging of $-\rho \bar{u}(\bar{v} - V_d)$ (see Eqs. 4 and 5).

Because of the shallowness of the floodplain flow, the development of secondary currents is severely restricted. The dispersive term $-\rho \bar{u}(\bar{v} - V_d)$ is negligible compared to the other two terms. With higher values of velocity components U_d and V_d at LNEC, the variation range of $-\rho U_d V_d$ is larger at LNEC than LMFA, while the variation range of T_{xy} is comparable in both flumes. With a transverse flow to the floodplain ($N > 1$), T_{xy} and $-\rho U_d V_d$ are positive and of the same order of magnitude in both flumes. With an opposite transverse flow ($N < 1$): a) at LMFA, the advective momentum transport $-\rho U_d V_d$ increases with flow non-uniformity at the expense of the Reynolds stress T_{xy} , with the particular case

385 “ $N = 0.84$ ”, for which the total momentum flux is cancelled; b) at LNEC, the momentum flux
386 is essentially advective.

387 Figure 11 shows the vertical distributions of lateral Reynolds shear stress $-\overline{\rho u'v'}$
388 and of flux $-\overline{\rho uv}$, at same locations as in Fig. 10. With $N < 1$ at LNEC in Fig. 11(b), the
389 shear stress $-\overline{\rho u'v'}$ is always negligible compared to $-\overline{\rho uv}$ at each elevation and for all
390 cases. For $N > 1$ in Fig. 11(a,b), the shear-layer turbulence seems to be enhanced by the
391 sloping bank at LNEC, as the N -parameter is comparable in both flumes and the velocity
392 difference is similar (0.35 m/s vs 0.33 m/s). Hence, the following conclusions may be drawn:
393 (1) for an increasing transverse flow to the main channel, the advective momentum transport
394 $\rho|U_d V_d|$ progressively rises at the expense of the shear-layer turbulence; (2) for a transverse
395 flow to the floodplains, the two fluxes $-\rho U_d V_d$ and T_{xy} are of the same sign and order of
396 magnitude; (3) both $-\rho U_d V_d$ and T_{xy} are strengthened by a sloping bank relative to a
397 vertical one, irrespective of the lateral flow.

398 4.8. Eddy viscosity at floodplain edge

399 Given the qualitative link between the lateral shear stress T_{xy} and gradients $\partial U_d / \partial y$ in
400 section 4.6, a quantitative analysis of the relevance of the Boussinesq approach was
401 performed at the floodplain edge ($y/B_f = 1$) and $x/B_f = 6.8$ in the LMFA flume. Using a
402 centred difference with $\Delta x = 1$ cm and $\Delta y = 0.5$ cm, streamwise gradients $\partial V_d / \partial x$ were
403 found to be one or two orders of magnitude lower than $\partial U_d / \partial y$ (same results holds for local
404 gradients $\partial \bar{v} / \partial x$ and $\partial \bar{u} / \partial y$). The definitions of the local and depth-averaged transverse
405 eddy viscosities presented in Eqs. 6 and 7 were thus used. The distribution over the depth of
406 the eddy viscosity, ϵ_{xy} , is shown in Fig. 12(a). It noticeably varies with the magnitude and
407 direction of the time-averaged lateral flow. When mass is transferred to the floodplain
408 ($N = 1.32$), a strong increase of ϵ_{xy} from bed to surface is observed. In contrast, with a mass
409 transfer to the main channel, ϵ_{xy} decreases when approaching the water surface for the case
410 that is the furthest from equilibrium ($N = 0.57$). Hence, these profiles clearly highlight the
411 interaction between the transverse flow and the shear-layer turbulence.

412 In this context, we tested the model of depth-averaged eddy viscosity developed by
413 van Prooijen *et al.* (2005). The total eddy viscosity $\epsilon_{xy}|_d$ is the sum of the bed-induced eddy
414 viscosity, $\epsilon_{xy}^b|_d$, and of the shear-layer-induced viscosity, $\epsilon_{xy}^s|_d$:

$$\epsilon_{xy}|_d = \epsilon_{xy}^b|_d + \epsilon_{xy}^s|_d = \alpha h \sqrt{\frac{1}{8} f U_d} + \frac{h_f + h_m}{2h} \beta^2 \delta^2 \left| \frac{\partial U_d}{\partial y} \right| \quad (10)$$

The bed-induced turbulence is modelled by the Elder's model, in which α is a constant ($\alpha \approx 0.1$ for wide open channel flows according to Rodi (1980)), and f is the Darcy-Weisbach friction coefficient. The shear-layer turbulence is modelled by a Prandtl's mixing length model with a length scale that is proportional to the mixing layer width, δ (defined here in Eq. 9). With unbounded mixing layers, the proportionality constant β is related to the spreading rate $d\delta/dx$ of the mixing layer, and ranges from 0.088 to 0.124 according to van Prooijen *et al.* (2005). In the LMFA flume, $d\delta/dx = 0$ for the uniform flow at $x/B_f = 6.8$, where the eddy viscosity model is estimated (see Fig. 6). Moreover, the mixing layer is shallow, and the geometry is compound. The β -parameter will thus be considered as a new constant, calibrated for the uniform flow ($\beta = 0.026$), which was then used to model the non-uniform cases.

Figure 12(b) shows the results at LMFA at $y/B_f = 1$ and $x/B_f = 6.8$. White and black circles are used for the total eddy viscosity $\epsilon_{xy}|_d$, and the shear-layer-induced viscosity, $\epsilon_{xy}^s|_d$, respectively. The f -coefficient is estimated with a modified Colebrook formula (French 1985). Its value is approximately constant (0.021-0.022). This leads to very small variations in the bed-induced eddy viscosity, $\epsilon_{xy}^b|_d$, from 0.052 to 0.058 (difference between white and black circles in Fig. 12(b)).

Figure 12(b) shows that, with the β -parameter calibrated for uniform flow, accurate values of eddy viscosity $\epsilon_{xy}|_d$ are obtained for $N < 1$. In contrast, $\epsilon_{xy}|_d$ is greatly underestimated for $N = 1.32$. This flow is characterized by the highest shear-layer turbulence at LMFA, as shown in Fig. 10 (top plots). The underestimation of $\epsilon_{xy}|_d$ could thus be attributed to the limitations of the mixing length model. Firstly, this model assumes a local equilibrium between turbulence production and dissipation (*e.g.* Rodi 1980). Secondly, the local turbulent diffusion is exclusively related to the local gradients of time-averaged flow (Boussinesq approach), which can be erroneous if some structures are advected from upstream by the bulk flow. When mass is transferred to the floodplain, this advective transport of turbulent quantities can become important. In this case, Prandtl's model is not valid. In addition, considering the strong increase in eddy viscosity ϵ_{xy} in the near-surface layer (Fig. 12(a)), the depth averaging of ϵ_{xy} constitutes a rough approximation.

4.9. Momentum flux in the main channel

The three contributions to transverse momentum flux, $-\rho U_d V_d$, $-\rho \bar{u}(\bar{v} - V_d)\big|_d$ and T_{xy} were estimated in the main channel of the LMFA flume, in which the dispersive term of spanwise velocity $\bar{v}$ is important. The vertical distributions of velocity $\bar{v}$, flux $-\rho \bar{u}\bar{v}$ and Reynolds shear stress $-\rho \overline{u'v'}$ are shown in Fig. 13 at $x/B_f = 5.6$, near the vertical interface at $y/B_f = 1.01$, and near the centreline position at $y/B_f = 1.28$. Table 2 shows at these two locations, the depth-averaged value of $-\rho \bar{u}\bar{v}$, namely M_{xy} , the sum of terms $-\rho U_d V_d$ and $-\rho \bar{u}(\bar{v} - V_d)\big|_d$, and shear T_{xy} .

At $y/B_f = 1.01$, inside the shear-layer, the three fluxes can be of the same order of magnitude for the non-uniform cases (see Table 2). Figure 13(a) shows that the peak of lateral shear $-\rho \overline{u'v'}$ is located at the bank full level, irrespective of the value of the N -parameter. It is also shown that the variations in the $\bar{v}$ -profiles are mostly located above the bank full level.

At $y/B_f = 1.28$, outside the shear-layer, the momentum flux is essentially driven by the time-averaged flow for the non-uniform cases. In this case, the dispersive term $-\rho \bar{u}(\bar{v} - V_d)\big|_d$ is lower than the advective transport of momentum $-\rho U_d V_d$, but of the same order of magnitude. Figure 13(b) shows that the overall shape of the $\bar{v}$ -profiles is constant for all N -values, but with a lateral displacement towards the main channel sidewall when N decreases. Table 2 also shows that the relative weight of the dispersive term of $\bar{v}$ decreases with N -parameter.

5. Conclusions

Turbulent non-uniform flows were experimentally investigated in two compound channels, with vertical and sloping banks in the main channel. A time-averaged transverse flow and an advective transport of momentum occurred until the most downstream measuring sections. The water depth reaches equilibrium more rapidly than the velocity difference between the sub-sections, and this latter can significantly vary for a given flow depth.

The advective transport of mass and momentum interacts with the shear-layer turbulence as follows:

- (1) With a lateral flow to the main channel, the mixing layer and the shear-layer turbulence are laterally displaced in the same direction. The region of high values of lateral Reynolds stress $-\rho \overline{u'v'}$ is transversally stretched by the plunging flow into the

main channel. As non-uniformity increases, the advective transport of momentum by the depth-averaged flow, $-\rho U_d V_d$, rises at the expense of the depth-averaged value of $-\overline{\rho u'v'}$, T_{xy} , at floodplain edge and in the main channel.

(2) With a lateral flow to the floodplains, the shear layer turbulence widely extends on the floodplains, with higher values of $-\overline{\rho u'v'}$ and of transverse eddy viscosity ϵ_{xy} in the near-surface layer. Both the flux $-\rho U_d V_d$ and shear stress T_{xy} are of the same order of magnitude.

The shear-layer turbulence and the flux $-\rho U_d V_d$ are enhanced by the sloping bank, relative to the vertical bank. With this latter, the dispersive term of spanwise velocity, $-\overline{\rho u'(\bar{v}-V_d)}|_d$, can be of the same order of magnitude as $-\rho U_d V_d$, and is dependent on the flow direction. As a result, a 2D-depth-averaged model that does not account for the vertical dispersion of velocity $\bar{v}$, or a depth-averaged model that is based on uniform flow hypotheses ($\partial h / \partial x = 0$ and $V_d = 0$) may poorly reproduce the actual transverse momentum flux.

The two data sets showed that the Boussinesq approach was qualitatively appropriate for non-uniform flows. Using the depth-averaged model of eddy viscosity developed by van Prooijen *et al.* (2005) for uniform flows, we found that the model was still valid with a lateral flow to the main channel. In contrast, it significantly underestimates the eddy viscosity with an opposite lateral flow, *i.e.* when the horizontal vortices are widely extended on the floodplains. Both the Boussinesq approach and the mixing length models are not valid in this case.

An excess (resp. a deficit) in floodplain discharge is observed in a compound channel with converging (resp. diverging) floodplains. As a result, a part of the physical processes depicted in this paper, notably the interaction between time-averaged transverse flow and shear-layer turbulence, may be valid for non-prismatic geometries.

Since these results were obtained with a single relative flow depth, $D_r = 0.3$ under uniform flow conditions, this work will be continued by an investigation of the shallowness effect on the turbulent non-uniform flows.

Acknowledgements

Travel costs of J. Leal, J. Fernandes and S. Proust were supported by a Hubert Curien Project Pessoa, funded by EGIDE, France, and by FCT, Portugal. The authors are grateful to Fabien Thollet, Mickaël Lagouy and Pedro Duarte, for their assistance during the experiments. They are also grateful to Roger Bettess for his corrections.

510 Notation

511	Superscript u refers to uniform flows
512	Subscripts m and f refer to main channel and floodplain, respectively
513	Subscript d refers to a depth averaging
514	A = compound channel cross-section area [m ²]
515	B_f = width of one floodplain [m]
516	f = Darcy-Weisbach friction coefficient [–]
517	h = local water depth [m]
518	h_f, h_m = mean water depths on the floodplain and in the main channel [m]
519	h_b = bank full height in the main channel [m]
520	M_{xy} = depth-averaged value of transverse momentum flux $-\overline{\rho uv}$ [N/m ²]
521	Q = total discharge [m ³ /s]
522	Q_f = floodplain discharge [m ³ /s]
523	T_{xy} = depth-averaged value of lateral Reynolds shear stress $-\overline{\rho u'v'}$ [N/m ²]
524	U_A = bulk velocity, Q/A [m/s]
525	u, v = instantaneous longitudinal and lateral velocity components [m/s]
526	$\bar{u}, \bar{v}$ = time-averaged longitudinal and lateral velocity components [m/s]
527	$-\overline{\rho u'v'}$ = lateral Reynolds shear stress [N/m ²]
528	U_d, V_d = depth-averaged, time-averaged longitudinal and lateral velocity [m/s]
529	U_f, U_m = mean longitudinal velocity in the floodplain and main channel [m/s]
530	x, y, z = longitudinal, lateral and vertical distances [m]
531	ϵ_{xy} = local transverse eddy viscosity [m ² /s]
532	$\epsilon_{xy d}$ = depth-averaged transverse eddy viscosity [m ² /s]
533	

534 References

- 535 Bousmar, D., Zech, Y. (1999). Momentum transfer for practical flow computation. *J.*
536 *Hydraulic Eng.* 125(7), 696–706.
- 537 Bousmar, D., Proust, S. and Zech, Y. (2006). Experiments on the flow in a enlarging
538 compound channel. In *Proc. of the int. conf. on fluvial hydraulics, River flow 2006*, vol.
539 1, pp. 323–332. 6-8 September, Lisbon, Portugal: Ferreira, Alves, Leal and Cardoso
540 (eds.).
- 541 Bousmar, D., Wilkin, N., Jacquemart, J.H., Zech, Y. (2004). Overbank flow in symmetrically
542 narrowing floodplains. *J. Hydraulic Eng.* 130 (4), 305–312.
- 543 Bousmar, D., Riviere, N., Proust, S., Paquier, A., Morel, R. Zech, Y. (2005) Upstream
544 discharge distribution in compound-channel flumes. *J. Hydraulic Eng.* 131 (5), 408–
545 412.
- 546 Chanson, H., Trevethan, M., C Koch. Discussion of "Turbulence Measurements with
547 Acoustic Doppler Velocimeters" by Carlos M. Garcia, Mariano I. Cantero, Yarko Niño,
548 and Marcelo H. Garcia. *J. Hydraulic Eng.* 133 (2007) 1286-9.
- 549 French, R.H. (1985). *Open-channel hydraulics*, McGraw-Hill, New York.
- 550 Goring, D. G., Nikora, V. I. (2002). Despiking acoustic doppler velocimeter data. *J.*
551 *Hydraulic Eng.* 128(1), 117–126.
- 552 Ikeda, McEwan (2009). Flow and sediment transport in compound channels. *IAHR*
553 *Monograph series*, 333 p.
- 554 Jirka, G.H. (2001). Large scale flow structures and mixing processes in shallow flows. *J.*
555 *Hydraulic Res.* 39 (6), 567–573.

- 556 Kara, S., Stoesser, T., Sturm, T. W. (2012). Turbulence statistics in compound channels with
557 deep and shallow overbank flows. *J. Hydraulic Res.* 50(5), 482-493.
- 558 Knight, D.W., Shiono, K. (1990). Turbulence measurements in a shear layer region of a
559 compound channel. *J. Hydraulic Res.* 28 (2), 175-194.
- 560 McLelland, S. J., Nicholas, A. P (2000). A new method for evaluating errors in high-
561 frequency adv measurements. *Hydrological Processes* 14, 351-366.
- 562 Nezu, I., Onitsuka, K., Iketani, K. (1999). Coherent horizontal vortices in compound open
563 channel flows. In *Hydraulic modelling* (ed. I. W. Seo V. P. Singh & J. H. Sonu), pp. 17-
564 32. Water Resources Publications, Colorado, USA.
- 565 Peltier, Y., Proust, S., Rivière, N., Paquier, A., Shiono, K (2013a). Turbulent flows in straight
566 compound open-channel with a transverse embankment on the floodplain. *J. Hydraulic*
567 *Res.*, iFirst, 1-13, DOI:10.1080/00221686.2013.
- 568 Peltier, Y., Rivière, N., Proust, S., Mignot E., Paquier A., Shiono, K. (2013b). Estimation of
569 the error on the mean velocity and on the Reynolds stress due to a misoriented ADV
570 probe in the horizontal plane: case of experiments in a compound open-channel. *Under*
571 *review to Flow Meas. And Inst.*
- 572 Pope, S. (2000). *Turbulent flows*. Cambridge University Press, Cambridge UK.
- 573 van Prooijen, B.C., Battjes, J.A., Uijttewaai, W.S.J. (2005). Momentum exchange in straight
574 uniform compound channel flow. *J. Hydraulic Eng.* 131 (3), 175-183.
- 575 Proust, S., Riviere, N., Bousmar, D., Paquier, A., Zech, Y., Morel, R. (2006). Flow in
576 compound channel with abrupt floodplain contraction. *J. Hydraulic Eng.* 132 (9), 958-
577 970.
- 578 Proust, S., Bousmar, D., Rivire, N., Paquier, A., Zech, Y. (2009). Non-uniform flow in
579 compound channel: a 1D-method for assessing water level and discharge distribution.
580 *Water Resources Res.* 45 (W12411), 1-16.
- 581 Proust, S., Bousmar, D., Rivière, N., Paquier, A., Zech, Y. (2010). Energy losses in
582 compound open channels. *Adv. Water Res.* 33 (1), 1-16.
- 583 Rodi, W. (1980). *Turbulence models and their application in hydraulics: a state of the art*
584 *review*, IAHR book publication, Delft.
- 585 Roy, A. G., Biron, P., de Serres, B. (1996). On the necessity of applying a rotation to
586 instantaneous velocity measurements in river flows. *Earth Surface Processes and*
587 *Landforms*, 21(9), 817-827.
- 588 Sellin, R.H.J. (1964). A laboratory investigation into the interaction between the flow in the
589 channel of a river and that over its flood plain. *La Houille Blanche* (7), 793-802.
- 590 Shiono, K. and Knight, D.W. (1991). Turbulent open channel flows with variable depth
591 across the channel. *J. Fluid Mech.* 222, 617-646.
- 592 Tominaga, A. and Nezu, I. (1991). Turbulent structure in compound open-channel flows. *J.*
593 *Hydraulic Eng.* 117 (1), 21-41
- 594 Vermaas, D.A., Uijttewaai, W.S.J., Hoitink, A.J.F. (2011). Lateral transfer of streamwise
595 momentum caused by a roughness transition across a shallow channel. *Water Resources*
596 *Res.* 47 (W02530), 1-12.
- 597

598 Table 1 Flow conditions

	Inflow ($x = 0$)		^b Most upstream measuring section						
	^a ΔQ_f	Q_f / Q	N	D_r	h_f	U_f	F_f	U_m	F_m
	[%]	[%]	[-]	[-]	[mm]	[cm/s]	[-]	[cm/s]	[-]
LMFA	-19	20.6	1.42	0.286	21.2	31.0	0.69	70.0	0.94
	0	25.4	1.00	0.303	23.0	33.3	0.71	60.7	0.81
	+19	30.2	0.66	0.311	24.0	38.5	0.80	56.6	0.75
	+38	35.0	0.45	0.324	25.4	40.7	0.83	53.0	0.70
	+53	38.8	0.32	0.329	25.9	42.3	0.85	51.0	0.67
LNEC	-19	26.6	1.54	0.275	38.0	41.8	0.70	79.6	0.78
	0	32.8	1.00	0.285	40.1	47.9	0.79	72.5	0.70
	+19	39.0	0.52	0.297	42.2	53.0	0.85	65.7	0.63
	+38	45.2	0.00	0.304	43.8	58.6	0.92	58.6	0.56

599 ^a Imbalance in floodplain inflow, relative to uniform flow (see Eq. 1)

600 ^b $x = 2.5$ m at LMFA, $x = 1.1$ m at LNEC

601

602 Table 2 Transverse momentum flux in the main channel at LMFA, $x/B_f = 5.6$.

y/B_f	N	M_{xy}	$-\rho U_d V_d$	$-\rho U(V - V_d)l_d$	T_{xy}
[-]	[-]	[Pa]	[Pa]	[Pa]	[Pa]
1.01	1.33	4.2	4.2	0.0	0.7
	1	0.0	0.0	0.0	0.6
	0.79	0.0	-0.1	0.1	0.3
	0.64	0.0	-0.2	0.2	0.2
	0.50	-1.1	-1.2	0.1	0.1
1.28	1.33	1.0	1.6	-0.6	0.0
	1	-0.5	0.0	-0.5	0.1
	0.79	-0.6	-0.3	-0.3	0.0
	0.64	-2.6	-2.3	-0.3	0.0
	0.50	-2.8	-2.6	-0.2	0.0

603

604

FIGURES

Figure 1 Various flow conditions for natural compound channels: (a) diverging or (b) converging floodplains upstream from a prismatic reach, (c) prismatic reach with a longitudinal increase in roughness on the floodplains

LMFA flume

LNEC flume

Figure 2 Schematic top view and cross-section of the two flumes (markers '+': ADV measuring grid)

627
628

629 Figure 3 (a) Relative flow depth, D_r , and (b) velocity difference between sub-sections relative
630 to uniform flow conditions, $N = (U_m - U_f)/(U_m^u - U_f^u)$, against downstream distance, x/B_f

631

632 Figure 4 Lateral distribution of depth-averaged spanwise velocity, V_d , scaled by bulk velocity,
633 U_A^u , for various N -parameters.

634

635

636 Figure 5 Lateral distribution of depth-averaged streamwise velocity, U_d , scaled by U_A^u

637

638

639 Figure 6 Longitudinal profile of (a) mixing layer width, δ , and (b) lateral boundary, $y_{0.1}$ (see
640 Eq. 9), scaled by B_f .
641

Figure 7 Time-averaged streamwise velocity, $\bar{u}$, scaled by U_A^u , for various N -parameters: (a) LMFA, $x/B_f = 8.1$; and (b) LNEC, $x/B_f = 10.7$

647

648 Figure 8 Depth-averaged lateral Reynolds shear stress, T_{xy} , against lateral distance, y/B_f .

650

651 Figure 9 Normalized lateral Reynolds shear stress, $-\overline{u'v'}/(U_m - U_f)^2 (\times 100)$. (a) LMFA,

652 $x/B_f = 8.1$; and (b) LNEC, $x/B_f = 10.7$

653

654

655 Figure 10 The three contributions to transverse momentum flux at floodplain edge ($y/B_f = 1$)

656

657

658

659 Figure 11 Vertical distribution of lateral Reynolds shear stress $-\rho \overline{u'v'}$ and of momentum
660 flux $-\rho \overline{uv}$ at floodplain edge ($y/B_f = 1$). (a) LMFA, $x/B_f = 6.8$; (b) LNEC, $x/B_f = 7.1$

661

662 Figure 12 (a) Vertical distribution of eddy viscosity, ϵ_{xy} , and (b) depth-averaged eddy
663 viscosity, $\epsilon_{xy|_d}$, measured and modelled data (see Eq. 10). LMFA flume, floodplain edge
664 ($y/B_f = 1$), $x/B_f = 6.8$.
665
666

Figure 13 Vertical distribution of spanwise velocity $\bar{v}$, flux $-\rho\bar{u}\bar{v}$ and Reynolds shear stress $-\rho\bar{u}\bar{v}'$, in the main channel of LMFA flume, $x/B_f = 5.6$