MAC-BC duality with linear-feedback schemes

Selma Belhadj Amor, Yossef Steinberg, Michèle Wigger

► To cite this version:

Selma Belhadj Amor, Yossef Steinberg, Michèle Wigger. MAC-BC duality with linear-feedback schemes. 2014 IEEE International Symposium on Information Theory (ISIT), Jun 2014, Honolulu, United States. 10.1109/ISIT.2014.6875131 . hal-01221220

HAL Id: hal-01221220

<https://hal.science/hal-01221220>

Submitted on 27 Oct 2015

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

MAC-BC Duality with Linear-Feedback Schemes

Selma Belhadj Amor
Telecom ParisTech
Paris, France
belhadjamor@telecom-paristech.fr

Yossef Steinberg
Technion—Israel Inst. of Technology
Haifa, Israel
ysteinbe@ee.technion.ac.il

Michèle Wigger
Telecom ParisTech
Paris, France
wigger@telecom-paristech.fr

Abstract—We show that for the multi-antenna Gaussian MAC and BC with perfect feedback, the largest achievable regions with linear-feedback schemes (called *linear-feedback capacity regions*) coincide when the same total input-power constraint is imposed on both channels and when the MAC channel matrices are the transposes of the BC channel matrices.

In the two-user case, when either transmitters or receiver are single-antenna, the capacity region for the Gaussian MAC is known and the capacity-achieving scheme is a linear-feedback scheme. With our results we can thus determine the linear-feedback capacity region of the two-user Gaussian BC when either transmitter or receivers are single-antenna. For these cases we can also identify the linear-feedback schemes that achieve the linear-feedback capacity.

Our results also extend to a partial-feedback setup where only a subset of the feedback links are present.

I. INTRODUCTION

We study the multi-input multi-output (MIMO) Gaussian multi-access channel (MAC) and broadcast channel (BC) with perfect output feedback, where the transmitter(s) observe(s) the channel outputs in a noise-free but causal way. It is well known that feedback can increase capacity for these channels. The exact capacity regions however are generally unknown.

In this paper we restrict attention to a specific class of coding schemes, called *linear-feedback schemes* [1], where the transmitter(s) can use the feedback signals only in a linear way. More specifically, in every channel use, the produced inputs are restricted to *linear* combinations of the past feedback signals and some information-carrying code symbols which only depend on the messages available at the corresponding transmitter. The best coding schemes known to date both for the MIMO Gaussian MAC and BC with perfect feedback [2], [3], [4], [5], [6], [7], [8], [9] are linear-feedback schemes. For the two-user single-input single-output (SISO), the two-user single-input multi-output (SIMO), and the two-user multi-input single-output (MISO) Gaussian MAC [2], [3] linear-feedback schemes even achieve the entire capacity region. (Notice that also the rate-splitting extensions of the schemes in [2] and [3] are linear-feedback schemes.)

Without feedback, the following *duality relation* is well known [10], [11], [12]: under the same total input-power constraint the capacity regions of the MIMO Gaussian MAC and BC coincide when the channel matrices of the MAC and BC are transposes of each other. Such a pair of MAC and BC is called *dual*. We have recently shown a similar duality relation for the SISO Gaussian MAC and BC with perfect feedback when one restricts to linear-feedback schemes [13].

Our main result in this paper is the following new duality result: with perfect feedback and when restricting to linear-feedback schemes, the set of all achievable rates, called *linear-feedback capacity regions*, coincide for the MIMO Gaussian MAC and BC when the two channels are dual and when the same total input-power constraint is imposed on both channels. This result is particularly interesting for the two-user SISO, SIMO, and MISO cases where computable single-letter characterizations of the linear-feedback capacity regions of the Gaussian MAC are known. With our duality result, we thus immediately obtain single-letter characterizations of the linear-feedback capacity regions for the two-user SISO, SIMO, and MISO Gaussian BC.

We further introduce a class of (multi-letter) linear-feedback schemes for the MIMO Gaussian MAC and BC that achieve the linear-feedback capacity. Within this class we then identify the pairs of schemes that achieve the same rate-regions over dual MACs and BCs. Since we know the best linear-feedback schemes for the two-user SISO, SIMO, and MISO MAC [2], [3], we can identify the best linear-feedback schemes for the two-user SISO, SIMO, and MISO BC.

For clarity of exposition, in what follows we consider only two users. All our results extend to arbitrary $K \geq 2$ number of users. Moreover, our results also extend to partial-feedback setups where only a subset of the feedback links are present.

II. MIMO GAUSSIAN BC WITH FEEDBACK

We consider the two-user memoryless MIMO Gaussian BC with perfect feedback. The transmitter is equipped with κ transmit-antennas and each Receiver i , for $i \in \{1, 2\}$, with ν_i receive-antennas. At each discrete time t , if $\mathbf{x}_t$ denotes the real vector-valued input symbol sent by the transmitter, Receiver i observes the real vector-valued channel output

$$\mathbf{Y}_{i,t} = \mathbf{H}_i \mathbf{x}_t + \mathbf{Z}_{i,t}, \quad (1)$$

where $\mathbf{H}_i$, for $i \in \{1, 2\}$, is a deterministic real ν_i -by- κ channel matrix known to transmitter and receivers and $\{\mathbf{Z}_{1,t}\}_{t=1}^n$ and $\{\mathbf{Z}_{2,t}\}_{t=1}^n$ are independent sequences of independent and identically distributed (i.i.d.) centered κ -dimensional Gaussian random vectors of identity covariance matrix.

The goal of the communication is that the transmitter conveys Message M_1 to Receiver 1 and Message M_2 to Receiver 2. The messages are independent of the noise sequences $\{\mathbf{Z}_{1,t}\}_{t=1}^n$ and $\{\mathbf{Z}_{2,t}\}_{t=1}^n$ and uniformly distributed over the sets $\mathcal{M}_1 \triangleq \{1, \dots, \lfloor 2^{nR_1} \rfloor\}$ and $\mathcal{M}_2 \triangleq \{1, \dots, \lfloor 2^{nR_2} \rfloor\}$,

where R_1 and R_2 denote the rates of transmission and n the blocklength. The transmitter observes causal, noise-free output feedback from both receivers. Thus, the time- $t \in \{1, \dots, n\}$ channel input $\mathbf{X}_t$ can depend on the messages M_1 and M_2 and the channel outputs $\mathbf{Y}_{1,1}, \dots, \mathbf{Y}_{1,t-1}$ and $\mathbf{Y}_{2,1}, \dots, \mathbf{Y}_{2,t-1}$:

$$\mathbf{X}_t = \varphi_t^{(n)}(M_1, M_2, \mathbf{Y}_{1,1}, \dots, \mathbf{Y}_{1,t-1}, \mathbf{Y}_{2,1}, \dots, \mathbf{Y}_{2,t-1}), \quad (2)$$

for some encoding function of the form $\varphi_t^{(n)}: \mathcal{M}_1 \times \mathcal{M}_2 \times \mathbb{R}^{\nu_1(t-1)} \times \mathbb{R}^{\nu_2(t-1)} \rightarrow \mathbb{R}^\kappa$.

We impose an *expected average block-power constraint*

$$\frac{1}{n} \sum_{t=1}^n \mathbb{E}[\|\mathbf{X}_t\|^2] \leq P. \quad (3)$$

Each Receiver i decodes its corresponding message M_i by means of a decoding function $\phi_i^{(n)}$ of the form $\phi_i^{(n)}: \mathbb{R}^{\nu_i n} \rightarrow \mathcal{M}_i$, for $i \in \{1, 2\}$. That means, based on the output sequence $\mathbf{Y}_i^n$, Receiver i produces the guess $\hat{M}_i^{(n)} = \phi_i^{(n)}(\mathbf{Y}_i^n)$. The average probability of error is

$$P_{e,BC}^{(n)} \triangleq \Pr[(\hat{M}_1, \hat{M}_2) \neq (M_1, M_2)]. \quad (4)$$

A rate-pair (R_1, R_2) is achievable over the MIMO Gaussian BC with feedback under a power constraint P , if there exists a sequence of encoding and decoding functions $\{\{\varphi_t^{(n)}\}_{t=1}^n, \phi_1^{(n)}, \phi_2^{(n)}\}_{n=1}^\infty$, as described above, satisfying the power constraint (3) and such that the average probability of error $P_{e,BC}^{(n)}$ tends to zero as n tends to infinity. The closure of the union of all achievable regions is called *capacity region*.

In the present paper, we focus on *linear-feedback coding schemes* where the transmitter's channel input is a *linear* combination of the previous feedback output signals and an information-carrying vector that depends only on the messages (M_1, M_2) (but not on the feedback). Specifically, we assume that the channel input vectors have the form

$$\mathbf{X}_t = \mathbf{V}_t + \sum_{i=1}^2 \sum_{\tau=1}^{t-1} \mathbf{A}_{i,\tau,t} \mathbf{Y}_{i,\tau}, \quad t \in \{1, \dots, n\}, \quad (5)$$

where $\{\mathbf{A}_{i,\tau,t}\}$ are arbitrary κ -by- ν_i matrices and $\mathbf{V}_t = \xi_t^{(n)}(M_1, M_2)$ for some function $\xi_t^{(n)}: \mathcal{M}_1 \times \mathcal{M}_2 \rightarrow \mathbb{R}^\kappa$.

The set of all rate-pairs achieved by linear-feedback schemes is called *linear-feedback capacity region* and is denoted $\mathcal{C}_{BC}^{\text{linfb}}(H_1, H_2; P)$. The largest sum-rate achieved by a linear-feedback scheme is called *linear-feedback sum-capacity* and is denoted $\mathcal{C}_{BC,\Sigma}^{\text{linfb}}(H_1, H_2; P)$.

III. MIMO GAUSSIAN MAC WITH FEEDBACK

We consider the two-user memoryless MIMO Gaussian MAC with perfect feedback. Each Transmitter i , for $i \in \{1, 2\}$, is equipped with ν_i transmit-antennas and the receiver with κ receive-antennas. At each discrete time t , if $\mathbf{x}_{1,t}$ and $\mathbf{x}_{2,t}$ denote the vector signals sent by Transmitters 1 and 2, the receiver observes the real vector-valued channel output

$$\mathbf{Y}_t = \mathbf{H}_1^T \mathbf{x}_{1,t} + \mathbf{H}_2^T \mathbf{x}_{2,t} + \mathbf{Z}_t, \quad (6)$$

where $\mathbf{H}_i$, for $i \in \{1, 2\}$, is a deterministic real ν_i -by- κ channel matrix known to transmitters and receiver and $\{\mathbf{Z}_t\}$ is

a sequence of i.i.d. κ -dimensional centered Gaussian random vectors of identity covariance matrix.

The goal of communication is that Transmitters 1 and 2 convey independent messages M_1 and M_2 (which are also independent of $\{\mathbf{Z}_t\}$) to the common receiver. Since the transmitters have perfect feedback, Transmitter i 's, $i \in \{1, 2\}$, channel input at time t , $\mathbf{X}_{i,t}$, can depend on its message M_i and the previous output vectors $\mathbf{Y}_1, \dots, \mathbf{Y}_{t-1}$:

$$\mathbf{X}_{i,t} = \varphi_{i,t}^{(n)}(M_i, \mathbf{Y}_1, \dots, \mathbf{Y}_{t-1}), \quad t \in \{1, \dots, n\}, \quad (7)$$

for some encoding functions $\varphi_{i,t}^{(n)}: \mathcal{M}_i \times \mathbb{R}^{\kappa(t-1)} \rightarrow \mathbb{R}^\kappa$.

The channel input sequences $\{\mathbf{X}_{1,t}\}_{t=1}^n$ and $\{\mathbf{X}_{2,t}\}_{t=1}^n$ have to satisfy a *total expected average block-power constraint* P :

$$\frac{1}{n} \sum_{t=1}^n (\mathbb{E}[\|\mathbf{X}_{1,t}\|^2] + \mathbb{E}[\|\mathbf{X}_{2,t}\|^2]) \leq P. \quad (8)$$

The receiver decodes the messages (M_1, M_2) by means of a decoding function $\phi^{(n)}$ of the form $\phi^{(n)}: \mathbb{R}^{\kappa n} \rightarrow \mathcal{M}_1 \times \mathcal{M}_2$. This means, based on the output sequence $\mathbf{Y}_1, \dots, \mathbf{Y}_n$, the receiver produces its guess $(\hat{M}_1, \hat{M}_2) = \phi^{(n)}(\mathbf{Y}_1, \dots, \mathbf{Y}_n)$. The average probability of error is defined as

$$P_{e,MAC}^{(n)} \triangleq \Pr[(\hat{M}_1, \hat{M}_2) \neq (M_1, M_2)]. \quad (9)$$

A rate-pair (R_1, R_2) is achievable over the Gaussian MIMO MAC with feedback under a sum-power constraint P , if there exists a sequence of encoding and decoding functions $\{\{\varphi_{1,t}^{(n)}\}_{t=1}^n, \{\varphi_{2,t}^{(n)}\}_{t=1}^n, \phi^{(n)}\}_{n=1}^\infty$, as described above, such that the average probability of a decoding error $P_{e,MAC}^{(n)}$ tends to zero as n tends to infinity. The closure of the union of all achievable regions is called *capacity region*.

Also here, we focus on the class of *linear-feedback coding schemes* where the channel inputs at Transmitter i , for $i \in \{1, 2\}$, are given by *linear* combinations of the previous feedback signals and an information-carrying vector that only depends on the message M_i (but not on the feedback). Specifically, we assume that the channel input vectors satisfy

$$\mathbf{X}_{i,t} = \mathbf{U}_{i,t} + \sum_{\tau=1}^{t-1} \mathbf{C}_{i,\tau,t} \mathbf{Y}_\tau, \quad t \in \{1, \dots, n\}, \quad (10)$$

where $\{\mathbf{C}_{i,\tau,t}\}$ are arbitrary ν_i -by- κ matrices and $\mathbf{U}_{i,t} = \xi_{i,t}^{(n)}(M_i)$ for an arbitrary encoding function $\xi_{i,t}^{(n)}: \mathcal{M}_i \rightarrow \mathbb{R}^{\nu_i}$.

Linear-feedback capacity and linear-feedback sum-capacity are defined analogously to the BC. We denote them by $\mathcal{C}_{MAC}^{\text{linfb}}(H_1^T, H_2^T; P)$ and $\mathcal{C}_{MAC,\Sigma}^{\text{linfb}}(H_1^T, H_2^T; P)$.

IV. DUAL SCHEMES FOR MAC AND BC AND LINEAR-FEEDBACK CAPACITIES

The idea of our schemes is to divide the blocklength n into n' subblocks of equal length η . An inner code uses the feedback to transform each subblock of η channel uses of the original MIMO BC or MAC into a single channel use of a new MIMO BC or MAC, with more transmit and receive antennas. An outer code is then applied to communicate over the new MIMO BC or MAC without using the feedback.

A. A class of linear-feedback schemes for the BC

Fix the blocklength n . Our schemes are parametrized by

- a positive integer η ;
- κ -by- ν_i matrices $\{A_{i,\tau,\ell}\}$, for $\ell = 2, \dots, \eta$, $\tau = 1, \dots, \ell - 1$, and $i \in \{1, 2\}$;
- an encoding mapping $f^{(n')}: \mathcal{M}_1 \times \mathcal{M}_2 \rightarrow (\mathcal{R}^{\kappa\eta})^{n'}$ that produces $n' \triangleq \lfloor \frac{n}{\eta} \rfloor$ codevectors of size $\kappa\eta$; and
- two decoding mappings $g_1^{(n')}: (\mathbb{R}^{\nu_1\eta})^{n'} \rightarrow \mathcal{M}_1$ and $g_2^{(n')}: (\mathbb{R}^{\nu_2\eta})^{n'} \rightarrow \mathcal{M}_2$ that each decode a block of n' output vectors of lengths $\nu_1\eta$ and $\nu_2\eta$, respectively.

As already mentioned, the total blocklength n is divided into n' subblocks of length η . The matrices $\{A_{i,\tau,\ell}\}$ describe the inner code that is used within each of the n' subblocks. The parameters $f^{(n')}, g_1^{(n')}, g_2^{(n')}$ describe the outer code that is used to code over the n' subblocks without using the feedback.

We now describe how the inner code transforms the first block of η channel uses into a single channel use of the new MIMO BC. All other blocks are transformed similarly. Let $\mathbf{X} \triangleq (\mathbf{X}_1^\top, \dots, \mathbf{X}_\eta^\top)^\top$, $\mathbf{Z}_i \triangleq (\mathbf{Z}_{i,1}^\top, \dots, \mathbf{Z}_{i,\eta}^\top)^\top$, $\mathbf{Y}_i \triangleq (\mathbf{Y}_{i,1}^\top, \dots, \mathbf{Y}_{i,\eta}^\top)^\top$, for $i \in \{1, 2\}$, and let $\mathbf{W}$ denote the $\eta\kappa$ -dimensional codevector produced by outer encoder $f^{(n')}$ for this first block. Define strictly-lower block-triangular matrices

$$\mathbf{A}_i^B = \begin{bmatrix} 0 & & & & 0 \\ A_{i,1,2} & 0 & & & \\ A_{i,1,3} & A_{i,2,3} & 0 & & \\ \vdots & & & \ddots & \\ A_{i,1,\eta} & A_{i,2,\eta} & \dots & A_{i,(\eta-1),\eta} & 0 \end{bmatrix}, \quad i \in \{1, 2\}, \quad (11)$$

where here 0 denotes the κ -by- ν_i matrix with all zero entries, and the block channel-matrices $\mathbf{H}_i^B \triangleq \mathbf{I}_\eta \otimes \mathbf{H}_i$, for $i \in \{1, 2\}$, where $\otimes$ denotes the Kronecker product.

The channel inputs in the first block are chosen as

$$\mathbf{X} = (\mathbf{I} - \mathbf{A}_1^B \mathbf{H}_1^B - \mathbf{A}_2^B \mathbf{H}_2^B) \mathbf{W} + \mathbf{A}_1^B \mathbf{Y}_1 + \mathbf{A}_2^B \mathbf{Y}_2. \quad (12)$$

Define further the matrices

$$\mathbf{B}_i^B \triangleq (\mathbf{I} - \mathbf{A}_1^B \mathbf{H}_1^B - \mathbf{A}_2^B \mathbf{H}_2^B)^{-1} \mathbf{A}_i^B, \quad i \in \{1, 2\}, \quad (13)$$

after some algebraic manipulations, we can rewrite (12) as:

$$\mathbf{X} = \mathbf{W} + \mathbf{B}_1^B \mathbf{Z}_1 + \mathbf{B}_2^B \mathbf{Z}_2 \quad (14)$$

and the corresponding outputs as:

$$\mathbf{Y}_1 = \mathbf{H}_1^B \mathbf{W} + (\mathbf{I} + \mathbf{H}_1^B \mathbf{B}_1^B) \mathbf{Z}_1 + \mathbf{H}_1^B \mathbf{B}_2^B \mathbf{Z}_2, \quad (15a)$$

$$\mathbf{Y}_2 = \mathbf{H}_2^B \mathbf{W} + (\mathbf{I} + \mathbf{H}_2^B \mathbf{B}_2^B) \mathbf{Z}_2 + \mathbf{H}_2^B \mathbf{B}_1^B \mathbf{Z}_1. \quad (15b)$$

Mapping $(\mathbf{A}_1^B, \mathbf{A}_2^B) \mapsto (\mathbf{B}_1^B, \mathbf{B}_2^B)$ in (13) is bijective and $\mathbf{B}_i^B$, for $i \in \{1, 2\}$, is strictly-lower block-triangular with blocks of sizes $\kappa \times \nu_i$.

By (14), the total input power in the first subblock is

$$\mathbb{E}[\|\mathbf{X}\|^2] = \mathbb{E}[\|\mathbf{W}\|^2] + \text{tr}(\mathbf{B}_1^B (\mathbf{B}_1^B)^\top) + \text{tr}(\mathbf{B}_2^B (\mathbf{B}_2^B)^\top).$$

Since all the n' subblocks are constructed using the same $\mathbf{B}_1^B$ and $\mathbf{B}_2^B$, we conclude that the channel inputs $\{\mathbf{X}_t\}_{t=1}^n$ to our original MIMO BC satisfy the average block-power

constraint (3) if $\text{tr}(\mathbf{B}_1^B (\mathbf{B}_1^B)^\top) + \text{tr}(\mathbf{B}_2^B (\mathbf{B}_2^B)^\top) \leq \eta P$ and if the codewords produced by the outer encoder $f^{(n')}$ are average block-power constrained to power

$$\eta P - \text{tr}(\mathbf{B}_1^B (\mathbf{B}_1^B)^\top) - \text{tr}(\mathbf{B}_2^B (\mathbf{B}_2^B)^\top). \quad (16)$$

Definition 1. Let $\mathcal{R}_{\text{BC}}(\eta, \mathbf{B}_1^B, \mathbf{B}_2^B, \mathbf{H}_1^B, \mathbf{H}_2^B; P)$ denote the capacity region of the MIMO BC in (15) when the vector-input $\mathbf{W}$ is average block-power constrained to power (16).

Recall that our inner code transforms η uses of the original MIMO BC into a single use of the new MIMO BC (15). Thus, if we design the outer code $\{f^{(n')}, g_1^{(n')}, g_2^{(n')}\}$ to achieve the nofeedback capacity of MIMO BC (15) under average input-power constraint (16) as described in [12], then over the original MIMO BC we achieve the rate region $\frac{1}{\eta} \mathcal{R}_{\text{BC}}(\eta, \mathbf{B}_1^B, \mathbf{B}_2^B, \mathbf{H}_1^B, \mathbf{H}_2^B; P)$. This proves the achievability part of the following proposition. The converse can be shown using Fano's inequality, and is omitted here due to lack of space.

Proposition 1.

$$\mathcal{C}_{\text{BC}}^{\text{linfb}}(\mathbf{H}_1, \mathbf{H}_2; P) = \text{cl} \left(\bigcup_{\eta, \mathbf{B}_1^B, \mathbf{B}_2^B} \frac{1}{\eta} \mathcal{R}_{\text{BC}}(\eta, \mathbf{B}_1^B, \mathbf{B}_2^B, \mathbf{H}_1^B, \mathbf{H}_2^B; P) \right)$$

where the union is over all positive integers η and all strictly-lower block-triangular $(\eta\kappa)$ -by- $(\eta\nu_1)$ and $(\eta\kappa)$ -by- $(\eta\nu_2)$ matrices $\mathbf{B}_1^B$ and $\mathbf{B}_2^B$ with blocks of sizes $\kappa \times \nu_1$ and $\kappa \times \nu_2$ that satisfy $\text{tr}(\mathbf{B}_1^B (\mathbf{B}_1^B)^\top) + \text{tr}(\mathbf{B}_2^B (\mathbf{B}_2^B)^\top) \leq \eta P$.

B. A class of linear-feedback schemes for the MAC

Fix the blocklength n . The schemes are parametrized by

- a positive integer η ;
- ν_i -by- κ matrices $\{C_{i,\tau,\ell}\}$, for $\ell = 2, \dots, \eta$, $\tau = 1, \dots, \ell - 1$, and $i \in \{1, 2\}$;
- two encoding mappings $f_1^{(n')}: \mathcal{M}_1 \rightarrow (\mathcal{R}^{\nu_1\eta})^{n'}$ and $f_2^{(n')}: \mathcal{M}_2 \rightarrow (\mathcal{R}^{\nu_2\eta})^{n'}$ that produce n' codevectors of sizes $\nu_1\eta$ and $\nu_2\eta$, respectively; and
- a decoding mapping $g^{(n')}: (\mathbb{R}^{\nu\eta})^{n'} \rightarrow \mathcal{M}_1 \times \mathcal{M}_2$ that decodes a block of n' output vectors of length $\kappa\eta$.

The total blocklength is divided into n' subblocks of length η . The matrices $\{C_{1,\tau,\ell}\}$ and $\{C_{2,\tau,\ell}\}$ describe the inner code used within each of the n' subblocks of length η . The parameters $f_1^{(n')}, f_2^{(n')}, g^{(n')}$ describe the outer code used to code over the n' subblocks without using the feedback.

We describe the first block of η channel inputs. The inputs to the other blocks are similar. For $i \in \{1, 2\}$, let $\mathbf{X}_i \triangleq (\mathbf{X}_{i,1}^\top, \dots, \mathbf{X}_{i,\eta}^\top)^\top$, $\mathbf{Y} \triangleq (\mathbf{Y}_1^\top, \dots, \mathbf{Y}_\eta^\top)^\top$, and $\mathbf{Z} \triangleq (\mathbf{Z}_1^\top, \dots, \mathbf{Z}_\eta^\top)^\top$ and let $\mathbf{U}_i$ denote the $\eta\nu_i$ -length codevector (a column vector) produced by $f_i^{(n')}$ for this first block. Define the strictly-lower block-triangular matrices

$$\mathbf{C}_i^B = \begin{bmatrix} 0 & & & & 0 \\ C_{i,1,2} & 0 & & & \\ C_{i,1,3} & C_{i,2,3} & 0 & & \\ \vdots & & & \ddots & \\ C_{i,1,\eta} & C_{i,2,\eta} & \dots & C_{i,(\eta-1),\eta} & 0 \end{bmatrix}, \quad i \in \{1, 2\}, \quad (17)$$

where here 0 denotes an ν_i -by- κ zero matrix. Transmitter i 's inputs during the first block are chosen as

$$\mathbf{X}_i = \mathbf{Q}_i^{-1} \mathbf{U}_i + \mathbf{C}_i^B \mathbf{Y}. \quad (18)$$

Defining

$$\mathbf{D}_i^B \triangleq \mathbf{C}_i^B (\mathbf{I} - (\mathbf{H}_1^B)^\top \mathbf{C}_1^B - (\mathbf{H}_2^B)^\top \mathbf{C}_2^B)^{-1}, \quad i \in \{1, 2\}, \quad (19)$$

and $\mathbf{Q}_1$ and $\mathbf{Q}_2$ as the unique positive square roots of the (positive-definite) matrices

$$\begin{aligned} \mathbf{M}_1 &\triangleq (\mathbf{I} + \mathbf{D}_1^B (\mathbf{H}_1^B)^\top)^\top (\mathbf{I} + \mathbf{D}_1^B (\mathbf{H}_1^B)^\top) + (\mathbf{D}_2^B (\mathbf{H}_1^B)^\top)^\top \mathbf{D}_2^B (\mathbf{H}_1^B)^\top \\ \mathbf{M}_2 &\triangleq (\mathbf{I} + \mathbf{D}_2^B (\mathbf{H}_2^B)^\top)^\top (\mathbf{I} + \mathbf{D}_2^B (\mathbf{H}_2^B)^\top) + (\mathbf{D}_1^B (\mathbf{H}_2^B)^\top)^\top \mathbf{D}_1^B (\mathbf{H}_2^B)^\top, \end{aligned}$$

we can rewrite the inputs (18) and the corresponding outputs:

$$\begin{aligned} \mathbf{X}_i &= \mathbf{Q}_i^{-1} \mathbf{U}_i + \mathbf{D}_i^B ((\mathbf{H}_1^B)^\top \mathbf{Q}_1^{-1} \mathbf{U}_1 + (\mathbf{H}_2^B)^\top \mathbf{Q}_2^{-1} \mathbf{U}_2 + \mathbf{Z}) \quad (21) \\ \mathbf{Y} &= (\mathbf{I} + (\mathbf{H}_1^B)^\top \mathbf{D}_1^B + (\mathbf{H}_2^B)^\top \mathbf{D}_2^B) \\ &\quad \cdot ((\mathbf{H}_1^B)^\top \mathbf{Q}_1^{-1} \mathbf{U}_1 + (\mathbf{H}_2^B)^\top \mathbf{Q}_2^{-1} \mathbf{U}_2 + \mathbf{Z}). \quad (22) \end{aligned}$$

Mapping $(\mathbf{C}_1^B, \mathbf{C}_2^B) \mapsto (\mathbf{D}_1^B, \mathbf{D}_2^B)$ in (19) is bijective and $\mathbf{D}_i^B$, for $i \in \{1, 2\}$, is strictly-lower block-triangular with blocks of sizes $\nu_i \times \kappa$.

Lemma 1. *The channel inputs $\{\mathbf{X}_{1,t}\}_{t=1}^n$ and $\{\mathbf{X}_{2,t}\}_{t=1}^n$ to the original MIMO Gaussian MAC satisfy the total average input-power constraint (8), if $\text{tr}(\mathbf{D}_1^B (\mathbf{D}_1^B)^\top) + \text{tr}(\mathbf{D}_2^B (\mathbf{D}_2^B)^\top) \leq \eta P$ and if the codevectors produced by $f_1^{(n')}$ and $f_2^{(n')}$ are total average block-power constrained to power*

$$\eta P - \text{tr}(\mathbf{D}_1^B (\mathbf{D}_1^B)^\top) - \text{tr}(\mathbf{D}_2^B (\mathbf{D}_2^B)^\top). \quad (23)$$

Proof: The proof is omitted due to lack of space. ■

Definition 2. Let $\mathcal{R}_{\text{MAC}}(\eta, \mathbf{D}_1^B, \mathbf{D}_2^B, (\mathbf{H}_1^B)^\top, (\mathbf{H}_2^B)^\top; P)$ denote the capacity region of the MIMO MAC in (22) under total average block-power constraint (23) on the inputs $\mathbf{U}_1$ and $\mathbf{U}_2$.

If we design the outer code $\{f_1^{(n')}, f_2^{(n')}, g^{(n')}\}$ so that it achieves the nofeedback capacity of the new MIMO MAC in (22) under total average input-power constraint (23), then over the original MIMO MAC we can achieve the rate region $\frac{1}{\eta} \mathcal{R}_{\text{MAC}}(\eta, \mathbf{D}_1^B, \mathbf{D}_2^B, (\mathbf{H}_1^B)^\top, (\mathbf{H}_2^B)^\top; P)$. This proves the achievability part of the following proposition. The converse is based on Fano's inequality and omitted here due to lack of space.

Proposition 2.

$$\begin{aligned} \mathcal{C}_{\text{MAC}}^{\text{linfb}}(\mathbf{H}_1^\top, \mathbf{H}_2^\top; P) \\ = \text{cl} \left(\bigcup_{\eta, \mathbf{D}_1^B, \mathbf{D}_2^B} \frac{1}{\eta} \mathcal{R}_{\text{MAC}}(\eta, \mathbf{D}_1^B, \mathbf{D}_2^B, (\mathbf{H}_1^B)^\top, (\mathbf{H}_2^B)^\top; P) \right) \end{aligned}$$

where the union is over all positive integers η and all strictly-lower block-triangular $(\eta\nu_1)$ -by- $(\eta\kappa)$ and $(\eta\nu_2)$ -by- $(\eta\kappa)$ matrices $\mathbf{D}_1^B$ and $\mathbf{D}_2^B$ with blocks of sizes $\nu_1 \times \kappa$ and $\nu_2 \times \kappa$ that satisfy $\text{tr}(\mathbf{D}_1^B (\mathbf{D}_1^B)^\top) + \text{tr}(\mathbf{D}_2^B (\mathbf{D}_2^B)^\top) \leq \eta P$.

C. Dual linear-feedback schemes for MAC and BC

Definition 3. For a given k -by- ℓ matrix $\mathbf{M}$, we define its reverse image as the ℓ -by- k matrix $\bar{\mathbf{M}} \triangleq \mathbf{E}_\ell \mathbf{M}^\top \mathbf{E}_k$, where $\mathbf{E}_k$ denotes the k -by- k exchange matrix which is 0 everywhere except for the counter-diagonal where it is 1. (In the following we often drop the subscript and simply write $\mathbf{E}$.)

Proposition 3. Let $\bar{\mathbf{H}}_i^B = \mathbf{I}_\eta \otimes \bar{\mathbf{H}}_i$. If

$$\mathbf{B}_i^B = \bar{\mathbf{D}}_i^B, \quad i \in \{1, 2\}, \quad (24)$$

then the following two regions coincide:

$$\mathcal{R}_{\text{BC}}(\eta, \mathbf{B}_1^B, \mathbf{B}_2^B, \mathbf{H}_1^B, \mathbf{H}_2^B; P) = \mathcal{R}_{\text{MAC}}(\eta, \mathbf{D}_1^B, \mathbf{D}_2^B, \bar{\mathbf{H}}_1^B, \bar{\mathbf{H}}_2^B; P). \quad (25)$$

Proof: See Section VI. ■

Condition (24) is equivalent to

$$\mathbf{A}_i^B = \bar{\mathbf{C}}_i^B. \quad (26)$$

Remark 1. On a MIMO MAC with channel matrices $\mathbf{H}_1$ and $\mathbf{H}_2$ the transmitters and receiver can mimic a MIMO MAC with channel matrices $\bar{\mathbf{H}}_1$ and $\bar{\mathbf{H}}_2$. It suffices that each transmitter multiplies (from the left) its input vectors by $\mathbf{E}$ before feeding them to the channel and that the receiver and the transmitters first multiply the output and feedback vectors by $\mathbf{E}$ (from the left) before further processing.

Combining Proposition 3, (26), and Remark 1 we obtain:

Corollary 1. Consider a MIMO BC with channel matrices $(\mathbf{H}_1, \mathbf{H}_2)$ and its dual MAC with channel matrices $(\mathbf{H}_1^\top, \mathbf{H}_2^\top)$. Fix the MAC-scheme parameters η , $\{\mathbf{C}_{1,\tau,\ell}\}$, $\{\mathbf{C}_{2,\tau,\ell}\}$, $f_1^{(n')}$, $f_2^{(n')}$, and $g^{(n')}$. Choose now the BC-scheme parameters

$$\mathbf{A}_{i,\tau,\ell} = \bar{\mathbf{C}}_{i,\eta-\tau,\eta-\ell+2}, \quad (27)$$

and an optimal outer code $f^{(n')}$, $g_1^{(n')}$, and $g_2^{(n')}$ as described in [12]. Then, our MAC and BC-schemes achieve the same rate regions.

In the SISO case, all conditions (27) are summarized by

$$\mathbf{A}_i^B = \bar{\mathbf{C}}_i^B. \quad (28)$$

V. MAIN RESULTS

Theorem 1. $\mathcal{C}_{\text{BC}}^{\text{linfb}}(\mathbf{H}_1, \mathbf{H}_2; P) = \mathcal{C}_{\text{MAC}}^{\text{linfb}}(\mathbf{H}_1^\top, \mathbf{H}_2^\top; P)$.

Proof: Follows by Propositions 1, 2, and 3, and since Remark 1 implies $\mathcal{C}_{\text{MAC}}^{\text{linfb}}(\mathbf{H}_1^\top, \mathbf{H}_2^\top; P) = \mathcal{C}_{\text{MAC}}^{\text{linfb}}(\bar{\mathbf{H}}_1, \bar{\mathbf{H}}_2; P)$. ■

Corollary 2. $\mathcal{C}_{\text{BC},\Sigma}^{\text{linfb}}(\mathbf{H}_1, \mathbf{H}_2; P) = \mathcal{C}_{\text{MAC},\Sigma}^{\text{linfb}}(\mathbf{H}_1^\top, \mathbf{H}_2^\top; P)$.

Let $\mathcal{C}_{\text{MAC,SISO}}^{\text{linfb}}$, $\mathcal{C}_{\text{MAC,SIMO}}^{\text{linfb}}$, $\mathcal{C}_{\text{MAC,MISO}}^{\text{linfb}}$ denote the linear-feedback capacity regions for the SISO, SIMO, and MISO Gaussian MAC with feedback. From the results by Ozarow [2] & Jafar and Goldsmith [3] one readily obtains¹ computable single-letter expressions for these linear-feedback capacity regions, which coincide with the true capacity regions for

¹Ozarow and Jafar & Goldsmith determined the capacity regions under individual power constraints for each transmitter. The capacity region under a total power constraint is obtained by taking the union of these capacity regions over all possible power splits.

the respective setups. By Theorem 1, we thus obtain single-letter expressions for the linear-feedback capacity regions of the SISO, SIMO, and MISO Gaussian BC:

Corollary 3. *Consider the SISO case where the channel matrices are scalars h_1 and h_2 :*

$$\mathcal{C}_{\text{BC,SISO}}^{\text{linfb}}(h_1, h_2; P) = \mathcal{C}_{\text{MAC,SISO}}^{\text{linfb}}(h_1, h_2; P), \quad (29)$$

where a computable single-letter characterization of $\mathcal{C}_{\text{MAC,SISO}}^{\text{linfb}}(h_1, h_2; P)$ is obtained from Ozarow's result [2].

Corollary 4. *Consider the SIMO and MISO cases where the channel matrices are given by column vectors $\mathbf{h}_1$ and $\mathbf{h}_2$:*

$$\mathcal{C}_{\text{BC,MISO}}^{\text{linfb}}(\mathbf{h}_1^\top, \mathbf{h}_2^\top; P) = \mathcal{C}_{\text{MAC,SIMO}}^{\text{linfb}}(\mathbf{h}_1, \mathbf{h}_2; P) \quad (30)$$

$$\begin{aligned} \mathcal{C}_{\text{BC,SIMO}}^{\text{linfb}}(\mathbf{h}_1, \mathbf{h}_2; P) &= \mathcal{C}_{\text{MAC,MISO}}^{\text{linfb}}(\mathbf{h}_1^\top, \mathbf{h}_2^\top; P) \quad (31) \\ &= \mathcal{C}_{\text{MAC,SISO}}^{\text{linfb}}(\|\mathbf{h}_1\|, \|\mathbf{h}_2\|; P), \quad (32) \end{aligned}$$

where the last equality follows from a result in [3]. A computable single-letter characterization of $\mathcal{C}_{\text{MAC,SIMO}}^{\text{linfb}}$ and $\mathcal{C}_{\text{MAC,MISO}}^{\text{linfb}}$ can be obtained from the results in [3].

In view of Corollary 1 and the MAC capacity-achieving schemes in [2] and [3], for the SISO, the SIMO, and the MISO BC we can easily deduce the parameters of our linear-feedback schemes in Section IV-A that achieve the linear-feedback capacity.

Remark 2. *Analogous results also hold with partial feedback where only a subset of the feedback links are present.*

VI. PROOF OF PROPOSITION 3

Fix η and strictly-lower block-triangular matrices $\mathbf{B}_1^B, \mathbf{B}_2^B$. Also, let $\mathbf{D}_1^B, \mathbf{D}_2^B$ be given by (24). (Since $\mathbf{B}_1^B$ and $\mathbf{B}_2^B$ are strictly-lower block-triangular, so are $\mathbf{D}_1^B$ and $\mathbf{D}_2^B$.)

Consider the MIMO MAC (22) with $(\mathbf{H}_i^B)^\top$ replaced by $\bar{\mathbf{H}}_i^B$: $\mathbf{Y}' = (\mathbf{I} + \bar{\mathbf{H}}_1^B \mathbf{D}_1^B + \bar{\mathbf{H}}_2^B \mathbf{D}_2^B)(\bar{\mathbf{H}}_1^B \mathbf{Q}_1^{-1} \mathbf{U}_1 + \bar{\mathbf{H}}_2^B \mathbf{Q}_2^{-1} \mathbf{U}_2 + \mathbf{Z})$ (33) where now $\mathbf{Q}_1$ and $\mathbf{Q}_2$ are the unique positive square-roots of

$$\mathbf{M}_1 = (\mathbf{I} + \mathbf{D}_1^B \bar{\mathbf{H}}_1^B)^\top (\mathbf{I} + \mathbf{D}_1^B \bar{\mathbf{H}}_1^B) + (\mathbf{D}_2^B \bar{\mathbf{H}}_1^B)^\top (\mathbf{D}_2^B \bar{\mathbf{H}}_1^B), \quad (34a)$$

$$\mathbf{M}_2 = (\mathbf{I} + \mathbf{D}_2^B \bar{\mathbf{H}}_2^B)^\top (\mathbf{I} + \mathbf{D}_2^B \bar{\mathbf{H}}_2^B) + (\mathbf{D}_1^B \bar{\mathbf{H}}_2^B)^\top (\mathbf{D}_1^B \bar{\mathbf{H}}_2^B). \quad (34b)$$

Since $(\mathbf{I} + \bar{\mathbf{H}}_1^B \mathbf{D}_1^B + \bar{\mathbf{H}}_2^B \mathbf{D}_2^B)$ is invertible, under any given input power constraint, MAC (33) has the same capacity as MAC

$$\mathbf{Y}'_{\text{MAC}} \triangleq \bar{\mathbf{H}}_1^B \mathbf{Q}_1^{-1} \mathbf{U}_1 + \bar{\mathbf{H}}_2^B \mathbf{Q}_2^{-1} \mathbf{U}_2 + \mathbf{Z}. \quad (35)$$

We now turn to BC (15). Let $\mathbf{S}_1$ and $\mathbf{S}_2$ be the positive square roots of

$$\mathbf{N}_1 \triangleq (\mathbf{I} + \mathbf{H}_1^B \mathbf{B}_1^B)(\mathbf{I} + \mathbf{H}_1^B \mathbf{B}_1^B)^\top + (\mathbf{H}_1^B \mathbf{B}_2^B)(\mathbf{H}_1^B \mathbf{B}_2^B)^\top \quad (36a)$$

$$\mathbf{N}_2 \triangleq (\mathbf{H}_2^B \mathbf{B}_1^B)(\mathbf{H}_2^B \mathbf{B}_1^B)^\top + (\mathbf{I} + \mathbf{H}_2^B \mathbf{B}_2^B)(\mathbf{I} + \mathbf{H}_2^B \mathbf{B}_2^B)^\top. \quad (36b)$$

Define $\tilde{\mathbf{W}} \triangleq \mathbf{E}\mathbf{W}$ and notice $\|\tilde{\mathbf{W}}\|^2 = \|\mathbf{W}\|^2$. Since multiplying the output vectors of a MIMO BC by invertible matrices (here $\mathbf{E}\mathbf{S}_1^{-1}$ and $\mathbf{E}\mathbf{S}_2^{-1}$) does not change capacity, we conclude: The MIMO BC (15) and the MIMO BC

$$\mathbf{Y}'_{i,\text{BC}} \triangleq \mathbf{E}\mathbf{S}_i^{-1} \mathbf{H}_i^B \mathbf{E} \tilde{\mathbf{W}} + \tilde{\mathbf{Z}}_i, \quad i \in \{1, 2\}, \quad (37)$$

where $\tilde{\mathbf{Z}}_1$ and $\tilde{\mathbf{Z}}_2$ are independent centered Gaussian vectors of identity covariance matrices, have equal capacity when the inputs $\mathbf{W}$ and $\tilde{\mathbf{W}}$ are average block-power constrained to (16).

We conclude the proof by showing that the capacity regions of the MIMO BC in (37) under power constraint (16) and the MIMO MAC (35) under power constraint (23) coincide. In view of (24), comparing (34) and (36), we have

$$\mathbf{E}\mathbf{M}_i \mathbf{E} = \mathbf{N}_i, \quad i \in \{1, 2\}, \quad (38)$$

and thus by the definitions and uniqueness of $\mathbf{S}_i$ and $\mathbf{Q}_i$,

$$\mathbf{S}_i = \mathbf{E}\mathbf{Q}_i \mathbf{E} = \mathbf{E}\mathbf{Q}_i^\top \mathbf{E}, \quad i \in \{1, 2\}, \quad (39)$$

where we used the symmetry of $\mathbf{Q}_i$. This implies

$$\mathbf{E}\mathbf{S}_i^{-1} \mathbf{H}_i^B \mathbf{E} = \mathbf{Q}_i^{-\top} \mathbf{E} \mathbf{H}_i^B \mathbf{E} = (\bar{\mathbf{H}}_i^B \mathbf{Q}_i^{-1})^\top, \quad i \in \{1, 2\}, \quad (40)$$

and the BC (37) and the MAC (35) are duals and have therefore the same capacity regions under the same total power constraints on the inputs [10], [11]. Since by (24), the powers (16) and (23) are the same, this concludes the proof.

ACKNOWLEDGEMENTS

The work of S. Belhadj Amor and M. Wigger has been supported by the city of Paris under the ‘‘Emergences’’ program. The work of Y. Steinberg has been supported by the Israel Science Foundation (grant no. 684/11).

REFERENCES

- [1] E. Ardestanizadeh, M. Wigger, Y. H. Kim, and T. Javidi, ‘‘Linear-feedback sum-capacity for Gaussian multiple access channels,’’ *IEEE Trans. on Inf. Th.*, vol. 58, no. 1, pp. 224–236, 2012.
- [2] L. Ozarow, ‘‘The capacity of the white Gaussian multiple access channel with feedback,’’ *IEEE Trans. on Inf. Th.*, vol. 30, no. 4, pp. 623–629, 1984.
- [3] S. Jafar and A. Goldsmith, ‘‘On the capacity of the vector MAC with feedback,’’ *IEEE Trans. on Inf. Th.*, vol. 52, no. 7, pp. 3259–3264, 2006.
- [4] G. Kramer, ‘‘Feedback strategies for white Gaussian interference networks,’’ *IEEE Trans. on Inf. Th.*, vol. 48, no. 6, pp. 1423–1438, 2002.
- [5] L. Ozarow and S. Leung-Yan-Cheong, ‘‘An achievable region and outer bound for the Gaussian broadcast channel with feedback,’’ *IEEE Trans. on Inf. Th.*, vol. 30, no. 4, pp. 667–671, 1984.
- [6] N. Elia, ‘‘When Bode meets Shannon: control-oriented feedback communication schemes,’’ *IEEE Trans. Automat. Contr.*, vol. 49, no. 9, pp. 1477–1488, 2004.
- [7] S. Vishwanath, W. Wu, and A. Arapostathis, ‘‘Gaussian interference networks with feedback: duality, sum capacity and dynamic team problems,’’ in *Proc. 43rd Ann. Allerton Conf.*, pp. 926–935, 2005.
- [8] E. Ardestanizadeh, P. Minero, and M. Franceschetti, ‘‘LQG control approach to Gaussian broadcast channels with feedback,’’ *IEEE Trans. on Inf. Th.*, vol. 58, no. 8, pp. 5267–5278, 2012.
- [9] M. Gastpar, A. Lapidoth, Y. Steinberg, and M. Wigger, ‘‘Coding schemes and asymptotic capacity for the Gaussian broadcast and interference channels with feedback,’’ *IEEE Trans. on Inf. Th.*, vol. 60, no. 1, pp. 54–71, 2014.
- [10] S. Vishwanath, N. Jindal, and A. Goldsmith, ‘‘Duality, achievable rates, and sum-rate capacity of Gaussian MIMO broadcast channels,’’ *IEEE Trans. on Inf. Theory*, vol. 49, no. 10, pp. 2658–2668, 2003.
- [11] P. Viswanath and D.N.C. Tse, ‘‘Sum capacity of the vector Gaussian broadcast channel and uplink-downlink duality,’’ *IEEE Trans. on Inf. Theory*, vol. 49, no. 8, pp. 1912–1921, 2003.
- [12] H. Weingarten, Y. Steinberg, and S. Shamai, ‘‘The capacity region of the Gaussian multiple-input multiple-output broadcast channel,’’ *IEEE Trans. on Inf. Theory*, vol. 52, no. 9, pp. 3936–3964, 2006.
- [13] S. Belhadj Amor, Y. Steinberg, and M. Wigger, ‘‘Duality with linear-feedback schemes for the scalar Gaussian MAC and BC,’’ in *Proceedings of IZS*, pp. 25–28, 2014.