Some remarks on computational approaches towards sustainable complex agri-food systems

Nathalie Perrot, Hugo de Vries, Evelyne Lutton, Harald G. J. van Mil, Mechthild Donner, Alberto Tonda, Sophie Martin, Isabelle Alvarez, Paul Bourguine, Erik van Der Linden, et al.

► To cite this version:

Nathalie Perrot, Hugo de Vries, Evelyne Lutton, Harald G. J. van Mil, Mechthild Donner, et al.. Some remarks on computational approaches towards sustainable complex agri-food systems. Trends in Food Science and Technology, 2016, 48, pp.88-101. 10.1016/j.tifs.2015.10.003 . hal-01269357

HAL Id: hal-01269357

<https://hal.science/hal-01269357>

Submitted on 28 May 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Accepted Manuscript

Nathalie Perrot, Hugo De Vries, Evelyne Lutton, Harald G.J. van Mil, Mechthild Donner, Alberto Tonda, Sophie Martin, Isabelle Alvarez, Paul Bourguine, Erik van der Linden, Monique A.V. Axelos

PII: S0924-2244(15)00218-6

DOI: [10.1016/j.tifs.2015.10.003](https://doi.org/10.1016/j.tifs.2015.10.003)

Reference: TIFS 1710

To appear in: *Trends in Food Science & Technology*

Received Date: 7 April 2014

Revised Date: 15 September 2015

Accepted Date: 3 October 2015

Please cite this article as: Perrot, N., De Vries, H., Lutton, E., van Mil, H.G.J., Donner, M., Tonda, A., Martin, S., Alvarez, I., Bourguine, P., van der Linden, E., Axelos, M.A.V., *Trends in Food Science & Technology* (2015), doi: 10.1016/j.tifs.2015.10.003.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Comment citer ce document :

Perrot, N., De Vries, H., Lutton, E., van Mil, H. G. J., Donner, M., Tonda, A., Martin, S., Alvarez, I., Bourguine, P., van der Linden, E., Axelos, M. (2016). Some remarks on computational approaches towards sustainable complex agri-food systems. *Trends in Food Science and Technology*, 48, 88-101. DOI : 10.1016/j.tifs.2015.10.003

SOME REMARKS ON COMPUTATIONAL APPROACHES TOWARDS SUSTAINABLE COMPLEX AGRI-FOOD SYSTEMS

Structured Abstract

Background

Agri-food is one of the most important sectors of the industry in Europe and potentially a major contributor to the global warming. Sustainability issues in this context pose a huge challenge for several reasons: the variety of considered scales, the number of disciplines involved, the uncertainties, the out-of-equilibrium states, the complex quantitative and qualitative factors, the normative issues and the availability of data. Although important insight and breakthroughs have been attained in different scientific domains, an overarching and integrated analysis of these complex problems have yet to be realized.

Scope and Approach

This context creates huge opportunities for research in interaction with mathematical programming, integrative models and decision-support tools. The paper propose a computational viewpoint including questions of holistic approach, multiscale reconstruction and optimization. Some directions are discussed.

Key Findings and Conclusions

Several research questions based on a mathematical programming framework are emerging: how can such a framework manage uncertainty, cope with complex qualitative and quantitative information essential for social and environmental considerations, encompass diverse scales in space and time, cope with a multivariable dynamic environment and with scarcity of data. Moreover, how can it deal with different perspectives, types of models, research goals and data produced by conceptually disjoint scientific disciplines, ranging from physics and physiology to sociology and ethics? Building models is essential, but highly difficult; it will need a strong iterative interaction combining computational intensive methods, formal reasoning and the experts of the different fields. Some future research directions are proposed, involving all those dimensions: mathematical resilience, human-machine interactive learning and optimization techniques.

Keywords

Agri-food systems, sustainability, multiscale modeling, optimization, resilience, human-machine interactive learning.

SOME REMARKS ON COMPUTATIONAL APPROACHES TOWARDS SUSTAINABLE COMPLEX AGRI-FOOD SYSTEMS

Authors

Nathalie Perrot^{a,c*1}, Hugo De Vries^b, Evelyne Lutton^{a,c}, Harald G.J. van Mil^h, , Mechthild Donner^g,
Alberto Tonda^{a,c}, Sophie Martin^{c,d}, Isabelle Alvarez^{d,e}, Paul Bourguine^c, Erik van der Linden^{h,i}, Monique
A.V. Axelos^f

Affiliations

^a INRA, UMR782 Génie et Microbiologie des Procédés Alimentaires, F-78850 Thiverval-Grignon,
France (Tel.: +33 1-30-81-53-79; fax : +331-30-81-55-97; email: nathalie.perrot@grignon.inra.fr,
evelyne.lutton@grignon.inra.fr, alberto.tonda@grignon.inra.fr)

^b INRA, UMR1208 Ingénierie des Agropolymères et Technologies Emergentes, F-34060 Montpellier,
France (Tél. : +33 4 99 61 28 31) devries@supagro.inra.fr,

^c ISCPF (Institut des Systèmes complexes Paris Ile de France, 133 rue Nationale – F 75013 Paris (Tél.
+331 45 52 64 11 - Fax : +331 45 52 64 55)

^d IRSTEA, LISC. 24 avenue des Landais, BP5 0085 631 72 Aubière, France, (Tel/fax: +33 4 73 44 06 00,
sophie.martin@irstea.fr, isabelle.alvarez@irstea.fr)

^e UPMC, Lip6, 104 av. du Président Kennedy, 75016 Paris, France, (Tel/fax: +33 1 44 27 87 38)

^f INRA, UR1268 Biopolymères Interactions et Assemblages, F-44300 Nantes, France (Tel: +33 (0) 2 40
67 50 31 : email : Monique.Axelos@nantes.inra.fr)

¹ Corresponding author : Nathalie Perrot Tel.: +33 1-30-81-53-79; fax : +331-30-81-55-97; email:
nathalie.perrot@grignon.inra.fr)

^g Montpellier SupAgro, UMR MOISA, 2 Place Pierre Viala, 34060 Montpellier Cedex 02, France (Tél. :
+33 4 99 61 28 31 ; email : devries@supagro.inra.fr, mechthild.donner@supagro.inra.fr)

^h TI Food and Nutrition, Nieuwe Kanaal 9A, 6709 PA Wageningen, The Netherlands, irede@vanmil.net, vanderlinden@tifn.nl

ⁱ Laboratory of Physics and Physical Chemistry of Foods, Wageningen University and Research Center, Bornse Weiland 9 (building 118) 6708 WG Wageningen, The Netherlands. e-mail: erik.vanderlinden@wur.nl

Abstract

Agri-food is one of the most important sectors of the industry in Europe. Sustainability issues in this context pose a huge challenge. This paper gives a computational viewpoint on this problematic in order to develop a more holistic approach, a link between different scales and clear insights in the complexity of agri-food systems. This creates huge opportunities for research in mathematical programming, integrative models and decision-support tools. In this paper we outline some future research directions on mathematical resilience, human-machine interactive learning and optimization techniques.

Keywords

Agri-food systems, sustainability, multiscale modeling, computing complex system, decision support system, optimization, resilience, human expertise, interactive learning.

1. Introduction

Food (Lehmann, Reiche & Schiefer, 2012) is one of the most important sectors of the industry (CIAA 2009), encompassing chemicals, agriculture, feed, food processing and trade, retail and consumer

sectors. Production and consumption of food is the major contributor to the global warming potential in Europe (31%), taking into account all products required by the society. Amongst food products, meat and dairy have been identified as the main contributors to the global environmental impact, with a share of up to 12% in the case of meat, and up to 4% in the case of dairy products.

The food industry is fully aware that environmental performances of products and processes need to be improved in the full production-till-consumption chain². In addition, the consumer's needs should be met for food safety, health, convenience, lifestyle and product choice; and at the same time, commercial and financial benefits of the entire value chain must be assured in order to retain competitiveness. The problem to solve is particularly complex, since the management of the sustainability approach requires a multi-scale, multi-disciplinary and multi-factorial approach.

Sustainability starts at the farm level with the application of a large set of good farming practices, the preservation of natural resources and biodiversity, the development of specialized skills and capabilities, as well as the respect of farmer's choices in a given social and economic environment.

Subsequently, the transformation phase for biomass must be considered. Processes need to use these natural resources in a highly efficient way, developing bio-refineries to transform waste in by-products, and reconsidering the supply chain, currently still organized in a "product chain". Energy saving and water recycling are of course the major challenges in this step: they require development of new technologies through investments in research, increased awareness, especially crucial for SMEs (small and medium enterprises) to integrate innovation and a strong support from regional and (inter-)national policies. The volume of packaging has considerably increased in response to consumer demands for safety and affordability of products; its reduction is a tremendous challenge in the wider context of reducing household food waste while maintaining food quality.

² For further details, see

http://ec.europa.eu/research/bioeconomy/pdf/201202_innovating_sustainable_growth_en.pdf
http://etp.fooddrinkurope.eu/documents/2012/SRIA_2012/SRIA_ETP_Food4Life_2012.pdf

67 The third part of the equation concerns logistics, in particular when dealing with perishable products.
 68 In a world which did not take into account the environmental balance for a long time, road
 69 transportation became the major delivery means, with a considerable impact on greenhouse gas
 70 emission. Solutions exist, but require strong initiatives at a pan European level from politics, industry,
 71 research institutions and NGOs.

72 Finally, consumers should not be overlooked, because they play a major role in the sustainability of
 73 the food chain through their home practices, purchasing decisions, trade of shares and stocks,
 74 cultural and normative diverse background and requirements, etc.

75 In this context, creativity to reach breakthrough innovations on the one hand, and efficiency and
 76 optimization on the other hand, are crucial to obtain sustainable solutions: appropriate strategic
 77 visions, organization, transparency and control, assure safety and quality of novel products and
 78 ingredients (Lehmann, Reiche & Schiefer, 2012), as well as accessibility and affordability of food.
 79 Reaching these objectives requires multi-scale approaches, starting from the nano-scale for products
 80 and their ingredients, up to the km-scale for regional and global management issues, including
 81 organization and control of factories and food chains.

82 At each scale, one may observe a diversity of complex products and networks of organizations. In
 83 highly developed countries, production is characterized by very different types of enterprises,
 84 ranging from single-product manufacturers to generalists providing diverse products, technologies,
 85 services and logistics (Lehmann, Reiche & Schiefer, 2012). Production organization ranges from local
 86 to global, from farm to fork and beyond, from fast-foods to high-end restaurants, from laboratories
 87 to factories and supermarkets, from supply to demand and from single entities to full networks.
 88 Historically, agriculture and the linked manufacturing industry are considered to be independent
 89 sectors (Thompson & Scoones 2009) (Reilly & Willenbockel 2010); this holds today as well for the bio-
 90 based non-food sector. If we consider full food value chains as multi-input and multi-output

networks (or systems), it is noticeable how they are still poorly developed, when compared to the specific needs of consumers, society and environment at large; but since this vision of food chains has rarely been taken into account, numerous new opportunities and more sustainable solutions have yet to be considered.

In order to achieve sustainable approaches, different strategies can be developed by enterprises and societies. These strategies and their underlying models, however, might be synergic, neutral or in conflict with each other. It is thus crucial to carefully choose the strategies to follow, since these decisions are laden with moral, aesthetical and socio-economical values. Many heterogeneous factors, some being dynamical like zeitgeist, availability of information and perceived pressures, are to be taken into account when creating new legislation on sustainability. Normative dimensions of agri-food problems have the property of being heterogeneous, and can even be self-organising (see section 2.1). Indeed, we may view the normative dimensions involved as a stand-alone complex system, one that influences in turn the development of sustainability in many areas. This problem calls for a systematic approach on fair decisions, able to respect different moral, aesthetic and social-economical constraints (e.g. see Rawls, 1999).

A transition towards a bio-based society, while maintaining a viable planet and ethically well-accepted conditions, requires addressing various opportunities and devising appropriate solutions.

This paper gives a computational viewpoint and guidelines in order to develop (1) a more holistic approach, (2) a link between different scales and (3) clear insights in the complexity of agri-food systems. The rest of the paper is organized as follows: Section 2 considers the most relevant questions in a complex system approach for sustainable food systems. Section 3 reviews possible research directions, while Section 4 details three sources of inspiration for new approaches in the food domain. Sections 5 and 6 draw the conclusions and sketch high-level perspectives for the future.

2. Methodological approach, main questions and predictable bottlenecks

2.1 A holistic approach: an introduction to complex system science

A **holistic approach** can be characterized as the process of integrating, through interdisciplinarity and synthesis, cross-scale research and analysis (Thompson & Scoones, 2009). Integrative science provides a means to answer questions about inherent linkages and feedbacks within social-ecological systems, such as sustainable fisheries (Miller et al., 2010) and agricultural value chains (Higgins et al., 2010). Several dimensions should be taken into account: spatial, organizational, temporal scales, and the correlated rates of change; spatial distributions of variables, their scaling, and feedback loops have to be considered, as well as their interpretation within the relevant scientific disciplines.

This holistic approach cannot be managed “manually” *ab initio* and there is a clear need for decision-support tools based on different fields of computer science (applied mathematics, artificial intelligence, optimization), see sub-section 2.3 below. One of the most crucial tasks related to the development of such support tools is the design of models (Perrot et al., 2011, Charpentier, 2010, Trystram, 2012). **Modeling complex systems through a holistic approach** is an iterative activity that requires knowledge and comprehension of scientific facts, expert skills and sensory assessments, and relies upon methods allow for cross-overs with new fields in computer science.

CSS (**complex system science**) makes it possible to cope with the expanding boundaries of complex adaptability in agri-food systems; there is an increasing focus on interacting economic, social and environmental goals. Emergence of properties from these dynamical interactions should be studied.

The 2012-2020 roadmap defined the science of complex systems³ as distinct from any other particular science, because it focuses on the methods of reconstructing the dynamics of heterogeneous systems across traditional domains.

Systems can exhibit many properties that make them appear complicated or complex. These include:

- heterogeneous parts, e.g. a city, agriculture and the climate;
- complicated transition laws, e.g. agriculture and climate transitions;
- unexpected or unpredictable emergence, e.g. chemical systems, accidents;
- sensitive dependence on initial conditions, e.g. weather systems, investments;
- path-dependent dynamics, e.g. international relations, regional subventions;
- network connectivity and multiple subsystem dependencies, e.g. ecosystems, multiple industrial sectors;
- dynamics that emerge from interactions of autonomous agents, e.g. agriculture, traders;
- self-organization into new structures or behavioral patterns, non-equilibrium and far-from equilibrium dynamics, adaptation to changing environments, e.g. biological systems, manufacturing design.

Such properties are vertical, in the sense that they cut across disciplines which are researched horizontally in greater depth, based on the assumption that they can be treated in isolation (to a greater or lesser extent) by other domains. Economists, sociologists, food engineers, plant scientists, etc. traditionally tend to work in isolation from each other, while the science of complex systems aims at using a new methodological perspective. The transdisciplinary nature of CSS makes it unique because it strives to combine the methods, knowledge and theory of other disciplines. The complex system methodology starts from heterogeneous data and knowledge (Figure 1). The objective is to produce an augmented phenomenology where Δ , the statistical difference from observation, is as

³http://roadmaps.csregistry.org/tikiindex.php?page=The+science+of+complex+systems&structure=european_roadmap

small as possible but taking care of the danger of overfitting. For example, from the data and knowledge available about the structure-function elaboration of a food product, a phenomenological model encompassing the impact of a change in raw material usage on the food structure, its function, and consumer acceptance, can be created. Coupled to a model expressing the link between the raw material production and the territory scale organization, an agent-based computer simulation can be built to create an augmented phenomenology for this system, spanning from the km-scale to the nano-scale (Figure 1, bottom-center). On the basis of these simulations and knowledge availability, a model of organization covering the various scales is proposed to create another augmented phenomenology and the possibility of conceptual modeling by mathematical means (Figure 1, bottom-right), developed in more detail in (Van Mil et al., 2014).

[Figure 1 about here]

These augmented phenomenological holistic models are complex in their own right, and not always easy to interpret on a more general level, nor directly translatable to different contexts or related problems. More general models can be applied to a broader range of systems, but they lack the quantitative precision of augmented phenomenological models: thus, we need different classes of models to deal with complex problems at a deeper conceptual and abstract level. It is almost impossible to deduce models of complex systems *ab initio*: a good research strategy would be to start from empirical or phenomenological models, and then search for invariant structures, see (Stoutemyer, 2013) and, in a slightly different context, (Suppes, 2002). These invariant structures can then be interpreted in the light of overarching theories, or help theory construction. In order to find meaningful model structures, it becomes necessary to use more advanced mathematics and computer science, which allow different models to be mapped onto each other, and uncover the

invariant parts (Suppes, 2002; Stoutemyer, 2013). Giving meaning to these invariant structures calls for thorough interdisciplinary knowledge of the subject and the consultation of experts (see below 3.2). Such a strategy creates interesting opportunities for fundamental mathematics and logic in the context of computer science: this fact is not yet fully realized, but it can lead to innovations very difficult to obtain otherwise. We will not explore this branch of research further in the publication but will focus more on computational methods.

We only would like to note here that augmented phenomenological models and more general models can strengthen each other in terms of research quality. As in physics, analytic models are checked by numerical simulation and vice versa. This abstract process makes it possible to gain insights that would be otherwise very difficult to reach, and shows the necessity of a pragmatic pluralistic approach, as defined by (Suppes, 2002). No matter how complex, a holistic approach should have internal checks and balances, and create a well defined link between study design, data and models of different types, precision and abstraction.

2.2 A multi-scale approach

A major challenge is to crossover and to connect the scales, from the resource-structure level to the territory scale, and even beyond. While individual farmers or food companies at particular locations may be our empirical focus, their options and opportunities must be understood in relation to processes interacting across scales (Thompson & Scoones 2009), from the very local to the global ones. A pathway being pursued at one level may interact – positively or negatively – with options at another level, thus interconnections between individual, household, institution, regional clusters on one hand and (sub-)molecules, cells, plants and ecosystems on the other hand are all critical. Too often, analyses begin and end at the same scale, failing to explore larger effects. It is thus necessary

to step out of “disciplinary boundaries”, the comfort zone, which define and frame traditional analyses, in order to establish more useful interdisciplinary connections.

Problems that are non-linear in nature, cross-scale in time and space, and dynamic in character require a systemic perspective (Thompson & Scoones 2009). Interdisciplinary and integrated modes of inquiry are necessary for understanding and designing effective responses to human-environment interactions, related to food and agriculture, in a dynamic world.

Nevertheless, bio-based sciences emerged from traditional experimental sciences, the latter having procedures that often to narrow down the focus in order to pose specific questions, set hypotheses, collect data and design critical tests for hypothesis rejection. The goal has been to reduce uncertainty up to the point where acceptance of an interpretation among scientific peers is essentially unanimous. A drawback of this traditional “trial & error” approach is the limited knowledge it provides on the entire systems (Thompson & Scoones 2009) (Walker *et al.*, 2006).

Recent work on resilience suggests that many of the observed shifts, crises, or nonlinearities in ecological systems arise from processes and structures interacting across scales (Holling, 2001); and in fact, disruptions at different scales at the same time push the full system into another attractor more easily than a single perturbation on a single scale. For instance, resilience has been studied and extensively discussed for sustainable fisheries (Miller *et al.*, 2010). A possible trap experts can fall into is to try to understand the single parts and, consequently, lose the global perspective of the system (Walker *et al.*, 2006). Complexity, diversity and opportunity in complex (local) systems emerge from a handful of critical variables and processes that operate over distinctly different scales in space and time. There is a strong need for integrative frameworks that bridge disciplines and scales (Van Mil *et al.*, 2014).

2.3 Decision making issues and quantitative sociodynamics

Decision support tools and argumentation based models are built and used in a limited number of areas. These areas are often well described, possess reliable data sources (e.g. processing line characteristics) and are single-step oriented (Matser *et al.*, 2010). When dealing with chains of operations, the tools and models become more complex (Bourguet *et al.*, 2013). For complex multi-scale systems, we need to further develop sound argumentation and decision support systems integrating a considerable number of variables and interactions; here, one should face the following key elements:

- Surprises: as defined by (Thompson & Scoones 2009), are the qualitative gaps between perceived reality and expectation in ecological systems. Taking them into account, as well as the so-called technological surprises (Reilly & Willenbockel 2010) is a major challenge for agri-food systems. These unpredictable events must be considered in management practices besides other social and institutional mechanisms, in order to reduce poverty and increase resilience.
- Uncertainties: many variables are influenced by uncertainties, namely environmental regulations, demand, supply, initial capital cost, technological, biological effects like structure/function relationships, impact of processes and ingredients on quality (Perrot *et al.*, 2011). Interesting reviews and examples related to uncertainties in the biofuel Supply Chain Management can be found for instance in (Doukas, 2013) and (Awudu & Zhang, 2012). Additionally, if we consider uncertainty in energy sustainability, vague and complex concepts and their implications as a policy objective are difficult to define and measure (Grossman & Guillén-Gosálbez, 2010).

- Complex, qualitative and quantitative information sources, uncertain and incomplete data (Higgins et al., 2010), non-harmonized data acquisition⁴, availability and accessibility of information (Perrot et al., 2011).
- Sustainability metrics: currently available sustainability metrics are mostly devoted to individual organizations, only (Hassini, Surti, Searcy 2012).
- Dynamic adaptive behaviour: a reductionist vision is not enough to understand complex adaptive networks (Surana, Kumara, Greaves & Raghavan, 2013).
- Heterogeneous problems: market values, environmental, social, legal issues with some indicator measurements difficult to quantify (Meulen, 2013), due to the lack of numerical or probabilistic assessments.

The emerging field of quantitative sociodynamics, an offspring of econophysics, provides some interesting results in dealing with the problems discussed above; using theory and models developed in physics, but reinterpreting them with concepts from the sociology domain (Helbing 2010a, Helbing 2010b).

2.4 Summary of relevant questions

In the synthesis of model and real agri-food systems lies a huge research opportunity for mathematical programming, integrative models and decision-support tools (Gupta & Palsule-Desai, 2011).

Several research questions based on a mathematical programming framework are emerging: how can such a framework manage uncertainty, cope with complex qualitative and quantitative information essential for social and environmental considerations, encompass diverse scales in space and time, cope with a multivariable dynamic environment, and with scarcity of data. Moreover, how

⁴ <http://www.globalharmonizationinitiative.net>

can it deal with different perspectives, types of models, research goals and data produced by conceptually disjoint scientific disciplines, ranging from physics and physiology to sociology and ethics?

These questions are generally addressed separately by laboratories working in fundamental mathematics or computer science, and focus on theoretical, “simple” systems of various disciplines. These approaches should now be integrated and adapted to with regards to sustainability in real-world problems.

A new science corpus should be developed at the frontier of theoretical sciences and agri-food science, where these topics can be addressed. Some directions for building this corpus from the computational perspective are proposed in the next section.

3. Directions for future research in sustainability

Some directions are proposed in this section to face the challenge of sustainability in agri-food systems:

- Defining an overarching conceptual scheme: e.g. mathematical resilience,
- Sharing knowledge and expertise: man-machine interactions
- Augmented phenomenology: model construction and decision making.

3.1 Mathematical resilience perspectives

When integrating research that spans a number of scales and disciplines, it is expedient to introduce an overarching principle or concept. The term “resilience” is often used when the sustainability of a system is analyzed. Resilience is an emergent property of interactions within a system. Quantifying it remains a key scientific challenge (Carpenter *et al.*, 2001). The word resilience was first used at the

end of the nineteenth century in Material Physics to refer to the quality of some metals to resist to stresses and to return to their original shape after a blow. During the 20th century, its use has extended to several other domains, in ecology, economics, social sciences, etc. While the objects change, the underlying idea remains the same: resilience is defined as the capacity of the system under study to keep or restore some properties despite disruptions caused by perturbations (Carpenter et al. 2001). In ecology, the conceptual definition of Pimm (Pimm, 1984), considers resilience as the ability of a system to resist disturbance and the rate at which it returns to its steady state following a disturbance. For Gunderson and Holling (Gunderson & Holling, 2002), resilience is the capacity of a system to undergo disturbance and maintain its functions and controls and is therefore related to the concept of robustness in control theory (Carlson & Doyle, 200). As far as operational definitions in the context of ecosystem models are concerned, the main mathematical definitions of resilience are based on dynamical systems theory, and more specifically on attractors and attraction basins (see (Pimm & Lawton 1977), (van Collier, 1997)). More recently, the viability-based measure of resilience (Martin 2004) focuses on the desired properties of the system that do not necessarily correspond to attraction basins, but to an evolutionary development. Moreover, this general definition makes it possible to consider different management actions, and allows the experts to interact with the system and appropriately respond to disturbances (Alvarez, De Aldama, Martin & Reuillon, 2013). In economics, Martinet and Doyen have been the first to link sustainability with viability concepts. An intergenerational equity feature is naturally integrated within this framework (Martinet & Doyen, 2007). Moreover, the definition of a set of constraints bringing together desirable sustainable situations makes it possible to address sustainability as the possibility of finding a path that is an acceptable compromise for all parties (Fuentes, 1993). Since then, (Wei, Alvarez & Martin, 2013) have shown how the concepts of viability kernels and capture basins allow researchers to take into account spatial and time factors of a sustainability analysis with transient dynamic features. Several sustainability studies using mathematical viability tools have been

performed, for example in fisheries management (Martinet, Thebaud & Doyen 2007), (De Lara & Martinet 2009), and in forest preservation (Bernard & Martin 2013).

The main characteristic of the viability theory approach is to emphasize the definition of the constraints and means of actions before applying any optimization concerns. This is a powerful source of innovation, as illustrated, for example, by an application on the Camembert cheese ripening process (Sicard *et al.*, 2012)(Mesmoudi *et al.*, 2014).

The viability framework is used to compute the set of possible states and controls from which it is possible to reach a predefined quality target of Camembert cheese (figure 2 presents a result of the computation described in (Mesmoudi *et al.*, 2014)). This procedure makes it possible to evaluate that some ripening times are more crucial for the viable pathways of the state variables than others; at the beginning, for example, few values are admissible; and after 10 days, irreversible phenomena have taken place. This set of possible states contains trajectories that have never been considered by experts so far (Sicard *et al.*, 2012). The exploration of this set makes it possible to find ripening trajectories one-third shorter than the standard procedure, which had never even been contemplated at the beginning of the project, contrary to more traditional criteria such as energy or raw material quantity. In parallel, quality was maintained.

Moreover the knowledge of this set of viable states allows to take into account the distance to the boundary and to define in this way the robustness to perturbation. This approach was validated by experiments at the pilot scale.

[Figure 2 about here]

When the key variables, constraints (including sustainable ones) and possible controls of an agri-food systems can be identified, the viability approach can establish whether present practices and sustainable objectives are compatible and how.

351 Assume we look at a small local Camembert factory that caters a small connoisseurs market of
 352 Camembert devotees. Then we can combine two sustainability targets, environmental and cultural;
 353 two value systems that have always been intertwined and each of their own form an example of a
 354 complex problem, and as a combination. By
 355 including environmental/sustainability parameters/variables/targets to decrease of environmentally
 356 unfriendly output or increasing environmentally positive output, the model built could optimize
 357 sustainability targets if combined with optimizing computing tools (cf. chapter 3.3). One of the
 358 reasons to use the augmented phenomenology is to effectively optimize the process using the local
 359 Camembert expert to safeguard the cultural and uniqueness of the product and the knowledge of
 360 environmental experts in the process optimization using the augmented phenomenology as a third
 361 party. In this way the process also includes cultural values of the food product that relates the
 362 product to the cultural heritage of the region that is essential of its unique taste and structure so
 363 recognizable and enjoyed by the connoisseurs (cultural sustainability target) and the environmental
 364 sustainability target. Moreover, as culture is not a static phenomenon but a balance result between a
 365 conservative cultural dogmas and new innovations, it fits well in the culture development allowing
 366 for the evolution of new products out of old ones within the cultural same context; e.g a new variety
 367 of Camembert with a distinct taste, structure and smell, a triumph of the "man-
 368 machine cooperation". The main limit of the approach is the complexity of the computation which is
 369 exponential with the number of state variables. This presently limits practical nonlinear applications
 370 to less than 10 variables. Research work is currently performed to overcome this limitation (with the
 371 use of classification functions or test methods)

372

373 The trade-off between efficiency and resilience remains obvious (Walker et al., 2006, , Carlson &
 374 Doyle, 2000 and ref). Optimizing performance by increasing efficiency in a nonlinear adaptive system
 375 is a complex task. Experts have indeed gained the skills to cope with the complexity of their

environment while keeping the sense of the whole. For example, pilots are able to steer their aircraft in complex environments without losing control. Drawing a parallel with sustainability purposes can be relevant: however, the major bottleneck of these approaches remains the acquisition of knowledge (Hoffman, Shadbolt, Burton, & Klein, 1995), which is often a difficult and time consuming step (Sicard *et al.*, 2011). Interactive approaches coupling autonomous computations and human expertise thus represent an attractive perspective.

3. 2 Interactions with human knowledge and expertise

Another question, addressed by several authors, concerns the place of experts and human knowledge in mathematical approaches applied to sustainability. Although several studies analyze expertise both in psychology and artificial intelligence, it is not possible to provide a consensual and operational definition of this notion (Shanteau, 1992). Expertise may include skills, knowledge or abilities in tasks, jobs, games or sports, and is domain-specific (Chi, Feltovich, & Glaser, 1981). In spite of the diversity of task domains and of expert definitions, literature reports three criteria to define experts: they are better at producing inference, at anticipating dynamics, and have a more functional view of the process (Cellier, Eyrolle, & Marine, 1997). Finally, experts are characterized by a large number of automatisms and knowledge acquired during practice (Raufaste, Neves, & Marine, 2003). In human cognition, perceptive processes are an automatic and continuous form of learning (Gibson, 1969). Perception learning is based more on experience (so called SB, for sensory based) than on rules (so called RB, for rules based) (Ballester, Patris, Symoneaux, & Valentin, 2008), (Valentin, Chollet and Abdi, 2003) show that experts have an advantage in recognition memory: they illustrate that these higher performances are likely derived from more efficient coding and retrieval of long-term memories. One of the efficient coding mechanisms used by experts is the cognitive “chunk” recognition (Chase & Simon, 1973). A “chunk” is a grouped set of variables, taken from a situation,

that are closely related to each other. These variables are acquired through experts' sensorial perceptions.

Operational research is a discipline that deals with the application of advanced analytical methods to help make better decisions. This is an active field in the domain of sustainability, where expertise has an important role. Higgins et al. (Higgins et al. 2010) have underlined the following key elements:

- Mathematical representation of the problems (integer or linear programming) is not generally consistent with the way in which the decision maker understands the problem when constructing the solution. Approaches should take into account this dimension and integrate it iteratively, for instance through an interface with the decision makers (figure 3, from Miller et al., 2010), where authors propose a structure where a participatory process is embedded iteratively in the loop of an algorithm. Integration is performed at the validation level.

[Figure 3 about here]

- Quantifying factors considered by experts when generating a desired solution is hard; often solutions are found through extensive exploration, and not focusing on efficiency and inclusion of feedback loops.
- Data requirements and uncertainties may be huge.
- Whole-of-chain system understanding of practical problems, particularly when social and environmental drivers are concerned, is difficult to reach for the industry and practitioners.

Another element is given by (Melnik, 2009): with the increasing complexity of technological systems that operate in dynamically changing environments, the relative share of human errors is increasing across all applications. This means that human errors can no longer be ignored (or eliminated easily

424 by conventional formal statistical methodologies) but should be integrated into the modeling
425 framework.

426 Reilly and Willenbockel (2010) propose to consider uncertainty, complexity and diversity as means to
427 enhance adaptability of agri-food systems; by contrast, current policies and practices aspire to
428 maintain the status quo or to control change in systems assumed to be stable. In other words, this
429 implies a radical change from reactive to proactive system approaches. Improving the process of
430 innovation via knowledge sharing is strongly linked to the ability of models to capture not only the
431 planned but also the unplanned outputs of knowledge sharing (Miles & Snow, 2007; Zwart et al,
432 2006). Computer aided design must help the person or group to communicate easily and generate
433 more and richer ideas (encourage generation of diverse even inept ideas that carry potential for new
434 ideas), while maintaining their diversity.

435 Applied to manufacturing processes, where generally the assessment of alternative solutions is based
436 on life cycle assessment, (LCA), some contributions have been developed at the frontier of artificial
437 intelligence, to take into account expert knowledge. Authors like (Giovannini *et al.*, 2012) used for
438 example ontologies that implement a support to sustainable manufacturing. The authors' main
439 statement is that a cultural shift is required that involves in-depth software and hardware insights in
440 manufacturing processes. They propose to design a KBS (knowledge based system) simulating the
441 role of a sustainable manufacturing expert, who is able to automatically identify change
442 opportunities and to propose alternatives. The human dimension is thus included and considered in
443 the cost function evaluation. The next step is to integrate not only the external evaluator role within
444 a more or less balanced system but in a full network that link local connections and from which
445 global properties emerge.

446 For instance, a tool that is currently available to explore multi-dimensional data sets is EvoGraphDice.
447 It is based on the EVE framework (Evolutionary Visual Exploration) (Boukhelifa et al., 2013). This

approach for data exploration combines a classic interactive visualization technique (a scatterplot matrix with linked views) with evolutionary stochastic optimization. The EvoGraphDice prototype extends the concept of principal component analysis of scatter plots by using interactive optimization to evolve a population of secondary axes of observations as linear or nonlinear combinations, thus providing users with nontrivial views on their data.

However, current projection axes are not defined from the mathematical structure of the model in hand; rather they are dynamically generated to favor views showing an interesting visual pattern to the user where the notion of “interesting” is defined dynamically using an image-based metric and subjective user ranking of views.

The EVE framework could be further extended to take into account different types of knowledge, both quantitative and qualitative (e.g. mathematical structures, statistical information, or confidence level), to better guide the exploration to pertinent areas of the search space. The uncertainty itself could be fed into the interactive evolutionary algorithm such that user exploration is driven towards more certain (or informative) areas of the search space. Whereas Scatterplot Matrices (SPLOMs) are effective for visualizing small to medium-sized static multidimensional data sets, new scalable visualization techniques need to be investigated to better visualize time-varying scale-dependent relationships between a large number of dimensions (e.g. using dynamic networks instead of or linked to the SPLOM). In this new context, new navigation techniques are also required to allow for the smooth transitioning between the different scales and types of data (e.g. using appropriate animated transitions).

3.3 Optimization

Optimization in the context of complex adaptive systems is far more difficult than when dealing with plain systems based on sequences of static configurations; the latter has been extensively elaborated, for example in chemical engineering (Grossmann & Guillén-Gosálbez, 2010; Lainez & Puigjaner, 2012).

Optimization is used for various purposes: in this work, we are mainly interested in (a) building models, learning their parameters and structures from available data and knowledge; and (b) using such models in decision-making processes.

Optimizing the efficiency and resilience of an entire industry, as a network of business partners and competitors, is fundamentally different from optimizing each individual business unit within the context of that industry (Miller *et al.*, 2010). However, contemporary management is based almost entirely on the optimization of individual business units for static “average” conditions. Influences arising from states and dynamics above and below the scale of interest are ignored, but affect the ability of the system to reorganize and resist after some disturbance (Walker *et al.*, 2006). Furthermore it should be noticed that integer or linear program optimization strategies can have a small spatial or temporal range in terms of predicting the effects of an action if the system exhibit strong nonlinear properties. Depending on the point in parameter space, the variable underlying distributions or phase space can change, leading to different dynamics and equilibriums or steady state solutions. Moreover, these systems evolve; intervention, control mechanism and innovations introduce new objects and relations, affecting the fitness landscape of the function to be sustained or other seemingly unrelated important processes. Therefore optimization should be viewed as a continuing dynamic and adaptive process.

As said above, the implication of single human users or groups of users in optimization processes is a challenging question (for dealing with expertise on model building, decision making, control, monitoring, data gathering, tacit knowledge, etc.). Techniques involving human expertise in optimization processes are sometimes referred to as *humanized optimization* (Takagi, 2008).

While potentially very effective, humanized optimization has several important limitations, the major one being *user fatigue*, the tendency of human users to lower the quality of their assessment as the time spent interacting with an algorithm increases. There is a considerable amount of literature on compensating or limiting user fatigue (Lam, 2008): concerning model building, a possible approach is to let the user itself set the pace of the procedure. (Tonda *et al.*, 2014), for instance, proposes a framework for Bayesian network structure learning, capable of producing probabilistic graphical models with a semi-supervised approach. The framework is tested by two experts in food science, using datasets from food processing, and while the results are satisfying, further limitations are uncovered: given the choice between multiple learning algorithms, users show a predominant preference for quick and sub-optimal algorithms, with respect to slower, more effective ones. Thus, it seems that the expert would rather see the immediate result of his/her ideas, more than obtain the best possible approximation. Another limit of this approach concerns the number of variables that a human can manage: even when interacting with a graphical model, users cannot successfully analyze more than a few tens of nodes. This limit is also true for the advanced visualization methods discussed in paragraph 3.2. These are non-trivial insights that should be taken into account for devising further methods combining human expertise and machine learning.

Even more difficult but strategic issues are related to optimization for decision making in a hierarchical environment with a variety of business functionalities (Lainez & Puigjaner, 2012), where the behaviour of the system and the available knowledge at different scales has to be considered.

In order to design efficient optimization algorithms, various points need to be addressed: structure of the search space (for instance with mixed variables), constraints, and optimisation aims (mono- or multi-criteria objectives) (Pavone and Coello Coello, 2012). The question of multiple conflicting aims can be tackled using multi-objective optimization tools (Miettinen and Sayin, 2013), providing the user with a full range of optimal compromises, called Pareto front. Even if the Pareto front might be large and hard to understand for a human user, efficient decision tools and ad-hoc visualization techniques can help the user to efficiently explore the set of proposed solutions, and finally take a decision (Coello Coello, 2009).

4. Examples

4.1 Multi-scale analysis in the chemical industry

Sustainability is indeed largely addressed by the chemical industry, in particular in process synthesis. A review about this topic can be found in (Nicopoulou and Lerapetritou, 2012). Several scales can be considered as depicted by (Lainez & Puigjaner, 2012). An example among others is related to a biofuel chemical plant (You, Tao and Snyder, 2011), where several configurations at the equilibrium are tested. The focus of this work is not only on the manufacturing process but also on the supply chain. Numerical approaches like MILP (multiperiod, mixed integer linear programming) and MOO (multiobjective optimization) are widely used to reduce costs in process synthesis by choosing the best organisation at the equilibrium. The strategy is based on the following steps (Grossmann & Guillén-Gosálbez, 2010): (1) development of a representation of alternatives, (2) formulation of a mathematical program for the selection of the configuration and operating levels that involve discrete and continuous variables, (3) the solution of the optimization from which the optimal solution is selected. Several optimization methods have been tested in literature, from gradient search to global ones, as tabu-search or evolutionary algorithms.

The drawback of system dynamics models (type MILP) is that the structure has to be defined before the simulation starts. Another drawback of these chemical engineering applications is that optimization is achieved on solutions at the equilibrium of the system, and transient dynamics are disregarded. Queuing theory has primarily been used to address the steady-state operation of a typical network. Mathematical programming has also been used to solve the problem of resource allocation in networks. This is meaningful when dynamic transients can be disregarded, which is not always relevant with regards to the problem tackled. A useful paradigm for modelling a supply chain, taking into consideration the detailed patterns of interaction, is to view the process as a network involving interacting agents: (Surana, Kurava, Greanes & Raghavan, 2013) propose an approach originating from complexity theory: an agent-based model, or 'bottom-up approach', simulates the underlying processes that yields a global pattern. This makes it possible to evaluate which mechanisms are the most influential in producing the emergent pattern. Networks are inherently difficult to understand due to their structural complexity, evolving structure, connection diversity, dynamical complexity of nodes, node diversity and meta-complication where all these factors influence each other.

If we translate this to agri-food systems, it becomes even more crucial to consider many agents and scales, and especially their reciprocal interconnections. Embodying scales in this domain means also taking simultaneously into account structure, function, preferences, acceptance, perception and needs. If this viewpoint is shared with the chemical industry (Charpentier, 2010) (see figure 4) there is an increased complexity due to the nature of living phenomena and their environmental impact on the entire system. As a consequence, sustainability approaches include the molecular level (even down to sub-atomic levels), i.e. the scale guiding the dynamics of structure-function relationships and biological processes around equilibrium, up to the factory level and beyond. Territory mega scale level may even be considered when sustainability purposes are investigated. In this context,

sustainable solutions emerge from transient states and not only at equilibrium. This makes it possible to include human interventions, both locally and globally.

[Figure 4 about here]

4.2 Multi-scale analysis in biological processes

An interesting example of multiscale challenge is the management of the ecosystems in agri-food systems. Microbial ecosystems are present everywhere (e.g. in soil, animal gut, food products and marine sediments). Understanding their multi-scale properties to be able to make predictions is of major importance to life sciences (Faust and Raes, 2012). The assessment of microbial ecosystems mechanisms, from gene expression to emergence of functional properties is a challenging issue for several reasons, including the presence of many scales, uncertainties, out of equilibrium (instability), and complex quantitative (generally big data) and qualitative information (a long scientific descriptive expertise).

Ecosystems are involved in a large variety of food systems. For example one typical microbial ecosystem widely studied is cheese. Cheese is one of the oldest dairy products and, nowadays, constitutes the most diverse group of dairy products with several hundreds of distinct varieties. It involves a dairy industry that plays a key role in the French economy with 27.7 billion income and 3.6 billions trade surplus in 2013, representing over 250000 jobs.

Cheese ripening is a complex process involving a range of microbiological and biochemical reactions. During this process, three major biochemical events occur: lactose consumption, lipolysis, and proteolysis. These catabolic reactions are responsible for the production of various compounds including volatile aroma compounds which play an important role in flavor perception.

The cheese microflora is characterized by a high cell density, as it can reach more than one billion cells per gram of cheese. It is composed of both aerobic members, i.e. those developing on the

cheese surface such as microorganisms found in the rind of soft cheeses, and anaerobic, i.e. those growing inside the curd like species found in the middle of hard cheeses. The main technological activities sustained by the microbial community regard the matrix biodegradation which lead to the development of interesting organoleptic properties (cheese sensory quality), and the potential protection effect against spoilage microorganisms and pathogens (cheese safety).

A large microbial diversity has already been isolated from cheese products, providing an important resource of cultivable microbes for microbiological, biochemical and molecular analyses. It mainly contains Firmicutes (lactic acid bacteria, staphylococci), Actinobacteria (coryneform bacteria), Proteobacteria, Bacteroidetes, yeasts and moulds. Recent inventories of the cheese microbial diversity allowed estimating that almost three hundred different species might inhabit cheese products. For example, microbial interactions between ripening microorganisms have been highlighted by co-culturing isolated strains in experimental cheeses providing key knowledge on competitions or growth inhibitions occurring in cheese (Mounier et al., 2008) but not completely explained. In parallel, meta-omics analyses were conducted on a reduced ecosystem composed of nine microorganisms in which keystone species omissions were experimented. This project generated > 300 GB of meta-transcriptomic data corresponding to the expression level of 37,923 individual genes as well as numerous associated physico-chemical, biochemical and metabolomic data. The classification of the expression data from those genes into functional classes made possible to obtain an overview of the metabolic activities of the nine microorganisms composing the ecosystem (Figure 5). Nevertheless from those study to the mathematical prediction and simulation of the system, there is a gap not yet filled in.

In such a complexity (limited in comparison to the intestinal microbiota!), there is still a gap that needs to be bridged between the molecular scale information (genetic, expression, compounds detection) and the macroscopic properties (e.g. flavor for a cheese) (Landaud, Helinck & Bonnarme, 2008). Several reasons can explain this fact.

First, the chemical compounds, particularly the products that are secondary metabolites for well-known metabolic functions are often not connected to metabolic models due to the lack of genetic information. Emergence of macroscopic properties from genome expression using classical bioinformatics tools is then still limited. If knowledge can be found in several descriptive studies about microbial communities, it is not often exploited because it generally needs a huge work of extraction and formalization (Liu et al., 2014).

A second reason is related to the scale of observation of the mechanisms involved. Indeed, if several works are achieved regarding a single organism based on genome-scale metabolic network (see Bordbar et al., 2012 and Wodke et al., 2015 for examples), few have proposed to manage an in situ metabolic activity of a microbial community (Bowen et al., 2014). Generally the focus of such studies is on the description, sometimes the modelling of the metabolic detailed pathways and their associated chemical compounds.

It is not at all easy to manage a balance between (1) a detailed description of each compound of the metabolism pathways for one microorganism and (2) an ability to cut across the individual scale to go through an in situ expression of a community. Computing problems arise as well as an uncertainty on the scales needed to extract a synthetic architecture able to predict the emergence of macroscopic functionalities. Moreover, reconstructing multiscale dynamics of the in situ community, involves finding a mathematical structure able to organize in a relevant way the links between the scales and variables. Nevertheless, the optimal way to structure and aggregate the knowledge embedded in the big database available and in the heuristics manipulated by experts is not an easy task to achieve. This is why we have to work on how to develop optimal mathematical structures (cf. chapter 3.3);

[Figure 5 about here]

As stated the gap between micro-scale information and macroscopic properties (e.g. flavour profiles and macro-structures) should be bridged. Even more, the bridge needs to be extended towards the

flavour and structure perceptions of consumers. Even though those perceptions are individual - and highly dependent on the environmental conditions during consumptions, cultural values, etc - one needs to (1) abstract collective information in order to efficiently adapt products offers with demands and (2) understand the underlying consumer preferences. Concerning the latter, quantitative sociodynamics could help in better understanding those preferences. The first requires handling of complex data sources and optimization processes in order to let emerge collective properties.

4.3 Sustainability of networks by collective regional branding.

France is characterized by strong regional forces and relevant connected activities. Their “pôles de compétitivité” (“competitive clusters”) are recognized by the European Commission as a source of innovation and employment, while maintaining and enforcing traditional values (EC report on regional policy for sustainable growth, see below). Linked to local cultural values, these clusters show a diversity of multi-scale characteristics, dynamical patterns (Porter, 2000), resilience, (intuitive and strategic) decision making and optimization steps, either by a ‘hierarchic leader’ or by the stakeholders within the cluster. Two key examples are the collective regional food marketing initiatives “Produit en Bretagne” (North-West of France; region Brittany) and “Sud de France” (South of France, region Languedoc-Roussillon).

The first is a private, entrepreneurial-driven network of food companies that have developed a common regional brand for typical products. It has slowly evolved into a strong business network of nearly 300 companies in Bretagne, sharing not only a common commercial ambition, but also cultural values and ethical principles as solidarity and sustainability. It is a key example of a self-organized complex system in which the stakeholders and their interactions – either intuitively or via joint strategic actions – result in resilience accompanied by periodically renewed emerging properties

663 showing the diverse quality characteristics of their products. “Produit en Bretagne” is one of the
664 oldest European regional brands.

665
666 The second example, “Sud de France”, is a public policy-driven initiative to promote products of the
667 Languedoc-Roussillon; the major reason to create the brand in 2006 was the decline in sales of
668 regional wines, due to an increasing worldwide competition and low appreciation of their origin. As
669 the largest region of wine production worldwide, this tendency should be counteracted according to
670 policy makers. Step by step, wine producers have been persuaded to use the “Sud de France” label;
671 later on, the brand has been extended to other food producers and to sustainable tourism. The
672 brand is even used as institutional tool, labeling other sectors, as logistics, sport, culture, research
673 etc., raising its complexity. Wine export has been rising afterwards, and over 3000 companies have
674 joined the initiative, which currently brings 9.400 different agricultural products and 850 quality
675 tourism services under the banner “Sud de France”. However, it is not adopted by the companies in a
676 sense that they have fully taken over the investment and running costs of this joint marketing action;
677 it is still a publicly funded marketing offensive (Donner *et al.*, 2014). Thus, one could conclude that
678 involved stakeholders of “Sud de France” are not yet fully embedded in a regional cluster (Uzzi,
679 1996), neither the brand has evolved in a dynamic, self-organised, network.

680 Here, the full complexity of the regional food system is recognized, as well as its players (agents) and
681 their interactions, the diversity of products – and their overall quality and functional properties –
682 and production chains (including local and global resources), its (historical) development, emerging
683 properties and new perspectives at local and global scale for a wide range of consumers. Boundary
684 conditions also impact the system as a whole, including regional branding restricted usage,
685 protection of origin labels, global trade regulations, protective measures, global price volatility,
686 political changes, public and/or private investments, etc. A key feature is the leading role of the
687 Region Languedoc Roussillon, with periodically large investments and extensive marketing initiatives
688 trying to optimize the overall output of the Sud-de-France region. Hence, the various regional

689 activities show a multitude of patterns, from periodical but rather static, up to highly chaotic. The
690 activities in between seem to balance well at the edge of order and chaos, and would most likely
691 reveal resilience and a high level of self-organization, in this case supervised by the Region LR who is
692 major decision maker, at all scales from molecular level (recognized functional properties of their
693 products) up to global scales (recognized marketing related to a well-appreciated country of origin
694 cluster).

695 As stated by the Santa Fé institute (Kaufmann, 1995) (self-organization in complex systems) and by
696 Helmsing and Vellema (Helmsing & Vellema, 2011) (socio-technological innovations and embedding),
697 the design of a full technological-socio-economical food system deserves to be a major research line.
698 A multi-disciplinary approach for qualitatively and quantitatively analyzing complex regional branding
699 for high quality and diverse products, combining several disciplines such as economics, mathematics,
700 marketing, politics, sociology or geography (Dinnie, 2004), together with engineering, agri-food and
701 bio-based sciences, is needed in order to better understand the success and failures of regional
702 clusters.

703 Practically, we propose the following strategy to achieve those new insights and to give sound
704 recommendations. Step 1 concerns painting a picture in time (including thus its history) of a territory
705 marketed via a common brand, including products and their distinct values locally and globally,
706 stakeholders involved and their interactions, regional characteristics, boundary conditions and
707 incentives, ... Step 2 considers the different scales all along the chain from resources and product
708 quality characteristics towards final characteristics appreciated by target groups of consumers. Step
709 3 addresses a first complex system model in which the rigidity, resilience and chaos situations of the
710 territorial cluster(s) are incorporated. Step 4 analyzes in more detail the emergent properties of the
711 cluster in which new products are (co-)developed, marketed, ... Step 5 focuses on which optimization
712 steps are carried out and by whom as decision makers in order to better position a competitive

cluster. Step 6 includes a repetitive procedure to further optimize the complex system approach to better adapt the complex system to the realistic conditions.

5. Conclusions

To conclude, even if some approaches -- agent-based approaches among the most representative ones -- are already available and applied to some fields of research like embryogenesis (Olivier et al., 2010) and urban simulations (Irwin, 2010), there is a clear need for efficient, intensive and parallel computational methods for the agri-food domain (Reuillon, Traore, Passerat-Palmbach and Hill, 2012).

At present, several issues remain unanswered:

- Find the right level(s) of description to simulate the system. The answer will generally be strongly connected to the objective of the study and at present a methodology to find the right level(s) does not exist and should be rediscovered for each application without any guarantee of relevance.
- Multiscale reconstruction limitations: progress has been done on computational tools to manage uncertainty, for example Bayesian formalisms, theory of possibility on heuristics manipulated by humans, stochastic approaches applied to different mathematical representation ie on individual based models, ontology-based data access. Nevertheless, used independently these solutions require lots of knowledge or data at each scale while only some of them are available (cf. example chapter 4.2). Moreover, even with a big data basis, without any oriented structured approach, a part of the knowledge is lost or unusable. In this sense there is a necessity to propose tools for coupling heterogeneous model and knowledge and connect different computing communities (see the smart data tendency).
- Parameters tuning limitations: another limitation is linked to the necessity for those approaches to tune empirically some parameters: graph and discretization for the DBN;

indexation for the data mining; parameters of the stochastic laws, far more complex to be tuned than parameters of known physical laws; parameters of the optimization algorithms or other AI algorithms. Some new research focusses on this point at present (interactive learning, visualization).

- Computational limitations: if stochastic approaches are really well adapted to the multiscale reconstruction in an uncertain context, it relies on a high capacity of computation. Even if now the computational power is largely increased, with clusters of computers, the number of variables that could be manipulated by some approaches is still limited: for example, less than 10 for the viability theory (cf. chapter 3.1), 5 variables for the approaches of optimization coupled to visualization (cf. chapter 3.3),....
- Visualization and user fatigue limits: all methods based on machine-man interaction impose a consistent exertion on the expert (Lem, 2008), often referred to as user fatigue. While semi-supervised learning of models through graphical user interfaces can be very effective, combining the best aspects of machine learning and expert knowledge, the strain imposed on the user severely limits the effectiveness of these approaches.

Decision making in sustainability management of agri-food systems will require building a science able to cope with uncertainty, emergence of properties, multi-scale reconstruction, optimization of non-linear systems in dynamic environments, interactive learning and human expert knowledge, non-equilibrium exploration and dynamical behavior at the edge between order and chaos. Building models is essential, but highly difficult and allows for plenty opportunities for the mathematical and computational sciences; it will need a strong iterative interaction combining computational intensive methods, formal reasoning and the experts of the different fields.

Although generic methods are still not available and relevant expert knowledge dispersed, complex system science and associated fields already provide the first answers to basic, well-defined and context-oriented problems. Nevertheless, the tools of complex science need to be extended to

especially in-depth research at interfaces of previously considered separated scales, as illustrated here. The key building blocks of efficient methods have been addressed, as well as the way they potentially could contribute to a generic complex system approach. Table 1 is a synthesis of the steps required for an approach of the complex problem of sustainability of food systems, the work realized in this direction, reachable or more difficult to achieve, and a list of mathematical or computing tools already available or under study at present. As a next step, we need to enter a technological-socio-economical regime in which scales are interlinked in order to develop a flexible but rigorous concept for the complex system approach. Then, this would make it possible to come up with practical tools for decision makers who are facing challenges on sustainability.

[Table 1 about here]

6. Perspectives

We need to come up with more radical innovations and solutions integrating all (linked) scales, with the help of a generic approach as proposed here, in order to maintain a viable planet; if not, our current innovations may only extend the “expiration date” of our planet. We are convinced that a creative, multi-scale, multi-discipline and complex system approach is able to provide tools that are needed to tackle the current challenges in research, development and business strategies.

Our society is facing challenges that have to be approached with new strategies. The review of current trends for the obesity, growth of world population, atmospheric levels of greenhouse gases, national debt of countries, all exhibit a common feature, that is a (near) exponential growth. This growth is incompatible with balanced systems. These systems show periodic changes but always

return to an attractor or a stable position after a given period. The optimization of such out-of-the-equilibrium systems should rely on the stochasticity of the signal during a significant time. Innovations relying on integrated and deep knowledge, may help in trying to level off exponential curves.

Acknowledgements

The authors would like to thank all participants of the duALine project, and in particular Dr C. Esnouf for her help; Acknowledgement for the financial support of government (French ANR project INCALIN). Acknowledgment for the funding received from the European Community's Seventh Framework Program (FP7/2009–2013) under grant agreement DREAM No. 222654-2.

References

- Alvarez, I., de Aldama, R., Martin, S., Reuillon, R., Aug. 2013. Assessing the resilience of bilingual societies: coupling viability and active learning with kd-tree. application to bilingual societies. In: IJCAI 2013 AI and Computational Sustainability Track. Beijing, China, pp. 2776–2782.
- Alvarez, I., de Aldama, R., Martin, S., Reuillon, R., 2013. Assessing the resilience of socio-ecosystems: Coupling viability theory and active learning with kd-trees. In: IJCAI 2013, Proc. of the 23rd International Joint Conference on Artificial Intelligence pp. 2776-2782.
- Aubin, J., 1991. Viability Theory. Birkhauser, Basel.
- Awudu, I., Zhang, J., 2012. Uncertainties and sustainability concepts in biofuel supply chain management: A review. Renewable and Sustainable Energy Reviews 16, 1359–1368.
- Baudrit C., Willemin, P.H., Perrot, N. (2013). Parameter elicitation in probabilistic graphical models for modelling multi-scale food complex systems" Journal of food engineering, 115(1), 1-10.
- Bernard, C., Martin, S., 2013. Comparing the sustainability of different action policy possibilities: Application to the issue of both household survival and forest preservation in the corridor of fianarantsoa. Mathematical Biosciences 245 (2), 322–330.
- Bordbar, A., Mo, M.L., Nakayasu, E.S., Schrimpe-Rutledge, A.C., Kim, Y.M., Metz, T.O., et al. Model-driven multi-omic data analysis elucidates metabolic immunomodulators of macrophage activation. Mol Syst Biol. 2012;8. doi:10.1038/msb.2012.21
- Boukhelifa, N., Cancino, W., Bezerianos, A. and Lutton, E., 2013. Evolutionary Visual Exploration: Evaluation With Expert Users. Computer Graphics Forum (EuroVis 2013, June 17–21, 2013, Leipzig, Germany), Eurographics Association, 32 (3).

- 817 Bowen, J.L., Babbin, A.R., Kearns, P.J., Ward, B.B., 2014. Connecting the dots: linking nitrogen cycle gene
818 expression to nitrogen fluxes in marine sediment mesocosms. *Aquat Microbiol*, 5, 429.
819 doi:10.3389/fmicb.2014.00429.
- 820 Bourguet, J.R., Thomopoulos, R., Mugnier, M.L., Abecassis, J. 2013. An Artificial Intelligence-Based Approach to
821 Deal with Argumentation Applied to Food Quality in a Public Health Policy. *Expert Systems with Applications*, 40
822 (11): 4539–4546.
- 823 Bousson, K., Steyer, J.P., Travé-Massuyès, L. Monitoring and diagnosis of fermentation processes, in *Issues of*
824 *Fault Diagnosis for Dynamic Systems*, (Ed. Patton, Franck and Clark), Springer-Verlag, 2000, ISBN 3-540-19968-
825 3.
- 826 Carlson, J., & Doyle, J. (2000). Highly Optimized Tolerance: Robustness and Design in Complex Systems. *Physical*
827 *Review Letters*, 84(11), 2529–2532.
- 828 Carpenter, S., Walker, B., Anderies, J., Abel, N., 2001. From metaphor to measurement: resilience of what to
829 what? *Ecosystems* 4, 765–781.
- 830 Charpentier, J., 2010. Among the trends for a modern chemical engineering, the third paradigm: The time and
831 length multiscale approach as an efficient tool for process intensification and product design and engineering.
832 *chemical engineering research and design* 88, 248–254.
- 833 Coello Coello, C. A., 2009. Evolutionary multi-objective optimization: some current research trends and topics
834 that remain to be explored. *Frontiers of Computer Science in China* 3 (1), 18–30. URL
835 <http://dx.doi.org/10.1007/s11704-009-0005-7>
- 836 De Lara, M., Martinet, V., 2009. Multi-criteria dynamic decision under uncertainty: A stochastic viability analysis
837 and an application to sustainable fishery management. *Math. Biosci.* 217 (2), 118–124.
- 838 Dinnie, K., 2004. Place branding: overview of an emerging literature. *Place Branding*, 1, 106-110.
- 839 Donner, M., Fort, F., Vellema S., 2014. How to capture place brand equity? The case of Sud de France. *Place*
840 *branding and public diplomacy* (forthcoming).
- 841 Doukas, H., 2013. Modelling of linguistic variables in multicriteria energy policy support. *European Journal of*
842 *Operational Research* 227 (2), 227–238.
- 843 Dovers, S. R., Handmer, J. W., 9 1993. Contradictions in sustainability. *Environmental Conservation* 20, 217–
844 222. URL <http://journals.cambridge.org/articleS0376892900022992>
- 845 Dugat-Bony, E., Straub, C., Teissandier, A., Onésime, D., Loux, V., Monnet, C. et al. (In Press). Overview of a
846 surface-ripened cheese community functioning by meta-omics analyses. *PLoS ONE*. In press.
- 847 EC Document, 2011 Regional Policy contributing to sustainable growth in Europe ; ISBN: 978-92-79-20333-6;
848 doi:10.2776/39448 published by European Commission, Directorate-General for Regional Policy
- 849 Edwards, M., 2006. Product engineering: some challenges for chemical engineering. *Chemical Engineering.*
850 *Research and Design, TranslChem* 84, 255–260.
- 851 Faust, K., Raes, J., 2012. Microbial interactions: from networks to models. *Nat Rev Microbiol.* 10, 538–550.
852 doi:10.1038/nrmicro2832

- 853 Fengqi You, F., Tao, L., Graziano, D., Snyder, S., 2012. Optimal design of sustainable cellulosic biofuel supply
854 chains: Multiobjective optimization coupled with life cycle assessment and inputoutput analysis. *AIChE Journal*
855 58(4), 1157–1180.
- 856 Fuentes, R. E., 1993. Scientific research and sustainable development. *Ecol. Appl.* 3, 576–577.
- 857 Giovannini, A., Aubry, A., Panetto, A., Dassisti, M., Haouzi, H., 2012. Ontology-based system for
858 supporting manufacturing sustainability. *Annual Reviews in Control* 36, 309317.
- 859 Grossmanna, I., Guilln-Goslbez, G., 2010. Scope for the application of mathematical programming techniques in
860 the synthesis and planning of sustainable processes. *Computers and Chemical Engineering* 34, 13651376.
- 861 Gunderson, L., Holling, C. S., 2002. *Panarchy : understanding transformations in human and natural systems.*
862 Island Press, Washington, D.C., USA.
- 863 Gupta, S., Palsule-Desai, O., 2011. Sustainable supply chain management: Review and research opportunities.
864 *IIMB Management Review* 23, 234–245.
- 865 Hassini, E., Surti, C., Searcy, C., 2012. A literature review and a case study of sustainable supply chains with a
866 focus on metrics. *Int. J. Production Economics* 140, 69–82.
- 867 Helbing, D., 2010a Pluralistic Modeling of Complex Systems CCSS-10-009,
868 <http://ssrn.com/abstract=1646314>.
- 869 Helbing, D., 2010b. *Quantitative Sociodynamics*, Springer Berlin Heidelberg.
- 870 Helmsing, A.H.J., Vellema, S., 2011. Value Chains Governance and Inclusive Endogenous Development: Towards
871 a Knowledge Agenda. Development policy review network (DPRN), 2011.
- 872 Higgins, A., Miller, C. J., Archer, A., Ton, T., Fletcher, C., McAllister, R., 2010. Challenges of operations research
873 practice in agricultural value chains. *Journal of the Operational Research Society* 61, 964 –973.
- 874 Holling, C., 1973. Resilience and stability of ecological systems. *Annual Review of Ecology and Systematics* 4, 1–
875 24.
- 876 Holling, C. S., 2001. Understanding the complexity of economic, ecological, and social systems. *Ecosystems* 4,
877 390–405.
- 878 Kauffman, S., 1995. *At Home in the Universe, The Search for the Laws of Self-Organization and Complexity.*
879 Oxford University Press.
- 880 Lainez, J., Puigjaner, L., 2012. Prospective and perspective review in integrated supply chain modeling for the
881 chemical process industry. *Current Opinion in Chemical Engineering* 1, 430–445.
- 882 Lam, Heidi, 2008. A framework of interaction costs in information visualization. *Visualization and Computer*
883 *Graphics, IEEE Transactions on* 14.6, 1149-1156.
- 884 Landaud, S., Helinck, S., Bonnarne, P., 2008. *Applied Microbiology and Biotechnology* 77, 1191 (Jan, 2008).
- 885 Lehmann, R., Reiche, R., Schiefer, G., 2012. Future internet and the agri-food sector: State-of-the-art in
886 literature and research. *Computers and Electronics in Agriculture* 89, 158–174.

- 887 Liu, M., Bienfait, B., Sacher, O., Gasteiger, J., Siezen, R.J., Nauta, A., et al., (2014). Combining Chemoinformatics
888 with Bioinformatics: In Silico Prediction of Bacterial Flavor-Forming Pathways by a Chemical Systems Biology
889 Approach "Reverse Pathway Engineering." PLoS ONE, 9: e84769. doi:10.1371/journal.pone.0084769
- 890 Martin, S., 2004. The cost of restoration as a way of defining resilience: a viability approach applied to a model
891 of lake eutrophication. Ecology and Society 9 (2). URL <http://www.ecologyandsociety.org/vol9/iss2/art8>.
- 892 Martin, S., Deffuant, G., Calabrese, J., Gilbert, N., 2011. Defining resilience mathematically: from attractors to
893 viability. Understanding complex systems. Springer. URL <http://cemadoc.cemagref.fr/cemoa/PUB00033173>.
- 894 Martinet, V., Doyen, L., 2007. Sustainability of an economy with an exhaustible resource: A viable control
895 approach. Resour. Energy Econ. 29 (1), 17–39.
- 896 Martinet, V., Thebaut, O., Doyen, L., 2007. Defining viable recovery paths toward sustainable fisheries. Ecol.
897 Econ. 62 (2), 411–422.
- 898 Matser, A., Quataert M., Hamoen R., de Vries HSM, 2010. Decision Support System. New Food, Issue 5, P. 65 –
899 69
- 900 Melnik, R., 2009. Coupling control and human factors in mathematical models of complex systems. Engineering
901 Applications of Artificial Intelligence 22, 351–362.
- 902 Meulen, B., 2013. The structure of european food law. Laws 2, 69–98. 2.
- 903 Mesmoudi, S., Perrot, N., Reuillon, R., Bourguine, P., Lutton, E., 2010. Optimal viable path search for a cheese
904 ripening process using a multi-objective ea. (2010). ICEC 2010. International conference on evolutionary
905 computation. 24-26 October Valencia (Spain).
- 906 Mesmoudi, S., Alvarez, I., Martin, S., Reuillon, R., Sicard, M., Perrot, N., 2014. Coupling geometric analysis and
907 viability theory for system exploration: Application to a living food system. Journal of Process Control, 24, 18-
908 28.
- 909 Miettinen, K., Sayin, S., 2013. Special issue: 21st international conference on multiple criteria decision making;
910 articles on multiobjective optimization. Journal of Global Optimization 57 (2), 279–280. URL
911 <http://dx.doi.org/10.1007/s10898-013-0041-6>.
- 912 Miles, R., Snow, C., 2007. Organization theory and supply chain management: An evolving research perspective.
913 Journal of Operations Management 25, 459–463.
- 914 Miller, K., Charles, A., Barange, M., Brander, K., Gallucci, V., Gasalla, M., Khan, A., Munro, G., Murtugudde, R.,
915 Ommerj, R., Perry, R., 2010. Climate change, uncertainty, and resilient fisheries: Institutional responses through
916 integrative science. Progress in Oceanography 57, 338–346.
- 917 Mounier, J., Monnet, C., Vallaëys, T., Arditi, R., Sarthou, A-S., Helias, A. et al. (2008). Microbial Interactions
918 within a Cheese Microbial Community. Appl Environ Microbiol. 74: 172–181. doi:10.1128/AEM.01338-07.
- 919 Mouzé-Amady, M., Raufaste, E., Prade, H., & Meyer, J.P. (2013). Fuzzy-TLX: using fuzzy integrals for evaluating
920 human mental workload with NASA-Task Load index in laboratory and field studies. *Ergonomics*, 56 (5), 752-
921 763.
- 922 Neubert, M., Caswell, H., 1997. Alternatives to resilience for measuring the responses of ecological systems to
923 perturbations. Ecology 78 (3), 653–665.

- 924 Nikolopoulou, A., Ierapetritou, M., 2012. Optimal design of sustainable chemical processes and supply chains:
925 A review. *Computers and Chemical Engineering* 44, 94–103.
- 926 Olivier, N., Luengo-Oroz, M., Duloquin, L., Faure, E., Savy, T., Veilleux, I., e. a., 2010. Cell lineage reconstruction
927 of early zebrafish embryos using label-free nonlinear microscopy. *Science* 329, 967–971.
- 928 Pavone, M., Coello Coello, C. A., 2012. Optimization on complex systems. *Memetic Computing*, 1–2.
- 929 Perrot, N. (2006). Fuzzy concepts applied to food product quality control. Editorial. *Fuzzy Sets and Systems*,
930 157, 1143–1144.
- 931 Perrot, N., Trelea, I. C., Baudrit, C., Trystram, G., Bourguine, P., 2011. Modelling and analysis of complex food
932 systems: State of the art and new trends. *Trends in Food Science & Technology* 22 (6), 304–314.
- 933 Pimm, S., 1984. The complexity and stability of ecosystems. *Nature* 327, 321–326.
- 934 Pimm, S., Lawton, J., 1977. Number of trophic levels in ecological communities. *Nature* 268, 329–331.
- 935 Porter, M.E., 2000. Location, competition, and economic development: Local clusters in a global economy.
936 *Economic development quarterly*, 14, 15–34.
- 937 Rawles, 1999, *A theory of justice*. Belknap press, Cambridge Massachusetts.
- 938 Reilly, M., Willenbockel, D., 2010. Managing uncertainty: a review of food system scenario analysis and
939 modelling. *Philosophical transactions of the royal society* 365, 3049–3063.
- 940 Sebag, M., 2014. *A tour of Machine learning: an AI perspective*. AI communications, IOS Press, 27(1), 11–23.
- 941 Sicard, M., Baudrit, C., Leclerc-Perlat, M.N., Wuillemin, P.H., Perrot, N., 2011. Expert knowledge integration to
942 model complex food processes. Application on the camembert cheese ripening process. *Expert Systems with*
943 *Applications*, 38(9), 11804–11812.
- 944 Sicard, M., Perrot, N., Reuillon, R., Mesmoudi, S., Alvarez, I., Martin, S. 2012. A viability approach to control
945 food processes: Application to a Camembert cheese ripening process. *Food Control*, 23, 312–319.
- 946 Stoutemyer, D. R., 2013, Can the Eureka Symbolic Regression Program, Computer Algebra, and Numerical
947 Analysis Help Each Other? *Notices of the AMS* (60), 713–724.
- 948 Suppes, P., 2002. *Representation and Invariance of Scientific Structures*, University of Chicago publications.
- 949 Surana, A., Kumara, S., Greaves, M., Nandini, C., Raghavan, U., 2013. Supply-chain networks: a complex
950 adaptive systems perspective. *International Journal of Production Research* 43(20), 4235–4265.
- 951 Takagi, H., 2008. New topics from recent interactive evolutionary computation researches. In: *Knowledge-*
952 *Based Intelligent Information and Engineering Systems*. p. 14.
- 953 Thompson, J., Scoones, I., 2009. Addressing the dynamics of agri-food systems: an emerging agenda for social
954 science research. *Environmental science & policy* 12, 386–397.
- 955 Tonda, A., Spritzer, A., and Lutton, E., 2014. Balancing User Interaction and Control in BNSL. In *Artificial*
956 *Evolution* (pp. 211–223). Springer International Publishing.
- 957 Trystram, G., 2012. Modelling of food and food processes. *Journal of Food Engineering* 110, 269277.

- 958 Uzzi, B., 1996. The sources and consequences of embeddedness for the economic performance of
959 organizations: The network effect. *American sociological review*, 674-698.
- 960 Van Collier, L., 1997. Automated techniques for the qualitative analysis of ecological models : Continuous
961 models. *Conservation Ecology* 1 (1), 5.
- 962 Van Mil, H.G.J. , Foegeding, A.E. , Windhab, E.J. , Perrot, N., Van der Linden, E. (2014). A complex system
963 approach to address world challenges in food and agriculture. *Trends in Food Science and Technology*, 40 (1),
964 20-32.
- 965 Walker, B., Gunderson, L., Kinzig, A., Folke, K., Carpenter, S., Schultz, L., 2006. A handful of heuristics and some
966 propositions for understanding resilience in social-ecological systems. *Ecology and Society* 11, 1–13.
- 967 Wei, W., Alvarez, I., Martin, S., 2013. Sustainability analysis: Viability concepts to consider transient and
968 asymptotical dynamics in socio-ecological tourism-based systems. *Ecological Modelling* 251, 103–113.
- 969 Wodke, J.A.H, Alibés, A., Cozzuto, L., Hermoso, A., Yus, E., Lluch-Senar, M., et al., 2015. MyMpn: a database for
970 the systems biology model organism *Mycoplasma pneumoniae*. *Nucleic Acids Res.* 2015;43: D618–D623.
971 doi:10.1093/nar/gku1105
- 972 Zwart, Sjoerd D., Ibo van de Poel, Harald van Mil, and Michiel Brumsen. 2006. A Network Approach for
973 Distinguishing Ethical Issues in Research and Development. *Science and Engineering Ethics* 12 (4):663-684.

974

975 **Figure captions**

976

977 Figure 1: Complex system approach inspired from the CS roadmap 2012-2020

978 Figure 2: A viability kernel recalculated for the cheese ripening application described in (Sicard *et al.*,
979 2012) (Mesmoudi *et al.*, 2014). The First 8 days of the 12-days viability tube of the ripening process of
980 Camembert Cheese are represented. The color shows the robustness (square distance to the
981 boundary of the viability day-section) with blue points less robust than red ones. The target in black
982 is reached in 12 days but at day 8 some robust states are already in the target.

983 Figure 3: Integrated assessment and policy-development process indicating key ingredients, flows,
984 and interactions between analytical and participatory components of the process. Inspired and
985 redrawn from Miller *et al.*, 2010

986 Figure 4: Length scales in the manufacture and supply structured products.

987 Figure 5: Example of Functional classification of the metatranscriptome during surface-ripened
988 cheese maturation (from Dugat-Bony *et al.*, In press).

989

Table caption

Table 1: A synthesis of methodologies and computing tools, already available or in development, for sustainable food systems. For each point, we provide examples taken from subsection 4.3, as this case study addresses issues spanning all the considered elements.

Table 1

		Partly realized	Reachable	To achieve
Step 1: Systemic analysis, or 'painting the picture'	Description	Description of concepts and factual information.	Gathering human and expert knowledge. This step is sometimes performed, but there is no generic methodology yet.	Linking knowledge from different sources.
	Computing paradigms	Ontologies and conceptual graphs, mathematical descriptions mediated by cognitive science approaches (Sicard et al., 2011)	Fuzzy logic (Perrot, 2006), qualitative physics (Bousson et al., 2000), mathematical graphs (Baudrit, Willemin & Perrot, 2013), cognitive science. Concepts from cognitive science, however, are not easy to link to mathematical concepts (Mouzé-Amady, Raufaste, Prade & Meyer, 2013)	Intelligent systems, able to treat different sources of information into a homogeneous framework.

Step 2: reconstructing different scales in a mathematical frame	Description	Characterization of separate elements, at different levels of detail and complexity.	Linking separate elements into a systemic approach. Inter-cluster operations and dynamics are sometimes already described, but usually the focus is one part, while the rest of the system is treated as constraints.	A multi-scale approach is needed (cf. chapter 2.2). Too many variables may hinder a consistent model showing emergent properties of the entire system. The difficulty is to select the right scales bringing a good representation of the whole. Managing uncertainty is fundamental.
	Computing paradigms	Depending on the case study and the available data: differential equations, neural networks, fuzzy logic, ...	Model coupling, Bayesian networks, probabilistic approaches (Sicard et al., 2011). However, these techniques are rarely connected and used in conjunction with each other, even	Complex system science, coupling stochastic (roadmap) and deterministic approaches, individual-based models, interactive learning. These techniques have

			when the final application could benefit from such an integration (see Perrot et al., 2011, Van der Linden et al., 2014)	been already successfully applied, but not in the food science domain (see Van Mil et al., 2014)(Sebag, 2014)
	Example (from 4.3)	Description of separate food chains and characteristics of products. Some regional clusters are described in detail regarding actors and the competitive force (Porter, 2000)	Valorize not only the grapes for wine, but also all remaining plant parts, for non-food applications, energy, etc.	The translation of consumer demands to the various scales, namely interaction between actors, characteristics of products, functionality of ingredients.
Step 3: uncovering emerging properties	Description	Knowledge engineering approaches allow having factual information about emerging properties of a system under study.	Human and expert knowledge approaches may allow to get explicit and implicit knowledge.	Consistent interpretation of the different knowledge sources and their 'real' contributions to emergent properties in a multi-dimensional

				landscape.
	Computing paradigms	Visualization techniques (Boukhelifa et al. 2013), especially interactive ones, can be efficiently used to uncover emerging trends.	Interactive learning (Tonda et al., 2014), interactions between machine learning systems and human experts (Sebag, 2014). These approaches still exist as prototypes, and are mainly used in research.	Existing interactive approaches cannot still overcome user fatigue (Lem, 2008); machine learning, despite recent improvements, cannot automatically detect all emerging trends.
	Example (from 4.3)	Once a model of a regional cluster is prepared, it is executed, and the results of the in-silico experiments are analyzed for emerging properties.	Working with experts of each company inside a cluster, trying to encode the implicit knowledge they possess about the network into explicit knowledge.	Build a homogeneous framework of expert knowledge, encompassing all aspects of a regional cluster.

<p>Step 4: system optimization and resilience</p>	<p>Description</p>	<p>The various actors could be easily identified including their decisive power at all scales and their constraints and decision criteria. Formalization of their constraints and choices is possible.</p>	<p>The necessity is to learn from a large benchmark of simulations in interaction with the experts. The expression of the mathematical function to optimize, the tuning of the algorithms are not trivial (Sebag, 2014).</p>	<p>The value of optimization may be rather complicated to establish, because the appropriate definition of the highly complex and diverse environmental context would require taking into account feedback and feedforward effects. In practice, these factors cannot yet be practically implemented, as the non-linearity of the system increases.</p>
--	---------------------------	--	--	---

	Computing paradigms	Evolutionary computation, memetic algorithms, viability theory.	For all optimization methods, computation is very heavy: the target models are stochastic in nature, and several repetitions are needed to obtain reliable results. This issue can be addressed by clusters, grids and computing clouds; as well as by surrogate functions (computationally lighter).	Another way to optimize is to be able to cluster the search space, using formalized expertise and interactive optimization; these techniques might solve some of the issues, but research in the field is still far from producing tools that are usable out-of-the-box. See (Lam, 2008) for a discussion on the costs of human-machine interaction.
	Example (from 4.3)	Regional clusters with a long history could be analysed in terms of repetitive actions taken to optimize a local cluster.	Example: resilience of the systems may be well tested in real life as a consequence of decisive actions, e.g. improved international sales, faster adaptation	Example: optimizing logistics of a whole network of regional clusters, taking into account their reciprocal interaction, and

			to external changes by enterprises, ...	their influence on the environment and other existing structures.
--	--	--	--	--

ACCEPTED MANUSCRIPT

Figure 1

Figure 2

Comment citer ce document :

Perrot, N., De Vries, H., Lutton, E., van Mil, H. G. J., Donner, M., Tonda, A., Martin, S., Alvarez, I., Bourguin, P., van der Linden, E., Axelos, M. (2016). Some remarks on computational approaches towards sustainable complex agri-food systems. Trends in Food Science and Technology, 48, 88-101. DOI : 10.1016/j.tifs.2015.10.003

Figure 3

Figure 4

ACCEPTED MANUSCRIPT

Figure 5

Highlights :

The agri-food sector is one of the most important sectors of the industry

Dealing with sustainability issues in this sector, is a enormous and difficult challenge.

Here lies a huge opportunity at the frontier of agri-food and computing science.

New mathematical tools are proposed to address sustainability of food systems.

Key examples are developed.

ACCEPTED MANUSCRIPT

Comment citer ce document :

Perrot, N., De Vries, H., Lutton, E., van Mil, H. G. J., Donner, M., Tonda, A., Martin, S., Alvarez, I., Bourguin, P., van der Linden, E., Axelos, M. (2016). Some remarks on computational approaches towards sustainable complex agri-food systems. Trends in Food Science and Technology, 48, 88-101. DOI : 10.1016/j.tifs.2015.10.003