Frequency Limited H_∞ -Controller Order Reduction for Linear Parameter Varying Systems

Hossni Zebiri, Benjamin Mourllion, Michel Basset

► To cite this version:

Hossni Zebiri, Benjamin Mourllion, Michel Basset. Frequency Limited H_∞ -Controller Order Reduction for Linear Parameter Varying Systems . International journal of control 0020-7179, 2016, 10.1080/00207179.2016.1233482 . hal-01510688

HAL Id: hal-01510688

<https://hal.science/hal-01510688>

Submitted on 19 Apr 2017

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Frequency Limited H^∞ -Controller Order Reduction for Linear Parameter Varying Systems

Hossni Zebiri, Benjamin Mourllion & Michel Basset

To cite this article: Hossni Zebiri, Benjamin Mourllion & Michel Basset (2016): Frequency Limited H^∞ -Controller Order Reduction for Linear Parameter Varying Systems, International Journal of Control

To link to this article: <http://dx.doi.org/10.1080/00207179.2016.1233482>

View supplementary material [↗](#)

Accepted author version posted online: 13 Sep 2016.
Published online: 13 Sep 2016.

Submit your article to this journal [↗](#)

View related articles [↗](#)

View Crossmark data [↗](#)

To appear in the *International Journal of Control*
Vol. 00, No. 00, Month 20XX, 1–30

Publisher: Taylor & Francis

Journal: *International Journal of Control*

DOI: <http://dx.doi.org/10.1080/00207179.2016.1233482>

Frequency Limited $\mathcal{H}_\infty$ -Controller Order Reduction for Linear Parameter Varying Systems.

Hossni Zebiri, Benjamin Mourllion and Michel Basset

*Laboratoire Modélisation, Intelligence, Processus et Systèmes MIPS EA2332 Université de Haute-Alsace,
12, rue des frères Lumière, F-68093 Mulhouse Cedex, France* surname.name at uha.fr

(Received 00 Month 20XX; accepted 00 Month 20XX)

In this paper, a controller order-reduction method for linear parameter varying systems is presented. The proposed method is based on the frequency weighted balanced truncation technique, which has the advantage to reduce the order in a specific frequency range. The approach is discussed and is proved to preserve the closed-loop stability with a guaranteed upper error bound. Effectiveness and performance of the obtained reduced-order controller, are investigated by applying it to an automotive semi-active suspension control. The obtained simulation results show that objectives such as the road handling and the passenger comfort realised with the reduced-order controller are kept in the same performance level as with the full order controller. Moreover, a comparison with an other order reduction method is shown and confirms the advantage of the developed method.

Keywords: linear parameter varying system, $\mathcal{H}_\infty$ -control, generalised reachability and observability Gramians, balanced truncation, semi-active suspension control.

Notations

$\mathbb{R}$	: fields of real numbers
$\prec (\preceq), \succ (\succeq)$	: negative (semi-negative), positive (semi-positive) definite
$\mathbb{S}_{>0}^n$	: cone of $n \times n$ symmetric positive definite matrices
$\mathcal{R}, \mathcal{O}$	: reachability and observability Gramians
$P(\rho), Q(\rho)$	: generalised reachability and observability Gramians
$\mathbf{P}_\Omega(\rho), \mathbf{Q}_\Omega(\rho)$	: frequency limited generalised reachability and observability Gramians
σ_i	: i th generalised Hankel singular value
γ_i	: i th frequency limited generalised Hankel singular value
S^*	: complex conjugate transpose of S
$A^{-\top}$	: $(A^{-1})^\top = (A^\top)^{-1}$
I_n	: $n \times n$ identity matrix

1. Introduction

Most of physical systems are inherently non-linear and almost all of them have parameter dependent representations. Considering those aspects and the advantages of linear control theory, more and more control strategies use Linear Parameter Varying (LPV) models. In the same way, and as operating conditions may change, the closed-loop performance designed by an LTI controller may be degraded. To overcome this problem, the design of parameter dependent controller is more suitable. Consequently, a major part of the recently developed control strategies is based on optimal and/or robust control. The $\mathcal{H}_\infty$ -control strategies have the advantage to design controllers

achieving stabilisation with guaranteed performance. However, these techniques usually produce high order controllers. The design and the use of such high-order controllers can lead to numerical difficulties. This is why their use is still limited in the engineering field. Thus, for these practical reasons, low-order controllers are particularly preferred: their simple dynamics are easier to manage, they require less computing cost and simpler software can be finally implemented. Then, an order reduction step appears of great interest. Simultaneously, the reduction process should always preserve the closed-loop stability and should guarantee a level of performance close to the one obtained with the full-order controller. In a general way, a low-order controller can be obtained through the direct method or the indirect ones (see Figure 1). Considering the direct method, the final low-order controller is obtained directly from the high-order plant and the order is generally fixed beforehand [AHH11, AG95].

In the indirect ways, the low-order controller is the result of a model or a controller order reduction step: either a reduced-order plant is found and then a controller is designed or a high-order controller is first designed and then a controller order reduction step is performed. The last method is widely used to obtain reduced-order controllers [Kon12, God95]. For LTI systems, a large investigation has been made on model order reduction procedures. In this domain, methods based on balanced realisation are extensively used [GA04]. First introduced by [MR76] and later in the systems and control literature by [Moo81], the balanced truncation has been a significant contribution to system theory. In [PS82], the stability of the reduced-order model is preserved. Then, [Glo84] has proposed an $\mathcal{H}_\infty$ -norm upper bound of the approximation error.

Based on this, BT method has been proposed to reduce the order of controllers for LTI systems [LA89, ZDC95]. The extension of these reduction techniques to LPV-systems is still in progress. Generally, these methods substitute the use of LTI Gramians by using parameter/time varying equivalents [SR04, WGG96]. A generalised method with unbounded rate parameter model is given in [EZJ98]. In the same way, an effective BT method for $\mathcal{H}_\infty$ -LPV-controller order reduction is proposed in [WRS04].

The balanced truncation produces good approximations in high frequency, whereas for control propose, an acceptable reduction is often required at intermediate and/or low frequencies. To solve this problem, the so-called Frequency Weighted Balancing Truncation FWBT has been proposed firstly for LTI systems in [Enn84]. In this approach, two weighting functions are included in the procedure to reduce the model in a certain frequency range. However, the stability preservation is not guaranteed anymore. To tackle this problem, a modified version assuming that the full-order model does not have any common pole zero with the weighting functions is proposed in [LC90]. Then, [WSL99, VA01] have developed a new approach based on the Enns method without the previous assumption to guarantee the stability. It gives also an upper error bound. Others upper bounds have also been established by [SA95], [KAM95] and [Zho95]. The frequency range is explicitly defined instead of the two frequency weights in [GJ90]. More recently, in [GA04], the method is modified and an error upper bound to the relative error is given. Note that the stated techniques are developed for the stable LTI-systems and no guarantee is given to preserve the passivity of the systems. Recent work in this direction are given in [LYG14, LYG15] where the $\mathcal{H}_\infty$ -norm of the error is bounded and the positive realness of the obtained model is guaranteed.

Based on these recent results in the literature, the aim of this paper is to adapt the FWBT method ([GA04]) in order to reduce the order of an $\mathcal{H}_\infty$ -LPV controller. For the development of this approach, the generalised Gramian framework is used [SW11].

The paper is organised as follows: the LPV-systems, their properties and the the full-order $\mathcal{H}_\infty$ -LPV-controller design are introduced in section 2. In Section 3. the Generalised Gramian framework for LPV-systems is given and the main proposed method is detailed and discussed. To emphasize the effectiveness of the developed method, the obtained reduced-order controller is evaluated on a practical engineering problem: the control of an automotive semi-active suspension. The performance of the obtained reduced-order controller are investigated and compared with another reduced-order method based on BT approach [WRB06] in Section 4. Final conclusion is

given in Section 5.

2. Problem Statement

2.1 LPV-Systems

Linear Parameter Varying LPV models represent systems whose state-space descriptions are known functions of varying parameters. This notion of LPV-system has been introduced in context of gain scheduling [SA90] and has been also widely used in control design for non-linear systems [PK96]. Considering a compact subset $\Delta_\rho \subset \mathbb{R}^s$, an LPV-system can be described by the following the state-space realisation

$$\begin{cases} \dot{x}(t) = A(\rho(t))x(t) + B(\rho(t))u(t) \\ y(t) = C(\rho(t))x(t) + D(\rho(t))u(t) \end{cases} \quad \forall t \geq 0 \quad (1)$$

where $A: \Delta_\rho \rightarrow \mathbb{R}^{n \times n}$, $B: \Delta_\rho \rightarrow \mathbb{R}^{n \times m}$, $C: \Delta_\rho \rightarrow \mathbb{R}^{p \times n}$, $D: \Delta_\rho \rightarrow \mathbb{R}^{p \times m}$. The state-space representation (1) can be also written as

$$G(\rho) = \left[\begin{array}{c|c} A(\rho) & B(\rho) \\ \hline C(\rho) & D(\rho) \end{array} \right]. \quad (2)$$

The exogenous parameter vector ρ is varying in a bounded set $\mathcal{P}_\rho$ defined as

$$\mathcal{P}_\rho = \{ \rho: \begin{array}{ccc} \mathbb{R}^+ & \rightarrow & \Delta_\rho \\ t & \mapsto & \rho(t) \end{array} \mid \underline{\rho}_i(t) \leq \rho_i(t) \leq \bar{\rho}_i(t), i = 1, 2, \dots, s \} \quad (3)$$

where ρ_i is the i th component of the ρ vector.

The ρ function is not known in advance but is assumed to be bounded and measurable on-line. This assumption ensures that all trajectories of the system are contained in those ones of the LPV-model.

It is noted that some LPV-models could be written as function of system states [OPJ13]. Such models known as *quasi-LPV*-systems are used for the modelling of non-linear systems.

Definition 1 (Quadratic Stability): System (1) is said to be quadratically stable if the positive definite quadratic form

$$V_\rho: x \mapsto x^\top P_0 x, \quad P_0 \in \mathbb{S}_{>0}^n \quad (4)$$

is a Lyapunov function for (1). A such Lyapunov function is often referred to a common Lyapunov function or a parameter-independent Lyapunov function.

Proposition 1 ([Bri15]): *The system (1) is quadratically stable if and only if there exists a matrix $P \in \mathbb{S}_{>0}^n$ such that the LMI*

$$A^\top(\rho)P + PA(\rho) \prec 0 \quad (5)$$

holds for all $\rho \in \Delta_\rho$.

Moreover, the induced $\mathcal{L}_2$ -gain notion is of a big interest for the proposed approach. Indeed, an upper bound is given to the $\mathcal{L}_2$ -norm of error between the full and the reduced order models. It can be defined as

Definition 2 (Induced $\mathcal{L}_2$ -gain [God95]): Given a quadratic-stable LPV-system (1) with zero initial conditions, the induced $\mathcal{L}_2$ -gain is defined as

$$\|G_\rho\|_{i,2} = \sup_{\rho \in \mathcal{P}_\rho} \sup_{\substack{u \in \mathcal{L}_2 \\ u \neq 0}} \frac{\|y\|_2}{\|u\|_2} \quad (6)$$

The induced $\mathcal{L}_2$ -norm represents the largest induced gain from inputs in $\mathcal{L}_2$ to outputs in $\mathcal{L}_2$ over the set of all causal linear operators described by the LPV system.

2.2 LPV-Controller Synthesis

Consider a general LPV-system represented under the following state-space realisation

$$\begin{cases} \dot{x}(t) &= A(\rho(t))x(t) + B_1(\rho(t))w(t) + B_2(\rho(t))u(t) \\ z(t) &= C_1(\rho(t))x(t) + D_{11}(\rho(t))w(t) + D_{12}(\rho(t))u(t) \\ y(t) &= C_2(\rho(t))x(t) + D_{21}(\rho(t))w(t) + D_{22}(\rho(t))u(t) \end{cases} \quad \forall t. \quad (7)$$

where $x(t) \in \mathbb{R}^n$, $u(t) \in \mathbb{R}^{n_u}$, $w(t) \in \mathbb{R}^{n_w}$, $z(t) \in \mathbb{R}^{n_z}$, $y(t) \in \mathbb{R}^{n_y}$ are respectively the state, the input, the disturbance, the controlled output and the measured output. Then, $A: \Delta_\rho \rightarrow \mathbb{R}^{n \times n}$, $B_1: \Delta_\rho \rightarrow \mathbb{R}^{n \times n_w}$, $B_2: \Delta_\rho \rightarrow \mathbb{R}^{n \times n_u}$, $C_1: \Delta_\rho \rightarrow \mathbb{R}^{n_z \times n}$, $C_2: \Delta_\rho \rightarrow \mathbb{R}^{n_y \times n}$, $D_{11}: \Delta_\rho \rightarrow \mathbb{R}^{n_z \times n_w}$, $D_{12}: \Delta_\rho \rightarrow \mathbb{R}^{n_z \times n_u}$, $D_{21}: \Delta_\rho \rightarrow \mathbb{R}^{n_y \times n_w}$ and $D_{22}: \Delta_\rho \rightarrow \mathbb{R}^{n_y \times n_u}$.

The $\mathcal{H}_\infty$ -LPV-controller associated to the LPV-system (7) is defined by

$$K(\rho): \begin{cases} \dot{x}_K(t) &= A_K(\rho(t))x_K(t) + B_K(\rho(t))y(t) \\ u(t) &= C_K(\rho(t))x_K(t) + D_K(\rho(t))y(t) \end{cases} \quad (8)$$

where $x_K \in \mathbb{R}^{n_K}$, $y(t) \in \mathbb{R}^{n_y}$ and $u(t) \in \mathbb{R}^{n_u}$ are respectively the states, the inputs and outputs of the controller $K(\rho)$. $A_K: \Delta_\rho \rightarrow \mathbb{R}^{n_K \times n_K}$, $B_K: \Delta_\rho \rightarrow \mathbb{R}^{n_K \times n_y}$, $C_K: \Delta_\rho \rightarrow \mathbb{R}^{n_u \times n_K}$ and $D_K: \Delta_\rho \rightarrow \mathbb{R}^{n_u \times n_y}$.

The $\mathcal{H}_\infty$ -LPV-controller synthesis concerns the design of an LPV global controller that guarantees both *stability* and *performance* for all parameters variations defined in the set Δ_ρ . To guarantee the closed-loop system quadratic stability and to satisfy the $\mathcal{H}_\infty$ -performance criteria, the approach developed in [SGC97] is used to design the $\mathcal{H}_\infty$ -LPV-controller. It is assumed that

- The matrices B_2, D_{12}, C_2 and D_{21} are parameter independent and $D_{22} = 0$.
- The parameter-dependent matrix pair $[A(\rho), B_2(\rho)]$ is stabilisable and detectable $\forall \rho \in \Delta_\rho$.
- The matrix $[C_2(\rho), D_{21}(\rho)]$ has full row rank $\forall \rho \in \Delta_\rho$.

Then, for a given real positive scalar γ and a parameter dependent quadruplet matrices $(\hat{A}_K, \hat{B}_K, \hat{C}_K, \hat{D}_K)$, there exist two parameter independent symmetric matrices X and Y such that the sufficient condition that solves the $\mathcal{H}_\infty$ -LPV problem is given by the following LMIs $\forall \rho \in \Delta_\rho$

$$\begin{bmatrix} A(\rho)X + B_2\hat{C}_K(\rho) + (*) & * & * & * \\ \hat{A}_K(\rho) + A^\top(\rho) + C_2^\top\hat{D}_K^\top(\rho)B_2^\top & Y A(\rho) + \hat{B}_K(\rho)C_2 + (*) & * & * \\ B_1^\top(\rho) + D_{21}^\top\hat{D}_K^\top(\rho)B_2^\top & B_1^\top(\rho)Y + D_{21}^\top\hat{B}_K^\top(\rho) & -\gamma I_{n_w} & * \\ C_1(\rho)X + D_{12}\hat{C}_K(\rho) & C_1(\rho) + D_{12}\hat{D}_K(\rho)C_2 & D_{11}(\rho) + D_{12}\hat{D}_K(\rho)C_2 & -\gamma I_{n_z} \end{bmatrix} \prec 0, \quad (9)$$

$$\begin{bmatrix} X & I_n \\ I_n & Y \end{bmatrix} \succ 0, \quad (10)$$

where terms denoted $(*)$ are induced by symmetry, for example

$$\begin{bmatrix} M + N + (*) & * \\ K & L \end{bmatrix} = \begin{bmatrix} M + N + M^\top + N^\top & K^\top \\ K & L \end{bmatrix}$$

The LPV-controller of the form (8) is then reconstructed as

$$\begin{aligned} D_K(\rho) &= \hat{D}_K(\rho) \\ C_K(\rho) &= (\hat{C}_K(\rho) - D_K(\rho)C_2X)M^{-\top} \\ B_K(\rho) &= N^{-1}(\hat{B}_K(\rho) - YB_2D_K(\rho)) \\ A_K(\rho) &= N^{-1}(\hat{A}_K(\rho) - YA(\rho)X - YB_2D_K(\rho)C_2X)M^{-\top} - B_K(\rho)C_2XM^{-\top} - N^{-1}YB_2C_K(\rho), \end{aligned} \quad (11)$$

where M and N are defined such that $MN^\top = I_n - XY$ and which can be solved through a singular value decomposition and a Cholesky factorisation.

2.3 Full-Order Controller Design

Before introducing the approximation method, the full-order controller should be designed as shown in Section 2.2. Then, let

$$T_{zw}(\rho) = \left[\frac{\mathbf{A}(\rho) \mid \mathbf{B}(\rho)}{\mathbf{C}(\rho) \mid \mathbf{D}(\rho)} \right] = \text{LFT} \left(\left[\frac{A(\rho) \mid B(\rho)}{C(\rho) \mid D(\rho)} \right], \left[\frac{A_K(\rho) \mid B_K(\rho)}{C_K(\rho) \mid D_K(\rho)} \right] \right), \quad (12)$$

be the state-space realisation of the closed-loop system considering the augmented model (7) and its $\mathcal{H}_\infty$ -controller defined in (8) with:

$$\begin{aligned} \mathbf{A}(\rho) &= \begin{bmatrix} A(\rho) + B_2D_K(\rho)C_2 & B_2C_K(\rho) \\ B_K(\rho)C_2 & A_K(\rho) \end{bmatrix}, \quad \mathbf{B}(\rho) = \begin{bmatrix} B_1(\rho) + B_2D_K(\rho)D_{21} \\ B_K(\rho)D_{21} \end{bmatrix}, \\ \mathbf{C}(\rho) &= \begin{bmatrix} C_1(\rho) + D_{12}D_K(\rho)C_2 & D_{12}C_K(\rho) \end{bmatrix} \text{ and } \mathbf{D}(\rho) = D_{11}(\rho) + D_{12}D_K(\rho)D_{21}. \end{aligned}$$

Note that the closed-loop system $T_{zw}(\rho)$ is an LPV-system in its own right which is quadratic stable by construction. In order to apply the proposed method, the $T_{zw}(\rho)$ state space representation is assumed to be minimal.

3. Main Contribution

In this section, the new controller order reduction method for LPV-controllers is proposed. The method is based on the Frequency Weighted Balanced Truncation FWBT approach used for the LTI-models order reduction. The FWBT is proposed to reduce the model-order over a known frequency range $[\omega_1, \omega_2]$ in [GJ90]. This approach uses the classical reachability and observability Gramians.

Inspired by this work, the proposed method is an extension in two directions:

- Extended to the LPV-case.
- Applied to reduce the controller order (rather than the model order).

To this end, the classical reachability and observability Gramians for LTI systems are introduced first. Then, the equivalent ones of the LPV-case are defined. Based on this, the so-called generalised

Gramians are introduced then used to perform the proposed controller order reduction approach. The relation between the Gramians and generalised Gramians is given in Lemma 1.

3.1 Frequency Limited Generalised Gramians

The proposed method is based on the FWBT method where the key notions are the so-called *reachability and observability Gramians*.

Definition 3 (Gramians): Considering the quadratic stable and minimal realisation of the closed-loop LPV-system $T_{zw}(\rho)$ given in (12), Let us define $\mathcal{R}(\rho)$ and $\mathcal{O}(\rho)$, the related reachability and observability Gramians respectively, they are defined as the solution of the two parameter dependent Lyapunov equations

$$-\sum_{i=1}^s v_i \frac{\partial \mathcal{R}(\rho)}{\partial \rho_i} + \mathbf{A}(\rho)\mathcal{R}(\rho) + \mathcal{R}(\rho)\mathbf{A}^\top(\rho) + \mathbf{B}(\rho)\mathbf{B}^\top(\rho) = 0, \quad (13)$$

$$\sum_{i=1}^s v_i \frac{\partial \mathcal{O}(\rho)}{\partial \rho_i} + \mathbf{A}^\top(\rho)\mathcal{O}(\rho) + \mathcal{O}(\rho)\mathbf{A}(\rho) + \mathbf{C}^\top(\rho)\mathbf{C}(\rho) = 0. \quad (14)$$

For a given parameter trajectory ρ , let $\Phi_\rho(t, 0)$ be the state-transition matrix. Then, the functional $\mathcal{R}(\rho)$ and $\mathcal{O}(\rho)$, respectively the reachability and observability Gramians of the closed-loop LPV-system (12), are expressed such that

$$\mathcal{R}(\rho) = \int_{-\infty}^0 \Phi_\rho(0, t) \mathbf{B}(\rho(t)) \mathbf{B}^\top(\rho(t)) \Phi_\rho^\top(0, t) dt, \quad (15)$$

$$\mathcal{O}(\rho) = \int_0^\infty \Phi_\rho^\top(t, 0) \mathbf{C}^\top(\rho(t)) \mathbf{C}(\rho(t)) \Phi_\rho(t, 0) dt. \quad (16)$$

Definition 4 (Generalised Gramians): Let $\mathbf{P}(\rho)$ and $\mathbf{Q}(\rho)$ be respectively the *generalised* reachability and observability Gramians of the quadratic stable and minimal closed-loop LPV-system (12) given as

$$\forall(\rho, v) \in \Delta_\rho \times \Delta_v$$

$$-\sum_{i=1}^s v_i \frac{\partial \mathbf{P}(\rho)}{\partial \rho_i} + \mathbf{A}(\rho)\mathbf{P}(\rho) + \mathbf{P}(\rho)\mathbf{A}^\top(\rho) + \mathbf{B}(\rho)\mathbf{B}^\top(\rho) \prec 0 \quad (17)$$

$$\sum_{i=1}^s v_i \frac{\partial \mathbf{Q}(\rho)}{\partial \rho_i} + \mathbf{A}^\top(\rho)\mathbf{Q}(\rho) + \mathbf{Q}(\rho)\mathbf{A}(\rho) + \mathbf{C}^\top(\rho)\mathbf{C}(\rho) \prec 0. \quad (18)$$

Indeed, Lyapunov inequalities (rather than Lyapunov equations) are solved to compute generalised Gramians. This linear matrix inequality (LMI) approach to the model reduction problem is particularly useful when some structures need to be preserved in the process of model reduction. Controller reduction is a typical example of this type of problems[SW11]. Note that the physical interpretations of generalised Gramians are similar to ordinary Gramians. Considering $T_{zw}(\rho)$, $\mathcal{R}(\rho)$ and $\mathcal{O}(\rho)$, the following lemma introduces useful results about the relation between Gramians and generalised Gramians.

Lemma 1: Let $T_{zw}(\rho)$ be a minimal state-space realisation of the quadratic stable and minimal

closed-loop system defined by (12). Then, $\forall \rho \in \mathcal{P}_\rho$

$$\begin{aligned}\mathcal{R}(\rho) &\prec \mathbf{P}(\rho(0)) \\ \mathcal{O}(\rho) &\prec \mathbf{Q}(\rho(0)).\end{aligned}\tag{19}$$

where $\mathcal{R}(\rho)$, $\mathcal{O}(\rho)$, $\mathbf{P}(\rho)$ and $\mathbf{Q}(\rho)$ are the solutions of (15), (16), (17) and (18) respectively.

Proof: By multiplying on the left by $\Phi_\rho(0, t)$ and on the right by $\Phi_\rho^\top(0, t)$, the relation (17) yields

$$\begin{aligned}-\Phi_\rho(0, t) \sum_{i=1}^s v_i \frac{\partial \mathbf{P}}{\partial \rho_i} \Phi_\rho^\top(0, t) + \Phi_\rho(0, t) \mathbf{A}(\rho(t)) \mathbf{P}(\rho) \Phi_\rho^\top(0, t) &+ \Phi_\rho(0, t) \mathbf{P}(\rho) \mathbf{A}^\top(\rho(t)) \Phi_\rho^\top(0, t) \\ &+ \Phi_\rho(0, t) \mathbf{B}(\rho(t)) \mathbf{B}^\top(\rho(t)) \Phi_\rho^\top(0, t) \prec 0.\end{aligned}\tag{20}$$

Using fact that $\frac{\partial}{\partial t_0} \Phi_\rho(t, t_0) = -\Phi_\rho(t, t_0) \mathbf{A}(\rho(t_0))$, then (20) yields

$$-\frac{d}{dt} \left(\Phi_\rho(0, t) \mathbf{P}(\rho) \Phi_\rho^\top(0, t) \right) + \Phi_\rho(0, t) \mathbf{B}(\rho(t)) \mathbf{B}^\top(\rho(t)) \Phi_\rho^\top(0, t) \prec 0.\tag{21}$$

which on integrating over the semi-infinite time axis $(-\infty, 0]$ and considering that $\lim_{t \rightarrow -\infty} \Phi_\rho(0, t) = 0$, gives

$$\mathbf{P}(\rho(0)) \prec \underbrace{\int_{-\infty}^0 \Phi_\rho(0, t) \mathbf{B}(\rho(t)) \mathbf{B}^\top(\rho(t)) \Phi_\rho^\top(0, t) dt}_{\mathcal{R}(\rho)}\tag{22}$$

Similarly, let us multiply on the right by the closed-loop state-transition matrix $\Phi_\rho(t, 0)$ and on the left by $\Phi_\rho^\top(t, 0)$, the relation (18):

$$\begin{aligned}\Phi_\rho^\top(t, 0) \sum_{i=1}^s v_i \frac{\partial \mathbf{Q}}{\partial \rho_i} \Phi_\rho(t, 0) + \Phi_\rho^\top(t, 0) \mathbf{A}^\top(\rho(t)) \mathbf{Q}(\rho) \Phi_\rho(t, 0) &+ \Phi_\rho^\top(t, 0) \mathbf{Q}(\rho) \mathbf{A}(\rho(t)) \Phi_\rho(t, 0) \\ &+ \Phi_\rho^\top(t, 0) \mathbf{C}^\top(\rho(t)) \mathbf{C}(\rho(t)) \Phi_\rho(t, 0) \prec 0\end{aligned}\tag{23}$$

Using the fact that $\frac{\partial}{\partial t} \Phi_\rho(t, t_0) = \mathbf{A}(\rho(t)) \Phi_\rho(t, t_0)$, then (23) yields

$$\frac{d}{dt} \left(\Phi_\rho^\top(t, 0) \mathbf{Q}(\rho) \Phi_\rho(t, 0) \right) + \Phi_\rho^\top(t, 0) \mathbf{C}^\top(\rho(t)) \mathbf{C}(\rho(t)) \Phi_\rho(t, 0) \prec 0.\tag{24}$$

Integrating the last expression from 0 to $+\infty$ gives

$$\mathbf{Q}(\rho(0)) \prec \underbrace{\int_0^{+\infty} \Phi_\rho^\top(t, 0) \mathbf{C}^\top(\rho(t)) \mathbf{C}(\rho(t)) \Phi_\rho(t, 0) dt}_{\mathcal{O}(\rho)}\tag{25}$$

■

3.2 Frequency-Limited Order Reduction

For a given parameter trajectory ρ , let consider $\Phi_\rho(t, 0)$ the state-transition matrix of the closed-loop system (12). Then, let us define

$$\begin{aligned} f_\rho(t) &= \Phi_\rho(0, t) \mathbf{B}(\rho(t)) H(-t) \\ g_\rho(t) &= \mathbf{C}(\rho(t)) \Phi_\rho(t, 0) H(t) \end{aligned} \quad \forall t, \quad (26)$$

where H is the heaviside step function.

By considering $\Omega = [\omega_1 ; \omega_2]$ the frequency range where order-reduction is desired to be better, the following definition is given

Definition 5 (Frequency Limited Gramians): Let $\mathcal{R}_\Omega(\rho)$ and $\mathcal{O}_\Omega(\rho)$ two frequency dependent terms defined as

$$\mathcal{R}_\Omega(\rho) = \mathcal{R}_{\omega_2}(\rho) - \mathcal{R}_{\omega_1}(\rho) \quad \text{and} \quad \mathcal{O}_\Omega(\rho) = \mathcal{O}_{\omega_2}(\rho) - \mathcal{O}_{\omega_1}(\rho)$$

where

$$\mathcal{R}_\omega(\rho) = \int_{-\omega}^{+\omega} F_\rho(w) F_\rho^*(w) dw \quad (27)$$

$$\mathcal{O}_\omega(\rho) = \int_{-\omega}^{+\omega} G_\rho^*(w) G_\rho(w) dw \quad (28)$$

with F_ρ (resp. G_ρ) is the Fourier transform of f_ρ (resp. g_ρ). Then, the functional $\hat{\mathcal{R}}_\Omega(\rho)$ and $\hat{\mathcal{O}}_\Omega(\rho)$, respectively the *frequency limited* reachability and observability Gramians of the closed-loop LPV-system (12), are defined as the solutions of

$\forall(\rho, v) \in \Delta_\rho \times \Delta_v$

$$-\sum_{i=1}^s v_i \frac{\partial \hat{\mathcal{R}}_\Omega(\rho)}{\partial \rho_i} + \mathbf{A}(\rho) \hat{\mathcal{R}}_\Omega(\rho) + \hat{\mathcal{R}}_\Omega(\rho) \mathbf{A}^\top(\rho) + \mathcal{R}_\Omega(\rho) = 0 \quad (29)$$

$$\sum_{i=1}^s v_i \frac{\partial \hat{\mathcal{O}}_\Omega(\rho)}{\partial \rho_i} + \mathbf{A}^\top(\rho) \hat{\mathcal{O}}_\Omega(\rho) + \hat{\mathcal{O}}_\Omega(\rho) \mathbf{A}(\rho) + \mathcal{O}_\Omega(\rho) = 0. \quad (30)$$

The quantities $\mathcal{R}_\Omega(\rho)$ and $\mathcal{O}_\Omega(\rho)$ have the following eigenvalues decomposition

$$\mathcal{R}_\Omega(\rho) = U_\Omega(\rho) \text{diag}(\lambda_1(\rho), \dots, \lambda_{n_K}(\rho)) U_\Omega^\top(\rho) \quad (31)$$

$$\mathcal{O}_\Omega(\rho) = V_\Omega(\rho) \text{diag}(\delta_1(\rho), \dots, \delta_{n_K}(\rho)) V_\Omega^\top(\rho) \quad (32)$$

with $|\lambda_1| \geq \dots \geq |\lambda_{n_K}| \geq 0$ and $|\delta_1| \geq \dots \geq |\delta_{n_K}| \geq 0$. Let $u_\rho \leq n_K$ and $v_\rho \leq n_K$ be respectively the ranks of $\mathcal{R}_\Omega(\rho)$ and $\mathcal{O}_\Omega(\rho)$. Based on these definitions, let us define the two quantities:

$$\mathbf{B}_\Omega(\rho) = U_\Omega(\rho) \text{diag}(|\lambda_1(\rho)|^{\frac{1}{2}}, \dots, |\lambda_{u_\rho}(\rho)|^{\frac{1}{2}}, 0, \dots, 0), \text{ and} \quad (33)$$

$$\mathbf{C}_\Omega(\rho) = \text{diag}(|\delta_1(\rho)|^{\frac{1}{2}}, \dots, |\delta_{v_\rho}(\rho)|^{\frac{1}{2}}, 0, \dots, 0) V_\Omega^\top(\rho). \quad (34)$$

Definition 6 (Modified Frequency Limited Generalised Gramians): Consider $K(\rho)$, the full-order stabilising LPV-controller given in (8). Let $\hat{\mathbf{P}}_\Omega(\rho) = \begin{bmatrix} \hat{\mathbf{P}}_1(\rho) & 0 \\ 0 & \hat{\mathbf{P}}_2(\rho) \end{bmatrix} \succ 0$ and

$\hat{\mathbf{Q}}_{\Omega}(\rho) = \begin{bmatrix} \hat{\mathbf{Q}}_1(\rho) & 0 \\ 0 & \hat{\mathbf{Q}}_2(\rho) \end{bmatrix} \succ 0$ be the *modified frequency limited* reachability and observability Gramians defined as the solutions of the following Lyapunov equations
 $\forall(\rho, v) \in \Delta_{\rho} \times \Delta_v$

$$-\sum_{i=1}^s v_i \frac{\partial \hat{\mathbf{P}}_{\Omega}(\rho)}{\partial \rho_i} + \mathbf{A}(\rho) \hat{\mathbf{P}}_{\Omega}(\rho) + \hat{\mathbf{P}}_{\Omega}(\rho) \mathbf{A}^{\top}(\rho) + \mathbf{B}_{\Omega}(\rho) \mathbf{B}_{\Omega}^{\top}(\rho) = 0 \quad (35)$$

$$\sum_{i=1}^s v_i \frac{\partial \hat{\mathbf{Q}}_{\Omega}(\rho)}{\partial \rho_i} + \mathbf{A}^{\top}(\rho) \hat{\mathbf{Q}}_{\Omega}(\rho) + \hat{\mathbf{Q}}_{\Omega}(\rho) \mathbf{A}(\rho) + \mathbf{C}_{\Omega}^{\top}(\rho) \mathbf{C}_{\Omega}(\rho) = 0. \quad (36)$$

For the generalisation, we have the following inequalities:

$$-\sum_{i=1}^s v_i \frac{\partial \mathbf{P}_{\Omega}(\rho)}{\partial \rho_i} + \mathbf{A}(\rho) \mathbf{P}_{\Omega}(\rho) + \mathbf{P}_{\Omega}(\rho) \mathbf{A}^{\top}(\rho) + \mathbf{B}_{\Omega}(\rho) \mathbf{B}_{\Omega}^{\top}(\rho) \prec 0 \quad (37)$$

$$\sum_{i=1}^s v_i \frac{\partial \mathbf{Q}_{\Omega}(\rho)}{\partial \rho_i} + \mathbf{A}^{\top}(\rho) \mathbf{Q}_{\Omega}(\rho) + \mathbf{Q}_{\Omega}(\rho) \mathbf{A}(\rho) + \mathbf{C}_{\Omega}^{\top}(\rho) \mathbf{C}_{\Omega}(\rho) \prec 0. \quad (38)$$

with $\mathbf{P}_{\Omega}(\rho) = \begin{bmatrix} \mathbf{P}_1(\rho) & 0 \\ 0 & \mathbf{P}_2(\rho) \end{bmatrix} \succ 0$ and $\mathbf{Q}_{\Omega}(\rho) = \begin{bmatrix} \mathbf{Q}_1(\rho) & 0 \\ 0 & \mathbf{Q}_2(\rho) \end{bmatrix} \succ 0$.

If the block diagonal solutions $\mathbf{P}_{\Omega}(\rho)$ and $\mathbf{Q}_{\Omega}(\rho)$ exist, then let $T_1(\rho)$ and $T_2(\rho)$ be two nonsingular matrices given such that

$$\begin{aligned} T_1^{-1}(\rho) \mathbf{P}_1(\rho) T_1^{-\top}(\rho) &= T_1^{\top}(\rho) \mathbf{Q}_1(\rho) T_1(\rho) \\ &= \Sigma_1(\rho) \\ &= \text{diag}(\xi_1(\rho), \dots, \xi_n(\rho)), \end{aligned} \quad (39)$$

with $\xi_1(\rho) \geq \xi_2(\rho) \geq \dots \geq \xi_n(\rho)$, and

$$\begin{aligned} T_2^{-1}(\rho) \mathbf{P}_2(\rho) T_2^{-\top}(\rho) &= T_2^{\top}(\rho) \mathbf{Q}_2(\rho) T_2(\rho) \\ &= \Sigma_2(\rho) \\ &= \text{diag}(\underbrace{\gamma_1(\rho), \dots, \gamma_r(\rho)}_{\Sigma_{21}}, \underbrace{\gamma_{r+1}(\rho), \dots, \gamma_{n_K}(\rho)}_{\Sigma_{22}}), \end{aligned} \quad (40)$$

with $\gamma_1(\rho) \geq \gamma_2(\rho) \geq \dots \geq \gamma_r(\rho) > \gamma_{r+1}(\rho) \geq \gamma_{r+2}(\rho) \geq \dots \geq \gamma_{n_K}(\rho)$ are the frequency limited generalised Hankel singular values of $K(\rho)$ and r is the desired order for the reduced-order controller. The balanced realisation of $K(\rho)$ can be written as

$$\tilde{K}(\rho) = \left[\begin{array}{c|c} \frac{T_2^{-1}(\rho) A_K(\rho) T_2(\rho)}{C_K(\rho) T_2(\rho)} & \frac{T_2^{-1}(\rho) B_K(\rho)}{D_K(\rho)} \end{array} \right] = \left[\begin{array}{c|c} \frac{\tilde{A}_K(\rho)}{\tilde{C}_K(\rho)} & \frac{\tilde{B}_K(\rho)}{\tilde{D}_K(\rho)} \end{array} \right]. \quad (41)$$

Further, $\tilde{K}(\rho)$ is partitioned as conformably with $\Sigma_2(\rho)$ as

$$\tilde{K}(\rho) = \left[\begin{array}{c|c} \left[\begin{array}{cc} \hat{A}_K(\rho) & \tilde{A}_{K12}(\rho) \\ \tilde{A}_{K21}(\rho) & \tilde{A}_{K22}(\rho) \end{array} \right] & \left[\begin{array}{c} \hat{B}_K(\rho) \\ \tilde{B}_{K2}(\rho) \end{array} \right] \\ \hline \left[\begin{array}{cc} \hat{C}_K(\rho) & \tilde{C}_{K2}(\rho) \end{array} \right] & \hat{D}_K(\rho) \end{array} \right]. \quad (42)$$

Finally, a truncation step is performed to obtain a reduced-order controller.

Definition 7: Given the balanced realisation $\tilde{K}(\rho)$ defined in (42), let $\hat{K}(\rho)$ be the truncated realisation to the r th order and denoted as follows

$$\hat{K}(\rho) = \left[\begin{array}{c|c} \hat{A}_K(\rho) & \hat{B}_K(\rho) \\ \hline \hat{C}_K(\rho) & \hat{D}_K(\rho) \end{array} \right] \quad (43)$$

Furthermore, the reduced-order parameter dependent closed-loop system is given as

$$\begin{aligned} \hat{T}_{zw}(\rho) &= \left[\begin{array}{c|c} \hat{\mathbf{A}}(\rho) & \hat{\mathbf{B}}(\rho) \\ \hline \hat{\mathbf{C}}(\rho) & \hat{\mathbf{D}}(\rho) \end{array} \right] \\ &= \left[\begin{array}{cc|c} A(\rho) + B_2 \hat{D}_K(\rho) C_2 & B_2 \hat{C}_K(\rho) & B_1(\rho) + B_2 \hat{D}_K(\rho) \hat{D}_K(\rho) D_{21} \\ \hline \hat{B}_K(\rho) C_2 & \hat{A}_K(\rho) & \hat{B}_K(\rho) D_{21} \\ \hline C_1(\rho) + D_{12} \hat{D}_K(\rho) C_2 & D_{12} \hat{C}_K(\rho) & D_{11}(\rho) + D_{12} \hat{D}_K(\rho) D_{21} \end{array} \right]. \end{aligned} \quad (44)$$

Theorem 1: Suppose $K(\rho)$ is the stabilising parameter dependent controller defined in (8) such that the closed-loop transfer $T_{zw}(\rho)$ defined in (12) is minimal, quadratic stable and there exist Lyapunov inequality solutions $\mathbf{P}_\Omega(\rho)$ and $\mathbf{Q}_\Omega(\rho)$ such that (37) and (38) are satisfied. Let $\hat{K}(\rho)$ be the reduced-order controller defined in (43) and obtained by truncation. Then, the closed-loop system with the reduced-order controller $\hat{T}_{zw}(\rho)$ defined in (44) is stable. If in addition

$$\text{rank}[\mathbf{B}(\rho), \mathbf{B}_\Omega(\rho)] = \text{rank}[\mathbf{B}_\Omega(\rho)], \quad (45)$$

and

$$\text{rank}[\mathbf{C}^\top(\rho), \mathbf{C}_\Omega^\top(\rho)] = \text{rank}[\mathbf{C}_\Omega^\top(\rho)], \quad (46)$$

then, $\hat{T}_{zw}(\rho)$ is quadratic stable and satisfies

$$\|T_{zw}(\rho) - \hat{T}_{zw}(\rho)\|_{i,2} \leq 2\|J_B(\rho)\|_\infty \|J_C(\rho)\|_\infty \sum_{i=r+1}^{n_K} \gamma_{i,\rho} \quad (47)$$

where $J_B(\rho) := \text{diag}(|\lambda_1|^{-\frac{1}{2}}(\rho), \dots, |\lambda_{u_\rho}|^{-\frac{1}{2}}(\rho), 0, \dots, 0) U_\Omega(\rho) \mathbf{B}(\rho)$ and $J_C(\rho) := \mathbf{C}(\rho) V_\Omega(\rho) \text{diag}(|\delta_1|^{-\frac{1}{2}}(\rho), \dots, |\delta_{v_\rho}|^{-\frac{1}{2}}(\rho), 0, \dots, 0)$,

Proof: The reachability and the observability Gramians given in (15),(16) can be expressed as

$$\mathcal{R}(\rho) = \int_{-\infty}^{+\infty} f_\rho(\tau) f_\rho^*(\tau) d\tau \quad (48)$$

$$\mathcal{O}(\rho) = \int_{-\infty}^{+\infty} g_\rho^*(\tau) g_\rho(\tau) d\tau \quad (49)$$

where $f_\rho(\tau)$ and $g_\rho(\tau)$ are given in (26).

Then, using Parseval relationship, the reachability and the observability Gramians could be expressed as follows

$$\mathcal{R}(\rho) = \frac{1}{2\pi} \int_{-\infty}^{+\infty} F_\rho(w) F_\rho^*(w) dw \quad (50)$$

$$\mathcal{O}(\rho) = \frac{1}{2\pi} \int_{-\infty}^{+\infty} G_\rho^*(w) G_\rho(w) dw. \quad (51)$$

By considering F_ρ (resp. g_ρ) the Fourier transform of f_ρ (resp. g_ρ), we can define $\mathcal{R}_\omega(\rho)$ and $\mathcal{O}_\omega(\rho)$ as the limited reachability and observability Gramians given in (28) and (28). Then, by setting $\Omega = [\omega_1; \omega_2]$ the frequency range where approximation is desired to be better. Then, a new modified terms $\mathcal{R}_\Omega(\rho)$ and $\mathcal{O}_\Omega(\rho)$ are defined.

Since $\mathcal{R}_\Omega(\rho)$ and $\mathcal{O}_\Omega(\rho)$ are not guaranteed to be positive definite, stability of the reduced-order controller is not guaranteed. Then, an idea based on eigenvalues decomposition presented in [GA04] is proposed here to guarantee stability by providing an upper error bound. Indeed, the solution of (37) and (38) is performed instead of (29) and (30). In addition, the modified frequency limited Gramians in (35) and (36) are used instead of the ordinary ones defined in (35) and (36). In fact, Lemma 1 shows that the generalised Gramians could be an approximation of the ordinary Gramians. The transition to generalised Gramian framework might induce less accurate approximation but the order-reduction error still bounded. Finally the expression of the upper error bound given in (47) is found according to this

Let $\tilde{T}_{zw}(\rho)$ be the frequency limited balanced realisation of the full-order closed-loop system. Then, $\tilde{T}_{zw}(\rho)$ is defined by

$$\tilde{T}_{zw}(\rho) = \left[\begin{array}{c|c} \frac{T^{-1}(\rho) \mathbf{A}(\rho) T(\rho)}{\mathbf{C}(\rho) T(\rho)} & \frac{T^{-1}(\rho) \mathbf{B}(\rho)}{\mathbf{D}(\rho)} \end{array} \right] = \left[\begin{array}{c|c} \left[\begin{array}{cc} \hat{\mathbf{A}}(\rho) & \tilde{\mathbf{A}}_{12}(\rho) \\ \tilde{\mathbf{A}}_{21}(\rho) & \tilde{\mathbf{A}}_{22}(\rho) \end{array} \right] & \left[\begin{array}{c} \hat{\mathbf{B}}(\rho) \\ \tilde{\mathbf{B}}_2(\rho) \end{array} \right] \\ \hline \left[\begin{array}{cc} \hat{\mathbf{C}}(\rho) & \tilde{\mathbf{C}}_2(\rho) \end{array} \right] & \tilde{\mathbf{D}}(\rho) \end{array} \right], \quad (52)$$

where $T(\rho) = \text{diag}(T_1(\rho), T_2(\rho))$.

By considering the assumptions (45) and (46), there exist $J_B(\rho)$ and $J_C(\rho)$ such that $\mathbf{B}(\rho) = \mathbf{B}_\Omega(\rho) J_B(\rho)$ and $\mathbf{C}(\rho) = J_C(\rho) \mathbf{C}_\Omega(\rho)$. On the other hand, the reduction error is expressed as

$$\begin{aligned} \|T_{zw}(\rho) - \tilde{T}_{zw}(\rho)\|_{i,2} &= \|\mathbf{C}(\rho)(sI - \mathbf{A}(\rho))^{-1} \mathbf{B}(\rho) - \hat{\mathbf{C}}(\rho)(sI - \hat{\mathbf{A}}(\rho))^{-1} \hat{\mathbf{B}}(\rho)\|_{i,2} \\ &= \|J_C(\rho) \left[\mathbf{C}_\Omega(\rho)(sI - \mathbf{A}(\rho))^{-1} \mathbf{B}_\Omega(\rho) - \hat{\mathbf{C}}(\rho)(sI - \hat{\mathbf{A}}(\rho))^{-1} \hat{\mathbf{B}}(\rho) \right] \cdot J_B(\rho)\|_{i,2} \\ &\leq 2\|J_B(\rho)\|_\infty \|J_C(\rho)\|_\infty \sum_{i=r+1}^{n_K} \gamma_{i,\rho} \end{aligned}$$

■

Remark 1: The Assumptions (45) and (46) mean that there exist $J_B(\rho)$ and $J_C(\rho)$ such that $\mathbf{B}(\rho) = \mathbf{B}_\Omega(\rho) J_B(\rho)$ and $\mathbf{C}(\rho) = J_C(\rho) \mathbf{C}_\Omega(\rho)$. In addition, by following the steps in [WSL99, AC81,

IGS14] it was shown that assumptions (45) and (46) are almost always true. Hence we expect that our approach will apply in most of the cases. Indeed, during our simulations, the assumptions have always been satisfied.

Algorithm 1 $\mathcal{H}_\infty$ -LPV-Controller Order Reduction

Considering the LPV-plant described in (7) the reduced-order controller can be computed as follows

Inputs: $(A(\rho), B(\rho), C(\rho), D(\rho))$.

Outputs: $(\hat{A}(\rho), \hat{B}(\rho), \hat{C}(\rho), \hat{D}(\rho))$.

Assumptions: $(\mathbf{A}(\rho), \mathbf{B}(\rho), \mathbf{C}(\rho), \mathbf{D}(\rho))$ minimal.

Algorithm:

- (1) Compute $K(\rho)$ the full-order controller according Section 2.2.
 - (2) Compute the closed-loop system T_{zw} given in (12).
 - (3) Compute the generalised Gramians $\mathbf{P}(\rho)$ and $\mathbf{Q}(\rho)$ solutions of (17) and (18) respectively.
 - (4) Compute the balanced realisation $\tilde{K}(\rho)$ of the full-order controller $K(\rho)$ by:
 - (a) Find T_2 , the basis change matrix according to (40). (For instance, Procedure in [MTL88] can be used).
 - (b) Compute the balanced realisation $\tilde{K}(\rho)$ as defined in (42).
 - (5) Compute the reduced-order controller $\hat{K}(\rho)$ from $\tilde{K}(\rho)$ by truncation.
-

4. Case Study: Semi-Active Suspension Control

4.1 LPV-Model

In this section, the given method to reduce the LPV-controller is applied on a semi-active automotive suspension presented in [DSDB11]. Actually, when suspension modelling and control are considered, the vertical quarter car model is often used. This model allows to study the vertical behaviour of a vehicle according to the suspension characteristic (passive or controlled). Figure 3 shows the so-called vertical quarter car. Then, the dynamical equations of the system are given by

$$\begin{cases} m_s \ddot{z}_s = -k_s z_{\text{def}} - F_{\text{mr}} \\ m_{\text{us}} \ddot{z}_{\text{us}} = k_s z_{\text{def}} + F_{\text{mr}} - k_t(z_{\text{us}} - z_r) \end{cases} \quad (53)$$

where F_{mr} is the magneto-rheological force generated by the semi active suspension. According to the non-linear model of Guo [GYP06], F_{mr} can be expressed as follows

$$F_{\text{mr}} = a_2 \left(\dot{z}_{\text{def}} + \frac{v_0}{x_0} z_{\text{def}} \right) + a_1 \tanh \left(a_3 \left(\dot{z}_{\text{def}} + \frac{v_0}{x_0} z_{\text{def}} \right) \right) \quad (54)$$

with $z_{\text{def}} = z_s - z_{\text{us}}$ is the damper deflection (must be measured or estimated) and $\dot{z}_{\text{def}} = \dot{z}_s - \dot{z}_{\text{us}}$ is the damper velocity. Parameters a_2, a_3, v_0 and x_0 are constant, and a_1 is the controllable force such that $a_1 \in [a_{1\min}; a_{1\max}]$.

By defining

$$\begin{aligned} \rho_1 &= \tanh \left(a_3 \left(\dot{z}_{\text{def}} + \frac{v_0}{x_0} z_{\text{def}} \right) \right), \\ c_{\text{mr}} &= a_2 : \text{MR damping coefficient}, \\ k_{\text{mr}} &= a_2 \frac{v_0}{x_0} : \text{MR stiffness coefficient}, \end{aligned}$$

Then, a state-space representation can be given by considering the state vector $x_s = [z_s \ \dot{z}_s \ z_{\text{us}} \ \dot{z}_{\text{us}}]^T$

and the exogenous input $w = z_r$, as follows

$$\begin{cases} \dot{x}_s = A_s x_s + B_s \rho_1 a_1 + B_{s1} w \\ z = C_{s1} x_s + D_{s1} \rho_1 a_1 \\ y = C_s x_s \end{cases} \quad (55)$$

with

$$A_s = \begin{pmatrix} 0 & 1 & 0 & 0 \\ -\frac{k_s+k_{mr}}{m_s} & -\frac{c_{mr}}{m_s} & \frac{k_s+k_{mr}}{m_s} & \frac{c_{mr}}{m_s} \\ 0 & 0 & 0 & 1 \\ \frac{k_s+k_{mr}}{m_{us}} & \frac{c_{mr}}{m_{us}} & -\frac{k_s+k_{mr}+k_t}{m_{us}} & -\frac{c_{mr}}{m_{us}} \end{pmatrix}, B_s = \begin{pmatrix} 0 \\ -1 \\ 0 \\ -1 \end{pmatrix}, B_{s1} = \begin{pmatrix} 0 \\ 0 \\ 0 \\ -\frac{k_t}{m_{us}} \end{pmatrix}.$$

The measurement output is $y = z_s - z_{us}$, and the controlled outputs are chosen as $z = [\dot{z}_s \ z_s]^\top$, respectively the acceleration and the displacement of the sprung mass. Then

$$C_{s1} = \begin{pmatrix} -\frac{k_s+k_{mr}}{m_s} & -\frac{c_{mr}}{m_s} & \frac{k_s+k_{mr}}{m_s} & \frac{c_{mr}}{m_s} \\ 1 & 0 & 0 & 0 \end{pmatrix}, D_{s1} = \begin{pmatrix} -\frac{1}{m_s} \\ 0 \end{pmatrix}, C_s = \begin{pmatrix} 1 & 0 & -1 & 0 \end{pmatrix}.$$

However, two constraints must be satisfied

- (1) The control signal a_1 must be positive (dissipative constraint)
- (2) The input matrices $B_s \rho_1$ and $D_{s1} \rho_1$ must be constant to satisfy the LPV- $\mathcal{H}_\infty$ synthesis assumption.

The passivity problem is solved by defining a new control signal $u = a_1 - F_0$ where F_0 is the mean value of a_1 ($F_0 = (a_{1\max} - a_{1\min})/2$). Then, the problem of the passivity on a_1 is recast to a simple saturation problem on u ($u \in [-F_0; F_0]$). With these modifications, (56) yields

$$\begin{cases} \dot{x}_s = (A_s + B_{s2} \frac{\rho_1}{C_{s2} x_s} C_{s2}) x_s + B_s \rho_1 u + B_{s1} w \\ z = C_{s1} x_s + D_{s1} \rho_1 u \\ y = C_s x_s \end{cases} \quad (56)$$

where

$$B_{s2} = \begin{pmatrix} 0 & -\frac{F_0}{m_s} & 0 & \frac{F_0}{m_{us}} \end{pmatrix}^\top \text{ and } C_{s2} = \begin{pmatrix} -\frac{a_3 v_0}{x_0} & a_3 & -\frac{a_3 v_0}{x_0} & -a_3 \end{pmatrix}^\top.$$

To overcome the second problem, [AG95] proposes to add a strictly proper filter $\mathcal{F}$ to make the controlled output matrices independent of the scheduling parameters

$$\mathcal{F} : \begin{pmatrix} \dot{x}_f \\ u \end{pmatrix} = \begin{pmatrix} A_f & B_f \\ C_f & 0 \end{pmatrix} \begin{pmatrix} x_f \\ u_c \end{pmatrix} \quad (57)$$

Then, by defining $\rho_2 = \frac{\rho_1}{C_{s2} x_s}$ and $x = (x_s \ x_f)^\top$ the system (56) can be represented as

$$\begin{cases} \dot{x} = A(\rho_1, \rho_2) x + B u_c + B_1 w \\ z = C_1(\rho_1, \rho_2) x \\ y = C x \end{cases} \quad (58)$$

where

$$A(\rho_1, \rho_2) = \begin{pmatrix} A_s + \rho_2 B_{s2} C_{s2} & \rho_1 B_s C_f \\ 0 & A_f \end{pmatrix}, \quad B = \begin{pmatrix} 0 \\ B_f \end{pmatrix}, \quad B_1 = \begin{pmatrix} B_{s1} \\ 0 \end{pmatrix},$$

$$C_1(\rho_1, \rho_2) = \begin{pmatrix} C_{s1} & \rho_1 D_{s1} C_f \end{pmatrix} \text{ and } C = \begin{pmatrix} C_s & 0 \end{pmatrix}.$$

4.2 $\mathcal{H}_\infty$ -Controller Synthesis

By considering the LPV-model (58), an $\mathcal{H}_\infty$ controller is designed to guarantee the internal closed-loop stability and to satisfy some required performance. In fact, the main objective and challenge of a controlled suspension system is to improve the comfort for car passengers simultaneously to the performance on road holding. The passenger comfort can be improved by isolating the vibrations transmitted from the road surface. Then, the "frequency response" from the road profile z_r to the vehicle chassis acceleration $\ddot{z}_s$ must be kept small in the low frequency range. Then, a weighting function is designed as

$$W_{\ddot{z}_s} = w_{\ddot{z}_s} \frac{s^2 + \xi_{11} w_{11} s + w_{11}^2}{s^2 + 2\xi_{12} w_{12} s + w_{12}^2}$$

Furthermore, the road holding is evaluated from the unsprung mass (wheel) oscillations with respect to the road profile. This transfer should be kept small at high frequencies. Then, $W_{z_{us}}$ is designed as

$$W_{z_{us}} = w_{z_{us}} \frac{s^2 + \xi_{21} w_{21} s + w_{21}^2}{s^2 + 2\xi_{22} w_{22} s + w_{22}^2}$$

$W_{z_r} = 5 \times 10^{-3}$ is the road profile gain. Finally, the filter introduced in (57) is given as: $\mathcal{F} = \frac{w_f}{s + w_f}$. It is designed with a large bandwidth to decouple the input and the varying parameters, where

$$w_{\ddot{z}_s} = 1, \quad \xi_{11} = 0.1, \quad \xi_{12} = 1, \quad w_{11} = 2\pi \times 1 \text{ rad.s}^{-1}, \quad w_{12} = 2\pi \times 3 \text{ rad.s}^{-1},$$

$$w_{z_{us}} = 10, \quad \xi_{21} = 0.3, \quad \xi_{22} = 1, \quad w_{21} = 2\pi \times 9 \text{ rad.s}^{-1}, \quad w_{22} = 2\pi \times 9 \text{ rad.s}^{-1}, \quad w_f = 90.34.$$

Then, an interconnection between the LPV-model and these weighting functions are presented in Figure 4.

Model parameters are obtained by considering experimental data in [TMFV⁺13] and given as Table 3. To carry out a controller satisfying these objectives, the $\mathcal{H}_\infty$ -LPV-synthesis is designed by using solution for polytopic systems: it consists in finding a global LPV-controller $K(\rho_1, \rho_2)$ which is a convex combination of local controllers obtained by solving the LMIs set at each vertex (formed by limits values of the varying parameters). All varying parameters are bounded: $\rho_1 \in [-1; 1]$, $\rho_2 \in [0; 1]$.

For more details and explanation on $\mathcal{H}_\infty$ -LPV-control synthesis, see [AG95, SGC97]. The design method for LPV-systems is used like in [AGB94].

4.3 Numerical Issue

The proposed method requests the solution of two Lyapunov inequalities with an infinite number of constraints. These sets of infinite LMIs can be solved by gridding techniques. Then, some ap-

proximations must be made by gridding the set Δ_ρ with finite number L of points $\{\rho_i\}_{i=1}^L$ [Lee97]. Moreover, the infinite variables $\mathbf{P}_\Omega(\rho)$ and $\mathbf{Q}_\Omega(\rho)$ in LMIs (37),(38) are approximated by combinations of scalar basis functions such as

$$\mathbf{P}_\Omega(\rho) = \sum_{j=1}^{N_P} \phi_j(\rho) P_j \succ 0$$

$$\mathbf{Q}_\Omega(\rho) = \sum_{j=1}^{N_Q} \varphi_j(\rho) Q_j \succ 0$$

where $P_j = P_j^\top, Q_j = Q_j^\top$. There is a large freedom in the choice of basis functions [Woo95]. For this example, the following choice is made:

$$\{\phi_j\}_{j=1}^{13} = \{\varphi_j\}_{j=1}^{13} = \{1, \rho_1, \rho_2, \rho_1^2, \rho_2^2, \rho_1\rho_2, \rho_1\rho_2^2, \rho_1^2\rho_2, \rho_1^2\rho_2^2, \rho_1^3, \rho_2^3, \rho_1\rho_2^3, \rho_1^3\rho_2\}.$$

The main consequence of this approximation is that the number of LMIs to be solved is finite and is $2L(2^{s+1} + 1)$ where s is the number of parameters, i.e. $s = 2$.

The full-order controller is designed using the procedure developed in [SGC97]. Then, an 8-order controller K_{full} is obtained. The proposed method is used to reduce K_{full} . Then, K_{FWBT} is produced. To test its effectiveness, a comparison with the method developed in [WRS04] (LPV balanced truncation) namely K_{BT} , is performed. The feasibility problems (37)(38) are convex. Using (Matlab LMI Control Toolbox), controllers are reduced to the 5th order obtained heuristically by trial-and-error approach. Therefore, a frequency and time analysis are performed.

4.4 Results and Discussion

The first evaluation is represented in Table 1 where first the assumption (45) and (46) are checked. Note that for 25 frozen values of (ρ_1, ρ_2) , the rank assumption is satisfied for all these points. This fact confirms Remark 1 and allows us compute an upper bound. Precisely, Table 2 express the upper bounds and $\mathcal{H}_\infty$ -norm of the error values. These results evince that the upper bound is correctly positioned (the gap is positive). However, we note that this upper bound is not tight to error H_∞ -norm.

Frequency analysis:

The Bode diagrams at several frozen values of ρ_1 and ρ_2 (25 points) of the three transfer function $T_{z_s}, T_{\ddot{z}_s}$ and $T_{z_{us}}$ are shown respectively in Figure 5, 6 and 7. In fact, the frequency behaviours of the chassis position z_s and acceleration $\ddot{z}_r$ are chosen to be analysed in order to observe the comfort performance regarding the road profile input z_r . The wheel position signal z_{us} is also analysed to test the road holding. Then, the weighting functions $W_{\ddot{z}_s}$ and W_{z_s} designed in Section 4.2, limit the amplification of the previously cited transfers in low frequency range (around $[1 ; 10]$ Hz). In fact, the human sensitivity to vertical vibrations is important in this frequency range [DSS⁺10]. For this reason, the frequency interval of the proposed frequency limited FWBT method is chosen as $[1 ; 8]$ Hz.

In Figure 5, note the reduced-order closed-loop system produced by FWBT approximate well the full-order closed-loop system in the chosen frequency range $[1 ; 10]$ Hz. In this interval, the reduced-order closed-loop system produced by the unweighted BT fails. In fact, an important gap appears a 2 Hz and 3 Hz which is exacted as th BT is known to guarantee good approximation at high frequency. The same comment is given in Figure 6 where FWBT fits the full order closed-loop system in all the shown range unlike BT method that miss the peak around 2 (a resonance frequency). These results are more explicit when observing Figure 7. Indeed, FWBT gives a good approximation when BT

fails (2 Hz and 8 Hz). The other important fact stated by these results, is the sensitivity against the parameters variation. Actually, a dispersion of ρ_1 and ρ_2 values is induced by the reduction step. This degradation is expected since the given application is a qLPV system where ρ_1 and ρ_2 are depending on the state vector. Then, every decrease in the order (states) affects the ρ_1 and ρ_2 values. However, this loss when reducing is under control for two reasons: the first one, the stability of reduced-order closed-loop is preserved and the error is guaranteed limited. The second one is that this dispersion is weak in the required frequency range. Thus, performance are not affected.

Remark 2: As Bode diagram for non-linear systems is not possible, a pseudo-Bode plot is then proposed in [PV08]

Time analysis:

In the time domain, the several controlled suspensions are travelling a bump of $0.01 \text{ m} \times 2 \text{ m}$ for a vehicle speed 8.3 m/s (i.e. 30 km/h). It is observed that the time response confirms the contribution of the FWBT reduction method. In fact, in Figure 8, the chassis is stabilised rapidly (1 sec. after the perturbation) without overtake on the suspension unlike the suspension with K_{BT} . This observation, preserves the required ‘comfort’ performance. Moreover, for z_{us} , the wheel equipped with a K_{FWBT} -suspension, keeps almost the same profile of the road although its variations which respects the ‘road handling’ performance. The K_{BT} -suspension generate an infinite perturbation just after the bump (after 1 sec.). Note also, that temporal test draw two output signals (chassis and wheel positions) regarding the input (the road profile) and by the way there will be just one plot of each transfer besides the several plots in the frequency responses.

5. Conclusion

In this paper, the problem of LPV-Controller order reduction is investigated, and the approximation in a limited frequency range is considered. based on a similar work on the LTI-case, a new frequency limited method for LPV-controller order reduction is derived. The obtained reduced-order controller is proven stable and the degradation in the closed-loop performance is guaranteed bounded. An application of the proposed method to reduce the order of a semi-active suspension-controller is performed. The obtained results show its effectiveness to preserve the closed-loop stability and to respect the required performance specifications. The comparison with another existent LPV order-reduction technique based on the the classical BT, confirms the contribution of the proposed method.

6. Acknowledgement

The author would like to address their acknowledgement to the Associate Editor and the anonymous reviewers for their valuable comments that have helped significantly improve this paper.

References

- [AC81] Brian D.O. Anderson and David J. Clements. Algebraic characterization of fixed modes in decentralized control. *Automatica*, 17(5):703 – 712, 1981.
- [AG95] P. Apkarian and P. Gahinet. A convex characterization of gain-scheduled H_∞ controllers. *Automatic Control, IEEE Transactions on*, 40(5):853–864, 1995.
- [AGB94] P. Apkarian, P. Gahinet, and G. Becker. Self-scheduled H_∞ linear parameter-varying systems. In *IEEE Transactions on Automatic Control*, pages 856–860, 1994.
- [AHH11] Daniel Ankelhed, Anders Helmersson, and Anders Hansson. A partially augmented lagrangian method for low order h-infinity controller synthesis using rational constraints. In *CDC-ECE'11*, pages 8219–8224, 2011.
- [AL89] B.D.O. Anderson and Y. Liu. Controller reduction: concepts and approaches. *IEEE Transactions on Automatic Control*, 34(8):802 –812, 1989.
- [Bri15] C. Briat. *Linear Parameter-Varying and Time-Delay Systems*. Springer, 2015.
- [DSDB11] A.L. Do, O. Sename, L. Dugard, and S. Boussaad. Multi-objective optimization by genetic algorithms in H_∞ /LPV control of semi-active suspension. In *Proceedings of the 18th IFAC World Congress*, 2011.
- [DSS⁺10] A.L. Do, C. Spelta, S.M. Savaresi, O. Sename, L. Dugard, and D. Delvecchio. An lpv control approach for comfort and suspension travel improvements of semi-active suspension systems. In *Decision and Control (CDC), 2010 49th IEEE Conference on*, pages 5560–5565, 2010.
- [Enn84] D.F. Enns. Model reduction with balanced realizations: An error bound and a frequency weighted generalization. In *Decision and Control, 1984. The 23rd IEEE Conference on*, volume 23, pages 127 –132, 1984.
- [EZJ98] H. El-Zobaidi and I. Jaimoukha. Robust control and model and controller reduction of linear parameter varying systems. In *Decision and Control, 1998. Proceedings of the 37th IEEE Conference on*, volume 3, pages 3015–3020 vol.3, 1998.
- [GA04] S. Gugercin and A.C. Antoulas. A survey of model reduction by balanced truncation and some new results. *International Journal of Control*, 77:748–766, 2004.
- [GJ90] W. Gawronski and J. Juang. Model reduction in limited time and frequency intervals. *International Journal of Systems Science*, 21(2):349–376, 1990.
- [Glo84] K. Glover. All optimal Hankel-norm approximations of linear multivariable systems and their l_∞ error bounds. *International Journal of Control*, 39(6):1115–1193, 1984.
- [God95] P. J. Goddard. *Performance-Preserving Controller Approximation*. PhD thesis, Trinity College Cambridge, 1995.
- [GYP06] S. Guo, S. Yang, and C. Pan. Dynamic modeling of magnetorheological damper behaviors. *Journal of Intelligent Material Systems and Structures*, 17(1):3–14, 2006.
- [IGS14] Muhammad Imran, Abdul Ghafoor, and Victor Sreeram. A frequency weighted model order reduction technique and error bounds. *Automatica*, 50(12):3304 – 3309, 2014.
- [KAM95] S.W. Kim, B.D.O. Anderson, and A.G. Madievski. Error bound for transfer function order reduction using frequency weighted balanced truncation. *Syst. Control Lett.*, 24:183–192, February 1995.
- [Kon12] L. Kong. *Controller reduction for linear systems*. PhD thesis, Louisiana State University, 2012.
- [LA89] Y. Liu and B.D.O. Anderson. Singular perturbation approximation of balanced systems. In *Decision and Control, 1989., Proceedings of the 28th IEEE Conference on*, pages 1355–1360 vol.2, 1989.
- [LC90] C.A. Lin and T.Y. Chiu. Model reduction via frequency weighted balanced realization. In *American Control Conference*, pages 2069 –2070, may 1990.
- [Lee97] L. H. Lee. *Identification and Robust Control of Linear Parameter-Varying Systems*. PhD thesis, University of California at Berkeley, 1997.

- [LYG14] Xianwei Li, Shen Yin, and Huijun Gao. Passivity-preserving model reduction with finite frequency H_∞ approximation performance. *Automatica*, 50(9):2294 – 2303, 2014.
- [LYG15] Xianwei Li, Changbin Yu, and Huijun Gao. Frequency-limited $H - \infty$ model reduction for positive systems. *Automatic Control, IEEE Transactions on*, 60(4):1093–1098, 2015.
- [Moo81] B. Moore. Principal component analysis in linear systems: Controllability, observability, and model reduction. *IEEE Transactions on Automatic Control*, 26(1):17–32, February 1981.
- [MR76] C. Mullis and R. Roberts. Synthesis of minimum roundoff noise fixed point digital filters. *IEEE Transactions on Circuits and Systems*, 23(9):551 – 562, September 1976.
- [MTL88] John B. Moore, Andrew J. Telford, and U-L. Ly. Controller reduction methods maintaining performance and robustness. In *Conference on Decision and Control*, 1988.
- [OPJ13] Sename O., Gaspar P., and Bokor J. *Robust Control and Linear Parameter Varying approaches: Application to Vehicle Dynamics*. Springer, Feb 2013.
- [PK96] A. Packard and M. Kantner. Gain scheduling the LPV way. In *Decision and Control, 1996., Proceedings of the 35th IEEE Conference on*, volume 4, pages 3938–3941 vol.4, 1996.
- [PS82] L. Pernebo and L. Silverman. Model reduction via balanced state space representations. *IEEE Transactions on Automatic Control*, 27:382–387, 1982.
- [PV08] C. Poussot-Vassal. *Robust LPV multivariable Automotive Global Chassis Control*. Theses, Institut National Polytechnique de Grenoble - INPG, 2008.
- [SA90] J.S. Shamma and M. Athans. Analysis of gain scheduled control for nonlinear plants. *Automatic Control, IEEE Transactions on*, 35(8):898–907, 1990.
- [SA95] V. Sreeram and B.D.O. Anderson. Frequency weighted balanced reduction technique: a generalization and an error bound. In *Decision and Control, 1995., Proceedings of the 34th IEEE Conference on*, volume 4, pages 3576 –3581 vol.4, dec 1995.
- [SGC97] C. Scherer, P. Gahinet, and M. Chilali. Multiobjective output-feedback control via lmi optimization. *Automatic Control, IEEE Transactions on*, 42(7):896–911, 1997.
- [SR04] H. Sandberg and A. Rantzer. Balanced truncation of linear time-varying systems. *Automatic Control, IEEE Transactions on*, 49(2):217–229, 2004.
- [SW11] H. R. Shaker and R. Wisniewski. Generalized gramian framework for model/controller order reduction of switched systems. *International Journal of Systems Science*, pages 1277–1291, 2011.
- [TMFV+13] J. C. Tudon-Martinez, S. Fergani, S. Varrier, O. Sename, L. Dugard, R. Morales-Menendez, and R. Ramirez-Mendoza. Road Adaptive Semi-active Suspension in a Pick-up Truck using an LPV Controller. In *The 7th IFAC international symposium on Advances in Automotive Control (AAC)*, page n/c, Tokyo, Japan, 2013.
- [VA01] A. Varga and B.D.O. Anderson. Accuracy enhancing methods for the frequency-weighted balancing related model reduction. In *Decision and Control, 2001. Proceedings of the 40th IEEE Conference on*, volume 4, pages 3659 –3664 vol.4, 2001.
- [WGG96] G.D. Wood, P.J. Goddard, and K. Glover. Approximation of linear parameter-varying systems. In *Decision and Control, 1996., Proceedings of the 35th IEEE Conference on*, volume 1, pages 406–411 vol.1, 1996.
- [Woo95] G. D. Wood. *Control of Parameter-Dependent Mechanical Systems*. PhD thesis, St Johns College, 1995.
- [WRB06] W. Widowati, B. Riyanto, and T. Bambang. Model reduction of LPV control with bounded parameter variation rates. In *The 6th Asian Control Conference*, 2006.
- [WRS04] W. Widowati, B. Riyanto, and R. Saragih. Controller reduction of parameter dependent systems. *ITB Journal of Engineering Science*, 36:43–56, 2004.
- [WSL99] G. Wang, V. Sreeram, and W.Q. Liu. A new frequency-weighted balanced truncation method and an error bound. *Automatic Control, IEEE Transactions on*, 44(9):1734

- 1737, sep 1999.
- [ZDC95] K. Zhou, C. D’Souza, and J. R. Cloutier. Structurally balanced controller order reduction with guaranteed closed loop performance. *Systems & Control Letters*, 24(4):235–242, 1995.
- [Zho95] K. Zhou. A comparative study of H_∞ controller reduction methods. In *American Control Conference, 1995. Proceedings of the*, volume 6, pages 4015 –4019, jun 1995.

Figure 1.: Controller-order reduction scheme [AL89]

Figure 2.: Closed-loop scheme

Figure 3.: Quarter-vehicle model

Figure 4.: $\mathcal{H}_\infty$ -control scheme

Figure 5.: Bode diagram magnitude of the transfer T_{z_g/z_r}

Figure 6.: Bode diagram magnitude of the transfer T_{z_g/z_r}

Figure 7.: Bode diagram magnitude of the transfer T_{z_{us}/z_r}

Figure 8.: Time response on a bump of 0.01 m x 2 m

Table 1.: values of $(\text{rank}[\mathbf{B}(\rho), \mathbf{B}_\Omega(\rho)]/\text{rank}[\mathbf{B}_\Omega(\rho)]; \text{rank}[\mathbf{C}^\top(\rho), \mathbf{C}_\Omega^\top(\rho)]/\text{rank}[\mathbf{C}_\Omega^\top(\rho)])$ for the several frozen values of (ρ_1, ρ_2)

$\rho_1 \backslash \rho_2$	-1.0	-0.5	0.0	0.5	1.0
0	(14/14; 14/14)	(14/14; 14/14)	(14/14; 14/14)	(14/14; 14/14)	(14/14; 14/14)
0.25	(14/14; 14/14)	(13/13; 14/14)	(14/14; 14/14)	(14/14; 14/14)	(14/14; 14/14)
0.5	(11/11; 14/14)	(13/13; 14/14)	(11/11; 14/14)	(12/12; 14/14)	(11/11; 14/14)
0.75	(12/12; 14/14)	(14/14; 14/14)	(14/14; 14/14)	(14/14; 14/14)	(14/14; 14/14)
1.0	(14/14; 14/14)	(14/14; 14/14)	(14/14; 14/14)	(14/14; 14/14)	(14/14; 14/14)

Table 2.: values of the $\|T_{zw}(\rho) - \hat{T}_{zw}(\rho)\|_{i,2}$ and the upper bound for several frozen values of (ρ_1, ρ_2)

$\rho_1 \backslash \rho_2$	-1.0	-0.5	0.0	0.5	1.0
0.0	$1.36 \leq 5.07$	$1.35 \leq 3.32$	$1.33 \leq 4.08$	$1.31 \leq 3.37$	$1.30 \leq 3.72$
0.25	$0.32 \leq 9.88$	$0.32 \leq 9.93$	$0.32 \leq 10.38$	$0.31 \leq 10.39$	$0.31 \leq 9.80$
0.5	$0.00 \leq 1.79$	$0.00 \leq 0.13$	$0.00 \leq 2.22$	$0.00 \leq 11.81$	$0.00 \leq 2.03$
0.75	$0.31 \leq 9.97$	$0.31 \leq 9.92$	$0.30 \leq 10.58$	$0.30 \leq 9.86$	$0.29 \leq 9.89$
1.5	$1.22 \leq 3.77$	$1.20 \leq 3.04$	$1.19 \leq 4.46$	$1.18 \leq 2.88$	$1.17 \leq 2.90$

Table 3.: Parameter values

Parameter	Value
Sprung mass (m_s)	470 [kg]
Unsprung mass (m_{us})	110 [kg]
Tyre stiffness coefficient (k_t)	86378 [N/m]
Spring stiffness coefficient (k_s)	270000 [N/m]