Time-resolved quantum transport for optoelectronics

Fabienne Michelini, Katawoura Beltako, M. Bescond, N. Cavassilas, L.
Raymond

► To cite this version:

Fabienne Michelini, Katawoura Beltako, M. Bescond, N. Cavassilas, L. Raymond. Time-resolved quantum transport for optoelectronics. 2017 IEEE International Electron Devices Meeting (IEDM), Dec 2017, San Francisco, France. 10.1109/IEDM.2017.8268478 . hal-01761825

HAL Id: hal-01761825

<https://hal.science/hal-01761825>

Submitted on 15 May 2018

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Time-resolved quantum transport for optoelectronics

F. Michelini, K. Beltako, M. Bescond, N. Cavassilas and L. Raymond

Aix Marseille Univ, Univ Toulon, CNRS, IM2NP UMR 7334, Marseille, France, email: fabienne.michelini@im2np.fr

Abstract— We investigate time-resolved energy currents in a molecular optoelectronic junction made of two donors and an acceptor sandwiched between two electrodes and excited by a Gaussian femtosecond laser pulse. Features of direct energy currents are thus correlated to the intra-molecular structure.

I. INTRODUCTION

Recent experimental trend toward femtosecond multidynamical excitations has triggered an interest for investigating time-dependent regimes in nanostructured semiconductor, molecular or hybrid electronic systems [1]. Molecular electronic devices form indeed a promising alternative to standard electronic devices due to their fast response on ultra-short time scale. The quest for understanding the time-resolved response of nanometer scale junctions interacting with external electromagnetic fields is thus fueled by both the fundamental questions it raises and the premise for long term applications in optoelectronics. In this delicate context, the problem of energy transfer is emerging as one of the most crucial issues at several levels, from the impassable meat by quantum thermodynamics [2] to biologically inspired high efficiency concepts [3]. In this paper, we derive and examine time-resolved energy currents induced by femtosecond laser pulses in a molecular optoelectronic junction sandwiched between metallic electrodes.

II. THEORETICAL ORIENTATIONS

By the end of the last century, nanodevices reached the nanometer scale, and lived a tremendous change of paradigm as they become quantum systems. Such a breakthrough has revealed powerful methods of quantum statistics for simulating nanowire transistor characteristics, in particular the method of non-equilibrium Green's functions (NEGFs) [4]. Today, this formalism is widely used for several device functionalities, but challenges remain, especially for time-dependent regimes and quantum thermoelectricity.

Few years ago, a technique was proposed by Gaury and co-workers in order to manage time-dependence in mesoscopic systems [5]. Elementary objects of the technique are wave functions (WFs) instead of NEGFs, vectors instead of matrices. In fact, WFs are components of the retarded Green's function projected on propagation modes that are defined from reservoir self-energies. Despite being applied only in non-interacting cases so far, the technique seems also promising to tackle interactions. The technique aims to manage time-dependence by means of simpler simulations while accounting for the complete energy dependence of the self-energies, i.e. beyond the wide band limit.

On the other side, quantum thermoelectricity has recently emerged as a part of the solution to the problem of sustainable emission-free energy production. However, these advances have raised some fundamental questions about energy and heat [6], which are crucial for thermodynamics and energy conversion at the nanoscale especially in time-dependent regimes [2]. Moreover, few teams around the world develop specific time-resolved techniques to directly address the photo-carrier dynamics [1], and even less the photo-carrier thermodynamics at the nanometer scale.

We present a practical methodology based on lattice Hamiltonian to investigate energy exchanges on ultimate time and size scales. The approach is developed for the study of a molecular optoelectronic junction that interacts with femtosecond laser pulses.

III. ENERGY CURRENT IN THE MOLECULAR JUNCTION

We consider an optoelectronic junction made of three subsystems: two donors (D_1 and D_2) interact with a Gaussian femtosecond laser pulse, and they are both connected to an acceptor (A). The whole complex is in contact with two thermal reservoirs. The junction is shown Fig. 1. Each donor is described by a two-level model of HOMO and LUMO states. For the acceptor, we use a two-site model with a single level model to study energy transport. All parameters are shown in the molecular complex level structure of Fig. 2.

For the loop circuit designed by the molecular complex, see Fig. 3, we derive an energy current operator from the continuity equation. In Ref. [7], the authors developed an energy current operator for a one-dimensional lattice Hamiltonian. We here address the loop case. The difficulty underlying the definition of an energy current operator resides in the fact that in contrast with the charge current operator for which: $N = \sum_s n_s$, the total Hamiltonian of the system

doesn't have the form of a sum of subsystem Hamiltonians.

Indeed $H = \sum_s h_s^0 + \sum_{r(s)} V(s, r)$: all sites s have a local

Hamiltonian, h_s^0 , but they are also interconnected with coupling terms $V(s, r) = t_{sr} a_s^\dagger a_r + h.c.$, where t_{sr} is the coupling parameter, $t_{sr} = 0$ if sites s and r are not connected.

We have to redefine local Hamiltonians that include intersite coupling terms. We adopt the same proposal as [7] with

$$h_s = h_s^0 + \frac{1}{2} \sum_{r(s)} V(s, r).$$

For this peculiar circuit, we identify four contributions to energy current operator by comparison with the one-dimensional discrete case treated by Wu and Segal [7]. This viewpoint makes possible to distinguish between the two single line terms, two-site $J^{E(2)}$ and four-site $J^{E(4)}$ terms, the additional branch term, $J^{E(B)}$, and finally two loop contribution in $J^{E(L)}$. All these contributions are schematically represented Fig. 3. Time-resolved mean values of these contributions and total energy current were calculated using WF technique [5], still in the wide band limit.

IV. FINDINGS

In Fig. 4, the time-resolved energy current exhibits oscillations whose frequency varies as a function of the D_1 - D_2 coupling. These oscillations manifest the proper frequencies of the internal structure of the molecular complex. Indeed, the donor-donor coupling modifies the internal structure of the complex: frequencies change. As long as electrons have enough time to explore all the hybridized states in the system, they oscillate between these states before tunneling to reservoirs. To study the effects of couplings and excitation characteristics, we now rely on the direct energy current, that is the energy current integrated over time.

The direct energy current together with its different components are plotted as a function of the D_1 - D_2 coupling in Fig. 5. The $J^{E(2)}$ term represents the two-site current which is directly proportional to charge current. This contribution is the major one. The $J^{E(4)}$ term represents the four-site contribution along the D_1 -A line, while $J^{E(B)}$ involves the D_2 -A branch. However, term $J^{E(B)}$ is several orders of magnitude lower than $J^{E(4)}$ because carriers cannot reach the left reservoir via this branch (tunneling parameter is zero for left LUMO states). Finally, the loop term, $J^{E(L)}$, provides a negative contribution to the total energy current. The D_1 - D_2 coupling drives energy in the loop formed by the two donors and the acceptor. Increasing simultaneously both D-A and Γ couplings naturally emphasize both $J^{E(4)}$ and $J^{E(L)}$ contributions (see Fig. 3 for schematic definitions).

We finally explore impacts on energy current of a dissymmetry between the two donors.

The first difference is introduced via excitation. We suppose that the two laser pulses are not synchronized on a femtosecond timescale, a delay occurs between the two light-donor interactions. For this study, two molecule configurations are considered: the case where the donors are not connected, and the loop in its highly symmetric configuration, where the two donors are connected with a coupling parameter equal to the D-A coupling value, both cases are shown Fig. 6. While a monotonous behavior of both currents is observed in the first case, in the loop case the two currents flowing from D_1 and D_2 towards A are oscillating with an opposite phase and a frequency about D-A coupling.

The second difference between the two donors is implemented in the D-A coupling parameter. The D_2 -A coupling value increases from zero to twice the D_1 -A one. In the D_1 -A branch, energy current decreases while it increases starting from zero in the D_2 -A branch, as plotted Fig. 7. Interestingly, the sum of the two currents exhibits a maximum close to the symmetric configuration also shown Fig. 7.

At last, the roles of D-D and D-A couplings are exchanged: the D_2 -A coupling is zero while the D_1 - D_2 coupling increases from zero to twice the D_1 -A coupling value. We observe two remarkable behaviors on Fig. 8. On the one hand, $J_{D_1-A}^E$ increases when D_1 is connected to D_2 , and on the other hand, $J_{D_2-A}^E$ is non-zero while the two sites D_2 and A are not connected. This intriguing last result is originating from one of the $J^{E(L)}$ components. Indeed, from the definition we have chosen, $J^{E(L)}$ includes a term which is not proportional to the coupling between D_2 and A (see Fig. 8). What is the meaning of this contribution? We believe that it is likely related to transport channels activated by the time-dependent electromagnetic field. Otherwise, the energy current operator shall be accordingly adapted.

V. CONCLUSION

We studied the dynamics of energy transfer at donor-acceptor interfaces in a molecular optoelectronic junction using a mean-field approach inside the wave function technique. This exploratory work still ignores electron-electron interaction and vibrations, but nonetheless provides basic insights towards the design of new energy-conversion schemes for time-dependent optoelectronics.

ACKNOWLEDGMENT

The authors acknowledge financial support from the ANR-French National Research Agency [NOODLES, contract No. ANR-13-NANO-0009].

REFERENCES

- [1] A. A. Bakulin, C. Silva, and E. Vella, Ultrafast Spectroscopy with photocurrent detection: Watching Excitonic Optoelectronic Systems at work", *J. Phys. Chem. Lett.* 7, pp. 250-258, 2016.
- [2] M. Esposito, "The nature of heat:", *Phys. Rev. B*, pp (2015).
- [3] C. Creatore, M. A. Parker, S. Emmott, and A.W. Chin, "Efficient biologically inspired photocell enhanced by delocalized states", *Phys. Rev. Lett.* 111, 253601, 2013.
- [4] G. Stefanucci and R. van Leeuwen, "Nonequilibrium Many-Body Theory of Quantum Systems: a Modern Introduction", Cambridge: Cambridge University Press, 2013.
- [5] B. Gaury, J. Weston, M. Santin, M. Houzet, C. Groth, and X. Waintal, "Numerical simulations of time-resolved quantum electronics" *Phys. Rep.* 534(1): pp. 1- 37, 2014.
- [6] F. Michelini, A. Crépieux, and K. Beltako, "Entropy production in photovoltaic- thermoelectric nanodevices from the non-equilibrium Green's function formalism", *J. Phys.: Condens. Matter* 29, 175301, 2017.
- [7] L.-A. Wu and D. Segal, "Energy flux operator, current conservation and the formal Fourier's law", *J. Phys. A: Math. Theor.* 42, 025302, 2009.

Fig. 1. Schematics of the molecular complex junction. The Gaussian pulse has a central frequency equal to the donor gap (1.4 eV), a width of 30 fs and an amplitude of 1 eV.

Fig. 2. Molecular level structure and set of parameters. By-default configuration is given by: all inter-site couplings t_{ij} are equal to 0.2 eV (including coupling to reservoir Γ), and all gaps are equal to 1.4 eV.

Fig. 3. Molecular loop circuit. The four contributions to the energy current flowing from D_1 to A. Colored lines represent the inter-site couplings involved in each contribution.

Fig. 4. Time-resolved energy current as a function of the donor-donor coupling.

Fig. 5. Direct energy current as a function of the donor-donor coupling for two values of D-A coupling. All components of energy current are shown.

Fig. 6. Direct energy current as a function of the delay between the two femtosecond laser pulses for two D-D coupling values.

Fig. 7. Direct energy currents, J^E_{D1-A} , J^E_{D2-A} and their sum, as a function of the D₂-A coupling.

Fig. 8. Direct energy current as a function of the D-D coupling when sites D₂ and A are disconnected.

Schematics of inter-site couplings involved in the $J^{E(L)}$ component of J^E_{D2-A} .