Low phase noise cryogenic amplifiers and oscillators based on superconducting resonators

David Chaudy, Olivier Llopis, Bruno Marcilhac, Yves Lemaître, Olivier
d'Allivy Kelly, J.-M Hode

► To cite this version:

David Chaudy, Olivier Llopis, Bruno Marcilhac, Yves Lemaître, Olivier d'Allivy Kelly, et al.. Low phase noise cryogenic amplifiers and oscillators based on superconducting resonators. IEEE International Frequency Control Symposium (IFCS 2018), May 2018, Olympic Valley, CA, United States. 3p., 10.1109/FCS.2018.8597508 . hal-01868407

HAL Id: hal-01868407

<https://hal.science/hal-01868407>

Submitted on 5 Sep 2018

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Low phase noise cryogenic amplifiers and oscillators based on superconducting resonators

D. Chaudy^{1,3}, O. Llopis¹

¹LAAS-CNRS, Université de Toulouse, CNRS
7 avenue du Colonel Roche, 31031, Toulouse, France
dchaudy@laas.fr

B. Marcilhac², Y. Lemaitre², O. d'Allivy Kelly²

²Unité Mixte de Physique, CNRS, Thales, Paris-Sud
Université Paris-Saclay, 91767, Palaiseau, France

J.-M. Hode³

³Thales Defense Mission Systems
75-77 Avenue Marcel Dassault, 33700, Mérignac, France

Abstract—A cryogenic low phase noise amplifier and an high Q superconductor resonator at 1 GHz have been designed and realized. A good agreement between the measured and simulated data at 80 K for these two devices is observed. An all cryogenic oscillator has also been designed with the same devices on an alumina substrate. This oscillator is still under test.

Keywords— microwave oscillator, phase noise, superconductor resonator, cryoelectronics

I. INTRODUCTION

High Tc superconductor materials allows the design of ultra high Q resonators in the low microwave range. The design of an oscillator with these resonators requires an accurate modelling of the oscillating loop, which includes not only the resonator but also the transistor and the passive devices (capacitances, resistances, transmission lines). If the loop can be designed for an all-cryogenic operation, the oscillation stability will be increased. However, this is a hard task because any tuning of a device requires a time consuming process of cooling up and down the circuit. Therefore, the model of the loop elements at low temperature must be very accurate. If this step can be overcome, it could open the path to a disruptive technology. Indeed, the simulated phase noise results outperform the best commercially available 1 GHz sources, as presented in our previous work [1].

In a first step, we present the design of a low phase noise cryogenic amplifier. This device is easier to characterize than the closed oscillating loop, and allows us to understand the problems which may appear in the oscillator design. Then, the superconducting resonator characterization and modelling is described. The integrated cryogenic oscillator is currently under test but preliminary measurements show interesting results, with a phase noise level very close to the state of the art quartz based sources..

II. LOW TEMPERATURE AND PHASE NOISE AMPLIFIER

Designing a low phase noise amplifier has never been an easy task and the difficulty is enhanced when all the devices are at cryogenic temperature. Every device must be carefully

chosen and modelled. That is why, as presented in the last IFCS conference [1], characterization and modeling of SiGe transistors has been performed at 80 K. An amplifier has been designed on an alumina substrate using this model. Knowing that our final goal is the realization of an oscillator at 1 GHz, we focus our designs and measurements around this frequency.

We have thus designed a single stage amplifier using a common emitter bipolar SiGe transistor. In order to stabilize the amplifier and to optimize its residual phase noise, several resistances and capacitors have been added, particularly to realize two feedback paths: one series feedback on the emitter and one parallel feedback between base and collector. The amplifier topology is presented in Fig 1.

Fig. 1. 1 GHz cryogenic amplifier.

To characterize the circuit at cryogenic temperature, the amplifier has been partially immersed in liquid nitrogen. S-parameters and noise measurement have been performed both at ambient and low-temperature. A good agreement is observed between simulations and measurements, as shown in Fig 2 for S-parameters at 80 K. The amplifier residual phase noise has also been measured and is depicted in Fig 3. The measured phase noise floor is in the range of -170 dB_{rad}²/Hz and is very similar to the one simulated. However, an excess noise is observed close to the carrier (below 100 Hz) compared to the simulated 1/f phase noise level. This excess noise may be caused by vibrations and spurious signals. Indeed, the amplifier was not in a shielded housing at the time of the experiment.

Fig. 2. Amplifier simulated and measured S- parameters curves at $I_C = 5$ mA, $V_{CE} = 2$ V, $T = 80$ K.

Fig. 3. Amplifier simulated and measured 1 GHz phase noise at $I_C = 5$ mA, $V_{CE} = 2$ V, $T = 80$ K.

The next experimental step for the amplifier is to decrease the temperature down to 60K. Up to now, all the measurements have been performed using liquid nitrogen, at approximately 80K. The use of a cryocooler will allow us to reach 60 K. The experiment is ready as shown in Fig. 4 but measurement are still on-going.

Fig. 4. 1 GHz cryogenic amplifier on a coldfinger.

III. HIGH-TEMPERATURE SUPERCONDUCTOR RESONATOR

The other important part of oscillator is the resonator. In the past few years, Thales research on high-temperature superconductor has led to the development of planar resonators with quality factors in the range of 200 000 near 1 GHz. After the design of a test alumina for the resonator, we have measured its frequency response at 80 K (Table 1, 2 and Fig 5). Four interesting parameters can be extracted from those measurements: the loaded quality factor, which is 55700 at low microwave power, the input/output coupling factors and the transmission losses. From these parameters, the computed unloaded Q is 190000, as expected. A resonator model is then extracted. In a first step, a linear black box model has been used. Then, in a second step, an electrical RLC circuit coupled with two transformers has been implemented. This model allows us to include various nonlinear elements to take into account the RF power dependence of the resonator frequency response. Indeed, as depicted in Table 1 and 2, the insertion losses and the Q factor are degraded at high RF power. This is a well-known behavior in superconducting cavities [2,3], due to normal current generation at high current density. This behavior has first been described by a nonlinear resistor in the RLC circuit model (1). However, a distortion of the resonance can also be observed at high power. This effect is also discussed in some papers [3,4] and can be described by adding a non-linear inductor (2).

TABLE I. HTS-RESONATOR MEASURE CHARACTERISTICS

Input Power (dBm)	S_{21} -Max (dB)	Loaded Q	UnLoaded Q
-30	-3.7	55 700	190 000
-20	-3.7	55 500	190 000
-10	-4.2	51 000	160 000
0	-8.5	26 100	49 000

TABLE II. HTS-RESONATOR SIMULATED CHARACTERISTICS

Input Power (dBm)	S_{21} -Max (dB)	Loaded Q	UnLoaded Q
-30	-3.7	55 200	180 000
-20	-3.8	54 500	180 000
-10	-4.6	48 000	140 000
0	-8.4	26 700	49 000

Fig. 5. Transmission parameters of an HTS-Resonator at 80 K ($f_0 \sim 1$ GHz)

Fig. 6. Nonlinear HTS-resonator model

$$R = R_0(1 + \alpha I^2 + \beta I^4) \quad (1)$$

$$L = L_0(1 + \gamma I^2) \quad (2)$$

IV. OSCILLATOR

These two devices, amplifier and resonator, have been assembled to realize a cryogenic oscillator (Fig. 7). All the oscillator loop is cooled down to cryogenic temperature. The only part which is not cooled, is the battery based biasing network. For all the experimental investigations, the biasing network is kept outside the cryocooler in order to provide some tuning parameters. However, in the end, it will be included on the alumina substrate so that only one wire (to connect to the battery) and one SMA cable (the RF output) will go out of the cryocooler.

The first simulations on ADS software have led to a phase noise level close to -140 dBc/Hz at 1 kHz offset from 1 GHz carrier. The first experimental measurement, presented in Fig. 8, features an higher noise level than expected, close to -130 dBc/Hz at 1 kHz offset from carrier. After improving our model, the gap between simulation and measurement has been reduced (Fig. 8), but we still have to understand the increase of phase noise compared to the simulated one. One possible cause may be an excessive intra-cavity power in the resonator.

In any case, the oscillator performance can be improved using an higher Q resonator. A new resonator has thus been realized, featuring an higher loaded quality factor thanks to lower coupling factors and higher intrinsic Q, as presented in Table 3. For the moment, the modeling is still in process, but the use of this resonator may allow us to outperform the best commercially available 1 GHz sources.

Fig. 7. 1 GHz cryogenic oscillator

Fig. 8. Simulated and measured 1 GHz oscillator phase noise at 70 K. Comparison with two commercially available sources.

TABLE III. NEW HTS-RESONATOR MEASURED CHARACTERISTICS

Input Power (dBm)	S ₂₁ -Max (dB)	Loaded Q	UnLoaded Q
-30	-6.2	190 000	370 000
-20	-6.3	180 000	350 000
-10	-7.0	160 000	285 000
0	-9.4	105 000	160 000

V. CONCLUSION

Measurements and simulations of an amplifier and a superconductor resonator at 80 K have been presented. These devices have been assembled to realize a cryogenic oscillator. This circuit is, up to our knowledge, the first low phase noise full cryogenic oscillator at 1 GHz using superconductor resonators. The phase noise performance is good (-130 dBc/Hz at 1 kHz offset from 1 GHz carrier), even if we still do not reach exactly the state of the art of 1 GHz sources. Further improvements are expected thanks to a new resonator and some design improvements.

REFERENCES

- [1] D. Chaudy, O. Llopis, B. Marcilhac, Y. Lemaitre, O. d. Kelly and J. M. Hode, "Active devices choice and design of an all cryogenic superconductor resonator oscillator," *2017 EFTF and IEEE IFCS joint conference*, Besancon, 2017, pp. 842-845.
- [2] J. Kermorvant, PhD thesis (in french), Ecole Polytechnique, 2010.
- [3] D. E. Oates, S. H. Park, D. Agassi, G. Koren and K. Irgmaier, "Temperature dependence of intermodulation distortion in YBCO: understanding nonlinearity," in *IEEE Transactions on Applied Superconductivity*, vol. 15, no. 2, pp. 3589-3595, June 2005.
- [4] J. Wosik, L. M. Xie, R. Grabovickic, T. Hogan and S. A. Long, "Microwave power handling capability of HTS superconducting thin films: weak links and thermal effects induced limitation," in *IEEE Trans. on Applied Superconductivity*, vol. 9, no. 2, pp. 2456-2459, June 1999.