Analytic model of a resistive magnetohydrodynamic shock without Hall effect

Roland P.H. Berton

► To cite this version:

Roland P.H. Berton. Analytic model of a resistive magnetohydrodynamic shock without Hall effect. Journal of Fluid Mechanics, 2018, 842, pp.273-322. 10.1017/jfm.2018.90 . hal-01881613

HAL Id: hal-01881613

<https://hal.science/hal-01881613>

Submitted on 1 Jul 2019

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Analytic model of a resistive magnetohydrodynamic shock without Hall effect

Roland P.H. Berton

ONERA, Chemin de la Hunière, BP 80100, 91123 Palaiseau Cedex, France

An analytic model of a stationary hypersonic magnetohydrodynamic (MHD) shock with an externally applied magnetic field is proposed. Basically, original jump conditions at a plane oblique shock, analogous to the Rankine–Hugoniot formulae, with a moderately resistive air plasma downstream are derived. Viscous, thermal and Hall effects are neglected, but the plasma dissociation behind the shock causing a jump of isentropic exponent is also a major input of the model. Then a shock-fitting procedure with ambient atmospheric conditions is worked out by the coupling of these MHD jumps with thermodynamic correlations and an electric conductivity model. For an application to atmospheric entry problems, the flow behind an axisymmetric blunt-body shock is modelled with a stream function satisfying these MHD jump conditions as boundary conditions. An important feature put into evidence is a similarity rule involving the hypersonic parameter $M_1 \cos \chi_1$ which shows an aerodynamic correspondence between the upstream Mach number M_1 and the velocity angle χ_1 . It also emerges that curvature effects become important past 30° and the assumption of spherical shock also becomes untenable past 50° ; therefore, we limit the model of shock thickness used in the MHD fitting to $\chi_1 < 50^\circ$.

Key words: magnetohydrodynamics, plasmas, shock waves

1. Introduction

The magnetohydrodynamic (MHD) interaction of an ionized flow with a magnetized body moving in the atmosphere at a hypersonic speed was modelled as early as the 1950s, initiated with theoretical approaches (Bush 1958; Lévy 1963; Levy & Petschek 1963; Jarvinen 1965) and afterwards complemented by numerical simulations stimulated by space flight and atmospheric entry problems (signal blackout, wall heating, drag monitoring...). Numerical resolution of the Euler equations for the aerodynamic blunt-body problem at supersonic speeds was developed in the 1960s (Moretti & Abbett 1966; Moretti & Bleich 1967; Rusanov 1976), soon followed by numerical resolution of the MHD equations (Coackley & Porter 1971), and has reached a high level of accuracy.

Nevertheless, analytical tools presently in development have renewed the understanding of phenomena and proved the necessity of a complementary approach to cope with non-linear problems (Maicke, Barber & Majdalani 2010). Moreover, system models require the instantaneous calculation of forces and heat fluxes along trajectories. Therefore, the analytic approach of the present paper, extending the classical Rankine–Hugoniot relations (Rankine 1870; Hugoniot 1889), opens a prospect towards MHD shock fitting as an alternative to the shock-capturing approach broadly used in the many numerical models published and in progress. The respective advantages and drawbacks of shock fitting over shock capturing have been recently pointed out in aerodynamic applications (Moretti 2002; Bonfiglioli & Paciorri 2010; Pepe *et al.* 2014).

In ideal MHD problems, frequently solved in various media, it is assumed that the electrical conductivity of the flowing medium is infinite – or, more accurately, the magnetic Reynolds number is infinite. This greatly simplifies the equations and, in solar physics for instance, enables one to eliminate the electric field. Owing to the large volumes involved, the magnetic Reynolds number is actually very large ($\sim 10^5$) and causes the magnetic field to evolve, producing dynamo effects, for instance in solar active regions (Priest 1987, chap. 5; Berton 2000).

In the present case of re-entry MHD problems, the conductivity is also finite, but the small volumes involved do not allow one to eliminate the electric field and let an applied magnetic field persist, since the magnetic Reynolds number is very small ($\sim 10^{-3}$), so that the steady state can therefore be considered as a first approach. Moreover, symmetry considerations lead one to set the electrostatic field to zero. We shall assume a finite conductivity and derive in the next section the original jump equations.

First, an oblique MHD shock with real gas effects due to air dissociation will be considered. In this first task, viscous and thermal effects, as well as the Hall effect arising when the electric conductivity becomes a tensor (at altitudes above 50 km), have been neglected (Levy 1963; Ericson & Maciulaitis 1964). The expressions thus obtained are compared with the existing hydrodynamic Rankine–Hugoniot formulae, which are also usually derived without viscous and thermal effects but also without jump of the isentropic exponent. As will be shown, the jump expressions depend not only on the usual hydrodynamic ratio ε of mass densities, but also on a new MHD parameter, denoted η , acting as a bending parameter of streamlines. Because of the ionizing action of the shock, the electric conductivity is assumed to be zero ahead of the shock.

In § 3, test cases are examined in order to check the jump equations for a plane shock in simple configurations. For this purpose, we make use of existing thermodynamic models of dissociated air and work out a shock-fitting method with the isentropic exponent. The problems arising from the assumptions are put into evidence, in parallel with aerodynamic situations. An important similarity rule is put into evidence and is confirmed in § 5.

In § 4, as an application, we describe the procedure of a detached spherical shock fitting, and for this purpose make use of the same models of dissociated air and a model of conductivity. The fitting procedure is extended to other parameters (conductivity, shock distance and thickness). The MHD results are compared with hydrodynamic solutions for the physical conditions at two altitudes along a re-entry trajectory.

In § 5, a simplified model of the flow behind the shock produced by a blunt body is proposed on the basis of stream functions matched with the corresponding one ahead of the shock and taking into account MHD and real gas effects. We consider a rotational flow taking into account a vorticity jump at the shock. Shock stand-off is estimated and compared with existing models. The overall approach is depicted in figure 1.

The similarity rule put into evidence in § 3, involving the hypersonic parameter $M_1 \cos \chi_1$, shows a correspondence between the upstream Mach number M_1 and the velocity angle χ_1 . The model of shock thickness used appears to be limited to $\chi_1 < 50^\circ$.

In § 6, an assessment of the re-entry application is proposed. Magnetohydrodynamic effects inside the shock are compared with MHD effects in the shock layer.

Conclusions and prospects for trajectories in re-entry problems are discussed in the final section. The validity of our approximations is examined, and justifications and remedies are proposed. Notations used throughout the paper are defined in table 1.

2. Resistive MHD jump conditions

2.1. Basic equations

Let us consider a stationary plane oblique shock in a flow moving from left to right (figure 2). In the following sections, subscripts 1 and 2 respectively denote quantities ahead of the shock (upstream) and behind it (downstream). In hydrodynamics, the classical Rankine–Hugoniot relations giving the pressure and density ratios through such a shock are well known and are written respectively for a perfect gas with a constant isentropic exponent γ (Hugoniot 1889) as

$$\frac{p_2}{p_1} = \frac{2\gamma M_1^2 \cos^2 \chi_1 - (\gamma - 1)}{\gamma + 1}, \quad \frac{\rho_2}{\rho_1} = \frac{(\gamma + 1) M_1^2 \cos^2 \chi_1}{(\gamma - 1) M_1^2 \cos^2 \chi_1 + 2}. \quad (1a,b)$$

The normal shock is retrieved when $\chi_1 = 0$. The hypersonic hydrodynamic shock relations are obtained as $M_1 \rightarrow +\infty$

$$\frac{p_2}{p_1} \approx \frac{2\gamma M_1^2 \cos^2 \chi_1}{\gamma + 1}, \quad \frac{\rho_2}{\rho_1} = \frac{\gamma + 1}{\gamma - 1}. \quad (2a,b)$$

The angle χ_2 of the downstream velocity satisfies the equation

$$\tan \chi_2 = \frac{\rho_2}{\rho_1} \tan \chi_1. \quad (3)$$

It is important to notice that for a physically acceptable shock, we must have $p_2/p_1 > 0$, and this implies that χ_1 must be smaller than a critical angle χ_{1c} solution of the equation

$$\cos \chi_{1c} = \frac{1}{M_1} \sqrt{\frac{\gamma - 1}{2\gamma}}. \quad (4)$$

For a perfect gas with $\gamma = 1.4$ and at a hypersonic speed $M_1 = 20$, this gives a critical angle $\chi_{1c} = 88.9^\circ$.

In order to derive the resistive MHD jump conditions, let us write, in the frame of the moving body (and ambient air at rest), the partial differential equations expressing on one hand the conservation of mass, momentum and energy (Sutton & Sherman 2006),

$$\left\{ \begin{array}{l} \frac{\partial}{\partial x}(\rho u) + \frac{\partial}{\partial y}(\rho v) = 0, \\ \rho u \frac{\partial u}{\partial x} = -\frac{\partial p}{\partial x} + \frac{\partial}{\partial x} \left(\frac{4}{3} \mu \frac{\partial u}{\partial x} \right) - \sigma(E + uB \sin \chi_b - vB \cos \chi_b)B \sin \chi_b, \\ \rho u \frac{\partial v}{\partial x} = -\frac{\partial p}{\partial y} + \frac{\partial}{\partial x} \left(\frac{4}{3} \mu \frac{\partial v}{\partial x} \right) + \sigma(E + uB \sin \chi_b - vB \cos \chi_b)B \cos \chi_b, \\ \rho u \frac{\partial}{\partial x} \left(h + \frac{u^2 + v^2}{2} \right) = \frac{\partial}{\partial x} \left(\frac{4}{3} \mu u \frac{\partial u}{\partial x} + \frac{4}{3} \mu v \frac{\partial v}{\partial x} \right) + \sigma(E + uB \sin \chi_b - vB \cos \chi_b)E, \end{array} \right. \quad (5)$$

and on the other hand Maxwell's equations (Sutton & Sherman 2006),

$$\left\{ \begin{array}{l} \frac{\partial}{\partial x}(B \cos \chi_b) + \frac{\partial}{\partial y}(B \sin \chi_b) = 0, \\ \frac{\partial}{\partial x}(B \sin \chi_b) - \frac{\partial}{\partial y}(B \cos \chi_b) = 0, \\ \frac{\partial}{\partial z}(B \sin \chi_b) = 0, \\ \frac{\partial}{\partial z}(B \cos \chi_b) = 0, \end{array} \right. \quad (6)$$

with

$$E = -\frac{\partial \phi}{\partial z}, \quad J = \sigma(E + uB \sin \chi_b - vB \cos \chi_b), \quad h = \frac{\gamma}{\gamma - 1} \frac{p}{\rho}. \quad (7a-c)$$

The vectors $\mathbf{V}$ and $\mathbf{B}$ define the figure plane, and u, v denote velocity components along axes x and y , respectively normal and tangent to the shock. The vectors $\mathbf{E}$ and $\mathbf{J}$ are perpendicular to this plane. The relation defining the electric current J in (7) expresses Ohm's law. Notations are otherwise defined in the nomenclature (table 1).

The property of invariance assumed along y and z implies that

$$E = 0, \quad J = \sigma(uB \sin \chi_b - vB \cos \chi_b), \quad \frac{\partial B}{\partial z} = 0, \quad \frac{\partial \chi_b}{\partial z} = 0. \quad (8a-d)$$

This leads to recasting system (5) into the following system of ordinary differential equations:

$$\left\{ \begin{array}{l} \frac{d}{dx}(\rho u) = 0, \\ \rho u \frac{du}{dx} = -\frac{dp}{dx} + \frac{d}{dx} \left(\frac{4}{3} \mu \frac{du}{dx} \right) - \sigma B^2 (u \sin \chi_b - v \cos \chi_b) \sin \chi_b, \\ \rho u \frac{dv}{dx} = \frac{d}{dx} \left(\frac{4}{3} \mu \frac{dv}{dx} \right) + \sigma B^2 (u \sin \chi_b - v \cos \chi_b) \cos \chi_b, \\ \rho u \frac{d}{dx} \left(\frac{\gamma}{\gamma-1} \frac{p}{\rho} + \frac{u^2 + v^2}{2} \right) = \frac{d}{dx} \left(\frac{4}{3} \mu u \frac{du}{dx} + \frac{4}{3} \mu v \frac{dv}{dx} \right), \\ \frac{d}{dx}(B \cos \chi_b) = 0, \\ \frac{d}{dx}(B \sin \chi_b) = 0. \end{array} \right. \quad (9)$$

Now, integration of the differential system (9) across the shock with discontinuous γ and σ yields

$$\left\{ \begin{array}{l} [\rho u] = 0, \\ [mu + p] = \left[\frac{4}{3} \mu \frac{du}{dx} \right] - B^2 \sin \chi_b \left(\sin \chi_b \int_{x_1}^{x_2} \sigma u dx - \cos \chi_b \int_{x_1}^{x_2} \sigma v dx \right), \\ [mv] = \left[\frac{4}{3} \mu \frac{dv}{dx} \right] + B^2 \cos \chi_b \left(\sin \chi_b \int_{x_1}^{x_2} \sigma u dx - \cos \chi_b \int_{x_1}^{x_2} \sigma v dx \right), \\ m \left[\frac{\gamma}{\gamma-1} \frac{p}{\rho} + \frac{V^2}{2} \right] = \left[\frac{4}{3} \mu u \frac{du}{dx} + \frac{4}{3} \mu v \frac{dv}{dx} \right], \\ [B] = 0, \\ [\chi_b] = 0, \end{array} \right. \quad (10a-f)$$

where we have defined the normal mass flux m as

$$m = \rho_1 u_1 = \rho_2 u_2. \quad (11)$$

Consistently with the assumption of very small magnetic Reynolds number ($R_m \sim 10^{-3}$), the equations (10e) and (10f) show that the magnetic field is continuous across the shock. Moreover, the magnetic contribution to the energy equation is zero because the transverse electric field E , causing the Joule effect, is zero.

Then, if we consider that the medium is stationary before and behind the shock, the velocity derivatives might be assumed to vanish at the front side and the back side of the shock, so that the viscous jumps are removed from the momentum and energy equations. This situation is similar to that occurring in the derivation of the Rankine–Hugoniot relations.

2.2. Derivation of the jump equations

In order to integrate magnetic terms, let us now express the velocity component u by means of the mass continuity equation in the system (5),

$$u = -\rho \left(\frac{\partial \rho}{\partial x} \right)^{-1} \frac{\partial u}{\partial x}, \quad (12)$$

wherever the mass density derivative is not zero, and define the characteristic length scale of density $\mathcal{L}_\rho$ such that

$$\frac{1}{\mathcal{L}_\rho} = \frac{1}{\rho} \frac{\partial \rho}{\partial x}. \quad (13)$$

On inserting this into (12), we obtain

$$u = -\mathcal{L}_\rho \frac{\partial u}{\partial x}, \quad (14)$$

and likewise for the velocity component v , by defining a characteristic length scale $\mathcal{L}_v$, we assume that

$$v = \mathcal{L}_v \frac{\partial v}{\partial x}. \quad (15)$$

The plus sign in this case is justified by the fact that the transverse component of the velocity increases through the shock. The length scale $\mathcal{L}_\rho$ is of the order of the mean free path ℓ of particles inside the shock. We shall assume that $\mathcal{L}_\rho$ and $\mathcal{L}_v$ are constant within the shock and we shall later derive an expression for $\mathcal{L}_\rho$. It should be noted that the above formalism is equivalent to a first-order expansion of velocity components. Following the same formalism, we also assume that the same relation holds for the electrical conductivity,

$$\sigma = \mathcal{L}_\sigma \frac{\partial \sigma}{\partial x}, \quad (16)$$

with a plus sign, since the conductivity increases across the shock in our problem. We shall derive an estimate for $\mathcal{L}_\sigma$ in § 2.4.

First, we derive the following relations by integrating the integrals by parts and using (14), (15) and (16):

$$\begin{cases} \int_{x_1}^{x_2} \frac{\partial}{\partial x} (\sigma u) dx = \left(-\frac{1}{\mathcal{L}_\rho} + \frac{1}{\mathcal{L}_\sigma} \right) \int_{x_1}^{x_2} \sigma u dx, \\ \int_{x_1}^{x_2} \frac{\partial}{\partial x} (\sigma v) dx = \left(\frac{1}{\mathcal{L}_v} + \frac{1}{\mathcal{L}_\sigma} \right) \int_{x_1}^{x_2} \sigma v dx. \end{cases} \quad (17)$$

Then, defining the compound length scales

$$\begin{cases} \frac{1}{\mathcal{L}_{\rho\sigma}} = \frac{1}{\mathcal{L}_\sigma} - \frac{1}{\mathcal{L}_\rho}, \\ \frac{1}{\mathcal{L}_{v\sigma}} = \frac{1}{\mathcal{L}_\sigma} + \frac{1}{\mathcal{L}_v}, \end{cases} \quad (18)$$

we obtain the desired jumps from (17),

$$\begin{cases} \int_{x_1}^{x_2} \sigma u dx = \mathcal{L}_{\rho\sigma}[\sigma u], \\ \int_{x_1}^{x_2} \sigma v dx = \mathcal{L}_{v\sigma}[\sigma v]. \end{cases} \quad (19)$$

Considering from the equations (10e) and (10f) that the magnetic field is continuous, and consequently B_2 and χ_{b2} are no longer unknowns,

$$\begin{cases} B_2 = B_1 = B, \\ \chi_{b2} = \chi_{b1} = \chi_b, \end{cases} \quad (20)$$

the system (10) reduces to the set

$$\begin{cases} \rho_1 u_1 = \rho_2 u_2 = m, \\ m[u] + [p] = -B^2 \sin \chi_b (\mathcal{L}_{\rho\sigma} \sin \chi_b [\sigma u] - \mathcal{L}_{v\sigma} \cos \chi_b [\sigma v]), \\ m[v] = B^2 \cos \chi_b (\mathcal{L}_{\rho\sigma} \sin \chi_b [\sigma u] - \mathcal{L}_{v\sigma} \cos \chi_b [\sigma v]), \\ m \left[\frac{\gamma}{\gamma-1} \frac{p}{\rho} + \frac{u^2 + v^2}{2} \right] = 0. \end{cases} \quad (21a-d)$$

This is a nonlinear system of four equations for four unknowns, namely ρ_2 , p_2 , u_2 , v_2 , depending on five parameters, namely γ_2 , σ_2 , B , $\mathcal{L}_{\rho\sigma}$, $\mathcal{L}_{v\sigma}$. We notice that the tangential component v of velocity is not continuous in general, except in the case of a pure hydrodynamic shock ($B = 0$) or a perpendicular shock ($\chi_b = \pi/2$).

From the system (21) with jumps of γ and σ , we obtain

$$\begin{cases} \rho_1 u_1 = \rho_2 u_2 = m, \\ m(u_1 - u_2) + B^2 \sin \chi_b \{ \mathcal{L}_{\rho\sigma} \sin \chi_b (\sigma_1 u_1 - \sigma_2 u_2) - \mathcal{L}_{v\sigma} \cos \chi_b (\sigma_1 v_1 - \sigma_2 v_2) \} + p_1 - p_2 = 0, \\ m(v_1 - v_2) - B^2 \cos \chi_b \{ \mathcal{L}_{\rho\sigma} \sin \chi_b (\sigma_1 u_1 - \sigma_2 u_2) - \mathcal{L}_{v\sigma} \cos \chi_b (\sigma_1 v_1 - \sigma_2 v_2) \} = 0, \\ \left(\frac{\gamma_1}{\gamma_1-1} \frac{p_1}{\rho_1} - \frac{\gamma_2}{\gamma_2-1} \frac{p_2}{\rho_2} \right) + \frac{u_1^2 - u_2^2}{2} + \frac{v_1^2 - v_2^2}{2} = 0. \end{cases} \quad (22a-d)$$

For standard clear sky atmospheric conditions, we shall assume that $\sigma_1 = 0$ and $\sigma_2 \neq 0$, since the ambient conductivity is very low because of the scarce dissociation or ionization of air in the lower stratosphere ($\approx 10^{-6}$ S m⁻¹ at 65 km) (Tran & Polk 1979a,b). On the other hand, the gas before the shock (non-dissociated air) and the air plasma behind it (dissociated air) are supposed to be perfect gases, but with different molar masses and specific heats; therefore, they are supposed to have different isentropic exponents γ_1 and γ_2 . Let us now define the interaction parameters

$$\begin{cases} S_{\rho\sigma} = \frac{\sigma_2 B^2 \mathcal{L}_{\rho\sigma}}{m}, \\ S_{v\sigma} = \frac{\sigma_2 B^2 \mathcal{L}_{v\sigma}}{m}. \end{cases} \quad (23)$$

From the two equations of momentum conservation (22b) and (22c), we obtain the velocity components u_2 and v_2 behind the shock

$$\begin{cases} u_2 = a \left(u_1 + \frac{p_1 - p_2}{m} \right) + b v_1 \\ v_2 = c \left(u_1 + \frac{p_1 - p_2}{m} \right) + d v_1 \end{cases} \quad (24a,b)$$

with the coefficients a, b, c, d defined by

$$\left\{ \begin{array}{l} a = \frac{1 + S_{v\sigma} \cos^2 \chi_b}{1 + S_{\rho\sigma} \sin^2 \chi_b + S_{v\sigma} \cos^2 \chi_b}, \\ b = \frac{S_{v\sigma} \sin \chi_b \cos \chi_b}{1 + S_{\rho\sigma} \sin^2 \chi_b + S_{v\sigma} \cos^2 \chi_b}, \\ c = \frac{S_{\rho\sigma} \sin \chi_b \cos \chi_b}{1 + S_{\rho\sigma} \sin^2 \chi_b + S_{v\sigma} \cos^2 \chi_b}, \\ d = \frac{1 + S_{\rho\sigma} \sin^2 \chi_b}{1 + S_{\rho\sigma} \sin^2 \chi_b + S_{v\sigma} \cos^2 \chi_b}. \end{array} \right. \quad (25)$$

After some algebra, we derive the following relationship between the pressure and mass density ratios:

$$\frac{\rho_1}{\rho_2} = a + b \tan \chi_1 + \frac{a}{\gamma_1 M_1^2 \cos^2 \chi_1} \left(1 - \frac{p_2}{p_1} \right), \quad (26)$$

where M_1 stands for the upstream Mach number,

$$M_1 = \frac{V_1}{c_{s1}}, \quad c_{s1} = \sqrt{\frac{\gamma_1 p_1}{\rho_1}}. \quad (27a,b)$$

We noticed that the modified Rankine–Hugoniot equations were derived for a normal shock by a simple average of the magnetic force within the shock thickness without a jump of γ (Saeks & Murray 2003). As the purpose of this analysis is the influence of Ohmic dissipation, $E \neq 0$ has been kept in (5). However, the shock thickness is also involved in the model, and it is estimated as being six times the mean free path ℓ_1 (see § 2.4 below).

2.3. Simplification

In order to make calculations more straightforward, we make here an important simplification based on a theoretical argument. As shown by non-standard analysis of a one-dimensional shock, pressure and velocity have approximately the same depth variations through the shock (Salas & Iollo 1996). This might suggest that the scale lengths of mass density and velocity components are all equal, and so we may assume that

$$\mathcal{L}_v \approx \mathcal{L}_p, \quad (28)$$

which implies that for characteristic length scales (18)

$$\left\{ \begin{array}{l} \frac{1}{\mathcal{L}_{u\sigma}} = \frac{1}{\mathcal{L}_\sigma} - \frac{1}{\mathcal{L}_\rho}, \\ \frac{1}{\mathcal{L}_{v\sigma}} = \frac{1}{\mathcal{L}_\sigma} + \frac{1}{\mathcal{L}_\rho}. \end{array} \right. \quad (29)$$

Appendix A is devoted to the derivation of $\mathcal{L}_\sigma$.

2.4. Estimate of $\mathcal{L}_\rho$

Since $\mathcal{L}_\rho$ is a key parameter in our model, we derive an analytic formula for this quantity, assimilated to the shock thickness. A usual rough estimate of the aerodynamic shock

thickness is provided by the mean free path ℓ_1 ahead of the shock, expressed as (Shapiro 1953; Hayes & Probstein 1959)

$$\ell_1 = \frac{\nu_1}{c_{s1}}, \quad (30)$$

where ν_1 denotes the kinetic viscosity (not to be confused with the ν component of velocity), and c_{s1} the sound speed in the vicinity ahead of the shock. By equating the shear and normal stresses, another calculation leads to the expression (Zel'dovich & Raizer 1967)

$$\ell'_1 = \frac{\nu_1}{V_1}, \quad (31)$$

which is obviously much smaller than the former one, since in supersonic conditions $V_1/c_{s1} = M_1 \gg 1$. In appendix B, we derive a more appropriate formula taking into account the variations of the viscosity in the shock,

$$\mathcal{L}_0 = \frac{2}{3} \frac{3\mu_2 - \mu_1}{m}, \quad (32)$$

and we shall adopt this scale as $\mathcal{L}_\rho$. It should be noted that m is the mass flow rate normal to the shock, as defined by (11) or (49), which is a function of the incidence angle χ_1 . As the viscosity term is neglected in our jump derivation in § 2.2, we neglected the influence of the magnetic field on the shock thickness.

2.5. Summary and discussion

After some algebra, we finally obtain the following relations for an oblique shock with a real gas, with discontinuous isentropic exponent γ and electric conductivity σ across the shock, and without viscous, thermal or Hall effects. By eliminating the mass density ratio in (22), we obtain for the pressure ratio p_2/p_1 the quadratic equation

$$A_2 X^2 + 2A_1 X + A_0 = 0, \quad (33)$$

where we have defined the coefficients

$$\left\{ \begin{array}{l} A_2 = \frac{1}{\gamma_1 M_1^2 \cos^2 \chi_1} \left(a^2 + c^2 - 2 \frac{\gamma_2}{\gamma_2 - 1} a \right), \\ A_1 = \frac{\gamma_2}{\gamma_2 - 1} \left(a + b \tan \chi_1 - \frac{a}{\gamma_1 M_1^2 \cos^2 \chi_1} \right) - (a^2 + c^2) - (ab + cd) \tan \chi_1, \\ A_0 = \gamma_1 M_1^2 \left[\left\{ (a + b \tan \chi_1)^2 + (c + d \tan \chi_1)^2 \right\} \cos^2 \chi_1 - 1 \right] \\ \quad + 2 \frac{\gamma_2}{\gamma_2 - 1} (a + b \tan \chi_1) - 2 \frac{\gamma_1}{\gamma_1 - 1} \end{array} \right. \quad (34)$$

and the unknown X ,

$$X = \frac{p_2}{p_1} - 1. \quad (35)$$

Provided that the discriminant is positive, the real solutions are written as

$$X = \frac{-A_1 \pm \sqrt{A_1^2 - A_0 A_2}}{A_2}. \quad (36)$$

The minus solution ('-' in ' $\pm$ ') is chosen for the sake of continuity with the non-magnetic case as $B \rightarrow 0$ (see below in § 3.1).

Likewise, for the mass density ratio ρ_2/ρ_1 , by eliminating the pressure ratio in (22), we obtain the quadratic equation

$$A_2 Y^2 + 2A_1 Y + A_0 = 0, \quad (37)$$

with the coefficients

$$\begin{cases} A_2 = \frac{2\gamma_1}{\gamma_1 - 1} - \left(d - \frac{bc}{a}\right)^2 \gamma_1 M_1^2 \sin^2 \chi_1 + \gamma_1 M_1^2, \\ A_1 = -\left[\frac{\gamma_2}{\gamma_2 - 1} \left\{ 1 + \left(1 + \frac{b}{a} \tan \chi_1\right) \gamma_1 M_1^2 \cos^2 \chi_1 \right\} + \left(d - \frac{bc}{a}\right) \frac{c}{a} \gamma_1 M_1^2 \sin \chi_1 \cos \chi_1 \right], \\ A_0 = \left(\frac{2\gamma_2}{\gamma_2 - 1} \frac{1}{a} - 1 - \frac{c^2}{a^2} \right) \gamma_1 M_1^2 \cos^2 \chi_1 \end{cases} \quad (38)$$

and the unknown Y , which is the compression ratio

$$Y = \frac{\rho_2}{\rho_1}. \quad (39)$$

Provided that the discriminant is positive, the real solutions are written as

$$Y = \frac{-A_1 \pm \sqrt{A_1^2 - A_0 A_2}}{A_2}. \quad (40)$$

Here, the plus solution ('+' in ' $\pm$ ') must be chosen for continuity with the non-magnetic case as $B \rightarrow 0$ (see below in § 3.1).

It is fundamental to remark that (33) and (38) are not independent. Actually, from (26), we derive the compatibility relation

$$\frac{p_2}{p_1} - 1 = \frac{\gamma_1 M_1^2 \cos^2 \chi_1}{a} (a + b \tan \chi_1 - \varepsilon). \quad (41)$$

For the velocity angle χ_2 , we get the equation

$$\tan \chi_2 = \frac{c}{a} + \left(d - \frac{bc}{a}\right) \frac{\rho_2}{\rho_1} \tan \chi_1, \quad (42)$$

with the four constants a , b , c , d defined by (25), which depend on the magnetic field angle χ_b and the interaction parameters $S_{\rho\sigma}$ and $S_{v\sigma}$ defined by (128). These parameters are based on the scale lengths $\mathcal{L}_{\rho\sigma}$ and $\mathcal{L}_{v\sigma}$ (127). The key parameter is the ratio ω , described by the formula (143), in which α is the exponent of relation (130). We can write (42) quite simply as

$$\frac{\tan \chi_2}{\tan \chi_1} = \frac{\eta}{\varepsilon}, \quad (43)$$

using the definition of the usual ratio ε (Hayes & Probstein 1959)

$$\varepsilon = \frac{\rho_1}{\rho_2} \quad (44)$$

and defining the magnetic parameter η ,

$$\eta = d - \frac{bc}{a} + \frac{c}{a} \varepsilon \cot \chi_1. \quad (45)$$

It is usual to notice that (43) looks like a refraction law for streamlines through the shock considered as a dioptré – except that it relates tangents instead of sines – and shows that η acts as a bending factor, compensating the effect of the mass density ratio ε . By using the definitions (25), η can be recast into the form

$$\eta = \frac{1 + \varepsilon S_{\rho\sigma} \sin \chi_b \cos \chi_b \cot \chi_1}{1 + S_{v\sigma} \cos^2 \chi_b}. \quad (46)$$

We also derive the following relation between the two velocity amplitudes V_1 and V_2 :

$$\frac{V_2}{V_1} = \sqrt{\eta^2 \sin^2 \chi_1 + \varepsilon^2 \cos^2 \chi_1}, \quad (47)$$

which is perfectly symmetric with respect to ε and η . The downstream Mach number M_2 can be expressed in the form

$$\gamma_2 M_2^2 \cos^2 \chi_2 = a \frac{\frac{p_1}{p_2} - 1}{1 - \frac{a + b \tan \chi_1}{\varepsilon}}. \quad (48)$$

It should be noted that the normal mass flow rate (11) depends on the shock angle

$$m = \rho_1 V_1 \cos \chi_1. \quad (49)$$

Therefore, equations (37) and (34) basically depend on a set of six parameters, four of them being of purely aerodynamic origin, namely M_1 , χ_1 , γ_1 , γ_2 , and two of MHD origin, namely S_ρ and χ_b . It can be noticed that in the absence of magnetic field ($S_\rho = 0$, $a = d = 1$, $b = c = 0$), we obtain $\eta = 1$, and (42) reduces to the hydrodynamic equation (3), and (47) alike.

In the following sections, we shall work out a fitting procedure for the air plasma behind the shock and apply the above jump relations

- (i) to a plane oblique hypersonic shock, for various relative configurations of $\mathbf{V}$ and $\mathbf{B}$, at different Mach numbers M_1 and fixed values of S_ρ ;
- (ii) to the curved detached shock formed ahead of the nose of a blunt body moving at hypersonic speed, at different angles χ_1 and using the dipolar magnetic field created by a magnet located beneath the nose.

3. Application to plane shock fitting

3.1. Theoretical considerations

3.1.1. Non-magnetic case

In this hydrodynamic situation ($B_0 = 0$, $S_\rho = 0$, $a = d = 1$, $b = c = 0$, $\eta = 1$) we put into evidence basic features of the equations and limits which may be different from those usually encountered for a perfect gas. For the pressure ratio p_2/p_1 we obtain from (33) and (34) the quadratic equation

$$-\frac{\gamma_2 + 1}{\gamma_2 - 1} X^2 + \frac{2}{\gamma_2 - 1} (\gamma_1 M_1^2 \cos^2 \chi_1 - \gamma_2) X - 2 \left(\frac{\gamma_1}{\gamma_1 - 1} - \frac{\gamma_2}{\gamma_2 - 1} \right) \gamma_1 M_1^2 \cos^2 \chi_1 = 0, \quad (50)$$

where the minus solution ('-' in ' $\pm$ ') should be kept in (36). Likewise, for the mass density ratio we obtain from (37) and (38) the quadratic equation

$$\gamma_1 \left(\frac{2}{\gamma_1 - 1} + M_1^2 \cos^2 \chi_1 \right) Y^2 - \frac{2\gamma_2}{\gamma_2 - 1} (1 + \gamma_1 M_1^2 \cos^2 \chi_1) Y + \frac{\gamma_2 + 1}{\gamma_2 - 1} \gamma_1 M_1^2 \cos^2 \chi_1 = 0, \quad (51)$$

where the plus solution ('+' in ' $\pm$ ') should be kept in (40). It should be noted that even in non-magnetic aerodynamics, our model shows an improvement over the classical perfect-gas relations (1) since it involves the isentropic exponent γ_2 behind the shock and takes real gas effects due to air dissociation into account.

The reduced discriminant of the pressure equation (50) multiplied by $\gamma_2 - 1$ is written as

$$\Delta_x = (\gamma_1 M_1^2 \cos^2 \chi_1 - \gamma_2)^2 - 2(\gamma_1 - \gamma_2) \frac{\gamma_2 + 1}{\gamma_1 - 1} \gamma_1 M_1^2 \cos^2 \chi_1, \quad (52)$$

and the solutions take the form

$$\frac{p_2}{p_1} = 1 - \frac{-(\gamma_1 M_1^2 \cos^2 \chi_1 - \gamma_2) \pm \sqrt{\Delta_x}}{\gamma_2 + 1}. \quad (53)$$

Likewise, the reduced discriminant of the density equation (51) multiplied by $\gamma_2 - 1$ is written as

$$\Delta_y = \left(\frac{2\gamma_1}{\gamma_1 - 1} + \gamma_1 M_1^2 \cos^2 \chi_1 - \frac{\gamma_1 + 1}{\gamma_1 - 1} \gamma_2^2 \right) \gamma_1 M_1^2 \cos^2 \chi_1, \quad (54)$$

and the solutions take the form

$$\frac{\rho_2}{\rho_1} = \frac{\gamma_2 (1 + \gamma_1 M_1^2 \cos^2 \chi_1) \pm \sqrt{\Delta_y}}{(\gamma_2 - 1) \left(\frac{2\gamma_1}{\gamma_1 - 1} + \gamma_1 M_1^2 \cos^2 \chi_1 \right)}. \quad (55)$$

Like for the Rankine–Hugoniot relations (1), we can show, after some algebra, that the condition of positive pressure ($p_2 > 0$) yields a critical angle χ_{1c} solution of the equation

$$\cos \chi_{1c} = \frac{1}{M_1} \sqrt{\frac{\gamma_1 - 1}{2\gamma_1}}, \quad (56)$$

equivalent to (4) for a perfect gas. Actual values of $\gamma_1 = 1.4$ and $M_1 = 20$ yield a critical angle of $\chi_{1c} \approx 89^\circ$. This means that in the hypersonic case our model cannot be used for $\chi_1 > 89^\circ$.

The fundamental relationship (41) between the pressure and the mass density ratios simplifies here as

$$\frac{p_2}{p_1} - 1 = \gamma_1 M_1^2 \cos^2 \chi_1 \left(1 - \frac{\rho_1}{\rho_2} \right). \quad (57)$$

After these general considerations, we shall detail the following sub-cases.

(i) In the hypersonic limit, $M_1 \rightarrow +\infty$, equivalent to $\chi_1 = 0$ for a re-entry trajectory ($M_1 \gg 1$), we obtain from (52) and (53) a kind of hypersonic solution

$$\frac{p_2}{p_1} \approx \frac{2\gamma_1 M_1^2}{\gamma_2 + 1} \quad (58)$$

and

$$\frac{\rho_2}{\rho_1} = \frac{\gamma_2 + 1}{\gamma_2 - 1}. \quad (59)$$

These relations reduce to the Rankine–Hugoniot equations (2) when $\gamma_1 = \gamma_2 = \gamma$. With $M_1 = 21.7$, $\gamma_1 = 1.4$ and $\gamma_2 = 1.15$ at 40 km, these relations yield the values $X = 613$ and $Y = 14.3$.

(ii) In the quasitangential shock limit, $\chi_1 \rightarrow 90^\circ$, equivalent to $M_1 = 0$, we obtain

$$X\{(\gamma_2 + 1)X + 2\gamma_2\} = 0 \quad (60)$$

and

$$Y\left(\frac{2\gamma_1}{\gamma_1 - 1}Y - \frac{2\gamma_2}{\gamma_2 - 1}\right) = 0, \quad (61)$$

and, apart from the trivial solutions ($X = 0$ and $Y = 0$), we recover the solutions

$$\frac{p_2}{p_1} = -\frac{\gamma_2 - 1}{\gamma_2 + 1} \quad (62)$$

and

$$\frac{\rho_2}{\rho_1} = \frac{\gamma_1 - 1}{\gamma_1} \frac{\gamma_2}{\gamma_2 - 1}. \quad (63)$$

With $\gamma_1 = 1.4$ and $\gamma_2 = 1.15$, these relations yields the values $X = -1.07$, which is unphysical, and $Y = 2.4$. These results could be expected since the condition $\chi_1 < \chi_{1c}$ is violated and the shock is supersonic ($M_1 > 1$).

(iii) Now, for a perfect gas ($\gamma_1 = \gamma_2$) we obtain from (50)

$$X\left\{X - \frac{2\gamma}{\gamma + 1}(M_1^2 \cos^2 \chi_1 - 1)\right\} = 0, \quad (64)$$

and from (51)

$$\{2 + (\gamma - 1)M_1^2 \cos^2 \chi_1\}Y^2 - 2(1 + \gamma M_1^2 \cos^2 \chi_1)Y + (\gamma + 1)M_1^2 \cos^2 \chi_1 = 0. \quad (65)$$

Since $X \neq 0$, we obtain from (64)

$$\frac{p_2}{p_1} = 1 + \frac{2\gamma}{\gamma + 1}(M_1^2 \cos^2 \chi_1 - 1). \quad (66)$$

Likewise, we notice that $Y = 1$ is a solution of (65), which therefore can be recast as

$$(Y - 1)\{[2 + (\gamma - 1)M_1^2 \cos^2 \chi_1](Y + 1) - 2(1 + \gamma M_1^2 \cos^2 \chi_1)\} = 0, \quad (67)$$

and eventually since $Y \neq 1$

$$\frac{\rho_2}{\rho_1} = \frac{(\gamma + 1)M_1^2 \cos^2 \chi_1}{2 + (\gamma - 1)M_1^2 \cos^2 \chi_1}. \quad (68)$$

The relations (68) and (66) are identical to the Rankine–Hugoniot relations (1) recalled in § 2.1. It can be easily checked that the pressure and mass density solutions (66) and (68) satisfy the compatibility relation (57). Since $\eta = 1$, the ‘refraction’ law (43) reduces to the usual aerodynamic relation (3) of § 2.1.

The influence of viscosity on the jump determination has been considered in a recent work (Cavus 2013). A quadratic equation similar to our (51) is given, for a perfect gas ($\gamma_1 = \gamma_2$), with two additional terms involving upstream and downstream kinetic Reynolds numbers Re_1 and Re_2 .

3.1.2. Quasitangential shock

This case ($\chi_1 = 90^\circ$), formally equivalent to $M_1 \rightarrow 0$, yields for the pressure ratio

$$X\left\{\left(a^2 + c^2 - 2\frac{\gamma_2}{\gamma_2 - 1}a\right)X - 2a\frac{\gamma_2}{\gamma_2 - 1}\right\} = 0 \quad (69)$$

and for the mass density ratio

$$Y \left(\left[\frac{2\gamma_1}{\gamma_1 - 1} + \left\{ 1 - \left(d - \frac{bc}{a} \right)^2 \right\} \gamma_1 M_1^2 \right] Y - 2 \frac{\gamma_2}{\gamma_2 - 1} \right) = 0. \quad (70)$$

Rejecting the trivial solutions ($X = 0$ and $Y = 0$), we get the new solutions

$$X = \frac{2a \frac{\gamma_2}{\gamma_2 - 1}}{a^2 + c^2 - 2 \frac{\gamma_2}{\gamma_2 - 1} a} \quad (71)$$

and

$$Y = \frac{2 \frac{\gamma_2}{\gamma_2 - 1}}{\frac{2\gamma_1}{\gamma_1 - 1} + \left\{ 1 - \left(d - \frac{bc}{a} \right)^2 \right\} \gamma_1 M_1^2}. \quad (72)$$

The pressure ratio is therefore written as

$$X + 1 = \frac{a^2 + c^2}{a^2 + c^2 - 2 \frac{\gamma_2}{\gamma_2 - 1} a}. \quad (73)$$

With typical values at 40 km, we obtain $X < 0$, so that case is unphysical, like in aerodynamics, since the shock is supersonic ($M_1 > 1$).

3.1.3. Normal and tangential magnetic field

For a normal magnetic field ($\chi_b = 0$ or 180°), the coefficients a, b, c, d defined by (25) become

$$a = 1, \quad b = 0, \quad c = 0, \quad d = \frac{1}{1 + S_{v\sigma}}. \quad (74a-d)$$

This implies that for (41)

$$\frac{p_2}{p_1} - 1 = \gamma_1 M_1^2 \cos^2 \chi_1 (1 - \varepsilon), \quad (75)$$

and for (45)

$$\eta = d. \quad (76)$$

Therefore, we recover the same pressure–density relationship as in aerodynamics, but there is a jump of tangential velocity.

On the other hand, for a tangential magnetic field ($\chi_b = \pm 90^\circ$), the coefficients a, b, c, d become

$$a = \frac{1}{1 + S_{\rho\sigma}}, \quad b = 0, \quad c = 0, \quad d = 1. \quad (77)$$

This implies that for (41)

$$\frac{p_2}{p_1} - 1 = \gamma_1 M_1^2 \cos^2 \chi_1 \left(1 - \frac{\varepsilon}{a} \right), \quad (78)$$

and for (45)

$$\eta = 1. \quad (79)$$

Therefore, there is continuity of the tangential velocity, like in aerodynamics, but the pressure–density relationship involves a correcting MHD factor.

In conclusion, these two particular cases are hybrid since they combine aerodynamic and MHD features. They are not encountered in the blunt body problem but they could be devised in shock-tube experiments.

3.2. Fitting procedure

This procedure requires knowledge of the air state at high temperature and moderate pressures since the downstream air is mainly dissociated by the shock as N , O atoms and ionized as positive NO^+ , N_2^+ , O_2^+ ions, thus yielding free electrons and producing electrical conductivity. We assumed equilibrium of the plasma and, since to calculate the pressure and density jump we need the isentropic exponent and conductivity behind the shock, we used a thermodynamic correlation model (Srinivasan, Tannehill & Weilmuenster 1987), providing a thermal state equation $T(p, \rho)$ and a caloric state equation, providing the isentropic exponent $\gamma(p, \rho)$ (tables 7, 8, 9 for $\gamma(p, \rho)$ and tables 10, 11, 12 for $T(p, \rho)$ in Srinivasan *et al.* (1987)). This model is an improved version of a former model (Tannehill & Muge 1974).

The shock is fitted by iteration of the isentropic exponent γ_2 , and the algorithm is depicted in figure 3 with the interaction parameter S_ρ fixed. The convergence test at step n is simply taken as

$$\left| \frac{\gamma_2^{(n)} - \gamma_2^{(n-1)}}{\gamma_2^{(n-1)}} \right| < \varpi, \quad (80)$$

with the threshold value $\varpi = 10^{-8}$. The initial value is chosen as $\gamma_2^{(0)} = 1.4$.

3.3. Numerical results

In order to show general features of resistive MHD shocks, we chose well suited situations combining the relative configurations of velocity and magnetic fields (χ_1, χ_b) and the state of the upstream medium, characterized by the physical conditions at an altitude of 40 km. The shock itself is characterized by the Mach number M_1 ranging from 5 to 30 and the microscopic interaction parameter S_ρ ranging from 0 to 0.1, since we must stay in the linear range ($S_\rho \ll 1$), and this parameter is small in re-entry applications.

The two cases we consider, $\chi_1 = 20^\circ$, $\chi_b = 170^\circ$ and $\chi_1 = 60^\circ$, $\chi_b = 150^\circ$, depict two situations encountered before a blunt body. The results for case 1 (figure 4) show on one hand that the pressure ratio p_2/p_1 is practically independent of S_ρ and increases quadratically with M_1 according to (58). On the other hand, the mass density ratio ρ_2/ρ_1 increases and a hump occurs at $M_1 \approx 13$. In case 2 (figure 5), the pressure ratio curves can be slightly distinguished, and the mass density ratio curves are much more separated than in case 1. A hump occurs at $M_1 \approx 23.5$ in the aerodynamic situation ($S_\rho = 0$). Moreover, the level is lower in case 2, since the relative angle of the velocity and magnetic field vectors is smaller, indicating a smaller MHD effect.

The hump appearing at $M_1 \approx 13$ in case 1 is confirmed by earlier aerodynamic models of normal shocks in shock tubes (Glass & Hall 1959) behind the detached shock ahead of a stratospheric blunt body in hypersonic re-entry flight (Huber 1958). As stated in the reference papers, it reflects the resonance due to the dissociation of molecular oxygen and nitrogen in the temperature range 3500–4500 K. In case 2, the aerodynamic hump is shifted to $M_1 \approx 23.5$, because the variation of the incidence angle χ_1 is equivalent to a shift of the critical Mach number, according to a similarity rule we shall explain in § 5.2,

$$M_{11} \cos \chi_{11} = M_{12} \cos \chi_{12}, \quad (81)$$

with

$$\begin{cases} M_{11} \approx 13, \\ \chi_{11} = 20^\circ, \\ M_{12} \approx 23.5, \\ \chi_{12} = 60^\circ. \end{cases} \quad (82)$$

As S_ρ increases, the level of the density ratio is lowered and the abscissa of the hump is shifted to smaller Mach numbers (figure 5b). This suggests the following inverse problem: from such plots of the variations of the mass density ratio, it might be possible to determine the microscopic interaction parameter S_ρ , and then, using measurements of the conductivity, magnetic field and normal mass rate, eventually estimate the length scale $\mathcal{L}_\rho$.

4. Application to blunt-body shock-fitting

4.1. Fitting procedure

Here, we address the problem of the blunt body and work out a more complex procedure for fitting the various parameters behind the bow shock by applying the model of § 2 and neglecting curvature effects. The state of the air plasma generated behind the shock is described by the same correlation model as in the elementary fitting procedure of § 3.2.

Following other modellers (Bush 1958; Coackley & Porter 1971; Otsu *et al.* 2006; Otsu, Konigorski & Abe 2010), we used a power law of temperature for the conductivity, namely relation (130), with the constants $T_0 = 8000$ K, $\sigma_0 = 731$ S m⁻¹. Otherwise, former models have used a power law of velocity (Jarvinen 1965). We have checked that the conductivity obtained in this way is slightly overestimated compared with that produced by a plasma model (Viegas & Peng 1961; Sutton & Sherman 2006; Bisek, Boyd & Poggie 2009), although other calculations in the same range of altitudes for nearly the same velocity ($V_1 = 8.5$ km s⁻¹) obtain several hundreds of S m⁻¹ (Ericson & Maciulaitis 1964). Nevertheless, it has the great advantage of providing a simple dependence of the shock jumps on the microscopic interaction parameter S_ρ , as we showed in § 2.4.

Moreover, it is more accurate to use the magnetic field strength at the very location (r, θ) along the shock depending on the shock distance δ from the body nose, and, for this purpose, we also need to make iterations on δ in the MHD algorithm. The distance δ is related to the parameters ε and η once a flow model is found. This will be explained in § 4.5.

The shock thickness $\mathcal{L}_\rho$, involved in the interaction parameter S_ρ , depends on the viscosity behind the shock through the expression (32) derived in appendix B and is therefore iterated since it depends on various parameters before and behind the shock.

The resulting algorithm, depicted in figure 7, turns out to be more complex than the one in § 3, since electrical conductivity, shock distance and thickness are also iterated. The fourfold convergence test at step n is therefore taken as

$$\begin{aligned} \left| \frac{\gamma_2^{(n)} - \gamma_2^{(n-1)}}{\gamma_2^{(n-1)}} \right| &< \varpi, & \left| \frac{\sigma_2^{(n)} - \sigma_2^{(n-1)}}{\sigma_2^{(n-1)}} \right| &< \varpi, \\ \left| \frac{\delta^{(n)} - \delta^{(n-1)}}{\delta^{(n-1)}} \right| &< \varpi, & \left| \frac{\mathcal{L}^{(n)} - \mathcal{L}^{(n-1)}}{\mathcal{L}^{(n-1)}} \right| &< \varpi, \end{aligned} \quad (83a-d)$$

with the same threshold value $\varpi = 10^{-8}$. Initial values are chosen such that $\gamma_2^{(0)} = 1.4$, $\sigma_2^{(0)} = 100$ S m⁻¹, $\delta^{(0)} = 0.1R_b$, $\mathcal{L}^{(0)} = (4/3) \mu_1/m$. The convergence depends on the angles of velocity χ_1 and of magnetic field χ_b . In the pure aerodynamic case run for comparison, the

convergence criterion reduces to the iteration on γ_2 since the absence of magnetic field drops the influence of the conductivity, the shock distance and the shock thickness.

The viscosity, which is necessary for the estimation of the scale length (32) and the MHD parameters (23) and (25), is calculated in front of the shock by means of Sutherland's formula for air (in Pl or $\text{kg m}^{-1} \text{s}^{-1}$) (Sutherland 1893),

$$\mu(T) = 1.7 \times 10^{-5} \frac{T_0 + T_s}{T + T_s} \left(\frac{T}{T_0} \right)^{3/2}, \quad (84)$$

with the reference temperature $T_0 = 273 \text{ K}$ and the Sutherland temperature for air $T_s = 110 \text{ K}$. Behind the shock, the viscosity has been assumed to be independent of pressure and linear as a function of temperature below 10000 K , on the basis of a published work for high-temperature air plasma (Capitelli, Colonna & D'Angola 2001).

At each angular position θ along the shock (figure 6), we shall locally approximate the shock as being a plane, i.e. neglect the curvature, and apply the jump conditions derived in the previous section. The angle χ_1 of the upstream velocity is such that

$$\chi_1 = \theta_n. \quad (85)$$

Moreover, the shock layer will be modelled in the vicinity of the symmetry axis with the approximation of a spherical shock. Therefore, we shall have the equivalence

$$\theta_n = \theta. \quad (86)$$

A simple analytical model of non-spherical shock assuming $\theta_n = \beta\theta$ ($0 \leq \beta \leq 1$) and matching with the Mach angle for $M_1 = 23$ at $\theta = 90^\circ$ shows that $\beta = 0.97$ and thereupon proves the small deviation from sphericity. We shall now proceed to describe the topology of the magnetic, electric and velocity fields.

4.2. Magnetic and electric fields

A dipolar magnetic field $\mathbf{B}$ created by a magnet included in the body is applied to the spherical nose, with its axis parallel to the incident flow direction (Ziemer & bush 1958),

$$B_r = 2B_0 \left(\frac{R_b}{r} \right)^3 \cos\theta, \quad B_\phi = 0, \quad B_\theta = B_0 \left(\frac{R_b}{r} \right)^3 \sin\theta. \quad (87a-c)$$

This field is solenoidal ($\nabla \cdot \mathbf{B} = 0$) and vanishes at infinity. The magnetic strength B is

$$B = B_0 \left(\frac{R_b}{r} \right)^3 \sqrt{4\cos^2\theta + \sin^2\theta} \quad (88)$$

and the moment $\mathcal{M}_B$ of the generating magnetic dipole is such that

$$B_0 = \frac{\mu_0 \mathcal{M}_B}{4\pi R_b^3}. \quad (89)$$

It can be shown that the above magnetic field is non-rotational everywhere ($\nabla \times \mathbf{B} = \mathbf{0}$).

Several magnetic lines of force have been drawn in figure 8. We notice that these lines are more and more inclined as we move away from the symmetry axis. Equation (89) shows that a nominal induction $B_0 = 0.5 \text{ T}$ in relation (87) yields a magnetic field of 1 T at radius $R_b = 0.15 \text{ m}$ at the stagnation point on the body, and can be obtained with a magnet possessing a magnetic moment of $\mathcal{M}_B = 16\,875 \text{ A m}^2$.

Using (87), we obtain that χ_b is related to θ and θ_n by the equation

$$\tan(\pi - \chi_b + \theta_n - \theta) = \frac{\tan\theta}{2}. \quad (90)$$

The variations of χ_b as function of θ are displayed in figure 10(b) for a spherical shock ($\theta_n = \theta$). They are nonlinear, but can be approximated by expanding (90) to third order in θ ,

$$\chi_b \approx \pi - \frac{\theta}{2} \left(1 + \frac{\theta^2}{3} \right). \quad (91)$$

We shall verify that the radial dependence of B in (88) must be taken into account in the shock-fitting process.

As regards the electric field, without Hall effect, the condition $E = 0$ in the set (8) still holds because of the axisymmetry. To prove this, we consider a closed path $\mathcal{C}$ and a closed surface $\mathcal{S}$ admitting $\mathcal{C}$ as boundary. Then, taking the circulation of $\mathbf{E}$ along $\mathcal{C}$, using Stoke's theorem and Maxwell's stationary equation of induction ($\nabla \times \mathbf{E} = \mathbf{0}$), it is shown that the circulation of $\mathbf{E}$ vanishes. Since in axisymmetric geometry $\mathcal{C}$ may be chosen as a circle, we conclude that $\mathbf{E} = 0$.

4.3. Velocity field

We model the flow behind the shock as simply as possible in order to estimate how our jump relations generate the coupling of shock distance and thickness, which is a key-parameter. To describe this flow, assumed to be steady and laminar, we use a formalism based on streamlines, along which the stream function ψ is constant (Oguchi 1960; Maslen 1964; Noori, Hosseini & Ebrahimi 2009). It is possible to define a ψ function even in compressible magnetohydrodynamics, since the continuity equation has the same form.

For the sake of simplicity, we consider a hypersonic motion with zero incidence, i.e. the incident flow is along the symmetry axis of the blunt body. In spherical coordinates suitable here for a blunt nose (figure 6), the velocity components are written as

$$V_r = -\frac{\rho_0}{\rho} \frac{1}{r^2 \sin \theta} \frac{\partial \psi}{\partial \theta}, \quad V_\theta = \frac{\rho_0}{\rho} \frac{1}{r \sin \theta} \frac{\partial \psi}{\partial r}. \quad (92a,b)$$

The normalizing mass density ρ_0 is a constant which makes ψ of dimension $\text{m}^3 \text{s}^{-1}$.

4.4. Jump conditions for the stream functions

In order to match upstream and downstream solutions at the shock, we derive jump conditions for the stream function, through their first derivatives. Let us relate the normal and tangential components of velocity to the magnitude V and angle χ with the axis,

$$\begin{cases} u_1 = V_1 \cos \chi_1, \\ v_1 = V_1 \sin \chi_1, \\ u_2 = V_2 \cos \chi_2, \\ v_2 = V_2 \sin \chi_2. \end{cases} \quad (93)$$

On both sides of the shock, the spherical components V_r and V_θ are related to V and the angle χ with respect to the shock normal and tangent by the relations

$$\begin{cases} V_{1r} = -V_1 \cos \theta, \\ V_{1\theta} = V_1 \sin \theta, \\ V_{2r} = -V_2 \cos(\theta + \chi_2 - \chi_1), \\ V_{2\theta} = V_2 \sin(\theta + \chi_2 - \chi_1). \end{cases} \quad (94)$$

Using the upstream Mach number M_1 (27) and relation (41), we recast (24) into

$$\begin{cases} u_2 = \varepsilon V_1 \cos \chi_1, \\ v_2 = \left\{ \left(d - \frac{bc}{a} \right) \sin \chi_1 + \frac{c}{a} \varepsilon \cos \chi_1 \right\} V_1. \end{cases} \quad (95)$$

Then, making use of the magnetic parameter η defined by (45), we derive the following simple relations for the velocity projections on the normal and the tangent to the shock:

$$\begin{cases} u_2 = \varepsilon u_1, \\ v_2 = \eta v_1. \end{cases} \quad (96)$$

Combining (93) and (96), we derive the important relations

$$\begin{cases} V_{2r} = -\varepsilon V_1 \cos \theta, \\ V_{2\theta} = \eta V_1 \sin \theta. \end{cases} \quad (97)$$

We notice the symmetrical roles played by ε and η . In the non-magnetic case ($B = 0$, $a = d = 1$, $b = c = 0$), η equals unity, and we recover the continuity of the tangential velocity.

Now, relating normal and tangential components to spherical coordinates by eliminating the amplitudes V_1 and V_2 , on taking the ratio of (93) and (94),

$$\begin{cases} \frac{V_{1r}}{u_1} = -\frac{\cos \theta}{\cos \chi_1}, \\ \frac{V_{1\theta}}{v_1} = \frac{\sin \theta}{\sin \chi_1}, \\ \frac{V_{2r}}{u_2} = -\frac{\cos(\theta + \chi_2 - \chi_1)}{\cos \chi_2}, \\ \frac{V_{2\theta}}{v_2} = \frac{\sin(\theta + \chi_2 - \chi_1)}{\sin \chi_2}, \end{cases} \quad (98)$$

and making use of (92) we finally get the general relations

$$\begin{cases} \left(\frac{\partial \psi_2}{\partial \theta} \right)_c = \left(\frac{\partial \psi_1}{\partial \theta} \right)_c \frac{\cos \chi_1}{\cos \chi_2} \frac{\cos(\theta + \chi_2 - \chi_1)}{\cos \theta}, \\ \left(\frac{\partial \psi_2}{\partial r} \right)_c = \left(\frac{\partial \psi_1}{\partial r} \right)_c \frac{\cos \chi_1}{\cos \chi_2} \frac{\sin(\theta + \chi_2 - \chi_1)}{\sin \theta}. \end{cases} \quad (99)$$

For a spherical shock ($\chi_1 = \theta$), making use of (43), we can simplify this to

$$\begin{cases} \left(\frac{\partial \psi_2}{\partial \theta} \right)_{shock} = \left(\frac{\partial \psi_1}{\partial \theta} \right)_{shock}, \\ \left(\frac{\partial \psi_2}{\partial r} \right)_{shock} = \frac{\eta}{\varepsilon} \left(\frac{\partial \psi_1}{\partial r} \right)_{shock}. \end{cases} \quad (100)$$

We notice the continuity of the θ derivative of the stream function. The jump in the radial derivative is enhanced by the factor η . For the non-magnetic flow, we have $\eta = 1$, and so we retrieve the hydrodynamic expression.

It is important to notice that the relations (99) and (100) are valid for any kind of flow, potential or not, that is described by ψ_2 . Moreover, the relations (99) hold for magnetic and non-magnetic flows as well.

4.5. Stream function and stand-off

Since the upstream flow is uniform, it is potential, i.e. curl-free, and its stream function is simply written as (Hayes & Probst 1959)

$$\psi_1(r, \theta) = \frac{\rho_1 V_1}{2} r^2 \sin^2 \theta. \quad (101)$$

Using relations (92), we derive the velocity components before the shock,

$$V_{1r} = -V_1 \cos \theta, \quad V_{1\phi} = 0, \quad V_{1\theta} = V_1 \sin \theta. \quad (102)$$

As a first approximation, the downstream flow behind the shock might be assumed to be potential and to be described by a stream function of the following form (Kawamura 1950, 1952, 1952–53):

$$\psi_2(r, \theta) = \frac{\rho_1 V_1}{2} \frac{2\eta + \varepsilon}{3\varepsilon} \left(1 - \frac{R_b^3}{r^3} \right) r^2 \sin^2 \theta, \quad (103)$$

which we derived using boundary conditions (100). Without magnetic field ($\eta = 1$), the aerodynamic solution is recovered (Kawamura 1950, 1952, 1952–53), which was formerly accepted as a good approximation, in agreement with the then observed supersonic flows (Van Dyke 1958).

Nevertheless, vorticity is generated behind a curved aerodynamic shock (Hida 1953; Hayes 1957; Lighthill 1957), or even behind a plane MHD shock as we have shown in appendix C. An MHD vorticity jump has been calculated for a curved shock, but in ideal magnetohydrodynamics (Sharma & Ram 1971). Moreover the potential assumption fails at high Mach number and it leads to an underestimated shock stand-off.

Better approximations are provided by Lighthill's model in aerodynamics (Lighthill 1957) and Wu's model in magnetohydrodynamics (Wu 1960). This kind of model assumes inviscid flow and constant mass density behind the shock. The extension of Lighthill's model to magnetohydrodynamics with the assumption of constant conductivity leads to a vorticity jump of the following form at the shock (Wu 1960; Poggie & Gaitonde 2002):

$$[\Omega_\phi] = -\frac{(1-\varepsilon)^2}{\varepsilon} \frac{V_{\theta 2}}{R_s} - \frac{F_\theta}{\rho_2 V_{r2}}. \quad (104)$$

From this expression, since the magnetic force component F_θ is expressed as

$$F_\theta = \sigma(V_r B_\theta - V_\theta B_r) B_r, \quad (105)$$

assuming a spherical shock ($\chi_1 = \theta$), using the expressions (97) and the magnetic field components (87) on the shock ($r = R_s$), in a first step, we express the total vorticity behind the shock ($\Omega_{\phi 1} = 0$) as

$$\Omega_{\phi 2} = -\eta \frac{(1-\varepsilon)^2}{\varepsilon} \frac{V_1}{R_s} \sin \theta - 2(2\eta + \varepsilon) \frac{\sigma_2 B_0^2}{\rho_1} \left(\frac{R_b}{R_s} \right)^6 \sin \theta \cos \theta. \quad (106)$$

This expression is formally consistent with the non-dimensional result published in a reference work (Poggie & Gaitonde 2002). Then, in a second step, following Lighthill's procedure, we derive the equation of the vorticity,

$$\frac{\partial^2 \psi}{\partial r^2} + \frac{\sin \theta}{r^2} \frac{\partial}{\partial \theta} \left(\frac{1}{\sin \theta} \frac{\partial \psi}{\partial \theta} \right) = \rho_1 V_1 \left\{ \eta \frac{(1-\varepsilon)^2}{\varepsilon^2} + 2S_b \left(2\frac{\eta}{\varepsilon} + 1 \right) q^5 \cos \theta \right\} \frac{r^2}{R_s^2} \sin^2 \theta. \quad (107)$$

After defining the macroscopic interaction parameter S_b built on the body nose radius R_b ,

$$S_b = \frac{\sigma_2 B_0^2 R_b}{\rho_1 V_1}, \quad (108)$$

and the ratio

$$q = \frac{R_b}{R_s}, \quad (109)$$

we assume that the stream function solution ψ_2 can be cast as the sum of two terms,

$$\psi_2 = \psi_2^{(0)} + S_b \psi_2^{(1)}. \quad (110)$$

The first term $\psi_2^{(0)}$ corresponds to Lighthill's solution of (107) with the first term of the right-hand side, involving the correcting magnetic factor η , such that

$$\begin{aligned} \frac{\psi_2^{(0)}(r, \theta)}{\rho_1 V_1 R_s^2 \sin^2 \theta} = & \eta \frac{(1-\varepsilon)^2}{10\varepsilon^2} \left(\frac{r}{R_s} \right)^4 + \frac{1}{3} \left\{ \frac{1}{2} + \frac{\eta}{\varepsilon} - \eta \frac{(1-\varepsilon)^2}{2\varepsilon^2} \right\} \left(\frac{r}{R_s} \right)^2 \\ & + \frac{1}{3} \left\{ 1 - \frac{\eta}{\varepsilon} + \eta \frac{(1-\varepsilon)^2}{5\varepsilon^2} \right\} \frac{R_s}{r}. \end{aligned} \quad (111)$$

In the non-magnetic case ($S_b = 0$, $\eta = 1$), this first term $\psi_2^{(0)}$ yields exactly Lighthill's solution,

$$\psi_2(r, \theta) = \frac{\rho_1 V_1 R_s^2}{30\varepsilon^2} \left\{ 3(1-\varepsilon)^2 \left(\frac{r}{R_s} \right)^4 - 5(1-4\varepsilon) \left(\frac{r}{R_s} \right)^2 + 2(1-\varepsilon)(1-6\varepsilon) \frac{R_s}{r} \right\} \sin^2 \theta. \quad (112)$$

The shock distance δ defined by

$$\delta = \frac{R_s - R_b}{R_b} \quad (113)$$

is therefore such that

$$\delta = \frac{1}{q} - 1, \quad (114)$$

and q is a solution of the equation

$$\psi_2(R_b) = 0, \quad (115)$$

that is,

$$\eta \frac{(1-\varepsilon)^2}{10\varepsilon} q^5 + \frac{1}{3} \left\{ \frac{\varepsilon}{2} + \eta - \eta \frac{(1-\varepsilon)^2}{2\varepsilon} \right\} q^3 + \frac{1}{3} \left\{ \varepsilon - \eta + \eta \frac{(1-\varepsilon)^2}{5\varepsilon} \right\} = 0. \quad (116)$$

Looking for a simple perturbation $\psi_2^{(1)}$ in $\sin^2 \theta$ by assuming $\cos \theta \approx 1$ in the second term of the vorticity expression, equation (107), leads to a sixth-degree equation for q instead of (116), which has no real solution with the prescribed physical conditions at 40 and 65 km. This point is a question to be considered in future work.

Obtained by a different approach based on the Newtonian pressure relation, Lykoudis's MHD solution gives the following expression for the MHD distance δ (Lykoudis 1961):

$$\frac{\delta}{\delta_0} \approx \frac{S_b}{2} \sqrt{\frac{3}{8} \varepsilon} + \sqrt{1 + \frac{3\varepsilon S_b^2}{32}}, \quad (117)$$

with the non-magnetic distance δ_0 such that

$$\frac{\delta_0}{R_b} = \frac{\varepsilon}{1 + \sqrt{\frac{8}{3}} \varepsilon}, \quad (118)$$

and the macroscopic interaction parameter S_b defined by (108).

Lighthill's aerodynamical solution, assuming constant mass density behind the shock and a perfect gas, leads to the following expansion to second order (Lighthill 1957; Hayes & Probstein 1959):

$$\frac{\delta_0}{R_b} \approx \varepsilon \left(1 - \sqrt{\frac{8}{3}} \varepsilon + 3\varepsilon \right). \quad (119)$$

It can be checked that the aerodynamic distance obtained by the formulae (118) and (119) give results slightly smaller and larger than the solution given by (116) with $\eta = 1$. Therefore, we used the solution to (116) with $\eta = 1$ for δ_0 .

Since the ratio $\sin \chi_b / \sin \chi_1$ is an indeterminate form 0/0 on the stagnation line ($\chi_1 = 0$ and $\chi_b = 0$), the limit of η on the stagnation line ($\theta \rightarrow 0$) by (45) using the expansion (91) yields

$$\eta \approx \frac{1}{1 + S_{v\sigma 0}} \left(1 - \frac{\varepsilon S_{\rho\sigma 0}}{2} \right), \quad (120)$$

with the 'normal' interaction parameters corresponding to $\chi_1 = 0$,

$$S_{\rho\sigma 0} = \frac{\sigma_2 B^2 \mathcal{L}_{\rho\sigma}}{m_0}, \quad S_{v\sigma 0} = \frac{\sigma_2 B^2 \mathcal{L}_{v\sigma}}{m_0}, \quad m_0 = \rho_1 V_1. \quad (121a,b,c)$$

5. Application to atmospheric entry

5.1. Results

The calculation was made with $\chi_1 = 1.4$ and $B_0 = 0.5$ T for a hypersonic shock at stratospheric heights of 40 and 65 km, where significantly different ambient physical conditions are found (table 2). The large discrepancies in the kinematic viscosity ν_1 result in very different mean free paths ℓ_1 and shock thicknesses $\mathcal{L}_p$ estimated by means of relations (30) and (32). In both cases, we assumed an exponent of $\alpha = 2$ and a factor of $\zeta = 10$.

As the spherical assumption is only valid not far from the symmetry axis, we use the complete scheme of figure 7 with all four test ratios (83) only for $\chi_1 = 0$ on the symmetry axis. For $\chi_1 \neq 0$, we keep the shock distance δ constant and equal to its value at $\chi_1 = 0$ and fit only χ_2 , σ_2 and $\mathcal{L}_p$. The aerodynamic behaviour is found with application of the fitting procedure only on χ_2 .

Plots displaying typical variations of convergence test ratios (86) as functions of iteration number at 65 km on the symmetry axis (figure 9) show that convergence is easily reached within around 10 iterations for χ_2 , σ_2 and $\mathcal{L}_p$, but only within around 20 iterations for δ .

The angular variations of the magnetic field strength are displayed in figure 10(a) for $0 < \chi_1 < 80^\circ$. They depend upon the shock stand-off, and the field is therefore stronger on the shock at 40 km than at 65 km because the shock distance is larger at 65 km than at 40 km.

Figure 11 displays the variations of pressure, temperature, isentropic exponent, Mach number and velocity angle behind the shock as functions of χ_1 in the same range. The

pressures profiles (figure 11a) have a classic cosine shape, the aerodynamic and MHD profiles being coincident at 40 km and 65 km, in agreement with the analysis of § 3 (figures 4a and 5a).

Temperature profiles (figure 11b), showing a kind of cosine shape, nearly coincide at 40 km, whereas at 65 km the MHD profile lies slightly above the aerodynamic profile ($\Delta T_2 \approx 111$ K at $\chi_1 = 50^\circ$). Consequently, the mass density profiles (figure 11c) are coincident at 40 km, whereas the MHD profile lies beneath the aerodynamic one at 65 km (≈ 5.3 % at $\chi_1 = 50^\circ$).

The isentropic exponent (figure 11d) is of order 1.1 in the vicinity of the nose axis and increases as χ_1 increases, with a parabolic branch. As mentioned above, the inflexion at $\chi_1 \approx 55^\circ$ is due to the hump in the profile $\gamma(T)$, reflecting the dissociation of oxygen and nitrogen molecules. As expected, the Mach number (figure 11e) increases with χ_1 , but it is lowered by MHD effects, according to the slowing down action of the magnetic force.

The deflection angle (figure 11f) is smaller with magnetic field than without, as could be guessed from relation (43) with $\eta < 1$. This means that the magnetic field slows down the flow and causes the streamlines to be less deflected through the shock by the body. This is also consistent with the fact that the shock is more repelled by MHD forces than without. We note also that the maximum of deflection occurs at a smaller inclination angle ($\chi_1 \approx 15^\circ$) than for supersonic speeds ($\chi_1 \approx 30^\circ$) (Anderson 1989).

Figure 12 shows the variation of the electrical conductivity σ_2 , the magnetic parameter η and the interaction parameter S_ρ behind the shock. The conductivity variation has a larger amplitude at 40 km (150 S m^{-1}) than at 65 km (100 S m^{-1}), due to the temperature variation (figure 11b). The parameter η is constantly equal to unity at 40 km, indicating that the MHD effects are negligible in the shock, consistent with a very small S_ρ , whereas it goes down to 0.95 at 65 km, consistent with a larger S_ρ of 6.2 % (table 3), indicating that MHD forces are more efficient within the shock at that altitude.

It is worth noticing that the MHD and aerodynamic profiles (pressure, temperature, mass density) are coincident on the axis since, at this location, the velocity and magnetic vectors are nearly aligned (opposite or reverse), so that the magnetic force is small and MHD effects are locally negligible. This can be compared with the ideal MHD fast-shock which degenerates to a gas-dynamic shock when the magnetic field is normal to the shock (Cowling 1976).

5.2. Discussion

The analysis of angular profiles as functions of χ_1 performed in § 5.1 leads us to make the following remarks.

- (i) Lykoudis's and Lighthill's models, by means of which we calculate the shock stand-off are valid in the vicinity of the stagnation line, i.e. near the symmetry axis, in the spherical approximation.
- (ii) The actual non-spherical shape of the shock means that $\chi_1 < \theta$, as is shown by the simple exponential model of § 4.1. Since the shock front steepens as θ increases ($dr/d\theta > 0$), θ_n increases more slowly than θ ($\theta > \theta_n$). In the hypersonic case considered, the deviation is as small as 3 %.
- (iii) In the hypersonic regime, our model of jump relations cannot be used for incident angles such that $\chi_1 > 89^\circ$, and for a non-spherical bow shock this corresponds to an even smaller critical angle of $\theta_c < \chi_{1c}$, depending on the Mach number.
- (iv) There is a hump in the χ_1 profile of certain quantities around 50° (mass density, isentropic exponent). The correlation of γ_2 and T_2 , respectively plotted in figures 11(b) and 11(d), clearly shows the same hump located at the same place (figure 17). Therefore, the hump is nothing other than the resonance of the dissociation of oxygen

and nitrogen molecules in air in the range 3500–4500 K. This behaviour, due to the real gas effect resulting from air dissociation ($\gamma_1 \neq \gamma_2$), points out the algorithmic complexity noticed in shock-fitting in argon flow (Pepe *et al.* 2014).

Moreover, we checked that this feature is present even in the non-magnetic case, and in the variation of γ_2 and ρ_2/ρ_1 at constant $\chi_1 = 0$ as the incident Mach number M_1 varies from 5 to 30. We note that a similar hump actually occurs at approximately $M_1 = 14$ (figure 18). Since the quantity $\gamma_1 M_1 \cos \chi_1$, which represents the incident normal velocity, is involved as a whole in the jump equations (33) and (37), or (50) and (51), we conclude that the angular and Mach-number behaviours are related by the equivalence

$$M_{10} \cos \chi_{10} = M_1 \cos \chi_1, \quad (122)$$

with

$$\begin{cases} M_{10} \approx 14, \\ \chi_{10} = 0, \\ M_1 \approx 22, \\ \chi_1 \approx 50^\circ. \end{cases} \quad (123)$$

This quantity plays the same role in the present model as the hypersonic similarity parameter introduced by Anderson (1989).

The hump at $M_1 \approx 14$ actually appears in former models of normal shocks in shock tubes (Glass & Hall 1959). This suggests that there is a transition at a critical value $\chi_{1t} \approx 50^\circ$ in the angular domain, or $M_{1t} \approx 14$ in the velocity domain, between a ‘hypersonic regime’ ($0 \leq \chi_1 \leq \chi_{1t}$; $M_1 \geq M_{1t}$) and a ‘supersonic regime’ ($\chi_{1t} \leq \chi_1 \leq \chi_{1c}$; $1 < M_1 \leq M_{1t}$), where the quantity $\gamma_1 M_1^2 \cos^2 \chi_1$ is respectively a leading or negligible term in the equations.

- (v) The strong distortion of the profile of ρ_2/ρ_1 (figure 11c) is due to the presence of the factor $\gamma_2 - 1$ in the denominator of the solution (55), which enhances the resonance of γ_2 .

It must be stressed that the aerodynamic behaviour around 50° is independent of the shock thickness, since non-magnetic cases do not involve $\mathcal{L}_\rho$.

5.3. Shock thickness and vorticity

As pointed out above, the shock thickness $\mathcal{L}_\rho$ is a fundamental quantity of our model of the MHD shock since all quantities depend on the microscopic interaction parameter (129), which is based on $\mathcal{L}_\rho$. The approximate expression (32) derived in appendix B shows that the magnetic correction vanishes on the symmetry axis ($\chi_b = 180^\circ$ or 0°), and the non-magnetic value is roughly an increasing function of temperature.

Therefore, the profile of $\mathcal{L}_\rho$ as a function of χ_1 displayed in figure 12(c) confirms that the increasing part between 0° and 45° is due to the reciprocal of the cosine dependence. The shock thickness would be expected to increase beyond 50° , so that the wavy part above 50° may be due to the velocity gradient being neglected behind the curved shock.

Actually, the total vorticity $\Omega_{\varphi 2}$ behind the shock (106), due to curvature effects, can be considered as an estimation of the derivative dv/dx neglected in (10). Its variation as a function of χ_1 or θ (in the spherical approximation) is plotted in figure 13 and shows a flat maximum at approximately 40° – 60° for the aerodynamic contribution at both altitudes and the total vorticity at 40 km, whereas the total vorticity at 65 km has a peaked maximum at

approximately 35° . This is consistent with the analysis of the shock distance in § 5.2 below (figure 15a), which is larger at 65 km than 40 km and much larger with magnetic field than without.

These angular variations suggest that curvature effects increase as one moves from the symmetry axis and must be taken into account beyond 50° in the bow shock we consider. It should be remembered that the shock thickness is not involved in the aerodynamic jump equations (50) and (51).

6. Assessment

6.1. Experimental

Our model requires hypersonic experimental data for direct testing, which are not available at the moment. These specific experiments should be devised in order

- (i) to validate the jump relations for a plane shock of §§ 2 and 3;
- (ii) to check the shock fitting of a blunt-body shock of §§ 4 and 5.

Experiments of the first type could be devised with an MHD shock tube embedded in a constant magnetic field, provided that one can produce stationary shocks with microscopic interaction parameters S_ρ larger than 0.1, since we notice that in the situation of the blunt body, this parameter is smaller than 0.1.

Concerning the second type, hypersonic speeds in wind tunnel experiments ($M_1 \approx 15$) are now reachable (Cristofolini *et al.* 2008, 2010). Values measured during NASA's RAM-C experiments (Schexnayder, Huber & Evans 1971; Dunn & Kang 1973; Evans, Schexnayder & Huber 1973) provide values of electronic densities off the nose but enable the validation of numerical results on the nose (Candler & McCormack 1991; Josyula & Bailey 2003) that we use below. Having a shape similar to that of the RAM-C body, the SARA microsatellite (Santos 2012) and the ESA's capsule EXPERT (Muylaert *et al.* 2007) or IXV spacecraft would be good up-to-date re-entry vehicles for providing *in situ* MHD data.

6.2 Numerical

As detailed in § 3.2, our results on the plane shock are confirmed, at least in aerodynamic situations, by earlier models of normal shocks in shock tubes (Glass & Hall 1959) and ahead of a stratospheric re-entry blunt body (Huber 1958). The hump at Mach 14 is clearly produced in these models.

Turning to the curved shock, an indirect test consists of comparing electronic densities n_e with published data on the RAM-C vehicle (Huber 1963; Candler & McCormack 1991; Josyula & Bailey 2003). These calculations were originally motivated by the radio blackout due to the plasma sheath around the space shuttle during Earth-space communications (Takahashi, Nakasato & Oshima 2016). For this purpose, let us consider the classical expression of Spitzer's scalar conductivity (Sutton & Sherman 2006),

$$\sigma_2 = \frac{n_e q_e}{m_e f_e}. \quad (124)$$

This is an implicit equation for n_e since the collision frequency f_e resulting from electron-ion and electron-neutral contributions depends on n_e and the temperature T_2 behind the shock. We fixed the collision cross-section of electrons with neutrals (nitrogen) according to tabulated values of approximately $8 \times 10^{-20} \text{ m}^2$ (Itakawa 2006).

An iterative method converges in 30 steps and provides the curve of figure 14 for the variations of electronic collision frequency f_e (a) and density n_e (b) as functions of altitude. The hump at approximately 25 km is due to the fast decrease of Mach number caused by the

deceleration. This result can be compared with former plasma calculations plotted in the same figure (Huber 1963; Candler & McCormack 1991). The fact that these results are slightly below ours may confirm that our conductivity is larger, as already mentioned in § 4.1. However, the trend is similar except at low altitude where pressure effects, not considered by the power law (130), are very important.

The variation of the relative distance δ/R_b with altitude is plotted in figure 15(a). The ratio of the MHD (δ/R_b) to the aerodynamic (δ_0/R_b) relative stand-off is approximately 1.2 at 40 km ($\delta/R_b \approx 0.0651$ and $\delta_0/R_b \approx 0.0528$) and 3.9 at 65 km ($\delta/R_b \approx 0.180$ and $\delta_0/R_b \approx 0.0462$). The results of non-equilibrium calculations (Fujino & Ishikawa 2013) also plotted on the same figure show that the stand-off distance is somewhat larger in this case, for either the aerodynamic or the MHD stand-off.

The variation of δ/R_b as a function of S_b displayed in figure 15(b) is nearly linear in the altitude range where the Mach number is roughly constant ($M_1 \approx 23$). This behaviour can be compared with the results of a numerical model performed at a supersonic speed ($M_1 = 5$) with $\gamma = 1.2$ (Poggie & Gaitonde 2002), which we have also plotted. The line slope (≈ 0.007) in our model is smaller than that found from the quoted work (≈ 0.01).

As could be expected, our hypersonic results ($M_1 \approx 23$) lie below the supersonic data ($M_1 = 5$), since the stand-off decreases as the Mach number increases. Moreover, the rule of thumb according to which the aerodynamic distance ($S_b = 0$) varies as $(\gamma - 1)/(\gamma + 1)$ yields a smaller distance in our case ($\gamma \approx 1.13$; $\delta/R_b \approx 0.06$) than in the quoted work ($\gamma = 1.2$; $\delta/R_b \approx 0.09$), as can be checked in figure 15(b).

The electrical conductivity σ_2 displayed in figure 16(b) is clearly overestimated with a power law of temperature at low altitude because below 40 km, high pressure actually causes the conductivity to decrease drastically. A simplified air plasma model with only five species describes the plasma correctly below 40 km, and underestimates σ_2 above.

The depth scale of the mean free path within the shock estimated by other authors at 61 km is approximately 1.2 mm (Josyula & Bailey 2003); this is about 3 times our estimate of the shock thickness (0.375 mm). The ratio $\ell_1/\mathcal{L}_0$ of mean free path before the shock (30) over shock thickness (32) on the symmetry axis is also a relevant test often displayed in models of shock structure. Its values at 40 km (0.832) and 65 km (0.959) in the hypersonic regimes considered here (tables 2 and 3) are in good agreement with several published results in supersonic aerodynamic regimes ($M_1 < 10$) (Gilbarg & Paolucci 1953; Paolucci & Paolucci 2016).

7. Conclusion and prospects

7.1. Results

The present work proposes a basis for an alternative approach to the usual shock-capturing schemes involved in numerical MHD models. We have derived original expressions for the jumps at a resistive MHD shock with real gas effects that depend on the upstream Mach number and a microscopic MHD interaction parameter based on the shock thickness.

A shock-fitting scheme involving an ionized-air plasma model has been worked out and applied to a plane oblique shock and to a detached bow shock (blunt body) with physical conditions before the shock corresponding to two given altitudes (40 and 65 km) along a typical re-entry trajectory in the stratosphere. In the case of the blunt body, the applied magnetic field is generated by a dipole magnet aligned with the symmetry axis.

We thus calculated the physical conditions behind the shock front at different angles from the axis. Cosine-like profiles are found for pressure and temperature. The MHD effect is stronger at 65 km in repelling the shock, and becomes practically inefficient at 40 km. This holds for zero incidence, i.e. incident velocity aligned with the symmetry axis; with non-zero incidence, tilting moments would develop.

We also derived general expressions for the jumps of the stream function derivatives at the blunt-body shock depending on the parameters ε and η , which play symmetric roles in the problem. As a by-product, we put into evidence a refraction of streamlines across the shock with a tangent law, instead of sine in the Snell–Descartes law of optics, the ratio η/ε playing the role of the refractive index.

Published expressions for the vorticity jump (Truesdell 1952; Wu 1960; Poggie & Gaitonde 2002) usually neglect the jump of the transverse component of velocity, and our model shows that this is formally incorrect in resistive magnetohydrodynamics (appendix C), although the effect is small in the atmospheric situations investigated. The estimate of the shock thickness used near the symmetry axis is in good agreement with published values, but fails beyond 50° .

The application of our model of shock jumps together with a model of the shock layer actually shows that, for a strong shock, the MHD effect amounts to approximately 6 % in the shock front and 50 % in the shock layer in addition to the aerodynamic effect. This explains why the experimental check of our microscopic jump model is expected to be more difficult than the validation of the macroscopic effects. Indeed, published experimental results with error bars show that the accuracy is not better than 5 %, and more probably approximately 10 % (Nagata *et al.* 2013). The variation of the two interaction parameters S_ρ and S_b with altitude (figure 16a) confirms that this relative behaviour occurs up to the top of the stratosphere. At 100 km, the two effects may become of the same magnitude, but the molecular flow regime and the Hall effect should then be considered.

An important feature also put into evidence is a similarity rule involving the parameter $M_1 \cos \chi_1$, which sets a correspondence between the upstream Mach number M_1 and the velocity angle χ_1 . This leads to a hypersonic regime and a supersonic regime being distinguished, these two regimes joining at a critical angle ($\chi_1 \approx 55^\circ$) or a critical Mach number ($M_1 \approx 14$), which lies within the temperature range where the resonance due the dissociation of oxygen and nitrogen molecules occurs. This transition is also located at the maximum of the vorticity jump across the shock.

7.2. Prospects

We now proceed to a review of the approximations made regarding the shock front and the aftershock flow, first for the basic plane oblique shock model and second for the application to the blunt-body re-entry problem.

- (i) The electrical conductivity decreases strongly under high pressure at low altitude, so that in an improved model, equation (130) should be modified with a pressure dependence

$$\sigma = \sigma_0 \left(\frac{T}{T_0} \right)^\alpha \left(\frac{p}{p_0} \right)^\beta. \quad (125)$$

In this situation, relation (143) defining ω should be revised. The Hall effect, which we have neglected here within the shock, should also be taken into account in a further work, since it can be shown that the Hall parameters β_e (for electrons) and β_i (for ions) increase with altitude. The Hall effect is most developed at 60–70 km height and is therefore most studied in that region (Bityurin & Bocharov 2006).

- (ii) The first-order rotational solution we used shows how the aftershock flow is impacted by our jump relations. An analytic solution $\psi_2^{(1)}$ corresponding to the second term on the right-hand side of (107), the magnetic term in $\sin^2 \theta \cos \theta$, would lead us to calculate more consistently the shock stand-off and the pressure–temperature distributions (i.e. electrical conductivity) in the shock layer. A similar expansion has been looked for in terms of the small aerodynamic parameter ε (Oguchi 1960).

As the upstream velocity angle χ_1 with the plane shock increases, the actual depth followed by the flow through the shock deviates from the expected thickness, suggesting that curvature effects and velocity gradient become important. Therefore, it would be an improvement to include viscous and thermal effects neglected in (10) in the modelling of aerodynamic and MHD shock jumps.

According to the analysis based on the Damköhler number (appendix A), non-equilibrium is likely to arise behind the shock above 50 km and should also be taken into account (Hall, Eschenroeder & Marrone 2003; De Crombrugghe *et al.* 2014). We also showed that the shock stand-off is sensitive to non-equilibrium effects (§ 6.2).

We assumed a spherical shock and showed that a small deviation from sphericity occurs, in consistency with former studies which suggest a kind of catenary shape (Falanga & Sullivan 1970). Magnetic field asymmetry and flow incidence should be taken into account in future analytical works. It should be noted that magnetic configurations other than dipolar could be considered (Chen *et al.* 2016).

Specific experiments at hypersonic speeds not available at the moment are required in order to validate our theoretical work, on one hand the jump relations for a plane oblique shock and on the other hand the shock fitting of a blunt-body bow shock.

Magnetohydrodynamic shock tubes could provide a suitable benchmark for plane shocks and reciprocally could help to estimate the shock thickness from density profile functions of Mach number and interaction parameter. Dedicated measurements in wind tunnels like those actually in progress at Mach numbers 6 and 15 (Cristofolini *et al.* 2008, 2010) could provide material for bow shocks, knowing that the effect is 10 times smaller in the shock front than in the shock layer.

Acknowledgements

This work was supported by funding from ONERA. The author is indebted and grateful to three anonymous referees and also to Prof. R. Verzicco for very valuable and stimulating remarks and suggestions which greatly helped to improve both the content and the presentation of the paper.

Appendix A

This appendix is devoted to the derivation of an estimate for $\mathcal{L}_\sigma$. We first define the parameter ω as the ratio of length scales $\mathcal{L}_\sigma$ and $\mathcal{L}_\rho$,

$$\omega = \frac{\mathcal{L}_\sigma}{\mathcal{L}_\rho}. \quad (126)$$

Consequently, the characteristic lengths defined by (18) are such that

$$\begin{cases} \frac{\mathcal{L}_{\rho\sigma}}{\mathcal{L}_\rho} = \frac{\omega}{1-\omega}, \\ \frac{\mathcal{L}_{v\sigma}}{\mathcal{L}_\rho} = \frac{\omega}{1+\omega}, \end{cases} \quad (127)$$

and the interaction parameters (23) become

$$\begin{cases} S_{\rho\sigma} = \frac{\omega}{1-\omega} S_\rho, \\ S_{v\sigma} = \frac{\omega}{1+\omega} S_\rho, \end{cases} \quad (128)$$

with the interaction parameter built on $\mathcal{L}_\rho$,

$$S_\rho = \frac{\sigma_2 B^2 \mathcal{L}_\rho}{m}. \quad (129)$$

The ratio ω defined by (126) requires the characteristic length scale $\mathcal{L}_\sigma$ of electrical conductivity across the shock. As is usually assumed in published works (Poggie & Gaitonde 2002; Otsu *et al.* 2006, 2010), let us assume here that σ is proportional to a power of temperature T , i.e.

$$\sigma = \sigma_0 \left(\frac{T}{T_0} \right)^\alpha, \quad (130)$$

with $\alpha = 2$ or 4 . Then, we take the logarithmic derivative of (130),

$$\frac{d\sigma}{\sigma} = \alpha \frac{dT}{T}, \quad (131)$$

and substitute the characteristic lengths $\mathcal{L}_\sigma$ and $\mathcal{L}_T$, analogous to (13) and (15), defined by

$$\frac{1}{\sigma} \frac{d\sigma}{dx} \approx \frac{1}{\mathcal{L}_\sigma}, \quad \frac{1}{T} \frac{dT}{dx} \approx \frac{1}{\mathcal{L}_T}, \quad (132a,b)$$

thus yielding

$$\mathcal{L}_\sigma \approx \frac{\mathcal{L}_T}{\alpha}. \quad (133)$$

Furthermore, let us consider the equation of state with standard notations,

$$p = \rho \frac{R}{\mathcal{M}} T, \quad (134)$$

where $\mathcal{M}$ denotes here the equivalent molar mass of decomposed air and R the molar constant of perfect gas. Let us take the logarithmic derivative of (134),

$$\frac{dp}{p} = \frac{d\rho}{\rho} - \frac{d\mathcal{M}}{\mathcal{M}} + \frac{dT}{T}, \quad (135)$$

and make use of the characteristic lengths $\mathcal{L}_\rho$ and $\mathcal{L}_T$ defined above and the two more defined by

$$\frac{1}{p} \frac{dp}{dx} \approx \frac{1}{\mathcal{L}_p}, \quad \frac{1}{\mathcal{M}} \frac{d\mathcal{M}}{dx} \approx -\frac{1}{\mathcal{L}_\mathcal{M}}, \quad (136a,b)$$

since molecular dissociation of air causes $\mathcal{M}$ to decrease. Then, insertion of these relations into (135) yields

$$\frac{1}{\mathcal{L}_p} \approx \frac{1}{\mathcal{L}_\rho} + \frac{1}{\mathcal{L}_\mathcal{M}} + \frac{1}{\mathcal{L}_T}. \quad (137)$$

Next, let us consider the sound speed c_s , defined by

$$c_s^2 = \left(\frac{\partial p}{\partial \rho} \right)_s = \frac{\gamma p}{\rho}. \quad (138)$$

Using the characteristic lengths $\mathcal{L}_p$ and $\mathcal{L}_\rho$, we can derive from (138) the relation

$$\frac{\mathcal{L}_\rho}{\mathcal{L}_p} \approx \gamma. \quad (139)$$

Combining relations (133), (137) and (139), we obtain

$$\frac{1}{\mathcal{L}_\sigma} \approx \alpha \left(\frac{\gamma-1}{\mathcal{L}_\rho} - \frac{1}{\mathcal{L}_\mathcal{M}} \right). \quad (140)$$

Moreover, theoretical (Conti 1966) and numerical (Pepe *et al.* 2015) works suggest that ionization, and therefore conductivity, develops in the shock, and beyond it, deeper than merely the shock thickness, so that molar mass might be supposed to have a somewhat larger characteristic length scale than mass density, i.e.

$$\mathcal{L}_\mathcal{M} \approx \zeta \mathcal{L}_\rho, \quad (141)$$

with $\zeta > 1$. We eventually obtain the desired relation,

$$\frac{\mathcal{L}_\rho}{\mathcal{L}_\sigma} \approx \alpha (\gamma - 1 - 1/\zeta), \quad (142)$$

or equivalently

$$\omega \approx \frac{1}{\alpha(\gamma - 1 - 1/\zeta)}. \quad (143)$$

Since ω must be positive, we derive the following condition on ζ :

$$\zeta > \frac{1}{\gamma - 1}. \quad (144)$$

With typically $\gamma \approx 1.15$ behind the shock, we are led to choose $\zeta \approx 10$, confirming the above argument. Fixing ζ to a value larger than 10 does not change anything since $\gamma - 1$ in (143) is of order $1/10$. Moreover, with $\alpha = 2$, relation (143) shows that ω is approximately 10, and consequently from (127) we shall have $\mathcal{L}_{\rho\sigma} \approx -1.1\mathcal{L}_\rho$ and $\mathcal{L}_{\nu\sigma} \approx 0.9\mathcal{L}_\rho$. This is therefore a multi-scale problem.

The equilibrium assumption can be tested on the basis of the Damköhler number N_D , which is a non-dimensional number defined as the ratio of the leading reaction rate to the convective time. When $N_D \gg 1$, the medium is in chemical equilibrium, and when $N_D < 1$, it is in non-equilibrium. Estimation of this number in the range dominated by the dissociation of N_2 (Candler 1989), leads to N_D of approximately 0.039 and 10.3 at 65 km and 40 km respectively. We therefore deduce that the air plasma is in equilibrium at 40 km but not at 65 km.

Appendix B

This calculation is a simplified approach to provide a useful expression for the shock thickness and to show the influence of the magnetic field on the shock thickness. A classical way to define it in one dimension, due to Prandtl, is the following:

$$\mathcal{L} \approx \frac{u_2 - u_1}{\frac{du}{dx}}, \quad (145)$$

where the derivative is taken in the core of the shock. Extending a classical aerodynamic approach (Shapiro 1953), we consider, in the equations of motion (9) of the oblique shock,

the balance in order of magnitude of the inertia, viscous and magnetic terms,

$$\begin{cases} \rho u \frac{du}{dx} \approx \frac{d}{dx} \left(\frac{4}{3} \mu \frac{du}{dx} \right) - \sigma B^2 (u \sin \chi_b - v \cos \chi_b) \sin \chi_b, \\ \rho u \frac{dv}{dx} \approx \frac{d}{dx} \left(\frac{4}{3} \mu \frac{dv}{dx} \right) + \sigma B^2 (u \sin \chi_b - v \cos \chi_b) \cos \chi_b, \end{cases} \quad (146)$$

the pressure and inertia terms being of same order. Using the mass conservation equation (10a), knowing that the magnetic field is not changed through the shock and taking the average of σu and σv , we obtain

$$\begin{cases} m \frac{du}{dx} \approx \frac{d}{dx} \left(\frac{4}{3} \mu \frac{du}{dx} \right) - B^2 (\overline{\sigma u} \sin \chi_b - \overline{\sigma v} \cos \chi_b) \sin \chi_b, \\ m \frac{dv}{dx} \approx \frac{d}{dx} \left(\frac{4}{3} \mu \frac{dv}{dx} \right) + B^2 (\overline{\sigma u} \sin \chi_b - \overline{\sigma v} \cos \chi_b) \cos \chi_b. \end{cases} \quad (147)$$

Then, let us express the velocity derivatives du/dx and dv/dx and the viscous terms in magnitude using (145),

$$\begin{cases} \frac{du}{dx} \approx \frac{u_2 - u_1}{\mathcal{L}}, \\ \frac{dv}{dx} \approx \frac{v_2 - v_1}{\mathcal{L}}, \\ \frac{d}{dx} \left(\mu \frac{du}{dx} \right) = \frac{d\mu}{dx} \frac{du}{dx} + \mu \frac{d^2 u}{dx^2} \approx \frac{\mu_2 - \mu_1}{\mathcal{L}} \frac{u_2 - u_1}{\mathcal{L}} + \bar{\mu} \frac{u_2 - u_1}{\mathcal{L}^2}, \\ \frac{d}{dx} \left(\mu \frac{dv}{dx} \right) = \frac{d\mu}{dx} \frac{dv}{dx} + \mu \frac{d^2 v}{dx^2} \approx \frac{\mu_2 - \mu_1}{\mathcal{L}} \frac{v_2 - v_1}{\mathcal{L}} + \bar{\mu} \frac{v_2 - v_1}{\mathcal{L}^2}, \end{cases} \quad (148)$$

and the averages

$$\begin{cases} \bar{\mu} \approx \frac{\mu_1 + \mu_2}{2}, \\ \overline{\sigma u} \approx \frac{\sigma_1 u_1 + \sigma_2 u_2}{2}, \\ \overline{\sigma v} \approx \frac{\sigma_1 v_1 + \sigma_2 v_2}{2}. \end{cases} \quad (149)$$

On substituting the average of μ , we obtain the expressions for the shear stress components, and on inserting them into (147) and using the fact that the conductivity is zero in front of the shock ($\sigma_1 = 0$), we obtain

$$\begin{cases} m \frac{u_2 - u_1}{\mathcal{L}} \approx -\frac{p_2 - p_1}{\mathcal{L}} + \frac{4}{3} \frac{u_2 - u_1}{\mathcal{L}^2} \frac{3\mu_2 - \mu_1}{2} - \frac{\sigma_2 B^2}{2} (u_2 \sin \chi_b - v_2 \cos \chi_b) \sin \chi_b, \\ m \frac{v_2 - v_1}{\mathcal{L}} \approx \frac{4}{3} \frac{v_2 - v_1}{\mathcal{L}^2} \frac{3\mu_2 - \mu_1}{2} + \frac{\sigma_2 B^2}{2} (u_2 \sin \chi_b - v_2 \cos \chi_b) \cos \chi_b. \end{cases} \quad (150a,b)$$

Now, defining the scale lengths

$$\begin{cases} \mathcal{L}_0 = 2 \frac{3\mu_2 - \mu_1}{3m}, \\ \mathcal{L}_B = \frac{2m}{\sigma_2 B^2}, \end{cases} \quad (151)$$

and extracting v_2 from (150b), inserting it into (150a), then by factorizing and using the definition (44) of ε , the definitions of χ_1 and the Mach number M_1 , we obtain

$$\left(1 + \frac{\mathcal{L}}{\mathcal{L}_B} \cos^2 \chi_b - \frac{\mathcal{L}_0}{\mathcal{L}}\right) \left\{ \left(1 - \frac{\mathcal{L}_0}{\mathcal{L}}\right) (\varepsilon - 1) + \frac{1}{\gamma_1 M_1^2 \cos^2 \chi_1} \left(\frac{p_2}{p_1} - 1\right) \right\} \\ \approx - \left(1 - \frac{\mathcal{L}_0}{\mathcal{L}}\right) \frac{\mathcal{L}}{\mathcal{L}_B} (\varepsilon \sin \chi_b - \tan \chi_1 \cos \chi_b) \sin \chi_b. \quad (152)$$

On the axis ($\chi_1 = 0$, $\chi_b = 0$ or π), this equation reduces to

$$\left(1 + \frac{\mathcal{L}}{\mathcal{L}_B} - \frac{\mathcal{L}_0}{\mathcal{L}}\right) \left\{ \left(1 - \frac{\mathcal{L}_0}{\mathcal{L}}\right) (\varepsilon - 1) + \frac{1}{\gamma_1 M_1^2} \left(\frac{p_2}{p_1} - 1\right) \right\} \approx 0 \quad (153)$$

and the physical solution is written as ($\mathcal{L} > 0$)

$$\mathcal{L} = \frac{\mathcal{L}_B}{2} \left(-1 + \sqrt{1 + 4 \frac{\mathcal{L}_0}{\mathcal{L}_B}} \right). \quad (154)$$

When $\mathcal{L}_0 \ll \mathcal{L}_B$, this yields, by expanding the square root to second order,

$$\mathcal{L} \approx \mathcal{L}_0 \left(1 - \frac{\mathcal{L}_0}{\mathcal{L}_B} \right). \quad (155)$$

The interesting relation (155) shows that the shock thickness decreases as the magnetic field and the electrical conductivity increase. It should be noted that the mass flow rate m in (151) depends on the shock inclination through relation (49).

The magnetic correction term $\mathcal{L}_0/\mathcal{L}_B$ amounts to 1.08×10^{-4} at 40 km and 2.95×10^{-2} at 65 km, yielding values of respectively 15.6 μm and 364 μm for the actual $\mathcal{L}$ (table 3). The values of the relative deviation $\mathcal{L}/\mathcal{L}_0 - 1$ are thus 0.0 % and -2.93 % respectively.

By means of the microscopic interaction parameter S_ρ defined by (129) we cast the ratio $\mathcal{L}_0/\mathcal{L}_B$ into the following form:

$$\frac{\mathcal{L}_0}{\mathcal{L}_B} = \frac{S_\rho}{2}. \quad (156)$$

This behaviour is confirmed in order of magnitude by a plasma physics approach based on the cyclotron or Larmor radius of charged particles moving in an applied magnetic field (Parker 1959),

$$\mathcal{L}_c = \frac{m_p \bar{u}}{q_p B \cos \chi_b}, \quad (157)$$

where m_p and q_p denote respectively the mass and electric charge of the main charged particles, and $\bar{u}$ is the average normal velocity in the shock.

At low altitude, the Hall parameters for electrons and ions become larger than unity, but they are smaller than 1 below 50 km. This means that the plasma is collisional at low altitude and non-collisional above. Therefore, with $m_p = 2.7 \times 10^{-25}$ kg, $\bar{u} = 3.7$ km/s, $q_p = 1.6 \times 10^{-19}$ C and $B = 1$ T, equation (157) yields a value of 620 μm at 65 km on the dipole axis ($\chi_b = 0$ or π) and thus confirms the orders of magnitude we obtain with our expression (151). Moreover, equation (157) shows that $\mathcal{L}_c$ decreases as B increases and confirms the behaviour we put into evidence with (155).

These results justify *a posteriori* the fact that we neglected MHD effects on $\mathcal{L}$. Moreover, the magnetic Reynolds number estimated with the radius of the body nose ($R_b = 0.15$ m) is found to be quite small (table 3) and this justifies the assumption that the applied magnetic field is not modified by the flow.

Appendix C

In this section, we calculate the vorticity jump at a resistive MHD plane shock using the jump relations we derived in § 2.2. With the formalism of § 2 for a plane shock, we write the velocity and vorticity components as

$$\mathbf{V} \begin{pmatrix} u & v & 0 \end{pmatrix}, \quad \boldsymbol{\Omega} \begin{pmatrix} -\frac{\partial v}{\partial z} & \frac{\partial u}{\partial z} & \frac{\partial v}{\partial x} - \frac{\partial u}{\partial y} \end{pmatrix}. \quad (158)$$

The assumption of invariance along y and z implies that the vorticity reduces to its z component,

$$\Omega_z = \frac{\partial v}{\partial x}. \quad (159)$$

The jump of Ω_z is written as

$$[\Omega_z] = \int_{x_1}^{x_2} \frac{\partial}{\partial x} \left(\frac{\partial v}{\partial x} \right) dx. \quad (160)$$

Using relation (15), we obtain

$$[\Omega_z] = \int_{x_1}^{x_2} \frac{\partial}{\partial x} \left(\frac{v}{\mathcal{L}_v} \right) dx, \quad (161)$$

and assuming $\mathcal{L}_v$ constant within the shock

$$[\Omega_z] = \frac{1}{\mathcal{L}_v} \int_{x_1}^{x_2} \frac{\partial v}{\partial x} dx, \quad (162)$$

i.e.

$$[\Omega_z] = \frac{[v]}{\mathcal{L}_v}. \quad (163)$$

Using the approximation (28), namely $\mathcal{L}_v \approx \mathcal{L}_\rho$, we conclude that

$$[\Omega_z] \approx \frac{[v]}{\mathcal{L}_\rho}. \quad (164)$$

This relation shows that vorticity cannot appear behind a plane aerodynamic ($B = 0$) or perpendicular MHD ($\chi_b = \pi/2$) shock since $[v] = 0$ from (21c).

The relation (164) is valid for any plane shock, either normal or oblique. Nevertheless, in the case of an oblique shock, there is a jump of the tangential velocity component that we calculated in § 2.2. From (24b), using the upstream Mach number (27) and the shock angle, and by use of (41), we can eliminate the pressure ratio and make the mass density ratio ε appear. Hence, the jump of transverse velocity becomes

$$v_2 - v_1 = u_1 \left\{ \frac{c}{a} \varepsilon + \left(d - 1 - \frac{bc}{a} \right) \tan \chi_1 \right\}. \quad (165)$$

In the non-magnetic case ($a = 1, b = 0, c = 0, d = 1$), we retrieve that the jump of v is zero.

On substituting the normal component u_1 with its expression

$$u_1 = V_1 \cos \chi_1, \quad (166)$$

we obtain the jump of tangential velocity, so that the vorticity jump (163) therefore is written as

$$[\Omega_z] = \frac{V_1}{\mathcal{L}_\rho} \left\{ \frac{c}{a} \varepsilon \cos \chi_1 + \left(d - 1 - \frac{bc}{a} \right) \sin \chi_1 \right\}. \quad (167)$$

The coefficients a , b , c , d defined by (25) yield

$$\frac{c}{a} = \frac{S_{\rho\sigma} \sin \chi_b \cos \chi_b}{1 + S_{v\sigma} \cos^2 \chi_b}, \quad d - 1 - \frac{bc}{a} = -\frac{S_{v\sigma} \cos^2 \chi_b}{1 + S_{v\sigma} \cos^2 \chi_b}, \quad (168a,b)$$

and after substitution into (167) we finally obtain the vorticity jump,

$$[\Omega_z] = \frac{V_1}{\mathcal{L}_\rho} \frac{\cos \chi_b}{1 + S_{v\sigma} \cos^2 \chi_b} (\varepsilon S_{\rho\sigma} \sin \chi_b \cos \chi_1 - S_{v\sigma} \sin \chi_1 \cos \chi_b). \quad (169)$$

As can be expected, this expression vanishes for a normal shock ($\chi_l = 0$; $\chi_b = 0$). It should be noted also that this vorticity jump is due to the magnetic force alone and does not include curvature effects. Lighthill's aerodynamic expression involves curvature effects but for a perfect gas (Lighthill 1957). Hida's hydromagnetic theory proposes an expression for a perfect gas, and it seems that it works for slightly supersonic shocks ($M_1 \leq 3$) and fails in hypersonic cases (Hida 1953). Our expression is consistent with Wu's theory (Wu 1960).

REFERENCES

- ANDERSON, J.D., JR 1989 *Hypersonic and High Temperature Gas Dynamics*. McGraw-Hill.
- BERTON, R. P. H. 2000 Consistent determination of quasi force-free magnetic fields from observations in solar active regions. *Astron. Astrophys.* **356**, 301–307.
- BISEK, N. J., BOYD, I. D. & POGGIE, J. 2009 Numerical study of electromagnetic aerodynamic control of hypersonic vehicles. In *47th AIAA Aerospace Sciences Meeting, 5–8 January 2009, Orlando (Florida)*, AIAA Paper 2009-1000.
- BITYURIN, V. A. & BOCHAROV, A. N. 2006 Magnetohydrodynamic interaction in hypersonic air flow past a blunt body. *Fluid Dyn.* **41** (5), 843–856.
- BONFIGLIOLI, A. & PACIORRI, R. 2010 Hypersonic flow computations on unstructured grids: shock-capturing versus shock-fitting approach. In *40th Fluid Dynamics Conference and Exhibit, 28 June–1 July 2010, Chicago (Illinois)*, AIAA Paper 2010-4449.
- BUSH, W. B. 1958 Magnetohydrodynamics-hypersonic flow past a blunt body. *J. Aero. Sci.* **25** (11), 685–690, 728.
- CANDLER, G. V. 1989 On the computation of shock shapes in nonequilibrium hypersonic flows. In *27th Aerospace Sciences Meeting, 9–12 January 1989, Reno (Nevada)*, AIAA Paper 1989-312.
- CANDLER, G. V. & MACCORMACK, R. W. 1991 Computation of weakly ionized hypersonic flows in thermochemical nonequilibrium. *J. Thermophysics.* **5** (3), 266–273.
- CAPITELLI, M., COLONNA, G. & D'ANGOLA, A. 2001 Thermodynamic properties and transport coefficients of high-temperature air plasma. In *Pulsed Power Plasma Science, PPPS-2001, 17–22 June 2001, Las Vegas (Nevada)*, vol. 1, pp. 694–697. IEEE.
- CAVUS, H. 2013 On the effects of viscosity on the shock waves for a hydrodynamical case – Part I: basic mechanism. *Adv. Astron.* **2013**, 582965, 1–6.

- CHEN, G., ZHEN, H., LI, X., SU, W. & DONG, C. 2016 Numerical simulation of external MHD generator on board reentry vehicle. *J. Autom. Cont. Engin.* **4** (4), 273–278.
- COACKLEY, J. F. & PORTER, R. W. 1971 Time-dependent numerical analysis of MHD blunt body problem. *AIAA J.* **9** (8), 1624–1626.
- CONTI, R. J. 1966 A theoretical study of non-equilibrium blunt-body flows. *J. Fluid Mech.* **24** (1), 65–88.
- COWLING, T. G. 1976 *Magnetohydrodynamics*. Adam Hilger.
- CRISTOFOLINI, A., BORGHI, C. A., NERETTI, G., PASSARO, A., BACARELLA, D., SCHETTINO, A. & BATTISTA, F. 2010 Experimental activities on the MHD interaction in a hypersonic air flow around a blunt body. In *41st AIAA Plasmadynamics and Lasers Conference, 28 June–1 July 2010, Chicago (Illinois)*, AIAA Paper 2010-4490.
- CRISTOFOLINI, A., BORGHI, C. A., NERETTI, G., PASSARO, A., FANTONI, G. & PAGANUCCI, F. 2008 Magnetohydrodynamics interaction over an axisymmetric body in a hypersonic flow. *J. Spacecr. Rockets* **45** (3), 438–444.
- DE CROMBRUGHE, G., GILFIND, D., ZANDER, F. MCINTYRE, T. & MORGAN, R. 2014 Design of test flows to investigate binary scaling in high enthalpy CO₂–N₂ mixtures. In *19th Australasian Fluid Mechanics Conference, Melbourne (Australia), 8–11 December 2014*, RMIT University.
- DUNN, M. G. & KANG, S. 1973 Theoretical and experimental studies of reentry plasmas. *NASA CR 2232*.
- ERICSON, W. B. & MACIULAITIS, A. 1964 Investigation of magnetohydrodynamic flight control. *J. Spacecraft*, **1** (3), 283–289.
- EVANS, J. S., SCHEXNAYDER, C. J. JR. & HUBER, P. W. 1973 Boundary-layer electron profiles for entry of a blunt slender body at high altitude. *NASA TN D 7332*.
- FALANGA, R. A. & SULLIVAN, E. M. 1970 An inverse-method solution for radiating, nonadiabatic, equilibrium inviscid flow over a blunt body. *NASA TN D 5907*.
- FUJINO, T. & ISHIKAWA, M. 2013 Numerical simulation of MHD flow control along super orbital reentry trajectory. In *44th AIAA Plasmadynamics and Lasers Conference, 24–27 June 2013, San Diego (CA)*, AIAA Paper 2013-3000.
- GILBARG, D. & PAOLUCCI, D. 1953 The structure of shock waves in the continuum theory of fluids. *J. Rat. Mech. Anal.* **2**, 617–642.
- GLASS, I. I. & HALL, J. G. 1959 *Handbook of Supersonic Aerodynamics. Section 18. Shock Tubes*. NAVORD R-1488.
- HALL, J. G., ESCHENROEDER, A. Q. & MARRONE, P. V. 2003 Blunt-nose inviscid airflows with coupled nonequilibrium processes. *J. Spacecr. Rockets* **40** (5), 796–809.
- HAYES, W. D. 1957 The vorticity jump across a gasdynamic discontinuity. *J. Fluid Mech.* **2** (6), 595–600.
- HAYES, W. D. & PROBSTEIN, R. F. 1959 *Hypersonic Flow Theory*. Academic.
- HIDA, K. 1953 An approximate study on the detached shock wave in front of a circular cylinder and a sphere. *J. Phys. Soc. Jap.* **8** (6), 740–745.
- HUBER, P. W. 1958 Tables and graphs of normal-shock parameters at hypersonic Mach numbers and selected altitudes *NACA TN 4352*.
- HUBER, P. W. 1963 Hypersonic shock-heated flow parameters for velocities to 46 000 feet per second and altitudes to 323 000 feet. *NASA TR R-163*.
- HUGONIOT, H. 1889 Mémoire sur la propagation du mouvement dans les corps et spécialement dans les gaz parfaits. Deuxième partie. 58ème cahier, 1–125.

- ITAKAWA, Y. 2006 Cross sections for electron collisions with nitrogen molecules. *J. Phys. Chem. Ref. Data.* **35** (1), 31–53.
- JARVINEN, P. O. 1965 On the use of magnetohydrodynamics during high speed re-entry. *NASA CR-206*.
- JOSYULA, E. & BAILEY, W. F. 2003 Governing equations for weakly ionized plasma flow fields of aerospace vehicles. *J. Spacecr. Rockets* **40** (6), 845–857.
- KAWAMURA, T. 1950 On the detached shock wave in front of a body moving at speeds greater than that of sound. *Mem. Coll. Sci., Univ. Kyoto A* **26** (3), 207–232.
- KAWAMURA, T. 1952 On the detached shock wave in front of a body of revolution moving with supersonic speeds. *J. Phys. Soc. Jap.* **7** (5), 486–488.
- KAWAMURA, T. 1952–53 A note on the detached shock wave in front of a body. *Appl. Mech.* **5** (30–31), 162–165.
- LEVY, R. H. 1963 A simple MHD flow with Hall effect. *AIAA J.* **1** (3), 698–699.
- LEVY, R. H. & PETSCHKE, H. E. 1963 Magnetohydrodynamically supported hypersonic shock layer. *Phys. Fluids* **6** (7), 946–961.
- LIGHTHILL, M. J. 1957 Dynamics of a dissociating gas. Part I – Equilibrium flow. *J. Fluid Mech.* **2** (1), 1–32.
- LYKOUDES, P. S. 1961 The Newtonian approximation in magnetic hypersonic stagnation point flow. *J. Aerosp. Sci.* **28**, 541–546.
- MAICKE, B., BARBER, T. & MAJDALANI, J. 2010 Analytical methodologies for hypersonic propulsion. In *46th AIAA/ASME/SAE/ASEE Joint Propulsion Conference & Exhibit, Joint Propulsion Conferences, 25–28 July 2010, Nashville (TN), AIAA Paper 2010-6553*.
- MASLEN, S. H. 1964 Inviscid hypersonic flow past smooth symmetric bodies. *AIAA J.* **2** (6), 1055–1061.
- MORETTI, G. 2002 Thirty-six years of shock fitting. *Comput. Fluids* **31** (4), 719–723.
- MORETTI, G. & ABBETT, M. 1966 A time-dependent computational method for blunt body flows. *AIAA J.* **4** (12), 2436–2441.
- MORETTI, G. & BLEICH, G. 1967 Three-dimensional flows around blunt bodies. *AIAA J.* **5** (9), 1557–1562.
- MUYLAERT, J., WALPOT, L., OTTENS, H. & CIPOLLINI, F. 2007 Aerothermodynamic reentry flight experiments EXPERT. RTO-EN-AVT-130, Paper 13.
- NAGATA, Y., SATOFUKA, Y., WATANABE, Y., TEZUKA, A., YAMADA, K. & ABE, T. 2013 Experimental study on the magneto-aerodynamic force deflected by magnetic field interaction in a weakly-ionized plasma flow. In *44th AIAA Plasmadynamics and Lasers Conference, 24–27 June 2013, San Diego (CA), AIAA Paper 2013-2999*.
- NOORI, S., HOSSEINI, S. A. & EBRAHIMI, M. 2009 An approximate engineering method for aerodynamic heating solution around blunt body nose. *Engng. Tech.* **70**, 893–897.
- OGUCHI, H. 1960 Blunt body viscous layer with and without a magnetic field. *Phys. Fluids* **3**, 567–580.
- OTSU, H., KONIGORSKI, D. & ABE, T. 2010 Influence of Hall effect on electrodynamic heat shield system for reentry vehicles. *AIAA J.* **48** (10), 2177–2186.
- OTSU, H., MATSUDA, A., ABE, T. & KONIGORSKI, D. 2006 Numerical validation of the magnetic flow control for reentry vehicles. In *37th AIAA Plasmadynamics and Lasers Conference, 5–8 June 2006, San Francisco (CA), AIAA Paper 2006-3236*.
- PAOLUCCI, S. & PAOLUCCI, C. 2016 Shock structure in hypersonic flows. XXIV ICTAM, 21–26 August 2016, Montreal (Canada).

- PARKER, E. N. 1959 Plasma dynamic determination of shock thickness in an ionized gas. *Astrophys. J.* **129**, 217–223.
- PEPE, R., BONFIGLIOLI, A., D'ANGOLA, A., COLONNA, G. & PACIORRI, R. 2014 Shock-fitting versus shock-capturing modeling of strong shocks in nonequilibrium plasmas. *IEEE Trans. Plasma Sci.* **42** (10), 2526–2527.
- PEPE, R., BONFIGLIOLI, A., D'ANGOLA, A., COLONNA, G. & PACIORRI, R. 2015 An unstructured shock-fitting solver for hypersonic plasma flows in chemical non-equilibrium. *Comput. Phys. Commun.* **196**, 179–193.
- POGGIE, J. & GAITONDE, D. V. 2002 Magnetic control of flow past a blunt body: numerical validation and exploration. *Phys. Fluids* **14** (5), 1720–1731.
- PRIEST, E. 1987 *Solar Magneto-Hydrodynamics*. Dordrecht.
- RANKINE, W. J. M. 1870 On the thermodynamic theory of waves of finite longitudinal disturbance. *Proc. R. Soc. Lond.* **160**, 277–288.
- RUSANOV, E. E. 1976 A blunt body in a supersonic stream. *Annu. Rev. Fluid Mech.* **8**, 377–404.
- SAEKS, R. & MURRAY, J. 2003 Analysis of the modified Rankine Hugoniot equations. In *34th AIAA Plasmadynamics and Lasers Conference, 23–26 June 2003, Orlando (Florida)*, AIAA Paper 2003-4180.
- SALAS, M. D. & IOLLO, A. 1996 Entropy jump across an inviscid shock wave. *Theor. Comput. Fluid Dyn.* **8**, 365–375.
- SANTOS, W. F. N. 2012 Aerothermodynamic analysis of a reentry Brazilian satellite. *Braz. J. Phys.* **42** (5), 373–390.
- SCHEXNAYDER, C. J., JR., HUBER, P. W. & EVANS, J. S. 1971 Calculation of electron concentration for a blunt body at orbital speeds and comparison with experimental data. *NASA TN D 6294*.
- SHAPIRO, A. 1953 *The Dynamics and Thermodynamics of Compressible Fluid Flow*. The Ronald Press.
- SHARMA, V. D. & RAM, R. 1971 The vorticity jump across a stationary magnetohydrodynamic discontinuity. *Z. Angew. Math. Phys.* **22**, 1126–1134.
- SRINIVASAN, S., TANNEHILL, J. C. & WEILMUNSTER, K. J. 1987 Simplified curve fits for the thermodynamic properties of equilibrium air. *NASA RP 1181*.
- SUTHERLAND, W. 1893 The viscosity of gases and molecular force. *Phil. Mag.* **5**, **36**, 507–531.
- SUTTON, G. W. & SHERMAN, A. 2006 *Engineering Magnetohydrodynamics*. Dover.
- TAKAHASHI, Y., NAKASATO, R. & OSHIMA, N. 2016 Analysis of radio frequency blackout for a blunt-body capsule in atmospheric reentry missions. *Aerospace* **3** (2), 3010002.
- TANNEHILL, J. C. & MUGGE, P. H. 1974 Improved curve fits for the thermodynamic properties of equilibrium air suitable for numerical computation using time-dependent or shock-capturing methods. *NASA CR 2470*.
- TRAN, A. & POLK, C. 1979a Schumann resonances and electrical conductivity of the atmosphere and lower ionosphere – I. Effects of conductivity at various altitudes on resonance frequencies and attenuation. *J. Atmos. Terr. Phys.* **41**, 1241–1248.
- TRAN, A. & POLK, C. 1979b Schumann resonances and electrical conductivity of the atmosphere and lower ionosphere – II. Evaluation of conductivity profiles from experimental Schumann resonance data. *J. Atmos. Terr. Phys.* **41**, 1249–1261.
- TRUESDELL, C. 1952 On curved shocks in steady plane flow of an ideal fluid. *J. Aero. Sci.* **19**, 826–828.

- VAN DYKE, M. D. 1958 The supersonic blunt-body problem – Review and extension. *J. Aerosp. Sci.* **25** (8), 485–496.
- VIEGAS, J. R. & PENG, T. C. 1961 Electrical conductivity of ionized air in thermodynamic equilibrium. *ARS J.* **31**, 654–657.
- WU, C.-S. 1960 Hypersonic viscous flow near the stagnation point in the presence of magnetic field. *J. Aerosp. Sci.* **27**, 882–893, 950.
- ZEL'DOVICH, YA. B. & RAIZER, YU. P. 1967 *Physics of Shock Waves and High-Temperature Hydrodynamic Phenomena*, vol. 2. Academic.
- ZIEMER, R. W. & BUSH, W. B. 1958 Magnetic field effects on bow shock stand-off distance. *Phys. Rev. Lett.* **1** (2), 58–59.

FIGURES

FIGURE 1. Flowchart of the proposed analytic approach for an MHD resistive shock.

FIGURE 2. Geometrical configuration of a plane oblique MHD shock. The current vector $\mathbf{J}$ along z is perpendicular to the x - y plane and lies in the shock plane.

FIGURE 3. Fitting procedure for a plane oblique MHD resistive shock.

FIGURE 4. Pressure (a) and mass density (b) ratios as functions of upstream Mach number M_1 and microscopic interaction parameter $S_{\rho 0}$ for the test case $\chi_1 = 20^\circ$ and $\chi_b = 170^\circ$ for a plane oblique shock ($\alpha = 2$; $\zeta = 10$).

FIGURE 5. The same as figure 4 for the test case $\chi_1 = 60^\circ$ and $\chi_b = 150^\circ$.

FIGURE 6. Geometrical sketch of an MHD bow shock ahead of an axisymmetric blunt body at hypersonic speed.

FIGURE 7. The fitting procedure for a resistive MHD bow shock.

FIGURE 8. Magnetic lines of force (dashed lines). The shock (dotted line) is assumed to be spherical, at a distance $0.1R_b$ from the sphere in its initial position.

FIGURE 9. Convergence plots of isentropic exponent γ_2 (a), electrical conductivity σ_2 (b), relative shock standoff δ/R_b (c) and shock thickness $\mathcal{L}_\rho$ (d) in resistive MHD shock fitting with the procedure of figure 7 for physical conditions at 65 km on the symmetry axis of a resistive MHD bow shock ($\chi_1 = \theta = 0^\circ$; $\chi_b = 180^\circ$).

FIGURE 10. Magnetic field strength on the shock and on the body surface (a), and angle χ_b of magnetic field vector with respect to the shock normal (b) as functions of the polar angle θ for a spherical shock and the axial dipolar magnetic field of figure 8 ($B_0 = 0.5$ T).

FIGURE 11. Pressure ratio p_2/p_1 (a), temperature T_2 (b), mass density ratio ρ_2/ρ_1 (c), isentropic exponent γ_2 (d), Mach number (e) and deflection angle $\chi_2 - \chi_1$ (f) as functions of upstream velocity angle χ_1 behind a bow shock ($B_0 = 0.5$ T).

FIGURE 12. Electrical conductivity σ_2 (a), magnetic parameter η (b), shock thickness $\mathcal{L}_\rho$ (c) and microscopic interaction parameter S_ρ (d) as functions of upstream velocity angle χ_1 behind a resistive MHD bow shock ($B_0 = 0.5$ T).

FIGURE 13. The magnitude of the vorticity Ω_2 as a function of the upstream velocity angle χ_1 for a spherical shock ($B_0 = 0.5$ T).

FIGURE 14. Electronic collision frequency f_e (a) and density n_e (b) as functions of altitude for a resistive MHD bow shock and rotational downstream flow. The altitude sampling step is 5 km. Also plotted are results from Candler & McCormack (1991) and Huber (1963).

FIGURE 15. Relative shock stand-off δ/R_b as a function of the altitude (a) and macroscopic interaction parameter S_b (b) for a resistive MHD bow shock and rotational downstream flow. Also plotted are results from Poggie & Gaitonde (2002) and Fujino & Ishikawa (2013).

FIGURE 16. Macroscopic (S_b) and microscopic (S_{ρ}) interaction parameters (a) and electrical conductivity (b) as functions of the altitude. Also plotted are results from Huber (1963).

FIGURE 17. (a) Profile of the original isentropic exponent $\gamma(T)$ plotted at two pressures (10^4 Pa (solid) and 10^5 Pa (dotted)) with the reference correlation model (Srinivasan *et al.* 1987). (b) Correlations of our results of figure (11b,d).

FIGURE 18. Profiles of the isentropic exponent γ_2 : (a) for a hypersonic plane oblique shock ($M_1 = 21.7$) as a function of the incident velocity angle χ_1 ; (b) for a normal aerodynamic shock ($\chi_1 = 0^\circ$) as a function of the incident Mach number M_1 , plotted with the same ambient physical conditions at 40 km.

Symbol	Meaning
a, b, c, d	Coefficients of MHD velocity jump
$\mathbf{B}$	Magnetic induction (field) (T)
c_A	Alfvén speed (m s^{-1}) ($= B/(\mu\rho)^{1/2}$)
c_s	Sound speed (m s^{-1})
$\mathbf{E}$	Electric field (V s^{-1})
f_e	Collision frequency of electrons (Hz)
J_r, J_ϕ, J_θ	Electric current components in spherical coordinates (A m^{-2})
HD	Hydrodynamic
$\mathbf{J}$	Electric current vector
$\mathcal{L}$	Characteristic length (m) ; shock thickness
ℓ	Mean free molecular path (m)
M	Mach number ($= V/c_s$)
MHD	Magnetohydrodynamic
$\mathcal{M}$	Molar mass (kg) ; moment of force (N m)
$\mathcal{M}_B$	Magnetic moment (A m^2)
m	Normal mass flow rate ($= \rho_1 u_1$)
m_e	Electron mass ($= 0.91091 \times 10^{-30} \text{ kg}$)
q_e	Electron charge ($= 1.60210 \times 10^{-19} \text{ C}$)
R	Molar constant of perfect gas ($= 8,314 \text{ J K}^{-1} \text{ mole}^{-1}$)
Re	Kinetic Reynolds number
R_m	Magnetic Reynolds number
R_s	Shock radius (m)
R_b	Body nose radius (m)
S	MHD interaction parameter
T	Absolute temperature (K)
$\mathbf{V}$	Fluid velocity vector (m s^{-1})
V	Fluid velocity magnitude (m s^{-1})
V_r, V_ϕ, V_θ	Velocity components in spherical coordinates
u, v, w	Velocity components in Cartesian coordinates
α	Exponent of conductivity power law
γ	Isentropic exponent or specific heat ratio
ε	Ratio ρ_1/ρ_2 of mass densities
η	Magnetic parameter
χ_1, χ_2	Angles of velocity with respect to shock normal
χ_b	Angle of magnetic field with respect to shock normal
μ	Dynamic viscosity (Pl or $\text{kg m}^{-1} \text{ s}^{-1}$)
μ_0	Permittivity of vacuum (H m^{-1})
ν	Kinematic viscosity ($\text{m}^2 \text{ s}^{-1}$)
ν_m	Magnetic diffusivity ($\text{m}^2 \text{ s}^{-1}$)
ρ	Mass density (kg m^{-3})

TABLE 1. Nomenclature of symbols and notations.

Parameter	40 km		65 km	
	1	2	1	2
ρ (kg m ⁻³)	3.85×10^{-3}	5.52×10^{-2}	1.36×10^{-4}	2.26×10^{-3}
p (Pa)	277	1.71×10^5	9.06	6.27×10^3
T (K)	251	6809	232	5868
c_s (m s ⁻¹)	317	1885	305	1768
V (m s ⁻¹)	6900	481	7000	421
M	21.7	0.255	22.9	0.238
γ	1.400	1.148	1.400	1.127
μ (kg m ⁻¹ s ⁻¹)	1.59×10^{-5}	2.13×10^{-4}	1.49×10^{-5}	1.83×10^{-4}
ν (m ² s ⁻¹)	0.00413	0.00386	0.110	0.0811
Re	2.5×10^5	—	9.5×10^3	—
ℓ (mm)	0.0130	0.00205	0.359	0.0459
m (kg m ⁻² s ⁻¹)	26.6	26.6	0.952	0.952

TABLE 2. Physical conditions on the axis before (1) and behind (2) the shock of a re-entry blunt body at 40 km and 65 km in our calculations ($B_0 = 0.5$ T ; $\gamma_1 = 1.40$). Magnetic and non-magnetic results are coincident on the symmetry axis.

Parameter	40 km	65 km
σ (S m ⁻¹)	530	393
B (T)	0.835	0.617
c_A (m s ⁻¹)	1899	9382
ν_m (m ² s ⁻¹)	1503	2023
R_m	4.80×10^{-2}	3.12×10^{-2}
$2\mu_0 p_2/B^2$	0.616	0.0414
ω	10.3	18.6
ε	0.0698	0.0602
η	1.000	0.949
S_ρ	2.17×10^{-4}	5.90×10^{-2}
S_b	2.08	23.6
δ/R_b	0.0620 (0.0524)	0.1744 (0.0458)
$\mathcal{L}_B$ (mm)	143.9	12.7
$\mathcal{L}_\rho$ (mm)	0.0156	0.375
$\mathcal{L}_\rho/\mathcal{L}_B$	1.08×10^{-4}	2.95×10^{-2}
$\ell_l/\mathcal{L}_\rho$	0.832	0.959

TABLE 3. MHD plasma parameters behind the shock on the symmetry axis ($\chi_1 = 0^\circ$; $\chi_b = 0^\circ$ or 180°) ($B_0 = 0.5$ T ; $R_b = 0.15$ m ; $\alpha = 2$; $\zeta = 10$). The relative aerodynamic shock distance δ_0/R_b is also given in parentheses for reference.