Optimal-Cost Reachability Analysis Based on Time Petri Nets

Hanifa Boucheneb, Didier Lime, Olivier Henri Roux, Charlotte Seidner

► To cite this version:

Hanifa Boucheneb, Didier Lime, Olivier Henri Roux, Charlotte Seidner. Optimal-Cost Reachability Analysis Based on Time Petri Nets. 18th International Conference on Application of Concurrency to System Design (ACSD 2018), Jun 2018, Bratislava, Slovakia. hal-01957173

HAL Id: hal-01957173

<https://hal.science/hal-01957173>

Submitted on 17 Dec 2018

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Optimal-cost reachability analysis based on time Petri nets

Hanifa Boucheneb

École Polytechnique de Montréal,
P.O. Box 6079, Station Centre-ville,
Montréal, Québec, Canada, H3C 3A7
hanifa.boucheneb@polymtl.ca

Didier Lime and Olivier H. Roux

École Centrale de Nantes,
1, rue de la Noe – BP 92101
44321 Nantes Cedex 3, France
{didier.lime,olivier-h.roux}@ec-nantes.fr

Charlotte Seidner

Université de Nantes
2 avenue du Pr Jean Rouxel – BP 539
44475 Carquefou Cedex, France
Charlotte.Seidner@univ-nantes.fr

Abstract—This paper investigates the optimal-cost reachability problem in the context of time Petri nets, where a rate cost is associated with each place. This problem consists in deciding whether or not there exists a sequence of transitions reaching, with minimal cost, a given goal marking. This paper shows that for some subclasses of cost time Petri nets, the optimal-cost reachability problem can be solved more efficiently using a method based on the state classes, without resorting to linear programming or splitting state classes.

I. INTRODUCTION

Time Petri nets (TPNs for short) are a simple yet powerful formalism useful to model and verify real-time, concurrent systems that are therefore subject to time constraints. In TPNs, a firing interval, associated with each transition, specifies the minimum and maximum duration it must be maintained enabled before its firing. Thus, TPNs can model time constraints, even when the exact delays or durations of events are not known. The verification of a TPN is based on the state space abstraction that takes into account the time constraints of the model, while preserving its markings and firing sequences.

This paper deals with the cost time Petri nets (cTPNs for short) and investigates the optimal cost reachability problem. A cTPN is a TPN extended with rate costs associated with its places. The rate cost of a place p is the sojourn cost (per time unit) of each token in place p . These rate costs do not affect the behaviour of the TPN but they allow to determine the sojourn cost in each marking and also the cost of firing a sequence of transitions.

The optimal cost reachability problem can be stated as the problem of deciding if there exists a sequence of transitions ω that allows to reach with minimal cost a given goal marking. Starting from the initial marking, the marking of the model evolves by firing transitions. Each time a transition is fired, some tokens are consumed and some others are produced. We define, for each transition t , a rate cost called incidence rate cost of t as the sum of rate costs of tokens produced by t minus the sum of rate costs of tokens consumed by t . We show that for sequences such that the incidence rate costs of their transitions are all non-negative or all non-positive, their optimal-costs can be computed more efficiently based on the state class method without using techniques of linear programming or decomposing state classes, as done previ-

ously. Moreover, we show how to compute the optimal-cost of sequences such that the firing interval of their transitions are all singular. Therefore, the optimal cost reachability problem can be solved more efficiently for some subclasses of cTPNs.

Such subclasses might seem restrictive but can in fact model a wide range of applications. Consider for instance a leak in a pressure pipe: until its fixing, the rate at which the water leaks will surely increase, as the leak keeps getting larger. The subclass of model can also describe any economic system based on rarefying resources such as oil or Bitcoins, where the cost of things keep increasing.

The optimal-cost reachability problem has been addressed for Priced Timed Automata (PTAs for short) in [1]–[5] using the region graphs and the zone based graphs. In [1], the authors have proved the decidability of the optimal-cost problem for PTAs with non-negative costs. In [2]–[4], the computation of the optimal-cost to reach a goal location is based on a forward exploration of zones extended with linear cost functions. The linear cost function of a zone gives the optimal-costs to reach each state within the zone. In [5], the authors have improved the approach, developed in [2]–[4], so as to ensure termination of the forward exploration algorithm, even when clocks are not bounded and costs are negative, provided that the PTA is free of negative cost cycles.

For priced timed/time Petri nets, the optimal-cost reachability problem has been addressed in [6], [7]. In [6], the considered model is a timed arc Petri net, under weak firing semantics, extended with rate costs and firing costs associated with places and transitions, respectively. The computation of the optimal-cost for reaching a goal marking is based on similar techniques to those of PTAs [1]. In [7], the authors have investigated the optimal-cost reachability problem for time Petri nets where each transition has a firing cost and each marking has a rate cost (represented as a linear rate cost function over markings). To compute the optimal-cost to reach a goal marking, the authors have first revisited, to include costs, the state class graph method and then reduced the computation, as all other techniques, to a linear programming problem.

The rest of the paper is organised as follows. Section II is devoted to the TPN model, its semantics and its state class graph method. Section III presents the TPN extended with

costs considered here and then defines the cost of a run and the optimal-cost of a sequence. It also shows how to rewrite the cost of a run based on the incidence rate costs of its transitions. Section IV investigates efficient computation procedures of the optimal-cost of firing a sequence of transitions from a state class that need neither minimisation techniques nor splitting state classes. Section V shows by means of a case study how the optimal-costs are computed. Section VI concludes the paper by some future work.

II. TIME PETRI NETS

A. Definition and semantics

Syntactically, a time Petri net is a Petri net where a firing time intervals is associated with each transition.

Let $\mathbb{N}$, $\mathbb{Z}$, $\mathbb{Q}^+$ and $\mathbb{R}^+$ be the set of non-negative integers, the set of integers, the set of non-negative rational numbers and the set of non-negative real numbers, respectively. Let $\mathbb{Q}_{[\cdot]}^+$ be the set of non-empty intervals of $\mathbb{R}^+$ whose bounds are in $\mathbb{Q}^+$ and $\mathbb{Q}^+ \cup \{\infty\}$, respectively. For an interval $I \in \mathbb{Q}_{[\cdot]}^+$, $\downarrow I$ and $\uparrow I$ denote its lower and upper bounds, respectively.

Formally, a TPN is a tuple $\mathcal{N} = (P, T, pre, post, M_0, Is)$ where P and $T = \{t_1, \dots, t_m\}$ (with $m > 0$) are finite sets of places and transitions such that $P \cap T = \emptyset$, pre and $post$ are the backward and the forward incidence functions ($pre, post : P \times T \rightarrow \mathbb{N}$), M_0 is the initial marking ($M_0 : P \rightarrow \mathbb{N}$), and Is is the static firing interval function ($Is : T \rightarrow \mathbb{Q}_{[\cdot]}^+$).

Let $\mathcal{N} = (P, T, pre, post, M_0, Is)$ be a TPN, $M : P \rightarrow \mathbb{N}$ a marking and t_i a transition of T . Transition t_i is enabled for M iff all required tokens for firing t_i are present in M , i.e., $\forall p \in P, M(p) \geq pre(p, t_i)$.

In this paper, we use the original semantics of the TPN [8]: If a transition is multi-enabled in some state, only one instance of this transition is considered (single-server semantics), and when a transition is fired, all transitions disabled and enabled again, during this firing, are newly enabled.

We denote $En(M)$ the set of all transitions enabled for M , i.e., $En(M) = \{t_i \in T \mid \forall p \in P, pre(p, t_i) \leq M(p)\}$.

If M results from firing some transition t_f from some marking, $Nw(M, t_f)$ denotes the set of all transitions newly enabled in M , i.e., $Nw(M, t_f) = \{t_i \in En(M) \mid t_i = t_f \vee \exists p \in P, M(p) - Post(p, t_f) < pre(p, t_i)\}$.

The TPN state is defined as a pair $s = (M, I)$, where M is a marking and I is a firing interval function ($I : En(M) \rightarrow \mathbb{Q}_{[\cdot]}^+$). The initial state of the TPN model is $s_0 = (M_0, I_0)$ where $I_0(t_i) = Is(t_i)$, for all $t_i \in En(M_0)$. The TPN state evolves either by elapsing time or by firing transitions. When a transition t_i becomes enabled, its firing interval is set to its static firing interval $Is(t_i)$. The bounds of this interval decrease synchronously with time, until t_i is fired or disabled by another firing. t_i can fire if the lower bound of its firing interval reaches 0 but must fire, without any additional delay, as far as any conflict avoids it, if the upper bound of its firing interval reaches 0. The firing of a transition takes no time and leads to a new marking.

Let (M, I) and (M', I') be two interval states of the TPN model, $\theta \in \mathbb{R}^+$ and $t_f \in T$. We write $(M, I) \xrightarrow{\theta} (M', I')$,

also denoted $(M, I) + \theta$, iff from state (M, I) , we reach the state (M', I') by a time progression of θ units, i.e.,

$$\forall t_i \in En(M), \theta \leq \uparrow I(t_i), M' = M \text{ and}$$

$$\forall t_j \in En(M'), I'(t_j) = [Max(\downarrow I(t_j) - \theta, 0), \uparrow I(t_j) - \theta]$$

We write $(M, I) \xrightarrow{t_f} (M', I')$ iff from state (M, I) , we reach the state (M', I') by firing immediately the transition t_f , i.e.,

$$t_f \in En(M), \downarrow I(t_f) = 0$$

$$\forall p \in P, M'(p) = M(p) - pre(p, t_f) + post(p, t_f) \text{ and}$$

$$\forall t_i \in En(M'), I'(t_i) = \begin{cases} Is(t_i) & \text{if } t_i \in Nw(M', t_f) \\ I(t_i) & \text{otherwise.} \end{cases}$$

We also use the abbreviation $(M, I) \xrightarrow{\theta t_f} (M', I')$ for $(M, I) \xrightarrow{\theta} (M, I) + \theta \xrightarrow{t_f} (M', I')$.

The TPN state space is the transition system $(S, \xrightarrow{\cdot}, s_0)$, where s_0 is the initial state of the TPN and $S = \{s \mid s_0 \xrightarrow{*} s\}$ ($\xrightarrow{*}$ being the reflexive and transitive closure of the relation $\xrightarrow{\cdot}$ defined above) is the set of reachable states of the model.

A run in the TPN state space $(S, \xrightarrow{\cdot}, s_0)$, starting from a state s_1 , is a sequence $\sigma = s_1 \xrightarrow{\theta_1 t_1} s_2 \xrightarrow{\theta_2 t_2} s_3 \dots$. Sequences $\theta_1 t_1 \theta_2 t_2 \dots$ and $t_1 t_2 \dots$ are the timed trace and the trace (firing sequence) of σ , respectively. A marking M is reachable iff $\exists s \in S$ s.t. its marking is M . The runs of a TPN are all the maximal runs starting from its initial state s_0 .

B. State class graphs

Among the TPN state space abstractions proposed in the literature, we consider here the state class graph (SCG) [9], [10]. A SCG state class α consists of a marking M and a conjunction F of atomic constraints¹ over the firing dates of the enabled transitions in marking M and the firing date, denoted by $\underline{t}_0$ of the transition leading to α . It represents an over-approximation of the set of states reached by the same firing sequence from the initial TPN state. Note that for convenience purposes, firing delays in the classical SCG state classes in [9] are replaced by firing dates. The formula F characterises the union of the firing date domains of all states within α , reached by the same firing sequence from the initial state of the TPN.

The initial SCG state class of the TPN is the pair $\alpha_0 = (M_0, F_0)$, where M_0 is the initial marking and $F_0 =$

$$\bigwedge_{t_i \in En(M_0)} \downarrow Is(t_i) \leq \underline{t}_i - \underline{t}_0 \leq \uparrow Is(t_i),$$

where $\underline{t}_i$ is a non-negative real valued variable representing the firing date of the transition t_i and $\underline{t}_0$ is a variable representing the date of α_0 , which is supposed to be 0 for the initial state class.

From the practical point of view, F is represented by a *Difference Bound Matrix* (DBM in short) [11]. The DBM of F is a square matrix D , indexed by variables of F . Each entry

¹An atomic constraint is of the form $x - y \leq c$, where x, y are real valued variables, $c \in \mathbb{Q} \cup \{\infty\}$ and $\mathbb{Q}$ is the set of rational numbers (for economy of notation, we use operator $\leq$ even if $c = \infty$).

d_{ij} represents the atomic constraint $\underline{t}_i - \underline{t}_j \leq d_{ij}$. If there is no upper bound on $\underline{t}_i - \underline{t}_j$ with $i \neq j$, d_{ij} is set to ∞ . Entry d_{ii} is set to 0. Although the same non-empty domain may be encoded by different DBMs, they have a canonical form. The canonical form of a DBM is the representation with tightest bounds on all differences between variables, computed by propagating the effect of each entry through the DBM. A DBM can be seen as the matrix representation of a graph, called a constraint graph [12]. Its canonical form can be computed in $O(n^3)$, n being the number of variables in the DBM, using a shortest path algorithm, like Floyd-Warshall's all-pairs shortest path algorithm [13].

Let $\mathcal{C}_S$ be the set of all syntactically correct SCG state classes and succ a state class successor function: $\mathcal{C}_S \times T \rightarrow \mathcal{C}_S \cup \{\emptyset\}$, defined by: $\forall \alpha = (M, F) \in \mathcal{C}_S, \forall t_f \in T$,

- $\text{succ}(\alpha, t_f) \neq \emptyset$ iff $t_f \in \text{En}(M)$ and the following formula is consistent (i.e., satisfiable): $F \wedge (\bigwedge_{t \in \text{En}(M)} \underline{t}_f \leq \underline{t})$.

Intuitively, it means that t_f is enabled in M and t_f is firable from α before all other transitions enabled at M . In other words, t_f is enabled in M and there is, at least, a valuation of firing dates in F s.t. t_f has the smallest firing date.

- If $\text{succ}(\alpha, t_f) \neq \emptyset$ then $\text{succ}(\alpha, t_f) = (M', F')$, where: $\forall p \in P, M'(p) = M(p) - \text{pre}(p, t_f) + \text{post}(p, t_f)$ and F' is computed in 3 steps:

1) Set F' to

$$F \wedge \bigwedge_{t \in \text{En}(M)} \underline{t}_f \leq \underline{t} \wedge \bigwedge_{t \in \text{Nw}(M, t_f)} \downarrow \text{Is}(t) \leq \underline{t} - \underline{t}_f \leq \uparrow \text{Is}(t).$$

Notice that without loss of generality, for economy of notations, we suppose that the transitions of $\text{En}(M)$ are different from those newly enabled by transition t_f from M .

2) Put F' in canonical form².

3) Eliminate $\underline{t}_0$ and all variables associated with transitions of $\text{CF}(M, t_f) - \{t_f\}$ and rename $\underline{t}_f$ in $\underline{t}_0$.

Canonical forms make operations over DBMs much simpler [11]. Two state classes are said to be equal iff they have the same canonical form (i.e., they have the same marking and the DBMs of their formulas have the same canonical form). Note that, in the following, we will use indifferently (M, F) or (M, D) to refer to the state class α , and we suppose that all DBMs are in canonical form. DBM canonical forms allow also to reduce the complexity of the firing rule as follows [10].

Let $\alpha = (M, D)$ be a state class and $t_f \in T$ a transition.

- t_f is firable from α iff

$$t_f \in \text{En}(M) \wedge \forall t_i \in \text{En}(M), d_{if} \geq 0.$$

- If t_f is firable from α then its successor state class by t_f is the state class $\alpha' = (M', D')$, where M' and

the canonical form of the DBM of D' are computed as follows:

$$\forall p \in P, M'(p) = M(p) - \text{pre}(p, t_f) + \text{post}(p, t_f) \text{ and } \forall t_i, t_j \in \text{En}(M'),$$

$$d'_{i0} = \begin{cases} \uparrow \text{Is}(t_i) & \text{if } t_i \in \text{Nw}(M, t_f), \\ d_{if} & \text{if } t_i \notin \text{Nw}(M, t_f), \end{cases}$$

$$d'_{0j} = \begin{cases} -\downarrow \text{Is}(t_j) & \text{if } t_j \in \text{Nw}(M, t_f), \\ \min_{t_u \in \text{En}(M)} d_{uj} & \text{if } t_j \notin \text{Nw}(M, t_f), \end{cases}$$

$$d'_{ij} = \begin{cases} 0 & \text{if } i = j, \\ \min(d_{ij}, d'_{i0} + d'_{0j}) & \text{if } i \neq j \wedge t_i, t_j \notin \text{Nw}(M, t_f), \\ d'_{i0} + d'_{0j} & \text{otherwise} \end{cases}$$

III. COST TIME PETRI NETS

A. Definition and semantics

A cost time Petri net (cTPN for short) is a time Petri net where a rate cost is associated with each place, giving the sojourn cost per time unit of each token in that place. Formally, a *Cost Time Petri Net* is a tuple $\mathcal{N}_c = (P, T, \text{pre}, \text{post}, M_0, I_s, r)$ where:

- $\mathcal{N} = (P, T, \text{pre}, \text{post}, M_0, I_s)$ is a TPN,
- $r : P \rightarrow \mathbb{Z}$ is a rate cost function that associates a rate cost with each place of the TPN.

Note that no cost is associated with the discrete firings of transitions; however, these costs can be added without affecting the results provided in this paper.

Let $\mathcal{N}_c$ be a cTPN, $t \in T$ a transition and M a marking of the cTPN. We denote by $\text{rm}(M)$ the rate cost of M :

$$\text{rm}(M) = \sum_{p \in P} M(p) \times r(p).$$

The rate costs of places can be defined as in [7] by a linear function over markings. We define the incidence rate cost of t by:

$$\text{rt}(t) = \sum_{p \in P} (\text{post}(p, t) - \text{pre}(p, t)) \times r(p).$$

Intuitively, it represents the impact of firing t on the rate cost of a marking.

The semantics of a cTPN $\mathcal{N}_c = (P, T, \text{pre}, \text{post}, M_0, I_s, r)$ is the semantics of the TPN $\mathcal{N} = (P, T, \text{pre}, \text{post}, M_0, I_s)$. However, the rate costs associated with places allow to compute different costs such as the costs of runs and the optimal costs of firing a sequence from a state or a state class of $\mathcal{N}$.

B. Cost of a run

Let $s_1 = (M_1, I_1)$ be a state of $\mathcal{N}_c$ and $\sigma = (M_1, I_1) \xrightarrow{\theta_1 t_1} (M_2, I_2) \cdots (M_n, I_n) \xrightarrow{\theta_n t_n} (M_{n+1}, I_{n+1})$ a run of s_1 . The cost of σ is defined by:

$$\text{Cost}(\sigma) = \sum_{i=1}^n (\theta_i \times \text{rm}(M_i)).$$

²The canonical form of F' is the formula corresponding to the canonical form of its DBM.

Let τ_0 the date at which the state s_1 is reached and $\tau_j = \tau_0 + \sum_{i=1}^j \theta_i$ be the firing date of the transition t_j in σ , for $j = 1, n$. Proposition 1 rewrites $Cost(\sigma)$ by means of the firing dates and incidence rate costs of transitions of σ (see Fig. 1). As we will show, this form is more useful to deal with the optimal-cost problem in some cases. The optimal-cost of $Cost(\sigma)$ can be also rewritten by means of the firing dates and the rate costs of markings as shown in Proposition 2.

Proposition 1:

$$Cost(\sigma) = rm(M_1) \times (\tau_n - \tau_0) + \sum_{j=1}^{n-1} rt(t_j) \times (\tau_n - \tau_j).$$

Proof: By definition, $Cost(\sigma) = \sum_{i=1}^n (\theta_i \times rm(M_i))$. For $i = 2, n$, the rate cost of the successor marking M_i of M_{i-1} by t_i is $rm(M_i) = rm(M_{i-1}) + rt(t_{i-1})$. Therefore, for $i = 2, n$,

$$rm(M_i) = rm(M_1) + \sum_{j=1}^{i-1} rt(t_j).$$

Then:

$$Cost(\sigma) = \theta_1 \times rm(M_1) + \sum_{i=2}^n (\theta_i \times (rm(M_1) + \sum_{j=1}^{i-1} rt(t_j))).$$

It can be developed and rewritten as follows:

$$\begin{aligned} & \theta_1 \times rm(M_1) + \\ & \theta_2 \times (rm(M_1) + rt(t_1)) + \dots + \\ & \theta_n \times (rm(M_1) + rt(t_1) + rt(t_2) + \dots + rt(t_{n-1})). \end{aligned}$$

Finally, $Cost(\sigma)$ can be rewritten so as the rate cost of M_1 (i.e., $rm(M_1)$) is the coefficient of $\sum_{i=1}^n \theta_i$, the incidence rate cost of t_1 (i.e., $rt(t_1)$) is the coefficient of $\sum_{i=2}^n \theta_i$, ..., and so on, the incidence rate cost of t_{n-1} (i.e., $rt(t_{n-1})$) is the coefficient of θ_n . It follows that:

$$Cost(\sigma) = rm(M_1) \times \left(\sum_{i=1}^n \theta_i \right) + \sum_{j=1}^{n-1} rt(t_j) \times \left(\sum_{i=j+1}^n \theta_i \right).$$

To achieve the proof, it suffices to replace $\sum_{i=1}^n \theta_i$ with $\tau_n - \tau_0$

and $\sum_{i=j+1}^n \theta_i$ with $\tau_n - \tau_j$. ■

Proposition 2:

$$Cost(\sigma) = \left(\sum_{i=1}^{n-1} -rt(t_i) \times \tau_i \right) + rm(M_n) \times \tau_n.$$

Proof: By definition, $Cost(\sigma) = \sum_{i=1}^n (\theta_i \times rm(M_i))$. For $i = 1, n$, $\theta_i = \tau_i - \tau_{i-1}$. Then:

$$Cost(\sigma) = \sum_{i=1}^n ((\tau_i - \tau_{i-1}) \times rm(M_i)).$$

For $i = 1, n-1$, the rate cost of the successor marking M_{i+1} of M_i by t_i is $rm(M_{i+1}) = rm(M_i) + rt(t_i)$. Therefore, for $i = 1, n-1$, $rt(t_i) = rm(M_{i+1}) - rm(M_i)$. The previous expression of $Cost(\sigma)$ can be developed and rewritten as follows:

$$\left(\sum_{i=1}^{n-1} (rm(M_i) - rm(M_{i+1}) \times \tau_i) \right) + rm(M_n) \times \tau_n.$$

To achieve the proof, it suffices to replace $rm(M_i) - rm(M_{i+1})$ with $-rt(t_i)$. ■

C. Optimal cost of a firing sequence

Let α_1 be a state class of $\mathcal{N}_c$ and $\rho = \alpha_1 \xrightarrow{t_1} \alpha_2 \cdots \alpha_n \xrightarrow{t_n} \alpha_{n+1}$ a path of α_1 , $\omega = t_1 \cdots t_n$ and $\Pi(\alpha_1, \omega)$ the set of runs of α_1 that support the same sequence of transitions ω and lead to states of $\alpha = \alpha_{n+1}$. The optimal-cost of firing ω from α_1 (or the optimal-cost of ρ) is:

$$OptCost(\alpha_1, \omega) = \min_{\sigma \in \Pi(\alpha_1, \omega)} Cost(\sigma).$$

The optimal-cost of firing ω from α_1 can be computed by extending state classes with costs and using linear programming techniques as in [7].

D. Optimal-cost reachability problem

The classical forward exploration algorithm in [2]–[4], [7] is adapted in Algorithm 1 to compute the optimal-cost to reach, from the initial marking, a marking belonging to a given set of markings *Goal*. For each state class α such that its marking is in *Goal*, its optimal-cost is computed and compared with *MinCost*, where the smallest cost computed so far is saved. As usual, the lists *Passed* and *Waiting* are used to store the already processed and not yet processed state classes, respectively. The notation $\omega \prec \omega'$ means that ω is a prefix of ω' .

For bounded TPNs with no negative cost cycles, the algorithm terminates as for infinite sequences only finite prefixes, yielding the longest elementary paths, are explored.

In the following sections, we investigate cases where the optimal-costs of firing sequences can be computed without splitting state classes nor using linear programming techniques.

IV. COMPUTING OPTIMAL COST OF FIRING SEQUENCES

Let $\alpha_1 = (M_1, F_1)$ be a state class of $\mathcal{N}_c$ and $\rho = \alpha_1 \xrightarrow{t_1} \alpha_2 \cdots \alpha_n \xrightarrow{t_n} \alpha_{n+1}$ a path of α_1 and $\omega = t_1 \cdots t_n$. For ease of notation, we suppose that all transitions within $En(M_1)$ and those enabled by every transition of ω are all different. The firing date domain of transitions of ω from α_1 can be retrieved by modifying the firing rule given in Section II-B. Indeed, it suffices, in step 3 of *succ*(α_i, t_i), for $i \in [1, n]$, to keep $\underline{t}_i$. More precisely replace step 3 with: Eliminate all variables associated with transitions of $CF(M_i, t_i) - \{t_i\}$. With this modification, each variable $\underline{t}_i$, for $i \in [1, n]$, represents the firing date of the i^{th} transition of ω . The variable $\underline{t}_0$ is the

Fig. 1. The cost of the run σ based on the firing dates and incidence rate costs of its transitions

Algorithm 1 Symbolic algorithm for optimal-cost reachability problem

```

1:  $MinCost \leftarrow \infty$ 
2:  $Passed \leftarrow \emptyset$ 
3:  $Waiting \leftarrow \{((M_0, D_0), \epsilon)\}$ 
4: while  $Waiting \neq \emptyset$  do
5:   select  $((M, D), \omega)$  from  $Waiting$ 
6:   if  $M \in Goal$  and  $OptCost((M_0, D_0), \omega) < MinCost$  then
7:      $MinCost \leftarrow OptCost((M_0, D_0), \omega)$ 
8:   end if
9:   if (for all  $((M', D'), \omega') \in Passed$ ,  $((M', D') \neq (M, D))$  or  $\neg(\omega' \prec \omega)$ ) then
10:    add  $((M, D), \omega)$  to  $Passed$ 
11:    for all  $t \in Fr(M, D)$ , add  $(succ((M, D), t), \omega t)$  to  $Waiting$ 
12:   end if
13: end while
14: return  $MinCost$ 

```

date when α_1 is reached. Let FG be the resulting formula. The firing date domain of transitions of ω from α_1 is the projection of the domain of FG to $\underline{t}_i$ for $i \in [0, n]$.

A. Case of non-negative incidence rate costs

For this section, we suppose that the incidence rate costs of all transitions of ω , except the last one are non-negative and $rm(M_1) \geq 0$. We will show that, under these assumptions, to compute the optimal-cost of firing ω from α_1 , we need to keep track of the minimal delay between the previously fired transitions and the coming ones, including the current one. But we do not need to retrieve delays between the previously fired transitions. Consequently, the relevant part of FG needed to compute the optimal-costs can be represented by a DBM of order $(|\omega| + 1) \times |En(M) \cup \{t_n\}|$.

We denote by G the DBM in canonical form of order $(|\omega| + 1) \times |En(M) \cup \{\underline{t}_n\}|$ defined by $\forall i \in [0, |\omega|], \forall t_j \in En(M) \cup \{t_n\}, g_{ij} = Max(\underline{t}_i - \underline{t}_j | FG)$. Since $\underline{t}_i - \underline{t}_j \leq 0$, the value $-g_{ij}$ is the minimal delay between the firing dates $\underline{t}_j$ and $\underline{t}_i$. Note that G is a sub-matrix of the DBM in canonical form of FG . The size of the DBM of FG is $(|\omega| + 1 + |En(M)|)^2$.

Theorem 1:

$$OptCost(\alpha_1, \omega) = -g_{0n} \times rm(M_1) + \sum_{i=1}^{n-1} rt(t_i) \times -g_{in}.$$

Proof: Let GG be the DBM in canonical form of FG . Recall that G is a sub-matrix of GG . To achieve the proof, we first show that the valuation $v_i = g_{in} - g_{0n}$ for $i \in [1, n]$ is a feasible firing schedule for ω , i.e., for $i, k \in [1, n]$,

$$-gg_{0i} \leq v_i \leq gg_{i0} \text{ and } v_i - v_k \leq gg_{ik}.$$

By definition, for $i \in [1, n]$, $v_i = g_{in} - g_{0n} = gg_{in} - gg_{0n}$, then for $i, k \in [1, n]$, $v_i - v_k = g_{in} - g_{kn} = gg_{in} - gg_{kn}$. Since GG is in canonical form, it holds that $gg_{in} \leq gg_{i0} + gg_{0n}$, $gg_{0n} \leq gg_{0i} + gg_{in}$, and $gg_{in} \leq gg_{ik} + gg_{kn}$. It follows that $-gg_{0i} \leq v_i \leq gg_{i0}$ and $v_i - v_k \leq gg_{ik}$.

The run corresponding to this firing schedule of ω is shown in Fig. 2. Its cost is:

$$-g_{0n} \times rm(M_1) + \sum_{i=1}^{n-1} rt(t_i) \times -g_{in}.$$

By assumption, $rm(M_1) \geq 0$ and for $i \in [1, n-1]$, $rt(t_i) \geq 0$. Furthermore, for $i \in [0, n]$, $-g_{in}$ is the minimal value of $\underline{t}_n - \underline{t}_i$ in FG , where $\underline{t}_n$ is the firing date of last transition of ω .

$$\text{Therefore, } OptCost(\alpha_1, \omega) = -g_{0n} \times rm(M_1) + \sum_{i=1}^{n-1} rt(t_i) \times -g_{in}.$$

■

According to the definition of G , for $\omega = \epsilon$, G is a DBM of order $1 \times (|En(M)| + 1)$ defined by $\forall t_j \in En(M) \cup \{t_0\}, g_{0j} = d_{0j}$. Let us show now how to compute progressively the DBM G of a nonempty sequence.

Proposition 3: Let α be the state class reached by a path ρ , G the corresponding DBM and t_f a transition firable from α and $\alpha' = (M', D') = succ(\alpha, t_f)$.

Then, the DBM G' of the path $\rho \xrightarrow{t_f} (M', D')$ is the DBM in canonical form of order $(|\omega t_f| + 1) \times |En(M') \cup \{t_f\}|$ defined by: $\forall i \in [0, |\omega t_f|]$ and $t_j \in En(M') \cup \{t_f\}$, $g'_{ij} =$

$$\begin{cases} Min(g_{ij}, g_{if} + d'_{0j}) & \text{if } i \leq |\omega| \wedge t_j \notin Nw(M, t_f) \\ g_{if} + d'_{0j} & \text{if } i \leq |\omega| \wedge t_j \in Nw(M, t_f) \\ d'_{0j} & \text{if } i = |\omega t_f| \end{cases}$$

where $d'_{0j} = \min_{t_u \in En(M)} d_{uj}$, if $t_j \notin Nw(M, t_f)$ and $d'_{0j} = -\downarrow Is(t_j)$, otherwise.

Proof: The proof is based on the constraints added to compute $succ(\alpha, t_f)$. Indeed, the firing condition is obtained by adding to D , the constraints:

$$\begin{aligned} &\underline{t}_f \leq \underline{t}_u, \text{ for } t_u \in En(M) \text{ and} \\ &\downarrow Is(t_j) \leq \underline{t}_j - \underline{t}_f \leq \uparrow Is(t_j), \text{ for } t_j \in Nw(M, t_f). \end{aligned}$$

Notice that all the added constraints involve t_f and in the corresponding constraint graph, they are represented by arcs $(\underline{t}_f, \underline{t}_u, 0)$, for $t_u \in En(M)$, $(\underline{t}_j, \underline{t}_f, \uparrow Is(t_j))$ and $(\underline{t}_f, \underline{t}_j, -\downarrow Is(t_j))$, for $t_j \in Nw(M, t_f)$.

Therefore, the shortest path connecting a node $\underline{t}_i$, for $i \in [0, |\omega t_f|]$, to a node $\underline{t}_j \in En(M')$ is:

$Min(g_{ij}, g_{if} + \underset{t_u \in En(M)}{Min} d_{uj})$, if $t_j \notin Nw(M, t_f)$ and $g_{if} - \downarrow Is(t_j)$, otherwise.

By the firing rule given in II-B, it holds that:

$$d'_{0j} = \begin{cases} -\downarrow Is(t_j) & \text{if } t_j \in Nw(M, t_f), \\ \underset{t_u \in En(M)}{Min} d_{uj} & \text{if } t_j \notin Nw(M, t_f), \end{cases}$$

Note that, $\underset{t_u \in En(M)}{Min} d_{uf} = 0$ as t_f is firable. Consequently,

$g'_{if} = g_{if}$, for $i \in [0, |\omega t_f|]$.

For $i = |\omega t_f|$, $g'_{ij} = d'_{0j}$ as g'_{ij} is the smallest path connecting $\underline{t}_f$ to $\underline{t}_j$. ■

The computation of the optimal-cost of firing ω from α_1 needs to carry in the DBM G the minimal firing delay between each fired transition of ω and the coming ones, including the current one. Thus, the size of G grows with the size of ω : indeed, the optimal-cost of ωt_f is reached when t_f is fired as soon as possible (i.e., $-g_{nf} = -d_{0f}$) from α and the previous ones are fired as late as possible (i.e., $-g_{if}$) without causing any delay to t_f . It means that, to retrieve the firing schedule yielding the optimal-cost of ω , the firing dates of its previous transitions need to be updated to take into account the fact that t_f is fired as soon as possible and the previous ones are fired as late as possible but before t_f .

However, for bounded TPNs with no negative cost cycles, each infinite sequence ω'' of $\mathcal{N}_c$, has some prefix ω followed by a repetitive sequence ω' that loops on a state class α reachable from the initial state class α_0 by ω . It follows that $OptCost(\alpha_0, \omega) \leq OptCost(\alpha_0, \omega'')$ and $OptCost(\alpha, \omega') \leq OptCost(\alpha, \omega'^k)$, for $k \geq 1$. The cost of a cycle is non-negative, if the sum of the incidence rate costs of all its transitions is non-negative and the rate cost of one of its marking is non-negative. This sufficient condition guarantees for a cycle a non-negative cost.

In the following, we investigate the possibility to reduce the size of the DBM G .

B. Memoryless state classes w.r.t. optimal-costs

Let $\alpha = (M, D)$ be the state class reached by a sequence ω from a state class α_1 of $\mathcal{N}$. The state class α is said to be memoryless w.r.t. optimal-costs iff for each sequence ω' of α , $OptCost(\alpha_1, \omega\omega') = OptCost(\alpha_1, \omega) + OptCost(\alpha, \omega')$

Therefore, for any state classes α_1 and α'_1 leading by sequences ω and ω' , respectively, to the same memoryless state class $\alpha = (M, D)$ w.r.t. optimal-costs, it holds that for each firable sequence ω'' from α ,

$$OptCost(\alpha_1, \omega) \leq OptCost(\alpha'_1, \omega') \Rightarrow$$

$$OptCost(\alpha_1, \omega\omega'') \leq OptCost(\alpha'_1, \omega'\omega'')$$

Lemmas 1 and 2 provide two different sufficient conditions for the state class α to be memoryless w.r.t. optimal-costs. The first one depends on the DBM G of ω . The second one depends on α .

Lemma 1: Let $\alpha = (M, D)$ be the state class reached by some sequence $\omega = t_1 \dots t_n$ from a state class $\alpha_1 = (M_1, D_1)$ and G the DBM of its firing domain.

If $\forall i \in [0, |\omega|], \forall t_j \in En(M), g_{ij} = g_{in} + d_{0j}$ then, α is memoryless w.r.t. optimal-costs.

Proof: Suppose that $\forall i \in [0, |\omega|], \forall t_j \in En(M), g_{ij} = g_{in} + d_{0j}$. Let us show that for every sequence ω' of α , $OptCost(\alpha_1, \omega\omega') = OptCost(\alpha_1, \omega) + OptCost(\alpha, \omega')$. We consider 2 cases: 1) $\omega = t_1 \dots t_n$ and $\omega' = t_j$, and 2) $\omega = t_1 \dots t_n$ and $|\omega'| > 1$.

1) Case $\omega = t_1 \dots t_n$ and $\omega' = t_j$: Since $\forall i \in [0, |\omega|], g'_{ij} = g_{in} + d_{0j}$. Consequently, if t_j is firable from $\alpha = (M, D)$ then the optimal-cost of the successor of α by t_j is:

$$OptCost(\alpha_1, \omega) + (rm(M_1) + \sum_{i \in [1, |\omega|]} rt(\omega(t_i))) \times -d_{0j}.$$

Note that $rm(M) = rm(M_1) + \sum_{i \in [1, |\omega|]} rt(\omega(t_i))$ and

$rm(M) \times -d_{0j}$ is the optimal-cost of firing t_j from (M, D) .

2) Case $\omega = t_1 \dots t_n$ and $|\omega'| > 1$: Suppose that in the DBM G' of ω' from α , $\forall t_j \in En(M'), g'_{ij} = g_{in} + c_j$, where c_j does not depend on i and is the opposite of the minimal delay between firing dates of t_j and t_n . Let us show that in any extended sequence of ω' by any firable transition t_k leading to the state class (M'', D'') , it holds that $\forall t_j \in En(M''), g''_{ij} = g_{in} + c'_j$, where c'_j does not depend on i and is the opposite of the minimal delay between firing dates of t_j and t_n , and G'' is the DBM of the extended path. By Proposition 3, $\forall t_j \in En(M'') \cup \{t_n\}$, if $t_j \notin Nw(M', t_k)$ then,

$$g''_{ij} = Min(g'_{ij}, g'_{ik} + \underset{t_u \in En(M')}{Min} d'_{uj}) =$$

$$g_{in} + Min(c_j, c_k + \underset{t_u \in En(M')}{Min} d'_{uj}).$$

Otherwise,

$$g''_{ij} = g'_{ik} - \downarrow Is(t_j) = g_{in} + c_k - \downarrow Is(t_j).$$

Then, $g''_{ij} = g_{in} + c'_j$, where c'_j does not depend on i and c'_j is the opposite of the minimal delay between the firing dates of t_j and t_n (the proof of this claim is similar to the one provided for Proposition 3). Therefore, the optimal reachability cost of any extended sequence $\omega\omega'$ of ω is the sum of $OptCost(\alpha_1, \omega)$ and the optimal cost of firing ω' from α (i.e., $OptCost(\alpha, \omega')$). ■

Lemma 2: Let $\alpha = (M, D)$ be a state class such that all transitions of $En(M)$ are newly enabled in M . Then, α is memoryless w.r.t. optimal-costs.

Fig. 2. The run corresponding to the firing schedule $v_i = g_{in} - g_{0n}$, for $i \in [1, n]$, of ρ

Proof: Suppose that α is reached from some state class α_1 by a sequence $\omega = t_1 \cdots t_n$ and G the DBM of its firing domain. As all transitions of α are newly enabled, it follows that $\forall i \in [0, |\omega|], \forall t_j \in En(M), g_{ij} = g_{in} + d_{0j}$. According to Lemma 1, α is memoryless w.r.t. optimal-costs. ■

Thanks to lemmas 1 and 2, when a memoryless state class α w.r.t. optimal-costs is reached, there is no need to explore its successors, in case there is in the list *Passed* an identical memoryless state class with smaller optimal-cost. Among the identical memoryless state classes reached by different paths, the one with the smallest optimal-cost will yield the optimal reachable cost, for all state classes reachable from α . Therefore, Algorithm 1 can be improved for this subclass of cTPNs.

C. Case of non-positive incidence rate costs

For this section, we suppose that the incidence rate costs of all transitions of ω , except the last one, are non-positive and $rm(M_n) \geq 0$.

Theorem 2: Let $\rho = \alpha_1 = (M_1, D_1) \xrightarrow{t_1} \alpha_2 = (M_2, D_2) \cdots \alpha_n = (M_n, D_n) \xrightarrow{t_n} \alpha_{n+1} = (M_{n+1}, D_{n+1})$ be a path in the SCG of $\mathcal{N}_c$, supporting the sequence $\omega = t_1 \cdots t_n$. Let GG be the DBM in canonical form of FG (the firing domain transitions of ω and those enabled in M_n). Then,

$$OptCost(\alpha_1, \omega) = \left(\sum_{i=1}^n rt(t_i) \times gg_{0i} \right) - gg_{0n} \times rm(M_n).$$

Proof: We first show that the valuation $v_i = -gg_{0i}$ for $i \in [1, n]$ is a feasible firing schedule for ω , i.e., for $i, k \in [1, n]$, $-gg_{0i} \leq v_i \leq gg_{i0}$ and $v_i - v_k \leq gg_{ik}$.

By definition, for $i \in [1, n]$, $v_i = -gg_{0i}$, then for $i, k \in [1, n]$, $v_i - v_k = gg_{0k} - gg_{0i}$. Since GG is in canonical form, it holds that $gg_{0k} \leq gg_{0i} + gg_{ik}$. It follows that $-gg_{0i} \leq v_i \leq gg_{i0}$ and $v_i - v_k \leq gg_{ik}$.

By assumption, $rm(M_n) \geq 0$ and for $i \in [1, n-1]$, $rt(t_i) \leq 0$. Furthermore, for $i \in [0, n]$, $-gg_{0i}$ is the minimal value of t_i in FG (i.e., the firing date of the i^{th} transition of ω).

By Proposition 2, the cost of each run supporting the sequence ω is:

$$\left(\sum_{i=1}^{n-1} -rt(t_i) \times \tau_i \right) + rm(M_n) \times \tau_n.$$

Therefore, $OptCost(\alpha_1, \omega) =$

$$\left(\sum_{i=1}^{n-1} rt(t_i) \times gg_{0i} \right) - rm(M_n) \times gg_{0n}.$$

D. Case of singular intervals

For this section, we suppose that the firing intervals of all transitions of ω are singular but the incidence cost rate of each transition of ω is negative, null or positive.

Theorem 3: Let $\rho = \alpha_1 = (M_1, D_1) \xrightarrow{t_1} \alpha_2 = (M_2, D_2) \cdots \alpha_n = (M_n, D_n) \xrightarrow{t_n} \alpha_n = (M_{n+1}, D_{n+1})$ be a path in the SCG of $\mathcal{N}_c$, supporting the sequence $\omega = t_1 \cdots t_n$. Then,

$$OptCost(\alpha_1, \omega) = \sum_{i=1}^n -d_{i0i} \times rm(M_i).$$

Proof: The cost of each run $\sigma = (M_1, I_1) \xrightarrow{\theta_1 t_1} (M_2, I_2) \cdots (M_n, I_n) \xrightarrow{\theta_n t_n} (M_{n+1}, I_{n+1})$ supporting ω is:

$$\sum_{i=1}^n (\theta_i \times rm(M_i)).$$

The domain of each θ_i , for $i \in [1, n]$, $[-d_{i0i}, d_{i0i}]$. As the firing interval of all transitions of ω are singular, each transition is fired at an exact date. Therefore, for $i \in [1, n]$, $-d_{i0i} = d_{i0i}$. ■

V. CASE STUDY

In the French academic system, faculty positions with both teaching and research activities can be held either by an associate professor (*maître de conférences*, or MCF) or by a full professor (*professeur des universités*, or PU). In this system, a typical career path is:

- start as an associate professor at the 1st grade (*échelon 1*);
- get promoted to higher grades; such promotions are automatic and usually³ happen every 34 months (that is, 2 years and 10 months after the last promotion);
- after some years, defend a habilitation thesis and obtain a higher degree (known as the *habilitation à diriger des recherches*), a qualification needed to supervise PhD students;
- depending on the opportunities, get a promotion from associate to full professor; keep getting automatic promotions to higher grades according to seniority⁴.

To each grade corresponds an *indice* (a salary scale grade), on which the salary is based; additionally, when promoted from associate to full professor, the *indice* cannot decrease.

Let us consider the case of an associate professor who reaches the 4th *échelon* when 32 years old. Let us further

³For some reason, the switch from 1st to 2nd grade only takes 12 months, whereas the switch from 6th to 7th takes 42 months (3 years and 6 months).

⁴After a while, *échelons* are called *chevrons* or stripes.

suppose that the university wishes that all faculty members become full professors and reach the last grade by the time they are 55. Obviously, the cheapest way for the university to reach this goal is to promote anyone at the latest possible time: given the durations between grades, this means letting the person reach the 9th grade after 14 years and 10 months; keep them in that grade for 2 years and 8 months; promote them to full professor and let them reach the last grade after 5 years and 6 months.

However, this strategy does not take into account the frustration of the person, which increases each time a promotion is denied, starting from the moment they reach the 6th grade and begin questioning their life choices.

We propose a model for this optimisation problem, shown in Fig. 3⁵. Each place with a $MCFxyz$ label corresponds to a grade in the associate professor scale; its rate cost is equal to xyz (and is actually equal to the *indice* for this grade). Similarly, each place with a $PUxyz$ label corresponds to a grade in the full professor scale. In the following, we give various values to $\mathcal{R} = r(\text{unhappy})$ so as to show the interest of our method; the rate cost of all the other places is set to 0.

The state class graph of the model is depicted in Fig. 4 and Table I; note that a total of 10 paths in the SCG lead to a marking where *goal* contains 1 token; in the following, we denote *Goal* the set of such markings.

To keep the model simple enough, it should be noted that it does not guarantee that the place *goal* is attained when the person is exactly 55 years old (a token could stay in place *wait* for more than 0 time unit, for instance). However, we can show that, in the following, all optimal-cost strategies are such that the place *goal* is attained as early as possible, that is, after 23 years.

Let us first set $\mathcal{R} = 0$. The optimal cost of each path leading to a marking in *Goal* is given in Table II and the minimum is equal to 208 668. The computation steps of this cost are reported in Fig. 5: as expected, the optimal strategy is to give the promotion at the latest possible time, thus leading to the following timed trace⁶: echelon5@34, echelon6@34, echelon7@42, echelon8@34, echelon9@34, up6@32, PUech6@42, chevron2@12, chevron3@12, age55years@0, end@0.

Let us now change the value of $\mathcal{R}$; whenever $\mathcal{R} \leq 32$, the optimum strategy remains the same. For $\mathcal{R} = 33$, the strategy consists in giving the promotion not too early, just before switching from 6th to 7th grade. The timed trace, with a total cost of 228 480, is: echelon5@34, echelon6@34, up3@42, PUech4@12, PUech5@12, PUech6@42, chevron2@12, chevron3@12, age55years@76, end@0.

Whenever $\mathcal{R} \geq 34$, the strategy consists in giving the promotion just before risking unhappiness, that is right before switching from 5th to 6th grade. For $\mathcal{R} = 35$, the computation steps are reported in Fig. 6 and the timed trace, with a total cost

of 228 660, is: echelon5@34, up2@34, PUech3@12, PUech4@12, PUech5@12, PUech6@42, chevron2@12, chevron3@12, age55years@106, end@0.

VI. CONCLUSION

This paper deals with the optimal-cost reachability problem in the context of time Petri Nets extended with costs (cTPNs). It establishes, for some interesting subclasses of cTPNs, efficient algorithms that compute the optimal-cost of firing a sequence of transitions from a given state class. Unlike the approaches developed in [1]–[7], the algorithms, presented here, are not based on techniques of linear programming. Finally, a case study is provided to show the interest of the proposed method.

As a future work, we will investigate the optimal-cost reachability problem in the context of parametric cTPNs.

REFERENCES

- [1] R. Alur, S. L. Torre, and G. J. Pappas, “Optimal paths in weighted timed automata,” *Theoretical Computer Science*, vol. 318, no. 3, pp. 297 – 322, 2004. [Online]. Available: <http://www.sciencedirect.com/science/article/pii/S0304397503005838>
- [2] G. Behrmann, A. Fehnker, T. Hune, K. Larsen, P. Pettersson, J. Romijn, and F. Vaandrager, *Minimum-Cost Reachability for Priced Timed Automata*. Berlin, Heidelberg: Springer Berlin Heidelberg, 2001, pp. 147–161. [Online]. Available: http://dx.doi.org/10.1007/3-540-45351-2_15
- [3] G. Behrmann, K. G. Larsen, and J. I. Rasmussen, “Optimal scheduling using priced timed automata,” *SIGMETRICS Perform. Eval. Rev.*, vol. 32, no. 4, pp. 34–40, Mar. 2005. [Online]. Available: <http://doi.acm.org/10.1145/1059816.1059823>
- [4] K. Larsen, G. Behrmann, E. Brinksma, A. Fehnker, T. Hune, P. Pettersson, and J. Romijn, “As cheap as possible: Efficient cost-optimal reachability for priced timed automata,” *Lecture Notes in Computer Science*, vol. 2102, pp. 493–505, 2001.
- [5] P. Bouyer, M. Colange, and N. Markey, “Symbolic optimal reachability in weighted timed automata,” *CoRR*, vol. abs/1602.00481, 2016. [Online]. Available: <http://arxiv.org/abs/1602.00481>
- [6] P. A. Abdulla and R. Mayr, “Priced timed Petri nets,” *Logical Methods in Computer Science*, vol. 9, no. 4, 2013. [Online]. Available: [http://dx.doi.org/10.2168/LMCS-9\(4:10\)2013](http://dx.doi.org/10.2168/LMCS-9(4:10)2013)
- [7] H. Boucheneb, D. Lime, B. Parquier, O. H. Roux, and C. Seidner, “Optimal reachability in cost time Petri nets,” in *Formal Modeling and Analysis of Timed Systems - 15th International Conference, FORMATS 2017, Berlin, Germany, September 5-7, 2017, Proceedings*, 2017, pp. 58–73. [Online]. Available: https://doi.org/10.1007/978-3-319-65765-3_4
- [8] B. Berthomieu and M. Diaz, “Modeling and verification of time dependent systems using time Petri nets,” *IEEE Transactions on Software Engineering*, vol. 17(3), pp. 259 – 273, 1991.
- [9] B. Berthomieu and F. Vernadat, “State class constructions for branching analysis of time Petri nets,” in *9th International Conference of Tools and Algorithms for the Construction and Analysis of Systems*, ser. LNCS, vol. 2619, 2003, pp. 442–457.
- [10] H. Boucheneb and H. Rakkay, “A more efficient time Petri net state space abstraction useful to model checking timed linear properties,” *Fundamenta Informaticae*, vol. 88(4), pp. 469–495, 2008.
- [11] J. Bengtsson, *Clocks, DBMs and States in Timed Systems*. Uppsala University: PhD thesis, Dept. of Information Technology, 2002.
- [12] T. H. Cormen, C. E. Leiserson, R. L. Rivest, and C. C. Stein, “Introduction to Algorithms,” in *Second Edition*. The MIT Press, 2002.
- [13] G. Behrmann, P. Bouyer, K. G. Larsen, and R. Pelánek, “Lower and upper bounds in zone-based abstractions of timed automata,” *International Journal on Software Tools for Technology Transfer*, vol. 8(3), pp. 204 – 215, 2006.

⁵Note that, keeping in tune with the French spirit, unhappiness keeps building up and that even after getting a promotion from associate to full professor, the resentment is such that the unhappiness level is maintained.

⁶For the sake of legibility, we denote $t_1@t_1, t_2@t_2 \dots$ the sequence $\theta_1 t_1 \theta_2 t_2 \dots$.

Fig. 3. Possible career paths from age 32 to 55

Fig. 4. The SCG of the TPN at Fig.3

Fig. 5. Optimal-cost of the sequence (echelon5 ... echelon9 up6 PUech6 chevron2 chevron3 age55years end) is 208 668

α_0 $MCF623 + 32to55years$ $echelon5 = 34,$ $age55years = 276,$ $0 \leq up1 \leq 34$	α_1 $MCF673 + 32to55years$ $echelon6 = 34,$ $age55years = 242,$ $0 \leq up2 \leq 34$	α_2 $PU658 + 32to55years$ $PUech2 = 12,$ $242 \leq age55years \leq 276$	α_3 $MCF719 + 32to55years + unhappy$ $echelon7 = 42,$ $age55years = 208,$ $0 \leq up3 \leq 42$
α_5 $PU996 + 32to55years$ $PUech4 = 12,$ $230 \leq age55years \leq 264$	α_6 $MCF749 + 32to55years + 2unhappy$ $echelon8 = 34,$ $age55years = 166,$ $0 \leq up4 \leq 34$	α_7 $PU734 + 32to55years + unhappy$ $PUech4 = 12,$ $166 \leq age55years \leq 208$	α_8 $PU734 + 32to55years$ $PUech4 = 12,$ $196 \leq age55years \leq 230$
α_{10} $MCF783 + 32to55years + 3unhappy$ $echelon = 34, 0 \leq up5 \leq 34,$ $age55years = 132$	α_{11} $PU776 + 32to55years + 2unhappy$ $PUech5 = 12,$ $132 \leq age55years \leq 166$	α_{12} $PU776 + 32to55years + unhappy$ $PUech5 = 12,$ $154 \leq age55years \leq 196$	α_{13} $PU776 + 32to55years$ $PUech5 = 12,$ $184 \leq age55years \leq 218$
α_{15} $MCF821 + 32to55years + 4unhappy$ $0 \leq up6,$ $age55years = 98$	α_{16} $PU821 + 32to55years + 3unhappy$ $PUech6 = 42,$ $98 \leq age55years \leq 132$	α_{17} $PU821 + 32to55years + 2unhappy$ $PUech6 = 42,$ $120 \leq age55years \leq 154$	α_{18} $PU821 + 32to55years + unhappy$ $PUech6 = 42,$ $142 \leq age55years \leq 184$
α_{20} $PU821 + 32to55years$ $PUech6 = 42,$ $194 \leq age55years \leq 228$	α_{21} $PU821 + 32to55years + 4unhappy$ $PUech6 = 42,$ $0 \leq age55years \leq 98$	α_{22} $MCF821 + wait + 4unhappy$ $0 \leq up6$	α_{23} $PU881 + 32to55years + 3unhappy$ $chevron = 12,$ $56 \leq age55years \leq 90$
α_{25} $PU881 + 32to55years + unhappy$ $chevron2 = 12,$ $100 \leq age55years \leq 142$	α_{26} $PU881 + 32to55years$ $chevron2 = 12,$ $130 \leq age55years \leq 164$	α_{27} $PU881 + 32to55years$ $chevron2 = 12,$ $152 \leq age55years \leq 186$	α_{28} $PU881 + 32to55years + 4unhappy$ $chevron2 = 12,$ $0 \leq age55years \leq 56$
α_{30} $PU916 + 32to55years + 3unhappy$ $chevron3 = 12,$ $44 \leq age55years \leq 78$	α_{31} $PU916 + 32to55years + 2unhappy$ $chevron3 = 12,$ $66 \leq age55years \leq 100$	α_{32} $PU916 + 32to55years + unhappy$ $chevron3 = 12,$ $88 \leq age55years \leq 130$	α_{33} $PU916 + 32to55years$ $chevron3 = 12,$ $118 \leq age55years \leq 152$
α_{35} $PU916 + 32to55years + 4unhappy$ $chevron3 = 12,$ $0 \leq age55years \leq 44$	α_{36} $PU881 + wait + 4unhappy$ $0 \leq chevron2 \leq 12$	α_{37} $PU963 + 32to55years + 3unhappy$ $0 \leq age55years \leq 66$	α_{38} $PU963 + 32to55years + 2unhappy$ $0 \leq age55years \leq 88$
α_{40} $PU963 + 32to55years$ $0 \leq age55years \leq 140$	α_{41} $PU963 + 32to55years + 4unhappy$ $0 \leq age55years \leq 162$	α_{42} $PU936 + 32to55years + 4unhappy$ $0 \leq age55years \leq 32$	α_{43} $PU916 + wait + 4unhappy$ $0 \leq chevron3 \leq 12$
α_{45} $PU963 + wait + 2unhappy$ $end = 0$	α_{46} $PU963 + wait + unhappy$ $end = 0$	α_{47} $PU963 + wait$ $end = 0$	α_{48} $PU963 + wait + 4unhappy$
α_{50} $goal + 2unhappy$	α_{51} $goal + unhappy$	α_{52} $goal$	α_{53} $goal + 4unhappy$
α_4 $PU696 + 32to55years$ $PUech4 = 12,$ $208 \leq age55years \leq 242$	α_9 $PU734 + 32to55years$ $PUech4 = 12,$ $218 \leq age55years \leq 252$	α_{14} $PU776 + 32to55years$ $PUech5 = 12,$ $206 \leq age55years \leq 240$	α_{19} $PU821 + 32to55years$ $PUech6 = 42,$ $172 \leq age55years \leq 206$
α_{24} $PU881 + 32to55years + 2unhappy$ $chevron = 12,$ $78 \leq age55years \leq 112$	α_{29} $PU821 + wait + 4unhappy$ $0 \leq PUech6 \leq 42,$	α_{34} $PU916 + 32to55years$ $chevron3 = 12,$ $140 \leq age55years \leq 174$	α_{39} $PU963 + 32to55years + unhappy$ $0 \leq age55years \leq 118$
α_{44} $PU963 + wait + 3unhappy$ $end = 0$	α_{49} $goal + 3unhappy$		

TABLE I
STATE CLASSES OF THE SCG IN FIG.4

Fig. 6. Optimal-Cost of the sequence (echelon5 up2 PUech3 ... PUech6 chevron2 chevron3 age55years end) is 228 660

Path	Optimal-Cost	Path	Optimal-Cost
$\alpha_0 \cdots \alpha_{41} \alpha_{47} \alpha_{52}$	234 860	$\alpha_0 \cdots \alpha_{40} \alpha_{47} \alpha_{52}$	228 660
$\alpha_0 \cdots \alpha_{51}$	221 616	$\alpha_0 \cdots \alpha_{50}$	217 088
$\alpha_0 \cdots \alpha_{49}$	213 212	$\alpha_0 \cdots \alpha_{15} \alpha_{22} \cdots \alpha_{53}$	262 854
$\alpha_0 \cdots \alpha_{15} \alpha_{21} \alpha_{29} \cdots \alpha_{53}$	262 854	$\alpha_0 \cdots \alpha_{15} \alpha_{21} \alpha_{28} \alpha_{36} \cdots \alpha_{53}$	228 372
$\alpha_0 \cdots \alpha_{15} \alpha_{21} \alpha_{28} \alpha_{35} \alpha_{43} \cdots \alpha_{53}$	218 520	$\alpha_0 \cdots \alpha_{15} \alpha_{21} \alpha_{28} \alpha_{35} \alpha_{42} \cdots \alpha_{53}$	208 668

TABLE II
OPTIMAL-COST OF EACH PATH OF THE SCG IN FIG.4 THAT LEADS TO A MARKING IN Goal