



HAL
open science

Brief Announcement: Infinite Grid Exploration by Disoriented Robots

Quentin Bramas, Stéphane Devismes, Pascal Lafourcade

► **To cite this version:**

Quentin Bramas, Stéphane Devismes, Pascal Lafourcade. Brief Announcement: Infinite Grid Exploration by Disoriented Robots. 26th International Colloquium on Structural Information and Communication Complexity SIROCCO 2019, Jul 2019, L'Aquila, Italy. hal-02145822

HAL Id: hal-02145822

<https://hal.science/hal-02145822>

Submitted on 3 Jun 2019

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Brief Announcement: Infinite Grid Exploration by Disoriented Robots^{*}

Quentin Bramas¹, Stéphane Devismes², and Pascal Lafourcade³

¹ University of Strasbourg, ICUBE, CNRS

² Université Grenoble Alpes, VERIMAG

³ University Clermont Auvergne, CNRS UMR 6158, LIMOS

Abstract. We deal with a set of autonomous robots moving on an infinite grid. Those robots are opaque, have limited visibility capabilities, and run using synchronous Look-Compute-Move cycles. They all agree on a common chirality, but have no global compass. Finally, they may use lights of different colors, but except from that, robots have neither persistent memories, nor communication mean. We consider the *infinite grid exploration* (IGE) problem. We first show that two robots are not sufficient in our settings to solve the problem, even when robots have a common coordinate system. We then show that if the robots' coordinate systems are not self-consistent, three or four robots are not sufficient to solve the problem neither. Finally, we present three algorithms that solve the IGE problem in various settings. The first algorithm uses six robots with constant colors and a visibility range of one. The second one uses the minimum number of robots, *i.e.*, five, as well as five modifiable colors, still under visibility one. The last algorithm requires seven oblivious anonymous robots, yet assuming visibility two. Notice that the two last algorithms also achieve exclusiveness.

1 Context and Motivation

We deal with a swarm of mobile robots having low computation and communication capabilities. The robots we consider are opaque (*i.e.*, a robot is able to see another robot if and only if no other robot lies in the line segment joining them) and run in synchronous Look-Compute-Move cycles, where they can sense their surroundings within a limited visibility range. All robots agree on a common chirality (*i.e.*, when a robot is located on an axis of symmetry in its surroundings, it is able to distinguish its two sides one from another), but have no global compass (they agree neither on a North-South, nor a East-West direction). However, they may use lights of different colors [13,18]. These lights can be seen by robots in their surroundings. However, except from those lights, robots have neither persistent memories nor communication capabilities.

We are interested in coordinating such weak robots, endowed with both typically small visibility range (*i.e.*, one or two) and few light colors (only a constant number of them), to solve an infinite task in an infinite discrete environment. As an attempt to tackle this general problem, we consider the exploration of an infinite grid, where nodes

^{*} This study has been partially supported by the ANR projects DESCARTES (ANR-16-CE40-0023) and ESTATE (ANR-16-CE25-0009).

represent locations that can be sensed by robots and edges represent the possibility for a robot to move from one location to another. Precisely, the exploration task consists in ensuring that each node of the infinite grid is visited within finite time by at least one robot. We refer to this problem as the *Infinite Grid Exploration* (IGE) problem.

2 Contribution

We present both negative and positive results. On the negative side, we show that if robots have a common chirality but a bounded visibility range, then the IGE problem is not solvable with:

- two robots, even if those robots agree on common North (the proof is essentially the adaptation to our context of the impossibility proof given in [14]);
- three or four robots with self-inconsistent compass (*i.e.*, the compass may change throughout the execution).

On the positive side, we provide three algorithms for solving the IGE problem using opaque robots equipped with self-inconsistent compass, yet agreeing on a common chirality. Two of them also satisfy *exclusiveness* [2], which requires any two robots to never simultaneously occupy the same position nor traverse the same edge. The first one requires the minimum number of robots, *i.e.*, five, and ensures exclusiveness. The robots use modifiable lights with only five states, and have a visibility range restricted to one. The second algorithm solves the problem with six robots and only three non-modifiable colors, still assuming visibility range one. The last algorithm requires seven identical robots without any light (*i.e.*, seven oblivious⁴ anonymous robots) and ensures exclusiveness, yet assuming visibility range two. Our contributions are summarized below.

visibility range	# of robots	# of colors	modifiable colors?	exclusiveness?
1	5 (opt)	5	yes	yes
1	6	3	no	no
2	7	1	N/A	yes

In order to help the reader, animations, for each algorithm, are available online [6]. Our algorithms and their proofs of correctness can be found in a technical report online [5].

3 Related Work

The model of robots with lights have been proposed by Peleg in [13,18]. In [8], the authors use robots with lights and compare the computational power of such robots with respect to the three main execution model: fully-synchronous, semi-synchronous, and asynchronous. Solutions for dedicated problems such as *weak gathering* or *mutual visibility* have been respectively investigated in [16] and [17].

Mobile robot computing in infinite environments has been first studied in the continuous two-dimensional Euclidean space. In this context, studied problems are mostly *terminating* tasks, such as *pattern formation* [11] and *gathering* [15], *i.e.*, problems where robots aim at eventually stopping in a particular configuration specified by their

⁴ *Oblivious* means that robots cannot remember the past.

relative positions. A notable exception is the *flocking* problem [19], *i.e.*, the infinite task consisting of forming a desired pattern with the robots and make them moving together while maintaining that formation.

When considering a discrete environment, space is defined as a graph, where the nodes represent the possible locations that a robot can take and the edges the possibility for a robot to move from one location to another. In this setting, researchers have first considered finite graphs and two variants of the exploration problem, respectively called the *terminating* and *perpetual* exploration. The terminating exploration requires every possible location to be eventually visited by at least one robot, with the additional constraint that all robots stop moving after task completion. In contrast, the perpetual exploration requires each location to be visited infinitely often by all or a part of robots. In [9], authors solve terminating exploration of any finite grid using few asynchronous anonymous oblivious robots, yet assuming unbounded visibility range. The exclusive perpetual exploration of a finite grid is considered in the same model in [3].

Various terminating problems have been investigated in infinite grids such as *arbitrary pattern formation* [4], *mutual visibility* [1], and *gathering* [10,12]. The possibly closest related work is that of Emek *et al.* [14]. In this paper, authors consider a treasure search problem, which is roughly equivalent to the IGE problem, in an infinite grid. They consider robots that operate in two models: the semi-synchronous and synchronous ones. However, they do not impose the exclusivity at all since their robots can only sense the states of the robots located at the same node (in that sense, the visibility range is zero). The main difference with our settings is that they assume all robots agree on a *global compass*, *i.e.*, they all agree on the same directions North-South and East-West; while we only assume here a *common chirality*. This difference makes their model stronger, indeed they propose two algorithms that respectively need three synchronous and four asynchronous robots, while in our settings the IGE problem (even in its non-exclusive variant) requires at least five robots. They also exclude solutions for two robots. Brandt *et al.* [7] extend the impossibility result of Emek *et al.* Indeed, they show the impossibility of exploring an infinite grid with three semi-synchronous deterministic robots that agree on a common coordinate system. Although proven using similar techniques, this result is not correlated to ours. Indeed, the lower bound of Brandt *et al.* holds for robots that are weaker in terms of synchrony assumption (semi-synchronous *vs.* fully synchronous in our case), but stronger in terms of coordination capabilities (common coordinate system *vs.* self-inconsistent compass in our case). In other words, our impossibility results does not (even indirectly) follows from those of Brandt *et al.* since in our model difficulties arise from the lack of coordination capabilities and not the level asynchrony. As a matter of facts, based on the results of Emek *et al.* [14], four (asynchronous) robots are actually necessary and sufficient in their settings, while in our context five robots are required.

References

1. Adhikary, R., Bose, K., Kundu, M.K., Sau, B.: Mutual visibility by asynchronous robots on infinite grid. In: Algorithms for Sensor Systems - 14th International Symposium on Algorithms and Experiments for Wireless Sensor Networks, ALGOSENSORS 2018, Helsinki, Finland, August 23-24, 2018, Revised Selected Papers. pp. 83–101 (2018)

2. Baldoni, R., Bonnet, F., Milani, A., Raynal, M.: Anonymous graph exploration without collision by mobile robots. *Inf. Process. Lett.* **109**(2), 98–103 (2008)
3. Bonnet, F., Milani, A., Potop-Butucaru, M., Tixeuil, S.: Asynchronous exclusive perpetual grid exploration without sense of direction. In: Anta, A.F. (ed.) *Proceedings of International Conference on Principles of Distributed Systems (OPODIS 2011)*. pp. 251–265. No. 7109 in *Lecture Notes in Computer Science (LNCS)*, Springer Berlin / Heidelberg, Toulouse, France (December 2011)
4. Bose, K., Adhikary, R., Kundu, M.K., Sau, B.: Arbitrary pattern formation on infinite grid by asynchronous oblivious robots. In: *WALCOM: Algorithms and Computation - 13th International Conference, WALCOM 2019, Guwahati, India, February 27 - March 2, 2019*, Proceedings. pp. 354–366 (2019)
5. Bramas, Q., Devismes, S., Lafourcade, P.: Infinite Grid Exploration by Disoriented Robots. Tech. rep., Arxiv (May 2019), <https://arxiv.org/abs/1905.09271>
6. Bramas, Q., Devismes, S., Lafourcade, P.: Infinite Grid Exploration by Disoriented Robots : Animations (May 2019), <https://doi.org/10.5281/zenodo.2625730>
7. Brandt, S., Uitto, J., Wattenhofer, R.: A Tight Bound for Semi-Synchronous Collaborative Grid Exploration. In: *32nd International Symposium on Distributed Computing (DISC)*, New Orleans, Louisiana (October 2018)
8. Das, S., Flocchini, P., Prencipe, G., Santoro, N., Yamashita, M.: Autonomous mobile robots with lights. *Theor. Comput. Sci.* **609**(P1), 171–184 (Jan 2016)
9. Devismes, S., Lamani, A., Petit, F., Raymond, P., Tixeuil, S.: Optimal grid exploration by asynchronous oblivious robots. In: *Proceedings of the 14th International Conference on Stabilization, Safety, and Security of Distributed Systems*. pp. 64–76. SSS’12, Springer-Verlag, Berlin, Heidelberg (2012)
10. Di Stefano, G., Navarra, A.: Gathering of oblivious robots on infinite grids with minimum traveled distance. *Information and Computation* **254** (09 2016)
11. Dieudonné, Y., Petit, F.: Circle formation of weak robots and Lyndon words. *Inf. Process. Lett.* **101**(4), 156–162 (2007)
12. Dutta, D., Dey, T., Chaudhuri, S.G.: Gathering multiple robots in a ring and an infinite grid. In: *Distributed Computing and Internet Technology - 13th International Conference, ICDCIT 2017, Bhubaneswar, India, January 13-16, 2017*, Proceedings. pp. 15–26 (2017)
13. Efrima, A., Peleg, D.: Distributed models and algorithms for mobile robot systems. In: van Leeuwen, J., Italiano, G.F., van der Hoek, W., Meinel, C., Sack, H., Plášil, F. (eds.) *SOFSEM 2007: Theory and Practice of Computer Science*. pp. 70–87. Springer Berlin Heidelberg, Berlin, Heidelberg (2007)
14. Emek, Y., Langner, T., Stolz, D., Uitto, J., Wattenhofer, R.: How many ants does it take to find the food? *Theor. Comput. Sci.* **608**(P3), 255–267 (Dec 2015)
15. Flocchini, P., Prencipe, G., Santoro, N., Widmayer, P.: Gathering of asynchronous robots with limited visibility. *Theoretical Computer Science* **337**(1), 147 – 168 (2005)
16. Luna, G.A.D., Flocchini, P., Chaudhuri, S.G., Poloni, F., Santoro, N., Viglietta, G.: Mutual visibility by luminous robots without collisions. *Inf. Comput.* **254**, 392–418 (2017)
17. Ooshita, F., Datta, A.K.: Brief announcement: Feasibility of weak gathering in connected-over-time dynamic rings. In: *Stabilization, Safety, and Security of Distributed Systems - 20th International Symposium, SSS 2018, Tokyo, Japan, November 4-7, 2018*, Proceedings. pp. 393–397 (2018)
18. Peleg, D.: Distributed coordination algorithms for mobile robot swarms: New directions and challenges. In: *Proceedings of the 7th International Conference on Distributed Computing*. pp. 1–12. IWDC’05 (2005)
19. Yang, Y., Souissi, S., Défago, X., Takizawa, M.: Fault-tolerant flocking for a group of autonomous mobile robots. *Journal of Systems and Software* **84**(1), 29–36 (2011)