



**HAL**  
open science

## Performance evaluation of a real time OFDM radio over fiber system at 2.5 GHz using software defined radio SDR

Juan David Cepeda, Santiago Isaac Rodríguez, Mónica Rico-Martínez, Christian Daniel Muñoz-Arcos, Margarita Varón-Durán, Idelfonso Tafur Monroy

### ► To cite this version:

Juan David Cepeda, Santiago Isaac Rodríguez, Mónica Rico-Martínez, Christian Daniel Muñoz-Arcos, Margarita Varón-Durán, et al.. Performance evaluation of a real time OFDM radio over fiber system at 2.5 GHz using software defined radio SDR. 2017 SBMO/IEEE MTT-S International Microwave and Optoelectronics Conference (IMOC), Aug 2017, Aguas de Lindoia, Brazil. pp.1-5. hal-02182491

**HAL Id: hal-02182491**

**<https://hal.science/hal-02182491>**

Submitted on 12 Jul 2019

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



## Open Archive Toulouse Archive Ouverte (OATAO)

OATAO is an open access repository that collects the work of some Toulouse researchers and makes it freely available over the web where possible.

This is an author's version published in: <https://oatao.univ-toulouse.fr/23700>

**Official URL :** <https://doi.org/10.1109/IMOC.2017.8121094>

### To cite this version :

Cepeda, Juan David and Rodríguez, Santiago Isaac and Rico-Martínez, Mónica and Muñoz-Arcos, Christian Daniel and Varón-Durán, Margarita and Tafur Monroy, Idelfonso Performance evaluation of a real time OFDM radio over fiber system at 2.5 GHz using software defined radio SDR. (2017) In: 2017 SBMO/IEEE MTT-S International Microwave and Optoelectronics Conference (IMOC), 27 August 2017 - 30 August 2017 (Aguas de Lindoia, Brazil).

Any correspondence concerning this service should be sent to the repository administrator:

[tech-oatao@listes-diff.inp-toulouse.fr](mailto:tech-oatao@listes-diff.inp-toulouse.fr)

# Performance Evaluation of a real time OFDM Radio Over Fiber System at 2.5 GHz using Software Defined Radio SDR

Juan David Cepeda, Santiago Isaac Rodríguez,  
Mónica Rico-Martínez, Christian Daniel Muñoz,  
Margarita Varón  
Department of Electric and Electronic Engineering  
Universidad Nacional de Colombia  
Bogotá, Colombia

Idelfonso Tafur Monroy  
Metro-Access and Short Range Communications Group,  
Department of Photonics Engineering,  
Technical University of Denmark  
Copenhagen, Denmark

**Abstract**—This paper presents the implementation of an OFDM radio over fiber (RoF) system at 2.5 GHz using software defined radio (SDR). In this work, first we present an introduction of the main concepts about radio over fiber and an orthogonal frequency-division multiplexing (OFDM) system at 2.5 GHz, then we present a comparison of an OFDM RoF system in three scenarios, modifying the wireless distances and the optical fiber distance in order to evaluate the performance of the system taking into account the symbol error rate (SER) vs signal to noise ratio (SNR) curves.

**Index Terms**—Radio over Fiber, RoF, LTE, OFDM, SDR, Real-time System

## I. INTRODUCTION

In the last few years the mobile data traffic growth, the increase in the number of users connected to the networks and the new services development have required a progressive updating of the standards and technologies managed by the mobile operators. Long Term Evolution (LTE) is the standard for 4G mobile networks communications, in which two multi-carrier multiplexing schemes coexist in the physical layer: Orthogonal Frequency-Division Multiplexing (OFDM) in the downlink and Single-Carrier Frequency-Division Multiple Access (SC-FDMA) in the uplink [1].

The aim of this paper is to study OFDM since the downlink has the highest requirements by the end user. OFDM is an orthogonal frequency division multiplexing whose purpose is to multiplex a data stream over time by assigning it a portion of the available bandwidth in the spectrum. The mechanism consists of a set of orthogonal sub-carriers that are a multiple of an original carrier, each one carrying a lower-rate stream encoded on digital modulation formats. This scheme is characterized by some advantages in comparison to traditional modulations used in previous standards of mobile telephony, as it has greater transmission rate, it is more spectrally efficient and it also has lower bit error rate [2].

On the other hand a RoF system is also known as a

fiber system wireless (FI-WI) [3]. In a RoF system the objective is to carry the information through the optical fiber by modulating the light signal with a radio signal [4]. RoF is widely used to provide access in wireless communications with a wide range of applications and coverage for locations where wired media are not suitable [5].

Basically a RoF system is composed of a Central Station (CS) or Header and a Base Station (BS). The RoF system processes the RF signal at the CS and uses fiber optics to distribute the RF signal to the BSs [6] [7]. The CS is the gateway between the transport network and the BSs, the BS handles the communication with the users. This is specially important when designing networks based on the C-RAN architecture which states the use of optical fiber as the fronthaul physical layer [8].

The new mobile network generation requires new features for its physical layer. Radio over Fiber links provides an advantage since it will be possible to send higher data rates through these systems for applications that require it [9]. Moreover, the evaluation of the OFDM multiplexing at 2.5 GHz for different scenarios allows to know how it is the real time behavior of this technique in a future LTE link implementation operating at 2.5GHz.

In this paper we first show the SDR interface of the OFDM system built in GNU Radio, then we describe the physical setup of a transmitter and receiver system with a radio-fiber link. In the experiment we modified the wireless distance and the fiber optical distance in order to assess the performance of the OFDM RoF system. Finally we describe the conclusions of the obtained results.

## II. GNU RADIO INTERFACE

This section describes the software defined radio (SDR) implementation of the OFDM transceiver along with the design parameters used for transmission.






Fig. 2: Experimental OFDM RoF link setup

$$A_n = \frac{1}{\sqrt{10^{0.1 * SNR}}} \quad (1)$$

Some experiments were carried out to determine the maximum level that still allowed a successful transmission by varying the level of the noise amplitude. Amplitude levels from 0.00 to 0.16 with steps of 0.02 were then introduced for the noise signal amplitude which led to different levels of actual SNR depending on the configuration of the setup used.

### III. EXPERIMENTAL SETUP

This section details the hardware and software features that enable the implementation of a real time OFDM RoF link. The methodology for carrying out the measurements is also presented.

#### A. Design

The system design was divided into three segments as shown in figure 2. The generation of an OFDM signal and its analysis at the end of the receiver using SDR and Universal Software Radio Peripheral (USRP) are the first segment. The transmitter is the second segment and it includes the elements that allow transporting the OFDM signal through a fiber optic link at a predetermined frequency. In the last segment, the optical OFDM signal is sent through an RF link.

For the optical link implementation, a VCSEL (Vertical-Cavity Surface-Emitting Laser) laser was used. A Raycan pigtailed VCSEL was driven by a Thorlabs ITC8052 Laser Diode Current Control Module and a TCLDM9 Temperature Controlled Mount. The Amonics Optical Amplifier AEDFA-IL-18-BFA and two USRP N210 were used. The Photline (MXAN-LN-20) Mach-Zehnder modulator (MZM) allowed optically modulating the OFDM signal generated by the Tx USRP. The optical link included single mode optical fiber of 500 m. At the end of link a New Focus High Speed Photodetector 1414 was used to convert the signal to the electrical domain. The received electrical signal was amplified by the amplifier ZX60-2534M (MiniCircuits) and transmitted by a broadband double ridged Horn antennas

A-INFO LB-880-NF. Finally the RF signal at 2.5 GHz was received by another Horn antenna and processed by the Rx USRP. The computers processors linked to the USRP were: Intel®corei5™ and corei3™.

The design of the transmitter and receiver was implemented in GNU Radio. Two computers are used in order to create the transmitter and receiver.

The hardware-software interface was performed in two steps. First, the USRP Sink and Source block were initialized, in this way the program identifies where to send or to receive the digital samples. On the other hand, the connection between the USRP and the computer is achieved through a 1GB Ethernet cable, which sends the digital samples directly to the built-in USRP's FPGA and then it performs up-conversion at the specified RF frequency according to the daughterboard capacities.

#### B. SNR and SER measurement methodology

The methodology used for the experiments involved carrying out measurements of the two variables related to the figure of merit chosen (SER and SNR). To obtain the data, three scenarios were proposed using a 500 m optical link and the RF link using a short coaxial cable or horn antennas at different distances (1.45 m and 8 m). The table II summarizes the setups and its features.

Table II: Setup configurations

Scenario	Optical link	RF element
Setup 1	Short link	Coaxial cable
Setup 2	500 m	Horn antennas at 1.45m
Setup 3	500 m	Horn antennas at 8m

For the actual on-field measurement of the SNR, a spectrum analyzer with RBW of 30 kHz and a window of 2 MHz was used. First, we conducted signal power measurements by setting on only the gaussian noise source for each one of the levels. Then, other measurements were made to determine the signal power of the OFDM signal with the noise on. The computation of the real SNR was performed by obtaining first the average power of the spectrum analyzer FFT bins according to equation 2.

$$P_{avg} = \frac{1}{B} \sum P_i \Delta f \quad (2)$$

Hereafter, equation 3 was used to find the signal-to-noise ratio taking into account that the noise is also present in the transmitted signal this is the reason for subtracting it while computing the ratio.

$$SNR = 10 \log \frac{P_s - P_n}{P_n} \quad (3)$$

The SNR measurements were performed in a systematic way. In particular, for the collection of SER data at the

receiver, a series of SNR measurements were made based on the amplitude of the digital noise, taking steps of 0.02 units of amplitude of the noise in a span from 0.00 to 0.16..

For the SER measurement, a text file with a known sequence and fixed size was transmitted repeatedly for 30 seconds. An offline analysis was performed on the receiver in order to compare each symbol of the sent and received file. To carry out this analysis it should be considered that each character sent using a constellation of QPSK digital symbols represents four transmitted digital symbols.

The offline analysis consists of a C++ script that aims to check the number of symbols received (four times the original file) and decompose each symbol to verify the parity every two bits, i.e. each QPSK symbol. The experimental SER is determined from the expression 4.

$$SER = \frac{Number\_of\_errors}{Total\_symbols\_sent} \quad (4)$$

Finally, this measurement was made for each noise level established in the transmitter, and for each configuration system (optical fiber and RF link) in real time. In this way, the experimental SER vs. SNR curves were obtained.

#### IV. EXPERIMENTAL RESULTS

For the three scenarios the SER vs SNR curves were obtained. These are illustrated in figure 3. As can be observed, the behavior of the error rate tends to decrease with increasing SNR as expected. However, only rates of up to  $10^{-2}$  are achieved in the sceneries using antennas and just a minimum  $10^{-3}$  rate using a direct connection with coaxial cable. In order to be able to observe lower error rates, the transmission time should also be increased, but this is limited by the size of the file that can be received.

The results also reflect the decrease of the SNR and its span due to losses by slow and fast fading, going from values of around 40 dB for the first setup, maximum 23 dB for the second setup and a maximum of 12 dB for setup number three. The latter occurs as a consequence of the path losses due to the distance of the antennas which happens to be a major design parameter to target a desired performance.

During the experiments the importance of controlling the digital signal amplitude to avoid nonlinear distortions in the PA of the USRP was observed. Very high amplitudes imply an increment of the errors in the receiver. On the other hand, the gain of the USRPs should also be fixed. Increases in SER were observed when the gain in the receptor was increased. This converges in a relationship between the distance of the antennas and the actual gain of the transmitter and receiver. In other words the performance is affected by the maximum SNR value obtained for a maximum fixed gain value according to the distance.




Fig. 3: SER vs SNR curves for each setup configuration

Finally, observations performed by varying the optical length demonstrated non significant effects over the performance due to the use of short distances. In further works, other distortions caused by dispersion over the optical link should also be addressed.

#### V. CONCLUSION

An OFDM system was implemented using RoF using a frequency of 2.5 GHz. An SDR interface using GNU Radio was implemented and tuned for parameters close to LTE. Three mounting configurations were made using, for example, a coaxial cable or horn antennas for the RF link and a 500m fiber optic link. A methodology was designed for the measurement of SER and SNR. The SER vs. SNR curves were obtained showing the performance of this system for the different configurations. An acceptable performance of the system was only present for the highest values of SNR in each configuration setup.

It was observed that the flowgraph parameters in terms of amplitude of the signals are key to the performance in terms of error. Evaluation of the influence of the parameters of other elements such as the polarization point of the optoelectronic modulator are proposed for the following works.

#### REFERENCES

- [1] W. Paper, "Mobile LTE Network design with ICS telecom." December 2008.
- [2] Taewon Hwang, Chenyang Yang, Gang Wu, Shaoqian Li, and G. Ye Li, "OFDM and Its Wireless Applications: A Survey," *IEEE Transactions on Vehicular Technology*, vol. 58, pp. 1673–1694, may 2009.
- [3] C. Lim, A. Nirmalathas, M. Bakaul, P. Gamage, D. Novak, and R. Waterhouse, "Fiber-Wireless Networks and Subsystem Technologies," *Journal of Lightwave Technology*, vol. 28, pp. 390–405, feb 2010.
- [4] J. Yao, "Microwave Photonics," *Journal of Lightwave Technology*, vol. 27, pp. 314–335, feb 2009.
- [5] L. Kazovsky, S.-W. Wong, T. Ayhan, K. M. Albeyoglu, M. R. N. Ribeiro, and A. Shastri, "Hybrid Optical–Wireless Access Networks," *Proceedings of the IEEE*, vol. 100, pp. 1197–1225, may 2012.

- [6] H.-C. Chien, C. Liu, J. Liu, S.-H. Fan, Y.-T. Hsueh, Z. Jia, S. He, J. Yu, and G.-K. Chang, "Emerging technologies for mm-wave RoF communication," *2012 IEEE Photonics Society Summer Topical Meeting Series*, vol. 4, pp. 88–89, jul 2012.
- [7] D. G. Lona, H. E. Hernández-Figueroa, S. A. Cerqueira, R. M. Assumpção, O. C. Branquinho, and M. L. F. Abbade, "Investigation of noise sources in radio-over-fiber systems for Wi-Fi applications," in *SBMO/IEEE MTT-S International Microwave and Optoelectronics Conference Proceedings*, pp. 97–101, IEEE, oct 2011.
- [8] A. Pizzinat, P. Chanclou, F. Saliou, and T. Diallo, "Things you should know about fronthaul," *Journal of Lightwave Technology*, vol. 33, pp. 1077–1083, March 2015.
- [9] A. Morales, S. Rodríguez, O. Gallardo, J. J. Vegas Olmos, and I. T. Monroy, "Performance analysis for W-band antenna alignment using accurate mechanical beam steering," *Microwave and Optical Technology Letters*, vol. 59, pp. 1125–1128, may 2017.
- [10] B. Bloessl, M. Segata, C. Sommer, and F. Dressler, "Towards an open source iee 802.11p stack: A full sdr-based transceiver in gnu radio," *IEEE Vehicular Networking Conference*, 2013.
- [11] S. Schwarz, J. C. Ikuno, M. Simko, M. Taranetz, and M. Rupp, "Pushing the Limits of LTE: A Survey on Research Enhancing the Standard," *IEEE Access*, vol. 1, pp. 51–62, 2013.
- [12] J. Zyren and W. Mccoy, "White Paper: Overview of the 3GPP Long Term Evolution Physical Layer." 2007.