Designing and Demonstrating a Master Student Project to Explore Carbon Dioxide Capture Technology

Florine Asherman¹, Gilles Cabot³, Cyril Crua⁴, Lionel Estel^{1,2}, Charlotte Gagnepain¹,
Thibault Lecerf¹, Alain Ledoux^{1,2}, Sébastien Leveneur^{1,2,5,*}, Marie Lucereau¹, Sarah
5 Maucorps¹, Mélanie Ragot¹, Julie Syrykh¹, Manon Vige¹

¹ MRIE-Maitrise des Risques Industriels et Environnementaux, INSA Rouen, BP08,
Avenue de l'Université, 76801 Saint-Etienne-du-Rouvray, France

10 ² LSPC-Laboratoire de Sécurité des Procédés Chimiques, EA4704, INSA Rouen, BP08,
Avenue de l'Université, 76801 Saint-Etienne-du-Rouvray, France. Tel: +33 2 32 95 66 54;
Fax: +33 2 32 95 66 52; E-mail: sebastien.leveneur@insa-rouen.fr

³ CORIA-UMR6614, Université et INSA de Rouen, 76 801 Saint-Etienne du Rouvray
15 cedex, France;

⁴ School of Computing, Engineering and Mathematics, University of Brighton, Brighton
BN2 4GJ, UK

20 ⁵ Laboratory of Industrial Chemistry and Reaction Engineering, Process Chemistry
Centre, Åbo Akademi University, Biskopsgatan 8, FI-20500 Åbo/Turku, Finland;

ABSTRACT

The rise in carbon dioxide (CO₂) concentration in the Earth's atmosphere, and the associated strengthening of the greenhouse effect, requires the development of low carbon technologies. New carbon capture processes are being developed to remove CO₂ that would otherwise be emitted from industrial processes and fossil fuel power stations. Given the increasing importance of this technology we report on a new educational project which aimed to instill greater awareness of the role of CO₂ in climate change, whilst stimulating student interest in science, technology, engineering, and the environment. The project was carried out by master students, i.e., Cool_LCap team, who contributed to the design and manufacture of a pilot plant that demonstrates the basic operation of an amine scrubbing plant. The main goal of the project was to develop educational material and presentations for a range of audiences, from primary school to university students and academics. In this article we present the project team's approach to design, commission and deliver the pilot plant and educational material, as well as the feedback received from 267 students from a primary school and a university. We provide supplementary material to enable other educators to recreate our pilot plant design.

ABSTRACT GRAPHIC

50

55

KEYWORDS

General Public, Elementary / Middle School Science, High School / Introductory Chemistry, Chemical Engineering, Environmental Chemistry, Public Understanding / Outreach, Communication / Writing, Laboratory Equipment / Apparatus.

INTRODUCTION

65 The increase of the greenhouse effect is known as a worldwide issue, partly due to human activities.¹⁻⁴ Global warming, sustainable development or greenhouse effect are taught at primary school or university. To reduce the consequences of human activities on the climate, it is not only essential to develop new technologies but also to raise awareness among the young generation and the non-scientific community.⁵ At our
70 department, we have reached to the conclusion that it could be an excellent challenge for master students to carry out such project.

The CoolCap project, which is a kind of acronym for CO₂ capture in liquid phase, was created. This project was carried out by successively two groups of eight master students of the engineering school INSA Rouen (France). The ambition of this project
75 was to introduce carbon capture technologies to different audiences by having an interactive dialogue. This project had three main objectives:

- To experience a team project for master students involving client relationship,
- To build transportable lab-scale pilot based on chemical absorption and desorption of CO₂ (Figure 1),
- 80 - To demonstrate and explain the technologies⁶ to broad audiences with a pedagogical strategy.

For the sake of clarity, the master students who have organized the project are named CoolCap team in the manuscript. Several events were organized by the CoolCap team to meet groups of students from primary school to university, to present and show the
85 pilot. The purpose of the demonstrations included developing children's interest in science by showing them that chemistry can be used to reduce the greenhouse effect. Moreover, the instrumentation used to make the pilot work was presented.

The goal of this article is mainly to present the carbon capture technologies and the pilot. The work team experience of the CoolCap project is briefly discussed.

90

Figure 1. Carbon dioxide capture pilot plant designed and manufactured by the student project team.

95 **THE TEAM PROJECT**

This chapter introduces the CoolCap project framework. At our university, master students should perform a project, named PIC project, which is a certified INSA. The team project is composed of eight students from the master of industrial and environmental risks management. The project is a one academic year and two workdays per week are dedicated to realize the PIC project. The PIC project should follow a quality approach, i.e. ISO 9001-2008. The PIC students are supervised by a quality supervisor during their project in order to obtain the certification at the end. A teaching staff (scientific supervisor) supervises the team project to ensure extensive theoretical basis.

100 A contract is signed with an industrial or academic client to define the different products to deliver. The evaluation of the PIC project is done four times per year. For the CoolCap project, the client was a European program, named E3C3. One of E3C3 goals was to promote sustainable development, and more precisely, to improve knowledge and create tools to carry out clean combustion and biomass combustion.

110 The CoolCap team was also mentored by a communication teacher to improve the communication skills of the team. It included interpersonal communication in the team and with the client. Also, the communication teacher helped the team to carry out presentations about the progress of the project. In the case of the CoolCap project, the laboratory manager has helped the student for the pilot building. Figure 2 illustrates

115 the interaction between the different actors of the CoolCap project.

Figure 2. Different actors participating to the CoolCap project.

DEVELOPMENT OF A PILOT FOR CARBON CAPTURE

Carbon capture is a decarbonization technology (also known as decarburization technology) that has been designed to capture carbon dioxide generated by combustion reactions in industrial applications⁶. Therefore, this technology abates CO₂ emissions into the atmosphere. In 2011, there were 89 CO₂ capture and storage (CCS) demonstration projects or pilots in USA.⁷ For example, a CCS technology has been in place since 1996 on the Sleipner offshore gas field (Norway) located in the central North Sea. On this field, CO₂ is both captured and stored into a dedicated well.⁸ More recently, a carbon capture power plant was launched in 2014 at Boundary Dam Power Station in Saskatchewan (Canada), and its goal is to capture 1 million tons of CO₂ every year, to reduce CO₂ emissions by 90%.⁸ In 2011 the Laboratory of Chemical Process Safety (*Laboratoire de Sécurité des Procédés Chimiques* LSPC, INSA Rouen - Université Rouen) has contributed to the scale up of a large-scale pilot, in association with Veolia Environment, for a waste incinerator in Normandy (France).⁹⁻¹⁰

Different chemical processes can be used to capture and regenerate pure CO₂. A suitable solution to integrate carbon capture into an existing combustion process, is to modify the post-combustion unit (Figure 3). It is also known as the downstream modification of the existing CO₂ emitting process. The post-combustion carbon capture is based on absorption and desorption phenomena. Those chemical principles are used to absorb CO₂ and separate it from other gases resulting from a combustion reaction. The flue gas is first absorbed into a solvent, e.g. monoethanolamine (MEA), and CO₂ can then be regenerated by altering the thermodynamic conditions of the CO₂-loaded solvent (e.g. by increasing its temperature).¹¹

Design and operation of the carbon capture and storage pilot plant

The pilot plant performed the carbon dioxide capture process through absorption using a chemical solvent. An amine-based solvent was selected to absorb CO₂ due to the strong chemical affinity between the two compounds. There are different types of amine that allow CO₂ capture. Most of the commercial plants use monoethanolamine (MEA). This aqueous primary amine is commonly used for post-combustion separation processes¹²⁻¹³, as it is highly reactivity with CO₂, inexpensive and readily available.¹⁴

The absorption occurs in accordance with the following reaction equation:

The CO₂ present in the flue gases is normally pumped into the carbon dioxide scrubber, and then cooled down by a heat exchanger. The cooled effluent gas is then fed into the bottom of an absorption column and propagates up through packing material. A counter flow of MEA is produced by nozzles located at the top of the absorption column and propagates down, contacting with the gases through the packing material. The packing material improves contact between the gas and the liquid phases, thus increasing the absorption rate of the CO₂. The CO₂-loaded MEA flows down to the bottom of the column, while the decarbonized effluent gas rises up to the top of the column and can be released from the scrubber. The absorption generally occurs at atmospheric pressure and at temperature of approximately 50°C.

The loaded-MEA is then pumped and heated up to 70°C before being introduced at the top of an air stripper. The liquid in the column is heated to 100°C, and the pressure remains at 1 bar. The increased temperature activates the desorption of CO₂ from the MEA, which remains in the liquid state. Once released, the gaseous CO₂ can be extracted from the top of the desorption column. The extracted gas is then cooled down with a water heat exchanger to condensate the water and solvent steam, and to obtain

pure CO₂ gas. The CO₂-lean MEA that remains in the desorption column is pumped out of the column and cooled down through a heat exchanger using the water and CO₂-rich MEA flows. MEA is then regenerated and returned to the absorption column to be reused in a closed-loop cycle (Figure 3).^{9-11, 13-15}

Figure 3. Schematic of the carbon capture chemical process.

Adapting the pilot plant for educational outreach purposes

The lab-scale pilot plant described above, and shown in Figure 1, was commissioned by the CoolCap team as a visual aid to demonstrate concretely the theoretical and operating principles of carbon capture to a broad audience. The pilot was placed in a mobile cabinet (1.2 m long, 1.8 m high, 0.6 m deep) fitted with casters to facilitate transportation.

The design and pilot appearance was specifically customized like a pilot plant to make it more informative to young audiences. Industrial activity was illustrated with a miniature factory made of steel. An alcohol lamp burned to represent industrial

combustion and created some effluent gas, which was then aspirated into the pilot and to the absorption column.

The MEA can also be dyed yellow to improve the visualization of its circulation through the pilot plant, by the addition of a small amount of fluorescein (a few milligrams).

At the end of the desorption process, experiments were used to demonstrate that the gas extracted from the desorption column contains mostly CO_2 . For example, limewater was used in a laboratory flask and connected to the end of the process. Limewater becomes cloudy when exposed to CO_2 because of the formation of a precipitate, thus demonstrating the presence of CO_2 in the gas extracted from the desorption column.

Moreover, to illustrate the geological storage of CO_2 the outlet of the desorption column was connected to a vase full of sand, representing geological layers. A vacuum is generated in the center of the vase to draw the gas through the vase. This is the technology of carbon capture and storage (CCS). The transformation or valorization of CO_2 to chemicals, fuels or its use as a solvent was also discussed. This is the technology of carbon capture and utilization (CCU).

EDUCATIONAL APPROACH

210 The demonstration had a number of education objectives:

- To raise awareness of the greenhouse effect among children.
 - To present a new technology that can help to reduce CO₂ emissions.
 - To show that chemistry can be useful to find concrete solutions to problems such as global warming.
- 215 • To share information about chemical principles: absorption and desorption phenomena between CO₂ and an amine-based solvent.
- To promote science and chemistry to children.

The demonstrations were tailored to the age of the audience, but always based on the same framework. The greenhouse effect and global warming were explained or
220 reminded as an introduction, and then the carbon capture technology was presented using the pilot plant and some interactive chemical experiments. The ways in which we adapted our pedagogical approach for primary school, high school and university students were based on effective communication strategies and recommended good practices¹⁶⁻¹⁷, and described in the next sections.

225 Presentation carried out

The CoolCap team carried out presentations to several groups in schools and universities:

- Four groups of 10 to 30 high school students.
- 230
- Two groups of 10 and 17 masters students.
 - Three groups of 15 to 30 bachelor students.
 - Eight groups of 30 primary school students.

The project team took part in the French national science festival “Fête de la Science” for three days in October 2014. This included presentations and demonstrations to several hundred students from primary school to university levels. In the following sections we present our approach to tailoring the learning experience to audiences from a primary school and a high school.

Primary school

The CoolCap team carried out presentations and interactive demonstrations at a British primary school, with students from 7 to 12 years of age. They were grouped into classes of 30 students of similar ages. The aim was to make the presentation as interactive as possible and to have a series of discussions with the children. In order to maintain the younger audience’s attention the demonstrations lasted no more than 30 minutes. Prior to these presentations, the learning objectives and lesson plans were presented to the class teachers, so they could introduce the topic to provide complementary information about chemistry fundamentals, including chemical reactions or basic thermodynamics.

The first part of the demonstration reviewed concepts of the greenhouse effect and global warming, in order to make the children aware of these environmental issues, and to explain the need for CO₂ capture technologies. First, the project team asked what they already knew about the greenhouse effect and global warming. The majority of students already had notions about climate change. The purpose was to add scientific notions about solar radiation, greenhouse gases and the global increase in the Earth’s surface temperature. This discussion was supported by a model (Figure 4) which facilitated the step-by-step demonstration of the propagation and reflection of the Sun’s rays through the atmosphere. Different solutions to reduce CO₂ emissions were discussed with the children, the CCS and CCU technologies were then presented as a

possible solution to diminish the release of industrially-generated CO_2 into the atmosphere.

In the second part of the demonstration, the operating principle of carbon capture was explained and demonstrated using the pilot plant. This helped the children better understand the various steps of the process, and how the absorption and desorption phenomena occur in such plants. From a chemical point of view, only the absorption and desorption phenomena were described through the chemical reaction and the affinity between MEA and CO_2 . Images were used to support the explanation of this chemical principle. One example we used was to compare the solvent to a train which collected CO_2 'passengers' inside the absorption column, and dropping them off in the desorption column. Another way to explain this process was to suggest that MEA swallows CO_2 molecules in the absorption column and releases them in the desorption column. After explaining the chemical process, CO_2 storage was then explained with the visual support from a vase full of colored sands, representing the sedimentary layers and the well-used to store the extracted carbon dioxide.

Figure 4. Model used to explain the greenhouse effect.

The third part of the presentation consisted in carrying out two experiments in order to highlight the phenomena of absorption and desorption. Those simple experiments helped the public engage with the presentation and participate in the demonstration.

280

Experiment to show the absorption phenomenon

The first experiment highlighted the phenomenon of absorption of carbon dioxide by MEA in the absorption column. For this purpose, we used 20 mL of a sodium hydroxide solution at a concentration of 2 mol.L⁻¹. Since NaOH is a base, it has similar properties
285 to MEA regarding the absorption of CO₂¹⁸, but it has the advantage of being less corrosive and toxic than MEA. Thus the experiments can be carried out more safely than with MEA.

The experiment required two empty plastic bottles of 0.5 L and one volumetric pipette. One of the plastic bottles was filled with CO₂ in advance, while the second
290 bottle was full of air. Using the pipette, 10 mL of the sodium hydroxide solution was then inserted in both bottles, and the bottles were sealed. Two students were asked to volunteer to shake the bottles for few seconds. Then, the audience could compare the two bottles: one bottle had contracted and became warmer, while the other one had remained unchanged (Figure 5). The NaOH solution absorbs CO₂ but not air, hence only
295 the bottle that contained CO₂ had contracted. This interactive demonstration helped support the explanation that liquid solvents can absorb gaseous CO₂. This simple experiment provided a visual support for explaining that the bottle full of CO₂ had contracted due to the CO₂ molecules being absorbed by the NaOH solution. As this is an exothermic reaction, it generated heat and warmed the bottle up. This phenomenon
300 was described with an increasing level of detail to high school and university students who have prior knowledge of chemical reactions.

Figure 5. Plastic bottles filled with sodium hydroxide solution and CO_2 (left), and filled with sodium hydroxide solution and air (right). The NaOH solution absorbs CO_2 but not air, hence only the bottle that contains CO_2 has contracted. This interactive demonstration helped support the explanation that liquid solvents could absorb gaseous CO_2 .

Experiment to show the desorption phenomenon

The second experiment demonstrated the phenomenon of CO_2 desorption. As mentioned previously, CO_2 can transfer into the gas phase by increasing the temperature of the solvent. In order to demonstrate this process, a beaker was filled with cold water (approximately 5°C) while another one was filled with hot water (approximately 40°C). Then, two test tubes were filled with a soft drink (carbonated beverage) and partially closed with a pierced lid. These two test tubes were turned upside down, blocking the pierced lid with the thumb, and plunged into the two water beakers. The experimenter could then release the pierced lids, and let the desorption phenomenon occurred. After a few minutes, it could be observed that the level of soft drink in the test tube plunged in the hot water beaker decreased, while the level of soft drink in the cold test tube remained constant (Figure 6).

This experiment demonstrated to the children the influence of temperature on the solubility of carbon dioxide in a liquid solvent, and that the heat enabled the desorption of CO_2 . As a result of this desorption the pressure above the soft drink increased, and the level of liquid in the test tube reduced.

Figure 6. Schematic representation of the desorption experiment with a warm water beaker (left) and a cold water beaker (right). This demonstrated the influence of temperature on the solubility of carbon dioxide in a liquid solvent, and that the added heat enabled the desorption of CO₂.

High school

The primary school presentation was adapted for older students from high schools and universities. The demonstrations lasted between 45 minutes and one hour, including more technically and scientifically detailed explanations. Since the students already have prior knowledge of the greenhouse effect, the project team presented facts and data about the international context of climate change, and the United Nations' agreements to develop new technologies for the reduction of anthropogenic production of CO₂. The CCS and CCU technologies were presented as one of the potential solutions. The three carbon capture methods were introduced: the oxyfuel-combustion, pre-combustion and post-combustion capture. Details were given about the combustion reaction, about the differences between the methods and how they were used in industrial processes. The post-combustion capture was used for the pilot plant. Hence this process was explained in more details, and supported by the pilot plant, with a view of the way the exhaust gases and the solvent propagate through the absorption

column, the heat exchangers and the air stripper. The chemical reactions and the thermodynamic conditions, such as molecule groups, temperature and pressure, were
345 more detailed than for the younger audience. The topic was also discussed with the students' teachers in order to extend the learning beyond our interactive demonstration, and to cover some of the fundamental principles linked to these chemical processes. Storage and transformation of carbon dioxide were then presented, including the different geological layers that can be used for storage, and the industrial
350 sectors that can reuse carbon dioxide. We observed that the students were particularly interested in the industrial aspects of the technology, such as how to incorporate the system in global industrial processes. They were also interested in the technical details of the carbon capture process.

STUDENT FEEDBACK

In order to evaluate the delivery of our demonstrations and the interest of the students we gave questionnaires to the audience after our presentations. Two types of feedback forms were prepared: one for students under the age of 11, and one for older students. For the presentation at the primary school, 90% of the 240 students were satisfied with the presentation and enjoyed the experiments. From the survey, 81% understood very much the greenhouse effect, 16% understood a little and 3% answered they did not understand it. From the survey, 77% understood very much the CO₂ capture and 23% understood a little (see Figure 2 supporting information).

The feedback for the older audience asked more specific questions, including their level of satisfaction with the presentation: the visual aids, the duration, the exchanges with the team and the level of technical detail. They were also asked if the presentation was adapted to their prior knowledge and if they understood the different elements. To give an example, for 27 master students in mechanical engineering, 96% were satisfied by the presentation, with 52% totally satisfied, 44% very much satisfied and 4% a little. The talk was globally understood by 96% of the students, 41% understood completely, 52% very much, and 7% a little. The analysis of the feedback forms indicates that the demonstrations were generally appreciated and well understood (see Figure 3 supporting information).

CONCLUSIONS

We presented a new and innovative approach to demonstrate carbon capture technology whilst supporting the learning of chemical processes to a wide range of audiences. The challenges of presenting a complex technology, and the chemical reaction between a liquid solvent and gaseous CO₂, to primary school students were overcome through visually simple and hands-on experiments supported by a purpose-built pilot plant. The educational pilot plant we designed and built can be replicated to demonstrate chemistry notions in a novel and interactive way. The feedback we received from 267 primary school students and master students suggests that the educational approach we have described in this article stimulated student interest in science and technology, while improving their awareness of the challenges posed by the strengthening of the greenhouse effect and the impact on climate change.

ASSOCIATED CONTENT

Supporting Information

The following documents can be found as supporting information:

- Construction of carbon dioxide capture pilot plant.
- Equipment for the pilot plant.
- Pilot plant startup procedure.
- Pilot plant shutdown procedure.
- Process flow diagram of the carbon dioxide capture pilot plant.
- Feedback results from masters students in Mechanical Engineering from the University of Brighton (Brighton, UK).
- Feedback results from the students of the Glebe Primary School (Southwick, UK).

AUTHOR INFORMATION

Corresponding Author

*E-mail: sebastien.leveneur@insa-rouen.fr

ACKNOWLEDGMENTS

This work was supported by the European Regional Development Fund [INTERREG IVA grant 4274]. The authors are particularly grateful to Bruno Daronat for his contribution to the experiment. The authors would like to acknowledge the contributions from the previous project student team, composed of Lucie Alleaume, Jeanne Bertoldi, Charles Briec, Camille Courbet, Mathilde Francois, Ana Gavrilenco, Arnaud Khun, Charlotte Nicolas, and Julien Ribotta. We would also like to thank Ludovic Auvray for proofreading this article.

REFERENCES

(1) NASA. Climate Change: How do we know? <http://climate.nasa.gov/evidence>

(accessed December 2014).

(2) Intergovernmental Panel on Climate Change (IPCC). Chapter 8 Anthropogenic and Natural Radiative Forcing. In Climate Change 2013: The Physical Science Basis.

http://www.ipcc.ch/pdf/assessment-report/ar5/wg1/WG1AR5_Chapter08_FINAL.pdf

(accessed December 2014).

(3) American Association for Advancement of Science. AAAS Board Releases New Statement on Climate Change. <http://www.aaas.org/news/aaas-board-releases-new-statement-climate-change>

(accessed December 2014).

(4) United Nations Framework Convention on Climate Change. Kyoto Protocol.

http://unfccc.int/kyoto_protocol/items/2830.php (accessed January 2015).

(5) Flener-Lovitt, C. Using the Socioscientific Context of Climate Change to Teach Chemical Content and the Nature of Science. *J. Chem. Educ.* **2014**, 91 (10), 1587-1593.

(6) King Abdullah Petroleum Studies, Saud M. Al-Fattah, Murad F. Barghouty, Bashir O. Dabbousi. Chapter 1: CCS in a Global Context. In: Carbon Capture and Storage: Technologies, Policies, Economics, and Implementation Strategies, CRC Press/Balkema:

Boca Raton, 2011; pp 3-10.

(7) Zhao, R.; Deng, S.; Zhao, L.; Liu, Y.; Tan, Y. Energy-saving Pathway Exploration of CCS Integrated with Solar Energy: Literature Research and Comparative Analysis. *Energy Conversion and Management* **2015**, 102, 66-80.

(8) Mumford, K.A.; Wu, Y.; Smith, K.H.; Stevens, G.W. Review of Solvent based Carbon-dioxide Capture Technologies. *Front. Chem. Sci. Eng.* **2015**, 9(2), 125-141.

(9) Aouini, I.; Ledoux, A.; Estel, L.; Mary, S. Pilot Plant Studies for CO₂ Capture from Waste Incinerator Flue Gas Using MEA Based Solvent. *Oil & Gas Science and Technology – Rev. IFP Energies nouvelles* **2014**, 69 (6), 1091-1104.

(10) Aouini I. Captage du dioxyde de carbone en postcombustion - Application à un
445 incinérateur de déchets industriels. PhD Thesis, LSPC INSA Rouen, 2012.

(11) King Abdullah Petroleum Studies, Saud M. Al-Fattah, Murad F. Barghouty, Bashir
O. Dabbousi. Chapter 3: CO₂ Capture and Separation. In: Carbon Capture and Storage:
Technologies, Policies, Economics, and Implementation Strategies, CRC Press/Balkema:
Boca Raton, 2011; pp 119-124.

450 (12) Nuchitprasittichai, A.; Cremaschi, S. Sensitivity of Amine-based CO₂ Capture Cost:
The Influences of CO₂ Concentration in Flue Gas and Utility Cost Fluctuations. *Int. J.*
Greenhouse Gas Control **2013**, 13, 34–43.

(13) Han, C.; Graves, K.; Neathery, J.; Liu, K. Simulation of the Energy Consumption of
CO₂ Capture by Aqueous Monoethanolamine in Pilot Plant. *Energy and Environment*
455 *Research* **2011**, 1(1), 67-80.

(14) Qi Yang, Susan James, Mathew Ballard, Mark Bown. Attalla M. Chapter 2:
Influence of Amine Chemical Structures to Amine Capacities in CO₂ Capture. In: Recent
Advances in Post-Combustion CO₂ Capture Chemistry, American Chemical Society:
Washington DC, 2012; pp 29–42.

460 (15) Yeh, J. T.; Pennline, H. W.; Resnik, K. P. Study of CO₂ Absorption and Desorption
in a Packed Column. *Energy Fuels* **2001**, 15 (2), 274–278.

(16) Schwan, S.; Grajal, A.; Lewalter, D. Understanding and Engagement in Places of
Science Experience: Science Museums, Science Centers, Zoos, and Aquariums.
Educational Psychologist **2014**, 49(2), 70-85.

465 (17) Sinatra, G.M.; Kienhues, D.; Hofer, B.K. Addressing Challenges to Public
Understanding of Science: Epistemic Cognition, Motivated Reasoning, and Conceptual
Change. *Educational Psychologist* **2014**, 49(2), 123-138.

(18) Mahmoudkhani, M.; Keith D.W. Low-energy Sodium Hydroxide Recovery for CO₂ Capture from Atmospheric Air—Thermodynamic Analysis. *Int. J. Greenhouse Gas*

470 *Control* **2009**, 3 (4), 376–384.