Abnormal Curves in a Zermelo Navigation Problem in the Plane and the Fan Shape of Small Time Balls

Bernard Bonnard, Olivier Cots, Joseph Gergaud, Boris Wembe

► To cite this version:

Bernard Bonnard, Olivier Cots, Joseph Gergaud, Boris Wembe. Abnormal Curves in a Zermelo Navigation Problem in the Plane and the Fan Shape of Small Time Balls. 2020. hal-02437507v4

HAL Id: hal-02437507

<https://hal.science/hal-02437507v4>

Preprint submitted on 16 Dec 2020 (v4), last revised 10 Jan 2022 (v6)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Abnormal Geodesics in 2D-Zermelo Navigation Problems in the Case of Revolution and the Fan Shape of the Small Time Balls

B. Bonnard¹, O. Cots^{*}, J. Gergaud^{2,*}, B. Wembe^{3,*}

Abstract

In this article, based on two cases studies, we discuss the role of abnormal geodesics in planar Zermelo navigation problems. Such curves are limit curves of the accessibility set, in the domain where the current is strong. The problem is set in the frame of geometric time optimal control, where the control is the heading angle of the ship and in this context, abnormal curves are shown to separate time minimal curves from time maximal curves and are both small time minimizing and maximizing. We describe the small time minimal balls. For bigger time, a cusp singularity can occur in the abnormal direction, which corresponds to a conjugate point along the nonsmooth geodesic. It is interpreted in terms of regularity property of the time minimal value function.

Keywords: Geometric optimal control, Zermelo navigation problems, Abnormal geodesics, Singularity of the value function in the abnormal direction.

2010 MSC: 49K15, 49L99, 53C60, 58K50

1. Introduction

A Zermelo navigation problem in the plane can be stated using [6] as a time minimal control problem described by the dynamics

$$\dot{q}(t) = F_0(q(t)) + \sum_{i=1}^2 u_i(t) F_i(q(t)) \quad (1)$$

^{*}Toulouse Univ., INP-ENSEEIH-IRIT, UMR CNRS 5505, 2 rue Camichel, 31071 Toulouse, France, olivier.cots@irit.fr.

¹Inria, 2004 route des Lucioles F-06902, Sophia Antipolis, France, bbonnard@u-bourgogne.fr.

²Toulouse Univ., INP-ENSEEIH-IRIT, UMR CNRS 5505, 2 rue Camichel, 31071 Toulouse, France, joseph.gergaud@irit.fr.

³Toulouse Univ., IRIT-UPS, UMR CNRS 5505, 118 route de Narbonne, 31062 Toulouse, France, boris.wembe@irit.fr.

where $q = (x, y)$ are the coordinates, F_i being C^∞ -vector fields and $u = (u_1, u_2)$ is the control, bounded by $\|u\| = \sqrt{u_1^2 + u_2^2} \leq 1$. The vector field F_0 is called the *current* (or drift) while the *control fields* F_1 and F_2 define a *Riemannian*
5 *metric* g , taking $\{F_1, F_2\}$ as an orthonormal frame. If $\|u\| = 1$, one can set $u = (\cos \alpha, \sin \alpha)$ and α is the *heading angle* of the ship.

This type of problems originated from a *historical example* due to Carathéodory and Zermelo [10, 15] in the frame of calculus of variations, where a rather complete analysis was presented, is one of the motivation of this article. In this example, the dynamics is described by the pair

$$F_0(q) = y \frac{\partial}{\partial x}, \quad g = dx^2 + dy^2,$$

where g is the *Euclidean metric*. Taking an arbitrary metric and considering the *weak current case* $\|F_0\|_g < 1$, with $\|\cdot\|_g$ the norm associated to the metric g , this problem leads to a Zermelo navigation problem in Finsler geometry [2].

More recently, in [4], a Zermelo navigation problem was analyzed in details, associated to the evolution of a *passive tracer*, where the current is related to a *vortex*, centered at the origin of the reference frame. This problem comes at the origin from hydrodynamics [1]. Moreover, it is a toy model for the N-body problem, in the frame of Hamiltonian dynamics [12]. In this case, the system evolves on the punctured plane $\mathbb{R}^2 \setminus \{0\}$, the current being given by

$$F_0(q) = \frac{k}{(x^2 + y^2)} \left(-y \frac{\partial}{\partial x} + x \frac{\partial}{\partial y} \right)$$

where $k > 0$ is the *circulation parameter* and the control fields being given by $g = dx^2 + dy^2$. Using polar coordinates $q = (r, \theta)$ one has

$$F_0(q) = \frac{k}{r^2} \frac{\partial}{\partial \theta}$$

and the Euclidean metric takes the form

$$g = dr^2 + r^2 d\theta^2.$$

These two use cases can be set in the same geometric frame by considering in a coordinate system $q = (r, \theta)$, a Zermelo navigation problem, where the current is in the form

$$F_0(q) = \mu(r) \frac{\partial}{\partial \theta} \tag{2}$$

and where the metric is given by

$$g = dr^2 + m^2(r) d\theta^2, \quad m(r) > 0.$$

10 Such a metric was the object of many studies in the context of mechanics and Riemannian geometry and it is called a *metric of revolution* in *Darboux coordinates* (r, θ) , where the lines $r = \text{constant}$ are the *parallels* and the lines $\theta = \text{constant}$ are the *meridians* [5]. Note that in (2), the current is along the

parallels only, which is sufficient to cover the two founding examples. We refer
to [11] for a case study in the differential geometric frame, in the case of a *weak*
current, that is *Randers problems* in Finsler geometry [2], assuming $\|F_0\|_g < 1$.
In this article, we focus on the case of a *strong current*, that is $\|F_0\|_g > 1$. It was
already the case studied in details in the historical example. On the opposite,
in the vortex problem [4], the analysis was concentrated on the situation where
at the initial point, the current is weak but the tracer can reach the vicinity of
the vortex where the current is strong.

To present our contribution, we must introduce the following concepts from
geometric optimal control. The set of admissible controls $\mathcal{U}$ is the set of mea-
surable mappings u from $[0, +\infty)$ to the unit closed Euclidean ball: $\|u\| \leq 1$,
endowed with the L^∞ -norm topology. We denote by $q(\cdot, q_0, u)$ the response of
the dynamics (1) associated to u , with $q(0) = q_0$. Let $t_f \geq 0$, the *accessibility*
set from q_0 in time t_f is defined by $A(q_0, t_f) = \{q(t_f, q_0, u) \mid u \in \mathcal{U}\}$ (if $q(\cdot, q_0, u)$
is defined on the whole $[0, t_f]$) and this gives the *accessibility set* from q_0 defined
by $A(q_0) = \cup_{t_f \geq 0} A(q_0, t_f)$. Thanks to existence theorems in optimal control, in
many cases (and in particular in the two cases studies), for each q_0, q_1 provided,
($q_0, q_1 \neq 0$ in the vortex case), there exists a time minimal solution to transfer
 q_0 to q_1 and from the *Maximum Principle* [13], candidates as minimizers are
geodesic curves. If such a theorem holds, fixing q_0 , the *time minimal value*
function is given by:

$$T(q_1) = \inf \{t_f \mid q(t_f, q_0, u) = q_1 \text{ and } u \in \mathcal{U}\}$$

and the *sphere* $\mathbf{S}(q_0, r)$ of radius r is the set of points q_1 which can be reached
from q_0 in minimum time r , while the *ball* of radius r is the set $\mathbf{B}(q_0, r) =$
 $\bigcup_{r' \leq r} \mathbf{S}(q_0, r')$.

The aim of this article is double. First of all, and based on [3] we provide the
geometric frame from optimal control theory to analyze such Zermelo navigation
problems and we make a focus on the role of abnormal geodesics (the limit curves
in Carathéodory terminology) in such problems. One ingredient is to introduce
the *Carathéodory-Zermelo-Goh transformation* which amounts to parameterize
the geodesics using as accessory control the derivative of the heading angle. This
allows to evaluate the accessibility set and its boundary filled by the geodesics,
in the abnormal directions, as the image of the extremity mapping, using *semi-*
normal forms. In particular the *tangent model* can be easily described. The
second step is to extend this analysis to larger time as shown by the two cases
studies. A singularity can occur along the abnormal geodesic corresponding to
a *cusp point* and associated to a concept of *conjugate point* along nonsmooth
abnormal geodesic, extending the concept of conjugate point in the smooth case,
introduced in [3]. This leads to describe the regularity of the time minimal value
function (from generic point of view) in both normal and abnormal cases. See
[8, 9] for the relation with singularities of semi-concave functions.

The organization of this article is as follows. In section 2, we introduce the
geometric frame from optimal control to analyze in a general case the time min-
imal solutions, in the context of Hamiltonian dynamics, using the Maximum

Principle [13]. This provides the parameterization of both *time minimal and*
45 *time maximal* solutions, which is crucial to understand the role of abnormal
geodesics. We introduce the Carathéodory-Zermelo-Goh transformation which
amounts to extend our dynamics to a *single-input affine system*, and therefore
to use the results from [3], in particular to construct the *tangent model* in order
to clarify the role of abnormal geodesics. This from a geometric point of view, in
50 relation with *Lie algebraic computations*. This allows to evaluate the extremity
mapping in the abnormal direction, image of the exponential mapping, and its
boundary using the concept of Jacobi field. In section 3, using the symmetry
of revolution, the geodesics curves can be parameterized, thanks to integra-
bility properties. This is the tool to compute the sphere and ball of general
55 radii and to describe the time minimal value function. In particular, this allows
to analyze in a more general context two important features observed in the
historical example: the *existence of a cusp singularity for abnormal geodesics*
(related to a phenomenon of self-intersections of neighboring geodesics) and the
non-continuity of the value function. In the conclusion we present a program of
60 further studies related to this note. First, *models of singularities* of the value
function are described, and this can be used in a more general context, since
integrability is not a crucial issue in our study. Second, Zermelo navigation prob-
lems with symmetry of revolution are an important geometric object of study,
in the frame of *integrable* Hamiltonian dynamics, in relation to mathematical
65 physics.

2. Maximum Principle and evaluation of the accessibility set in the regular geodesic case

2.1. Maximum Principle

Consider the Zermelo navigation problem whose dynamics is described by
(1). To formulate the Maximum Principle [13], we introduce the *pseudo-Hamiltonian*
associated to the cost (extended) system:

$$H(z, u) = H_0(z) + \sum_{i=1}^2 u_i H_i(z) + p^0 \quad (3)$$

where $z = (q, p)$, $p = (p_x, p_y)$ being the *adjoint vector*, $H_i(z) = p \cdot F_i(q)$ being,
70 for $i = 0, 1, 2$, the Hamiltonian lift of the vector field F_i ($\cdot$ denotes the standard
inner product) and p^0 is a constant.

The *maximized* (or true) *Hamiltonian* is given by the maximization condition

$$\mathbf{H}(z) = \max_{\|u\| \leq 1} H(z, u), \quad (4)$$

and since F_1, F_2 form a frame, we have

Proposition 2.1. 1. *The maximizing controls are given by*

$$u_i(z) = \frac{H_i}{\sqrt{H_1^2 + H_2^2}}, \quad i = 1, 2. \quad (5)$$

2. The maximized Hamiltonian is given by

$$\mathbf{H}(z) = H_0(z) + \sqrt{H_1^2 + H_2^2} + p^0 \quad (6)$$

3. Candidates as time minimizers (resp. maximizers) are solutions of the Hamiltonian dynamics:

$$\dot{z}(t) = \vec{\mathbf{H}}(z(t)), \quad (7)$$

with

$$\vec{\mathbf{H}} = \frac{\partial \mathbf{H}}{\partial p} \frac{\partial}{\partial x} - \frac{\partial \mathbf{H}}{\partial x} \frac{\partial}{\partial p}$$

and $p^0 \leq 0$ (resp. ≥ 0) in the time minimal (resp. maximal) case.

Definition 2.1. An extremal is a solution $z(\cdot) = (q(\cdot), p(\cdot))$ of (7) and a
75 projection of an extremal is called a geodesic. It is called strict if p is unique
up to a factor, normal if $p^0 \neq 0$ and abnormal (or exceptional) if $p^0 = 0$. In the
normal case it is called hyperbolic (resp. elliptic) if $p^0 < 0$ (resp. $p^0 > 0$).

Next we relate geodesic curves to singularities of the extremity mapping,
which is an important issue in our analysis, see [3] for a general context and
80 details.

Definition 2.2. Restrict the control domain to the set $\|u\| = 1$. Let $q(\cdot, q_0, u)$
be the response of u , with $q(0) = q_0$. Fixing q_0 , the extremity mapping is the
map: $E^{q_0, \cdot} : u \mapsto q(\cdot, q_0, u)$ and the fixed time extremity mapping (at time T)
is the map: $E^{q_0, T} : u \mapsto q(T, q_0, u)$.

85 **Proposition 2.2.** Take a reference extremal $z(\cdot) = (q(\cdot), p(\cdot))$ on $[0, T]$, where
the corresponding control is given by (5). If we endow the set of controls (valued
in $\|u\| = 1$) with the L^∞ -norm topology we have:

1. In the normal case, u is a singularity of the fixed time extremity mapping,
that is the image of the Fréchet derivative is not of maximal rank.
- 90 2. In the abnormal case, u is a singularity of the extremity mapping.

Definition 2.3. Let $t \mapsto q(t)$ be the response of (1). It is called regular if
it is a one-to-one immersion. From the Maximum Principle, the geodesics are
parameterized by the heading angle α and fixing $q(0) = q_0$, the exponential
mapping is $\exp_{q_0, t} : \alpha \mapsto \Pi(\exp(t\vec{\mathbf{H}})(q(0), \alpha))$ where $\Pi : (q, p) \mapsto q$ is the q -
95 projection. Take a strict normal geodesic $q(\cdot)$, a conjugate point along $q(\cdot)$
is a point where the exponential mapping is not an immersion and taking all
such geodesics, the set of first conjugate points will form the conjugate locus
 $C(q_0)$. The cut point along a given geodesic is the first point where the geodesic
loses optimality and they will form the cut locus $\Sigma(q_0)$. The separating line
100 $L(q_0)$ is the set of points where two minimizing geodesics starting from q_0 are
intersecting.

2.2. Carathéodory-Zermelo-Goh transformation and evaluation of the accessibility set

In the historical example [10], Carathéodory integrated the dynamics of the heading angle α to parameterize the geodesics. This corresponds to the Goh transformation in optimal control and this will be crucial in our study to set Zermelo navigation problems in the Lie algebraic frame.

Definition 2.4. Consider the control system (1), with $q = (x, y)$ and $\|u\| = 1$. One can set $u = (\cos \alpha, \sin \alpha)$, α being the heading angle of the ship. Denote $\tilde{q} = (q, \alpha)$, $X(\tilde{q}) = F_0(q) + \cos \alpha F_1(q) + \sin \alpha F_2(q)$ and $Y(\tilde{q}) = \frac{\partial}{\partial \alpha}$. This leads to prolongate (1) into the single-input affine system:

$$\dot{\tilde{q}} = X(\tilde{q}) + v Y(\tilde{q}) \quad (8)$$

and the derivative of the heading angle $v = \dot{\alpha}$ is the accessory control.

We refer to [3] for a presentation of such a transformation in a general context. In this prolongation, the extremal curves $z = (q, p)$ extend to *singular extremal curves* associated to (8), with coordinates $\tilde{z} = (q, \alpha, p, p_\alpha)$. This leads to define the extended Hamiltonian:

$$\tilde{H}(\tilde{z}, v) = \tilde{p} \cdot (X(\tilde{q}) + v Y(\tilde{q})). \quad (9)$$

From [3], using the Maximum Principle we obtain the following parameterization of the geodesic curves. Let γ be a reference geodesic for the extended system defined on $[0, T]$. We assume the following :

(A0) The q -projection of γ is regular.

Straightforward computation gives that under assumption (A0) the following holds along γ .

(A1) X, Y are linearly independent.

(A2) $Y, [X, Y]$ are linearly independent and the reference geodesic is strict.

(A3) From Legendre-Clebsch condition we have: $[[Y, X], Y] \in \text{Span}\{Y, [Y, X]\}$.

Hence from [3], the control v associated to γ can be computed as the feedback

$$v(\tilde{q}) = -\frac{D'(\tilde{q})}{D(\tilde{q})}, \quad (10)$$

where we denote

$$\begin{aligned} D &= \det(Y, [Y, X], [[Y, X], Y]), \\ D' &= \det(Y, [Y, X], [[Y, X], X]). \end{aligned} \quad (11)$$

Moreover, introducing

$$D'' = \det(Y, [Y, X], X), \quad (12)$$

we have the following.

Proposition 2.3. *We have:*

- *hyperbolic geodesics are in $DD'' > 0$,*
- *elliptic geodesics are in $DD'' < 0$,*
- *abnormal (or exceptional) geodesics are located in $D'' = 0$.*

The important application is to use the fine computations of [3] to evaluate in our problem the extremity mapping in the neighborhood of a reference geodesic curve γ , using *semi-normal forms*, for the action of the feedback group. This gives evaluation of the accessibility sets and *their boundaries*, filled by geodesic curves. For the details we refer to the previous reference in a more general dimensional setting.

2.2.1. Semi-normal forms

We proceed as follows. For a reference geodesic curve $t \mapsto \gamma(t)$ on $[0, T]$, under the action of the *feedback group*, one can identify γ to $t \mapsto (t, 0, 0)$ and it can be taken as the response of $v \equiv 0$.

Normalization are obtained in the jet spaces of (X, Y) , in the neighborhood of γ . This is convenient to distinguish normal and abnormal cases.

Normal Case. We can choose coordinates $\tilde{q} = (q_1, q_2, q_3)$ such that the system takes the form:

$$\begin{aligned} X &= \left(1 + \sum_{i,j=2}^3 a_{i,j}(q_1) q_i q_j \right) \frac{\partial}{\partial q_1} + q_3 \frac{\partial}{\partial q_2} + \varepsilon_1, \\ Y &= \frac{\partial}{\partial q_3}, \end{aligned} \tag{13}$$

with $a_{33} < 0$ (resp. $a_{33} > 0$) in the hyperbolic (resp. elliptic) case.

Abnormal Case. We can choose coordinates $\tilde{q} = (q_1, q_2, q_3)$ such that the system takes the form:

$$\begin{aligned} X &= (1 + q_2) \frac{\partial}{\partial q_1} + \frac{1}{2} a(q_1) q_2^2 \frac{\partial}{\partial q_3} + \varepsilon_2, \\ Y &= \frac{\partial}{\partial q_2}. \end{aligned} \tag{14}$$

Again see [3] for details of the computation and description of $\varepsilon_1, \varepsilon_2$. Taking $\varepsilon_i = 0$ and $q_1 = t$ in (13), (14), one can evaluate the accessibility set and its boundary and compute conjugate points (in the regular case) to deduce the optimality status of the reference geodesic.

140 *2.2.2. Optimality status: normal case*

Using the normalization in (13) one sets: $q_1(t) = t + w_1(t)$ and projection of the accessibility set in w_1 -direction is represented on Fig. 1. Note that hyperbolic and elliptic geodesics amount respectively to minimize and maximize the w_1 -coordinate. If $t > t_{1c}$ (first conjugate time) the fixed extremity mapping
 145 becomes open.

Figure 1: Projection of the fixed time accessibility set on the w_1 -coordinate; t_{1c} : first conjugate time.

We have:

Proposition 2.4. *Under the assumptions, in the hyperbolic (resp. elliptic) case, the reference geodesic γ is time minimizing (resp. maximizing) with respect to all trajectories of the system, contained in a conic neighborhood of the reference curve, if the final time is strictly less than the first conjugate time t_{1c} .*
 150

2.2.3. Optimality status: abnormal case

In this case, one must estimate the *time evolution* of the accessibility set and its boundary. It is represented on Fig. 2. The reference geodesic is $\gamma: t \mapsto (t, 0, 0)$ and is associated to $v \equiv 0$. We fix t along the reference curve and let a time t_f in a neighborhood of t . Using the model, we compute geodesics such that :

$$q_1(t_f) = t, \quad q_2(t_f) = 0, \quad (15)$$

and the associated cost is given by

$$q_3(t_f) = \int_0^{t_f} \frac{1}{2} a(q_1) q_2^2 \, dt. \quad (16)$$

Note that if we restrict to geodesics, this amounts to use the Jacobi (variational) equation, along the reference geodesic. One has:

$$q_3(t_f) = \alpha(t - t_f)^2 + o(t - t_f)^3 \quad (17)$$

α being a positive invariant, given by the Jacobi equation.

Figure 2: Projection of the accessibility sets on the q_3 -coordinate in the abnormal case.

Note that the model (14) shows clearly that the abnormal curve is a limit curve, as observed by Carathéodory. In the n -dimensional case, conjugate points along the abnormal curve can be computed and correspond to points where the extremity mapping becomes open. But clearly from (17) this cannot occur in the 3d-case.

In particular one has:

Proposition 2.5. *Under our assumptions, in the abnormal (exceptional) case the reference geodesic is time minimizing and time maximizing, with respect to all trajectories contained in a conic neighborhood of the reference curve.*

2.3. Small time balls and spheres in the strong current case

One consequence of our previous analysis is to recover the fan shape of the small time balls, in the case of a strong current and described in the historical example.

We proceed as follows.

2.3.1. The tangent model

We assume that $\|F_0(q_0)\|_g > 1$. We can identify q_0 to 0, $q = (x, y)$, $F_0(q_0)$ can be taken as vertical and we can assume $F_1(q_0) = \frac{\partial}{\partial x}$, $F_2(q_0) = \frac{\partial}{\partial y}$. The ball of directions at q_0 is defined by:

$$F(q_0) = \{F_0(q_0) + u \mid \|u\| \leq 1\}.$$

It is represented on Fig. 3 and its boundary is a translation of the unit circle. The two abnormal directions are associated to the heading angles $\{-\alpha, \alpha\}$ and correspond to the *tangent* of the unit circle. The upper part corresponds to hyperbolic directions and the lower part to elliptic directions.

2.3.2. Small spheres and balls

Using section 2.2, one gets the following.

Figure 3: Strong current case: ball of directions.

Proposition 2.6. *In the strong current case for a small time, the exponential mapping is a diffeomorphism from the unit circle onto its image, which is formed on the upper part by the extremities of the hyperbolic trajectories, the lower part being the extremities of the elliptic trajectories, the two parts being separated by the two points corresponding to the abnormal trajectories. Hyperbolic and elliptic geodesics corresponding respectively to time minimizing and time maximizing trajectories, while abnormal geodesics are time minimizing and time maximizing.*

The sphere and the ball with small radius are represented on Fig. 4 and in particular this gives the fan shape of the corresponding balls. The contact of the hyperbolic sector with the abnormal curve can be obtained as in section 2.2.3 using the micro-local model where the abnormal geodesic is normalized to the horizontal line. A more precised representation can be obtained in the rotational case, since the geodesic flow is Liouville integrable, which leads to the exact computation of the exponential mapping. This point of view will be developed in the next section.

Figure 4: Small sphere and ball for the strong current case.

3. The cusp singularity in the abnormal direction and regularity of the time minimal value function

We refer to [4, 10] for the occurrence of the cusp singularity in both examples, which motivate the study of this *stable* singularity. The problem is set in the family of problems with rotational symmetry, which covers the two case studies.

3.1. The geometric frame and integrability properties

Recall that in Dardoux coordinates (r, θ) , we consider a metric of the form $g = dr^2 + m^2(r) d\theta^2$ and a current $F_0(q) = \mu(r) \frac{\partial}{\partial \theta}$. With such a metric, $F_1 = \frac{\partial}{\partial \theta}$ and $F_2 = \frac{1}{m(r)} \frac{\partial}{\partial r}$ form an orthonormal frame.

Using the Carathéodory-Zermelo-Goh extension one gets with $\tilde{q} = (r, \theta, \alpha)$, (α being the heading angle):

$$X = \cos \alpha \frac{\partial}{\partial r} + \left(\mu(r) + \frac{\sin \alpha}{m(r)} \right) \frac{\partial}{\partial \theta}.$$

Straighforward computations give:

$$\begin{aligned} [Y, X](\tilde{q}) &= \sin \alpha \frac{\partial}{\partial r} - \frac{\cos \alpha}{m(r)} \frac{\partial}{\partial \theta}, \\ [[Y, X], Y](\tilde{q}) &= \cos \alpha \frac{\partial}{\partial r} + \frac{\sin \alpha}{m(r)} \frac{\partial}{\partial \theta}, \\ [[Y, X], X](\tilde{q}) &= -\mu'(r) \cos \alpha \frac{\partial}{\partial \theta} \end{aligned}$$

Hence we have:

$$D(\tilde{q}) = \frac{1}{m(r)}, \quad D'(\tilde{q}) = -\mu'(r) \cos \alpha \sin \alpha \quad \text{and} \quad D''(\tilde{q}) = \mu(r) \sin \alpha + \frac{1}{m(r)}.$$

So that conditions (A2) and (A3) are satisfied, in particular every geodesic is strict. But the collinearity condition (A1) can be violated at points where

$$\cos \alpha = \mu(r) + \frac{\sin \alpha}{m(r)} = 0.$$

The dynamics is given by

$$\begin{aligned} \dot{r} &= \cos \alpha, \\ \dot{\theta} &= \mu(r) + \frac{\sin \alpha}{m(r)}, \\ \dot{\alpha} &= \mu'(r) m(r) \cos \alpha \sin \alpha. \end{aligned} \tag{18}$$

The following is useful.

Proposition 3.1. *The dynamics (18) can be integrated by quadrature.*

Proof. The pseudo-Hamiltonian takes the form:

$$H = p_r \cos \alpha + p_\theta \left(\mu(r) + \frac{\sin \alpha}{m(r)} \right) + p^0. \quad (19)$$

Moreover, from the maximization condition one has:

$$\frac{\partial H}{\partial \alpha} = 0,$$

which gives the *Clairaut relation*:

$$p_r = \frac{p_\theta}{m(r) \tan \alpha}. \quad (20)$$

Plugging such p_r into (19) allows us to define the following implicit relation between α and r :

$$p_\theta \left(\mu(r) + \frac{1}{m(r) \sin \alpha} \right) + p^0 = 0. \quad (21)$$

200 Hence (18) can be solved by quadrature, integrating α by separation of variables.

From geometric control point of view, it amounts to compute first the control, r being given by equation (21). Then, θ can be obtained using a further quadrature. $\square$

205 This result can be applied to our two cases studies, to give a model of the cusp singularity. We shall present it in our frame, with the historical model.

3.2. Computations in the historical example

We use the cartesian coordinates, so that the dynamics is given by:

$$\dot{x} = y + \cos \alpha, \quad \dot{y} = \sin \alpha, \quad \dot{\alpha} = -\cos^2 \alpha. \quad (22)$$

Straighforward computations using the previous section lead to the following.

Proposition 3.2. *Let $q_0 = (x_0, y_0, \alpha_0)$ be the initial condition, the solution $q(t, q_0)$ is given by:*

$$\begin{aligned} \alpha(t, q_0) &= -\arctan(t - \tan \alpha_0), \\ y(t, q_0) &= -\frac{p^0}{p_x} - \frac{1}{\cos \alpha(t)}, \\ x(t, q_0) &= \frac{1}{2} \left[\ln \left(\frac{\cos \alpha}{1 + \sin \alpha} \right) \right]_{\alpha_0}^{\alpha(t)} + \frac{1}{2} \left[\frac{\tan \alpha}{\cos \alpha} \right]_{\alpha_0}^{\alpha(t)} - \frac{p^0}{p_x} t + x_0. \end{aligned}$$

Cusp point in the abnormal direction. In the abnormal case one has $p^0 = 0$, so that:

$$p_x = -\frac{1}{y_0},$$

and the heading angles of the two abnormal directions at an initial point with a strong current are:

$$\alpha_a^1 = \arccos\left(-\frac{1}{y_0}\right) \quad \text{and} \quad \alpha_a^2 = -\arccos\left(-\frac{1}{y_0}\right).$$

A cusp point occurs at t_{cusp} given by $\dot{x}(t_{\text{cusp}}) = \dot{y}(t_{\text{cusp}}) = 0$, this gives

$$y_{\text{cusp}} = \text{sign}(y_0).$$

Cusp singularity and regularity of the value function. The geometric features of the model, see also Fig. 5, are the following.

- 210 • The abnormal geodesic with the cusp singularity is the limit curve of the micro-local sector, formed by self-intersecting hyperbolic geodesics.
- The abnormal geodesic is optimal up to the cusp point. Hence it corresponds to a concept of conjugate point along the *nonsmooth* abnormal geodesic.
- 215 • Carathéodory [10] already described the following phenomenon. Due to the loss of local accessibility associated to the limit geodesic, the time minimal value function is *not continuous*. This is clear from Fig. 5. To reach from the initial point q_0 a point B at right of the limit curve, one must use a self-intersecting normal geodesic so that at the intersection
- 220 with the abnormal geodesic, the time is longer along the normal than along the abnormal geodesic. We also observe that in this sector, the normal geodesic is optimal up to the intersection point with the abnormal geodesic.

4. Conclusion

225 In this article, the results of [3] are applied to planar Zermelo navigation problems to give a real analysis of the role of abnormal geodesics as limit curves of the accessibility set and to describe the fan shape of the balls with small radius. Generic singularities of the time minimal value function associated to normal directions are all well known due to earlier Whitney classification [14],

230 see also [15] for the Hamiltonian frame. But based on the two case studies, we describe and provide a mathematical model of a (stable) singularity in the abnormal direction. This corresponds to a cusp singularity of the abnormal geodesics, taken as a limit points of self-intersecting normal geodesics. Moreover, in this situation, the time minimal value function is not continuous. Our study

235 completes the contribution of [4] devoted to the calculation of spheres with

Figure 5: (Left) The initial point is q_0 . The abnormal geodesic with the cusp singularity is in green while the others geodesics in red are normal. We can see that the cusp singularity is the limit of self-intersecting normal geodesics. Besides, to reach the point B from q_0 , one has to use a normal self-intersecting geodesic. When this normal geodesic intersects the abnormal, the time is longer along the normal than the abnormal. At this intersection, the normal geodesic ceases to be optimal. (Right) The time minimal value function along the dashed segment from the left subgraph. The discontinuity occurs at the intersection between the normal and abnormal geodesics. It is represented by the green dot, which is the time along the abnormal geodesic.

general radius, in the vortex case, when at the initial point the current is weak. It is a further step to analyze general navigation problems in the plane, in the case with a symmetry of revolution, combining geometric methods with numerical simulations. Also it can serve as models to analyze singularities of the exponential mapping in the non integrable case. In particular in the normal case using (13) and in the abnormal case using (14) and (22). Besides, this gives the corresponding models of the singularities of the value function.

- [1] V. I. Arnold & B. A. Khesin, *Topological Methods in Hydrodynamics*, vol 125 of Applied Mathematical Sciences, Springer-Verlag New York, 1998, 376 pages.
- [2] D. Bao, C. Robles & Z. Shen, *Zermelo Navigation on Riemannian Manifolds*, J. Differential Geom., **66** (2004), no. 3, pp. 377–435.
- [3] B. Bonnard & I. Kupka, *Théorie des Singularités de l'Application Entrée/sortie et Optimalité des Trajectoires Singulières dans le Problème du Temps Minimal*, Forum Math., **5** (1993), no. 2, pp. 111–159.
- [4] Bonnard, O. Cots & B. Wembe, *A Zermelo Navigation Problem with a Vortex Singularity*, ESAIM Control Optim. Calc. Var., (2020), 10.1051/cocv/2020058.
- [5] A. V. Bolsinov, A. T. Fomenko, *Integrable Hamiltonian Systems, Geometry, Topology, Classification*, Chapman and Hall/CRC, London, 2004.

- [6] A. E. Bryson & Y.-C. Ho, *Applied Optimal Control*, Hemisphere Publishing, New York, 1975.
- [7] J. W. Bruce, & V.M. Zakalyukin, *On the Geometry of Caustics*, American Mathematical Society, **180** (1997), pp. 1–11.
- 260 [8] P. Cannarsa & C. Sinestrari *Semiconcave functions, Hamilton-Jacobi equations, and optimal control*, Progress in Nonlinear Differential Equations and their Applications, 58. Birkhuser Boston Inc., Boston, MA, 2004.
- [9] P. Cannarsa & L. Rifford, *Semiconcavity results for optimal control problems admitting no singular minimizing controls*, Ann. Inst. H. Poincaré Non
265 Linaire, **25** (2008), pp. 773–802.
- [10] C. Carathéodory, *Calculus of Variations and Partial Differential Equations of the First Order, Part 1, Part 2*, Holden-Day, San Francisco, California, 1965/1967; Reprint: 2nd AMS printing, AMS Chelsea Publishing, Providence, RI, USA, 2001, 412 pages.
- 270 [11] R. Hama, J. Kasemsuwan and S. V. Sabau, *The Cut Locus of a Randers Rotational 2-Sphere of Revolution*, Publ. Math. Debrecen, **93** (2018), no 3-4, pp. 387–412.
- [12] K. Meyer, G. Hall & D. C. Offin, *Introduction to Hamiltonian Dynamical Systems and the N-Body Problem*, vol. 90 of *Applied Mathematical Sciences*,
275 Springer-Verlag New York, 2009, 399 pages.
- [13] L. S. Pontryagin, V. G. Boltyanskiĭ, R. V. Gamkrelidze & E. F. Mishchenko, *The Mathematical Theory of Optimal Processes*, Translated from the Russian by K. N. Trirogoff, edited by L. W. Neustadt, Interscience Publishers John Wiley & Sons, Inc., New York-London, 1962.
- 280 [14] H. Whitney, *On Singularities of Mappings of Euclidean Spaces. I. Mappings of the Plane into the Plane*, Annals of Mathematics, **62** (1955), no. 3, pp. 374–410.
- [15] E. Zermelo, *Über das Navigations Problem bei Ruhender oder
285 Veränderlicher Wind-Verteilung*, Z. Angew. Math. Mech., **11** (1931), no. 2, pp. 114–124.