Discussion of “Approximate Analytical Solutions for the Colebrook Equation” by Ali R. Vatankhah

Dejan Brkić, Pavel Praks

► To cite this version:

Dejan Brkić, Pavel Praks. Discussion of “Approximate Analytical Solutions for the Colebrook Equation” by Ali R. Vatankhah. *Journal of Hydraulic Engineering*, 2020, 146 (2), pp.07019011. 10.1061/(asce)hy.1943-7900.0001667 . hal-02438103

HAL Id: hal-02438103

<https://hal.science/hal-02438103>

Submitted on 14 Jan 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Discussion of “Approximate Analytical Solutions for the Colebrook Equation” by Ali R. Vatankhah, May 2018, Vol. 144, Issue 5, 06018007, Doi: 10.1061/(ASCE)HY.1943-7900.0001454

Dejan Brkić, PhD, Researcher, IT4Innovations, VŠB - Technical University of Ostrava, 17. listopadu 2172/15, 708 00 Ostrava, Czech Republic and Research and Development Center “Alfatec”, Bulevar Nikole Tesle, 18000 Niš, Serbia, dejanbrkic0611@gmail.com - ORCID id: 0000-0002-2502-0601

Pavel Praks, PhD, Researcher, IT4Innovations, VŠB - Technical University of Ostrava, 17. listopadu 2172/15, 708 00 Ostrava, Czech Republic, pavel.praks@vsb.cz - ORCID id: 0000-0002-3913-7800

The author of the discussed paper (Vatankhah and Kouchakzadeh 2008; 2009, Vatankhah 2014) has made significant contributions related to the Colebrook equation for flow friction (Colebrook 1939; Colebrook and White 1937); Eq. (1):

$$\frac{1}{\sqrt{f}} = -2 \cdot \log_{10} \left(\frac{2.51}{R} \cdot \frac{1}{\sqrt{f}} + \frac{\varepsilon}{3.71 \cdot D} \right) \quad (1)$$

Where f is Darcy flow friction factor, R is the Reynolds number, and ε/D is the relative roughness of inner pipe surface (all three quantities are dimensionless).

Approximations based on genetic programming

It is underlined that it is important to develop not only accurate (Gregory and Fogarasi 1985, Brkić 2011a; 2012, Winning and Coole 2013) but also computational efficient approximations to the Colebrook equation (Clamond 2009, Giustolisi et al. 2011, Čojbašić and Brkić 2013, Winning and Coole 2013, Brkić and Čojbašić 2017). To be computational efficient the approximations need to contain the least possible number of logarithmic and non-integer power expressions (Brkić and Praks 2019). Knowing that appropriately trained artificial neural networks (Özger and Yıldırım 2009, Brkić and Čojbašić 2016) can simulate the Colebrook equation accurately not knowing the structure of the equation but only knowing the input parameters which are the Reynolds number, R and the relative roughness, ε/D and the

corresponding output parameter which is the flow friction factor, f ; $\{R, \varepsilon/D\} \rightarrow f$, we tried to use that fact to extract the accurate and computational accurate explicit approximations using artificial intelligent techniques (Smidt and Lipson 2009, Dubčáková 2011), Eq. (2). We used Eureka, artificial intelligence software tool based on genetic programming (Praks and Brkić 2018a). The symbolic regression approach adopted herein is based upon genetic programming wherein a population of functions is allowed to breed and mutate with the genetic propagation into subsequent generations based upon a survival-of-the-fittest criteria.

$$\frac{1}{\sqrt{f_0}} \approx 1.15 \cdot \alpha + 0.569 \cdot \beta + 0.292 \cdot \alpha \cdot \beta + 0.478 \cdot \sin(0.939 \cdot \alpha - \beta) + 0.122 \cdot \sin^2(0.939 \cdot \alpha - \beta) - 1.284 - 0.12 \cdot \alpha^2 - 0.162 \cdot \beta^2 \quad (2)$$

Where $\alpha = \log_{10}(R)$; $\beta = -\log_{10}(\varepsilon/D)$.

It is revealed that the input parameters the Reynolds number, R and the relative roughness ε/D need to be normalized because their raw form where $R > 1000$ and $\varepsilon/D \ll 1$ can cause a problem for the genetic programming tool to recognize the pattern and to estimate flow friction f accurately and we use $\alpha = \log_{10}(R)$ and $\beta = -\log_{10}(\varepsilon/D)$. The practical domain of the Reynolds number, R is between around 4000 to 10^8 which means it is expressed in relatively large numbers, while the relative roughness, ε/D is up to 0.05 which means that it is expressed in relatively small numbers. As explained, the different scale is a problem for the artificial intelligence to recognize pattern (Özger and Yıldırım 2009, Brkić and Čojbašić 2016) where we discovered that the normalization in the form $\alpha = \log_{10}(R)$ and $\beta = -\log_{10}(\varepsilon/D)$ can overwhelm the problem. This means that Eq. (2) practically contain only two logarithmic expressions used only for normalization $\{\alpha = \log_{10}(R); \beta = -\log_{10}(\varepsilon/D)\} \rightarrow f$, and not a single non-integer power expression. In that way the estimated relative error of f_0 calculated through Eq. (2) compared with the accurate friction factor f ; $(|f - f_0|/f) \cdot 100\%$ is less than 2%. On the other hand the approximation presented with Eq. (2) contains sinus trigonometric function which can introduce higher computational cost.

Introducing one additional logarithmic form, i.e. one more fixed-point iterative step; Eq. (3); Brkić (2017a), the error in this case can be reduced ten times, and it is up to 0.2%. The strategy with acceleration using one additional internal iterative step; two in total including initial starting iteration (Chen 1979, Shorle et al. 1980, Brkić 2011b), is widely used.

$$\frac{1}{\sqrt{f_{i+1}}} \approx -2 \cdot \log_{10} \left(\frac{2.51}{R} \cdot \frac{1}{\sqrt{f_i}} + \frac{\varepsilon}{3.71 \cdot D} \right) \quad (3)$$

On the other hand, using the raw parameters without normalization; $\{R, \varepsilon/D\} \rightarrow f$ and with acceleration through Eq. (3) the maximal error of no more than 1.55% is introduced using only one logarithmic form; Eq. (4):

$$\frac{1}{\sqrt{f_1}} \approx -2 \cdot \log_{10} \left(\frac{2.51}{R} \cdot \left(5.05 - 30.73 \cdot \frac{\varepsilon}{D} + \frac{3.4 \cdot R + \frac{R^2}{469647.7}}{46137.9 + R + \frac{R^2}{3250657.6} + \frac{\varepsilon}{515.25} \cdot \frac{R^2}{D}} \right) + \frac{\varepsilon}{3.71 \cdot D} \right) \quad (4)$$

The accelerative procedure through Eq. (3) is very fast where for Eq. (4) the relative error decreases as follow: $f_0 \rightarrow 42.7\%$, $f_1 \rightarrow 1.55\%$, $f_2 \rightarrow 0.22\%$, $f_3 \rightarrow 0.036\%$, etc. The expression for f_0 is polynomial and hence very simple, but with the relative error that can reach up to 42.7% not sufficiently accurate. On the other hand, with two logarithmic expressions, the relative error f_2 introduced with Eq. (4) is about 0.22% which is almost the same as for f_1 introduced with Eq. (2) that requires three logarithmic expressions in total (two for normalization and one for acceleration).

Three-point methods

Approximations with virtually three iterative steps are also available (Zigrang and Sylvester 1982, Serghides 1984). Using only function evaluations and one evaluation of the first derivative (Sharma and Arora 2016), the Colebrook equation can be solved practically with the neglected error within one iteration step; Eq. (5), (Džunić et al. 2011). Through the three-point iterative procedure the friction factor is evaluated in points x_0 , y_0 and z_0 where the optimal starting point x_0 for the whole domain of the

74 Colebrook equation is $x_0=7.273124147$ which is chosen after numerous tests where $x_0 = \frac{1}{\sqrt{f_0}}$. The final
 75 solution is at the point x_1 ; Eq. (5) where $f_1 = \frac{1}{\sqrt{x_1}}$; (Praks and Brkić 2018bc):

$$\left. \begin{aligned}
 & \frac{1}{\sqrt{f_0}} = x_0 = 7.273124147 \\
 & F(x_0) = x_0 + 2 \cdot \log_{10} \left(\frac{2.51 \cdot x_0}{R} + \frac{\varepsilon}{3.71 \cdot D} \right) \\
 & F'(x_0) = \frac{186242}{\ln(10) \cdot (93121 \cdot x_0 + 10000 \cdot \frac{\varepsilon}{D} R)} + 1 = \frac{251}{50 \cdot R \cdot \ln(10) \cdot (\frac{100 \cdot \varepsilon}{371 D} + \frac{2.51 \cdot x_0}{R})} + 1 \\
 & y_0 = x_0 - \frac{F(x_0)}{F'(x_0)} \\
 & F(y_0) = y_0 + 2 \cdot \log_{10} \left(\frac{2.51 \cdot y_0}{R} + \frac{\varepsilon}{3.71 \cdot D} \right) \\
 & z_0 = y_0 - \frac{F(x_0)}{F(x_0) - 2 \cdot F(y_0)} \cdot \frac{F(y_0)}{F'(x_0)} \\
 & F(z_0) = z_0 + 2 \cdot \log_{10} \left(\frac{2.51 \cdot z_0}{R} + \frac{\varepsilon}{3.71 \cdot D} \right) \\
 & x_1 = z_0 - \frac{F(z_0)}{F'(x_0) \cdot \left[1 - 2 \cdot \frac{F(y_0)}{F(x_0)} \cdot \left(\frac{F(y_0)}{F(x_0)} \right)^2 \right] \cdot \left[1 - \frac{F(z_0)}{F(y_0)} \right] \cdot \left[1 - 2 \cdot \frac{F(z_0)}{F(x_0)} \right]} \\
 & x_1 = \frac{1}{\sqrt{f_1}} \rightarrow f
 \end{aligned} \right\} \quad (5)$$

77
 78 In Eq. (5) is used the first derivative $F'(x_0)$ of the Colebrook function in point x_0 in respect to parameter x ,
 79 where the Colebrook equation is expressed in the suitable form to start the Newton-Raphson iterative
 80 procedure; Eq. (6):

$$81 \quad F = \frac{1}{\sqrt{f}} + 2 \cdot \log_{10} \left(\frac{2.51}{R} \cdot \frac{1}{\sqrt{f}} + \frac{\varepsilon}{3.71 \cdot D} \right) = 0 \quad (6)$$

82
 83 The corresponding VPA (Variable precision arithmetic) approximations of the first derivative $F'(x)$ with
 84 16 digits precision expression is $=2.180158299154324/(R \cdot (0.2695417789757412 \cdot \varepsilon/D + (2.51 \cdot x)/R)) + 1.0 =$
 85 $80883.87289862543/(93121.0 \cdot x + 10000.0 \cdot R \cdot \varepsilon/D) + 1.0$ where $x = \frac{1}{\sqrt{f}}$

86
 87 **Optimization problem**

88 As noted in the discussed paper, the first derivative of the Colebrook equation expressed in the form
 89 suitable for the Newton-Raphson procedure in respect to the Reynolds number, R is used for the

optimization problem in pipe network simulations (Brkić 2016). For the purpose of this discussion we generated in MATLAB the appropriate first derivative $F'(R)$; Eq. (7):

$$F'(R) = -\frac{251 \cdot \frac{1}{\sqrt{f}}}{50 \cdot R^2 \cdot \ln(10) \cdot \left(\frac{100}{371} \frac{\varepsilon}{D} + \frac{2.51}{R} \frac{1}{\sqrt{f}} \right)} = -\frac{186242 \cdot \frac{1}{\sqrt{f}}}{R \cdot \ln(10) \cdot \left(93121 \cdot \frac{1}{\sqrt{f}} + 10000 \cdot R \cdot \frac{\varepsilon}{D} \right)} \quad (7)$$

The corresponding VPA (Variable precision arithmetic) approximations of the first derivative $F'(R)$ with 16 digits precision is $-(186242.0 \cdot x)/(23025.85092994046 \cdot R^2 \cdot \varepsilon/D + 214419.0264446985 \cdot x \cdot R) = -(80883.87289862543 \cdot x)/(R \cdot (93121.0 \cdot x + 10000.0 \cdot R \cdot \varepsilon/D))$ where $x = \frac{1}{\sqrt{f}}$

Padé polynomials

In the discussed paper, the improved versions of the approximations proposed by Sonnad and Goudar (2006), Mikata and Walczak (2016), Brkić (2017b), Vatankhah and Kouchakzadeh (2008, 2009), and Vatankhah (2014) are shown. In addition, the second logarithmic form in Eq. (12) of the discussed paper can be simplified using Padé approximation (Baker and Graves-Morris 1996); $\ln(1-a \cdot \delta/d) = \ln(1-\theta) \approx p/q$ where p and q are defined by Eq. (8):

$$\left. \begin{aligned} p &\approx \theta \cdot (-0.18333 \cdot \theta^2 + \theta - 1) \\ q &\approx -0.05 \cdot \theta^3 + 0.6 \cdot \theta^2 - 1.5 \cdot \theta + 1 \end{aligned} \right\} \quad (8)$$

For the domain of applicability of the Colebrook equation that is $0 < \varepsilon/D < 0.1$ and $4000 < R < 10^8$; $\theta = a \cdot \delta/d$ is always between 0 and 0.22; $0 < \theta < 0.22$, the relative percentage error of the Padé approximation p/q compared with the accurate $\ln(1-a \cdot \delta/d)$ is between $3.5 \cdot 10^{-8}\%$ and $2 \cdot 10^{-5}\%$. In this case the Padé approximation is very accurate, and also computationally cheap compared with logarithmic function: it is a division of two polynomials of degree of 3; we can call Padé approximation (3/3) because of two polynomials of degree of 3 used (Praks and Brkić 2018d).

Further to start Newton-Raphson procedure $\delta_{i+1} = \delta_i - \zeta(\delta_i)/\zeta'(\delta_i)$ starting from $i=0$, in order to evaluate δ , Eq. (12) of the discussed paper need to be rearranged where $\zeta(\delta)=0$, and where ζ is functional symbol; Eq. (9):

$$\zeta(\delta) = \ln(d) + \ln\left(1 - \frac{a \cdot \delta}{d}\right) - \delta \approx \ln(d) + \frac{\theta \cdot (-0.18333 \cdot \theta^2 + \theta - 1)}{-0.05 \cdot \theta^3 + 0.6 \cdot \theta^2 - 1.5 \cdot \theta + 1} - \delta = 0 \quad (9)$$

δ is the unknown parameter to be solved, a is constant $a=2/\ln(10)=0.8686$ and d is parameter $d=c/b \cdot a \cdot \ln(b)$; where $b=2.51/R$ and $c=(\varepsilon/D)/3.71$.

Also, the Newton-Raphson procedure requires the first derivative $\zeta'(\delta)=-a/(d-a \cdot \delta)-1$, which is computationally cheap. Because it is equally cheap but slightly more accurate, we use the first derivative of $\zeta(\delta)=\ln(d)+\ln(1-a \cdot \delta/d)-\delta=0$ and not the derivative of its Padé version. Knowing that δ ranges between 1.61 and 13.91, the starting point δ_0 for the Newton-Raphson procedure should be selected from that domain; $\delta_{i+1}=\delta_i-\zeta(\delta_i)/\zeta'(\delta_i)$ starting from $i=0$. The Newton-Raphson is faster than the simple fixed-point iterative procedure (Brkić 2017a), so hopefully Eq. (9) should be evaluated only few times; where the stopping criteria is $\delta_{i+1}-\delta_i \approx 0$.

Disclaimer: The views expressed are those of the authors and may not in any circumstances be regarded as stating an official position of the Alfatec or of the IT4Innovations, VŠB - Technical University Ostrava. Both authors contributed equally to this discussion.

Acknowledgments:

This work has been partially funded by the Technology Agency of the Czech Republic, partially by the National Centre for Energy [TN01000007] and partially by the project “Energy System for Grids” [TK02030039]. Work of D.B. has been also supported of the Ministry of Education, Youth, and Sports of the Czech Republic through the National Programme of Sustainability (NPS II) project “IT4Innovations excellence in science” [LQ1602] and by the Ministry of Education, Science, and Technological Development of the Republic of Serbia through the project “Development of new information and communication technologies, based on advanced mathematical methods, with applications in medicine, telecommunications, power systems, protection of national heritage and education” [iii44006].

139

140 **Notation**

141 The following symbols are used in this discussion:

142 a = constant, $a=2/\ln(10)=0.8686$;

143 b = parameter related to Reynolds number (dimensionless);

144 c = parameter related to ε and D (dimensionless);

145 D = inner diameter of pipe (length; the same unit as for D);

146 d = parameter related to a , b and c (dimensionless);

147 f = Darcy friction factor implicitly related to R , ε and D (dimensionless);

148 R = Reynolds number (dimensionless);

149 p and q = Padé polynomials related to θ ;

150 x = parameter related to friction factor f (dimensionless);

151 y = parameter related to x (dimensionless);

152 z = parameter related to y (dimensionless);

153 α = parameter related to the Reynolds number R (dimensionless);

154 β = parameter related to ε and D (dimensionless);

155 δ = unknown parameter implicitly related to a and d ;

156 ε = average height of protrusion of inner pipe surface (length; the same unit as for D);

157 θ = parameter related to a , δ and d

158 *functional symbols:*

159 F – functional symbol related to the Colebrook equation

160 $\ln$ - Napierian natural logarithm

161 $\log$ – Briggsian logarithm

162 $\sin$ – sine trigonometric function

163 $'$ – represents first derivative of function

164 ζ - functional symbol related to parameter δ

165 *Indexes:*

166 i – counter

167 0 – refers to first iteration

168 1 – refers to second iteration

169

170 **References:**

171 Baker, G. A., and Graves-Morris, P. (1996). Padé approximants. Encyclopedia of Mathematics and its
172 Applications, Cambridge University Press. <https://doi.org/10.1017/CBO9780511530074>

173 Brkić, D. (2011a). “Review of explicit approximations to the Colebrook relation for flow friction.”

174 Journal of Petroleum Science and Engineering, 77(1), 34-48. <https://doi.org/10.1016/j.petrol.2011.02.006>

175 Brkić, D. (2011b). “New explicit correlations for turbulent flow friction factor.” Nuclear Engineering and

176 Design, 241(9), 4055-4059. <https://doi.org/10.1016/j.nucengdes.2011.07.042>

177 Brkić, D. (2012). Determining friction factors in turbulent pipe flow. Chemical Engineering (New York),

178 119 (3), 34-39. Available from: [http://www.chemengonline.com/determining-friction-factors-in-](http://www.chemengonline.com/determining-friction-factors-in-turbulent-pipe-flow/?printmode=1)

179 [turbulent-pipe-flow/?printmode=1](http://www.chemengonline.com/determining-friction-factors-in-turbulent-pipe-flow/?printmode=1)

180 Brkić, D. (2016). “Spreadsheet-based pipe networks analysis for teaching and learning purpose.”

181 Spreadsheets in Education (eJSiE), 9(2), 4646. Available at: <https://sie.scholasticahq.com/article/4646.pdf>

182 Brkić, D. (2017a). “Solution of the implicit Colebrook equation for flow friction using Excel.”

183 Spreadsheets in Education (eJSiE), 10(2). 4663. Available at:

184 <https://sie.scholasticahq.com/article/4663.pdf>

185 Brkić, D. (2017b). “Discussion of ‘Exact analytical solutions of the Colebrook-White equation’ by Yozo

186 Mikata and Walter S. Walczak.” Journal of Hydraulic Engineering, 143(9), 07017007.

187 [https://doi.org/10.1061/\(ASCE\)HY.1943-7900.0001341](https://doi.org/10.1061/(ASCE)HY.1943-7900.0001341)

188 Brkić, D., and Čojbašić, Ž. (2016). “Intelligent flow friction estimation.” Computational Intelligence and

189 Neuroscience, Article ID 5242596. <http://dx.doi.org/10.1155/2016/5242596>

190 Brkić, D., and Čojbašić, Ž. (2017). "Evolutionary optimization of Colebrook's turbulent flow friction
191 approximations." *Fluids*, 2(2), 15. <https://doi.org/10.3390/fluids2020015>

192 Brkić, D., and Praks, P. (2019). "Accurate and efficient explicit approximations of the Colebrook flow
193 friction equation based on the Wright ω -function." *Mathematics*, 7(1), 34.
194 <https://doi.org/10.3390/math7010034>

195 Chen, N. H. (1979). "An explicit equation for friction factor in pipe." *Industrial & Engineering Chemistry*
196 *Fundamentals*, 18(3), 296-297. <https://doi.org/10.1021/i160071a019>

197 Clamond, D. (2009). "Efficient resolution of the Colebrook equation." *Industrial & Engineering*
198 *Chemistry Research*, 48(7), 3665-3671. <https://doi.org/10.1021/ie801626g>

199 Čojbašić, Ž., and Brkić, D. (2013). "Very accurate explicit approximations for calculation of the
200 Colebrook friction factor." *International Journal of Mechanical Sciences*, 67, 10-13.
201 <https://doi.org/10.1016/j.ijmecsci.2012.11.017>

202 Colebrook, C. and White, C. (1937). "Experiments with fluid friction in roughened pipes." *Proceedings of*
203 *the Royal Society of London. Series A, Mathematical and Physical Sciences* 161(906), 367-381.
204 <https://dx.doi.org/10.1098/rspa.1937.0150>

205 Colebrook, C. F. (1939). "Turbulent flow in pipes with particular reference to the transition region
206 between the smooth and rough pipe laws." *Journal of the Institution of Civil Engineers (London)* 11(4),
207 133-156. <https://dx.doi.org/10.1680/ijoti.1939.13150>

208 Dubčáková, R. (2011). "Eureqa: software review." *Genetic Programming and Evolvable Machines*, 12(2),
209 173-178. <https://doi.org/10.1007/s10710-010-9124-z>

210 Džunić, J., Petković, M. S., and Petković, L. D. (2011). "A family of optimal three-point methods for
211 solving nonlinear equations using two parametric functions." *Applied Mathematics and Computation*,
212 217(19), 7612-7619. <https://doi.org/10.1016/j.amc.2011.02.055>

213 Eureqa [computer software]. Nutonian, Inc., Boston, MA.

214 Giustolisi, O., Berardi, L., and Walski, T. M. (2011). "Some explicit formulations of Colebrook–White
 215 friction factor considering accuracy vs. computational speed." *Journal of Hydroinformatics*, 13(3), 401-
 216 418. <https://doi.org/10.2166/hydro.2010.098>
 217 Gregory, G. A., and Fogarasi, M. (1985). "Alternate to standard friction factor equation." *Oil and Gas*
 218 *Journal*, 83(13). 125-127.
 219 MATLAB [computer software]. MathWorks, Inc., Natick, MA.
 220 Mikata, Y., and Walczak, W. S. (2016). "Exact analytical solutions of the Colebrook-White equation."
 221 *Journal of Hydraulic Engineering*, 142(2), 04015050. [https://doi.org/10.1061/\(ASCE\)HY.1943-](https://doi.org/10.1061/(ASCE)HY.1943-7900.0001074)
 222 [7900.0001074](https://doi.org/10.1061/(ASCE)HY.1943-7900.0001074)
 223 Özger, M., and Yıldırım, G. (2009). "Determining turbulent flow friction coefficient using adaptive
 224 neuro-fuzzy computing technique." *Advances in Engineering Software*, 40(4), 281-287.
 225 <https://doi.org/10.1016/j.advengsoft.2008.04.006>
 226 Praks, P., and Brkić, D. (2018a). "Symbolic regression-based genetic approximations of the Colebrook
 227 equation for flow friction." *Water*, 10(9), 1175. <https://doi.org/10.3390/w10091175>
 228 Praks, P., and Brkić, D. (2018b). "Advanced iterative procedures for solving the implicit Colebrook
 229 equation for fluid flow friction." *Advances in Civil Engineering*, 2018, 5451034.
 230 <https://doi.org/10.1155/2018/5451034>
 231 Praks, P., and Brkić, D. (2018c). "Choosing the optimal multi-point iterative method for the Colebrook
 232 flow friction equation." *Processes*, 6(8), 130. <https://doi.org/10.3390/pr6080130>
 233 Praks, P., and Brkić, D. (2018d). "One-log call iterative solution of the Colebrook equation for flow
 234 friction based on Padé polynomials." *Energies*, 11(7), 1825. <https://doi.org/10.3390/en11071825>
 235 Schorle, B. J., Churchill, S. W., and Shacham, M. (1980). "Comments on: 'An explicit equation for
 236 friction factor in pipe'." *Industrial & Engineering Chemistry Fundamentals*, 19(2), 228-230.
 237 <https://doi.org/10.1021/i160074a019>
 238 Schmidt, M. and Lipson, H. (2009). "Distilling free-form natural laws from experimental data." *Science*
 239 324(5923), 81-85. <https://doi.org/10.1126/science.1165893>

240 Serghides, T.K. (1984). "Estimate friction factor accurately." *Chemical Engineering* (New York), 91(5),
 241 63-64.

242 Sharma, J. R., and Arora, H. (2016). "A new family of optimal eighth order methods with dynamics for
 243 nonlinear equations." *Applied Mathematics and Computation*, 273, 924-933.
 244 <https://doi.org/10.1016/j.amc.2015.10.049>

245 Sonnad, J. R., and Goudar, C. T. (2006). "Turbulent flow friction factor calculation using a
 246 mathematically exact alternative to the Colebrook–White equation." *Journal of Hydraulic Engineering*,
 247 132(8), 863-867. [https://doi.org/10.1061/\(ASCE\)0733-9429\(2006\)132:8\(863\)](https://doi.org/10.1061/(ASCE)0733-9429(2006)132:8(863))

248 Vatankhah, A. R. (2014). "Comment on 'Gene expression programming analysis of implicit Colebrook–
 249 White equation in turbulent flow friction factor calculation'." *Journal of Petroleum Science and*
 250 *Engineering*, 124, 402-405. <https://doi.org/10.1016/j.petrol.2013.12.001>

251 Vatankhah, A. R., and Kouchakzadeh, S. (2008). "Discussion of 'Turbulent flow friction factor
 252 calculation using a mathematically exact alternative to the Colebrook–White equation' by Jagadeesh R.
 253 Sonnad and Chetan T. Goudar." *Journal of Hydraulic Engineering*, 134(8), 1187-1187.
 254 [https://doi.org/10.1061/\(ASCE\)0733-9429\(2008\)134:8\(1187\)](https://doi.org/10.1061/(ASCE)0733-9429(2008)134:8(1187))

255 Vatankhah, A. R., and Kouchakzadeh, S. (2009). "Discussion: Exact equations for pipe-flow problems."
 256 *Journal of Hydraulic Research* 47(4), 537-538. <https://doi.org/10.1080/00221686.2009.9522031>

257 Winning, H. K., and Coole, T. (2013). "Explicit friction factor accuracy and computational efficiency for
 258 turbulent flow in pipes." *Flow, Turbulence and Combustion*, 90(1), 1-27. [https://doi.org/10.1007/s10494-](https://doi.org/10.1007/s10494-012-9419-7)
 259 [012-9419-7](https://doi.org/10.1007/s10494-012-9419-7)

260 Zigrang, D. J. and Sylvester, N. D. (1982). "Explicit approximations to the solution of Colebrook's
 261 friction factor equation." *AIChE Journal*, 28(3), 514-515. <https://dx.doi.org/10.1002/aic.690280323>