Optimal parameter estimation in a landslide motion model using the adjoint method

Mohit Mishra, Gildas Besancon, Guillaume Chambon, Laurent Baillet

► To cite this version:

Mohit Mishra, Gildas Besancon, Guillaume Chambon, Laurent Baillet. Optimal parameter estimation in a landslide motion model using the adjoint method. ECC 2020 - 19th European Control Conference, May 2020, St Petersburg, Russia. 10.23919/ECC51009.2020.9143819 . hal-02862346

HAL Id: hal-02862346

<https://hal.science/hal-02862346>

Submitted on 27 Jul 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Optimal parameter estimation in a landslide motion model using the adjoint method

Mohit Mishra¹, Gildas Besançon¹, Guillaume Chambon², and Laurent Baillet³

Abstract—This work proposes an optimal approach for parameter estimation in a landslide motion, based on the so-called adjoint method. The system is described by an extended sliding-consolidation model composed of an ordinary differential equation and 1D parabolic partial differential equation that represents landslide motion and pore pressure evolution respectively. The key feature of this model is pore pressure feedback, which regulates landslide motion and leads to coupling between both differential equations. Parameters to be estimated include the friction and dilatancy angle of the material. The objective functional for the optimal estimation is composed of: i) a cost function defined as the least square error between measurements and related simulated values, and ii) a product of Lagrange variables and system dynamics. A variational approach is applied to get the gradients of the cost functional with respect to parameters to be estimated and adjoint model. The cost functional is optimized, employing the steepest descent method to estimate parameters. Finally, the presented optimal estimation method is validated on a simulated test case.

I. INTRODUCTION

Rapid urbanization [1] and climate change [2] have increased the frequency of occurrence of landslides. Which, in return, can have severe socio-economic consequences such as substantial cost in life losses, infrastructure, economy, and ecosystem of the region. Traditional strategies in landslide risk management are mostly oriented at avoiding building infrastructure at an exposed zone based on landslide hazard maps or stabilizing unstable slopes (landslide geometry corrections, water draining) or installing protecting structures [3]. However, infrastructure is still being developed either on or near massive landslides due to a lack of risk awareness. In such cases, slope stabilization is unaffordable, while moving the population to stable areas can pose considerable societal problems. Under these circumstances, implementation of an Early Warning System (EWS) can help to take timely actions to reduce life and economic losses in advance of hazardous events [4]. According to the United Nation's International Strategy for Disaster Reduction (ISDR) checklist [5], one of the principal element of EWS is a monitoring and warning service. An essential function of this service is to assess the

current status of the environment and establish the trends in environmental parameters to generate accurate warnings.

Some of the landslide EWS makes use of a rainfall threshold approach to examine the relationship between the movement and the triggering precipitation. The threshold is defined as a critical value, above which the probability of landslide occurrence is high. In most cases, the thresholds are defined on statistical and experience bases, neglecting physical criteria [6]. Another widely used and dependable approach of landslide forecasting considers the use of monitoring displacement (or velocity), pore pressure, and rain for continuously active landslides. Such approaches generate warnings based on a change in slope displacement rates over time, e.g., inverse velocity criteria [7].

As a consequence, many developments are proposed in the literature for slope displacement prediction models. The sliding-consolidation model [8] proposes a single event behavior of flow slides in loose, cohesionless materials. This model was later revisited incorporating viscous force [3], [9], [10] and termed as a viscoplastic sliding-consolidation model. The extended sliding-consolidation model [11] demonstrates diverse rates of landslide due to mechanical feedback. Apart from the models mentioned above, many more hydrological, hydrogeological, meteorological, and geotechnical models [12] are investigated. These dynamical models are sensitive to the parameters of the system. For known geometry and material properties of the landslide, equations governing the dynamics of the landslide can be solved to predict the displacement pattern knowing rainfall input. However, in fact, not all the parameter values are known.

This paper presents optimal parameter estimation in an extended sliding-consolidation model (coupled ODE-PDE system) of a landslide using the adjoint method. The adjoint method scheme demonstrated its effectiveness in many studies and applications, for instance, air traffic flow management [13], space shuttle reentry problem [14], state and parameter estimation in switched 1D hyperbolic PDEs [15], traffic flow [16], and overland flow [17]. Some authors [18], [19], [20], [21] studied a similar approach to estimate the Manning roughness coefficient or to stabilize and control the water level in an open channel flow.

The contents of the paper are as follows: Section 2 defines a landslide model depicting landslide behavior and the problem statement, while Section 3 presents the proposed method to solve it. In Section 4, the simulation results demonstrate the effectiveness of the solution. Finally, Section 5 provides a conclusion and discusses future directions of the work.

*This work is supported by the French National Research Agency in the framework of the Investissements d'Avenir program (ANR-15-IDEX-02)

¹ M. Mishra and G. Besançon are with the Univ. Grenoble Alpes, CNRS, Grenoble INP - Institute of Engineering, Gipsa-Lab, 38000 Grenoble, France [mohit.mishra, gildas.besancon]@gipsa-lab.grenoble-inp.fr

² G. Chambon is with the Univ. Grenoble Alpes, IRSTEA, UR ETGR, Grenoble, France guillaume.chambon@irstea.fr

³ L. Baillet is with the Univ. Grenoble Alpes, CNRS, ISTerre, Grenoble, France laurent.baillet@univ-grenoble-alpes.fr

II. PROBLEM FORMULATION

A. Extended sliding-consolidation model

In the extended sliding-consolidation model of a landslide [11], a slide block is assumed to be placed on an inclined surface, as shown in Fig. 1. The model proposes a mechanism of opposition to slide block downslope movement by basal Coulomb friction and regulation through basal pore fluid pressure feedback. The model assumes two components of total basal pore pressure: i) imposed pore pressure p_i due to rain infiltration and ii) development of excess pore pressure p_e in response to the contraction or dilation of the basal shear zone. The motion of the slide block and excess pore pressure evolution are described by Eq. (1) and (2) respectively.

Momentum equation

$$\begin{aligned} \frac{d^2 u_x}{dt^2} &= \frac{dv}{dt} = g \cos \psi [\sin(\theta - \psi) - \cos(\theta - \psi) \tan \phi] \\ &+ \frac{\cos^2 \psi \tan \phi}{\rho Z} [p_i(0, t) + p_e(0, t)] \quad \text{i.e.} \quad (1) \\ \dot{v} &= f(\phi, \psi, p_e(0, t), p_i(0, t)), \quad v(0) = v_0 \end{aligned}$$

Excess pore pressure diffusion equation

$$\begin{aligned} \frac{\partial p_e(z, t)}{\partial t} &= D \frac{\partial^2 p_e(z, t)}{\partial z^2} \\ \frac{\partial p_e(0, t)}{\partial z} &= \frac{\rho_w g \psi}{K} v, \quad (2) \\ p_e(Z, t) &= 0, \quad p_e(z, 0) = p_{e0} \end{aligned}$$

where $u_x(t)$ and $v(t)$ denote the displacement and velocity of the slide block respectively, $p_i(0, t)$ is the imposed pore pressure at the slide block base, $p_e(z, t)$ is the excess pore pressure distribution, $(z, t) \in [0, Z] \times [0, T]$ with Z as a spatial domain length (slide block thickness), and T is the length of time horizon. A coordinate z translates with the base of the slide block such that with dilation or contraction of shear zone the base of the slide block is always located at $z = 0$. ϕ is the friction angle characterizing the mechanical strength of the material, ψ is the dilatancy angle representing volume change of the material when they are subjected to deformation, ρ is the soil density, ρ_w is the pore water density, D is the diffusion coefficient ($D > 0$), K is the hydraulic conductivity, g is the acceleration due to gravity and θ is the sliding angle. In addition, v_0 and p_{e0} are initial values (assumed to be known) of the v and p_e respectively. Finally, f is the function characterizing the right hand side of Eq. (1), depends on ϕ , ψ , $p_e(0, t)$, and $p_i(0, t)$.

Fig. 1. The coordinate systems, geometric variables and material property of the slide block

B. Optimal estimation problem

On the basis of the formed model, the main goal in this paper is to estimate friction and dilatancy angle (ϕ & ψ) of the material in a landslide from a measured velocity $v_{mea}(t)$ and known imposed pore pressure evolution $p_i(0, t)$. Technically, we are interested in minimizing the cost function $J(\phi, \psi)$ defined as the least square error between velocity measurement and simulated velocity profile in (3).

$$\begin{aligned} J(\phi, \psi) &= \frac{\epsilon_1}{2} \|\phi - \phi_G\|^2 + \frac{\epsilon_2}{2} \|\psi - \psi_G\|^2 \\ &+ \frac{\epsilon_3}{2} \int_0^T [v(t) - v_{mea}(t)]^2 dt \quad (3) \end{aligned}$$

where ϵ_1 , ϵ_2 and ϵ_3 are weighting factors to calibrate the estimated and guessed parameter values, and T is the simulation time. The first guessed values of parameters ϕ_G and ψ_G are introduced to improve the convergence of the optimization problem, which are chosen in a reasonable range around the expected real ones.

For cost function J in (3), continuous velocity measurement is required, which is sometimes not feasible. Instead, in many cases velocity measurements are only available at particular sampling times (e.g., on an hourly basis) i.e., the observation process is realized at some discrete points (t_k) on a time domain. In such a scenario, the cost function is formulated as

$$\begin{aligned} J(\phi, \psi) &= \frac{\epsilon_1}{2} \|\phi - \phi_G\|^2 + \frac{\epsilon_2}{2} \|\psi - \psi_G\|^2 \\ &+ \frac{\epsilon_3}{2} \sum_{k=1}^N \left(\int_0^T \delta_A(t - t_k) v(t) dt - v_{mea}(t_k) \right)^2 \quad (4) \end{aligned}$$

where N is the the number of observation values of $v_{mea}(t_k)$ and $\delta_A(t-t_k)$ is an approximate Dirac-Delta function defined as a Gaussian function with a very small variance σ^2 ,

$$\delta_A(t-t_k) = e^{-\frac{(t-t_k)^2}{\sigma^2}}.$$

This Gaussian approximation guarantees the smoothness of the observation function. In this paper, we thus consider the minimization of the cost function (4).

III. SOLUTION METHOD

A. Cost functional

From the defined problem statement, the optimal values of ϕ and ψ must minimize the cost function (4) subject to the dynamics (1)-(2) as constraints. To solve this constrained optimization problem, let us consider the Lagrange multipliers $\lambda(t)$ and $\Gamma(z,t)$ combining both system equations and cost function into a new cost functional L

$$L(v, p_e, \phi, \psi) = J + \int_0^T \lambda(t) [\dot{v} - f(\psi, \phi, p_e(0,t), p_i(0,t))] dt + \int_0^T \int_0^Z \Gamma(z,t) \left(\frac{\partial p_e}{\partial t} - D \frac{\partial^2 p_e}{\partial z^2} \right) dz dt. \quad (5)$$

Using integration by parts, the cost functional can be redefined as

$$\begin{aligned} L(v, p_e, \phi, \psi) = & \frac{\varepsilon_1}{2} \|\phi - \phi_G\|^2 + \frac{\varepsilon_2}{2} \|\psi - \psi_G\|^2 \\ & + \frac{\varepsilon_3}{2} \sum_{k=1}^N \left(\int_0^T \delta_A(t-t_k) v(t) dt - v_{mea}(t_k) \right)^2 \\ & + [\lambda v]_0^T - \int_0^T v \dot{\lambda} dt - \int_0^T \lambda(t) f(\phi, \psi, p_e(0,t), p_i(0,t)) dt \\ & + \int_0^Z [\Gamma p_e]_0^T dz - \int_0^T \int_0^Z p_e \left(\frac{\partial \Gamma}{\partial t} + D \frac{\partial^2 \Gamma}{\partial z^2} \right) dz dt \\ & + D \int_0^T \left[\frac{\partial \Gamma}{\partial z} p_e \right]_0^Z dt - D \int_0^T \Gamma(Z,t) \frac{\partial p_e(Z,t)}{\partial z} dt \\ & + \frac{D \rho_w g \psi}{K} \int_0^T \Gamma(0,t) v(t) dt \end{aligned} \quad (6)$$

B. Adjoint-based approach

Based on the adjoint approach, the first derivatives of L with respect to v and p_e are set to zero, the gradients of the cost functional with respect to ϕ and ψ are also computed.

- Variation of L w.r.t. v :

$$\begin{aligned} L_v = \varepsilon_3 \sum_{k=1}^N & \left(\int_0^T \delta_A(t-t_k) v(t) dt - v_{mea}(t_k) \right) \cdot \int_0^T \delta_A(t-t_k) dt \delta v \\ & - \int_0^T \dot{\lambda} dt \delta v + \lambda(T) \delta v(T) - \lambda(0) \delta v(0) \\ & + \frac{D \rho_w g \psi}{K} \int_0^T \Gamma(0,t) dt \delta v \end{aligned}$$

(Here, $\delta v(0) = 0$ since the initial value v_0 is fixed)

$$L_v = 0 \Leftrightarrow \begin{cases} \dot{\lambda} = \varepsilon_3 \sum_{k=1}^N \delta_A(t-t_k) \left[\int_0^T \delta_A(t-t_k) v(t) dt - v_{mea}(t_k) \right] \\ \quad + \frac{D \rho_w g \psi}{K} \Gamma(0,t) \\ \lambda(T) = 0 \end{cases} \quad (7)$$

- Variation of L w.r.t. p_e :

$$\begin{aligned} L_{p_e} = & - \int_0^T \lambda(t) f_{p_e(0,t)}(\phi, \psi, p_e(0,t), p_i(0,t)) dt \delta p_e(0,t) \\ & + \int_0^Z \Gamma(z,T) dz \delta p_e(z,T) - \int_0^Z \Gamma(z,0) dz \delta p_e(z,0) \\ & + D \int_0^T \frac{\partial \Gamma(Z,t)}{\partial z} dt \delta p_e(Z,t) - D \int_0^T \frac{\partial \Gamma(0,t)}{\partial z} dt \delta p_e(0,t) \\ & - \int_0^T \int_0^Z \left(\frac{\partial \Gamma}{\partial t} + D \frac{\partial^2 \Gamma}{\partial z^2} \right) dz dt \delta p_e \\ & - D \int_0^T \Gamma(Z,t) dt \delta \frac{\partial p_e(Z,t)}{\partial z} \end{aligned}$$

($\delta p_e(z,0) = \delta p_e(Z,t) = 0$ because $p_e(z,0)$ and $p_e(Z,t)$ are fixed)

$$L_{p_e} = 0 \Leftrightarrow \begin{cases} \frac{\partial \Gamma}{\partial t} = -D \frac{\partial^2 \Gamma}{\partial z^2} \\ \frac{\partial \Gamma(0,t)}{\partial z} = -\frac{1}{D} \lambda(t) f_{p_e(0,t)} \\ \Gamma(Z,t) = 0 \\ \Gamma(z,T) = 0 \end{cases} \quad (8)$$

Equations (7) and (8) are the adjoint system equations where $f_{p_e(0,t)}$ is the differentiation of $f(\phi, \psi, p_e(0,t), p_i(0,t))$ w.r.t. $p_e(0,t)$.

- Gradient of L w.r.t. ϕ :

$$L_\phi = \frac{\partial L}{\partial \phi} = \varepsilon_1 (\phi - \phi_G) - \int_0^T \lambda(t) f_\phi(t) dt \quad (9)$$

where $f_\phi(t)$ is the differentiation of $f(\phi, \psi, p_e(0,t), p_i(0,t))$ w.r.t. ϕ .

- Gradient of L w.r.t. ψ :

$$\begin{aligned} L_\psi = \frac{\partial L}{\partial \psi} = & \varepsilon_2 (\psi - \psi_G) - \int_0^T \lambda(t) f_\psi(t) dt \\ & + \frac{D \rho_w g \psi}{K} \int_0^T \Gamma(0,t) v(t) dt \end{aligned} \quad (10)$$

where $f_\psi(t)$ is the differentiation of $f(\phi, \psi, p_e(0,t), p_i(0,t))$ w.r.t. ψ .

The gradients (9)-(10) describe sensitivity of the cost function (4) to variation in parameters (ϕ, ψ) under the constraints of system dynamics (1)-(2).

C. Steepest descent method

We solve the optimization problem with a steepest descent method. The gradients L_ϕ and L_ψ give the descent directions to estimate optimal parameter values (ϕ^*, ψ^*) . We choose constant step sizes γ_ϕ and γ_ψ , which minimize the cost functional in the descent direction. We use Algorithm 1 below to solve the optimization problem. The algorithm stops when the norm of the gradient is smaller than the chosen tolerance ξ_ϕ and ξ_ψ . Notice that computing gradients require solving system equations (1)-(2) along with the adjoint system (7)-(8).

Algorithm 1: Optimal parameter estimation

Input: Initial values, $v(0)$ & $p_e(z,0)$
 Imposed pore pressure time series, $p_i(0,t)$
 Measured velocity profile, $v_{mea}(t_k)$
 Guessed parameter values, ϕ_G & ψ_G
 Set initial parameter values, ϕ_0 & ψ_0
 Step sizes, γ_ϕ & γ_ψ
 The gradient tolerances, ξ_ϕ & ξ_ψ
 Stop_flag = false
 Iteration index $k=1$
 Set $\phi^k = \phi_0$ and $\psi^k = \psi_0$

Output: ϕ^* , ψ^*

while Stop_flag = false **do**
 Simulate system equations (1)-(2) with $v(0)$,
 $p_e(z,0)$, ϕ^k , & ψ^k ;
 Simulate the adjoint system equation (7)-(8)
 (backward in time);
 Compute gradients L_ϕ^k , L_ψ^k using (9)-(10);
if $|L_\phi| \leq \xi_\phi$ & $|L_\psi| \leq \xi_\psi$ **then**
 Stop_flag = true;
else
 $\phi^{k+1} = \phi^k - \gamma_\phi L_\phi^k$;
 $\psi^{k+1} = \psi^k - \gamma_\psi L_\psi^k$;
 $k = k + 1$;
end
 Display ϕ , ψ and J
end
 Return ϕ^* , ψ^*

IV. SIMULATION RESULTS

A. Synthetic Data

To validate the effectiveness of our approach, a measured velocity profile $v^{mea}(t)$ is generated synthetically by solving the system equations (1)-(2). The parameter values and initial values used for the simulation are summarized in Table I. The numerical solution is here obtained with a stepwise analytical method for solving (1) and a Crank-Nicolson method for solving (2). In the simulations, imposed pore pressure is assumed to be sinusoidal in time, representing rainfall variations. The value of imposed pore pressure oscillates around p_{crit} given as

$$p_{crit} = \frac{g \cos \psi [\cos(\theta - \psi) \tan \phi - \sin(\theta - \psi)]}{\cos^2 \psi \tan \phi / \rho Z},$$

which corresponds to the value of pore pressure above which slide block starts to accelerate. At instances, when imposed pressure is less than or equal to p_{crit} the slide block is at rest, i.e., $v_0 = 0$, and as excess pore pressure generates in response to the motion of the slide block $p_{e0} = 0$. Simulated synthetic velocity measurement (with noises) and pore pressure profiles are shown in Fig. 2 and Fig. 3 respectively. The study is carried out for different noise levels in a measurement. White Gaussian noises are added to simulated velocity profile such that signal to noise ratios (SNR) are 10db and 20db respectively.

TABLE I
PARAMETER VALUES

Parameters	Value	Unit
Initial velocity, v_0	0	m/s
Initial excess pore pressure distribution, p_{e0}	0	Pa
Simulation time, T	2000	s
Time step, Δt	0.01	s
Space step, Δz	0.0066	m
Diffusion coefficient, D	3×10^{-3}	m^2/s
Acceleration due to gravity, g	9.8	m/s^2
Slide block thickness, Z	0.65	m
Hydraulic conductivity, K	2×10^{-5}	m/s
Plane inclination angle, θ	31	deg
Slide block mass density, ρ	2000	kg/m^3
Pore water density, ρ_w	1000	kg/m^3
Friction angle, ϕ	35	deg
Dilatancy angle, ψ	6	deg

Fig. 2. Synthetic velocity measurement (v_{mea})

Fig. 3. Critical (p_{crit}), imposed (p_i), and excess pore pressure (p_e)

B. Parameter estimation

The simulation for Parameter estimation is performed, following Algorithm 1, with the parameter values given

in Table II. Though the generated synthetic measurement is continuous, for the optimization problem only $N = 101$ observation values are taken into consideration i.e., at each $t_k = \{0, 20, 40, \dots, 2000\} \forall k \in (0, N)$. For the sake of simplicity, all the velocity measurements are considered in mm/sec without any loss of generality.

TABLE II
PARAMETER VALUES FOR THE ALGORITHM

Parameters	Value	Unit
Number of observation values, N	101	-
Guessed friction angle, ϕ_G	31	deg
Guessed dilatancy angle, ψ_G	4	deg
Initial friction angle, ϕ_0	25, 29, 32	deg
Initial dilatancy angle, ψ_0	3, 4, 5	deg
Step size, γ_ϕ	2.5×10^{-4}	-
Step size, γ_ψ	7×10^{-5}	-
Weighting factor, ε_1	2.5×10^{-3}	-
Weighting factor, ε_2	5×10^{-3}	-
Weighting factor, ε_3	30	-
Stop condition1, ξ_ϕ	10^{-2}	-
Stop condition2, ξ_ψ	10^{-2}	-

A convergence of the parameter estimates for two different noise levels and distinct initial parameter values can be seen in Fig. 4, Fig. 5, Fig. 6 and Fig. 7. We also observe a decrease in cost function and gradients in Fig. 8, and Fig. 9. For all these simulations step sizes (γ_ϕ, γ_ψ) and tolerance for gradients (ξ_ϕ, ξ_ψ) are kept the same. From the simulation results, the following observations can be made: i) for similar initial parameter values, the algorithm takes few more iterations to estimate parameters in case of a higher noise level in measurements, with some less accuracy (e.g., for $\phi_0 = 29$, with 20 dB SNR measurement estimated ϕ is 34.95 after $k=128$ iterations, while with 10 dB SNR measurement estimated ϕ is 34.90 after 130 iterations) and ii) for same measurements but initial parameter values farther from actual ones, the algorithm requires few more iterations to estimate parameters (e.g., for 10 dB SNR measurement, parameter estimation took $k=126$ iterations with $\psi_0 = 5$, whereas 130 iterations with $\psi_0 = 3$).

Fig. 4. Evolution of the parameter estimate (ϕ) for synthetic velocity measurement with SNR 20dB

Fig. 5. Evolution of the parameter estimate (ψ) for synthetic velocity measurement with SNR 20dB

Fig. 6. Evolution of the parameter estimate (ϕ) for synthetic velocity measurement with SNR 10dB

Fig. 7. Evolution of the parameter estimate (ψ) for synthetic velocity measurement with SNR 10dB

Fig. 8. Evolution of cost function J

Fig. 9. Evolution of norm of gradients L_ϕ & L_ψ

V. CONCLUSION AND FUTURE WORK

An optimal approach for parameter estimation in a landslide motion based on the adjoint method and the steepest descent approach has been proposed and validated in this paper. Firstly, an extended sliding-consolidation model of a landslide has been presented, which is an ODE-PDE coupled system. Secondly, the parameter estimation problem has been formulated as an optimization problem using Lagrange multiplier approach. Then the adjoint method has been introduced to obtain gradients of the cost functional and the adjoint equations. These gradients are then utilized as descent directions for the steepest descent method to get optimal parameter values. Lastly, the proposed solution method has been validated for synthetically generated noisy data. The optimal values of friction and dilatancy angle of the material have finally been well estimated.

Based on this result, a future direction for work will be to include estimation of the initial states of the system along with the parameters of interest for synthetically generated data and actual field measurements to relax the assumption on imposed pore pressure. Finally, this approach could be extended to more complex landslide models.

REFERENCES

- [1] E. M. Nyambod, "Environmental consequences of rapid urbanisation: Bamenda City, Cameroon", *Journal of Environmental Protection*, Vol. 1, 15-23, doi:10.4236/jep.2010.11003, 2010.
- [2] S. L. Gariano and F. Guzzetti, "Landslides in a changing climate", *Earth-Science Reviews*, Vol. 162, 227-252, ISSN 0012-8252, doi:10.1016/j.earscirev.2016.08.011, 2016.
- [3] J. Corominas, J. Moya, A. Lledesma, A. Lloret, and J. Gili, "Prediction of ground displacements and velocities from groundwater level changes at the Vallcebre landslide (Eastern Pyrenees, Spain)", *Landslides*, 2, 83-96. doi:10.1007/s10346-005-0049-1, 2005.
- [4] I. K. Krøgli, G. Devoli, H. Colleville, S. Boje, M. Sund, and I. K. Engen, "The Norwegian forecasting and warning service for rainfall- and snowmelt-induced landslides", *Nat. Hazards Earth Syst. Sci.*, 18, 1427-1450, https://doi.org/10.5194/nhess-18-1427-2018, 2018.
- [5] UN/ISDR, "Developing early warning systems: A checklist, EWCIII Third International Conference on Early Warning, From concept to action", https://www.unisdr.org/unisdr-archives/2006/ppew/info-resources/ewc3/checklist/English.pdf, 2006.
- [6] F. Guzzetti, S. Peruccacci, M. Rossi, and C. Stark, "Rainfall thresholds for the initiation of landslides in Central and Southern Europe", *Meteorology and Atmospheric Physics*, 98, 239-267. 10.1007/s00703-007-0262-7, 2007.
- [7] D. N. Petley, F. Mantovani, M. H. Bulmer, and A. Zannoni, "The use of surface monitoring data for the interpretation of landslide movement patterns", *Geomorphology*, Volume 66, Pages 133-147, ISSN 0169-555X, https://doi.org/10.1016/j.geomorph.2004.09.011, 2005.
- [8] J. N. Hutchinson, "A sliding-consolidation model for flow slides", *Canadian Geotechnical Journal*, 23 (2), 115-126, doi:10.1139/2004JF000268, 1986.
- [9] G. Herrera, J. A. Fernandez-Merodo, J. Mulas, M. Pastor, G. Luzi, and O. Monserrat, "A landslide forecasting model using ground based SAR data: The portalet case study", *Engineering Geology*, 105, 220-230, doi:10.1016/j.enggeo.2009.02.009, 2013.
- [10] S. Bernardie, N. Desramaut, J. P. Malet, G. Maxime, and G. Grandjean, "Prediction of changes in landslide rates induced by rainfall", *Landslides*, 12, doi:10.1007/s10346-014-0495-8, 2014.
- [11] R. Iverson, "Regulation of landslide motion by dilatancy and pore pressure feedback", *J. Physics. Res.*, 110, doi:10.1029/2004JF000268, 2005.
- [12] R. Baum, and J. Godt, "Early warning of rainfall-induced shallow landslides and debris flows in the USA", *Landslides*, 7, 259-272, doi:10.1007/s10346-009-0177-0, 2010.
- [13] I. S. Strub and A. M. Bayen, "Continuous adjoint method for Air Traffic Flow Management", *Proceedings of the 45th IEEE Conference on Decision and Control*, San Diego, CA, 2006, pp. 101-106, doi: 10.1109/CDC.2006.377458, 2006.
- [14] K. Graichen and N. Petit, "A continuation approach to state and adjoint calculation in optimal control applied to the reentry problem", *IFAC Proceedings Volumes*, vol. 41, iss. 2, 14307-14312, ISSN 1474-6670, ISBN 9783902661005, doi:10.3182/20080706-5-KR-1001.02424, 2008.
- [15] V. T. Nguyen, D. Georges, and G. Besançon, "Calculus of variations approach for state and parameter estimation in switched 1D hyperbolic PDEs", *Optimal Control Applications and Methods*, 39, doi:10.1002/oca.2405, 2017.
- [16] V. T. Nguyen, D. Georges, and G. Besançon, "State and parameter estimation in 1-D hyperbolic PDEs based on an adjoint method", *Automatica*, 67, doi:10.1016/j.automatica.2016.01.031, 2015.
- [17] V. T. Nguyen, D. Georges, and G. Besançon, "Optimal state estimation in an overland flow model using the adjoint method," *2014 IEEE Conference on Control Applications (CCA)*, Juan Les Antibes, pp. 2034-2039, 2014. doi: 10.1109/CCA.2014.6981602
- [18] Y. Ding and S. S. Y. Wang, "Identification of Manning's roughness coefficients in channel network using adjoint analysis", *Int. J. Comput. Fluid Dyn.*, vol. 19, no. 1, pp. 3-13, 2005.
- [19] G. Atanov, E. Evseeva, and E. Meselhe, "Estimation of roughness profile in trapezoidal open channels", *Journal of Hydraulic Engineering*, vol. 125, no. 3, pp. 309-312, 1999.
- [20] M. L. Chen and D. Georges, "Nonlinear optimal control of an open-channel hydraulic system based on an infinite-dimensional model", *Proc. of the 38th IEEE CDC*, vol. 5, pp. 4313-4318, vol.5, 1999.
- [21] R. Ramesh, B. Datta, S. Bhallamudi, and A. Narayana, "Optimal estimation of roughness in open-channel flows", *Journal of Hydraulic Engineering*, vol. 126, no. 4, pp. 299-303, 2000.