



IRIS FEATURES EXTRACTION USING WAVELET PACKETS

Erik Rydgren, Thomas Ea, Frédéric Amiel, Florence Rossant, Amara Amara

► To cite this version:

Erik Rydgren, Thomas Ea, Frédéric Amiel, Florence Rossant, Amara Amara. IRIS FEATURES EXTRACTION USING WAVELET PACKETS. ICIP, Oct 2004, Singapore, Singapore. 10.1109/ICIP.2004.1419435 . hal-02882950

HAL Id: hal-02882950

<https://hal.science/hal-02882950>

Submitted on 28 Jun 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

IRIS FEATURES EXTRACTION USING WAVELET PACKETS

Erik RYDGREN, Thomas EA, Frédéric AMIEL, Florence ROSSANT, Amara AMARA

Institut Supérieur d'Electronique de Paris, ISEP

21 rue d'Assas

75270 Paris Cedex 06

erik.rydgren | thomas.ea | frederic.amiel | florence.rossant | amara.amara@isep.fr

ABSTRACT

This article presents an application of wavelet packet analysis to the features extraction part of an iris recognition system. An energy measure is used to identify the particular packets that carries discriminating information about the iris texture. Several different orthogonal wavelets are tested and a comparison to non-orthogonal analysis using Gabor wavelets is done. The experimental results show 100% correct classifications when applying the algorithm on an iris image database and the new algorithm is therefore an interesting alternative to Gabor based methods.

1. INTRODUCTION

Biometric measures such as iris and retina texture, palmprint texture, face geometry and fingerprints is an interesting alternative to traditional authorization techniques such as keys and codes. Good biometric identification systems are well protected against forgery and hacking while also offering high user convenience.

Iris recognition technology has been a field of intensive research the last 15 years. The first system was patented by Daugman in 1994 [2]. Daugman's system is based on non-orthogonal wavelet analysis using so called Gabor wavelets [3], and has emerged as something of a benchmark in the field. Since then, much further work has been done by several research groups such as Zhu et al. [10], Tisse et al. [9] and Wildes [11]. Lim et al. has proposed a system based on orthogonal wavelet transform using the Haar wavelet [6]. Lim et al. uses the diagonal detail (HH) coefficients as iris signature. However, it will be shown in this paper that the wavelet packet approach can be a good alternative to the standard wavelet transform since it offers a more detailed division of the frequency plane.

The outline of this paper is as follows. The preprocessing part of the system is presented in section 2. In this case preprocessing refers to every operation that takes place before the features extraction. Section 3 introduces the two different extraction techniques used: wavelet packets versus Gabor wavelets. Section 4 presents the experimental results acquired with each of the two

methods. Finally, some conclusions and proposed future work can be found in section 5.

2. PREPROCESSING

The images used for this study are acquired by Miles Research [7] using dedicated iris imaging equipment providing very little eyelid and eyelash occlusion and also little light reflections. The images contain some of the surroundings of the iris which must be removed before further processing. This is done by a localization process where the center coordinates and radius for the pupil and iris are found. The iris texture is then transformed into a polar representation. The last step of the preprocessing procedure is to increase the contrast of the iris texture by histogram equalization. Figure 1 summarises the different preprocessing steps.




Figure 1. a) An eye photo before processing, b) a located iris, c) iris texture after unwrapping, d) unwrapped iris texture after histogram equalization

2.1 Image localization and equalization

The iris localization algorithm uses the fact that there is a relatively high contrast between the iris and the surrounding white sclera tissue. A simple gradient based search method has therefore proven successful. The pupil is located either by a similar gradient based method, or by isolating the gray-level values on the pupil through evaluating the histogram.

The phase of the complex-valued decomposition is used as iris signature. Both the real and imaginary parts of the decomposition coefficients are evenly distributed

around 0, and a coarse local phase measure is therefore given by the sign of the coefficients [3].

4. EXPERIMENTAL RESULTS

Table 1 to 3 presents some results using the two different features extraction techniques. The tests was conducted in the following way. A signature was extracted from each of the 82 photos in the database. The photos was taken from 33 different eyes and thus there were more than one photo per each eye. The size of the unwrapped textures was set to 128*512 pixels when using the wavelet packet method and 64*256 when using the Gabor method. The reason for using a larger texture for the wavelet packet method is that the subimages at level three are downsampled by a factor $2^3=8$ and as a result, the signature size would otherwise be too small. The signature size for the two methods were 896 bits (wavelet packets) and 2684 bits (Gabor). Each signature was compared to all the other signatures using the Hamming distance, given by:

$$HD = \frac{1}{N} \sum_{j,k} S_1(j,k) \oplus S_2(j,k) \quad (3)$$

where S_1 and S_2 are two binary signatures, N is the total number of bits in each signature and \oplus is the XOR operator defined as:

$$x \oplus y = \begin{cases} 0 & x = y \\ 1 & x \neq y \end{cases} \quad (4)$$

where x and y are single bits. The Hamming distance is thus a measure for the similarity between two bit sequences, the lower Hamming distance the higher similarity.

It is very important that the system is rotational invariant since any tilt of the head when taking the iris photos will produce a rotation in the iris texture. Two different methods to produce rotational invariance was tried. First, the actual photos was shifted to produce several signatures for every photo. Secondly, the signatures themselves were shifted. The two methods proved to yield equivalent results, but the second one is more effecient and therefore preferred.

For the wavelet packet features extraction, subimage number 2 (see figure 2 and 3) was used as signature. This was motivated by an energy measurement using eq. (2) that showed that most of the texture information is encoded by this subimage, see figure 4 for a plot giving the mean energy distribution for 25 unwrapped iris images from different eyes. The energy corresponding to subimage 0 has been removed since this subimage contains offset (DC) information. From the frequency plane mapping of figure 3 it is clear that subimage 2 codes relatively low frequency energy close to the horizontal

axis. The unwrapped iris images are characterised by lines extending in the vertical direction, and therefore contain much energy at horizontal frequency. Figure 4 shows that subimage 10 holds much energy as well. It is therefore interesting to also evaluate the possibilities to use this subimage as a signature.




Figure 4. Mean wavelet packet energy distribution for 25 unwrapped iris textures. The indexes on the x-axis corresponds to the frequency plane in figure 3.

The discrimination results using wavelet packets are found in table 1 and 2. The first column (Wavelet) indicates which wavelet was used and columns 2 to 5 (μ_a , σ_a , μ_i , σ_i) presents first and second order statistics for the distribution of Hamming distances for authenticics and imposters respectively. The authentic distances are from different signatures from the same individual while the imposter distances are from different individuals. The last column (Sep.) gives the separation between the two distributions, that is the distance between the largest authentic measurement and the smallest imposter measurement. The separation should be a positive number, the larger the better.

Wavelet	Authenticics		Imposters		Sep.
	μ_a	σ_a	μ_i	σ_i	
Haar	0.185	0.051	0.457	0.011	0.071
Daubechies2	0.202	0.058	0.459	0.010	0.040
Daubechies4	0.208	0.056	0.460	0.010	0.060
Daubechies6	0.220	0.054	0.461	0.010	0.046
Daubechies8	0.224	0.058	0.461	0.010	0.018
biorthog. 1.3	0.186	0.053	0.459	0.010	0.076
biorthog. 2.6	0.240	0.066	0.463	0.008	0.000
biorthog. 3.9	0.270	0.067	0.463	0.009	-0.017
coiflet 2	0.214	0.061	0.460	0.010	0.026
coiflet 4	0.216	0.055	0.462	0.010	0.060
symlet 2	0.202	0.058	0.460	0.010	0.040
symlet 4	0.213	0.061	0.460	0.011	0.027
symlet 6	0.215	0.062	0.460	0.010	0.019

Table 1. Results using wavelet packets with various wavelets. Notation: μ - mean, σ - std. dev.

From table 1 it is clear that the Haar and Biorthogonal 1.3 wavelets are most suitable in this application. The imposters mean value is slightly below 0.5. This is due to

the rotation invariance implementation, where the signatures are shifted relative to each other and the best match (lowest Hamming) for all shifts is recorded.

The discrimination performance of subimage 10 was also tested, the results can be found in table 2.

Wav.	Authentics		Imposters		Sep.
	μ_a	σ_a	μ_i	σ_i	
Haar	0.276	0.059	0.461	0.009	0.000
bior1.3	0.274	0.060	0.462	0.008	0.010

Table 2. Results using subimage 10.

Although the separation between the authentic and imposters distributions is smaller when using subimage 10 than subimage 2, the means are clearly separated and there is thus discriminating information also in this subimage.

Table 3 gives the results from experiments with Gabor wavelets. The optimal frequency for the modulating complex exponential was found to be $f = 0.021 f_s$, where f_s is the sampling frequency in rad/pixel.

f	Authentics		Imposters		Separ.
	μ_a	σ_a	μ_i	σ_i	
0.021	0.106	0.032	0.445	0.018	0.207

Table 3. Results using Gabor wavelets of frequency f .

Figure 5 show the histograms for authentic and imposters Hamming distance distributions, using wavelet packets and Gabor wavelets. The upper and lower left histograms shows the authentic and imposter distributions for the wavelet packet algorithm using subimage 2 as signature and the biorthogonal 1.3 wavelet. The upper and lower right histograms shows the corresponding distributions in the Gabor case.




Figure 5. Hamming distance distributions for authentic and imposters using wavelet packets (a), (b) and Gabor wavelets (c),(d)

5. CONCLUSIONS AND FUTURE WORK

A wavelet packet approach to iris recognition has been proposed and evaluated. The algorithm manages to correctly identify all authentic irises and dismiss all imposters. Since the algorithm is based on orthogonal analysis, the fast wavelet transform can be used to achieve high processing efficiency. The calculation complexity is particularly low if the Haar wavelet is used because of the simple structure of the associated filter. The performance for the benchmark Gabor wavelet is so far superior but it is likely that the performance of the wavelet packets algorithm can be increased in the future. The signatures extracted with wavelet packet analysis is also more compact than the signatures extracted using the Gabor method. Some propositions for future work includes evaluating the possibilities of using more than one subimage and a longer signature. The performance might also be increased by using another distance measure than the Hamming distance, such as the weighted Euclidian distance, or by using more than 3 levels of transformation.

6. ACKNOWLEDGEMENTS

The authors are grateful to Jon Miles at Miles Research [7] for providing the iris image database used in this study.

7. REFERENCES

- [1] J. Bergh, F. Ekstedt and M. Lindberg, *Wavelets*, Studentlitteratur, Lund, 1999
- [2] "Biometric Personal Identification System Based on Iris Analysis.", U.S. Patent No. 5,291,560 issued March 1, 1994 (J. Daugman)
- [3] J. Daugman, "High confidence visual recognition of persons by a test of statistical independence.", *IEEE Trans. PAMI*, vol. PAMI-15, pp. 1148-1161, 1993
- [4] J. Daugman, "Uncertainty relation for resolution in space, spatial frequency and orientation optimized by two-dimensional visual cortical filters." *Opt. Soc. Amer. A*, Vol 2, pp. 1160-1169, 1985
- [5] R. C. Gonzales and R. E. Woods, *Digital Image Processing*, Prentice Hall, New Jersey, 2002
- [6] S. Lim et al., "Efficient iris recognition through improvement of feature vector and classifier", *ETRI J.*, Vol 23, pp. 61-70, 2001
- [7] Miles Research, www.milesresearch.com
- [8] O. Nestares et al., "Efficient spatial-domain implementation of a multiscale image representation based on Gabor functions", *J. of Electronic Imaging*, Vol 7, pp. 166-173, 1998
- [9] Tisse et al., "Person Identification technique using human iris recognition", *Proc. 15th Int. Conf. on Vision Interface*, Calgary, Canada, 2002
- [10] Y. Zhu, T. Tan and Y. Wang, "Biometric personal identification based on iris patterns", *Proc. 15th Int. Conf. on Pattern Recognition*, Barcelona, Spain, 2000
- [11] R. P. Wildes, "Iris recognition: an emerging biometric technology", *Proc. IEEE* 85, Vol 9, pp. 1348-1363, 1997