



HAL
open science

To Be or Not To Be a Verbal Multiword Expression: A Quest for Discriminating Features

Caroline Pasquer, Agata Savary, Jean-Yves Antoine, Carlos Ramisch, Nicolas Labroche, Arnaud Giacometti

► **To cite this version:**

Caroline Pasquer, Agata Savary, Jean-Yves Antoine, Carlos Ramisch, Nicolas Labroche, et al.. To Be or Not To Be a Verbal Multiword Expression: A Quest for Discriminating Features. 2020. hal-02905874

HAL Id: hal-02905874

<https://hal.science/hal-02905874>

Preprint submitted on 23 Jul 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

To Be or Not To Be a Verbal Multiword Expression: A Quest for Discriminating Features

Caroline Pasquer

University of Tours
France

caroline.pasquer@gmail.com

Agata Savary, Jean-Yves Antoine

University of Tours
France

first.last@univ-tours.fr

Carlos Ramisch

Aix Marseille Univ, Université de Toulon,
CNRS, LIS, Marseille, France

carlos.ramisch@lis-lab.fr

Nicolas Labroche, Arnaud Giacometti

University of Tours
France

first.last@univ-tours.fr

Abstract

Automatic identification of multiword expressions (MWEs) is a pre-requisite for semantically-oriented downstream applications. This task is challenging because MWEs, especially verbal ones (VMWEs), exhibit surface variability. However, this variability is usually more restricted than in regular (non-VMWE) constructions, which leads to various variability profiles. We use this fact to determine the optimal set of features which could be used in a supervised classification setting to solve a subproblem of VMWE identification: the identification of occurrences of previously seen VMWEs. Surprisingly, a simple custom frequency-based feature selection method proves more efficient than other standard methods such as Chi-squared test, information gain or decision trees. An SVM classifier using the optimal set of only 6 features outperforms the best systems from a recent shared task on the French seen data.

1 Introduction

Multiword expressions (MWEs) are word combinations with idiosyncratic characteristics regarding for instance morphology, syntax or semantics (Baldwin and Kim, 2010). One of their most emblematic properties is semantic non-compositionality: the meaning of the whole expression cannot be straightforwardly deduced

from the meaning of its components, as in *to cut corners* ‘to do an incomplete job’¹. Due to this property, as well as to their pervasiveness (Jackendoff, 1997), MWEs constitute a major challenge for semantically-oriented downstream applications, such as machine translation, information retrieval or sentiment analysis. A prerequisite for an appropriate handling of MWEs is their automatic identification.

MWE identification aims at automatic location of MWEs in running text. This task is very challenging, as signaled by Constant et al. (2017), and further confirmed by the PARSEME Shared Task on automatic identification of verbal MWEs (Ramisch et al., 2018). One of the main difficulties stems from the variability of MWEs, especially verbal ones (VMWEs). Namely, even if a MWE has previously been observed (in a training corpus or in a lexicon), it can re-appear in morphosyntactically diverse forms, where components vary inflectionally, their order is inverted, discontinuities occur and syntactic relations change between lexicalized components, as in examples (1–2).

- (1) Some companies were **cutting corners**_{OBJ} to save costs.
- (2) The field would look uneven if **corners**_{SUBJ} were **cut**.

¹Henceforth, the lexicalized components of a MWE, i.e. those always realized by the same lexemes, appear in bold.

However, assuming unrestricted variability is not a good strategy either, since it may lead to literal or coincidental occurrences of MWEs' components, as in (3) and (4).²

- (3) Start with cutting one corner of the disinfectant bag.
(4) If you cut along this line, you'll get an acute corner.

To tackle these challenges, we focus on a subproblem of MWE identification (henceforth referred to as the Task), namely the identification of previously seen VMWEs.

We deal with French, which exhibits a particularly rich verbal inflection, and whose VMWE-annotated corpus is one of the richest PARSEME Shared Task benchmark datasets. However, the proposed methods are language-independent in that they rely on universal properties of VMWEs and feature sets. Our aim is to determine the optimal set of features which would allow us to automatically discriminate between VMWEs and non-VMWEs in a supervised classification framework. To this aim, we first study the linguistic properties of VMWEs which may serve as a basis for defining the initial set of features (Sec. 2). Then, we describe the corpora used for training and evaluation (Sec. 3). Further, we address the selection of the positive/negative candidates from the corpus (Sec. 4). We discuss the successive phases of feature selection (Sec. 5): the definition of the initial set of features; the ranking of these features by their relevance to the task; and establishing the optimal number of best-ranked features by off-the-shelf binary classifiers. Then, the results are discussed (Sec. 6) and we interpret some of the selected features from a linguistic point of view (Sec. 7). Finally, we conclude and suggest directions for future work (Sec. 8).

2 Linguistic properties of VMWEs

The major observation underlying our work is that VMWEs are mostly morphosyntactically regular at the level of tokens (individual occurrences) but idiosyncratic at the level of types (sets of surface realizations of the same expression). For instance, considering the VMWE type *to cut corners* instantiated by the VMWE tokens in (1) and (2), we find no "surface" (i.e. non-semantic) hints that distinguish them from regular English verb-object constructions (e.g. *cut branches*). They respect standard grammar rules (the object follows the

²Henceforth, literal and coincidental occurrences are highlighted with wavy underlining.

verb; in passive, the verb occurs in participle, etc.). Unlike named entities, they use no capitalisation and contain no trigger words. However, number inflection of the noun is prohibited by this VMWE, i.e. using the noun in singular leads to the loss of the idiomatic meaning, as shown in example (3). This is in contrast to regular verb-object constructions (*cut a branch*), in which noun inflection does not significantly change the overall meaning.

Such a restricted variability of MWEs is one of their fundamental properties, as argued in linguistic work (Gross, 1988; Nunberg et al., 1994; Tutin, 2016; Sheinflux et al., 2018). Namely, a given syntactic structure in a given language comes with a set of various morphosyntactic variations considered grammatical (e.g. English transitive verb constructions admit passivisation, noun inflection, pronominalisation, etc.). But a MWE of the same structure usually allows only a proper subset of these variants, which we will call its *variability profile*. These profiles are numerous and hard to predict, e.g. while *cut corners* admits passivisation but prohibits number inflection, *build bridges* 'establish links' accepts both of these variants, and *take place* 'happen' none of them.

Studying variability profiles in corpora is hindered by another fundamental property of VMWEs – their Zipfian distribution: few VMWE types occur frequently in corpora, and there is a long tail of VMWE types occurring rarely.

The third property we are interested in is the fact that some VMWE types do share common "surface" properties, e.g. most light-verb constructions have no lexicalized determiners (*take a/many/several/no break(s)*) and contain frequent light verbs (e.g. *take a walk/break/advantage/etc.*). These shared properties, however, are rarely semantically motivated: VMWEs exhibit a strong lexical inflexibility, i.e. replacing a lexicalized component with a semantically close word (a synonym, hyperonym, etc.) usually results in the loss of the idiomatic reading, in example (5), as opposed to (1–2).

- (5) The field would look uneven if borders were reduced.

In this work, we hypothesize that: (i) variability profiles of VMWEs, materialized by morphosyntactic features in annotated corpora, can help correctly identify occurrences of previously seen VMWEs, (ii) for rarely occurring VMWEs, their resemblance with other, more frequent, VMWEs can also help solve the Task. The two hypothe-

ses give rise to *relative* and *absolute* features, described in Sec. 5.1.

3 Corpus

In 2018, edition 1.1 of the PARSEME Shared Task, henceforth PST (Ramisch et al., 2018), took place, with a goal of boosting the development of identifiers for both seen and unseen VMWEs. To this end, a corpus of verbal MWEs was manually annotated and openly published for 19 languages.³ We use the French part of this corpus, and we refer to its particular subcorpora as TrainST and TestST, which reflects their function in PST.

In our experiments, TrainST is used: (i) for training and testing during feature selection (Sec. 4–5), (ii) for training during the evaluation of the final system against the PST results (Sec. 6.2), and prior to the extraction of candidates for manual evaluation on a large external corpus (Sec. 6.3). TestST is only used as a testing benchmark in the PST evaluation setting (Sec. 6.2).⁴

For manual evaluation (Sec. 6.3), we also use a large corpus collected from Wikipedia and by webcrawling for the CoNLL 2017 Shared Task.⁵

It is automatically segmented, tokenized and morpho-syntactically annotated (Zeman et al., 2018) but it does not contain VMWE annotations.

Tab. 1 shows the statistics of the 3 corpora, in terms of the number of sentences, tokens, all annotated VMWEs and those annotated VMWEs which also occur in TrainST (the Task is limited to them).

All corpora comply with the CoNLL-U format⁶, i.e. contain, for each surface form, its lemma, POS, morphological features and syntactic dependencies.

VMWEs are manually annotated and categorized into: verbal idioms (VID: *cut corners*), light-verb constructions (LVC: *take a walk*), inherently reflexive verbs (IRV: *s’apercevoir* ‘to perceive oneself’ ⇒ ‘to realize’) and multi-verb constructions (MVC: *to make do*). Thus, contrary to other works which focus on verb-noun VMWEs (Fazly et al., 2009), we handle various syntactic profiles. Note, however, that the Task only addresses VMWE identification and abstracts away from categorisation.

Corpus	# Sentences	# Tokens	# VMWEs	# Seen
TrainST	17,225	432,389	4,550	4,550 100%
TestST	1,606	39,489	498	251 50%
CoNLL	306,431,406	5,242,235,570	n/a	n/a

Table 1: Statistics about corpora. *Seen* refers to those VMWEs which also appear in TrainST.

4 Candidate extraction

In order to test the hypotheses put forward in Sec. 2, we propose a supervised classification method for identifying previously seen VMWEs.

In the first step, we design a procedure, henceforth called `ExtractCands`, to extract VMWE candidates. It will be employed in: (i) training, to choose positive and negative VMWE examples, further used for feature selection, (ii) testing, for pre-identifying VMWE candidates to be fed to the classifier. For every VMWE e attested in the training corpus, `ExtractCands` extracts each co-occurrence c of e ’s lexicalized components, provided that the following conditions are fulfilled.

First, the sets of lemmas and parts-of-speech of e ’s and c ’s components are identical. For instance, for e in (6), the candidate in (7) will be extracted but not the one in (8), due to the different POS of *mesure* ‘*measure*’.

- (6) Il **prend**_{VERB} plusieurs_{SDET} **measures**_{NOUN}. ‘He takes several measures.’
- (7) Je **prends**_{VERB} un_{DET} **measure**_{NOUN} unconstitutionnelle. ‘I take an unconstitutional measure.’
- (8) Il **prend**_{VERB} une règle et **mesure**_{VERB} la longueur. ‘He takes a ruler and measures the length.’

Second, if c contains two components or if there is only one verb and one noun, they must be either directly connected in the syntactic dependency tree or separated by only one element. This condition is fulfilled (7) and in case of complex determiners as in Fig. 1(a), but not in coincidental occurrences like in Fig. 1(b). No dependency constraints were defined for candidates with more than two components due to their lower frequency and to computational constraints.⁷

Third, based on c ’s discontinuities seen in TrainST, we restrict the number of external elements that can be inserted between c ’s components, to avoid large numbers of spurious candidates stemming from frequent lemmas (e.g. determiners or pronouns), as in (9).

⁷Searching for existing, direct or indirect, dependencies between pairs taken from up to 7 components would be time-consuming.

³<http://hdl.handle.net/11372/LRT-2842>

⁴In the PST corpus, there is also a small development corpus for French, which we do not use.

⁵<http://hdl.handle.net/11234/1-1989>

⁶<http://universaldependencies.org/format.html>



Figure 1: VMWE candidates with discontinuous dependency chains: (a) extracted, (b) non-extracted.

Corpus	Extracted candidates			P	R
	All	Positive	Negative		
TrainST	4,596	3,582 (78%)	1,014 (22%)	0.78	0.98
TestST	368	210 (57%)	158 (43%)	0.57	1.00
CoNLL	32,789,815	n/a	n/a	n/a	n/a

Table 2: Results of candidate extraction, based on attested VMWEs seen at least twice in TrainST.

- (9) Il faut rappeler que, jusqu'en 1983, il n'y avait pas ...
One must remind that, until 1983, there was no ...

Finally, since we wish to test the variability profile hypothesis (Sec. 2), we retain only those VMWEs whose number of occurrences is high enough to be representative of their variability. However, this frequency threshold cannot be too high, otherwise the size of the annotated data would dramatically drop. For a reasonable trade-off between these two factors, we select only those candidates whose attested VMWEs appear at least twice in the training corpus (3582 occurrences i.e. 78% of TrainST).

When `ExtractCands` is used for training, the extracted candidates are marked as positive, if they are manually annotated as VMWEs in TrainST, and negative otherwise. Tab. 2 shows the results of the candidate extraction in the corpora from Tab. 1. As expected, the method is tuned for a high recall and a reasonable precision. The latter factor should grow due to classification, based on a carefully selected set of features, which is addressed in the following section.

5 Feature selection

In supervised classification, the VMWE candidates to classify are to be represented by sets of features. The choice of such features is crucial for the quality of the classification outcome and its adequacy for the tested hypotheses. This section describes the initial set of features and the selection of those which are the most relevant to the Task.

5.1 Initial set of features

As discussed in Sec. 2, we hypothesize that the variability profiles of VMWEs can help correctly identify occurrences of previously seen VMWEs. Representing these profiles straightforwardly is

not always easy (e.g. for passivization or pronominalization), especially in a language-independent way. But, we assume that they can be approximated by simpler properties directly encoded in the CoNLL-U files (Sec. 3). Thus, our starting point is a set of features related to morphology, syntax and insertions. Morphological features mostly refer to verb or noun inflection. Syntactic features relate to dependency relations outgoing from a component (e.g. subject vs. object) or to the fact that the components are syntactically (in)directly connected. Insertion-bound features account for the number of words inserted between the lexicalized components, e.g. 2 insertions in (10), and to their POS sequence, e.g. DET ADJ in (10). Insertions and syntactic dependencies may convey similar information, e.g. in (10) the adjective is accounted for both as an insertion and as a modifier of the noun. But they may also be complementary, as in (11), since syntactic dependencies capture modifiers not included between the lexicalized components.

- (10) Il **prend** d'_{DET} importantes_{ADJ} **mesures** 'He takes \emptyset _{DET} important **measures**'

- (11) Il **prend** des_{DET} **mesures** aussi (voire de plus en plus) importantes_{ADJ} 'He takes as (or even more and more) important **measures**'

Recall (Sec. 2) that the variability profile is defined on the level of VMWE types rather than tokens. This is why, following Pasquer et al. (2018), we put strong impact on *relative* features. Namely, given a VMWE candidate c , and its reference VMWE token together with all attested VMWE tokens of the same type ($\{e_1, e_2, \dots, e_n\}$), we compare the properties of c to those of e_i ($1 \leq i \leq n$). Relative features always take binary values. Thus, the `REL_INSERTSEQ` feature is true if the POS sequence of the words inserted between c 's components is the same as in any e_i , as in (7) vs. (6), and false otherwise, as in (11) vs. (10). Also, `REL_SYNTACTICDEPENDENCIES_VERB` is true if the set of dependency relations outgoing from the verb in c is the same as in any e_i , and false otherwise, etc.

Recall that VMWEs have a Zipfian distribution, thus relative features may be unreliable for many VMWE types occurring rarely. Thus, we also use

absolute features. They are similar to the relative ones, but they are categorical rather than binary. For instance, the value of ABS_INSERTSEQ is the POS sequence of the inserted words, e.g. DET ADJ in (10). Absolute features also include the VMWE set of lemmas, e.g. $\{mesure, prendre\}$, and their categorization (e.g. LVC).

Note finally that no word embeddings are used in the initial set of features. This is justified by lexical inflexibility of VMWEs: a new VMWE can rarely be discovered by semantic similarity of its components to those of attested VMWEs. This observation is confirmed by the PST, where best VMWE identifiers, even those using word embeddings, never exceed F-measure of 0.28 for unseen VMWEs. In our opinion, this very weak generalisation power should be approached by systematically coupling VMWE identification with their automatic discovery, which our perspective for future work.

5.2 Usefulness of automatic feature selection

The initial set of relative and absolute features defined in the previous section is huge: with the UD tagset used in our corpora, we get 18,000 possible features in total. If we only keep those features which are activated at least once in the corpus, this number is reduced to about 800. The question is then how to select those features which are the most discriminating for the Task.

Most systems from PST use features which are known to be linguistically relevant, and which are relatively simple to calculate (Waszczuk, 2018; Taslimipoor and Rohanian, 2018; Boros and Burdica, 2018; Stodden et al., 2018; Moreau et al., 2018,?; Berk et al., 2018; Ehren et al., 2018; Pasquer et al., 2018; Zampieri et al., 2018).⁸

Another approach was to feed all/most potentially relevant features to the classifier and let it determine the appropriate weights for those features (Pasquer et al., 2018). In this work, we also rely on domain knowledge to define the initial set of features, but we use automatic feature selection methods. The motivation is threefold. First, a lower number of accurately chosen features should lead to classification of a higher quality and shorter training time. Second, we might discover features whose relevance to the Task has not been linguistically established. Third, automatic procedure is

⁸A summary of this state of the art is offered in the Appendix B.

language-independent, as soon as the initial set of features is generic enough.

The feature selection process runs in two stages: (i) feature ranking, (ii) choice of the optimal number of the best-ranked features.

5.3 Feature ranking

We experimented with 4 feature ranking methods described below. All but the first require annotated data and are applied to the TrainST corpus.

FREQ This is a custom frequency-based method. We apply the `ExtractCands` from Sec. 4 to the CoNLL corpus, which yields 2.6 million candidates.⁹ Then, we select only those feature-value pairs which appear in at least one candidate, and we rank them by decreasing frequency. Finally, we strip the values and only keep the features.¹⁰

CHI2 The Chi-squared test (Kumbhar and Mali, 2016) looks at candidates having both the given feature-value pair fv and the given class cl . It calculates the difference between their observed and expected frequencies, under the hypothesis that fv and cl are independent. We use the Pearson’s version of this test, and the feature-value ranking corresponds to decreasing chi-squared value. We finally strip the values, as in **FREQ**.

GAIN The information gain (Kumbhar and Mali, 2016) method partitions the set of observations according to different values of a given feature f , calculates the weighted sum of the entropies of these partitions, and compares it to the entropy of the whole set. If the entropy strongly drops after the partition, the information gain is high, i.e. f is strongly discriminating. The feature ranking corresponds to the decreasing value of the gain.

FOREST The Random Forest algorithm (Breiman, 2001), combines many decision trees (here: 10 trees with no depth limit) into a single model by a majority or weighted vote. For the construction of the tree, the quality of each split is measured by the Gini impurity. Features are then ranked by their relevance when determining splits.

5.4 Tuning the number of features

Each of the methods from the previous section ranks the initial set of features according to their estimated relevance to the Task. We now need to

⁹Their classes are unknown, since the CoNLL corpus is not annotated for VMWEs.

¹⁰After stripping, features may have several occurrences, corresponding to different values. We only keep the occurrence with the highest rank.

decide how many best-ranked features from each ranking should be selected. We tune this parameter with 3 standard supervised classification methods – Naive Bayes, linear SVM and decision trees – using their off-the-shelf implementations.¹¹

For each classifier C , and for each feature ranking list R from Sec. 5.3, we proceed by a greedy method : (i) we select the i best-ranked features from R , (ii) we train and test C , with the i selected features, in a 10-fold unstratified cross-validation setting with a 90%-10% split of the TrainST corpus, where the candidates for both training and testing are those extracted by `ExtractCands`, (iii) we calculate the mean F-measure F_{mean} for the 10 folds, (iv) we repeat steps (i–iii) for every i from 1 to $length(R)$ and we select the value of i for which F_{mean} is the highest.

6 Results

In this section we show the results of the feature selection process described above. Then, we evaluate the obtained set of features by two methods: by the comparison of the best-performing classifier-selection pair to benchmark results, and by a manual evaluation of the same pair on an external large corpus.

6.1 Optimal feature sets

Tab. 3 shows the best results (i.e. the results for the optimal number of best-ranked features) of the feature selection experiments described in Sec. 5, for the 4 feature ranking methods and the 3 classifiers. P , R and F are the mean scores from the 10 folds, and σ is the variance of the 10 F-scores.¹²

Surprisingly, `FREQ`, which is a custom method, initially conceived to only remove irrelevant features from the initial set, achieves identical or better results than standard feature selection methods, with $F = 0.936$ for the linear SVM.

The optimal feature sets corresponding to these results are described in Tab. 4. There is a notable consistence in the optimal sets selected by each method. For `CHI2`, `GAIN` and `FOREST`, each of the 3 classifiers selects always the same set

¹¹NLTK (Loper and Bird, 2002) for Naive Bayes, and Scikit-learn (Pedregosa et al., 2011) for SVM and decision trees.

¹²The low value of variance indicates that the simple 90%-10% corpus split method is sufficiently reliable. If variance were higher, stratified validation would be more appropriate (i.e. the corpus would have to be split in such a way that the proportion of data belonging to each class is the same in each fold as in the whole corpus).

FeatSelect	Feature set	Classif	P	R	F	σ
FREQ	①	NB	0.881	0.965	0.921	0.012
	②	SVM	0.896	0.980	0.936	0.015
		Dec. Tree	0.913	0.934	0.923	0.009
CHI2	③	NB	0.818	0.975	0.889	0.011
		SVM	0.826	0.973	0.893	0.013
		Dec. Tree	0.833	0.964	0.894	0.012
GAIN	④	NB	0.826	0.974	0.894	0.013
		SVM	0.897	0.980	0.936	0.015
		Dec. Tree	0.875	0.962	0.916	0.020
FOREST	⑤	NB	0.787	0.975	0.871	0.016
		SVM	0.787	0.975	0.871	0.016
		Dec. Tree	0.787	0.975	0.871	0.016

Table 3: Best mean performance on 10% of TrainST (in 10 cross-fold validation). The feature sets are detailed in Tab. 4.

ABSolute and RELative features	Feature sets in Tab. 3					Total
	①	②	③	④	⑤	
ABS_LEMMASET (e.g. { prendre , décision })	✓	✓		✓		3
ABS_VMWECA (e.g. LVC)	✓	✓				2
ABS_INSERTSEQ (e.g. DET-ADJ)	✓	✓		✓		3
ABS_LEMMA_VERB (e.g. ' prendre ')		✓				1
REL_INSERTSEQ	✓	✓	✓	✓	✓	5
REL_INSERT_ADP			✓	✓	✓	3
REL_INSERT_CCONJ					✓	1
REL_INSERT_DET			✓	✓		2
REL_INSERT_NOUN			✓	✓	✓	3
REL_INSERT_PUNCT			✓			1
REL_INSERT_VERB			✓			1
REL_0TO5INSERTIONS			✓	✓		2
REL_LEMMA_VERB		✓				1
REL_SYNTACTICDISTANCE			✓			1
Number of features	4	6	8	7	4	

Table 4: Optimal feature sets mentioned in Tab. 3

(resp. ③, ④, ⑤). For `FREQ`, the two sets (① and ②) vary by one feature only. However, the sets are quite diverse from one selection method to another, which proves the complementarity of the methods.

The optimal number of features varies from 4 to 8. As expected, relative features are more often selected; `CHI2` and `FOREST` select even exclusively relative features. This is consistent with our variability-profile hypothesis (Sec. 2). One feature (`REL_INSERTSEQ`) is selected by all methods, and there are 6 features selected only once.

6.2 Benchmark evaluation

It is interesting to evaluate the quality of the feature set selection by a direct comparison to the 17 systems having participated in the PST campaign (cf. Sec. 3). PST defined evaluation measures which are specific to phenomena constituting known challenges in VMWE identification. One of them is the seen-in-train score, i.e. the P/R/F calculated only for those VMWEs in TestST which were previously seen in TrainST. In PST, a VMWE from TestST is considered seen if a VMWE with the same (multi-)set of lemmas is annotated at least once in TrainST.

We compare our optimal (2)+SVM classifier with the PST results for French¹³ as follows: (i) SVM is trained on the whole TrainST corpus (with `ExtractCands` and feature set (2)), (ii) we apply it to the candidates extracted with `ExtractCands` from TestST, (iii) those VMWEs from TestST which were either omitted by `ExtractCands` or wrongly classified simply count as false negatives. This obviously lowers the results as compared to Tab. 3, where only the VMWEs seen at least twice are considered.

As shown in Tab. 5, the F-measure of (2)+SVM indeed drops by over 11 points in the PST setting (to 0.8207). However, this is much higher than $F = 0.7003$ obtained by `varIDE` (Pasquer et al., 2018) with a quite similar method, except that, there, only Naive Bayes with no feature selection is used. This highlights the fact that focusing on a small set of relevant features helps the classification. What is more, our F-measure is slightly higher than the best registered F-score (0.8172) by `TRAVERSAL` (Waszczuk, 2018), where logistic regression is applied to sequences of nodes in dependency trees. Additionally, the handling of the variant-of-train VMWEs (i.e. those VMWEs in TestST which appear with a different surface form than in TrainST) is better with our method than with `TRAVERSAL` ($F = 0.7317$ vs. 0.7123). We also get better seen-in-train F-scores than the second and third best systems, based on neural networks: `GBD-NER-resplit` (Boros and Burtica, 2018), which only uses the provided PST corpora, and `SHOMA` (Taslimipoor and Rohanian, 2018), which also employs Wikipedia word embeddings.

When (2)+SVM is evaluated on all VMWEs from the French TestST, not only the seen ones,

¹³<https://gitlab.com/parseme/sharedtask-data/tree/master/1.1/system-results>

Evaluation on 10% TrainST (seen twice VMWEs)			
Method	P	R	F
Feature set (2) + SVM	0.896	0.980	0.936
Evaluation on TestST (all seen VMWEs)			
Feature set (2) + SVM	0.8207	0.8207	0.8207
TRAVERSAL	0.8879	0.7570	0.8172
GBD-NER-resplit	0.8842	0.6693	0.7619
SHOMA	0.9167	0.6574	0.7657
varIDE	0.5682	0.9124	0.7003
Evaluation on WebSample			
Feature set (2) + SVM	0.873	0.977	0.922

Table 5: Evaluation results in the PST benchmark setting, and with a manually annotated external corpus

the F-score decreases to 0.55, which is still relatively close to 0.56 obtained by the best system (`TRAVERSAL`), even if unseen VMWEs are totally beyond the scope of our work.

6.3 Manual evaluation on an external corpus

It is also interesting to evaluate the quality of the selected feature set on an external corpus, independent of the one used for the selection. To this end we constructed a representative sample of the CoNLL corpus, called `WebSample`, that could be manually checked. Namely, `WebSample` should respect the distribution observed in TrainST, as far as frequencies of VMWEs and of their categories are concerned. To this aim, we first checked the proportion of the 4 categories (VIDs, LVCs, IRVs and MVCs) in the VMWEs seen at least twice in TrainST. Then, we selected 90 VMWE types¹⁴ in such a way that these proportions are respected (except for MVCs, which are very rare in TrainST) and that VMWEs types in each category have high, low and median frequency (with a balanced distribution). For MVCs, we selected all 4 VMWE types appearing in TrainST. Finally, the 90 VMWE types selected in TrainST were given as the reference set to `ExtractCands`, which was then applied to the CoNLL corpus. The resulting set of candidates was trimmed so that equal numbers of candidates come from the Wikipedia and the webcrawling part of the CoNLL corpus.

Tab. 6 shows the outcome of this procedure. The resulting set of 4645 candidates (from 90 types), together with their occurrence contexts, was then manually annotated by 4 experts. 27 occurrences (0.6%) were eliminated due to incor-

¹⁴cf. Appendix A.

Cat.	Candidates in TrainST			Candidates in WebSample		
	# types	# occ.	%	# types	# occ.	%
VID	180	1404	39,2	30	1900	40.9
IRV	144	1136	31,7	29	1508	32.5
LVC	263	1024	28,6	27	1213	26.1
MVC	4	18	0,5	4	24	0.5
Total	591	3582	100	90	4645	100

Table 6: WebSample w.r.t. TrainST (VMWEs seen at least twice)

VMWE category	P	R	F
VID	0.917	0.961	0.939
IRV	0.873	0.985	0.926
LVC	0.830	0.990	0.903
MVC	0.750	0.750	0.750
All	0.873	0.977	0.922

Table 7: SVM results on WebSample per category

rect sentences, errors (POS, lemma), non-French words or insufficient context. This low rejection rate confirms the good overall quality of the CoNLL corpus. The 4618 remaining candidates were manually labelled as positive (68.7%) and negative.

The WebSample corpus was then used as the testing corpus for our (2)+SVM classifier. As shown in Tab. 7, we obtained the overall F-measure of 0.922, which is comparable to the 0.936 achieved on TrainST and highlights the good repeatability of the method whatever the corpus: our system suffers neither from overfitting nor from sensitivity to the data source. As to per-category results disregarding the MVCs (whose number is negligible), LVCs are the hardest to classify ($F = 0.903$), probably due to their high variability, as illustrated in examples (12–16).

7 Linguistic relevance of the selected features

The selected features prove relevant to the phenomenon of VMWE variability. First, as outlined in Tab. 4, the inserted POS sequences like DET ADJ in (14) always stand at the top of feature rankings (as a REL and/or an ABS feature), whereas this feature is generally not taken into account in other works. Insertions can, indeed, model many relevant phenomena such as the determiner flexibility in (12) vs. (13), allowed modifiers as the adjective in (14), passivization (15) or relativization (16). Inserted POSes including VERB, NOUN or PUNCTUATION appear as the most relevant, maybe because they may suggest a non-VMWE as in *build viaducts_{NOUN}, you construct_{VERB} bridges.*

- (12) *Je prends des_{DET} décisions* ‘I make decisions’
(13) *Je prends deux_{NUM} décisions* ‘I make two decisions’
(14) *Je prends une_{DET} grande_{ADJ} décision* ‘I make a great decision’
(15) *Ma décision est_{AUX} prise* ‘My decision is made’
(16) *C’est la décision que_{PRON} je_{PRON} prends* ‘It is the decision I make’

Note that 3 of the 6 selected features are lexical: they relate to the lemmas of the VMWE components. Without these features, our F-score decreases by 4 points. This confirms the strength of the lexical inflexibility phenomenon (Sec. 2) and the hardness of generalization over unseen data, observed in PST.¹⁵

Some features, considered relevant to VMWE variability, do not appear as selected in Tab. 4. E.g. many VMWEs prohibit the modification of the noun (*to cut acute corners*) or its inflection for number (*to cut a corner*). Given that such variations are often tolerated by LVCs but not by VIDs, the VID candidates may not have been sufficiently numerous to acquire such knowledge about VID constraints.

8 Conclusions and future work

We presented a methodology for selecting a relevant set of features which can be used in a supervised classification framework to solve the task of identifying occurrences of previously seen VMWEs. It is based on defining an initial large set of linguistically-motivated features, and then applying 4 feature selection methods, together with 3 classifiers, to select the optimal sets of features.

The results show that relative features (those reflecting the variability profiles of VMWEs) dominate in the optimal selections. Most of the selected features are based on the properties of external insertions. Such features are never or rarely explicitly considered in previous works.

In sum, our system’s main contributions are: (i) its performances, on par, for French, with the best systems of a recent shared task, (ii) its ability to highlight linguistic properties of VMWEs by a novel combination of features, (iii) its interpretability and classification efficiency due to only 6 features, (iv) its generalization power confirmed by an evaluation on an external large corpus.

The fact that 50% of the optimal features are lemma-based stresses the lexical nature of the

¹⁵The best average PST results limited to unseen data are below $F = 0.29$, even for systems using neural networks and word embeddings (Ramisch et al., 2018).

MWE phenomenon, which implies the particularly acute hardness of generalising over unseen data. We believe that this hardness cannot be overcome by more powerful features (e.g. stemming from distributional semantics), but should rather be handled by coupling MWE identification with unsupervised MWE discovery. In this way, large parts of the unseen data can be transformed into seen data, and their corpus occurrences can complement the manually annotated training corpus. We will address such coupling in future work.

Other perspectives include a detailed error analysis as well as finding strategies for VMWEs seen once, which were disregarded here. The relevant features likely differ among different VMWE classes, since these classes have different syntactic properties. Therefore, it should be useful to perform the feature selection separately for each class. Finally, we could evaluate the genericity of our method by evaluating it on other languages of the PARSEME Shared Task. The feature selection across languages or language families might, indeed, reveal universal characteristics of VMWEs.

References

- Timothy Baldwin and Su Nam Kim. 2010. Multiword expressions. In Nitin Indurkha and Fred J. Damerau, editors, *Handbook of Natural Language Processing*, 2 edition, pages 267–292. CRC Press, Taylor and Francis Group, Boca Raton, FL, USA.
- Gözde Berk, Berna Erden, and Tunga Güngör. 2018. Deep-BGT at PARSEME Shared Task 2018: Bidirectional LSTM-CRF model for verbal multiword expression identification. In *Proceedings of the Joint Workshop on Linguistic Annotation, Multiword Expressions and Constructions (LAW-MWE-CxG-2018)*, pages 248–253.
- Tiberiu Boros and Ruxandra Burtica. 2018. GBDNER at PARSEME Shared Task 2018: Multi-word expression detection using bidirectional long-short-term memory networks and graph-based decoding. In *Proceedings of the Joint Workshop on Linguistic Annotation, Multiword Expressions and Constructions, LAW-MWE-CxG@COLING 2018, Santa Fe, New Mexico, USA, August 25-26, 2018*, pages 254–260. Association for Computational Linguistics.
- Leo Breiman. 2001. [Random forests](#). *Machine Learning*, 45(1):5–32.
- Mathieu Constant, Gülşen Eryiğit, Johanna Monti, Lonneke van der Plas, Carlos Ramisch, Michael Rosner, and Amalia Todirascu. 2017. [Multiword expression processing: A survey](#). *Computational Linguistics*, 43(4):837–892.
- Rafael Ehren, Timm Lichte, and Younes Samih. 2018. Mumpitz at PARSEME Shared Task 2018: A Bidirectional LSTM for the Identification of Verbal Multiword Expressions. In *Proceedings of the Joint Workshop on Linguistic Annotation, Multiword Expressions and Constructions (LAW-MWE-CxG-2018)*, pages 261–267.
- Afsaneh Fazly, Paul Cook, and Suzanne Stevenson. 2009. [Unsupervised Type and Token Identification of Idiomatic Expressions](#). *Computational Linguistics*, 35(1):61–103.
- Gaston Gross. 1988. Degré de figement des noms composés. *Langages*, 90:57–71. Paris : Larousse.
- R. Jackendoff. 1997. The architecture of the language faculty. *Linguistic Inquiry Monographs*.
- Pradnya Kumbhar and Manisha Mali. 2016. A survey on feature selection techniques and classification algorithms for efficient text classification. *International Journal of Science and Research*, 5(5):1267–1275.
- Edward Loper and Steven Bird. 2002. NLTK: The Natural Language Toolkit. In *Proceedings of the ACL Workshop on Effective Tools and Methodologies for Teaching Natural Language Processing and Computational Linguistics*. Philadelphia: Association for Computational Linguistics.
- Erwan Moreau, Ashjan Alsulaimani, Alfredo Maldonado, and Carl Vogel. 2018. CRF-Seq and CRF-DepTree at PARSEME Shared Task 2018: Detecting Verbal MWEs Using Sequential and Dependency-Based Approaches. In *Joint Workshop on Linguistic Annotation, Multiword Expressions and Constructions (LAW-MWE-CxG-2018) at the 27th International Conference on Computational Linguistics (COLING 2018)*, pages 241–247.
- Geoffrey Nunberg, Ivan A. Sag, and Thomas Wasow. 1994. Idioms. *Language*, 70:491–538.
- Caroline Pasquer, Carlos Ramisch, Agata Savary, and Jean-Yves Antoine. 2018. [VarIDE at PARSEME Shared Task 2018: Are Variants Really as Alike as Two Peas in a Pod?](#) In *Proceedings of the Joint Workshop on Linguistic Annotation, Multiword Expressions and Constructions (LAW-MWE-CxG-2018)*, pages 283–289. Association for Computational Linguistics.
- F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. 2011. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830.
- Carlos Ramisch, Silvio Ricardo Cordeiro, Agata Savary, Veronika Vincze, Verginica Barbu Mititelu, Archana Bhatia, Maja Buljan, Marie Candito, Polona Gantar, Voula Giouli, Tunga Güngör, Abdelati

Hawwari, Uxoia Iñurrieta, Jolanta Kovalevskaitė, Simon Krek, Timm Lichte, Chaya Liebeskind, Johanna Monti, Carla Parra Escartín, Behrang QasemiZadeh, Renata Ramisch, Nathan Schneider, Ivelina Stoyanova, Ashwini Vaidya, and Abigail Walsh. 2018. Edition 1.1 of the PARSEME Shared Task on Automatic Identification of Verbal Multiword Expressions. In *Proceedings of the Joint Workshop on Linguistic Annotation, Multiword Expressions and Constructions (LAW-MWE-CxG-2018)*, pages 222–240. ACL. <https://aclweb.org/anthology/W18-4925>.

Livnat Herzig Sheinflux, Tali Arad Greshler, Nurit Melnik, and Shuly Wintner. 2018. *Verbal MWEs: Idiomaticity and flexibility*, pages 5–38. Language Science Press, to appear.

Regina Stodden, Behrang QasemiZadeh, and Laura Kallmeyer. 2018. TRAPACC and TRAPACCS at PARSEME Shared Task 2018: Neural Transition Tagging of Verbal Multiword Expressions. In *Proceedings of the Joint Workshop on Linguistic Annotation, Multiword Expressions and Constructions (LAW-MWE-CxG-2018)*, pages 268–274.

Shiva Taslimipoor and Omid Rohanian. 2018. SHOMA at Parseme Shared Task on Automatic Identification of VMWEs: Neural Multiword Expression Tagging with High Generalisation. *CoRR*, abs/1809.03056.

Agnès Tutin. 2016. Comparing morphological and syntactic variations of support verb constructions and verbal full phrasemes in French: a corpus based study. In *PARSEME COST Action. Relieving the pain in the neck in natural language processing: 7th final general meeting*, Dubrovnik, Croatia.

Jakub Waszczuk. 2018. TRAVERSAL at PARSEME Shared Task 2018: Identification of Verbal Multiword Expressions Using a Discriminative Tree-Structured Model. In *Proceedings of the Joint Workshop on Linguistic Annotation, Multiword Expressions and Constructions (LAW-MWE-CxG-2018)*, pages 275–282. Association for Computational Linguistics.

Nicolas Zampieri, Manon Scholivet, Carlos Ramisch, and Benoît Favre. 2018. Veyn at PARSEME Shared Task 2018: Recurrent Neural Networks for VMWE Identification. In *Proceedings of the Joint Workshop on Linguistic Annotation, Multiword Expressions and Constructions (LAW-MWE-CxG-2018)*, pages 290–296.

Daniel Zeman, Jan Jan Hajič, Martin Popel, Martin Potthast, Milan Straka, Filip Ginter, Joakim Nivre, and Slav Petrov. 2018. CoNLL 2018 shared task: Multilingual parsing from raw text to Universal Dependencies. *Proceedings of the CoNLL 2018 Shared Task: Multilingual Parsing from Raw Text to Universal Dependencies*, pages 1–21.

A Appendix: List of the verbal multiword expressions in WebSample

Frequency in TRAIN	IRV	LVC	VID
High	s'étendre se voir se trouver se retrouver s'élever se situer s'engager se produire se dérouler se rendre	faire apparition avoir droit jouer match poser question faire appel avoir besoin rendre hommage avoir chance jouer rôle	il s'agir il convenir mettre fin avoir lieu il y avoir faire partie il falloir tenir compte faire l'objet prendre part
Median	s'efforcer se servir se baser s'agir s'envoler se lever s'adonner s'interroger s'élancer	conclure accord mener opération porter choix rendre service disputer épreuve avoir perception livrer bataille présenter signe donner concert	prendre au piège en finir avoir affaire venir à bout ne pas payer de mine vouloir dire s'en aller faire écho mettre sur pied mettre en lumière
Low	s'acquitter s'engouffrer se ressentir se donner se partager s'empresser se renseigner se signaler s'investir se promener	faire traduction avoir ennui prendre sanction faire entrée inscrire but effectuer tournée dresser horoscope signer victoire réserver accueil	tourner mal couper du monde être au rendez-vous tenir responsable faire les frais être l'occasion mettre sur la table prendre le dessus tel être le cas faire le plein

Table 8: Verbal multiword expression types (for IRV, LVC and VID categories) in WebSample (mentioned in Table 6).

MVC
entendre parler faire remarquer faire savoir laisser tomber

Table 9: Verbal multiword expression types (for MVC category) in WebSample (mentioned in Table 6).

B Appendix: Features used for VMWE identification in the state-of-the-art works

	Systems of the PARSEME Shared Task										Our system	
	(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	Initial set of features	Auto. selected features
ABSolute (categorical) and RELative (binary) features												
VMWE category (e.g. LVC)	yes			yes	yes				yes	yes	yes	yes
VMWE surface form	yes	yes	yes	yes			yes				no	no
VMWE whole set of lemmas									yes		yes	yes
VMWE separate lemmas	yes	yes	yes	yes	yes	yes		yes	yes	yes	yes	yes
VMWE POS	yes	yes	yes	yes		yes	yes	yes	yes		yes	no
VMWE length				yes							no	no
<i>VMWE morphosyntactic tags</i>			yes	yes	yes	yes			yes		yes	no
<i>VMWE syntactic dependencies</i>												
Connection	yes				yes				yes		yes	no
Quasi-connection									yes		yes	no
Labels	yes			yes	yes		yes	yes	yes		yes	no
<i>Insertions:</i>												
Sequences of POS									yes		yes	yes
Number									yes		yes	no
REL									yes		yes	yes
VMWE separate lemmas									yes		yes	yes
VMWE POS									yes		yes	no
<i>VMWE morphosyntactic tags</i>									yes		yes	no
<i>VMWE syntactic dependencies</i>												
Connection									yes		yes	no
Quasi-connection									yes		yes	no
Labels									yes		yes	no
<i>Insertions:</i>												
Sequences of POS									yes		yes	yes
Number									yes		yes	no
External word embeddings		yes					yes				no	no
Seen-in-train F-score (French)	0.8172	0.7657	0.7619	0.7506	0.7371	0.7290	0.7286	0.7084	0.7003	0.6224		0.8207

Table 10: Relevant features for VMWE identification and performances for the previously seen VMWEs for our system vs. the systems in the PARSEME Shared Task (Ramisch et al., 2018): (a) Waszczuk (2018), (b) Taslimipoor and Rohanian (2018), (c) Boros and Burtica (2018), (d) Stodden et al. (2018), (e) Moreau et al. (2018) (CRF-DepTree-categs system), (f) Moreau et al. (2018) (CRF-Seq-nocategs system), (g) Berk et al. (2018), (h) Ehren et al. (2018), (i) Pasquer et al. (2018), (j) Zampieri et al. (2018)