Listener evaluations of violins made from composites

Tim Duerinck, Geerten Verberkmoes, Claudia Fritz, Marc Leman, Luc Nijs,
Mathias Kersemans, Wim van Paepegem

► To cite this version:

Tim Duerinck, Geerten Verberkmoes, Claudia Fritz, Marc Leman, Luc Nijs, et al.. Listener evaluations of violins made from composites. Journal of the Acoustical Society of America, 2020, 147 (4), pp.2647-2655. 10.1121/10.0001159 . hal-02937610

HAL Id: hal-02937610

<https://hal.science/hal-02937610>

Submitted on 11 Dec 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Listener evaluations of violins made from composites.

Tim Duerinck¹, Geerten Verberkmoes¹, Claudia Fritz², Marc Leman³, Luc Nijs³, Mathias Kersemans⁴ and Wim Van Paepegem⁴

¹Instrument Making – School of Arts Gent KASK & Royal Conservatory, Nederpolder 26, 9000 Ghent, Belgium

²Institut Jean le Rond d'Alembert, Sorbonne Université / CNRS, 4 place Jussieu, 75005 Paris, France.

³Department of Art, music and theater sciences, Ghent University, Sint-Pietersnieuwstraat 41, B4 9000 Ghent, Belgium

⁴Department of materials, textiles and chemical engineering, Ghent University, Technologiepark 46, B-9052 Zwijnaarde, Belgium.

<https://doi.org/10.1121/10.0001159>

Published in JASA

(Received 9 December 2019; revised 6 March 2020; accepted 8 April 2020; published online 28 April 2020)

[Editor: Tamara Smyth]

ABSTRACT

For centuries, wood, and more specifically spruce, has been the material of choice for violin top plates. Lately, carbon fiber instruments have entered the market. Some studies show that composite materials have potential advantages for making instruments (Damodaran A. et al. (2015)). However, no studies exist that evaluate violins made of different composite materials as judged by listeners. For this study, six prototype violins, differing only by the material of the top plate, were manufactured in a controlled laboratory setting. The six prototype violins were judged by experienced listeners in two double-blind experiments. In contrast to popular opinion that violins made from carbon have or lack a specific sound quality, the study provides insights in the diverse sounds and timbres violins from fiber-reinforced polymers can create. It allows to investigate the links between the perception and the variations in material properties of the soundboards. Additionally, as neither players nor listeners are acquainted with these instruments, these results provide an interesting view on what type of qualities of violin-like sounds are preferred by listeners.

I. INTRODUCTION

The soundboard of a violin has, with few exceptions, always been made out of wood, more specifically of high quality spruce (*Picea Abies*). However, due to environmental changes and other factors, wood for music instruments is said to be depleting, becomes more expensive, but also lowers in quality¹. Meanwhile, the increase in use of technical composites such as carbon fiber reinforced polymer (CFRP) and their qualities with regard to moisture stability and durability, has generated research that investigates their material properties and compares them to wood²⁻⁴. Consequently, in recent years, research has resulted in prototypes and commercially available instruments made from composites⁵⁻⁹. However, no comparative studies that assess the sound of composite violins with the same design and setup under controlled conditions is found in literature. Most studies are limited in this regard because the violins to be tested were constructed independently from the research and can therefore vary in a number of attributes unknown to the researcher, like the model, quality of the materials used, construction method or setup¹⁰⁻¹⁴. In the present study, the influence of the soundboard material is our focus, as a consequence, all other parameters are taken as similar as possible among the tested violins. Under these conditions, we consider the following questions: How do these composite violins sound? Which variations in the construction of the soundboard influence the volume and timbre of the sound? What possible quality factors are more important to the listeners? What possibilities do composite materials offer to expand on the violin's sonic palette as we know it today?

To answer these questions six composite violins were designed and built with top plates from different materials. We ran two experiments with the instruments; the first consisted of an evaluation task with 37 participants, the second of a selection task with 40 participants. In both cases, we examined how experienced listeners judged the timbre of the instruments on a broad

spectrum of possible qualities. We examined which instruments were favored, and why, in order to shed light on what sound listeners prefer from such composite violin.

II. CONSTRUCTION OF THE PROTOTYPE VIOLINS

The goal was to build all violins identical except for the top plate, which was made from different materials between the violins. To achieve this goal, all prototype violins were constructed by the same luthier. A carbon fiber reinforced polymer (CFRP) produced by vacuum assisted resin transfer method (VARTM) was chosen as a quick and reliable way to produce the back, sides and neck in one piece in a consistent way (Video¹⁵ showing the production process on a cello). The soundboards were made either from a selection of four composite materials or from spruce, which was added as a reference material (Fig. 1):

1. UDFlax: unidirectional flax fiber reinforced polymer.
2. UDC: unidirectional carbon fiber reinforced polymer.
3. TwillC: laminate of twill woven and unidirectional carbon fiber reinforced polymer.
4. Sandwich: sandwich structure consisting of CFRP skin and an aramid honeycomb core.
5. Spruce: Picea Abies.

The TwillC violin was produced twice (TwillCA and TwillCB) to check the consistency of the influence of the material and production methods on the sound of the violin. Together, these six prototypes give us a variety in material properties like higher damping (UDFlax), different degrees of anisotropy (TwillC & UDC), and a low weight soundboard (Sandwich). The violin with a soundboard from Spruce serves as a benchmark material.

As the used composite materials have a higher longitudinal Young's modulus than wood, the thickness of the laminate can be decreased in order to have a similar bending stiffness as a spruce

78 plate. The bending stiffness of a plate is thought to be crucial to the sound of a wooden
79 instrument¹⁶, therefore it is taken as a guide to make these novel composite violins. Soundboards
80 of old conventional violins deform most often along the axis of the instrument¹⁷. Contemporary
81 luthiers therefore aim to make an arching stiff enough to be durable, without making it too stiff,
82 which is thought to be disadvantageous to the sound production of the violin¹⁶. As composite
83 materials offer a variety in anisotropy, the bending stiffness along the axis of the instrument
84 (D11) was chosen as the primary design criteria. The bending stiffness (or plate rigidities) are
85 derived from the ABD-Matrix of the Classical Laminate Theory. The required thickness for each
86 of these materials was calculated using the eLamX² software package¹⁸. The composite
87 soundboards were produced by VARTM. More detailed information on the materials, model, and
88 production method are provided in Appendix and¹⁹. Weight of the soundboards, calculated
89 bending stiffness's D11 (along the axis/longitudinal), D22 (transversal/radial), D66 (shear) and
90 damping of the materials are provided in Table I. The plate rigidities show the variety in
91 anisotropy between the materials. The damping is an approximation derived from the measured Q
92 factor of the first frequency of flat beams which were made in our lab by VARTM (Appx). As
93 this damping value is dependent on the mode measured, the exact value could be misleading.
94 Therefore the damping is given as an approximation in relation to spruce (0), our benchmark
95 material.

96 The spruce soundboard was carved by a luthier using templates that match the arching of the
97 composite plates. This spruce soundboard was then given a thin clear oil varnish coating. The
98 soundboards were given a simplified sound hole design and were fitted with a conventional
99 spruce bass bar of high quality. The instruments were mounted with a high quality *Aubert* bridge
100 (Savarez ©), spruce soundpost, *Wittner* tailpiece, chinrest, and *fine-tune pegs*® (WITTNER®)

GmbH & Co.KG). Strings were *Dominant* for G, D, A (Thomastik-Infeld GmbH ©) and *Kaplan* for E (D’Addario & Company, Inc.©). A second independent luthier was then asked to examine the instruments for any (accidental) differences in the set-up. In this way, a small difference (1 mm) in the placement of the bridge of the UDFlax violin was corrected.

III. THE EVALUATION EXPERIMENT

A. Methodology

Experienced listeners with relevant musical experience were invited to take part in the experiment. The group of participants included (student) instrument makers, musicians, music teachers and composers. Of the 37 listeners, 33 said that they play a music instrument on a regular basis. Their experience ranged from 3 to 52 years of experience with an average of 15.1 years of playing a music instrument. In the weeks before the experiment, potential participants were told that they would have to evaluate on an aural basis seven violins, of which at least one was made of carbon and one made from flax fibers. This information was given to raise interest and recruit a sufficient amount of experienced listeners. As a consequence, some of the recruited listeners were familiar with the research subject (new materials for violins) yet they did not know how many “new” instruments would be used in this test or if there would be one or multiple instruments with a wooden soundboard and/or conventional violins, as a reference.

In the first listening test the members of the audience, rated the six violins individually on a number of attributes. This method was chosen as it is a common way to judge instruments or musicians in competitions, giving the test a high verisimilitude. For each violin, the attributes were presented on a 8-point Likert scale between two opposite adjectives. Most invited participants had Dutch as their mother tongue. As no study that uses Dutch words to describe the

sound of violins was available in the literature, a common language had to be defined with the participants. First a list of English words was compiled from scientific literature^{11, 20}. Secondly, multiple listeners who would take part in the experiment were asked which words they would like to use for judging violins in Dutch and English as well as how they would translate these words between the two languages. Also the participants were asked how they would like to be questioned. Through this method an expert audience negotiated and agreed on the meaning of pairs of adjectives that could be understood as each other's opposite, with the Dutch translation in brackets: warm (warm) – cold (koud), clear (helder) – dull (dof), loud (luid) – quiet (stil), soft (zacht) – harsh (hard), open (open) – closed (gesloten), good (goed) – bad (slecht), nasal (nasaal) – clear (helder), round (rond) – sharp (scherp), powerful (krachtig) – weak (zwak), rich (rijk) – poor (arm), bright (briljant) – dim (glansloos). Although a unipolar scale is usually recommended in this type of research²⁰, the participants preferred a bipolar scale.

Participants could fill in the Likert scale for each presented pair of opposite adjectives, or tick a box 'I don't know' (Appx). The listening test took place in a 98-seat concert hall at the Royal Conservatory of Ghent (Mengal, campus Hoogpoort) – School of Arts Ghent. The violin player was a professional musician. Before the experiment, the violin player only tried the instruments on one occasion one month before the experiment. As each instrument would be played at least two times, which resulted in a total experiment time of 41 minutes, the first experiment was performed with one player. Repeating the entire experiment with a second player was found to be less appropriate, given the fact that the listener's task is quite demanding and there is a risk perceptual fatigue influences the results.

First, as requested by the participants, four random instruments (decided by draw) were played (Spruce, UDFlax, TwillCB and Sandwich) to allow the listeners time to get familiar with the

146 acoustics of the hall and the sound of the prototype instruments. The order in which the
147 instruments were presented for the actual experiment was decided by random draw and was:
148 TwillCA(1), TwillCB, Sandwich, UDFlax, TwillCA(2), Spruce, UDC. TwillCA was presented
149 two times unbeknownst to the audience. If TwillCA scores similar both times, this would be a
150 good indication that a difference between violins can be taken as a difference in the sound
151 produced and not a difference in playing or order effect or fatigue.

152 One after another, with approximately 25-30 seconds in between, each violin was played and the
153 audience was asked to rate the same set of pairs of adjectives for each violin. After the first
154 sequence was completed, the same sequence was repeated. Listeners could indicate their overall
155 preferred, second-preferred and least-preferred instrument, and their preferred instrument
156 regarding warmth, power and richness. For that additional assessment, the audience was given
157 the possibility to hear violins again in pairs of their choice. This resulted in the following
158 additional comparison: TwillCB and UDC; Sandwich and UDFlax; TwillCA(1) and TwillCA(2).
159 It has to be noted that the only violin which was not asked for the additional assessment was the
160 one with a wooden (spruce) top. Additionally, the listeners were asked which adjectives they
161 considered to be most important to judge the sound of a violin. Finally, some details regarding
162 their musical experience were asked as well.

163 During the entire evaluation experiment, the violinist was positioned on stage approximately 1m
164 behind a lightweight polyester fabric screen. The violin player was blinded with a sleeping mask
165 and the scent of the instruments was covered with a perfume. The instruments were handed to the
166 musician in the predetermined order by a researcher. The lights on stage were dimmed during the
167 test, but left on in the seating area, in order to make sure that the audience could not distinguish
168 the different instruments behind the screen. The violinist played the instruments with her own

bow. As in previous studies the bow is regarded in this experiment as an extension of the player's body¹²⁻¹⁴. She played a musical fragment of her own choice (88 seconds) to evaluate the violins, as a musician would normally do when evaluating an instrument. The experiment was recorded for further analysis. The violin player was not questioned during the test, to minimize the time in-between the playing of the instruments. After the test the violin player was asked by the researcher what her favorite instrument was, and if she had any other remarks.

B. Results

First, we examined how the participants described the sound of each violin, based on presented pairs of opposite adjectives. The ratings on each bipolar scale for each violin were compared with a null-hypothesis, using a one-sample t-test with the IBM SPSS® software. The one-sample t-test determines if the population mean is significantly different from a given value or not. This results in a probability value (p-value) providing strong ($p\text{-value} < 0.05$) or weak ($p\text{-value} < 0.1$) evidence of this deviation from the given value. The null-hypothesis (H_0) was that the audience did not favor one adjective over the other in a pair in order to describe the sound of a violin, which would result in a mean score of 3.5. Strong and weak evidence to reject the null-hypothesis was found for each of the presented violins in a number of cases (Table II). Through this method, adjectives could be objectively linked to the sound of the instruments.

To investigate how reliable these results were, a paired t-test of TwillCA(1) and TwillCA(2) was performed. This test revealed a statistically significant improvement ($p\text{-value} < 0.05$) in the rating of TwillCA(2) on four (out of 11) of the bipolar scales powerful – weak (+0.946), loud – quiet (+0.686), bright – dim (+0.829) and good – bad (+0.781) in comparison to the rating of TwillCA(1). This is likely due to the order effect and is discussed in section V.

Fig. 2 shows the rating for two bipolar adjectives: rich – poor and warm – cold. Rich has been shown to be the most important quality for violinists in a previous study²¹, while warm is often used to describe the sound of conventional wooden violins in comparison to other materials. TwillCB, UDFlax and UDC show large statistic deviations from the expected mean a random distribution would show towards *warm*. For *rich – poor* only TwillCB and Spruce show a statistically strong deviation towards *rich*. The scale from 2 to 5 was chosen as all our calculated means +/- standard error of the mean (SEM) fit within this scale (Appx).

Fig. 3 shows the selection of ‘best’, ‘second best’ and ‘worst’ instrument overall. TwillCB and UDFlax were mostly chosen as ‘best’ (9). UDC was most often chosen as ‘second best’ (9). Sandwich was chosen most often as ‘worst’ (12).

Listeners were asked which instrument they found “most rich/most powerful/most warm” (Fig. 4). Interestingly TwillCA(2) was preferred more than TwillCA(1), this corresponds with a consistently higher mean score on positive attributes like: *powerful* (+0.95), *bright* (+0.83), *good* (+0.78) and *loud* (+0.69) (Figures Appx). The differences could be explained by the order. TwillCA(1) was the first to be heard, TwillCA(2) came after UDFlax and before Spruce. As UDFlax was never chosen on the question ‘Which instrument did you find most powerful?’, TwillCA(2) may have appeared more powerful in contrast.

Listeners were asked which pair of adjectives they found were “most important to judge the quality of a violin?” (Fig 5). Three of the bipolar pairs were prompted by the previous question “Which instrument did you find most rich/most powerful/most warm”, and so listeners might have a positive bias towards these pairs. *warm – cold* (13) and *rich – poor* (12) scored higher than *powerful – weak* (2). This finding can be interpreted as follows: either these listeners find the power of the sound of a violin secondary to the sound color, or they could have (either

intentionally or unintentionally) favored sound color over power in an effort to rate attributes which are thought to be related to wood. The pairs *loud – silent*, *harsh – soft* and *good – bad* were never written down and are therefore not included in Figure 5.

When we examine the Root-Mean-Square (RMS) level of the audio recording made during the evaluation experiment (Fig. 6a) the Sandwich violin stands out with the highest RMS level. RMS level is a measure of the average value of a waveform over time and is an approximation of the acoustic sound level perceived by our ears. The violins with a top plate made from a material with a higher degree of anisotropy: UDC, UDFlax and Spruce have a slightly lower RMS value compared to the other violins. To rule out the effect of the player, additional acoustic radiation measurements of the violins were performed with an impact hammer in an anechoic chamber (Fig. 6b, more info in appendix). These measurements show that the Sandwich violin is the most effective sound radiator between approximately 400 and 4000 Hz. UDFlax is the least effective sound radiator between the measured violins above 400 Hz. Below 400 Hz, the violins with a soundboard made from unidirectional composites, UDC and UDFlax, have the highest average acoustic response.

The violin player’s favorite was the Sandwich violin because it was “easy to produce a lot of sound”. Her least favorite was UDFlax because she “felt she had to work very hard on the instrument”. The violin player had a suspicion that violins 1 and 5 were the same instrument, which was the case (TwillCA).

IV. THE SELECTION EXPERIMENT

A. Methodology

The musician, the acoustics of the hall and the procedure of the evaluation experiment have surely affected the results of our first experiment. Especially a significant order effect was observed in our measurements, which makes the interpretation of the results more difficult and limits the possibility to draw conclusions. Therefore, we conducted a second listening experiment to verify whether similar trends could be observed with a different protocol, based on pairwise comparisons. To limit the fatigue of the listeners, the number of comparisons should not be too large, which reduces the number of instruments that can be used. Three violins from the first experiment were selected: UDFlax, TwillCB and Sandwich. Both UDFlax and TwillCB were preferred in the first experiment, while Sandwich was evaluated most often as “worst” violin.

It is presumable that listeners perceive and judge the sound of a violin in relation to all other presented instruments. As the composite violins sound rather different from conventional violins, one could argue that the listeners’ perception of these violins could be affected if a conventional violin was presented during the same test and that our results would only hold in the particular context of these prototype violins. An additional wooden instrument was therefore added in this experiment. The violin was a Stradivarius model made by the same luthier and was set-up with the same bridge, strings, tailpiece, chinrest and pegs as the other composite instruments. Sound radiation measurements (Fig. 6b) show how this conventional violin has a very different frequency response function from the prototype violins. Considering that one of the main goals of this study is to link the perceptual evaluations of the composite violins to differences in their construction in order to shed light on traditional instruments manufacturing, the conventional violin was thus only used to ensure the relevance of the listeners’ evaluations of these prototype violins when taking into account regular violins as well. Therefore only the pairs comparing two composite violins were analyzed.

In this second experiment, the four violins were presented in pairs to 40 listeners, all members of the Ghent University Orchestra (GUSO). The listeners had an average of 14 years of experience playing music instruments. Fifteen listeners were violin players. The instruments were played behind the same screen as during the first experiment. The selection experiment took place in a 200-seat hall Trechterzaal, Thermanal, Ghent University.

The format of the listening test was based on the one used in¹⁴. The test was conducted twice with a different violin player for each part. The violin players were members of the orchestra. To judge each pair of violins, the musicians first played a scale (34 seconds) on each violin, followed by a short piece of music of their own choice (20-30 seconds) on each violin (Appx). This so-called ABAB format of the experiment made it possible for listeners to hear each violin twice, that is both before and after the other violin¹⁴. In this way, each musician presented all the violin pairs in ABAB format (Table III). Between the two musicians, the order in which the pairs were presented and which violin went first in a pair was changed over the two tests so the order of presentation was balanced (Appx). In the questionnaire, the listeners were asked which instrument they preferred and why. Listeners could skip a certain pair if they did not have a preference. Secondly, they were given three quality factors: ‘better projection’, ‘better balance’ and ‘better sound color’. They were asked to choose any number of those quality factors that explained why they chose the said violin. If they chose ‘better sound color’, they could further specify their choice using a list of selected adjectives to describe that sound color in more detail. They had the option to add additional remarks to explain their preference. (Questionnaire Appx).

B. Results selection experiment

As a summary of the results shows in Table III, TwillCB was preferred by most of the listeners over UDFlax with both violin players. Listeners clearly favored TwillCB over Sandwich when

listening to player 1 but did not in the case of player 2. UDFlax was favored over Sandwich in both cases.

Listeners based their preference mostly on sound color. Only in the case of Sandwich an equal number of listeners gave projection as their reason of preference (Figure in Appendix). As listeners used the adjectives to further specify why they favored the sound color of a certain violin, they ended up with similar choices of adjectives as in the first experiment. UDflax was described most as *warm* and *round*, TwillCB as *clear* and *open*, and Sandwich most as *powerful*, *bright* and *rich* and least as *warm* (Fig.7). Due to the nature of this test, listeners could only describe the sound of the violin they favored; *harsh*, *sharp* and *nasal* are most often interpreted as negative attributes when used to describe the sound of a violin. This explains why they were not often picked as adjectives to describe the sound color of the favorite instrument. As *nasal* was never picked in our selection experiment, it is not included in the graph.

V. DISCUSSION

In this study, the potential of different composite materials for the soundboards of violins was investigated. Six violin-shaped instruments were built in a controlled setting and investigated in two listening experiments.

The presented results describe the listeners' perspective. In the evaluation and selection experiment we investigated which instruments were preferred and how listeners described their sound. Do some project better than others? Do some have a sound color which is more preferred? What possible quality factors are more important to the listeners?

As expected, our experiments show that by using a variety of composite materials for soundboards of violins, a wide range of sounds and timbres can be produced. As the use of these

composite materials allow violin makers to change the sound of a violin in a number of ways, they can offer new artistic opportunities for violin players and composers to explore. Therefore, these findings could have implications for the future development and production of music instruments as well as future musical compositions and performances.

The low ratio of stiffness/density of the flax composite material resulted in a higher weight for the finished soundboard in comparison to the other materials. In the acoustic radiation measurements, UDFlax was the least effective sound radiator between our violins. It is therefore not surprising that the instrument was the least associated with attributes linked to loudness, such as powerful and projection. Our results confirm the theory²² that a material with a lower ratio of stiffness/density and higher damping is a less efficient sound radiator, resulting in a less powerful or loud sound. Although this instrument was the least favored by our violin player in the evaluation task, it was preferred by many listeners for its warm and round sound color.

The instrument made from a lightweight, low damping and low anisotropy sandwich material consisting of carbon and an aramid honeycomb (Sandwich) was mostly chosen as most powerful, had the highest mean for loud, had the highest RMS value and sound radiation measured and was the only instrument being favored largely for its projection. Yet this instrument was the least preferred in our evaluation task and least picked as favorite in our selection task when played by the first violin player, but was more liked when played by the second player. These findings are in line with a previous study¹⁴ showing that violins with the best projection are not always chosen as favorite by listeners. Listeners' evaluations can be influenced by the performer's way of playing the instrument. In our evaluation experiment, this violin's sound color was described as harsh. This is less clear in our selection experiment, as the nature of this experiment emphasizes the positive qualities of each instrument.

UDC, with a higher anisotropy than TwillCA and TwillCB, was described as round and soft and was chosen less as powerful. This could be an indicator that for composite materials, a higher degree of anisotropy results in an instrument with a round and soft tonal color preferred by many listeners, but with a less powerful sound. This is in line with the simulations performed by Viala²³ that showed variations in anisotropy to have a significant effect on certain modes of the violin. Indeed, the modes for which the radial direction is important will have a lower frequency and more damping when the radial stiffness (E_r) is lower (which is the case when the anisotropy is high), which intuitively goes well with a less powerful but rounder sound. More research is definitely needed to investigate this aspect and correlate it with numerical predictions.

In our evaluation experiment, two violins were preferred more than others. One had a soundboard from a laminate of unidirectional and woven carbon (TwillCB), the other was made from unidirectional flax (UDFlax). Although UDFlax had the least powerful sound among our prototypes, its sound color being described as warm, soft and round still made it a favorite for many listeners. The other favorite instrument TwillCB had a sound color described as warm and rich. In our selection experiment, TwillCB was favored over UDFlax by the listeners with both players. The listener's preference in our experiments seem mostly guided by sound color, and less by projection or loudness of the instruments. However, when both instruments have a favorable sound color, the instrument with the better projection was favored between the two most preferred violins. In both experiments, listeners indicated to find a warm sound an important quality parameter, followed by adjectives such as clear, open, round and rich.

When we compare the results from TwillCA to TwillCB, the two instruments with identical top plate materials, it is clear that the instruments were rated differently in our evaluation task. More research is needed to understand what is the cause of these differences. When we examine the

scores of TwillCA(1) and TwillCA(2) we observe some differences in attributes that are linked to loudness like powerful or loud. A possible explanation for this finding is that TwillCA(2) was presented after UDFlax, the least powerful and loud instrument. As the listeners had just heard UDFlax, they rated TwillCA(2) in relation to this, resulting in a different score in adjectives related to projection. As TwillCA(1) was the first violin played, it could have been affected by the order in which the instruments were presented. The order effect of the sequence on the rating of violins is not well documented in literature. Research on judge bias in the Idol series shows that in a sequence of seven, the score of the first contestant has the highest negative mean bias²⁴. As such, it is feasible that TwillCA(1) was affected by a negative bias due to the order effect.

The instruments presented in this study differ from a classic violin in a number of ways, therefore we cannot directly extrapolate the results from our violin with a spruce soundboard to that of wooden violins in general. We can only say that between our prototypes, the violin with a spruce soundboard was not favored over the full-composite violins and did not stand out in a particular way with regard to tonal color or projection. Future research has to be performed in order to allow for more direct comparisons between instruments with composite top plates and truly conventional, wooden violins. An alternative road future studies could take is to investigate the full-composite instruments as a class of sound-generators of their own, with their own sonic possibilities, and be less concerned about a comparison with their conventional counterparts.

As the experiments presented investigate the sound of these violins from a listener perspective, the perception of these violins by violin players is outside the scope of this study. As the preference of the violin player in our first experiment was the exact opposite of the trend shown by the listeners, it is evident this must be examined further in future experiments. Additionally, examining how these instruments are perceived when they are accompanied by an orchestra or

played in an ensemble can provide valuable psychoacoustic insights. Finally, the vibro-acoustical behavior of these violins could be further examined through modal analyses, which would give a deeper understanding on the effect of the material properties on the body shell response of music instruments.

VI. CONCLUSION

Contrary to popular opinion among violin players, there is no specific sound property or quality that we can assign to the material group of fiber reinforced composites. As a consequence no generalizations like ‘the sound of carbon violins lack warmth’ hold in our experiments. Composite materials allow to create violins with a large diversity in sounds and therefore offer possibilities to change the sound to the criteria of the player. In theory, by only varying the material of the soundboard, the sound of a violin could be changed to fit the requirements of the player. Our results follow the logic that soundboards which are more lightweight and have a lower anisotropy are more efficient sound radiators than heavier soundboards with a higher anisotropy. However, the influence of more or less anisotropy on the energy output should be further investigated, as this study only had a limited amount of instruments to compare and draw conclusions from.

Although all our participants can be considered experienced listeners, individuals prefer different violin-like sounds. Depending on which violin player is playing, the preference of the listener can shift between instruments. Although the sound of some violins was favored more than others, there was no such thing as the ‘best’ violin sound overall.

Our results indicate that when violins are played consecutively the order effect is large. Violinmaking or playing competitions, should adapt their methodology accordingly to ensure a fair evaluation of each violin or musician.

This research provides insight in how violins with soundboards from different composites can sound, the possible advantages these materials can offer in relation to the sound they produce as a soundboard for violins, and which of these violins were favored by listeners. However, composite materials offer a great diversity of fibers, polymer matrix and core materials that must still be examined. While the craftsmanship of making good wooden violins has evolved over centuries, resulting in an optimization of the realization of the material's potential. Composite instruments are very new and may require a new kind of craftsmanship in order to obtain optimal results. Composite instruments commercially available today might need more development in order to realize the full potential of these new materials. More research is needed if we wish to discover more regarding both the potential of composite materials for music instruments, and how to realize that potential.

Acknowledgements

We thank all musicians and listeners who took part in these experiments for their dedication and patience during the experiments. We thank FWO (Research Foundation Flanders grant nr. 1180217N) for funding this research. Ghent University and Hogent – School of Arts Ghent for providing logistic support. We would like to thank Matthieu Libeert for consulting throughout production of the composite parts using VARTM. Thanks also to Patrick Housen, who recorded the evaluation experiment. Thanks to Lineo for donating FLAXTAPE™ that was used to make the UDFlax violin.

Appendix

Information about materials and production method of the violins. The composite violin geometry is based on the dimensions of a conventional violin model (Table I), but adapted to facilitate fabrication using a mold. The height of the ribs is 30mm.

Table I: Dimensions of the top plate used for the violin prototypes.

Top plate dimensions	Dimensions (mm)
Length	356
Width upper bout	165
Width center	107
Width lower bout	206

The bodies (back, sides and neck) were made from twill woven mats of carbon fiber reinforced polymer (CFRP) produced by vacuum assisted resin transfer method (VARTM). The carbon fiber used was AKSACA™ A-38, 200 tex (3k) the matrix was EPIKOTE™ Resin MSG™ RIM 135 mixed in a 100:30 weight ratio with EPIKURE™ Curing Agent MGS™ RIMH 137. After VARTM the CFRP was post-cured in a curing oven following the specifications of the manufacturer. After production the quality of the carbon fiber bodies were visually inspected for quality and consistency in the product. Through this method, 3 pieces were eliminated for further use and additional pieces were made.

Table II: Material properties from literature used to calculate the required thickness of the composite soundboards.

Materials	Longitudinal Young's Modulus El (Gpa)	Transverse Young's modulus Et (Gpa)	Density (kg/m³)	Source
Spruce	10 – 14.8	0.36 – 0.73	382 – 495	Spycher M. (2008)
UD Carbon	118.4 – 119.13	8.85 – 10.18	1528.6	Kersemans M. (2014)
UD Flax	26.6 – 29.8	3.31	1330	Phillips S. (2011)
Woven Carbon	62.7 – 68.7	62.7 – 68.7	1540 – 1610	CES Edupack 2019
Aramid Honeycomb	0,0000149	0,0000149	32.5	CES Edupack 2019

Sources:

Spycher M., Schwarze F., Steiger R. (2008) Assessment of resonance wood quality by comparing its physical and histological properties. *Wood Sci Technol* 42:325–342.

Kersemans M., Martens A., Lammens N., Van Den Abeele K., Degrieck J., Zastavnik F., Pyl L., Sol H., Van Paepegem W. (2014) Identification of the Elastic Properties of Isotropic and Orthotropic Thin-Plate Materials with the Pulsed Ultrasonic Polar Scan. *Experimental Mechanics* 54:1121–1132.

Phillips S., Lessard L. (2011) Application of natural fiber composites to musical instrument top plates. *Journal of Composite Materials* 46(2): 145–154.

CES Edupack 2019 19.2.0 (2019) Granta Design Limited, Cambridge, United Kingdom.

As the materials varied in Young's modulus, but needed a similar longitudinal bending stiffness for consistency, the required thickness for each material was calculated based on a thickness pattern usually used in violinmaking. For the spruce top plate this was 3mm at its thickest in the center going towards 2.2mm at the outer edges. This calculation was done using the eLamX² software package that uses the Classical Laminate Theory. Through this method the thickness pattern for spruce was converted into a longitudinal stiffness pattern (D11) that could be used to calculate the required thickness of each composite material. All soundboards were infused (VARTM) using the same epoxy resin as the bodies (See figure 1). Parts were visually checked for quality and consistency and remade if necessary.

Figure 1 a) Glass fiber moulds for VARTM production of the body and soundboards of the violin. b) Production of a carbon fiber soundboard (UDC) through vacuum assisted resin transfer method (VARTM).

The lay-up for the composite soundboards was the following:

450 TwillC: 1 layer Twill-woven AKSACA™ A-38 200 tex (3k), 4 layers of unidirectional Tenax®-E
 451 HTS40/12K/HS, 1 layer Twill-woven AKSACA™ A-38 200 tex (3k).
 452 UDC: 7 unidirectional layers of Tenax®-E HTS40/12K/HS.
 453 Sandwich: 1 layer Twill-woven AKSACA™ A-38 200 tex (3k), Aramid honeycomb (thickness 1.5mm,
 454 density 29 kg/m³, cell size 3.2mm), 1 layer Twill-woven AKSACA™ A-38 200 tex (3k).
 455 UDFlax: 5 layers of FLAXTAPE™ 200. FLAXTAPE™ 200 was dried in a drying oven for 1 hour on 105°
 456 Celsius prior to the VARTM process, as suggested by the manufacturer.

457
 458

459
 460
 461
 462

Figure 2: Thickness pattern of the soundboard for TwillC (TwillCA and TwillCB) from left to right: 1 layer Twill-woven AKSACA™ A-38 200 tex (3k), 4 layers of unidirectional Tenax®-E HTS40/12K/HS, 1 layer Twill-woven AKSACA™ A-38 200 tex (3k).

463 The design of the sound hole is slightly different than a conventional
 464 violin, but its dimensions fall within standard measurements (Fig. 3).
 465 sound holes were 47mm wide and 68mm long. Both sound holes were
 466 42mm apart. Nodges were carved up to 9mm, the widest point without
 467 nodges was 6.3-6.4mm. The soundboards were fitted with a
 468 conventional spruce (P. Abies) bass bar (Fig. 4). All bass bars were
 469 from the same piece of wood to limit variations in material properties
 470 like density, Young's modulus, and shear modulus. All the spruce
 471 soundposts of the instruments were made from a single piece of wood for similar reasons. The shape and

The
 the
 made

Figure 3: Design and dimensions of the soundhole for the prototype violins.

472 size of the bass bar was conventional with a length of 26.7mm, thickness of 5.5mm at its base and height
473 from 13mm at the center on the bridge position towards 3mm at the end. String length from the upper nut
474 to the bridge is a standard 328mm, height of the bridge from the soundboard to the highest point of the
475 bridge was 32-33mm. The strings on all violins were: *Dominant* g (133 medium synthetic core, silver
476 wound), d (132a medium synthetic core, silver wound), a (131 medium synthetic core, aluminum wound)
477 produced by Thomastik-Infeld GmbH © and *Kaplan* e (k420B-3 medium tinned carbon steel core)
478 produced by D'Addario & Company, Inc. ©.

479

480 *Figure 4: Produced soundboard (TwilCB) with sound holes cut and spruce bass bar fitted.*

481 *Table III: Total weight of the finished violin prototypes.*

	Total weight of the violins (including strings and chinrest) (g)
Spruce	418
UDC	411
Sandwich	396
UDFlax	452
TwilCB	417
TwilCA	415

482
483 Damping measurements are derived from the modal analysis of beams cut along (longitudinal, l)
484 and across the fibers (transversal, t) through impact excitation in the center of the beam and
485 response measurement with 3 Polytec PSV 500 laser Doppler vibrometer directed at the left,
486 middle and right side of the beam respectively (Table IV). Only the quality factor of the first
487 mode of each beam is provided, which serves as an approximation of the damping properties of
488 the material. The quality factor Q describes how much energy is lost during the resonating
489 movement. A vibration with a high quality factor loses less energy over time and therefore has a
490 lower damping.

491
492 *Table IV Measured quality factors of beams cut along (l) and across (t) the fibers, from four spruce plates and six composite*
493 *material plates produced by VARTM*

Material		Quality factor
Spruce 1	l	120
	t	56
Spruce 2	l	154
	t	56
Spruce 3	l	170
	t	59
Spruce 4	l	86
	t	52
Flax UD 1	l	83
	t	32

Flax UD 2	l	98
	t	44
Carbon UD 1	l	946
	t	87
Carbon UD 2	l	570
	t	102
Carbon UD/ Woven	l	641
	t	491
Honeycomb/ Carbon woven	l	179
	t	189

Additional information on the sound radiation measurements.

Sound radiation measurements were performed in an anechoic chamber to reduce noise and the influence of room acoustics. The violin was mounted on a rig and excited with a miniature impact hammer (PCB 086E80), acoustic response was measured with a microphone (DPA 2006-C) at a distance of 33 cm from the bridge. The instrument was measured in 12 positions, with a 30° clockwise turn of the horizontal plane between each position. The measurement for each position consisted of 3 excitations, of which a complex average was calculated. The coherence function was

used as a quality parameter, if the coherence was not consistently close to 1 the measurement was repeated. The entire measurement was performed with both horizontal (on the side of the bridge) and vertical excitation (on the top of the bridge). The Oberlin Acoustics App (ObieApp1.0b71) was used as acquisition software, which runs on a LabView platform.

Figure 5: set-up of the sound radiation measurement for horizontal excitation.

510 **Additional information on the listening tests.**

511 In the evaluation experiment, the violin player chose to play a modified piece of Symphony Espagnole by
512 Édouard Lalo. In specific she chose part 4, pg 1, and modified it so that each string was played for
513 approximately the same time. The excerpt played was approximately 88 seconds at its longest. All
514 excerpts played were recorded with two Zoom H4N – Neuman microphones (km184NI). One microphone
515 was placed approximately 1m behind the screen, the other approximately 4m further in the room. The
516 recordings are available for other researchers on request, please contact the main author. In the selection
517 experiment, the two violin players first played a 3 octave scale starting from G₃ on each violin (34
518 seconds), followed by an excerpt of their choice from the 9th symphony by Antonin Dvořák (due to
519 practical limitations this experiment could not be recorded).

520 **Additional results of the evaluation experiment:**

521 In addition to the fixed questions, listeners were also given the option to add **other words or remarks on**
522 **the sound of each violin**. They left a total of 49 other remarks, the option was left blank 210 times. 30 of
523 these remarks described the balance being good or bad and/or described particular strings or registers. No
524 other trends were observed in the other 19 remarks.

525 **Listeners could indicate which instrument they would like to take-home**, no large differences with the
526 question what instrument is best were observed: UDFlax (9), TwillCB (7), TwillCA2 (6), Spruce (5),
527 UDC (3), Sandwich (3) and TwillCA1 (2).

528 **Figures showing the rating of the violins in evaluation task (mean +/-1 standard error of the mean).**

529 Filled brown dots indicate a statistically strong deviation (p-value<0.05) from the expected mean (3.5).

530 Filled yellow dots indicate a weak deviation (p-value<0.1).

531

532

533

534

535

536

537

Figure 6: Mean score $\pm$ SEM of the violins on the pairs of adjectives presented on a 8-point Likert scale. Filled black dots indicate a statistically strong deviation ($p\text{-value} < 0.05$) from the expected mean (3.5 dotted line). Filled grey dots indicate a statistically weak deviation ($p\text{-value} < 0.1$).

Order of presentation selection task. The order in which the different pairs were presented and their subsequent order was for Player 1: Conventional violin – TwillCB; Sandwich – Conventional violin; TwillCB – UDFlax; Conventional violin – UDFlax; TwillCB – Sandwich; UDFlax – Sandwich. Violin player 2: Sandwich – TwillCB; Conventional violin – Sandwich; UDFlax – TwillCB; Sandwich – UDFlax; TwillCB – Conventional violin; UDFlax – Conventional violin.

Additional results of the selection experiment.

In the selection experiment, listeners were asked to indicate why they chose a particular violin. As some violins were chosen more often than others, these are displayed in percentage to the amount of times a violin was chosen in figure 7.

Figure 7: Reason why listeners chose a particular violin in the selection test.

559 **Questionnaire evaluation task:**

560 Dear participant,

561

562 During this experiment, you will hear 7 violins a number of times, each time for about 1 minute. The violins will always be presented in the same
563 order. You will listen multiple times to respectively violin 1, 2, 3, 4, 5, 6, and 7.

564 On the following pages you will find an evaluation sheet for each violin, on which you will give your opinion on how the instrument sounds for
565 you. Pay attention! The pages are printed recto-verso. On the last page you will find some general questions about the instruments and your
566 personal background. Please take care to fill in everything, otherwise your contribution can not be used for the research.

567 You will be presented multiple scales with each time two words at the end of the scale. These two words function as the extremities of the
568 scale. Each time you will indicate which word describes the sound best for you and in what amount. If you don't know the answer or don't have
569 a preference between the two words you select the box 'I don't know'.

570 If you don't understand something or have questions about how to fill out this questionnaire, please ask before the start of the experiment.

571 After the experiment the instruments will be revealed, then there is time and space for questions and discussion. This questionnaire is personal,
572 please fill it out on yourself. If you don't know or if you don't have an opinion you can always select or write this.

573 You will give your answer on the scales with a dot on one of the vertical lines. With this questionnaire you will also receive a separate sheet on
574 which more information about the different words is given.

575 Here are some examples on how to fill in the scale using the example of tasting different apple pies.

576

577 *I think apple pie 1 tastes very sweet, so I put a dot at the extremity of the direction sweet.*

578 Sour Sweet I don't

579 know

☐

581

582 *I think apple pie 2 is a bit more sour than sweet, but I don't think the sour taste is very pronounced or big. I put the*
583 *dot on the scale to indicate this.*

584 *Sour* *Sweet* *I don't*

585 *know* ☐

587

588 *I don't know if apple pie 3 is more sour or sweet. I put a dot in the box 'I don't know'.*

589 *Sour* *Sweet* *I don't*

590 *know* ☒

592

593 If you wish, you can indicate a preliminary opinion with a line above the scale, before later putting a dot

594 somewhere on the scale.

595

Violin 1

596

597

598 Open

Closed I don't

599 know

11

600

601 Round

Sharp I don't

602 know

11

603

604 Quiet

Loud I don't

605 know

11

606

607 Cold

Warm I don't

608 know

11

609

610 Harsh

Soft I don't

611 know

11

612

613 Powerful

Weak I don't

614 know

11

615

616 Bad

Good I don't

617 know

7

618

619 Rich Poor I don't

620 know

☐

621

622 Dull Clear I don't

623 know

☐

624

625 Bright Dim I don't

626 know

☐

627

628 Nasal Clear I don't

629 know

☐

630

631

632

633 Do you have other words or remarks on the sound of this instrument?

634

635

636 General questions

637

638 The best instrument is in my opinion Nr:

639 The second best instrument is in my opinion Nr:

640 The worst instrument is in my opinion Nr:

641 Which instrument(s) do you think have a wooden soundboard? Nr(s):.....

642 Which instrument did you find most warm sounding?.....

643 Which instrument did you find most powerful sounding?.....

644 Which instrument did you think most rich sounding?.....

645 What pair of words do you think is most important to judge the quality of a violin?

646

647 How does a violin have to sound for you to be selected as best?

648

649

650 If I could take an instrument home I would take Nr:

651

652 Put a circle around what fits best:

653 I am a: student instrumentenbuilding student classical music teacher researcher other

654

655 Do you regularly play an instrument?

656

657 If yes, what/which instrument(s) do you play?

658

659 If yes, for how many years have you played an instrument?

660

661

662 EXPLANATION WORDS SHEET

663	English:	Dutch:
664		
665	open	open
666	Description: free, loose	Beschrijving: vrij, los
667	Contradiction: closed	Tegenstelling: gesloten
668		
669	loud	luid
670	Description: a great volume in sound.	Beschrijving: een groot volume in klank.
671	Comparison: shouting is loud, whispering is silent.	Vergelijking: Roepen is luid, fluisteren is stil.
672	Contradiction: quiet	Tegenstelling: stil
673		
674	warm	warm
675	Description: with depth.	Beschrijving: met veel diepte.
676	Comparison: some radio-presenters, often on	Vergelijking: sommige radio-presentatoren,
677	late-evening broadcasts, have a very 'warm' voice.	vooral op Klara en in laatavond programma's, hebben een zeer
678		'warme' stem.
679	Contradiction: cold	Tegenstelling: koud
680		
681	clear	helder
682	Description: without noise, lucid, light, pure.	Beschrijving: duidelijk en zonder bijgeluiden, klaar, licht, zuiver.
683	Contradiction: dull	Tegenstelling: dof
684		
685	powerful	krachtig
686	Description: strong, overwhelming, muscled	Beschrijving: sterk, overweldigend, gespierd
687	Contradiction: weak	Tegenstelling: zwak
688		
689	sharp	scherp
690	Description: cutting, pointy, penetrating	Beschrijving: snijdend, puntig, doordringend
691	Contradiction: round	Tegenstelling: rond
692		
693	nasal	nasaal
694	Description: nose sound	Beschrijving: neusklank
695	Comparison: someone who talks with a	Vergelijking: iemand die met een afgesloten neus praat,
696	closed nose, or sound that are carried through	of klanken die door de neus naar buiten worden gedragen
697	the nose like 'n' and 'ng'.	zoals 'n' en 'ng'
698	Tegenstelling: clear	Tegenstelling: helder
699		
700	harsh	hard
701	Description: something that is strongly expressed	Beschrijving: iets dat sterk uitgedrukt of uitgesproken is.
702	or pronounced. Solid and firm.	Vast en stevig.
703	Contradiction: soft	Tegenstelling: zacht
704		
705	rich	rijk
706	Description: with many harmonic overtones,	Beschrijving: veel harmonische boventonen, met een
707	with a broad and full harmonic spectrum.	breed en vol spectrum
708	Contradiction: poor	Tegenstelling: arm
709		
710	bright	briljant
711	Description: with a brilliance, sparkling, virtuoso	Beschrijving: Met een schittering, fonkelend, virtuoos

710 Contradiction: **dim** Tegenstelling: **glansloos**

711 **Questionnaire selection task**

712 Dear participant,

713 Thank you for participating in this blind listening test.

714 For each violin player, you will hear six pairs of violins. Please put a circle around the instrument that

715 enjoys your preference and indicate why you chose this violin as favorite. You can select multiple

716 reasons. If you choose Sound color, please describe it by putting a circle around the words that best

717 describe said sound color for you. If you have other words to describe the sound, you can write these on

718 the dotted line.

719 We will do this experiment with two violin players. The order in which the instruments are presented will

720 be changed between the violin players.

721 If you have any questions regarding this questionnaire please ask them before the start of the

722 experiment. After the test is concluded the instruments will be revealed and there will be time for

723 additional questions.

724

725 What instrument(s) do you play:

726 How many years do you play a musical instrument:

727

728 **Violinist nr. 1**

729 Pair 1:

Violin nr. 1

Violin nr. 2

730 ☐ Better projection

731 ☐ Better balance

732 ☐ Better sound color

 warm harsh clear rich open sharp round bright powerful nasal

733

734

References / sources

- ¹ A. Damodaran, L. Lessard and A. Suresh Babu, "An Overview of Fibre-Reinforced Composites for Musical Instrument Soundboards," *Acoust. Aust.* 43, 117–122 (2015).
- ² C. Besnainou, "From wood mechanical measurements to composite materials for musical instruments: new technology for instrument makers," *MRS Bull*, 03 34–36 (1995).
- ³ M. Mehdi Jalili, S. Yahya Mousavi and A.S. Pirayeshfar, "Investigating the acoustical properties of carbon fiber, glass fiber, and hemp fiber-reinforced polyester composites," *Polym. Compos.* 34. (2014).
- ⁴ T. Ono and D. Isomura, "Acoustic characteristics of carbon fibre reinforced synthetic wood for musical instrument soundboards," *Acoust. Sci. Technol.* 25, 475–477 (2004).
- ⁵ T. Ono and A. Okuda, "Acoustic characteristics of guitars with a top board of carbon fiber-reinforced composites," *Acoust. Sci. Technol.* 28, 442–443 (2007).
- ⁶ S. Webb, "Carbon-fiber cellos no longer playing second-fiddle to wooden instruments." <http://www.scientificamerican.com/article/carbon-fiber-cellos> (2009). Accessed 22 July 2019
- ⁷ J. Dominy and P. Killingback, "The development of a carbon fibre violin," *Proceedings of ICCM-17 Conference A 6.2*, Edinburgh (2009).
- ⁸ M. Parish, "Perfecting the sustainable guitar," <http://www.mmrmagazine.com/81-current-issue/spotlight/389-perfecting-the-sustainable-guitar.html> (2013). Accessed 15 Dec 2014.
- ⁹ S. Phillips and L. Lessard, "Application of natural fiber composites to musical instrument top plates," *J. Compos. Mater.* 46, 145–154 (2012).
- ¹⁰ G. Bissinger, "Structural Acoustics of good and bad violins," *J. Acoust. Soc. Am.* 124, 1764–1773 (2008).
- ¹¹ C. Fritz and D. Dubois, "Perceptual Evaluation of Musical Instruments: State of the Art and Methodology," *Acta Acust. united with Ac.* 101, 369–381 (2015).

759 ¹² C. Fritz, J. Curtin, J. Poitevineau, P. Morrel-Samuels and F.C. Tao, "Player preferences among new and
760 old violins," *Proc. Natl. Acad. Sci. USA* 109, 760–763 (2012).

761 ¹³ C. Fritz, J. Curtin, J. Poitevineau, H. Borsarello, I. Wollman, F.C. Tao and T. Ghasarossian, "Soloist
762 evaluations of six old Italian and six new violins." *Proc. Natl. Acad. Sci. USA* 111, 7224–7229 (2014).

763 ¹⁴ C. Fritz, J. Curtin, J. Poitevineau and F.C. Tao, "Listener evaluations of new and old Italian violin,"
764 *Proc. Natl. Acad. Sci. USA* 114, 5395–5400 (2017).

765 ¹⁵ See supplementary material at [<https://youtu.be/xtSoUKvDGTy>] for [*a video showing the making*
766 *process on a violin*].

767 ¹⁶ C. Johnson and R. Courtnall, "The Art of Violin Making," Robert Hale, London (1999).

768 ¹⁷ H. Weisshaar and M. Shipman, "Violin Restoration a manual for violinmakers" Weisshaar-Shipman,
769 Los Angeles CA (1988).

770 ¹⁸ eLamX 2.3 Java(TM) SE Runtime Environment, TU Dresden, Dresden. Available at [https://tu-](https://tu-dresden.de/ing/maschinenwesen/ilr/lft/elamx2/elamx)
771 [dresden.de/ing/maschinenwesen/ilr/lft/elamx2/elamx](https://tu-dresden.de/ing/maschinenwesen/ilr/lft/elamx2/elamx) (2016). Accessed on 28th of April 2017.

772 ¹⁹ T. Duerinck, "What's the alternative?" *The Strad* 129, 52-56 (2018).

773 ²⁰ C. Fritz, A. Blackwell, I. Cross, J. Woodhouse and B. Moore, "Exploring violin sound quality:
774 Investigating english timbre descriptors and correlating resynthesized acoustical modifications with
775 perceptual properties," *J. Acoust. Soc. Am.* 131, 783–794 (2012).

776 ²¹ C. Saitis, B.L. Giordano, C. Fritz and G.P. Scavone, "Perceptual evaluation of violins: A quantitative
777 analysis of preference judgments by experienced players," *J. Acoust. Soc. Am.* 132, 4002-4012
778 (2012).

779 ²² U. G. K. Wegst, "Wood for sound," *Am. J. of Botany* 93.10, 1439–1448 (2006).

780 ²³ R. Viala, *Towards a model-based decision support tool for stringed musical instruments making*, PhD
781 diss., University of Bourgogne Franche-Comté, France (2018).

²⁴ L. Page and K. Page, “Last shall be first: A field study of biases in sequential performance evaluation on the Idol series.” J. of Economic Behavior & Organization 73, 186-198 (2010).

Tables

Table I: Weight of the finished soundboards, engineering constants calculated using eLamX² and estimation of damping of the materials. The damping is an approximation in comparison to spruce, which was given the 0 value as the benchmark material.

Soundboard	Weight (g)	D11 (Nmm)	D22 (Nmm)	D66 (Nmm)	Damping
Spruce	74.8	15.8	1.1	1.5	0
UDFlax	100.3	14.7	0.9	1.2	0/+
UDC	72	14.7	0.9	0.6	--
TwillCA	71	15.5	6.4	0.7	--
TwillCB	74.8	15.5	6.4	0.7	--
Sandwich	42.3	15.7	15.7	0.7	-

Table II: Strong and weak evidence to reject the null-hypothesis and link adjectives to the sound of each of the seven investigated violins.

	Strong evidence (p-value<0.05)	Weak evidence (p-value<0.1)
TwillCA(1)	dim	loud, closed, bad
TwillCB	warm, clear, loud, good, powerful, rich	open, round, bright
Sandwich	loud, harsh, nasal, powerful	sharp, rich, bright
UDFlax	warm, soft, round	dull, quiet, closed, good, weak, rich
TwillCA(2)	loud, sharp, powerful	warm, clear, good, nasal, bright
Spruce	loud, powerful, rich, bright	harsh, good
UDC	warm, soft, good, round	bright

Table III: Preference of listeners for composite violins when presented in pairs during our selection experiment. The pairs with the conventional violin are excluded as these were not a double-blind condition.

Number of participants favoring a specific violin and the reason why

Player 1	Preference listeners	Projection	Balance	Sound Color
TwillCB	25	13	5	12
UDFlax	13	2	5	9
TwillCB	34	13	13	21
Sandwich	6	5	2	3

UDFlax	24	3	8	17
Sandwich	14	11	4	5
Player 2				
TwillCB	29	12	6	18
UDFlax	8	3	0	5
TwillCB	18	0	3	13
Sandwich	20	9	5	9
UDFlax	22	3	2	12
Sandwich	16	9	2	9

794

795

Figure captions

Figure 1: Prototype violins with soundboards from 5 different materials constructed for the study. Only one of the TwillC violins is displayed here as the two instruments are visually identical.

Figure 2: Mean value (dot) $\pm$ 1 Standard error of the mean SEM (vertical line) of the violins' rating on the attributes warm – cold and rich – poor. Filled black dots indicate a statistically strong deviation (p -value <0.05) from the expected mean (3.5 dotted line). Filled grey dots indicate a statistically weak deviation (p -value <0.1).

Figure 3: Amount of times each violin was chosen as best, second best and worst in the evaluation experiment.

Figure 4: Amount of times each instrument was chosen on the question 'Which instrument did you find most rich/most powerful/most warm'.

Figure 5: Amount of times a pair of words was written down as important to judge the quality of a violin. In black the pairs prompted by a previous question, in gray the non-prompted pairs. Between the prompted pairs warm – cold and rich – poor, attributes related to the sound color, were chosen significantly more than powerful – weak, an attribute often linked to projection and loudness.

Figure 6: a) RMS level of the recording made during the evaluation experiment. b) acoustic sound radiation of all violins measured in an anechoic chamber with impact hammer excitation. Frequency response functions (FRF's) smoothed over one tone for readability and interpretation purposes.

Figure 7: Percentage distribution on the description of the favored sound color for each of the violins.