Finite Element Modeling of Electrostatics and Seismoelectrics

Fabio Zyserman, Gauzellino Patricia Gauzellino, Laurence Jouniaux

► To cite this version:

Fabio Zyserman, Gauzellino Patricia Gauzellino, Laurence Jouniaux. Finite Element Modeling of Electrostatics and Seismoelectrics. Niels Grobbe. Seismoelectric exploration: Theory, experiments and applications, , 2020, Book Series:Geophysical Monograph Series, 978-1-119-12737-6. 10.1002/9781119127383.ch18 . hal-03091019

HAL Id: hal-03091019

<https://hal.science/hal-03091019>

Submitted on 30 Dec 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Finite element modelling of Electroseismics and Seismoelectrics

F. Zyserman^{1,2}, P. Gauzellino^{2*}, L. Jouniaux^{3†}

¹Facultad de Ciencias Astronómicas y Geofísicas, Universidad Nacional de La Plata, Paseo del Bosque s/n, B1900FWA La Plata, Argentina

²CONICET

³Institut de Physique du Globe de Strasbourg, EOST, Uds/CNRS UMR 7516, Université de Strasbourg, 5 rue René Descartes, 67084, Strasbourg, France

*gauze@fcaglp.unlp.edu.ar

†l.jouniaux@unistra.fr

Corresponding author: F. Zyserman, zyserman@fcaglp.unlp.edu.ar

Abstract

In this chapter we describe a set of finite element formulations employed to approximate the solution to an extension to partially saturated porous media of Pride’s equations, which is one of the most widespread theoretical frames that model the coupled electromagnetics and acoustics of saturated porous media. We also show how these numerical algorithms can be implemented on multi-core computers, and analyse their performance, observing that the parallel efficiency of the algorithms decays slower when the resources of each computing core are used as close to their maximum as possible. Further, we perform a study of two dimensional PSVTM electroseismic conversions in a time-lapse carbon dioxide geological deposition monitoring scenario, setting the electromagnetic source in depth, and measuring the seismic responses both in wells and at the surface. We observe that, contrary to what is known from standard field settings, the interface responses play no important role in elucidating the CO₂ plume behaviour, and that the in-depth converted signals convey information about the carbon dioxide saturation in the plume.

1 Introduction

Geophysical methods of subsurface exploration are based on either seismic or electrical geophysical principles. The seismo-electromagnetic method combines both approaches, with the resolution of the seismics and the sensitivity of the electromagnetic methods to the fluids. It offers a non-invasive structure characterisation of the near surface earth from first few hundred meters up to the order of one thousand meters depth, in terms of fluids (water, oil, gas) [Dupuis *et al.*, 2007; Haines *et al.*, 2007a; Thompson *et al.*, 2007]. It is usual to use different terms, according to the used source: Seismoelectrics (SE) involves generating a seismic wave and measuring the electrical field contained within or generated by it [Haartsen and Pride, 1997; Haines *et al.*, 2007a,b], while electroseismics (ES) does the opposite by injecting a large amount of current into the ground and measuring the resulting seismic energy [Thompson *et al.*, 2005, 2007]. First attempts on the seismic-electromagnetic effect were actually ES measurements, since an electric current was injected through the earth. The observations were thought to be due to changes in the earth resistivity under the influence of seismic waves. A first explanation was proposed to be linked to the fluctuations in the current through the electrolytic cell because of variations of the electro-chemical conditions at the surface of the electrodes, induced by the mechanical vibrations [Thyssen *et al.*, 1937]. Then different experimental set-ups could eliminate the effect of electrode surface [Thompson, 1939]; and later on Pride [1994];

Butler *et al.* [1996] showed that the resistivity modulation was not the relevant mechanism of the observed SE signals. Decades ago, Thompson and Gist [1993] observed conversions from electromagnetic to seismic energy at the siliciclastics Friendswood test site (Texas), with the presence of a sequence of high permeability water sands and low permeability shales over 300 m depth. They showed through modelling that electroseismics are more sensitive to low permeability formations whereas seismoelectrics are most sensitive to high permeability formations. Over the last two decades some observations showed that the electroseismic conversions could yield conversions of higher energy efficiency. First successful demonstration that electroseismic conversions can distinguish between aquifers and gas sands and can be used at depths up to 1000 m using geophones placed on the surface of the earth were provided by [Thompson *et al.*, 2007; Hornbostel and Thompson, 2007].

The pioneering studies of Reuss [1809], Wiedemann [1852], von Helmholtz [1879], Smoluchowski [1903] and Frenkel [1944] were completed in more recent times with the development of the corresponding theory. Thompson and Gist [1993] and Pride [1994] explained the electrokinetic coupling mechanism within the double electrical layer at the solid-fluid interface. Electro-osmotic flow occurs when an electric field acts on the electrolytes present in the fluids. This generates pressure gradients and, therefore, fluid flow and mechanical macroscopic perturbations, yielding the SE technique. Equally important is the reciprocal case called electro-filtration. In this one, an applied pressure gradient creates fluid flow and consequently, an ionic convection current, which in turn produces an electric field, phenomenon upon which ES is based. Pride [1994] derived the equations for both phenomena (ES-SE) whose linking factor is the so-called electrokinetic coupling coefficient. The uncoupled Biot's equations for fluid-saturated porous media [Biot, 1956a,b] and Maxwell's equations take place if this coefficient is zero; for a review on this or other theoretical frames for the electroosmotic and electrofiltration phenomena, and hence for SE and ES see Jouniaux and Ishido [2012]; Jouniaux and Zyserman [2016].

The computation of approximate solutions to any of the several model equations governing the rise of electromagnetic signals due seismic waves traversing a fluid saturated porous medium or conversely, the rise of seismic waves due to electromagnetic probes, is not a simple task. We review now a small part of the literature on this topic, focusing ourselves mainly on the numerical treatment of Pride's equations, which are the ones we deal with in this chapter. Haartsen and Pride [1997] performed numerical modelling featuring seismic and electromagnetic point sources on horizontally stratified media; they used a global matrix method to

obtain their results. They showed that Pride's equations can be decoupled in two modes, namely the SHTE (horizontal shear wave transverse electric field) mode, involving the seismic SH and transverse electric TE, and the PSVTM (transverse magnetic field of vertical P and S waves) mode, linking the seismic P-SV modes with the transverse magnetic TM mode; further they showed that the interface response was similar to the one of a vertical electric dipole situated right beneath the seismic source. *Mikhailov et al.* [1997] used this algorithm to analyse field measurements involving IR responses at a top soil-glacial till interface and later *Hu and Gao* [2011] extended this algorithm by including a moment tensor point source. *Han and Wang* [2001] proposed a finite element procedure in time-domain for modelling diffusive electric fields induced by pure shear waves. *Garambois et al.* [2002] presented a numerical simulation for SE events through the generalized reflection and transmission matrix method, extended afterwards by *Warden et al.* [2013] to unsaturated conditions to perform a study of the vadose zone. The works developed by *Pain et al.* [2005] and *Haines and Pride* [2006] describe a mixed finite element algorithm for ES in boreholes and a finite-difference procedure that applies ES in heterogeneous media, respectively. Also, *Guan and Hu* [2008] introduced a finite-difference time-domain method with perfectly matched layer (PML) technique as boundary conditions in borehole geometries (cylindrical symmetry). They calculated ES and SE logging responses to estimate the parameters of the porous medium around the borehole. A variation of this numerical technique was employed recently by *Zheng et al.* [2015] when simulating the electric field excited by the acoustic wave in a logging while drilling scenario. Two dimensional numerical tests about P-TM conversions using an implicit time stepping finite element algorithm in a commercial software were implemented by *Kröger et al.* [2014], while *Zhou et al.* [2014] studied converted waves inside a borehole setting boundary conditions at the interface between fluid and porous media. Receivers along the vertical axis of the borehole detected the components of electric and magnetic field depending on the distance from the acoustic source. In a series of works *Grobbe and Slob* [2013, 2014]; *Grobbe et al.* [2014]; *Grobbe and Slob* [2016] presented and applied the algorithm ESSEMOD, which is a layered-Earth analytically based simulation code, implementing all existing possible seismo-electromagnetic and electro-magneto-seismic sourcereceiver combinations. This code can presently model fluid/porous medium/fluid transitions, thereby enabling studying typical seismo-electromagnetic laboratory wave propagation experiments, as the authors did in the third of these last references. In the last one, they studies the responses of different thin-bed packages, proving that the seismo- electromag-

netic responses are sensitive to changes in medium parameters in length scales much smaller than the seismic resolution.

Recently, using one dimensional versions of the numerical algorithms presented in this work, *Zyserman et al.* [2015] could demonstrate that the seismoelectric and seismomagnetic interface responses generated at boundaries of a layer containing carbon dioxide are sensitive to its CO₂ content; and *Munch and Zyserman* [2016] analysed how the seismoelectric interface responses vary when a superficial aquifer is contaminated with light or dense NAPLs.

In this chapter, the differential model consists in Maxwell and Biot equations; the numerical formulation uses a mixed finite element technique to approximate the electromagnetic wave fields and a non-conforming finite element procedure to approximate the solid displacements with the vector part of the Raviart-Thomas-Nedelec space of zero order to the fluid displacements for the seismic wave fields, see e.g. [*Raviart and Thomas*, 1975; *Nedelec*, 1980; *Douglas, Jr. et al.*, 1999; *Zyserman and Santos*, 2000; *Santos and Sheen*, 2007; *Santos*, 2009; *Zyserman et al.*, 2010; *Savioli et al.*, 2014] for other works where these spaces are used and analysed. The iterative non-overlapping domain decomposition algorithm proposed here [*Santos and Sheen*, 2007; *Savioli et al.*, 2014] allows to solve problems with a large number of unknown and it is suitable to be implemented on computers with parallel architecture [*Zyserman and Santos*, 2000; *Gauzellino et al.*, 2009; *Zyserman et al.*, 2012]. We consider that events of feedback are neglected, and therefore Maxwell and Biot equations can be solved separately. Here, the fluid-saturated porous medium is characterized by effective models and viscoelastic behaviour [*Carcione*, 2001] also taken into account. With respect to the electromagnetic part, the electrical conductivity and electrokinetic coefficient are expressed as a function of the water saturation.

Our algorithm is applied to a case of time-lapse CO₂ geological sequestration scenario, where we analyse the seismic response to different saturations of CO₂. Finally, we would like to mention that although not included in this chapter, examples of applications of the presented algorithm to seismoelectric case studies can be found in [*Gauzellino et al.*, 2010a,b].

2 Simplifying and extending Pride's equations

With the goal of making the SE/ES equations more tractable, it is usual to introduce simplifying assumptions by reducing the dimensionality of the equations and/or by decoupling the full set of Pride's equations in one of two different ways: if the electroosmotic feedback is neglected, the poroelastic equations can be decoupled from the electromagnetic ones; this is usu-

ally done in SE. If the electrofiltration feedback can be neglected, Maxwell's equations can be decoupled from Biot's equations; this is the chosen way when dealing with ES problems. In both cases the uncoupling can be safely carried out if the condition

$$\frac{\eta \mathcal{L}^2(\omega)}{k(\omega) \sigma^e} \ll 1 \quad (1)$$

is fulfilled [Haines and Pride, 2006; Hu et al., 2007; Guan and Hu, 2008; Zyserman et al., 2010]; here η stands for the fluid viscosity, $\mathcal{L}(\omega)$ for the electrokinetic coupling coefficient, $k(\omega)$ for the dynamic permeability and σ^e for the electric conductivity. Most of the works present in the literature take this condition as granted, and likewise we proceed in the present chapter. In this way, to model a SE problem, Biot's equations are solved in a first instance to obtain solid and fluid displacements generated by a seismic source, and in a second step, the electromagnetic responses are got; the fluid displacements are a constitutive part of the electromagnetic source. On the other hand, in an ES problem, Maxwell's equations are solved to get the electric and magnetic fields created by electric currents, and the former is used in the source term of the poroelastic equations to obtain, in a second step, the induced seismic wave fields.

2.1 Problem dimensionality

Considering the dimensionality of the problem, until now there has been, to the authors' knowledge, just one attempt to solve Pride's equations involving finite sources and three dimensional geometries and fields [Wang et al., 2013a], and it has been done using the finite differences technique. The difficulty in numerically modelling fully three dimensional problems is the huge amount of unknowns involved, which implies the usage of very large computing resources. Because of this reason, we restrict ourselves to show finite element algorithms for two dimensional problems; that is, we consider in the next sections either seismic or electromagnetic sources generating two dimensional vector fields, which interact with two dimensional Earth models and induce two dimensional responses.

2.2 Extended models

The extension of the original set of SE/ES equations to deal with partially saturated or contaminated soils is usually carried out by having recourse to effective media models, as can be seen in the works of Zyserman et al. [2010]; Warden et al. [2013]; Bordes et al. [2015]; Zyserman et al. [2015]; Munch and Zyserman [2016]. There exist also other approaches considering Biot-type formulations, such as the composite media approach proposed by Zyserman

et al. [2012] to deal with the presence of methane hydrates, or the recent contribution by *Jardani and Revil* [2015], where the theory is enlarged to deal with mixtures of immiscible fluids. We use the effective media approach in the case study we present in this chapter -involving a CO_2 geological deposition situation-, so we show now how the model parameters are dealt with. The rock physics models we show below are widely employed in the literature, but the reader should recall that they are approximations and their validity must be tested, as we did in this work. Moreover, other approximations do exist for most of the effective parameters [Mavko *et al.*, 2009].

For the effective fluid mass density, calculated in terms of the water density ρ^w , CO_2 density ρ^{CO_2} and their respective saturations S_w and S_{CO_2} we use

$$\rho^E = \rho^w S_w + \rho^{CO_2} (1 - S_w), \quad (2)$$

where $S_w + S_{CO_2} = 1$ is assumed. For the effective bulk modulus of such fluid mixture we use *Brie et al.* [1995]

$$K^f = (K^w - K^{CO_2}) S_w^5 + K^{CO_2}; \quad (3)$$

the power five in this expression is chosen following *Carcione et al.* [2006a]. Here the CO_2 is supercritical, so there is no gaseous phase in our model. The effective viscosity is computed in terms of the mixture components viscosities η^l , $l = w, CO_2$ and water saturation S_w using *Teja and Rice* [1981]

$$\eta = \eta^{CO_2} \left(\frac{\eta^w}{\eta^{CO_2}} \right)^{S_w}. \quad (4)$$

In order to compute the saturated rock matrix properties, we proceed as follows: we consider three different materials building the solid matrix, namely sand, silt and clay, and we call γ_{sand} , γ_{silt} and γ_{clay} their respective volume fractions; $\gamma_{sand} + \gamma_{silt} + \gamma_{clay} = 1$. The mass density of the aggregate ρ^s is given by the volume weighted mean of the respective components mass densities,

$$\rho^s = \gamma_{sand} \rho^{s,sand} + \gamma_{silt} \rho^{s,silt} + \gamma_{clay} \rho^{s,clay}, \quad (5)$$

and the bulk mass density is calculated as usual,

$$\rho^b = \rho^s \phi + \rho^f (1 - \phi), \quad (6)$$

where ϕ is the rock porosity. The bulk modulus K^s and shear modulus G^s of the mixture of mineral grains are given by the Reuss average of the components bulk and shear moduli respectively [Mavko *et al.*, 2009]

$$K^s = \left(\frac{\gamma_{sand}}{K^{s,sand}} + \frac{\gamma_{silt}}{K^{s,silt}} + \frac{\gamma_{clay}}{K^{s,clay}} \right)^{-1}, \quad (7)$$

and

$$G^s = \left(\frac{\gamma_{\text{sand}}}{G_{s,\text{sand}}} + \frac{\gamma_{\text{silt}}}{G_{s,\text{silt}}} + \frac{\gamma_{\text{clay}}}{G_{s,\text{clay}}} \right)^{-1}. \quad (8)$$

The solid matrix bulk modulus K^{fr} and shear modulus G^{fr} are then calculated by Krief's model as

$$K^{fr} = K^s(1 - \phi)^{(3/(1-\phi))}, \quad G^{fr} = G^s(1 - \phi)^{(3/(1-\phi))}. \quad (9)$$

The expressions in this equation have been used to deal with shaley sand data [Mavko *et al.*, 2009].

The shear modulus of the effective fluid saturated rock matrix G_u is considered, as usual, equal to G^{fr} , but for the saturated matrix bulk modulus K_u we use Gassman's approach as follows [Gassmann, 1951; Santos *et al.*, 1992]

$$K_u = K^{fr} + \alpha^2 K^{av}, \quad K^{av} = \left[\frac{\alpha - \phi}{K^s} + \frac{\phi}{K^f} \right]^{-1}, \quad \alpha_B = 1 - \frac{K^{fr}}{K^s}. \quad (10)$$

In this equation, K^{av} and α_B are the so called fluid-storage and Biot-Willis coefficients respectively. The reader should recall here that Gassmann's model is valid for seismic frequencies, but for sonic or ultrasonic ones, other models taking into account squirt flow [Mavko and Jizba, 1991; Dvorkin and Nur, 1993; Dvorkin *et al.*, 1995] should be employed.

The model can be further extended if the diverse energy loss mechanisms present in the subsurface, which are not explicitly considered in Biot's equations are taken into account. One example of these mechanisms is the so called wave induce fluid flow, studied by several authors [Pride *et al.*, 2004; Rubino *et al.*, 2008; Picotti *et al.*, 2007; Song *et al.*, 2016]. With this goal, instead of considering particular loss processes, we consider that the studied region presents a viscoelastic behaviour, and we use Biot's correspondence principle [Biot, 1956c, 1962], replacing the (real) relaxed elastic moduli G and K by complex frequency dependent viscoelastic moduli. To obtain their expressions we employ Liu's linear viscoelastic model [Liu *et al.*, 1976], which reads for G (we deal with K in the same fashion): $\widehat{G}(\omega) = G/(R(\omega) - iT(\omega)) = G_r(\omega) + iG_i(\omega)$. The functions $R(\omega)$ and $T(\omega)$, associated with a continuous spectrum of relaxation times, characterize the viscoelastic behaviour and are given by

$$R(\omega) = 1 - \frac{1}{\pi\widehat{Q}} \ln \frac{1 + \omega^2 T_1^2}{1 + \omega^2 T_2^2}, \quad T(\omega) = \frac{2}{\pi\widehat{Q}} \tan^{-1} \frac{\omega(T_1 - T_2)}{1 + \omega^2 T_1 T_2}.$$

The model parameters $\widehat{Q}$, T_1 and T_2 are taken such that the quality factor $Q(\omega) = \frac{G_r(\omega)}{G_i(\omega)}$ is approximately equal to the constant $\widehat{Q}$ within the frequency range we deal with in this work. Values of $\widehat{Q}$ range from $\widehat{Q} = 10$ for highly lossy materials to about $\widehat{Q} = 1000$ for almost elastic ones. We used $\widehat{Q} = 100$, $T_1 = \frac{1}{2\pi} 10^6 s$ and $T_2 = \frac{1}{2\pi} 10^{-7} s$ in all the examples shown

below. Although there are other models to account for the energy loss, e.g. [Chotiros and Isakson, 2004], we used Liu's model because it provides a constant quality factor over the frequency range considered, the moduli are well behaved at $\omega \rightarrow 0$ and ensures causality, which is a reasonable behaviour for geophysical applications.

For the absolute permeability k_0 of the porous medium we use [Mavko *et al.*, 2009]

$$k_0 = B \frac{\phi^3}{(1 - \phi)^2} d_k^2 \quad \text{where} \quad \frac{1}{d_k} = \frac{\gamma_{sand}}{r_{sand}} + \frac{\gamma_{silt}}{r_{silt}} + \frac{\gamma_{clay}}{r_{clay}}. \quad (11)$$

Here B is a geometric constant (we assume $B = 0.003$ [Carcione and Picotti, 2006]) and r_* is the radius of the different rock constituent particles.

In order to characterize the electric conductivity of the effective fluid saturated solid matrix we use the expression recently proposed by Warden *et al.* [2013], extending Pride's original formula [Pride, 1994, Eq.(242)] to the realm of partially saturated media:

$$\sigma_{eff}^*(S_w, \omega) = \frac{S_w^n}{F} \sigma^w + \frac{2}{F} \frac{C_{em} + C_{os}^*(\omega)}{\Lambda} \quad (12)$$

The first term in this equation -where $F = \phi^{-m^c}$ stands for the formation factor, m^c being the cementation coefficient- is Archie's law for a partially saturated medium, while the second term accounts for the surface conductivity. The water electrical conductivity

$\sigma^w = \sum_{l=N_{a+}, Cl-} (ez_l)^2 b_l N_l$, where $e = 1.6 \times 10^{-19}$ C is the electron electric charge, and z_l is the ions' valence, taken to be one for both species. The ions' mobility b_l and concentration N_l (depending on the salinity C_0) are calculated following Carcione *et al.* [2003].

In the second term, accounting for the surface conductivity, the factor C_{em} [S] is the excess conductance associated with the electromigration of double layer ions; $C_{os}^*(\omega)$ [S] is the frequency-dependent electro-osmotic conductance due to electrically induced streaming of the excess double-layer ions and Λ [m] is the above presented pore-geometry dependent factor. We remark here that, as in Brovelli *et al.* [2005] and Warden *et al.* [2013], the surface conductivity is assumed to be independent of water saturation S_w , because under realistic saturation ranges (residual water saturation $S_{wr} \geq 10\%$) the thickness of the wetting phase layer on the pore surface is always larger than the Debye length d^l . This also means that all fluid related properties involved in the calculation of the surface conductivity and of the electrokinetic coupling -see below- are just those of water.

Again, following Warden *et al.* [2013], we propose for the effective fluid saturated media the following electrokinetic coupling:

$$\mathcal{L}_0(S_w) = -\frac{\phi}{\alpha_\infty} \frac{\varepsilon^w \zeta^p}{\eta^w} \left(1 - 2 \frac{d^l}{\Lambda}\right) S_w^n \mathcal{C}(S_w), \quad (13)$$

In this equation $\alpha_\infty = \phi F$ is the tortuosity, ε^w is the water electric permittivity, n is Archie's saturation exponent (taken to be equal to the cementation exponent m^c), d^l is the Debye length and $\mathcal{C}(S_w)$ is a function relating the streaming potential coefficient obtained under partial saturation conditions to the one corresponding to full saturation conditions. Several authors have investigated this relation from both theoretical and experimental viewpoints. In the study of *Strahser et al.* [2011], different models for the streaming potential coefficient (SPC) dependence on S_w were considered, namely the ones by *Perrier and Morat* [2000], *Revil et al.* [2007], *Guichet et al.* [2003] and *Allègre et al.* [2010]. Characterizing this dependence by a power law has been also proposed to model the relative electrokinetic coefficient in an imbibition experiment [*Saunders et al.*, 2008]. *Jackson* [2010] also used a capillary tubes model making explicit the SPC dependence with water saturation, relative permeability and relative charge density. Further models derived from considerations on how the excess charge dragged by the water varies with water saturation may be mentioned, as those derived by *Mboh et al.* [2012] and *Jougnot et al.* [2015]. Recently, *Allègre et al.* [2012] modelled both Richards' equation for hydrodynamics and Poisson's equation for electrical potential for unsaturated conditions, using a 1-D finite element method. They concluded, based on laboratory experiments [*Allègre et al.*, 2010, 2011] and using these equations, that the unsaturated electrokinetic coefficient should have a non-monotonous behaviour. Moreover experimental results from periodic succession of drainage and imbibition cycles on sand suggested that the airwater interface that develops for unsaturated conditions polarizes and therefore generates an electrical response [*Allègre et al.*, 2014]. Finally *Allègre et al.* [2015] showed that the interface between water and air should also be taken into account, since this interface is negatively charged, as the interface between the rock matrix and the water. Moreover during a drainage the amount of this interface does not decrease with decreasing water saturation, but first increases before decreasing, leading to a non-monotonic behaviour of the resulting SPC [*Allègre et al.*, 2015].

For the present we select the following relation, displaying a non monotonic dependence with water saturation [*Allègre et al.*, 2010]:

$$\mathcal{C}(S_w) = \left(\frac{S_w - S_{wr}}{1 - S_{wr}} \right) \left[1 + 32 \left[1 - \left(\frac{S_w - S_{wr}}{1 - S_{wr}} \right) \right]^{0.4} \right], \quad S_{wr} = 0.20, \quad (14)$$

in Fig. 1 the behaviour of $\mathcal{C}(S_w)$, where its sharp decrease for $S_w \geq 0.8$ is remarkable.

Finally, notice that in order to write Eq. (13), it was assumed in *Warden et al.* [2013] that the surface electrical conductivity is negligible against the electrical bulk conductivity; a requirement fulfilled in this work due to chosen values for the salinity C_0 . On the other hand, we compute the zeta potential ζ^p as $\zeta^p = 0.008 + 0.026 \log_{10}(C_0)$ [*Pride and Morgan*, 1991].

3 Domain decomposition and Finite elements formulation

In this section the treatment of the ES PSVTM-mode is described; the ES SHTE-mode and both modes of the SE case treated in similar way. We assume that the chosen soil properties and seismic frequency range guarantee that any considered angular frequency ω renders displacements currents that are negligible against conduction currents, i.e. $\epsilon\omega \ll \sigma$, and that it is well below Biot's critical frequency. Because of this reason, we use the static values k_0 and $\mathcal{L}_0$ instead of the dynamic ones $k(\omega)$ and $\mathcal{L}(\omega)$ for the permeability and electrokinetic coupling coefficient respectively.

We present below different kinds of mixed finite elements, which we use to approximate the solutions to both Maxwell's equations and Biot's equations; noting that previously to this step we apply to them domain decomposition (DD) procedures. The DD technique can be used at different levels [Toselli and Widlund, 2005]: continuous, discrete, or in the solution of the linear systems arising from the approximation of different partial differential equations. The domain decomposition procedures (DD) here presented belong to the continuous level, and are iterative methods that converge to the solution of the respective global procedures [Santos, 1998, 2009]; for different implementations, mainly involving the first and third mentioned levels, the reader can see, for example, references Japhet and Nataf [2001]; Gander *et al.* [2002, 2004].

The idea is to solve in parallel a collection of elliptic problems in the space-frequency domain with absorbing boundary conditions at artificial boundaries. Then, the solution in the time domain is obtained using the inverse Fourier transform.

Among the advantages of the presented procedure to solve wave propagation phenomena we can indicate:

- DD combined with any finite element method bypasses storage and solution of the large linear systems.
- In structured finite element meshes, DD is specifically designed to profit of the parallel architecture.
- Nonconforming finite element space significantly reduces the amount of information exchanged among processors.
- The rate of convergence of the iterative algorithm can be estimate using nonconforming finite element spaces.

3.1 Maxwell's equations

Let us then start by considering a domain $\Omega = \Omega^a \cup \Omega^s$ comprising air and subsurface, with boundary Γ . The domain Ω is partitioned into non overlapping subdomains Ω_j with boundary Γ_j as shown in Fig.2(a). Let also Ω_j and Ω_k be two adjacent subdomains of the domain decomposition, and Γ_{jk} their common boundary. Assuming that we are dealing with the TM mode, where the present electromagnetic fields are $E \equiv (E_x(x, z, \omega), E_z(x, z, \omega))$ and $H \equiv H_y(x, z, \omega)$, the domain decomposed formulation of Maxwell's equations reads [Zyserman *et al.*, 1999; Zyserman and Santos, 2000]:

$$\sigma^e E_j - (-\partial_z H_j, \partial_x H_j) = J^m \quad \text{in } \Omega_j, \quad (15)$$

$$\partial_z E_{x,j} - \partial_x E_{z,j} + i\omega\mu H_j = 0 \quad \text{in } \Omega_j, \quad (16)$$

$$H_j + \beta_{jk} E_j \cdot \chi_j = -\beta_{jk} E_k \cdot \chi_k + H_k \quad \text{on } \Gamma_{jk} \quad (17)$$

$$H_k + \beta_{jk} E_k \cdot \chi_k = -\beta_{jk} E_j \cdot \chi_j + H_j \quad \text{on } \Gamma_{kj} \quad (18)$$

$$(1-i)\sqrt{\frac{\sigma^e}{2\omega\mu}} E_j \cdot \chi_j + H_j = 0 \quad \text{on } \Gamma. \quad (19)$$

The first two of this set of equations are Ampere-Maxwell's and Faraday's respectively; in them we denote the partial derivative with respect to coordinate x as ∂_x ; J^m is the external source creating the TM polarized fields and μ is the magnetic permeability. Eqs. (17)-(18) are Robin boundary conditions [Douglas *et al.*, 1993; Kim, 1995] imposed on the boundaries between any two domains to ensure consistency of the global solution; χ is a vector tangent to the considered boundary and β a complex parameter; it is used to improve the efficiency of the iterative algorithm defined below. Finally, Eq. (19) is an absorbing boundary condition (ABC) approximating the Silver-Müller radiation condition for infinite domains imposed on the boundary Γ of the computational domain Ω [Sheen, 1997]. In order to approximate the solution to these equations an iterative hybridized mixed domain decomposed finite element procedure is implemented [Zyserman *et al.*, 2010, 2012]. As already mentioned, the main concept underlying this method is to split the problem in a collection of small ones whose individual solutions can be easily computed.

Consider then, as approximating mixed finite element spaces the following ones

$$V^h = \{E^h \in L^2(\Omega) : E^h|_{\Omega_j} \in P_{0,1} \times P_{1,0}\}, \quad (20)$$

$$W^h = \{H^h \in L^2(\Omega) : H^h|_{\Omega_j} \in P_{0,0}\}, \quad (21)$$

$$V_j^h = V^h|_{\Omega_j}, \quad W_j^h = W^h|_{\Omega_j}. \quad (22)$$

Here $P_{1,0}$ denotes a polynomial of degree less or equal 1 in x and less or equal 0 in z . Then, in each element, we approximate the magnetic field with a two dimensional vector, whose components are first order polynomials and the electric field with a constant. Therefore, these spaces have five degrees of freedom associated with each element, four to the electric field and one to the magnetic field, respectively. These degrees of freedom for TM mode are at the centres of the faces and centre of each element as shown in Fig.2(b).

Let us assume that the finite element partition exactly coincides with the domain decomposition, and denote with $(\cdot, \cdot)$ and with $\langle \cdot, \cdot \rangle$ the inner product in an element and on the boundary of an element respectively. Using these conventions, the iterative algorithm implemented for each frequency ω reads:

Find $(E_j^{h,n+1}, H_j^{h,n+1}, \ell_{jk}^{h,n+1}) \in V_j^h \times W_j^h \times \Psi_{jk}^h$ such that

$$\begin{aligned} & (\sigma^e E_j^{h,n+1}, \partial_z \psi - \partial_x \psi)_{\Omega_j} - (H_j^{h,n+1}, \psi)_{\Omega_j} + \sum_{\substack{k \\ \Gamma_{jk} \cap \Gamma = \phi}} \langle \beta_{jk} E_j^{h,n+1} \cdot \chi_j, \psi \cdot \chi \rangle_{\Gamma_{jk}} \\ & + \langle (1-i) \sqrt{\frac{\sigma^e}{2\omega\mu}} E_j^{h,n+1} \cdot \chi_j, \psi \cdot \chi_j \rangle_{\Gamma \cap \Gamma_j} = \\ & - (J^m, \psi)_{\Omega_j} - \sum_{\substack{k \\ \Gamma_{jk} \cap \Gamma = \phi}} \langle \beta_{jk} E_k^{h,*} \cdot \chi_k - H_k^{h,*}, \psi \cdot \chi \rangle_{\Gamma_{jk}}, \quad \psi \in V_j^h, \end{aligned} \quad (23)$$

$$((\partial_z E_j^{h,n+1} - \partial_x E_j^{h,n+1}), \varphi)_{\Omega_j} + (i\omega\mu H_j^{h,n+1}, \varphi)_{\Omega_j} = 0, \quad \varphi \in W_j^h, \quad (24)$$

$$\lambda_{jk}^{h,n+1} = \lambda_{kj}^{h,*} - \beta_{jk}(E_j^{h,n+1} \cdot \chi_j + E_k^{h,*} \cdot \chi_k) \quad \text{on } \Gamma_{jk}, \quad \Gamma_{jk} \cap \Gamma = \phi. \quad (25)$$

The mentioned complex parameter β is chosen as $\beta_{jk} = \frac{1}{2}(\sqrt{\frac{\sigma_j^e}{2\omega\mu}} + \sqrt{\frac{\sigma_k^e}{2\omega\mu}})$. The system of equations (23)-(25) yields an *algebraic system* of nine equations in each element/subdomain. The Lagrange multipliers appearing in (25) are approximations to the magnetic field *on the boundaries* of the elements; they are introduced following a technique called *hybridization*, see Santos [2009] and references therein. As the magnetic field is assumed to be piecewise constant, they are necessary to avoid -because of the continuity condition of the tangential component of the magnetic field- the constant solution throughout the computational domain. With this in mind, the space

$$\Psi^h = \{\ell^h : \ell^h|_{\Gamma_{jk}} = \ell_{jk}^h \in [P_0(\Gamma_{jk})]^2 \equiv \Psi_{jk}^h, \ell_{jk}^h + \ell_{kj}^h = 0\}$$

is introduced, where $P_0(\Gamma_{jk})$ denotes the constant functions defined on Γ_{jk} .

From one of the five equations originated in Eqs. (23)-(24) the magnetic field can be calculated; from the other four equations the electric field unknowns can be obtained, each one of the them computed just in terms of the calculated magnetic field unknown.

Further, notice that to the right hand side of each element contribute both the external source -evaluated in the centroid of the element- and the (already known) unknowns coming from adjacent elements (see last term of equation (23)).

3.1.1 Iterative schemes

The $*$ appearing as superscript of the fields and Lagrange multipliers in the right hand side of the iterative procedure given by (23)-(25) has different meanings, depending on how the iterative procedure is effectively implemented. For a Jacobi-type iterative algorithm, $*$ = n , a Seidel-type algorithm is obtained if for all subdomains Ω_k such that $j < k$, $*$ = $n + 1$ and for the ones such that $j > k$, $*$ = n . Other possible choice is the so called "Red-Black" scheme; in it half of the subdomains of the partition are labelled "Red", the other half "Black", and are disposed such that a Red subdomain has Black ones as first neighbours. In this scheme, $*$ = $n + 1$ if Ω_j is a Red subdomain, and $*$ = n if it is a Black one. In Figure 5 we display two different implementations of this scheme; in Fig. 5a the domain decomposition coincides with the finite element partition, so that the Red-Black scheme, depicted using black and white squares, has the pattern of a chess-board, we call this option "Massive domain decomposition (MDD)". On the other hand, Fig. 5b displays a situation in which each domain involves several elements of the finite element partition; this is the "Stripes domain decomposition (SDD)". The number of iterations necessary to reach convergence is dependent of the chosen implementation [Gauzellino et al., 2009].

In summary, if the MDD implementation of the Red-Black scheme is chosen, for each frequency ω the algorithm reduces to calculate in each iteration, nine algebraic equations (five for the fields and four for the Lagrange multipliers) in each one of the $n_x \cdot n_z$ elements. On the other hand, the number of degrees of freedom of the SDD implementation of the Red-Black scheme depends on how the discrete problem is solved within each stripe. Several options have been investigated in Gauzellino et al. [2009] when solving a three dimensional Helmholtz equation; it was there concluded that the MDD implementation of the Red-Black scheme is the most efficient.

3.2 Biot's equations with electroosmotic source

Once the electric field E_j is known in all domains $\Omega_j \in \Omega$, i.e., when the iterative procedure defined in the previous section has converged, we are in a position to calculate the induced fluid filtration in the partially saturated poroelastic medium Ω^s . We start by adding some

notation; let ν_{jk} be the outer normal on Γ_{jk} from Ω_j to Ω_k and ν_j the outer normal to Γ_j , see Fig.3(a). We continue by writing the domain decomposed Biot's equations, in which we want to find for every subdomain $\Omega_j \in \Omega^s$ the displacements $u_j = (u_j^s, u_j^f)$, where $u_j^s \equiv (u_x^s(x, z, \omega), u_z^s(x, z, \omega))_{\Omega_j}$ is the solid displacement and by $u_j^f \equiv (u_x^f(x, z, \omega), u_z^f(x, z, \omega))_{\Omega_j}$ the relative fluid displacement per unit volume of bulk material in the subdomain Ω_j solutions to

$$-\omega^2 \rho^b u_j^s - \omega^2 \rho^E u_j^f - \nabla \cdot \tau^b(u_j) = 0, \quad (26)$$

$$-\omega^2 \rho^E u_j^s - \omega^2 g_0 u_j^f + i\omega \frac{\eta}{k_0} u_j^f + \nabla p_f = \frac{\eta}{k_0} \mathcal{L}_0 E_j, \quad (27)$$

$$\tau_{lm}(u_j) = 2G^{fr} \varepsilon_{lm}(u_j^s) + \delta_{lm} \left(\lambda_c \nabla \cdot u_j^s + \alpha K^{av} \nabla \cdot u_j^f \right), \quad (28)$$

$$p_f(u_j) = -\alpha_B K^{av} \nabla \cdot u_j^s - K^{av} \nabla \cdot u_j^f, \quad (29)$$

$$\mathcal{G}_{jk}(u_j) + i\omega \tilde{\beta}_{jk} \Pi_{\Gamma_{jk}}(u_j) = \mathcal{G}_{kj}(u_k) - i\omega \tilde{\beta}_{jk} \Pi_{\Gamma_{kj}}(u_k), \text{ on } \Gamma_{jk} \subset \Gamma_j, \quad (30)$$

$$\mathcal{G}_{kj}(u_k) + i\omega \tilde{\beta}_{jk} \Pi_{\Gamma_{kj}}(u_k) = \mathcal{G}_{jk}(u_j) - i\omega \tilde{\beta}_{jk} \Pi_{\Gamma_{jk}}(u_j), \text{ on } \Gamma_{jk} \subset \Gamma_k, \quad (31)$$

$$-\mathcal{G}(u_j) = i\omega \mathcal{B} \Pi_{\Gamma_j}(u_j) \text{ on } \Gamma_j \cap \partial\Omega^s. \quad (32)$$

In Eq. (27) the coefficient $g_0 = 1.5\alpha_\infty \rho^E / \phi$ stands for the mass coupling coefficient; in it $\alpha_\infty = \phi^{-m^c}$, being the exponent m^c the so called Archie's consolidation factor, is the structure or tortuosity factor. The first of these coefficients represents the inertial effects associated with dynamic interactions between solid and fluid phases, and is sometimes referred to as effective fluid inertia [Haines and Pride, 2006]. Notice that the coupling between electromagnetic and mechanical processes in this equation is expressed in the right hand side, involving the electrokinetic coupling coefficient $\mathcal{L}_0$. In the constitutive relations (28)-(29), τ_{lm}^b and ϵ_{lm}^b denote the two dimensional stress and strain tensors, $\lambda_u = K_u - \frac{2}{3}G^{fr}$ and the other coefficients have been defined in Section 2.2. Eqs. (30)-(31) express, in terms of Robin transmission conditions, the consistency conditions at the interior boundaries Γ_{jk} , meaning the continuity of the solid displacement, the normal component of the fluid displacements and the generalized stresses [Santos et al., 2005]. In these expressions, $\tilde{\beta}_{jk}$ is a positive definite matrix [Santos et al., 2004b,a]. On the boundary of the domain Ω^s the first order ABC given by the Eq. (32) is employed; see the just mentioned references for details. In Eqs. (30)-(32) we have

401 denoted

$$\mathcal{G}_j(u_j) = (\tau(u_j)\nu_j \cdot \nu_j, \tau(u_j)\nu_j \cdot \chi_j, -p_f((u_j))) \text{ on } \Gamma_j, \quad (33)$$

$$\mathcal{G}_{jk}(u_j) = (\tau(u_j)\nu_{jk} \cdot \nu_{jk}, \tau(u_j)\nu_{jk} \cdot \chi_{jk}, -p_f((u_j))) \text{ on } \Gamma_{jk}, \quad (34)$$

$$\Pi_{\Gamma_j}(u_j) = (u_j^s \cdot \nu_j, u_j^s \cdot \chi_j, u_j^f \cdot \nu_j), \text{ on } \Gamma_j, \quad (35)$$

$$\Pi_{\Gamma_{jk}}(u_j) = (u_j^s \cdot \nu_{jk}, u_j^s \cdot \chi_{jk}, u_j^f \cdot \nu_{jk}) \text{ on } \Gamma_{jk}, \quad (36)$$

$$\mathcal{B} = \mathcal{R}^{1/2} \mathcal{D}^{1/2} \mathcal{R}^{1/2}, \text{ where } \mathcal{D} = \mathcal{R}^{-1/2} \mathcal{H} \mathcal{R}^{-1/2}, \quad (37)$$

402 with

$$\mathcal{R} = \begin{pmatrix} \rho^b & 0 & \rho^E \\ 0 & \rho^b - \frac{\rho^{E2}}{g_0} & 0 \\ \rho^E & 0 & g_0 \end{pmatrix}, \quad \mathcal{H} = \begin{pmatrix} \lambda_c + 2G^{fr} & 0 & \alpha K^{av} \\ 0 & G & 0 \\ \alpha_B K^{av} & 0 & K^{av} \end{pmatrix}. \quad (38)$$

403 We can introduce now the iterative hybridized domain decomposed finite element procedure,
 404 mentioning different versions of this method have been previously employed to simulate wave
 405 propagation in saturated porous media with composite matrices [Santos *et al.*, 2004b] and prop-
 406 agation of ultrasonic waves in media with patchy saturation [Santos *et al.*, 2005]. Here a brief
 407 description of the method is given; for details the reader is encouraged to read these last ref-
 408 erences.

409 To approximate each component of the solid displacements a nonconforming finite el-
 410 ement space is used; while the fluid displacements are approximated by the vector part of the
 411 Raviart-Thomas-Nedelec space of zero order [Nedelec, 1980]. Specifically, set $\theta(x) = x^2 -$
 412 $\frac{5}{3}x^4$, $R = [-1, 1]^2$ and

$$\varrho^L(x, z) = \frac{1}{4} - \frac{1}{2}x - \frac{3}{8}(\theta(x) - \theta(z)), \varrho^R(x, z) = \frac{1}{4} + \frac{1}{2}x - \frac{3}{8}(\theta(x) - \theta(z)), \quad (39)$$

$$\varrho^B(x, z) = \frac{1}{4} - \frac{1}{2}z + \frac{3}{8}(\theta(x) - \theta(z)), \varrho^T(x, z) = \frac{1}{4} + \frac{1}{2}z + \frac{3}{8}(\theta(x) - \theta(z)); \quad (40)$$

413 we define $\mathcal{Y}(R) = \text{Span}\{\varrho^L, \varrho^R, \varrho^B, \varrho^T\}$ and $\mathcal{W}(R) = \mathcal{Y}(R) \times \mathcal{Y}(R)$. Also, if $\varphi^L(x) =$
 414 $-1 + x$, $\varphi^R(x) = x$, $\varphi^B(z) = -1 + z$, $\varphi^T(z) = z$, set

$$\mathcal{Z}(R) = \text{Span}\{(\varphi^L(x), 0), (\varphi^R(x), 0), (0, \varphi^B(z)), (0, \varphi^T(z))\}, \quad (41)$$

415 and the finite element spaces $\mathcal{W}_j^h$ and $\mathcal{Z}_j^h$ are defined as usual by scaling and translating to
 416 the element Ω_j . Notice that in each domain of the finite element partition there exist twelve
 417 unknowns, four for each solid displacement component, and two for each component of the
 418 fluid displacement. A scheme of the degrees of freedom for this space of nonconforming fi-
 419 nite element is illustrated in Fig.3(b). The hybridization implies also here the introduction of

Lagrange multipliers, this time associated to generalized forces at the midpoints γ_{jk} on the inter-element boundaries Γ_{jk} , in the sense that $\lambda_{jk} \sim \mathcal{G}(u_j)(\gamma_{jk})$ [Santos *et al.*, 2005]. They belong to the following space of functions defined on the interior interfaces:

$$\mathcal{L} = \left\{ \lambda : \lambda|_{\Gamma_{jk}} = \lambda_{jk} \in [P_0(\Gamma_{jk})]^3 = \mathcal{L}_{jk}^h \forall j, k \right\} \quad (42)$$

Setting initial values $(u_j^{s,h,0}, u_j^{f,h,0}, \lambda_{jk}^{h,0})$ the iterative algorithm reads:

Find $(u_j^{s,h,n+1}, u_j^{f,h,n+1}, \lambda_{jk}^{h,n+1}) \in \mathcal{W}_j^h \times \mathcal{Z}_j^h \times \mathcal{L}_{jk}^h$ such that

$$\begin{aligned} & -\omega^2 \left(\rho^b u_j^{s,h,n+1} + \rho^E u_j^{f,h,n+1}, v^s \right)_{\Omega_j} - \omega^2 \left(\rho^E u_j^{s,h,n+1} + g_0 u_j^{f,h,n+1}, v^f \right)_{\Omega_j} \\ & + i\omega \left(g_0 u_j^{f,h,n+1}, v^f \right)_{\Omega_j} + \sum_{lm} \left(\tau_{lm}^b(v_j^{h,n+1}), \varepsilon_{lm}^b(v^s) \right)_{\Omega_j} \\ & - \left(p_f(u_j^{h,n+1}), \nabla \cdot v^f \right)_{\Omega_j} + \left\langle i\omega \mathcal{B} \Pi_{\Gamma_j}(u_j^{s,h,n+1}), \Pi_{\Gamma_j}(v) \right\rangle_{\Gamma_j \cap \partial\Omega^s} \\ & + \sum_{\substack{k \\ \Gamma_{jk} \cap \partial\Omega^s = \phi}} \left\langle i\omega \tilde{\beta}_{jk} \Pi_{\Gamma_{jk}}(u_j^{h,n+1}), \Pi_{\Gamma_{jk}}(v) \right\rangle_{\Gamma_{jk}} = \left(\frac{\eta}{k_0} \mathcal{L}_0 E_j, v^f \right)_{\Omega_j} \\ & - \sum_{\substack{k \\ \Gamma_{jk} \cap \partial\Omega^s = \phi}} \left\langle i\omega \tilde{\beta}_{jk} \Pi_{\Gamma_{kj}}(u_k^{h,*}), \Pi_{\Gamma_{jk}}(v) \right\rangle_{\Gamma_{jk}} + \sum_{\substack{k \\ \Gamma_{jk} \cap \partial\Omega^s = \phi}} \left\langle \lambda_{kj}^{h,*}, \Pi_{\Gamma_{jk}}(v) \right\rangle_{\Gamma_{jk}} \quad (43) \end{aligned}$$

$$\lambda_{jk}^{h,n+1} = \lambda_{kj}^{h,*} - i\omega \tilde{\beta}_{jk} \left[\Pi_{\Gamma_{jk}}(u_j^{h,n+1}) + \Pi_{\Gamma_{kj}}(u_k^{h,*}) \right] (\gamma_{jk}). \quad (44)$$

The same different choices for selecting the meaning $*$ present the iterative scheme Eqs. (23)-(25) are available in this case. Whatever the decision, to solve Eqs. (43)-(44) the calculations are more involved than in the former case. For example, if the chess-board implementation of the Red-Black scheme is selected, equation (43) implies that in each iteration and for each one of the elements into which the domain Ω^s is divided a 12×12 linear system of equations needs to be solved.

Notice also that the iteration parameter $\tilde{\beta}_{jk}$ is chosen as the average $\frac{1}{2}(\mathcal{B}_j + \mathcal{B}_k)$, where $\mathcal{B}$ is the matrix appearing in the absorbing boundary conditions. Furthermore, notice that the Lagrange multipliers, associated to generalized forces on the inter-element boundaries Γ_{jk} - but evaluated at the mid-points γ_{jk} - are calculated in each element by (44), which represents twelve scalar equations. Thus, for each frequency ω this algorithm reduces to solve in each iteration and for each one of the elements into which Ω^s is divided, a linear system of twelve unknowns (eight from the solid and four from the fluid) plus twelve scalar equations to get the Lagrange multipliers.

As a final remark, we mention that the spacetime solution is obtained by solving Eqs. (43)-(44) for a finite number of frequencies and taking the inverse Fourier transform. Of course, this comment is valid also for the iterative procedure used to get the electric field.

4 Parallel implementation

For the implementation of the parallel code we used the MPI standard [Pacheco, 2011]. The most efficient way to perform the calculations is to assign to each processor, as close as possible, the same number of unknowns [Alumbaugh *et al.*, 1996]. In our case, that means to assign the same number of subdomains Ω_j to each processor. If the load of the processors is not balanced, some will remain idle while others are still computing, reducing the efficiency of the algorithm. In order to fix ideas, let us work with nine processors (Fig5a), or three processors (Fig5b). Each one runs exactly the same copy of the program, and gets the input data from a single data file. Local variables are converted to global when necessary within the code; we preferred this strategy to splitting the input file in multiple ones to be read by each processor [Newman and Alumbaugh, 1997]. In Fig. 5 we display, by using different colors, the portion of the computational domain Ω assigned to each processor; the solid lines represent the virtual boundaries among them. Naturally, it is possible to do this assignment in different ways, we chose to display a very simple one for the sake of clarity. The processor $\mathbf{P}_0$ solves only in red (Fig5a) or green (Fig5b) regions, and simultaneously the other processors perform their calculations in their respective regions.

The time needed to get the solution is usually longer than one-ninth (Fig5a) or one-third (Fig5b) of the time with a serial code on one processor (assuming that processors of the same kind are used). This happens because in each iteration ‘adjacent’ processors must interchange information, so that the right hand sides of the elements situated on the borders of the region corresponding to each processor is correctly set: In Fig.5 these regions are signaled with stronger colours and delimited with dashed lines; they also show the processor number involved in the data exchange; e.g., in Fig.5a 0-3 indicates the twelve elements, six assigned to processor $\mathbf{P}_0$ (blue) and six assigned to processor $\mathbf{P}_3$ (green) which must be selected to interchange data between them. The information to be transmitted involves all the coefficients building the approximate solutions $(E_j^n, H_j^n, \ell_{jk}^n)$ for Maxwell’s equations, $(u_j^{s,n}, u_j^{f,n}, \lambda_{jk}^n)$ for Biot’s equations. Clearly, the same is valid for all the other regions; the interchange of information among processors is performed simultaneously, once Eqs. (23)-(25) (Maxwell) (43)-(44) (Biot) are solved in all nine (Fig. 5a) domains or three (Fig. 5b) domains.

We asserted that these domain decomposed algorithms are naturally rendered parallel not only because of the description given above, but also due to the fact that the amount of data to be transferred is not large. As sketched in Fig.5a and Fig. 5b the strong coloured re-

gions lay on only a single finite element width, because, as we explained above, the right hand side of the iterative procedures involve only nearest neighbours.

5 Case study: CO₂ sequestration

Although previous field results in electroseismics employed surface sources and surface receivers [Thompson *et al.*, 2007], in a more recent report on CO₂ geological storage monitoring, synthetic and field geoelectrical methods were applied to study possible gas migration [Kiessling *et al.*, 2010]. Moreover Ishido *et al.* [2013] have numerically investigated the application of self potential methods to monitor the migration of CO₂ sequestered into saline aquifers, concluding that the used methods are effective for sensing the approach of CO₂ to the well casings deep within the subsurface. On the other hand, Kim *et al.* [2013] have shown that seismics was useful to detect CO₂ saturation below 15% and that electrical resistivity was useful to detect CO₂ saturation above 15%.

Inspired by these results, we analyse the behaviour of seismic responses to an electromagnetic source deployed in a well, locating it beneath a CO₂ plume, trapped by an overlying seal layer, as we depict in Fig. 4. We simulate a time-lapse monitoring scenario, by taking three different situations; the first one when no CO₂ has been pumped into the subsurface, and therefore its saturation is 0%, a second one with a CO₂ saturation of 35%, and a third one with a CO₂ saturation of 60%. We consider a PSVTM case, so, in order to get the appropriate fields, the selected electromagnetic source is a magnetic dipole of infinite length in the strike direction (y -axis), located right beneath a CO₂ plume at 220 m depth. Its expression, to be set in Eq. (23) is $J^m = -i\omega\mu\hat{S}I(\omega)\delta(x - x_s)\delta(z - z_s)\hat{y}$; here $\hat{S}$ is the area of the current loop, $I(\omega)$ is the current and (x_s, z_s) is the center of the loop, assumed to be the source location. Seismic receivers are set in two different uncased wells, located at 10 m to the right (Well #1) and 100 m to the left (Well #2) of the horizontal position of the electromagnetic source. Notice that no conversions at the well walls are considered in our approach. This effect has been studied by [Hu and Liu, 2002], who analyzed the converted electric field during acoustoelectric logging. Surface receivers are also set, ranging from 300 m to the left to 300 m to the right of x_s , separated 4 m from each other. The time signature of the source is a Ricker wavelet with peak frequency of 60 Hz; its peak amplitude in time is located at $t = 0.16$ s.

This source is Fourier transformed, and 200 equally spaced samples $I(\omega)$ are used in the calculations; each one of them is used in the right hand side of Ampere-Maxwell's equations (23) in the above described PSVTM algorithms. Once all the results in the space-frequency

domain are obtained, they are inverse Fourier transformed to get the space-time responses that we show and analyse below.

The physical properties of the top layer, seal layer, bottom layer and CO₂ plume are derived from basic parameter values given in Tables 1 and 2 using the different effective properties described in Section 2. Notice that the effective fluid properties in the CO₂ plume are calculated assuming that the CO₂ is in its supercritical state, as is usually pumped into the subsurface [Kiessling *et al.*, 2010; Cairns *et al.*, 2012]. Although the depth at which we situated the reservoir is not deep enough to create the conditions for the CO₂ to remain supercritical [Kazemeini *et al.*, 2010], we retain the mentioned depth value to keep a reasonable computational cost, because of the size of the model. Note that the following analysis would remain exactly the same if we increased the depth of the bottom of the top layer as much as necessary to reach the pressure and temperature conditions for the CO₂ to be in supercritical state.

Concerning the calculation of the bulk electrical conductivity by means of Eq. (12) in the region occupied by the plume, we mention here that we consider the electrical conductivity of carbon dioxide negligible compared to that of the brine partially saturating it. The presence of CO₂ diminishes the bulk electrical conductivity as it would happen if air is present; however in supercritical state the reduction is not so strong as it would be if the CO₂ is gaseous [Borner *et al.*, 2013]. As a final remark concerning the computation of the electrokinetic coupling L_0 in the plume, we want to mention that when CO₂ is pumped into a reservoir a small portion dissolves in water [Carcione *et al.*, 2006b; Wang *et al.*, 2013b], forming weak carbonic acid which reacts with the present dissolved salt ions [Darwish and Hilal, 2010]. This process alters the ζ potential [Moore *et al.*, 2004], which in turn changes the electrokinetic coupling; in the present work the ζ potential does not depend on the presence of carbon dioxide. However, the latter is taken into account, as described above, by making L_0 saturation dependent. We assumed that the electrokinetic coupling is changed when the amount of CO₂ is increased and water expelled, as it changes when water-saturation is decreased, replaced by air.

5.1 Well gathers

Let us now turn our attention to our results; in Fig. 6 we display the x-component of the solid acceleration records of the receivers located in a portion of well #1, between 100 m depth and 280 m depth, before pumping CO₂ into the reservoir (Fig. 6(a)) and when the carbon dioxide saturation of the plume reached a 35 % saturation (Fig. 6(b)). The ES source is a magnetic dipole located at 220 m depth and originates the seismic signals from the interfaces be-

tween different porous media due to the electroosmotic coupling [Pride, 1994; Pride and Garambois, 2005; Haines and Pride, 2006]. In the Fig. 6(a), P and SV waves are clearly observed. They travel upwards and downwards from the seal layer and their velocities can be calculated by measuring the slopes; they are consistent with their values obtained from the dispersion relations. SV waves are well identified in the x-component for shallow and deep receivers. In Fig. 6(b) it is possible to notice changes in the character of the signals by the presence of the partially saturated CO₂ plume. The receivers located between 210 m and 220 m depth, i.e., the thickness of the plume, get a stronger signal which also lasts longer, due possible to reflections on the bases of the seal layer and plume respectively. The polarization change in the x-component of the solid acceleration observed at the depth at which the electromagnetic source is located is consistent with the fact that the x-component of the electric field, being tangent to the electric current circulating in the wire loop, changes its sign at $z = z_s$.

In Fig. 7 we display the z-component of the solid acceleration records, also for the receivers located in well #1, and for the same depth interval as in the previous figure. We observe also here that the presence of the CO₂ plume generates stronger signals for receivers located at its same depth interval, somehow "focusing" the converted seismic signals within the plume. In the case (a) of both figures, the signals are reinforced under the seal layer due to the influence of top and base of it.

Turning now our attention to the comparison of the relative amplitudes of the converted signals, we show, for both solid acceleration components, single traces measured at 190 m depth, i.e. above the seal layer in Fig. 8, and at 230 m depth, i.e. below the CO₂ plume (see Fig. 7), for the three CO₂ concentrations we are considering. It can be observed in all cases that the response for the 0% saturation is the weakest one and that the 35% saturation case is the strongest. The fact that the amplitude of the traces corresponding to the 35% saturation case is stronger than the ones corresponding to the 60% saturation case is compatible with the behaviour of the $\mathcal{C}(S_w)$ function, because in the saturation interval considered, it grows with the water saturation (40% to 65% of water, see Fig. 1), i.e., it diminishes with CO₂ saturation (from 35% to 60% of CO₂). Therefore, the electrokinetic coupling coefficient Eq. (13), and correspondingly the amplitude of the seismic source is smaller for the 60% CO₂ case than for the 35% CO₂. Note that the difference of amplitude in the traces is bigger than the corresponding in $\mathcal{C}(S_w)$, due to the factor S_w^n in this equation. It can also be observed that the amplitude of the traces measured below the plume, see Fig.7, are larger than the ones located above the seal layer, see Fig.6, for all CO₂ concentrations and both acceleration components, because pre-

cisely of the presence of the seal, which partially reflects the incident waves impinging into its base from below, due to the contrast in mechanical properties between them.

Finally in Fig. 10 we compare, for a single receiver located at 216 m depth, i.e. level with the plume, the amplitudes of the traces, for both acceleration components, recorded at well #1 and well #2. It can be clearly observed how the amplitude of the signal decays, because both of spherical divergence and viscoelasticity as it travels out of the source since the well #1 is situated at 10 m from the source whereas the well #2 is situated at 100 m from the source.

5.2 Surface gathers

Let us now consider the responses measured by the surface accelerometers, depicted in Fig. 11 for the z-component. Fig. 11(a) corresponds to the model without CO₂, while Fig. 11(b) show the results for the 35% saturation case. In the former case, two interface responses (IR) are observable. These IR arrive at the same time on surface receivers and are shown as horizontal arrivals in Figure 11(a). The topmost one, namely IR₁, corresponds to the conversion of the electromagnetic signal hitting the surface (almost) at the same time as the magnetic dipole is turned on at 220 m depth; recall that the Ricker wavelet we are using as the source signature is not centred at $t=0$ s, but it has a time delay of $t = 0.016$ s. Of course, this IR conveys no information of the subsurface structure. The other interface response, labelled IR₂ in the figure, is originated at the interfaces defined by base and top of the seal layer; notice that they are not resolved in the measured traces. The fact that the two IRs are not observable in Fig. 11(b) is just because the amplitude of hyperbolic-shaped signal is much higher than the one corresponding to the no CO₂ case. We show that this is indeed the situation in Fig. 12, where we have plotted a single trace from the surface gather of both CO₂ concentrations here considered, located at 260 m offset; the arrival times of both interface responses and the upwards travelling signal are at this offset easily individualized. The topmost interface response is, as expected, exactly the same for both situations, while the time arrivals of the second one for the two saturation cases do differ; this happens because at 35% CO₂ saturation there is a new interface response originated at the plume base, located at 220 m depth, which constructively interferes with the ones arising at the top and bottom interfaces of the seal layer. Finally, it can be noticed that the amplitude of the hyperbola is much bigger for the case with partial carbon dioxide saturation than for the case at zero saturation.

The other relevant feature, which does contain information about the carbon dioxide content, as we explain below, is the hyperbolic-shaped signal with vertex at about 0.046 s.

As we described when explaining the well gathers, this signal is due to the electroosmotic coupling at the electromagnetic source position, spreads outwards from it and hits the seal layer and CO₂ plume, generating multiple reflections inside them. Some of this reflected waves travels towards the surface, and are detected by the receivers there.

That this signal contains information of the CO₂ content can be justified as follows: on one hand, the amplitude of the signals measured for the 35% saturation case is bigger than for the 0% saturation case, as we have just shown. On the other hand, in Fig. 13 we depict surface traces recorded at 20 m offset, before pumping CO₂ into the reservoir and with CO₂ saturations of 35% and 60%. It can be here clearly seen that the amplitudes depend on the saturation in the plume, and that the amplitude of the trace for the no carbon dioxide case is weaker than the other ones, which make the IRs, detectable in the former case, invisible for the latter cases. Yet another point to be noticed is that the amplitude of the traces at the surface is about one order of magnitude weaker than the ones recorded at depth.

5.3 Parallel performance

In order to analyse the parallel performance of our algorithm, we compute the time needed to reach convergence by the iterative algorithms described by (23)-(25) and (43)-(44) for a single frequency and different number of cores, using the MDD implementation. We run the model previous to the CO₂ injection and select the source peak frequency. The number of iterations to reach convergence is not a function of the number of computing cores; i.e., the numerical procedure for Maxwell's equations ends at the same iteration number irrespective of the number of cores employed. The same happens for Biot's equations, but of course, the number of iterations to reach the convergence threshold it is not the same as Maxwell's. In our examples the chosen convergence threshold, being the value that the added relative error between successive solutions for all unknowns and for all the finite elements must reach, was set to 10^{-3} .

In Table 3 we display, for two different meshes, namely a "small" one containing 2048×1048 elements ($\approx 3.56 \times 10^7$ unknowns) and a "big" one containing 4096×2048 elements ($\approx 1.43 \times 10^8$ unknowns) an analysis of the performance of our numerical algorithm in a parallel computing environment. We display, for each mesh and as a function of the number of computing cores, the computing time, the ratio of the computing time with one core to the computing time with N cores, i.e., the so called "speedup" $\mathcal{S}_p = T_1/T_N$, and finally,

we display the so called "parallel efficiency" $\mathcal{E}_p = \mathcal{S}_p/N$ [Foster, 1995]. If the parallel algorithm was perfect, the speedup $\mathcal{S}_p$ would be a linear function of the number of computing cores; this is not what happens, mainly because the cores must interchange information to perform their computations, as explained in section 4 Parallel implementation. From the point of view of the parallel efficiency, $\mathcal{E}_p = 1$ would mean a perfectly efficient parallel algorithm; the reason of its decay with increasing number of computing cores is the same as before: the overhead due to the data transmission among processors. It is worth to mention that for the big mesh, the computation with four cores show superlinear behaviour, or parallel efficiency greater than one. Although it has been argued that this is not possible [Faber *et al.*, 1986], it has been later demonstrated that this behaviour can be observed [Agrawal *et al.*, 1994; Shan, 2002] if resources are used more efficiently, for example by reducing the RAM access time.

Notice also that the efficiency decays faster when more than 64 cores are used. This happens because the cluster we employed consists of nodes containing this core number, being the nodes interconnected through an InfiniBand network. Then, communication among cores of a single node is faster than when all cores belonging to two or four nodes have to transmit data among them.

It is also worth noticing that the efficiency decay is slower for the bigger mesh, i.e., our numerical algorithm is scalable [Foster, 1995; Pacheco, 2011]. Of course, the absolute computing time will still decay while increasing the number of cores, but if the size of the problem is not increased, the efficiency of the computation will decrease.

6 Conclusions

We have implemented a set of domain decomposed iterative finite element algorithms to approximate the solution to the Pride's equations. These algorithms can be used to model the two dimensional PSVTM and SHTE modes of both electroseismics and seismoelectrics; swapping between both techniques implies in our numerical formulation just to choose the nature of the employed source, and the order in which Maxwell's and Biot's equations are solved. In this chapter we have modelled a time lapse monitoring of a CO₂ deposition site by means of PSVTM electroseismics. Our results suggest that the wells used to pump carbon dioxide into the subsurface could be used to set magnetic dipoles as sources and accelerometers as recording devices, and the measured signals would be sensitive to the CO₂ concentration. Moreover, this setting would avoid the necessity of filtering the coseismic signal, a well known difficulty arising when both sources and receivers are set on the surface.

666 From the strictly numerical point of view, we have demonstrated that our algorithms can
667 handle large number of unknowns, and proved to be scalable. We deem that these character-
668 istics make our code a competitive one as a modelling tool both in electroseismics and seis-
669 moelectrics.

Common model parameters	
m^c	1.85
n	1.85
$K^{s,\text{sand}}$ [GPa]	35
$K^{s,\text{silt}}$ [GPa]	34
$K^{s,\text{clay}}$ [GPa]	12.3
$G^{s,\text{sand}}$ [GPa]	44
$G^{s,\text{silt}}$ [GPa]	43
$G_{s,\text{clay}}$ [GPa]	15.6
$\rho^{s,\text{sand}}$ [Kg/m ³]	2600
$\rho^{s,\text{silt}}$ [Kg/m ³]	2600
$\rho^{s,\text{clay}}$ [Kg/m ³]	2580
$D_{s,\text{sand}}$ [m]	8×10^{-5}
$D_{s,\text{silt}}$ [m]	1×10^{-5}
$D_{s,\text{clay}}$ [m]	5×10^{-7}
K^w [GPa]	2.25
η^w [Pa.s]	1×10^{-3}
ρ^w [Kg/m ³]	1000
ε^w [F/m]	$80 \varepsilon_0$
T [K]	298

Table 1. Values of model parameters used in the present work. Those not shown in this table can be obtained from the present ones using the formulae described throughout the text.

Layer parameters			
Parameter	Top Layer	Seal	Bottom Layer
$\gamma_{\text{sand}} [-]$	0.5	0.3	0.7
$\gamma_{\text{silt}} [-]$	0.4	0.45	0.25
$\gamma_{\text{clay}} [-]$	0.1	0.25	0.05
$\phi [-]$	0.15	0.2	0.33
$C_0 [\text{mol/L}]$	$1. \times 10^{-3}$	$4. \times 10^{-2}$	$4. \times 10^{-1}$
$K^{CO_2} [\text{Pa}]$	-	-	2.5×10^7
$\eta^{CO_2} [\text{Pa.s}]$	-	-	1.5×10^{-5}
$\rho^{CO_2} [\text{Kg/m}^3]$	-	-	505

Table 2. Dissimilar model parameters for the top, seal and bottom layers. The CO_2 values are used to obtain, together with the water corresponding ones, effective fluid parameters for the CO_2 plume, as explained in Section 2.

Parallel performance						
# of Cores	Mesh 2048×1024			Mesh 4096×2048		
	Time [s]	$\mathcal{S}_p$	$\mathcal{E}_p$	Time [s]	$\mathcal{S}_p$	$\mathcal{E}_p$
1	12956	1	1	57572	1	1
4	3252	3.98	0.99	13581	4.23	1.05
16	1171	11.06	0.69	5034	11.43	0.71
64	392	33.05	0.52	1600	35.98	0.56
128	288	44.98	0.35	1016	56.67	0.44
256	320	40.49	0.16	948	60.73	0.24

Table 3. *Computation times, speedup and parallel efficiency when solving a single frequency of the PSVTM algorithm, MDD implementation, for the model without CO₂. Two different discretizations are considered, one involving 2048×1024 finite elements, i.e., approximately 3.56×10^7 unknowns, the other one involving 4096×2048 finite elements, i.e., approximately 1.43×10^8 unknowns.*

679 **Figure 1.** The saturation function $C(S_w)$ employed to model the saturation dependent behaviour of the
 680 electrokinetic coupling coefficient L_0 .

681 **Figure 2.** Electromagnetic equations case. (a) The computational domain $\Omega = \Omega^a \cup \Omega^s$ integrating air
 682 and subsurface, with external boundaries Γ_j and internal boundaries Γ_{jk} . (b) Scheme for the five degrees of
 683 freedom associated with each element, four to the electric field and one to the magnetic field.

684 **Figure 3.** Biot's equations case. (a) The computational domain is only the subsurface $\Omega = \Omega^s$, with exter-
 685 nal boundaries Γ_j and internal boundaries Γ_{jk} . The outer normals ν_j and ν_{jk} are also indicated. (b) Scheme
 686 for the twelve degrees of freedom associated with each element, eight to the solid displacements and four to
 687 the fluid displacements.

688 **Figure 4.** The CO₂ geological deposition model. The electromagnetic source is at 220 m depth, below
 689 the CO₂ plume, whose top is located at 210 m and base at 220 m (being the CO₂ in supercritical state). The
 690 seismic receivers are on the surface and in two wells.

691 **Figure 5.** Each one of the displayed figures involves two layers, namely bottom layer and top layer. The
 692 former depicts the finite element partition, and domain decomposition of the computational domain Ω : (a)
 693 The MMD scheme, (b) The SDD scheme. The latter (coloured) shows the distribution of the computational
 694 domain according to the selected DD scheme: (a) nine computing cores, (b) three computing cores.

Figure 6. Well #1 x-component acceleration gather, before CO₂ pumping (a), and when CO₂ saturation reaches 35%. The electromagnetic source is at depth 220m just below the CO₂ plume which is between 210 and 220 m depth.

698 **Figure 7.** Well #1 z-component acceleration gather, before CO₂ pumping (a), and when CO₂ saturation
699 reaches 35%.

Figure 8. Well #1 acceleration traces, (a) x-component (b) z-component, before pumping CO_2 into the reservoir and with CO_2 saturations of 35% and 60%, for a receiver located at 190 m depth, i.e., above the seal layer.

Figure 9. Well #1 acceleration traces, (a) x-component (b) z-component, before pumping CO₂ into the reservoir and with CO₂ saturations of 35% and 60%, for a receiver located at 230 m depth, i.e., below the CO₂ plume.

Figure 10. Comparison of Well #1 and Well #2 solid acceleration traces, for a receiver located at 216 m depth, i.e. at the same level as the CO₂ plume, for (a) x-component (b) z-component. CO₂ saturation is 35%.

709 **Figure 11.** Surface acceleration traces, z component, (a) before pumping CO₂ into the reservoir, (b) 35%
 710 CO₂ saturation.

711 **Figure 12.** Surface acceleration traces, z component, taken at 260 m offset, before injection of CO₂ and at
712 35% CO₂ saturation.

Figure 13. Surface acceleration traces, (a) x-component (b) z-component, before pumping CO₂ into the reservoir and with CO₂ saturations of 35% and 60%, for a receiver located at 20 m offset.

References

- Agrawal, P., V. Agrawal, M. Bushnell, and J. Sienicki (1994), Superlinear Speedup in Multiprocessing Environment, in *First International Workshop on Parallel Processing*.
- Allègre, V., L. Jouniaux, F. Lehmann, and P. Sailhac (2010), Streaming Potential dependence on water-content in fontainebleau sand, *Geophys. J. Int.*, *182*, 1248–1266, doi:10.1111/j.1365-246X.2010.04716.x.
- Allègre, V., L. Jouniaux, F. Lehmann, and P. Sailhac (2011), Reply to the comment by A. Revil and N. Linde on: "Streaming potential dependence on water-content in fontainebleau sand" by V. Allègre, L. Jouniaux, F. Lehmann and P. Sailhac, *Geophys. J. Int.*, *186*, 115–117.
- Allègre, V., F. Lehmann, P. Ackerer, L. Jouniaux, and P. Sailhac (2012), Modelling the streaming potential dependence on water content during drainage: 1. A 1D modelling of SP using finite element method, *Geophys. J. Int.*, *189*, 285–295, doi:10.1111/j.1365-246X.2012.05371.x.
- Allègre, V., A. Maineult, F. Lehmann, F. Lopes, and M. Zamora (2014), Self-potential response to drainage-imbibition cycles, *Geophys. J. Int.*, *197*, 1410–1424, doi: 10.1093/gji/ggu055.
- Allègre, V., L. Jouniaux, F. Lehmann, P. Sailhac, and R. Toussaint (2015), Influence of water pressure dynamics and fluid flow on the streaming-potential response for unsaturated conditions, *Geophysical Prospecting*, *63*, 694–712, doi:10.1111/1365-2478.12206.
- Alumbaugh, D. L., G. A. Prevost, and J. N. Shadid (1996), Three-dimensional wide band electromagnetic modeling on massively parallel computers, *Radio Science*, *31*, 1–23.
- Biot, M. A. (1956a), Theory of propagation of elastic waves in a fluid-saturated porous solid: I. low frequency range, *J. Acoust. Soc. Am.*, *28*(2), 168–178.
- Biot, M. A. (1956b), Theory of propagation of elastic waves in a fluid-saturated porous solid: II. high frequency range, *J. Acoust. Soc. Am.*, *28*(2), 178–191.
- Biot, M. A. (1956c), Theory of deformation of a porous viscoelastic anisotropic solid, *J. Appl. Phys.*, *27*, 459–467.
- Biot, M. A. (1962), Mechanics of deformation and acoustic propagation in porous media, *J. Appl. Phys.*, *34*(1), 36–40.
- Bordes, C., P. Sénéchal, J. Barrière, D. Brito, E. Normandin, and D. Jougnot (2015), Impact of water saturation on seismoelectric transfer functions: a laboratory study of

- 747 coseismic phenomenon, *Geophys. J. Int.*, 200, 1317–1335, doi:10.1093/gji/ggu464.
- 748 Borner, J., V. Herdegen, J. Repke, and K. Spitzer (2013), The impact of CO₂ on the elec-
749 trical properties of water bearing porous media-laboratory experiments with respect to
750 carbon capture and storage, *Geophysical Prospecting*, 61, 446–460, doi:10.1111/j.1365-
751 2478.2012.01129.x.
- 752 Brie, A., F. Pampuri, A. Marsala, and O. Meazza (1995), Shear sonic interpretation in Gas
753 Bearing sands, *Society of Petroleum Engineers*.
- 754 Brovelli, A., G. Cassiani, E. Dalla, F. Bergamini, D. Pitea, and A. M. Binley (2005), Elec-
755 trical properties of partially saturated sandstones: Novel computational approach with
756 hydrogeophysical applications, *Water Resources Research*, 41, 12pp.
- 757 Butler, K., R. Russell, A. Kepic, and M. Maxwell (1996), Measurements of the seismo-
758 electric response from a shallow boundary, *Geophysics*, 61, 1769–1778.
- 759 Cairns, G., H. Jakubowics, L. Lonergan, and A. Muggeridge (2012), Using time-lapse
760 seismic monitoring to identify trapping mechanisms during CO₂ sequestration, *Interna-
761 tional Journal of Greenhouse Gas Control*, 11, 316–325.
- 762 Carcione, J., and S. Picotti (2006), P-wave seismic attenuation by slow-wave diffusion:
763 effects of inhomogeneous rock properties, *Geophysics*, 71(3), O1–O8.
- 764 Carcione, J., G. Seriani, and D. Gei (2003), Acoustic and electromagnetic properties of
765 soil saturated with salt water and NAPL, *Journal of Applied Geophysics*, 52, 177–191.
- 766 Carcione, J., S. Picotti, D. Gei, and G. Rossi (2006a), Physics and seismic modeling for
767 monitoring CO₂ storage, *Pure and Applied Geophysics*, 163(1), 175–207.
- 768 Carcione, J. M. (2001), *Wave fields in real media: Wave propagation in anisotropic, anelas-
769 tic and porous media*, *Handbook of Geophysical Exploration*, vol. 31, Pergamon Press
770 Inc., Amsterdam.
- 771 Carcione, J. M., S. Picotti, D. Gei, and G. Rossi (2006b), Physics and seismic modelling
772 for monitoring CO₂ storage, *Pure and applied geophysics*, 163, 175–207.
- 773 Chotiros, N., and M. Isakson (2004), A broadband model of sandy ocean sediments: Biot-
774 Stoll with contact squirt flow and shear drag, *J. Acoust. Soc. Am.*, 116(4), 2011–2022.
- 775 Darwish, N., and N. Hilal (2010), A simple model for the prediction of CO₂ solubility in
776 H₂-NaCl system at geological sequestration conditions, *Desalinization*, 260, 114–118,
777 doi:10.1016/j.desal.2010.04.056.
- 778 Douglas, J., Jr., P. J. P. Leme, J. E. Roberts, and J. Wang (1993), A parallel iterative
779 procedure applicable to the approximate solution of second order partial differential

- 780 equations by mixed finite element methods, *Numer. Math.*, 65, 95–108.
- 781 Douglas, Jr., J., J. E. Santos, D. Sheen, and Y. X (1999), Nonconforming Galerkin meth-
 782 ods based on quadrilateral elements for second order elliptic problems, *RAIRO Mathe-*
 783 *matical Modelling and Numerical Analysis (M2AN)*, 33, 747–770.
- 784 Dupuis, J. C., K. E. Butler, and A. W. Kepic (2007), Seismoelectric imaging of the vadose
 785 zone of a sand aquifer, *Geophysics*, 72, A81–A85, doi:10.1190/1.2773780.
- 786 Dvorkin, J., and A. Nur (1993), Dynamic poroelasticity: a unified model with the squirt
 787 and the biot mechanisms, *Geophysics*, 58, 524–533.
- 788 Dvorkin, J., G. Mavko, and A. Nur (1995), Squirt flow in fully saturated rocks, *Geo-*
 789 *physics*, 60, 97–107.
- 790 Faber, V., O. Lubeck, and J. A. B. White (1986), Superlinear speedup of an efficient
 791 sequential algorithm is not possible, *Parallel Comput.*, 3(3), 259–260.
- 792 Foster, J. (1995), *Designing and building parallel programs*, Addison Wesley, also avail-
 793 able online, <http://www.mcs.anl.gov/itf/dbpp/>.
- 794 Frenkel, J. (1944), On the theory of seismic and electroseismic phenomena in a moist soil,
 795 *J. Phys.*, 8(4), 230–241.
- 796 Gander, M. J., F. Margoulès, and F. Nataf (2002), Optimized schwarz methods without
 797 overlap for the helmholtz equation, *SIAM Journal on Scientific Computing*, 24(1), 38–60.
- 798 Gander, M. J., C. Japhet, Y. Maday, and F. Nataf (2004), A new cement to glue non-
 799 conforming grids with Robin interface conditions: The finite element case, in *Lecture*
 800 *Notes in Computational Science and Engineering*, edited by R. Kornhuber, R. Hoppe,
 801 J. Periaux, O. Pironneau, O. Widlund, and J. Xu, Springer.
- 802 Garambois, S., P. Senechal, and H. Perroud (2002), On the use of combined geophysical
 803 methods to access water content and water conductivity of near surface formations, *J.*
 804 *Hydrol.*, 259, 32–48.
- 805 Gassmann, F. (1951), Über die elastizität poröser medien (On the elasticity of porous
 806 media), *Vierteljahrsschrift der Naturforschenden Gessellschaft in Zurich*, 96, 1–23, cHE
 807 1856-1999 246.
- 808 Gauzellino, P., F. Zyserman, and J. Santos (2009), Nonconforming finite element methods
 809 for the three dimensional Helmholtz equation: iterative domain decomposition or global
 810 solution?, *Journal of Computational Acoustics*, 17(2), 159–173.
- 811 Gauzellino, P., F. Zyserman, and J. Santos (2010a), Seismic and electromagnetic waves in
 812 the study of layers near-surface, *Eos Trans. AGU, Meet. Am. Suppl., Abstract NS11B-21*,

- 813 91, 26.
- 814 Gauzellino, P., J. Santos, and F. Zyserman (2010b), Numerical simulation of seismoelec-
- 815 trograms, *Mecnica Computacional*, 29, 2309–2322.
- 816 Grobbe, N., and E. Slob (2013), Validation of an electroseismic and seismoelectric model-
- 817 ing code, for layered earth models, by the explicit homogeneous space solutions.
- 818 Grobbe, N., and E. Slob (2014), Seismoelectric interface response signal behaviour in
- 819 thin-bed geological settings, in *Expanded Abstracts*, pp. 3428–3422, Soc. Expl. Geo-
- 820 phys.
- 821 Grobbe, N., and E. C. Slob (2016), Seismo-electromagnetic thin-bed responses: Natural
- 822 signal enhancements?, *Journal of Geophysical Research: Solid Earth*, 121(4), 2460–
- 823 2479, doi:10.1002/2015JB012381.
- 824 Grobbe, N., J. Hunziker, and E. Slob (2014), Seismoelectric wave propagation modeling
- 825 for typical laboratory configurations: A numerical validation, in *Expanded Abstracts*, pp.
- 826 2072–2077, Soc. Expl. Geophys.
- 827 Guan, W., and H. Hu (2008), Finite-difference modeling of the electroseismic logging in a
- 828 fluid-saturated porous formation, *Journal of Computational Physics*, 227, 5633–5648.
- 829 Guichet, X., L. Jouniaux, and J.-P. Pozzi (2003), Streaming potential of a sand
- 830 column in partial saturation conditions, *J. Geophys. Res.*, 108(B3), 2141, doi:
- 831 10.1029/2001JB001517.
- 832 Haartsen, M., and S. Pride (1997), Electroseismic waves from point sources in layered
- 833 media, *Journal Geophysical Research*, 102(24), 745–769.
- 834 Haines, S. H., and S. R. Pride (2006), Seismoelectric numerical modeling on a grid, *Geo-*
- 835 *physics*, 71(6), 57–65.
- 836 Haines, S. S., A. Guitton, and B. Biondi (2007a), Seismoelectric data processing for
- 837 surface surveys of shallow targets, *Geophysics*, 72, G1–G8, doi:10.1190/1.2424542.
- 838 Haines, S. S., S. R. Pride, S. L. Klemperer, and B. Biondi (2007b), Seismoelectric imag-
- 839 ing of shallow targets, *Geophysics*, 72, G9–G20, doi:10.1190/1.2428267.
- 840 Han, Q., and Z. Wang (2001), Time-domain simulation of SH-wave-induced electromag-
- 841 netic field in heterogeneous porous media: A fast finite element algorithm, *Geophysics*,
- 842 66(2), 448–461, doi:10.1190/1.1444936.
- 843 Hornbostel, S., and A. Thompson (2007), Waveform design for electroseismic exploration,
- 844 *Geophysics*, 72(2), Q1–Q10, doi:10.1190/1.2436473.

- 845 Hu, H., and Y. Gao (2011), Electromagnetic field generated by a finite fault due to elec-
846 trokinetic effect, *J. Geophys. Res.*, *116*, 1132–1143,.
- 847 Hu, H., and J. Liu (2002), Simulation of the converted electric field during acoustoelectric
848 logging, *72nd SEG Annual International Meeting, Expanded Abstracts*, 21 (Salt Lake City,
849 Utah, USA), 348–351, doi:10.1029/2001JB001517.
- 850 Hu, H., W. Guan, and J. Harris (2007), Theoretical simulation of electroacoustic borehole
851 logging in fluid-saturated porous formation, *J. Acoust. Soc. Amer.*, *122*, 135–145.
- 852 Ishido, T., J. Pritchett, T. Tosha, Y. Nishi, and S. Nakanishi (2013), Monitoring under-
853 ground migration of sequestered CO₂ using self-potential methods, *Energy Procedia*,
854 *37*, 4077–4084.
- 855 Jackson, M. D. (2010), Multiphase electrokinetic coupling: Insights into the impact of
856 fluid and charge distribution at the pore scale from a bundle of capillary tubes model, *J.*
857 *Geophys. Res.*, *115*, B07,206, doi:10.1029/2009JB007092,2010.
- 858 Japhet, C., and F. Nataf (2001), *Artificial Boundary Conditions*, chap. The best interface
859 conditions for domain decomposition methods: Absorbing boundary conditions, Hau-
860 pagne, NY.
- 861 Jardani, A., and A. Revil (2015), Seismoelectric couplings in a poroelastic mate-
862 rial containing two immiscible fluid phases, *Geophys. J. Int.*, *202*, 850–870, doi:
863 10.1093/gji/ggv176.
- 864 Jougnot, D., N. Linde, E. Haarder, and M. Looms (2015), Monitoring of saline tracer
865 movement with vertically distributed self-potential measurements at the HOBE
866 agricultural site, Voulund, Denmark., *Journal of Hydrology*, *521*, 314–327, doi:
867 10.1016/j.jhydrol.2014.11.041.
- 868 Jouniaux, L., and T. Ishido (2012), Electrokinetics in Earth Sciences: a tutorial, *Int.*
869 *J. Geophysics*, vol. 2012 (Hindawi Publishing Corporation), Article ID 286,107, doi:
870 10.1155/2012/286107.
- 871 Jouniaux, L., and F. Zyserman (2016), A review on electrokinetically induced seismo-
872 electrics, electro-seismics, and seismo-magnetics for Earth sciences, *Solid Earth*, *7*,
873 249–284, doi:10.5194/se-7-249-2016.
- 874 Kazemeini, S., C. Juhlin, and S. Fomel (2010), Monitoring CO₂ response on surface
875 seismic data; a rock physics and seismic modeling feasibility study at the CO₂ se-
876 questration site, Ketzin, Germany, *Journal of Applied Geophysics*, *71*, 109–124, doi:
877 10.1016/j.jappgeo.2010.05.004.

- 878 Kiessling, D., C. Schmidt-Hatterberger, H. Schuett, F. Schilling, K. Krueger, B. Schoebel,
879 E. Dankwardt, and J. Kummerow (2010), Geoelectrical methods for monitoring geologi-
880 cal CO₂ storage: First results from cross-hole and surface-downhole measurements from
881 the CO₂SINK test site at Ketzin (Germany), *International Journal of Greenhouse Gas*
882 *Control*, 4, 816–826, doi:10.1016/j.ijggc.2010.05.001.
- 883 Kim, J., M. Nam, and T. Matsuoka (2013), Estimation of CO₂ saturation during both CO₂
884 drainage and imbibition processes based on both seismic velocity and electrical resistiv-
885 ity measurements, *Geophys. J. Int.*, *electronical access July 9th*, doi:10.1093/gji/ggt232.
- 886 Kim, S. (1995), Domain decomposition methods for contaminant transport in fractured
887 porous media, Ph.D. thesis, Purdue University.
- 888 Kröger, B., U. Yaramanci, and A. Kemna (2014), Numerical analysis of seismoelectric
889 wave propagation in spatially confined geological units, *Geophysical Prospecting*, 62,
890 133–147, doi:10.1111/1365-2478.12020.
- 891 Liu, H.-P., L. Don, and H. Kanamori (1976), Velocity dispersion due to anelasticity; impli-
892 cations for seismology and mantle composition, *J. Geophys. Res.*, 147, 41–58.
- 893 Mavko, G., and D. Jizba (1991), Estimating grain-scale fluid effects on velocity dispersion
894 in rocks, *Geophysics*, 56, 1940–1949.
- 895 Mavko, G., T. Mukerji, and J. Dvorkin (2009), *The rock physics handbook: Tools for seis-*
896 *mic analysis of porous media*, Cambridge University Press, The Pitt Building, Trumping-
897 ton Street, Cambridge CB2 1RP, United Kingdom.
- 898 Mboh, C. M., J. A. Huisman, E. Zimmermann, and H. Vereecken (2012), Coupled hy-
899 drogeophysical inversion of streaming potential signals for unsaturated soil hydraulic
900 properties, *Vadose Zone J.*, 11(2), doi:10.2136/vzj2011.0115.
- 901 Mikhailov, O. V., M. W. Haartsen, and M. N. Toksöz (1997), Electro seismic investigation
902 of the shallow subsurface: Field measurements and numerical modeling, *Geophysics*,
903 62, 97–105.
- 904 Moore, J., S. Glaser, and H. Morrison (2004), The streaming potential of liq-
905 uid carbon dioxide in berea sandstone, *Geophys. Res. Lett.*, 31, L17,610, doi:
906 10.1029/2004GL020774.
- 907 Munch, F., and F. Zyserman (2016), Detection of Non-Aqueous Phase Liquids Contami-
908 nation by SH-TE Seismoelectrics: a Computational Feasibility Study, *Journal of Applied*
909 *Geophysics*, doi:10.1016/j.jappgeo.2016.03.026.
- 910 Nedelec, J. C. (1980), Mixed finite elements in $\mathbb{R}^3$, *Numer. Math.*, 35, 315–341.

- 911 Newman, G., and D. Alumbaugh (1997), Three-dimensional massively parallel electro-
912 magnetic inversion-i. theory, *Geophys. J. Int.*, *128*, 345–354.
- 913 Pacheco, P. (2011), *An introduction to parallel programming*, Morgan Kaufmann.
- 914 Pain, C., J. H. Saunders, M. H. Worthington, J. M. Singer, C. W. Stuart-Bruges, G. Ma-
915 son, and A. Goddard. (2005), A mixed finite-element method for solving the poroelastic
916 Biot equations with electrokinetic coupling, *Geophys. J. Int.*, *160*, 592–608.
- 917 Perrier, F., and P. Morat (2000), Characterization of electrical daily variations induced by
918 capillary flow in the non-saturated zone, *Pure Appl. Geophys.*, *157*, 785–810.
- 919 Picotti, S., J. Carcione, J. Rubino, and J. Santos (2007), P-wave seismic attenuation by
920 slow-wave diffusion: Numerical experiments in partially saturated rocks, *Geophysics*,
921 *72*(4), N11–N21.
- 922 Pride, S. (1994), Governing equations for the coupled electromagnetics and acoustics of
923 porous media, *Phys. Rev. B: Condens. Matter*, *50*, 15,678–15,695.
- 924 Pride, S., and S. Garambois (2005), Electrostatic wave theory of Frenkel and more
925 recent developments, *Journal of Engineering Mechanics*, *131*(9), 697–706.
- 926 Pride, S., and F. D. Morgan (1991), Electrokinetic dissipation induced by seismic waves,
927 *Geophysics*, *56*(7), 914–925.
- 928 Pride, S. R., J. G. Berryman, and J. M. Harris (2004), Seismic attenuation due to wave-
929 induced flow, *J. Geophys. Res.*, *109*, 10.1029/2003JB002,639.
- 930 Raviart, P. A., and J. M. Thomas (1975), Mixed finite element method for 2^{nd} order el-
931 liptic problems, *Mathematical Aspects of the Finite Element Methods, Lecture Notes of*
932 *Mathematics*, vol. 606, Springer.
- 933 Reuss, F. (1809), Sur un nouvel effet de l’électricité galvanique, *Mémoires de la société*
934 *impériale des naturalistes de Moscou*, *2*, 326–337.
- 935 Revil, A., N. Linde, A. Cerepi, D. Jougnot, S. Matthäi, and S. Finsterle (2007), Electroki-
936 netic coupling in unsaturated porous media, *J. Colloid Interface Sci.*, *313*, 315–327.
- 937 Rubino, J. G., C. L. Ravazzoli, and J. E. Santos (2008), Biot-type scattering effects in gas
938 hydrate-bearing sediments, *J. Geophys. Res.*, *113*, B06,102.
- 939 Santos, J., C. Ravazzoli, P. Gauzellino, J. Carcione, and F. Cavallini (2004a), Simulation
940 of waves in poro-viscoelastic rocks saturated by immiscible fluids. numerical evidence
941 of a second slow wave., *J. Comput. Acoust.*, *12*, 1–21.
- 942 Santos, J. E. (1998), Global and domain-decomposed mixed methods for the solution of
943 Maxwell’s equation with application to magnetotellurics, *Numerical Methods for Partial*

- 944 *Differential Equations*, 14, 263–280.
- 945 Santos, J. E. (2009), Finite element approximation of coupled seismic and electromagnetic
946 waves in fluid-saturated poroviscoelastic media, *NMPDE*, p. doi:10.1002/num.20527.
- 947 Santos, J. E., and D. Sheen (2007), Finite element methods for the simulation of waves in
948 composite saturated poroviscoelastic media, *SIAM Journal of Numerical Analysis*, 45(1),
949 389–420.
- 950 Santos, J. E., J. Douglas, Jr., M. E. Morley, and O. M. Lovera (1992), Reflection and
951 transmission coefficients in fluid-saturated porous media, *J. Acoust. Soc. Amer.*, 91,
952 1911–1923.
- 953 Santos, J. E., C. L. Ravazzoli, and J. M. Carcione (2004b), A model for wave propaga-
954 tion in a composite solid matrix saturated by a single-phase fluid, *J. Acoust. Soc. Amer.*,
955 115(6), 2749–2760.
- 956 Santos, J. E., C. L. Ravazzoli, P. M. Gauzellino, and J. M. Carcione (2005), Numerical
957 simulation of ultrasonic waves in reservoir rocks with patchy saturation and fractal
958 petrophysical properties, *Computational Geosciences*, 9, 1–27.
- 959 Saunders, J. H., M. D. Jackson, and C. C. Pain (2008), Fluid flow monitoring in oilfields
960 using downhole measurements of electrokinetic potential, *Geophysics*, 73, E165–E180,
961 doi:10.1190/1.2959139.
- 962 Savioli, G., J. Santos, J. Carcione, and D. Gei (2014), Numerical modelling of fluid flow
963 and time lapse seismograms applied to CO₂ storage and monitoring.
- 964 Shan, J. (2002), Superlinear Speedup in parallel computation, *Tech. rep.*, Northeastern
965 University, Massachusetts.
- 966 Sheen, D. (1997), Approximation of electromagnetic fields: Part I. Continuous problems,
967 *SIAM J. Appl. Math.*, 57(6), 1716–1736.
- 968 Smoluchowski, M. (1903), Ph.D. thesis, M. Krak. Anz, 182.
- 969 Song, Y., H. Hu, and L. Rudnicki (2016), Dynamic bulk and shear moduli due to grain-
970 scale local fluid flow in fluid-saturated cracked poroelastic rocks: Theoretical model,
971 *Journal of the Mechanics and Physics of Solids*, 92, 2854.
- 972 Strahser, M., L. Jouniaux, P. Sailhac, P.-D. Matthey, and M. Zillmer (2011), Dependence
973 of seismoelectric amplitudes on water-content, *Geophys. J. Int.*, 187, 1378–1392.
- 974 Teja, A. S., and P. Rice (1981), Generalized corresponding states method for the viscosi-
975 ties of liquid mixtures, *Ind. Eng. Chem. Fund.*, 20(1), 77–81.

- Thompson, A., S. Hornbostel, J. Burns, T. Murray, R. Raschke, J. Wride, P. McCammon, J. Sumner, G. Haake, M. Bixby, W. Ross, B. White, M. Zhou, and P. Peczak (2005), Field tests of electroseismic hydrocarbon detection, *SEG Technical Program Expanded Abstracts*, pp. 565–568.
- Thompson, A., J. Sumner, and S. Hornbostel (2007), Electromagnetic-to-seismic conversion: A new direct hydrocarbon indicator, *The Leading Edge*, 26, 428–435, doi: 10.1190/1.2723205.
- Thompson, A. H., and G. A. Gist (1993), Geophysical applications of electrokinetic conversion, *The Leading Edge*, 12, 1169–1173.
- Thompson, R. R. (1939), A note on the seismic-electric effect, *Geophysics*, 4(2), 102–103.
- Thyssen, S. V., J. Hummel, and O. Rülke (1937), Die ursachen des seismisch-elektrischen effektes, *Z. Geophys.*, 13, 112–119.
- Toselli, A., and O. Widlund (2005), *Domain Decomposition Methods - Algorithms and Theory.*, Springer.
- von Helmholtz, H. (1879), Studien über elektrische grenzschichten, *Annalen der Physik und Chemie, Neue Folge*, 7(7), 337–382.
- Wang, Z., H. Hu, and W. Guan (2013a), Three-dimensional finite-difference time-domain computation of the seismoelectric field generated by a slipping fault, in *Poromechanics V: Proceedings of the Fifth Biot Conference on Poromechanics*, vol. Vienna, Australia, edited by C. Hellmich, B. Pichler, and D. Adam, pp. 2032–2041.
- Wang, Z., M. Small, and A. Karamalidis (2013b), Multimodel predictive system for carbon dioxide solubility in saline formation waters, *Environmental Science and Technology*, 47, 1407–1415, doi:10.1021/es303842j.
- Warden, S., S. Garambois, L. Jouniaux, D. Brito, P. Sailhac, and C. Bordes (2013), Seismoelectric wave propagation numerical modeling in partially saturated materials, *Geophys. J. Int.*, 194, 1498–1513, doi:10.1093/gji/ggt198.
- Wiedemann, G. (1852), Über die bewegung von Flüssigkeiten im Kreise der geschlossenen galvanischen saule., *Annalen der Physik und Chemie*, 87(11), 321–352.
- Zheng, X., H. Hu, W. Guan, and J. Wang (2015), Simulation of the borehole quasistatic electric field excited by the acoustic wave during logging while drilling due to electrokinetic effect, *Geophysics*, 80(5), D417–D427.
- Zhou, J., Z. Cui, and W. Lü (2014), Seismoelectric waves in a borehole excited by an external explosive source, *Chin. Phys. B*, 23(1), 014,301–1–014,301–6.

- 1009 Zyserman, F., P. Gauzellino, and J. Santos (2010), Finite element modeling of
1010 SHTE and PSVTM electroseismics, *J. Applied Geophysics*, *72*, 79–91, doi:
1011 10.1016/j.jappgeo.2010.07.004.
- 1012 Zyserman, F., P. Gauzellino, and J. Santos (2012), Numerical evidence of gas hydrate
1013 detection by means of electroseismics, *J. Applied Geophysics*, *86*, 98–108.
- 1014 Zyserman, F., L. Jouniaux, S. Warden, and S. Garambois (2015), Borehole seismoelectric
1015 logging using a shear-wave source: Possible application to CO₂ disposal?, *International*
1016 *Journal of Greenhouse Gas Control*, *33*, 82–102, doi:10.1016/j.ijggc.2014.12.009.
- 1017 Zyserman, F. I., and J. E. Santos (2000), Parallel finite element algorithm for three–
1018 dimensional magnetotelluric modelling, *Journal of Applied Geophysics*, *44*, 337–351.
- 1019 Zyserman, F. I., L. Guarracino, and J. E. Santos (1999), A hybridized mixed finite element
1020 domain decomposed method for two-dimensional magnetotelluric modelling, *Earth,*
1021 *Planets and Space*, *51*, 297–306.