Aerodynamic Behavior of a Floating Offshore Wind Turbine

Caroline Lienard, Ronan Boisard, Camille Daudin

► To cite this version:

Caroline Lienard, Ronan Boisard, Camille Daudin. Aerodynamic Behavior of a Floating Offshore Wind Turbine. AIAA Journal, 2020, 58 (9), pp.3835-3847. 10.2514/1.J059255 . hal-03138880

HAL Id: hal-03138880

<https://hal.science/hal-03138880>

Submitted on 11 Feb 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Aerodynamic behavior of a floating offshore wind turbine

Lienard C.,¹ Boisard R.,² Daudin C.³

ONERA – The French Aerospace Lab

F-92190 Meudon, France

The flowfield around the rotor blades of a wind turbine is extremely complex due to the occurrence of several aerodynamic phenomena. It is all the more true for floating offshore wind turbines (FOWT), for which the six rigid-body motions of the floating platform can induce blade/wake interactions. Therefore conventional numerical approaches for wind turbine applications, such as BEM, may be questionable for an accurate prediction of floating wind turbine aerodynamic loads. Consequently, the current paper investigates the aerodynamic behavior of a FOWT subjected to several idealized prescribed motions, representative of a wave movement, based on CFD simulations. These results, obtained on the NREL 5-MW wind turbine, are compared to previous results found in the literature and analyzed to provide a better understanding of the involved aerodynamic phenomena.

I. Nomenclature

a	=	shaft angle (°)
δ	=	precone angle (°)
R	=	NREL 5-MW blade radius (m)
A_{PITCH}	=	<i>pitch</i> motion amplitude
f_{PITCH}	=	<i>pitch</i> motion frequency
θ	=	<i>pitch</i> angle
A_{SURGE}	=	<i>surge</i> motion amplitude
f_{SURGE}	=	<i>surge</i> motion frequency

¹ Research Scientist, Aerodynamics, Aeroelasticity, Acoustics Department (DAAA).

² Research Scientist, Aerodynamics, Aeroelasticity, Acoustics Department (DAAA).

³ Intern, Aerodynamics, Aeroelasticity, Acoustics Department (DAAA).

dx = surge displacement

C_p = pressure coefficient

II. Introduction

In 2015, within the framework of the COP21 meeting held in Paris, France has committed itself to cover 32% of its energy demand with renewable energy by 2030. To do so, France benefits from a privileged location for marine renewable energies to emerge and develop, with its 3 500 km of coastline considering metropolitan areas only. Offshore wind turbines are so far the preferred solution, since they are currently technologically more advanced than water power or tidal power technologies. However, if fixed offshore wind turbines are already widely installed in several countries, floating offshore wind turbines (FOWT) are still in the prototype stage. They consist in an attractive alternative compared to fixed wind turbines in order to move them away from the coasts. They are nevertheless also exposed to more severe environmental conditions, and particularly to the wave movement.

The interest in FOWT being recent, the scientific literature dealing with this topic develops progressively. From almost one decades, IEAWind task 23 and then 30 were dedicated to the topic of offshore wind turbines (OC3 [1], OC4 [2], OC5 [3] and now OC6). These tasks aim at modeling the whole system including fixed and floating wind turbine but until now, only simplified approaches were used for the aerodynamic parts. The use of more advances models with the focus on aerodynamic analysis is more recent. Sebastian and Lackner [1], Tran et al. [5][6][7], Leble et al. [8], Bekiropoulos et al. [9], Cheng et al. [10], Li et al. [11] and the PhD thesis of V. Leroy [12] employ a variety of numerical methodologies to characterize the aerodynamics of these FOWT, while experimental results obtained on FOWT remained scarce for a long time because of the cost of the needed facilities. The PhD thesis of Courbois from Centrale Nantes [13] can however be mentioned with an experimental investigation of a FOWT under wind and wave loads. More recently, thanks to HIL techniques, [14] aerodynamic experiments dedicated to FOWT became more affordable and more literatures appeared on the subject. The most important experimental projects may be the EU H2020 project LIFES50+ [15] and UNAFLOW project [16] which also associate numerical simulations to experiments.

To investigate the wind turbine aerodynamic behavior, ONERA can rely on two different numerical tools with different fidelity level, already widely used and validated on aeronautical applications: PUMA as a fast-response

approach, and *elsA* as a high fidelity code. These tools have already been tested and validated on the MEXICO wind turbine in the framework of the IEA Task 29 project MexNextIII [17], the New MEXICO experimental database being used to perform a code to code comparison between all the participants.

The current paper aims at quantifying and analyzing the effect of several prescribed motions on the aerodynamic performances of a floating wind turbine, and will mainly rely on *elsA* CFD results. Some PUMA results can however be punctually used in order to have access to information which are more easily extracted from lifting line approaches.

III. Floating wind turbine geometry and associated motions

The selected wind turbine for this investigation is the NREL 5-MW wind turbine, designed by the National Renewable Energy Laboratory to be a representative utility-scale wind turbine suitable for a floating offshore installation [18]. It is a conventional three-bladed upwind turbine, with a rotor diameter of 126 m. The rotor blades are composed of series of DU (Delft University) and NACA 64xxx airfoils from the hub to the tip. The mast is 90 meters high but it should be noted that the mast will not be taken into account in the present simulations. All the details about the NREL 5-MW wind turbine can be found in [18]. The more significant parameters and properties are summarized in Table 1 below.

Table 1 - Design parameters of the NREL 5-MW wind turbine

Rating	5 MW
Rotor orientation, configuration	Upwind, 3 blades
Rotor, hub diameter	126 m, 3m
Hub height	90 m
Cut-in, rated, cut-out wind speed	3 m.s ⁻¹ , 11.4 m.s ⁻¹ , 25 m.s ⁻¹
Cut-in, rated rotation regime	6.9 rpm, 12.1 rpm
Rated blade tip speed	80 m.s ⁻¹
Shaft tilt, precone	5°, 2.5°

Once the wind turbine geometry chosen, a bibliographic review helped to define which motion to prescribe to the wind turbine, both representative of the floating behavior and simple enough to implement. The platform floating motion indeed includes six degrees of freedom, three translational and three rotational components (Fig. 1):

- The *heave* motion, which is the vertical translational movement;
- The *sway* motion, for the lateral translational movement;
- The *surge* motion, which is a translation in the axial direction;

- The *yaw* motion, a rotation around the vertical axis;
- The *pitch* motion, which is the rotational movement around the lateral axis;
- The *roll* motion, for the rotation around the axial axis.

Sebastian and Lackner [1] deeply investigated these 6 DOFs and characterized the modes which result in unsteady aerodynamic phenomena, making aerodynamic analysis of offshore floating wind turbines a challenge. Their main conclusions, based on FAST simulations, are that “*Surge* and *pitch* DOFs appear to be the largest amplitudes modes” for all the simulated platforms, leading them to be chosen for the current investigation.

These motions can possibly amplify existing unsteady aerodynamic phenomena, such as blade-vortex interaction and dynamic stall, or induce unsteady effects due to wind shear, gradient across the rotor disk, skewed flow and rapid local velocity modifications. Figure 2 notably emphasizes to which extent the flowfield around the wind turbine during a pitching motion becomes highly complex and unsteady: as the rotor begins to pitch back, it can interact with its own wake, leading to the development of recirculation areas. This explains why most design methods, usually based on the blade element momentum theory, can not accurately predict the aerodynamic performances and behavior of FOWT: unsteady numerical tools, “of higher-fidelity ‘engineering-level’ models than commonly in use” [1] are needed to model these effects.

Fig. 1 Degrees of freedom for an offshore floating wind turbine (from [5])

Fig. 2 Platform pitching motion and its effect on the surrounding flowfield (from [19])

IV. Numerical approaches

As already mentioned, two different levels of numerical simulation are used at ONERA on wind turbines: a fast-response one, based on the lifting line theory coupled to a free wake model, and a high fidelity one, based on unsteady CFD computations. The current investigation relies on complex time-accurate CFD simulations but the results may be complemented when necessary by free-wake information (local angle of attack or velocities for example).

A. Lifting line/Free-Wake approach

The PUMA (Potential Unsteady Methods for Aerodynamics) code, which is developed at ONERA since 2013, is based on a long lasting knowledge about free wakes methods for helicopter aerodynamics. It is built on a coupling between an aerodynamic module and a kinematic module. The aerodynamic module relies on a free wake model and a lifting line approach. The free wake model is based on Mudry theory [20] which rigorously describes the unsteady evolution of a wake modeled by a potential discontinuity surface. The lifting line method relies on 2D airfoils characteristics. Different time discretizations are available in order to balance between accuracy, scheme stability and computational time. Concerning the kinematic module, it is based on a rigid multi-body system approach using a tree-like structure with links and articulations. In order to reduce computational time, the code has been parallelized using OpenMP and the Multilevel Fast Multipole Method has been implemented for the computation of the velocities induced by each wake panel on any element. PUMA is extensively used at ONERA for any aerodynamic study which requires low computational cost or a large amount of parametrical investigation like pre-design studies. It has been successfully applied on quite a lot of different fixed wings and rotating wings configurations like propellers, counter rotating open rotors, helicopter rotors [21] and more recently wind turbines [17].

B. CFD approach

The CFD computations are performed using *elsA* CFD package, co-owned by Airbus, Safran and ONERA [22][23]. This package contains a RANS flow solver and several external modules, especially pre- and post-processing tools (*Cassiopee* tools [24]). *elsA* is dedicated to the numerical simulation of the compressible viscous mono-species steady and unsteady flows, on three-dimensional (or two-dimensional, or axisymmetric) multi-block

structured meshes. It solves the compressible (U)RANS equations in a finite volume cell-centered formulation. The mesh strategy is based on the Chimera approach: a curvilinear body-fitted grid is built around each component, which are assembled and embedded into a set of Cartesian background grids.

The wind turbine model includes the blades, a rotating hub and a fixed rear nacelle (Fig. 3), the influence of the mast being neglected. When the *pitch* and the *surge* motions are implemented, the whole turbine is moving in the fixed background grid. The total grid size is about 162 million points: approximately 7.5 million points per blade (Fig. 4), 3.5 million points for the nacelle and the hub, 132 million points in the background grids. In order to correctly model and convect the blade tip vortices, the smallest cell size in the Cartesian background grid is equivalent to 10% of the mean chord of the blade. Moreover, so as to enable good wake conservation even when the wind turbine is moving, this finest background grid level extends far beyond the wind turbine (up to $2.25 R$), and also upstream (Fig. 4).

Fig. 3 NREL 5-MW parts considered for the CFD simulations

Fig. 4 Blade tip surface mesh (left) and wind turbine in the Cartesian background grid (right)

All these simulations are performed using the 2nd order AUSM+P spatial scheme (chosen for its low dissipation and its low-Mach capabilities), with a time integration ensured by a 2nd order implicit backward finite difference scheme solved by a Newton algorithm. In order to ensure good accuracy, the number of Newton sub-iterations was set to 25. A physical timestep corresponding to an azimuthal angle of 1° was used for the first revolutions and then refined up to 0.5°. The chosen turbulence model is $k - \omega$ Kok. All CFD computations consider a freestream velocity of $11.4 \text{ m} \cdot \text{s}^{-1}$, constant rotating speed of 12.1 rpm and fixed blade pitch. In the real world wind turbine would encounter non uniform turbulent inflow, and RPM and blade pitch would be adjusted as a function on the inflow during the pitching and surge motion. However using these simplified conditions will enable to better isolate and understand the underling aerodynamic phenomenon, before moving to more realistic simulations.

These CFD simulations are extremely expensive, with a computational time of about 27000 CPU hours per rotor revolution. Most of these computations were performed on the HPC resources of CINES under the allocation 2018 – A0032A10280 made by GENCI.

V. Validation on the fixed NREL 5-MW wind turbine

Both PUMA end *elsA* simulations have first been performed on the baseline case of the fixed NREL 5-MW wind turbine. They have enabled to define some numerical parameters, especially for the free-wake approach, and have been validated against the thrust and power curves provided by the NREL (FAST code) and CFD obtained by Kirby et al [25] (Fig. 5**Erreur ! Source du renvoi introuvable.**).

Fig. 5 **Erreur ! Source du renvoi introuvable.** reveals that the power curve is very well reproduced by PUMA simulations, especially up to the rated regime. More discrepancies are observed on the thrust curve between FAST and PUMA even if the global trend is very similar. These discrepancies may be partly explained by the fact that FAST takes into account the blade deformation whereas both PUMA and *elsA* simulations consider rigid blades. The CFD results obtained with *elsA* at the nominal operating point are in very good agreement with FAST : the thrust is 3.2 % lower than in FAST results, whereas the power is 2.4 % higher. It has to be noted that 16 rotor revolutions have been computed to obtain these results, with a timestep of 0.5° on the last 9 revolutions (1° before).

Consequently, both methods (PUMA and *elsA* simulations) are validated on this fixed wind turbine case with regard to performance evaluation.

Fig. 5 Fixed WT: Power and thrust comparison between FAST, PUMA *elsA* and CFD results obtained by Kirby et al. [25]

Furthermore, the wake downstream the wind turbine was shown to be well captured and convected without being too much dissipated. Fig. 6 indeed emphasizes that 3 rotor revolutions are kept in the wake, which will be of great interest to investigate blade/wake interactions once the FOWT motion will be taken into account.

Fig. 6 Fixed WT: Q-criterion isosurface and velocity in the symmetry plane from *elsA* simulation

VI. Simulation of the floating offshore wind turbine: *pitch* motion

A. Motion description

The *pitch* motion of the FOWT in *elsA* and PUMA computations consists in a prescribed motion applied to the whole wind turbine grids (except the background grids), defined as follows:

$$\theta(t) = A_{PITCH} * \sin(2\pi f_{PITCH}t)$$

A_{PITCH} refers to the *pitch* motion amplitude and f_{PITCH} to the *pitch* motion frequency. The center of rotation of the pitching motion was chosen to be at the bottom of the mast, i.e. 90m below the rotation center of the wind turbine. Even if it could be seen as a simplification of a real motion, it will enable to compare to other study from the literature. Several amplitudes have been simulated, including 4° and 8° , whereas the frequency was decided to be kept to half the blade rotation frequency (ie. approximately 0.1 Hz). This was motivated by the fact that it would ease the post processing and the analysis to have a periodic movement, and this value was also similar to what was found in the literature. It should be noted that the blade n°1 is always located at 12 o'clock at the beginning of the motion, which starts in the backward direction.

Fig. 7 is a representation of the *pitch* motion (for $A_{PITCH} = 4^\circ$) and should help to analyze the upcoming results. The wind turbine *pitch* angle is plotted over two pitching periods (4 rotor revolutions) in red (a positive *pitch* angle

corresponding to a backward position), as well as the *pitch* angular velocity in green. One can already notice that the maximum angular velocity in absolute terms is obtained when the wind turbine comes back to its initial position (T_0 and T_4 , corresponding to $\theta(t) = 0^\circ$). The inflow velocity normal to the rotor plane (at the hub center) is finally added in grey and defined as follows:

$$V_{norm} = V_{WIND} * \cos(\theta) - \dot{\theta} * h_{MAST}$$

The maximum normal inflow velocity is obtained at T_4 , when the wind turbine comes back to its initial position in a forward motion.

The analysis of the *pitch* motion cases performed in the following sections will refer to the eight different timestep (T_0 to T_7) as they are defined in Fig. 7

Fig. 7 Pitch motion analysis (for $A_{PITCH} = 4^\circ$ and $f_{PITCH} \approx 0.1\text{Hz}$): WT *pitch* angle (red), WT *pitch* angular velocity (green) and relative axial velocity (grey)

B. Wind turbine loads

The results obtained in terms of global thrust and power for both amplitudes as functions of the pitch angle are plotted in Fig. 8 **Erreur ! Source du renvoi introuvable..** over 2 pitching periods, forming a hysteresis loop. The respective mean values are added to the plot and compared to the fixed wind turbine case.

One can notice that the mean thrust is only slightly impacted by the *pitch* motion: it is decreased by 1.4% for $A_{PITCH} = 4^\circ$ and by 5.8% for $A_{PITCH} = 8^\circ$. However, the difference is significantly larger when looking at the power curves: the power of the wind turbine is increased by 10.4% for $A_{PITCH} = 4^\circ$ and by 37.6% for $A_{PITCH} = 8^\circ$. Contrary to the thrust curve which is quite circular, the power hysteresis loop is indeed flattened in its lower part,

that is to say between T_6 and T_2 . This portion of the curve corresponds to the backward motion phase, which induces the lowest normal inflow velocities on the rotor plane (cf. Fig. 7).

In addition to this mean power value increase, the wind turbine undergoing a *pitch* motion with a 4° -amplitude (which is perfectly realistic) experiences tremendous instantaneous aerodynamic power variations (from almost 0MW to 12MW).

These results are very close to those obtained on the same wind turbine in [7] and on the DTU 10MW wind turbine in [8]. It is also very clear that the power curve maximum and minimum seen in Fig. 8 are linked to the normal inflow velocity extrema presented in Fig. 7 respectively at T_4 and T_0 .

Fig. 8 Pitch motion: Global thrust and power as function of *pitch* angle

Obviously, the same behavior is visible when looking at the power curves on each blade (Fig. 9): when the *pitch* amplitude reaches 8° , the aerodynamic power of each blade during the backward motion phase becomes very low, reaching slightly negative values between T_6 and T_0 for blades 1 and 2, and between T_0 and T_2 for blades 1 and 3. However the global power remains positive because of the third blade. One should keep in mind that a real wind turbine would not reach negative power values, the wind turbine would only slow down. The prescribed constant rotation speed is responsible for this and is a limitation on such computations.

Fig. 9 Pitch motion: Blade power variations as function of time

Fig. 9 **Erreur ! Source du renvoi introuvable.** also emphasizes that the loads variations are more important on blade 1: this is due to the fact that blade 1 is located at 12 o'clock at the beginning of the motion, inducing a higher lever arm with respect to the pitching motion center compared to the other blades.

It can also be interesting to look at what happens locally on each blade. To do so, PUMA simulations have been performed in addition to CFD: it is indeed much easier to get local blade section velocities and angles of attack from a lifting-line/free-wake approach than from a CFD result. Moreover, PUMA and *elSA* simulations have provided comparable results in terms of loads and loads variations on the baseline case. Thus, Fig. 10 (respectively Fig. 11) depicts the local blade section velocity magnitude variations (respectively the local blade section angle of attack) due to the 4° *pitch* motion. While this kind of plots are commonly used to analyze helicopters rotor performance, here, two rotor revolutions have to be plotted in order to have one full *pitch* motion period.

Even if the fluctuations of inflow velocity normal to the rotor plane are rather important (of the order of 50%, Fig. 7), Fig. 10 reveals that the local blade section velocity variations due to the motion are very limited on the three blades and mainly located near the blades root. On such configurations, the local inflow is indeed dominated by the rotational velocity. However, this modification of the normal inflow velocity has a significant impact on the blade section angle of attack, as emphasized in Fig. 11 which shows strong variations on all blades: while this angle of

attack remains close to $+5^\circ$ on the fixed wind turbine case, the *pitch* motion induces variations between -2° (during the backward motion phase) to approximately $+10^\circ$ (during the forward motion phase).

Fig. 10 Pitch motion: Local blade section velocity magnitude variations due to the *pitch* motion with $A_{PITCH} = 4^\circ$ (in %)

Fig. 11 Pitch motion: Local blade section angle of attack for the 4°-amplitude test case

When the *pitch* amplitude is increased to 8° for the same frequency, the fluctuations of normal inflow velocity are obviously larger, leading to larger variations of local angles of attack (from -6° to +19°). In such conditions, the wind turbine is operating out of its nominal design conditions, which could lead to very low (or even negative) values of aerodynamic power. For example, the NACA64 airfoil characteristics are presented in Fig. 12 with the angle of attack variations obtained for both amplitudes *pitch* motion at 75% radius. One can notice that this airfoil operates close to zero lift and close to stall conditions when $A_{PITCH} = 4^\circ$, and negative lift and real stall conditions are reached when the amplitude is increased to 8°. Although purely 2D and quite simplified (neglecting 3D effects), this behavior explains both the very low power values obtained during the backward motion of the wind turbine and the limitation of the global power increase obtained during the forward motion (due to blade stall).

Fig. 12 NACA64 airfoil characteristics

C. Blade spanwise loads

The mean blade spanwise loads obtained for the fixed WT and for $A_{PITCH} = 4^\circ$ are plotted in Fig. 13 together with their envelope (maximum and minimum values). The mean spanwise thrust and power are unsurprisingly almost identical on the three blades for the fixed WT: only slight differences can be seen because of the shaft angle. However these discrepancies are negligible compared to the ones obtained for the *pitch* motion case.

For both thrust and power distributions, the first blade, which is located at 12 o'clock at the beginning of the motion, differs from the two others: this blade n°1 produces less thrust and more power. This result is consistent with the results presented in Fig. 9 **Erreur ! Source du renvoi introuvable.** Focusing on the 4° -amplitude case envelope demonstrates that the loads variations on blade n°1 are also higher than on the two other blades. These discrepancies between the blades in terms of mean loads and load variations can be a big issue on a real wind turbine regarding blades deformation, vibrations, fatigue,... While this behavior will definitely exists in real conditions, it is overestimated in the CFD simulations because of the wind turbine and motion frequencies synchronization along with the prescribed constant rotation speed.

Fig. 13 Pitch motion: Spanwise loads on the 3 blades compared to the fixed WT case

D. Wake visualizations

For both pitching amplitude, the velocity contours in the symmetry plane of the wind turbine wake at several timesteps is shown in Fig. 14 . This representation highlights the vortices trajectory and interactions between the wind turbine and its own wake. The presented timesteps correspond to the markers (T_0 , T_1 , T_2 ,...) defined in Fig. 7, where a positive *pitch* angle corresponds to a rear position.

First, one can notice that the wake is really disrupted for the 8° -amplitude case. This amplitude is slightly excessive compared to what can happen on a real FOWT in nominal conditions but the idea was to amplify the motion so as to confirm the physical phenomena observed on the 4° case.

Then, on both cases, the simulations meet the expectations in terms of wake conservation since several interaction phenomena can be identify: blade/vortex interactions, vortex pairing...

In order to help analyzing these interactions, a new figure is produced based on helicopter reasoning and on Leble and Barakos investigation on FOWT aerodynamic [8]. When studying helicopters in descending flight, the ratio between the normal velocity to the rotor plane (here $V_c = -V_{norm}$, where the negative sign is added to agree with helicopter notations) and a “theoretical” induced velocity in hover for a given thrust (V_h) is often plotted to identify VRS (Vortex Ring State) conditions [26]. The same approach is used in Fig. 15 (based on [8]) with $V_h = \sqrt{T/2\rho S}$, T being the mean thrust obtained on a pitching period and S the rotor area. Vortex Ring State

conditions would be reached for $-1 \leq V_c/V_h \leq 0$ (thus approximately when the wind turbine moves beyond its wake).

When looking at the wake visualizations for $A_{PITCH} = 4^\circ$, some blade/vortex interactions can be seen, especially in Fig. 14a): the new tip vortex is emitted very close to the previous one due to the maximum *pitch* angular velocity at T_0 . These interactions actually do not occur for the maximum *pitch* angle of the wind turbine (T_2) but for the minimum inflow velocity normal to the rotor plane. The wind turbine is not truly operating in VRS since the blade is not immersed in the wind turbine wake, which is confirmed by Fig. 15. The wake is however in a turbulent state with very strong interactions between blade tip vortices. Some vortex pairing phenomena can also be identified (from Fig. 14e) to Fig. 14h)), producing wake meandering and leading to instabilities in the flow downstream the wind turbine.

Comparing $A_{PITCH} = 4^\circ$ and $A_{PITCH} = 8^\circ$ side by side outlines that the observed phenomena at lowest pitching amplitude are strongly amplified for higher *pitch* motion. Fig. 15 reveals that for $A_{PITCH} = 8^\circ$, the rotor partially enters VRS between T_7 and T_0 . This is confirmed by Fig. 14a), where the wind turbine has moved beyond its own wake, with the new tip vortex clearly emitted downstream the preceding blade one. These two vortices then roll-up together (Fig. 14c)) and are convected faster in the wake compared to the other vortices (from Fig. 14d) to Fig. 14h)). Once again, this results in wake meandering and strong instabilities downstream the FOWT. It has to be noted as well that these interactions rather occur on the top of the wind turbine: this is both due to the shaft angle and to the local axial velocity which is higher at the top of the wind turbine than at the bottom.

Fig. 14 *Pitch* motion: velocity in the symmetry plane at different timesteps for $A_{PITCH} = 4^\circ$ and $A_{PITCH} = 8^\circ$

Fig. 15 Pitch motion: VRS identification scheme

VII. Simulation of the floating offshore wind turbine: *surge* motion

A. Motion description

The *surge* motion of the FOWT in *elsA* computations is prescribed in the same way as the *pitch* motion using:

$$dx(t) = A_{SURGE} * \sin(2\pi f_{SURGE}t)$$

A_{SURGE} refers to the *surge* motion amplitude and f_{SURGE} to the *surge* motion frequency. Two *surge* amplitudes have been simulated (8m and 16m) with the same constant frequency (half the blade rotation frequency).

Fig. 16 is a representation of the *surge* motion ($A_{SURGE} = 8m$) and should help to analyze the upcoming results. The wind turbine axial displacement is plotted over two *surge* periods in red (a positive dx corresponding to a backward position), as well as the displacement velocity in green. Comparably to what happens for a *pitch* motion, the maximum displacement velocity in absolute terms is obtained when the wind turbine comes back to its initial position (T_0 and T_4 , corresponding to $dx(t) = 0$). The inflow velocity normal to the rotor plane (in grey) can be defined using:

$$V_{norm} = V_{WIND} - d\dot{x}$$

Its maximum is reached at T_4 , when the wind turbine comes back to its initial position in a forward motion.

The analysis of the *surge* motion cases performed in the following sections will refer to the eight different timesteps (T_0 to T_7) as they are defined in Fig. 16

Fig. 16 Surge motion analysis (for $A_{SURGE} = 8m$ and $f_{SURGE} \approx 0.1Hz$): WT axial displacement (red), WT displacement velocity (green) and relative axial velocity (grey)

B. Wind turbine loads

The wind turbine global thrust and power are represented as function of axial displacement in Fig. 17. Despite large variations on the global thrust and power, the same behavior is observed compared to the *pitch* motion: the mean thrust is only slightly decreased compared to the fixed WT case, whereas the mean power is greatly impacted (+14.8% for $A_{SURGE} = 8m$, +56.6% for a 16m *surge* amplitude). The instantaneous power varies from 0MW to 13MW for the 8m *surge* motion. The 16m *surge*, which is slightly excessive compared to what should happen on a real wind turbine in usual operating conditions, confirms and accentuates the phenomena with power variations from -0.6MW to 23.6 MW. Thrust and power maxima and minima are respectively obtained at T_4 and T_0 , which respectively correspond to the maximum and minimum normal inflow velocity.

The hysteresis loop of the power is considerably flattened on the lower part due to very low inflow velocity and on the contrary sharpened in its upper part. Strong interactions between the wind turbine and its wake should therefore be expected at T_0 when looking at the instantaneous flowfield. Since the *surge* motion consists in a pure translation, neglecting the small effect of the shaft angle, the incoming flow is axisymmetric: at a given time, all blades are operating in the same conditions, and thus produce equivalent thrust and power (not shown here)

Fig. 17 Surge motion: Global thrust and power as function of axial displacement

Fig. 18 shows the local blade section velocity magnitude variations and angle of attack obtained using PUMA. Comparably to what happened during the *pitch* motion, the motion has only little impact on the local blade section velocity magnitude but a much larger one on the local angle of attack. These maps also give a deeper understanding of the wake effect on the wind turbine. Let's compare the results obtained on blade 1 at T_2 and T_6 , which correspond to the extremum displacements of the wind turbine, respectively downstream and upstream the central position (highlighted in red in Fig. 18). At these positions, the displacement velocity is equal to zero (Fig. 16) so the wind turbine is supposed to see an identical incoming flow. The obtained local velocity magnitude and angle of attack are nevertheless different, due to the wake induced velocities. At T_2 , the wind turbine is very close to its own wake, producing higher induced velocities on the blade, decreasing the local blade section velocity and angle of attack. At T_6 , the wind turbine is further away from its wake, so the local velocity and angle of attack are higher. While physical, this effect is slightly overestimated in these PUMA simulations, because of the free-wake approach itself (no dissipation of the vortices).

Fig. 18 Surge motion: Local blade section velocity magnitude and angle of attack variations due to the surge motion with $A_{SURGE} = 8m$ (in %)

C. Blade spanwise loads

The mean spanwise aerodynamic power is shown in Fig. 19 for the two surge amplitudes (identical on the three blades) along with the spanwise power envelope. This confirms the extreme variation of power with negative values on the 16m surge motion.

Fig. 19 Surge motion: Spanwise power compared to the fixed WT case

D. Wake visualizations

Finally, the wake of the wind turbine at the identified timesteps $T_0, T_1, T_2, \dots$ is presented for both *surge* amplitudes in Fig. 20, and the “helicopter-like” VRS scheme in Fig. 21. It is reminded that a positive axial displacement corresponds to a downstream position. The wakes are once again well captured and convected with several observable interactions phenomena.

First, it can be noticed that the *surge* motion with $A_{SURGE} = 8m$ is equivalent in terms of normal inflow velocity at the wind turbine nacelle to the *pitch* motion with $A_{PITCH} = 4^\circ$ (Fig. 7 vs. Fig. 16). Less aerodynamic interactions are yet visible for the *surge* case (for example Fig. 14a) vs. Fig. 20a)). This is due to the fact that the *surge* motion is a pure translation: the wind turbine remains a little bit further from its wake since it is not inclined, and the displacement velocity at its top is the same as at its center, thus a little bit lower compared to the *pitch* motion.

It appears that the FOWT experiencing 8m-amplitude *surge* motion does not enter a VRS regime. At T_0 , the tip vortex is emitted very close to the previous one but the blade is not immersed in the wake (Fig. 20a)). This observation is in agreement with Fig. 21.

On the other hand, interactions become significant for $A_{SURGE} = 16m$ and the wind turbine experience severe VRS conditions. Fig. 20a) even highlights that at T_0 , when blade 1 crosses the symmetry plane, its tip vortex is emitted almost in the core of the previous one, they immediately merges and no new vortex is seen in Fig. 20b). Afterward, blade 2 tip vortex is emitted very close to this “double-vortex” (as seen at T_2 in Fig. 20c)), leading to vortex pairing and this pair is convected faster in the wake compared to the other vortices (cf. Fig. 20d), e) and f)) and end up by rolling around previous vortices (cf. Fig. 20g), h) and a)). Vortex meandering quickly appears in the wake, leading to significant flow instabilities behind the FOWT.

The FOWT undergoing this 16m-amplitude *surge* motion even actually switches to a propeller state around T_0 (both thrust and power **Erreur ! Source du renvoi introuvable.** are negative in Fig. 17). The curve from Fig. 21 does not clearly outline it because of some limitations of the helicopter approach adopted to produce it: the mean thrust over one motion *surge* is used to estimate the “theoretical” hover induced velocity, keeping the ratio V_c/V_h from reaching zero with non zero axial velocities. Moreover, V_h is estimated with $V_h = \sqrt{T/2\rho S}$ which is no longer valid for negative thrust. This representation is not an absolute criterion for identifying Vortex Ring State or Propeller State, it rather consists in an indicator which has to be confirmed by wake visualizations.

Eventually, it is also more visible on this *surge* case that the blade wake emitted for a backward motion of the wind turbine is greatly distorted on at least one-third of the blade (Fig. 20c) and d), more visible on the 16m *surge* motion). This wake distortion is linked to the negative thrust which is obtained on this blade portion when the wind turbine is moving faster backward.

Fig. 20 *Surge* motion: velocity in the symmetry plane at different timesteps for $A_{SURGE} = 8m$ and $A_{SURGE} = 16m$

Fig. 21 Surge motion: VRS identification scheme

Conclusions

The aerodynamic behavior of a wind turbine is already complex to investigate, due to several unsteady phenomena that can occur (unsteady inflow, yaw conditions, dynamic stall,...). This is all the more true when investigating the flowfield around a floating offshore wind turbine which is subject to the ocean waves. It has been demonstrated in the literature that, among the 6 degrees of freedom involved by the waves, two of them could have a significant impact on the wind turbine aerodynamics: *pitch* and *surge* motions.

The current paper therefore investigated the effect of these two prescribed simplified motions on aerodynamic performance and on the wind turbine wake thanks to CFD simulations. For each motion type, several amplitudes have been tested.

It turns out that both *pitch* and *surge* motions have a similar effect on the wind turbine global loads: the mean thrust is only slightly impacted (from 1% to 7% decrease) whereas the mean aerodynamic power is greatly increased (from 10% to 57%). The power gain is obtained during the forward motion of the wind turbine (*pitch* or *surge*) and reaches its maximum when the wind turbine is back to its central position during this forward phase (maximum angular/displacement velocity). The instantaneous loads variations on the blade are consequent as well, and can differ from one blade to the others in the case of *pitch* motion.

These loads variations are due to significant variations of the blade sections angle of attack. The local velocity magnitude is only slightly modified, since it is dominated by the rotational velocity on such configurations.

The loads variations from both motions shown here may be overestimated due to the modeling itself: blade pitch controller was not considered in this investigation and the rotation speed was prescribed in all simulations. The constant prescribed rotation is clearly a limitation on the presented computations. However, even if individual blade pitch control are currently studied for FOWT, controllers and actuators are not yet operational to compensate for wind speed variation due to the floating device interaction with the wave. On the contrary, atmospheric turbulent boundary layer which was not taken into account in this study would tend to increase the load variations.

Furthermore, it has been demonstrated that vortex ring state (VRS) (as observed for helicopters in descending flight) could be encountered by the FOWT for the highest considered amplitudes. This obviously occurs when the wind turbine is quickly moving backward. Even for the cases where VRS is not reached, strong interactions have been noticed between the blades and the wake, leading to vortex pairing, wake meandering and instabilities.

If PUMA results (free wake method) have been punctually used to complement the present analysis, the occurrence of all these complex unsteady aerodynamic phenomena underline all the benefits of using CFD to accurately predict the aerodynamic performances and behavior of FOWT.

Acknowledgments

Most of this work was granted access to the HPC resources of CINES under the allocation 2018 – A0032A10280 made by GENCI.

Bonus

References

- [1] Jonkman, J & Musial, W., “Final Technical Report, IEA Wind task 23, Subtask 2, Offshore Code Comparison Collaboration (OC3)”, 2010

- [2] Robertson, A. et al. "Offshore Code Comparison Collaboration, Continuation within IEA Wind Task 30: Phase II Results Regarding a Floating Semisubmersible Wind System", Presented at the Ocean, Offshore and Arctic Engineering Conference, June 2014. NREL Report No. CP-5000-61154.
- [3] Amy N. Robertson et al. "OC5 Project Phase II: Validation of Global Loads of the DeepCwind Floating semisubmersible Wind Turbine", *Energy Procedia*, Volume 137, 2017, Pages 38-57, ISSN 1876-6102,
- [4] Sebastian, T., Lackner, M. A., "Characterization of the unsteady aerodynamics of offshore floating wind turbines", *Wind Energy*, Vol. 16, Issue 3, 2013, pp. 339-352
- [5] Tran, T. T., Kim, D. H., Song, J., "Computational fluid dynamic analysis of a floating offshore wind turbine experiencing platform pitching motion", *Energies*, Vol. 7, 2014, pp. 5011-5026
- [6] Tran, T. T., Kim, D. H., "A CFD study into the influence of unsteady aerodynamic interference on wind turbine surge motion", *Renewable Energy*, Vol. 90, 2016, pp. 204-228
- [7] Tran, T. T., Kim, D. H., "The aerodynamic interference effects of a floating offshore wind turbine experiencing platform pitching and yawing motions", *Journal of Mechanical Science and Technology*, Vol. 29 (2), 2015, pp. 549-561
- [8] Leble, V., Barakos, G., "Rigid Actuation of the Wind Turbine", *72nd Annual Forum of the American Helicopter Society*, Palm Beach, FL, USA, 17-19 May 2016, ISBN 9781510825062
- [9] Bekiropoulos, D., et al., "Simulation of unsteady aerodynamic effects on floating offshore wind turbines", *11th German Wind Energy Conference*, 2012
- [10] Cheng, P., Wan, D., Hu, C., "Unsteady Aerodynamic Simulations of Floating Offshore Wind Turbines with Overset Grid Technology", *26th International Ocean and Polar Engineering Conference*, 2016
- [11] Li, P., et al., "Numerical simulations of wake flows of floating offshore wind turbines by unsteady actuator line model", *Proceedings of the 9th International Workshop on Ship and Marine Hydrodynamics*, 2015
- [12] Vincent Leroy. "Unsteady aerodynamic modelling for seakeeping analysis of Floating Offshore Wind Turbines", *Fluids mechanics [physics.class-ph]*. École centrale de Nantes, 2018. English. NNT : 2018ECDN0050
- [13] Courbois, A., "Etude expérimentale du comportement dynamique d'une éolienne offshore flottante soumise à l'action conjuguée de la houle et du vent", PhD Dissertation, Ecole Centrale de Nantes, 2013
- [14] Bayati, Ilmas & Facchinetti, Alan & Fontanella, A. & Giberti, H. & Belloli, Marco. (2018). "A wind tunnel/HIL setup for integrated tests of Floating Offshore Wind Turbines", *J. Phys. Conf. Ser.*, 1037. 052025. 10.1088/1742-6596/1037/5/052025.

- [15] I. Bayati, M. Belloli, L. Bernini, and A. Zasso, "Wind tunnel validation of AeroDyn within LIFES50+ project: Imposed Surge and Pitch tests", *J. Phys. Conf. Ser.*, vol. 753, no. 9, 2016.
- [16] I. Bayati et al, "UNAFLOW project: UNsteady Aerodynamics of FLOating Wind turbines", 2018 *J. Phys.: Conf. Ser.* 1037 072037
- [17] Lienard, C., Boisard, R., "Investigation of the MEXICO rotor aerodynamics in axial flow, including boundary layer transition effects", *2018 Wind Energy Symposium, AIAA SciTech Forum*, Kissimmee, FL, USA, 8-12 January 2018
- [18] Jonkman, J., Butterfield, S., Musial, W., Scott, G., "Definition of a 5MW Reference Wind Turbine for Offshore System Development", Technical Report NREL/TP-500-38060, National Renewable Energy Laboratory, Golde, CO, USA, 2009
- [19] Sebastian, T., "The aerodynamic and near wake of an offshore floating horizontal axis wind turbine", PhD Dissertation, University of Massachusetts, Amherst, MA, USA, 2012
- [20] Mudry, M., "La théorie des nappes tourbillonnaires et ses applications à l'aérodynamique instationnaire", PhD Dissertation, Paris VI University, 1982
- [21] R. Boisard, "Aerodynamic investigation of a helicopter rotor hovering in the vicinity of a building", 74th AHS forum, Phoenix, Arizona, USA, 14-17 May 2018
- [22] Cambier L., Veuillot J.-P., "Status of the elsA CFD software for Flow Simulation and Multidisciplinary Applications", *46th AIAA Aerospace Science Meeting and Exhibit*, AIAA Paper 2008-664, Reno, Nevada, USA, January 2008
- [23] Cambier, L., Heib, S., Plot, S., "The ONERA elsA CFD software: input from research and feedback from industry", *Mechanics and Industry*, 14 (3), 2013, pp. 159-174
- [24] Benoit, C., Peron, S., Landier, S., "Cassiopee : a CFD pre- and post-processing tool", *Aerospace Science and Technology*, vol. 45, pp. 243-272, 2015
- [25] Kirby, A., Brazell, M., Yang, Z., Rajib, R., Ahrabi, B., Mavriplis, D., Sitaraman, J., Stoellinger, M., "Wind farm simulations using an overset hp-adaptive approach with blade-resolved turbine models", *23rd Aerospace Sciences Meeting and Exhibit, Aerospace Sciences Meeting*, AIAA Paper 2017-3958, Denver, CO, Jun. 5–7, 2017
- [26] Leishman, J.G., "Principles of Helicopter Aerodynamics", Cambridge University Press, Second Edition, July 2006.