Electrochemical Technologies for the Treatment of Pesticides

Clément Trellu¹, Hugo Olvera Vargas², Emmanuel Mousset³, Nihal Oturan¹,
Mehmet A. Oturan^{1,*}

¹ Université Gustave Eiffel, Laboratoire Géomatériaux et Environnement EA 4508,
77454 Marne-la-Vallée, Cedex 2, France

² Instituto de Energías Renovables, Universidad Nacional Autónoma de México (IER-
UNAM), Priv. Xochicalco S/N, Col. Centro, 62580, Temixco, Morelos, México

³ Laboratoire Réactions et Génie des Procédés, Université de Lorraine, CNRS, LRGP,
F-54000 Nancy, France

* Corresponding author's Email: Mehmet.oturan@univ-eiffel.fr (Mehmet A. Oturan)

SI "Electrochemical Technologies for Wastewater Treatment" in Current Opinion in Electrochemistry

Abstract

Pesticides are worldwide used in large amount to increase yield in agriculture. On the other hand, they are in general toxic/persistent organic pollutants presenting strong adverse effects to the environment and human health, including acute and chronic toxicity. Consequently, water polluted by pesticides should be treated efficiently before its release into receiving water bodies to protect natural aquatic environment. Different methods have been used for treatment of water contaminated by pesticides. Among them, electrochemical technology seems to be very efficient to remove pesticides from water. Therefore this review aims to provide an overview of the recent works on the treatment of pesticide wastewater using electrochemical technology with a special focus on

electrochemical advanced oxidation processes which demonstrated high efficiency in removal of various type of pesticides from contaminated water.

Keywords:

Electro-Fenton; Pesticide; Electro-oxidation; Organic pollutants; Hydroxyl radicals, Wastewater treatment

1. Introduction

The term pesticides cover a large variety of molecules used for improving agricultural productivity. With more than 4 million tons applied worldwide annually, they are among the most widespread xenobiotics released by anthropogenic activities [1]. It has been demonstrated that several pesticides present strong adverse effects on ecosystems (alteration of the biodiversity) and human health, including acute toxicity (accidental deaths by poisoning, particularly in developing countries) and chronic toxicity (even when exposed at low concentrations), as reported, in the case of India for example [2]. After being used on agricultural crops, pesticides reach soil, air and water bodies where their accumulation depends on their persistence and can reach significant concentrations in the different environmental compartments [1]. Regulatory authorities are trying to take into consideration this environmental issue by introducing standards for pesticide content in drinking water (e.g., in the European Union, 100 ng L⁻¹ for individual pesticides and 500 ng L⁻¹ for the sum of all pesticides detected [3]). Therefore, the removal of pesticides is currently an important challenge for environmental engineers working on soil remediation and water treatment, including drinking water, municipal wastewater and some industrial wastewaters. The development of electrochemical processes might help to address this issue [4**]. While electrocoagulation process is able to separate some of pesticides, electrochemical advanced oxidation processes (EAOPs) are widely recognized for their capacity to remove efficiently and in a non-selective way a very large range of pesticides from water [5]. EAOPs can also be applied for the pesticides removal from groundwater and from soil after a soil washing step [6**]. The objective of this review is to provide a concise overview of the recent reports, including the advantages and drawbacks of electrochemical processes for treating pesticides and to provide new insights on the future of these technologies in this area.

62

63 **2. Which electrochemical technologies are used for treating pesticides?**

64 Different electrochemical technologies were applied to the treatment of pesticides in
65 water and soils. The two EAOPs (electro-Fenton (EF) and electrooxidation (or anodic
66 oxidation (AO)) are the most widely used processes for treatment of pesticides.
67 Electrooxidation is based on generation of hydroxyl radicals ($\cdot\text{OH}$) from electrooxidation
68 of water at the anode surface when using a non-active anode like BDD or PbO_2 . These
69 radicals are physisorbed on anode surface and constitute strongest oxidant species at the
70 vicinity of the electrode [7]. Therefore, oxidation of pollutants requires their transfer to
71 the surface of anode where they are oxidized/mineralized by $\cdot\text{OH}$. Several recent works
72 have demonstrated high efficiency of this process, alone [8–10] or in combination with
73 other technologies [11,12] for the treatment of synthetic or real pesticides wastewater. In
74 contrast, in EF, $\cdot\text{OH}$ are homogeneously generated in the bulk solution from the reaction
75 between electrochemically formed H_2O_2 and a catalyst (generally Fe^{2+} ion) to remove
76 pesticides from water [13,14]. To enhance process efficiency, EF has been coupled to
77 other methods such as photocatalysis [15] and solar photocatalysis [16].
78 Electrocoagulation [17,18] and electrokinetics [19] were also applied to water treatment
79 and soil remediation, respectively.

80

81 **3. Applications for the treatment of pesticides in water**

82 Several kinds of electrochemical processes have been successfully applied to treat a
83 number of pesticides in water including EF and its photo-assisted versions (photoelectro-
84 Fenton (PEF) and solar photoelectro-Fenton (SPEF)), direct or Cl^- mediated anodic
85 oxidation (AO), electrocoagulation (EC) and photoelectrocatalysis (PEC) (Table 1). In
86 general, fast degradation kinetics have been observed, with complete removal of target
87 pesticides ranging from few minutes to few hours depending on the process and
88 experimental conditions used. Besides, high mineralization yields (>50% of TOC
89 removal) are generally achieved within few hours of treatment. It is worthy to note that
90 EF and its photo-assisted variants (PEF and SPEF), along with AO using BDD anodes
91 have shown the fastest degradation kinetics and the highest mineralization yields (almost
92 total TOC removal in few hours) [9*,20–23*], which is attributed to the efficient

formation of strong oxidants: homogeneous $\cdot\text{OH}$ (EF) and heterogeneous BDD($\cdot\text{OH}$) (AO and EF with BDD anode) during the process.

The use of accessible carbonaceous cathode materials (i.e., carbon felt, carbon cloth, carbon fibers, etc.) constitutes a technical advantage of EF and makes the process economically attractive. In contrast, BDD is still a costly material restraining the application of AO at large-scale [24,25*].

Different pesticides have been used as model pollutants to evaluate the performance of new electrode materials. For example, an N-doped graphene cathode for H_2O_2 production and its activation was successfully tested for the degradation of 2,4-dichlorophenoxyacetic acid [26], while a dual anode consisting of one layer of SnO_2 - $\text{Sb}_2\text{O}_3/\text{PbO}_2$, and one of TiO_2 deposited on the opposite sides of a Ti plate was used to treat the herbicide fenuron by photocatalytically assisted AO [27]. The development of high-surface-area and durable electrode materials is an active research field with great improvement opportunities.

On the other hand, most of the investigations have been conducted using aqueous solutions of the target compounds (some of them using commercial formulations) to obtain important information about the kinetics, mechanisms, and optimal experimental conditions for the degradation/mineralization of such pollutants. However, the effect of the matrix in real wastewaters is not considered in such works. Hence, more investigations using real water sources contaminated by pesticides are highly recommended in order to evaluate the influence of the matrix (additives, other organics as well as inorganic compounds) on the process performance [25*]. In this sense, the presence of radical scavengers may significantly affect the degradation/mineralization efficiency. Additionally, the concentrations of target pollutants in synthetic solutions are generally orders of magnitude higher than the concentrations in real water sources [28], which may affect the efficiencies under real scenarios, especially considering the mass transport limitations to the electrode surface inherent to electrochemical processes.

Another important point to keep in mind is that most studies on electrochemical treatment of pesticides have been carried out in small laboratory-scale devices with capacities rarely exceeding 1 L. With this respect, the design of electrochemical reactors with the capacity to treat greater volumes is fundamental for the application of such treatment methods at industrial scale. Larger-scale systems would give a more reliable assessment of both

investment and operating costs of electrochemical processes (operating costs tightly related to electrical energy consumption).

4. Applications for the treatment of pesticides in soil

Diffuse pollution of soils is a very complex environmental issue because of the huge amount of soils that might be concerned for remediation and the great complexity of treating contaminated soils. Electrochemical technologies cannot be considered as sustainable solutions in such case. However, manufacturing and handling of pesticides can lead to accidental release and create a localized acute contamination, for which the application of electrochemical technologies might be suitable.

First, electrokinetic processes based on the application of an electric field in the soil present the great interest to avoid the use of any chemical compounds and to be applied *in situ*. It has been reported at lab-scale that it is possible to recover pollutants in catholyte and anolyte wells by dragging with the electroosmotic flux or by electromigration of ionic compounds [19]. However, it has been highlighted that the influence of these mechanisms is very low when applying this process at pilot scale [19]. As high current intensities have to be applied, the controlling mechanism becomes the electric heating of the soil, which influences pollutant volatilization from soil. Current studies focus mainly on the combination with other processes (e.g., phytoremediation or the use of additives such as oxidants) [33*,34] or by implementing efficiently this technology at pilot-scale (optimization of powering control, inversion of electrode polarity, etc.) [33*,34].

Secondly, a treatment strategy involving an electrochemical process as post-treatment step can be applied for treating soil washing solutions [6**]. Soil washing (as first step) aims at transferring pesticides from the soil-sorbed fraction to the aqueous phase. Extracting agents (cyclodextrins or surfactants such as Tween 80, Triton X 100 or sodium dodecyl sulfate) can be used for improving the transfer of hydrophobic pesticides. The soil washing solution is therefore a complex mixture of all compounds that can be mobilized, including target pesticides, soil organic matter, inorganic species, fine particles and extracting agents [6**]. Several studies have reported that EAOPs are able to remove the organic load of these effluents [36,37*]. Recent studies are reported in Table 2. The possibility of combination with a biological treatment has also been assessed

for improving the cost-effectiveness [38,39] and few studies focused on selective electro-oxidation of target pollutants in order to be able to reuse extracting agents [39**,40*]. However, further studies are required in order to scale up such treatment for field scale applications and for assessing the sustainability of this approach.

5. Challenges for full-scale applications

There are several challenges for upscaling the electrochemical technologies regarding the removal of pesticides, especially about the reactor design.

When the option consists to treat pesticides from urban wastewater or natural water, their concentrations in solution is very low (from ng L^{-1} to $\mu\text{g L}^{-1}$) [4*]. It means that it is required to strongly favor the contact between the pollutant and the electrodes in AO and/or to enhance the promotion of the homogeneous oxidation with EF process [45]. This will enhance the faradaic yield, while keeping high pesticides removal yields. Moreover, these effluents have generally a low electric conductivity [4*], which means that the reactor design need to be also adapted in order to avoid adding a supporting electrolyte. Microfluidic thin film electrochemical reactors have emerged as a possible response towards these issues by intensifying the transport of species and reducing the ohmic resistance [46–48]). Further studies are needed at large scale in order to validate the lab-scale systems.

When the pesticides are solubilized in soil washing/flushing effluent, their concentrations in solution can be increased to mg L^{-1} range [28]. Still, the faradaic yield remains low, because the extracting agent represents the main organic source. To make it economically viable at larger scale, the recovery of extracting agent has to be considered while the selective removal of the contaminants should be effective. Combined treatments in hybrid or sequenced reactor(s) required supplementary proofs at high technology readiness levels.

In electrokinetics systems, lab-scale experiments could not predict well the pilot and larger scale applications [33*]. The difficulties remain in the ability to have geometrical and operational similarity between the setups [33*], which makes changing the distribution of parameters (pH, conductivity, temperature, pollutants and ions concentrations) and the mechanisms involved [19,49]. Furthermore, the soil

characteristics (electric conductivity, granulometry, age of pollution,...) vary a lot from one sample to another, which makes difficult the extrapolation of the results for upscaling studies. Additional large scales studies need to be performed in a comparable way by implementing dimensional analysis.

6. Conclusions and future perspectives

Electrochemical processes stand out as promising technologies for the treatment of harmful organic pollutants (pesticides, synthetic dyes, pharmaceutical residues,...) in contaminated water and soils. Particularly, EAOPs present great advantages due to their capacity to remove, in a non-selective way, a large range of pesticides, which can be degraded and even fully mineralized in order to avoid the presence of toxic by-products remaining in the treated solution. Besides application to contaminated water, they can also be employed for the removal of pesticides in soil washing effluents. The next challenge for further development of electrochemical technology and particularly of EAOPs is clearly related to full-scale applications, including the design of suitable reactors and the application to real effluents. This step is required in order to conclude on the sustainability and cost-effectiveness of these processes.

References:

- [1] F. Maggi, F.H.M. Tang, D. la Cecilia, A. McBratney, PEST-CHEMGRIDS, global gridded maps of the top 20 crop-specific pesticide application rates from 2015 to 2025, *Sci. Data.* 6 (2019) 1–20. doi:10.1038/s41597-019-0169-4.
- [2] P.C. Abhilash, N. Singh, Pesticide use and application: An Indian scenario, *J. Hazard. Mater.* 165 (2009) 1–12. doi:10.1016/j.jhazmat.2008.10.061.
- [3] European Commission, Synthesis report on the quality of drinking water in the union examining member states' reports for the 2011-2013 period, foreseen under Article 13(5) of Directive 98/83/EC, Brussels, Belgium, 2016.
- [4] M.A. Rodrigo, N. Oturan, M.A. Oturan, Electrochemically assisted remediation of pesticides in soils and water: A review, *Chem. Rev.* 114 (2014) 8720–8745. doi:10.1021/cr500077e.
This is an extensive and critical review article on electrochemical technology applied to treatment of water and soils contaminated by pesticides.
- [5] C.A. Martínez-Huitle, M.A. Rodrigo, I. Sirés, O. Scialdone, Single and coupled electrochemical processes and reactors for the abatement of organic water pollutants: a critical review., *Chem. Rev.* 115 (2015) 13362–407. doi:10.1021/acs.chemrev.5b00361.
- [6] C. Trellu, E. Mousset, Y. Pechaud, D. Huguenot, E.D. van Hullebusch, G. Esposito, et al., Removal of hydrophobic organic pollutants from soil washing/flushing solutions: A critical review, *J. Hazard. Mater.* 306 (2016) 149–174. doi:10.1016/j.jhazmat.2015.12.008.
This review thoroughly summarises the feasibility and critical choices during treatment of soils contaminated hydrophobic organic pollutants with different methods combined with washing/flushing technics
- [7] P. V. Nidheesh, G. Divyapriya, N. Oturan, C. Trellu, M.A. Oturan, Environmental applications of boron - doped diamond electrodes: 1. applications in water and wastewater treatment, *ChemElectroChem.* 6 (2019) 2124–2142. doi:10.1002/celec.201801876.
- [8] G.O.S. Santos, K.I.B. Eguiluz, G.R. Salazar-Banda, C. Saez, M.A. Rodrigo, Biodegradability improvement of clopyralid wastes through electrolysis using different

diamond anodes, *Environ. Res.* 188 (2020) 109747. doi:10.1016/j.envres.2020.109747.

- [9] C.M. Dominguez, N. Oturan, A. Romero, A. Santos, M.A. Oturan, Lindane degradation by electrooxidation process: Effect of electrode materials on oxidation and mineralization kinetics, *Water Res.* 135 (2018) 220–230. doi:10.1016/J.WATRES.2018.02.037.

This work reports the treatment of a real wastewater from a lindane production site using electrochemical technology highlighting the role of electrode material on process efficiency

- [10] J. Cai, M. Zhou, X. Du, X. Xu, Enhanced mechanism of 2,4-dichlorophenoxyacetic acid degradation by electrochemical activation of persulfate on Blue-TiO₂ nanotubes anode, *Sep. Purif. Technol.* 254 (2021) 117560. doi:10.1016/j.seppur.2020.117560.
- [11] A. Raschitor, J. Llanos, M.A. Rodrigo, P. Cañizares, Combined electrochemical processes for the efficient degradation of non-polar organochlorine pesticides, *J. Environ. Manage.* 248 (2019) 109289. doi:10.1016/j.jenvman.2019.109289.
- [12] N.L. Pedersen, M. Nikbakht Fini, P.K. Molnar, J. Muff, Synergy of combined adsorption and electrochemical degradation of aqueous organics by granular activated carbon particulate electrodes, *Sep. Purif. Technol.* 208 (2019) 51–58. doi:10.1016/j.seppur.2018.05.023.
- [13] N. Oturan, M.A. Oturan, Electro-Fenton process: Background, new developments, and applications, in: *Electrochem. Water Wastewater Treat.*, Elsevier, 2018: pp. 193–221. doi:10.1016/B978-0-12-813160-2.00008-0.
- [14] M. Zhou, M.A. Oturan, I. Sirés, Electro-Fenton process : new trends and scale-up, in: *Handb. Environ. Chem.*, Springer Singapore, 2018: p. 430.
- [15] D.R.V. Guelfi, E. Brillas, F. Gozzi, A. Machulek, S.C. de Oliveira, I. Sirés, Influence of electrolysis conditions on the treatment of herbicide bentazon using artificial UVA radiation and sunlight. Identification of oxidation products, *J. Environ. Manage.* 231 (2019) 213–221. doi:10.1016/j.jenvman.2018.10.029.
- [16] F. Gozzi, I. Sirés, A. Thiam, S.C. de Oliveira, A.M. Junior, E. Brillas, Treatment of single and mixed pesticide formulations by solar photoelectro-Fenton using a flow plant, *Chem. Eng. J.* 310 (2017) 503–513. doi:10.1016/j.cej.2016.02.026.
- [17] S. Garcia-Segura, M.M.S.G. Eiband, J.V. de Melo, C.A. Martínez-Huitle, Electrocoagulation and advanced electrocoagulation processes: A general review about

- the fundamentals, emerging applications and its association with other technologies, *J. Electroanal. Chem.* 801 (2017) 267–299. doi:10.1016/J.JELECHEM.2017.07.047.
- [18] M. Muñoz, J. Llanos, A. Raschitor, P. Cañizares, M.A. Rodrigo, Electrocoagulation as the Key for an Efficient Concentration and Removal of Oxyfluorfen from Liquid Wastes, *Ind. Eng. Chem. Res.* 56 (2017) 3091–3097. doi:10.1021/acs.iecr.7b00347.
- [19] R. López-Vizcaíno, C. Risco, J. Isidro, S. Rodrigo, C. Saez, P. Cañizares, et al., Scale-up of the electrokinetic fence technology for the removal of pesticides. Part II: Does size matter for removal of herbicides?, *Chemosphere*. 166 (2017) 549–555. doi:10.1016/j.chemosphere.2016.09.114.
- [20] H. Zazou, N. Oturan, M. Sönmez Çelebi, M. Hamdani, M.A. Oturan, Cold incineration of 1,2-dichlorobenzene in aqueous solution by electrochemical advanced oxidation using DSA/Carbon felt, Pt/Carbon felt and BDD/Carbon felt cells, *Sep. Purif. Technol.* 208 (2019) 184–193. doi:10.1016/J.SEPPUR.2018.03.030.
- [21] A. Thiam, I. Sirés, R. Salazar, E. Brillas, On the performance of electrocatalytic anodes for photoelectro-Fenton treatment of synthetic solutions and real water spiked with the herbicide chloramben, *J. Environ. Manage.* 224 (2018) 340–349. doi:10.1016/j.jenvman.2018.07.065.
- [22] P.A. Diaw, N. Oturan, M.D. Gaye Seye, O.M.A. Mbaye, M. Mbaye, A. Coly, et al., Removal of the herbicide monolinuron from waters by the electro-Fenton treatment, *J. Electroanal. Chem.* 864 (2020) 114087. doi:10.1016/j.jelechem.2020.114087.
- [23] E. Brillas, A review on the photoelectro-Fenton process as efficient electrochemical advanced oxidation for wastewater remediation. Treatment with UV light, sunlight, and coupling with conventional and other photo-assisted advanced technologies, *Chemosphere* 250 (2020) 126198. doi: 10.1016/j.chemosphere.2020.126198
- This detailed and comprehensive review thoroughly summerises the different techniques combining the electro-Fenton process with different photochemical processes for water/wastewater treatment.
- [24] J. Radjenovic, D.L. Sedlak, Challenges and opportunities for electrochemical processes as next-generation technologies for the treatment of contaminated water, *Environ. Sci. Technol.* 49 (2015) 11292–11302. doi:10.1021/acs.est.5b02414.
- [25] H. Olvera-Vargas, N. Gore-Datar, O. Garcia-Rodriguez, S. Mutnuri, O. Lefebvre, Electro-Fenton treatment of real pharmaceutical wastewater paired with a BDD anode:

Reaction mechanisms and respective contribution of homogeneous and heterogenous OH, Chem. Eng. J. 404 (2021) 126524. doi:10.1016/j.cej.2020.126524.

This study underlines the simultaneous production of homogeneous (electro-Fenton) and heterogeneous (anodic oxidation) hydroxyl radicals when using BDD anode in electro-fenton process.

- [26] W. Yang, M. Zhou, N. Oturan, Y. Li, P. Su, M.A. Oturan, Enhanced activation of hydrogen peroxide using nitrogen doped graphene for effective removal of herbicide 2,4-D from water by iron-free electrochemical advanced oxidation, *Electrochim. Acta.* 297 (2019) 582–592. doi:10.1016/j.electacta.2018.11.196.
- [27] K. Barbari, R. Delimi, Z. Benredjem, S. Saaidia, A. Djemel, T. Chouchane, et al., Photocatalytically-assisted electrooxidation of herbicide fenuron using a new bifunctional electrode PbO₂/SnO₂-Sb₂O₃/Ti//Ti/TiO₂, *Chemosphere.* 203 (2018) 1–10. doi:10.1016/j.chemosphere.2018.03.126.
- [28] S. Garcia-Segura, A.B. Nienhauser, A.S. Fajardo, R. Bansal, C.L. Coonrod, J.D. Fortner, et al., Disparities between experimental and environmental conditions: Research steps toward making electrochemical water treatment a reality, *Curr. Opin. Electrochem.* 22 (2020) 9–16. doi:10.1016/j.coelec.2020.03.001.
- [29] R. Oriol, M. del P. Bernícola, E. Brillas, P.L. Cabot, I. Sirés, Paired electro-oxidation of insecticide imidacloprid and electrodenitrification in simulated and real water matrices, *Electrochim. Acta.* 317 (2019) 753–765. doi:10.1016/j.electacta.2019.05.002.
- [30] X. Xu, J. Cai, M. Zhou, X. Du, Y. Zhang, Photoelectrochemical degradation of 2,4-dichlorophenoxyacetic acid using electrochemically self-doped Blue TiO₂ nanotube arrays with formic acid as electrolyte, *J. Hazard. Mater.* 382 (2020) 121096. doi:10.1016/j.jhazmat.2019.121096.
- [31] J.E.L. Santos, M.A. Gómez, D.C.-D. Moura, M. Cerro-López, M.A. Quiroz, C.A. Martínez-Huitle, Removal of herbicide 1-chloro-2,4-dinitrobenzene (DNCB) from aqueous solutions by electrochemical oxidation using boron-doped diamond (BDD) and PbO₂ electrodes, *J. Hazard. Mater.* (2020) 123850. doi:10.1016/j.jhazmat.2020.123850.
- [32] N.S. Lima, É.M. Souza, N.H. Torres, R. Bergamasco, M.N. Marques, S. Garcia-Segura, et al., Relevance of adjuvants and additives of pesticide commercial

formulation on the removal performance of glyphosate by electrochemically driven processes, *J. Clean. Prod.* 212 (2019) 837–846. doi:10.1016/j.jclepro.2018.12.007.

- [33] V. Sánchez, F.J. López-Bellido, P. Cañizares, J. Villaseñor, L. Rodríguez, Scaling up the electrokinetic-assisted phytoremediation of atrazine-polluted soils using reversal of electrode polarity: A mesocosm study, *J. Environ. Manage.* 255 (2020) 109806. doi:10.1016/j.jenvman.2019.109806.

This reference brings interesting key issues regarding the scaling up studies in electrokinetic process, especially when combined with phytoremediation

- [34] L. Ren, H. Lu, L. He, Y. Zhang, Enhanced electrokinetic technologies with oxidation-reduction for organically-contaminated soil remediation, *Chem. Eng. J.* 247 (2014) 111–124. doi:10.1016/j.cej.2014.02.107.
- [35] M. Millán, P.Y. Bucio-Rodríguez, J. Lobato, C.M. Fernández-Marchante, G. Roa-Morales, C. Barrera-Díaz, et al., Strategies for powering electrokinetic soil remediation: A way to optimize performance of the environmental technology, *J. Environ. Manage.* 267 (2020) 110665. doi:10.1016/j.jenvman.2020.110665.
- [36] E.V. dos Santos, C. Sáez, C.A. Martínez-Huitle, P. Cañizares, M.A. Rodrigo, Combined soil washing and CDEO for the removal of atrazine from soils, *J. Hazard. Mater.* 300 (2015) 129–134. doi:10.1016/j.jhazmat.2015.06.064.
- [37] E.V. Dos Santos, C. Sáez, C.A. Martínez-Huitle, P. Cañizares, M.A. Rodrigo, The role of particle size on the conductive diamond electrochemical oxidation of soil-washing effluent polluted with atrazine, *Electrochem. Commun.* 55 (2015) 26–29. doi:10.1016/j.elecom.2015.03.003.

This work describes the role of particle size during treatment of soil washing solutions during electrooxidation with BDD anode.

- [38] E. Mousset, N. Oturan, E.D. van Hullebusch, G. Guibaud, G. Esposito, M.A. Oturan, Treatment of synthetic soil washing solutions containing phenanthrene and cyclodextrin by electro-oxidation. Influence of anode materials on toxicity removal and biodegradability enhancement, *Appl. Catal. B Environ.* 160–161 (2014) 666–675. doi:http://dx.doi.org/10.1016/j.apcatb.2014.06.018.
- [39] C. Trellu, O. Ganzenko, S. Papirio, Y. Pechaud, N. Oturan, D. Huguenot, et al., Combination of anodic oxidation and biological treatment for the removal of phenanthrene and Tween 80 from soil washing solution, *Chem. Eng. J.* 306 (2016)

588–596. doi:10.1016/j.cej.2016.07.108.

- [40] C. Trellu, N. Oturan, Y. Pechaud, E.D. van Hullebusch, G. Esposito, M.A. Oturan, Anodic oxidation of surfactants and organic compounds entrapped in micelles – Selective degradation mechanisms and soil washing solution reuse, *Water Res.* 118 (2017) 1–11. doi:10.1016/J.WATRES.2017.04.013.

This study underlines selective oxidation mechanisms during anodic oxidation in order to recover and reuse of surfactants used during washing/flashing processes.

- [41] C. Trellu, Y. Pechaud, N. Oturan, E. Mousset, E.D. van Hullebusch, D. Huguenot, et al., Remediation of soils contaminated by hydrophobic organic compounds: How to recover extracting agents from soil washing solutions?, *J. Hazard. Mater.* (2020) 124137. doi:10.1016/j.jhazmat.2020.124137.

This critical review thoroughly summarises different techniques used in remediation of soils and possibilities for recovering extracting agents used during washing step for cost effectiveness of treating soil washing solutions.

- [42] E. Vieira Dos Santos, C. Sáez, P. Cañizares, C.A. Martínez-Huitle, M.A. Rodrigo, Treating soil-washing fluids polluted with oxyfluorfen by sono-electrolysis with diamond anodes, *Ultrason. Sonochem.* 34 (2017) 115–122. doi:10.1016/j.ultsonch.2016.05.029.

- [43] M. Muñoz-Morales, M. Braojos, C. Sáez, P. Cañizares, M.A. Rodrigo, Remediation of soils polluted with lindane using surfactant-aided soil washing and electrochemical oxidation, *J. Hazard. Mater.* 339 (2017) 232–238. doi:10.1016/j.jhazmat.2017.06.021.

- [44] M.B. Carboneras Contreras, F. Fourcade, A. Assadi, A. Amrane, F.J. Fernandez-Morales, Electro Fenton removal of clopyralid in soil washing effluents, *Chemosphere.* 237 (2019) 124447. doi:10.1016/j.chemosphere.2019.124447.

- [45] E. Mousset, Y. Pechaud, N. Oturan, M.A. Oturan, Charge transfer/mass transport competition in advanced hybrid electrocatalytic wastewater treatment: Development of a new current efficiency relation, *Appl. Catal. B Environ.* 240 (2019) 102–111. doi:10.1016/J.APCATB.2018.08.055.

- [46] P. Ma, H. Ma, S. Sabatino, A. Galia, O. Scialdone, Electrochemical treatment of real wastewater. Part 1: Effluents with low conductivity, *Chem. Eng. J.* 336 (2018) 133–140. doi:10.1016/j.cej.2017.11.046.

- [47] J.F. Pérez, J. Llanos, C. Sáez, C. López, P. Cañizares, M.A. Rodrigo, Development of an innovative approach for low-impact wastewater treatment: A microfluidic flow-through electrochemical reactor, *Chem. Eng. J.* 351 (2018) 766–772.
doi:10.1016/j.cej.2018.06.150.
- [48] E. Mousset, Unprecedented reactive electro-mixing reactor: Towards synergy between micro- and macro-reactors?, *Electrochem. Commun.* 118 (2020) 106787.
doi:10.1016/j.elecom.2020.106787.
- [49] R. López-Vizcaíno, C. Risco, J. Isidro, S. Rodrigo, C. Saez, P. Cañizares, et al., Scale-up of the electrokinetic fence technology for the removal of pesticides. Part I: Some notes about the transport of inorganic species, *Chemosphere.* 166 (2017) 540–548.
doi:10.1016/j.chemosphere.2016.09.113.

Table 1. Compilation of recent works on the electrochemical treatment of pesticides in water.

Pesticide	Process	Cell configuration	Operating conditions	Removal efficiency	Energy consumption	Ref.
1,2-dichlorobenzene (0.1 mM = 14.7 mg L ⁻¹)	EF	Undivided cylindrical cell (230 mL), Nb/BDD anode (4 cm x 6 cm), carbon felt cathode (16 cm x 4 cm x 0.5 cm), with constant air supply	$I = 500$ mA, pH = 3, in Na ₂ SO ₄ 0.05 M, Fe ²⁺ = 0.1 mM	Complete degradation in 10 min. $k^a = 294.6$ min ⁻¹ $k_{abs}^b = 1.61 \times 10^9$ M ⁻¹ s ⁻¹ >90% TOC removal (3 h)	2.5 kWh (g-TOC) ⁻¹	[20]
Chloramben (herbicide) (1.19 mM = 245.1 mg L ⁻¹) spiked in urban wastewater (TOC ₀ = 15 mg L ⁻¹)	PEF ^c	Undivided cell (100 mL) Carbon-PTFE GDE ^d cathode (3 cm ²), BDD anode UVA lamp ($\lambda = 365$ nm)	$j = 33.3$ mA cm ⁻² , pH = 3.4, in Na ₂ SO ₄ 0.05 M, Fe ²⁺ = 0.05 mM, TOC ₀ = 115 mg L ⁻¹ , T = 35 °C	96% degradation in 40 min $k^a = 0.13$ min ⁻¹ 82% TOC removal (3 h)	N/A	[21]
Tebuthiuron (0.18 mM = 41.1 mg L ⁻¹) and ametryn (0.09 mM = 20.5 mg L ⁻¹) from commercial formulations	SPEF ^e	Flow plant with a filter-press cell and a planar solar photoreactor, BDD anode (20 cm ²) and carbon-PTFE GDE cathode (20 cm ²), V = 2.5 L	$j = 50$ mA cm ⁻² , pH = 3, in 0.05 Na ₂ SO ₄ , Fe ²⁺ = 0.5 mM, TOC ₀ = 30 mg L ⁻¹ , liquid flow rate = 200 L h ⁻¹	Time for complete degradation: 240 min for tebuthiuron and 120 min for ametryn. $k_{tebuthiuron}^a = 0.098$ min ⁻¹ , $k_{ametryn}^a = 0.26$ min ⁻¹ 53% TOC removal (6 h)	2.1 kWh (g-TOC) ⁻¹	[16]
Imidacloprid (insecticide) (23.7 mg L ⁻¹) in softened natural groundwater	AO-BDD	Undivided cylindrical cell (150 mL), Si/BDD anode, Fe cathode (both 10 cm ²)	$j = 5$ mA cm ⁻² , pH = 6.8, TOC ₀ = 10 mg L ⁻¹ , T = 25 °C, NO ₃ ⁻ = 129.4 mg L ⁻¹	Complete degradation at 210 min. $k^a = 0.014$ min ⁻¹ 61.5% TOC removal (4 h)	N/A	[29]

Lindane (10 mg L ⁻¹)	AO-BDD	Undivided cylindrical cell (230 mL), Nb/BDD anode (24 cm ²), carbon felt cathode (18 cm x 5 cm x 0.5 cm)	$j = 8.33 \text{ mA cm}^{-2}$, pH = 6.5, in Na ₂ SO ₄ 0.05 M, TOC ₀ = 2.45 mg L ⁻¹	Total removal (10 min) $k^a = 0.25 \text{ min}^{-1}$ 80% TOC removal (4 h)	15 kWh (g-TOC) ⁻¹	[9*]
2,4-dichlorophenoxyacetic acid (20 mg L ⁻¹) (herbicide)	PS ^f activation by AO-Blue TiO ₂	Undivided cell (100 mL), Blue TiO ₂ anode, SS cathode	$j = 2.5 \text{ mA cm}^{-2}$, pH = 3.5, PS = 30 mM	Complete degradation in 60 min $k^a = 0.07 \text{ min}^{-1}$ 83% TOC removal (2 h)	0.14 kWh m ⁻³	[10]
Oxyfluorfen (100 mg L ⁻¹) from commercial formulations (Fluoxil 24 EC)	EC ^g	Single-compartment flow cell (5 L-capacity), Fe anode, SS ⁱ cathode (both 100 cm ²)	$j = 5 \text{ mA cm}^{-2}$, pH = 7, in Na ₂ SO ₄ 0.02 M, TOC ₀ = 72 mg L ⁻¹ , $q = 0.6 \text{ L h}^{-1}$, $Q = 0.836 \text{ A h dm}^{-3}$	99% depletion in 100 min 45% TOC removal (1.7 h)	N/A	[18]
2,4-dichlorophenoxyacetic acid (10 mg L ⁻¹)	Solar PEC	3-electrode undivided cell (quartz), Ti/Blue TiO ₂ photoanode (2.5 x 2.5 cm), SS cathode	E = 2.4 V vs SCE, pH = 5, in Na ₂ SO ₄ 0.05 M, sunlight (200 W Xenon lamp, 80 mW cm ⁻²)	Total depletion in 120 min. $k^a = 0.03 \text{ min}^{-1}$	N/A	[30]
2,4-dichlorophenoxyacetic acid (20 mg L ⁻¹)	H ₂ O ₂ -based electrochemical oxidation	3-electrode undivided cell (150 mL), Ti/RuO ₂ -IrO ₂ anode, N-doped graphene cathode (both 3 cm x 4 cm).	E = 4 V vs SCE, pH = 7, in 0.05 M Na ₂ SO ₄	Total depletion in 60 min. $k^a = 0.04 \text{ min}^{-1}$ 88% TOC removal (8 h)		[26]
Monolinuron (herbicide) (0.1 mM = 21.5 mg L ⁻¹)	EF	Undivided cylindrical cell (230 mL), BDD anode (24 cm ²), carbon felt cathode, continuous air supply	$I = 500 \text{ mA}$, pH = 3, in Na ₂ SO ₄ 0.05 M	Complete degradation in 10 min. $k^b_{abs} = 3.1 \times 10^9 \text{ M}^{-1} \text{ s}^{-1}$ 98% TOC removal (8 h)	10 kWh (g-TOC) ⁻¹	[22]

Fenuron (0.1 mM = 16.42 mg L ⁻¹)	Photocatalytically-assisted electrochemical oxidation	Undivided cell (250 mL), dual anode: Ti/SnO ₂ -Sb ₂ O ₃ /PbO ₂ (electrocatalytic side), Ti/TiO ₂ (photocatalytic side), SS cathode	$j = 30 \text{ mA cm}^{-2}$, natural pH, in Na ₂ SO ₄ 0.05 M, $\lambda = 254 \text{ nm}$.	97.5% degradation in 60 min 97.4% COD removal (4 h)	N/A	[27]
1-chloro-2,4-dinitrobenzene (0.25 mM = 50.6 mg L ⁻¹)	AO-BDD	3-electrode undivided cell (150 mL), Si/BDD anode, graphite rod cathode, Hg/Hg ₂ SO ₄ reference electrode	$j = 30 \text{ mA cm}^{-2}$, pH = 3, in Na ₂ SO ₄ 0.05 M, T = 30 °C	90% removal (230 min) $k^a = 0.01 \text{ min}^{-1}$ 62% TOC removal (3.8 h)	N/A	[31]
Glyphosate from commercial formulations (TOC = 100 mg L ⁻¹)	Cl ⁻ mediated AO	Undivided cell (100 mL), Ti/Ru _{0.36} Ti _{0.64} O ₂ anode (14.76 cm ²), SS cathode (22.62 cm ²)	$j = 40 \text{ mA cm}^{-2}$, pH = 3, NaCl = 0.15 M	60% TOC removal (3 h) (Complete degradation in 120 min for solutions prepared with the pure chemical, with $k^a = 0.02 \text{ min}^{-1}$ and >90% TOC removal)	1 kWh -g-TOC) ⁻¹ (for solutions with the pure chemical)	[32]

^a apparent rate constant of oxidation reaction, ^b absolute (second order) rate constant of oxidation of 1,2-dichlorobenzene by $\cdot\text{OH}$, ^c photoelectro-Fenton, ^d gas diffusion electrode,

^e solar photoelectro-Fenton, ^f persulfate, ^g electrocoagulation, ⁱ stainless steel

Table 2. Examples of application of electrochemical technology to treatment of pesticides in soils and groundwater.

1- Target pollutant 2- Washing solution	Process	Cell configuration Operating conditions	Removal efficiency	Ref.
1- Atrazine (spiked clay) 2- Sodium dodecyl sulphate (100 – 5000 mg L ⁻¹) and NaHCO ₃ (500 mg L ⁻¹)	AO	Continuous circulation (200 L h ⁻¹) of the effluent (1 L) in a flow-by cell using BDD anode and steel (diameter = 10 cm). $I = 30 \text{ mA cm}^{-2}$	Complete degradation of atrazine and sodium dodecyl sulphate and >90% TOC removal at 30 Ah L ⁻¹ .	[36]
1- Oxyfluorfen (spiked clay) 2- Sodium dodecyl sulphate (100 – 5000 mg L ⁻¹) and NaHCO ₃ (500 mg L ⁻¹)	AO and sono-AO	Continuous circulation (200 L h ⁻¹) of the effluent (1 L) in a flow-by cell using BDD anode and steel cathode (diameter = 10 cm). $I = 30 \text{ mA cm}^{-2}$ Auxiliary tank for irradiated experiments (24 kHz, 250 W L ⁻¹)	Complete degradation of oxyfluorfen at 25 Ah L ⁻¹ for AO and 40 Ah L ⁻¹ for sono-AO. >90% TOC removal at 30 Ah L ⁻¹ .	[42]
1- Lindane (spiked clay soil) 2- Sodium dodecyl sulphate (100 – 5000 mg L ⁻¹) and NaHCO ₃ (500 mg L ⁻¹)	AO	Continuous circulation (60 L h ⁻¹) of the effluent (1 L) in a flow-by cell using BDD anode and steel cathode (diameter = 10 cm). $I = 50 \text{ mA cm}^{-2}$	Complete degradation of lindane at 15 Ah L ⁻¹ or 80 Ah L ⁻¹ depending on extracting agent concentration.	[43]
1- Clopyralid 2- Synthetic groundwater	EF	Batch undivided cylindrical glass reactor (800 mL) with Pt anode (32 cm ²) and carbon felt cathode (112 cm ²). Continuous air bubbling. $[\text{Fe}^{2+}]_0 = 0.1 - 5 \text{ mM}$. pH = 3 $I = 50 - 300 \text{ mA}$	80% degradation of clopyralid, 30% mineralization and biodegradability increase after 480 min of treatment at 200 mA.	[44]
1- Phenanthrene (not a pesticide) 2- Cyclodextrin (9000 mg L ⁻¹)	EF and AO	Batch undivided cylindrical glass reactor (400 mL) with Pt, DSA or BDD anode and carbon felt cathode (150	Complete removal of degradation after 240 min at 500 mA for EF-BDD ($k_{\text{app}} = 0.012 \text{ min}^{-1}$) and 9% TOC removal.	[38]

		cm ²). [Na ₂ SO ₄] = 0.15 M. [Fe ²⁺] = 0.2 mM and air bubbling for EF. <i>I</i> = 500 - 2000 mA		
1- Phenanthrene or several PAHs (not pesticides) 2- Tween ® 80 (6550 mg L ⁻¹)	AO	Batch undivided cylindrical glass reactor (400 mL) with BDD anode and stainless steel cathode (150 cm ²). [Na ₂ SO ₄] = 0.05 M. <i>I</i> = 2.1 - 42 mA cm ⁻²	Selective degradation of target pollutants. 75 – 90% removal of PAHs after 23 h at 2.1 mA cm ⁻² , while the extraction capacity was only 5% lower than the fresh one.	[40**]