



HAL
open science

First observations about response times and connectivity in a vehicles platooning experiment

Elsa Lanaud, Andres Ladino, Christine Buisson

► **To cite this version:**

Elsa Lanaud, Andres Ladino, Christine Buisson. First observations about response times and connectivity in a vehicles platooning experiment. *Transport Findings*, 2021, 10.21949/1504485. hal-03168981v1

HAL Id: hal-03168981

<https://hal.science/hal-03168981v1>

Submitted on 15 Mar 2021 (v1), last revised 13 Aug 2023 (v2)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

First observations about response times and connectivity in a vehicles platooning experiment

Elsa Lanaud¹, Andres Ladino¹, and Christine Buisson¹

¹Univ Gustave Eiffel, Univ Lyon, ENTPE, LICIT, F-69675 Lyon, France

Abstract A key question about cooperative vehicle longitudinal control is reactivity, which determines the future of road safety, and capacity. In adaptive cruise control (ACC), the controller adapts the speed of the vehicle to its immediate leader's speed whereas, in the cooperative version (CACC), connectivity between the platoon equipped vehicles reduces their response times. The USDoT Cooperative Automated Research Mobility Applications (CARMA) platform provides data for platooning experiments involving ACC and CACC vehicles. We measure ACC response times (mean = 2.78 seconds) larger than for human-driven cars. We study response times inside CACC platoons showing that connectivity is not always effective.

Research Questions and Hypothesis

Level 5 automation for autonomous vehicles (according to (SAE International, 2019) classification) is an ambitious objective. Safety and reliability are required within those automation systems. Promises of longitudinal control include a significant reduction of the inter-vehicular response times, increasing capacity. For human-driven cars, the reaction time (including perception, decision, and action) is about 1.2 s (with a standard deviation of 0.3 s) according to literature (see for example (Schakel et al., 2010), which agrees with earlier references). A surrogate for human eyes, brain and legs via an automated system comprising precise sensors, rapid computers, and reliable actuators would be the best way to reduce current response times. Two main types of automated longitudinal control exist:

ACC: Adaptive Cruise Control. The vehicle measures distance and estimates speed concerning its immediate leader, adapting its speed to the current situation. The controller acts locally, meaning that in a platoon the vehicle n reacts to vehicle $n - 1$ immediately in front of it. Therefore, in ACC platooning experiments, the response time of the ACC vehicle number n in the platoon compared to the leader vehicle 0 (we name this response time RT_{n-0}), will likely be about n times larger than the response time of any vehicle compared to its immediate leader ($RT_{n-0} \simeq n \times RT_{n-(n-1)}$).

CACC: Cooperative Adaptive Cruise Control. The platoon setting in this condition adds information to the local control by communicating information (speed, inter-distances) from preceding vehicles in the platoon $0, 1, \dots, n - 1$ towards vehicle n . Therefore, whatever is the position of the vehicle inside the platoon, the transmission of the speed change information should be almost the same, leading to the independence of RT_{n-0} to the value of n ($RT_{n-0} \simeq RT_{1-0}$).

We analyse data collected during two groups of experiments presented in (Tiernan et al., 2017). The experiments involve platoons of five successive vehicles driving in ACC or CACC mode¹. This provides the first answers to the following questions: (1) what are the observed values of response times inside a platoon made of ACC vehicles? And (2) are the response times to a leader speed change in a CACC platoon and the position inside the platoon independent?

Methods and Data

Data sets provided by U.S. Department of Transportation (2018) report platooning experiments of five vehicles driving in the same lane, with the platoon leader 0 applying scenarios of consecutive plateau of speeds 0, 20 or 26 m/s. Each experiment lasts 6 to 12 minutes with about five leader's speed changes in each. The first group of experiments, conducted in 2016, presents a lot of missing data. The second group of platooning experiments, performed in 2018, only includes the CACC mode. We aim to analyse the response time of the follower vehicle to a speed change of the leader.

Corresponding author: christine.buisson@univ-eiffel.fr

¹These experiments were realized in the Volpe Center test track. Each Cadillac SRX vehicle was equipped with the CARMA system and was driven by a professional driver. The data collection procedure was identical for each platoon experiment. Data available here: <http://doi.org/10.21949/1504485>.




Figure 1. Sample of speed transition detection in a platoon made of vehicles 0 to 4.

Based on the vehicle’s speed profile and the setting time when speed changes, we examine if such speed changes surpass a threshold given by the total variance of the vehicle’s acceleration. With this detection method, we identify the instants at which speed transitions occur (see Figure 1). Thus, by comparing the speed change instants of two successive vehicles, we compute response times².




Figure 2. Boxplot of response times [s] with respect to immediate leader for ACC mode.

We have considered the 2016 ACC and the 2018 CACC data sets. In the ACC case, we obtained a sample of 4 platoon experiments and identified 7 platoon leader’s speed changes. We thus identified 28 events of speed changes leading, after the rejection of 4 outliers (out of the interval [0; 7.7] s), to a group of 24 events, all treated independently. For the CACC case, the change in speed profile allowed our detection method to identify 9 speed transitions for vehicles 0 to 4 of the platoon.




Figure 3. Box plots of response times [s] with respect to platoon leader for the CACC case for various positions of the vehicles in the platoon.

²Code for reproduction of results available at: https://github.com/aladinoster/vrt_analysis

Findings

Values of the ACC response times of all followers to their immediate leader's speed changes (RT_{n-n-1}) are displayed in figure 2. We observe a mean value of 2.78 s and a standard deviation of 1.61 s. Compared to other findings, this is twice the mean value of human drivers' reaction times (see (Schakel et al., 2010; Ranjitkar et al., 2003)). Compared with other ACC experiments, our observations are significantly larger than the ones presented in previous papers:

- (Makridis et al., 2020) reports values twice lower, with different experimental settings,
- The recent results presented in (Li et al., 2020) are 1 s lower, with a similar measurement method, when the CACC is set to maximal headways.

This claims for further data analysis, in particular to scrutinize the influence of cars' automation heterogeneity (Gunter et al., 2020).

For the CACC case, the response times of the vehicles with respect to speed changes of the platoon leader (RT_{n-0}) are displayed in figure 3. For the first vehicle, as expected, we do observe much shorter reaction times compared to what was observed in the ACC case, similarly to (Milanés and Shladover, 2014). This is not the case for the vehicle in position 4. The answer to our second research question is therefore certainly not "yes", figure 3 showing a dependence of the response time with the vehicle position. From this, we can suspect a partial inefficiency of the communication layer.

To summarize, even though our analysis suffers from a low sample size, the first results suggest that ACC times are not significantly shorter or at least comparable to the one of human-driven cars. Connectivity remains an aspect for further study since connectivity loss may be the explanation of unexpected delays degrading the response time in CACC platoon mode.

Acknowledgements

The authors thank warmly the Volpe laboratory team (Tim Tiernan, Nicholas Richardson, Philip Azeredo, Wassim G Najm, and Taylor Lochrane) for their work, for making their data accessible, and for their responsiveness to our technical questions. Warm thanks are also due to the reviewers for their careful reading and comments.

References

- SAE International. Sae standards news: J3016 automated-driving graphic update, 2019. URL <https://www.sae.org/site/news/2019/01/sae-updates-j3016-automated-driving-graphic>. Last Modified: 2020-05-15T14:03:15-04:00.
- Wouter. J. Schakel, Bart Arem, van, and Bart D. Netten. Effects of cooperative adaptive cruise control on traffic flow stability. In *13th International IEEE Conference on Intelligent Transportation Systems*, pages 759–764, September 2010. doi: 10.1109/ITSC.2010.5625133.
- Tim Tiernan, Nicholas Richardson, Philip Azeredo, Wassim G Najm, and Taylor Lochrane. Test and evaluation of vehicle platooning proof-of-concept based on cooperative adaptive cruise control. Technical report, John A Volpe National Transportation Systems Center, U.S. Department of Transportation, McLean, VA 22101, April 2017. URL <https://rosap.ntl.bts.gov/view/dot/1038>.
- Prakash Ranjitkar, Takashi Nakatsuji, Yoichi Azuta, and Gemunu Senadeera Gurusinghe. Stability analysis based on instantaneous driving behavior using car-following data. *Transportation Research Record*, 1852(1):140–151, 2003.
- Michail Makridis, Konstantinos Mattas, Biagio Ciuffo, Fabrizio Re, Akos Kriston, Fabrizio Minarini, and Greger Rognelund. Empirical study on the properties of adaptive cruise control systems and their impact on traffic flow and string stability. *Transportation research record*, 2674(4):471–484, 2020.
- Tienan Li, Danjue Chen, Hao Zhou, Jorge Laval, and Yuanchang Xie. On the equilibrium and non equilibrium features of adaptive cruise control vehicles: a study based on empirical experiments. In *Transportation Research Board*, 2020.
- George Gunter, Derek Gloudemans, Raphael Stern, Sean McQuade, Rahul Bhadani, Matt Bunting, Maria Laure Delle Monache, Roman Lysecky, Benjamin Seibold, Jonathan Sprinkle, Benedetto Piccoli, and Daniel Work. Are commercially implemented adaptive cruise control systems string stable? *IEEE Transactions on Intelligent Transportation Systems*, pages 1–12, 2020.
- Vicente Milanés and Steven E. Shladover. Modeling cooperative and autonomous adaptive cruise control dynamic responses using experimental data. *Transportation Research Part C: Emerging Technologies*, 48:285–300, 2014. ISSN 0968-090X. doi: 10.1016/j.trc.2014.09.001. URL <http://www.sciencedirect.com/science/article/pii/S0968090X14002447>.
- Xiaoliang Ma and Ingmar Andréasson. Estimation of driver reaction time from car-following data: Application in evaluation of general motor-type model. *Transportation research record*, 1965(1):130–141, 2006.
- U.S. Department of Transportation. Cooperative automated research mobility applications (CARMA) 2, 2018. URL <http://doi.org/10.21949/1504485>.

Steven E. Shladover, Christopher Nowakowski, Xiao-Yun Lu, and Raymond Hoogendoorn. Using cooperative adaptive cruise control (CACC) to form high-performance vehicle streams - definitions, literature review and operational concept alternatives, 2014. URL https://path.berkeley.edu/sites/default/files/ear_cacc_task_1_concept_of_operations_report_changesaccepted2.pdf.