Equilibrium and Optimal Location of Warehouses in Urban Areas: A Theoretical Analysis with Implications for Urban Logistics

François Combes

► To cite this version:

François Combes. Equilibrium and Optimal Location of Warehouses in Urban Areas: A Theoretical Analysis with Implications for Urban Logistics. TRB : Transportation research record, 2019, 2673 (5), p 262-271. 10.1177/0361198119838859 . hal-03272805

HAL Id: hal-03272805

<https://hal.science/hal-03272805>

Submitted on 28 Jun 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Equilibrium and optimal location of warehouses in urban areas: a theoretical analysis with implications for urban logistics

François Combes*

Abstract

This paper presents a structural microeconomic model of the choice of warehouse location in urban logistics. The model is theoretical and analytical. It brings the focus on operational constraints, their diversity, and their influence on costs. The location decision is modelled as a trade off between land rents (making it costly to locate close to the center of the urban area) and transport costs (which increase non linearly when the warehouse moves away from the city center.) The influence of various parameters on the optimal warehouse location is analysed. The following conclusions are drawn. First, increased demand contributes to explain logistic sprawl: when the density of operations (pick-ups and deliveries) increase in a given area; transport is more efficient, making it less necessary for warehouses to be close to the city center. Second, urban logistics is a heterogenous sector and, depending on the operational constraints, will not react homogenously to changes in economic parameters or the implementation of public policies. Third, economies of scale are identified: some implications are discussed. Fourth, the paper briefly discusses how land-use planning, regarding in particular warehouses, can help internalise some of the externalities of urban logistics.

1 Introduction

Urban logistics commonly refers to the systems and processes which make possible the supply of commodities in urban areas. As such, it is an essential, non substitutable economic function of cities (1, 2). It includes urban freight transport, as well as supply chain management insofar as it directly regards urban areas, including storage, handling and cross-docking in warehouses inside or around urban areas. The location of these warehouses is a complex, yet critical process (3, 4).

From a public policy standpoint, urban logistics raises a number of issues: it requires real estate, in a place where real estate is scarce; it generates traffic, in a place where roads are congested, parking space lacks, and pollution and noise are particularly harmful, due to both building configuration and the mere concentration of residents (5).

*ORCID ID 0000-0001-5658-4437, IFSTTAR, AME/SPLOTT, 14-20 bvd Newton, 77447 - Marne-la-Vallée, France.

1 As a consequence, a reduction in the pressure that urban logistics exerts on urban areas
2 is strongly wished for.

3 And yet, the beneficiaries of urban logistics, i.e., mostly, residents (either directly or
4 through retail stores), are a particularly demanding and difficult segment to satisfy from
5 a supply chain management perspective. Indeed, the demand is spatially and temporally
6 dispersed, prefers frequent orders of small amounts of commodities, and values highly
7 variety, flexibility, and, when relevant, short lead time. Thus the cost of the last mile,
8 often estimated to be a substantial share of total logistic costs. As a consequence, urban
9 logistics heavily relies on a large flow of small vehicles, not used at weight or volume
10 capacity, often old and polluting.

11 Urban logistics is undergoing a number of trends which very probably intensify
12 these issues. One can quote e-commerce (6), which is generally associated with small
13 and unpredictable orders (7). Also, multi-channel distribution, where supply chains are
14 reorganised to provide customers with several logistic alternatives, comes with a com-
15 plexity which probably makes it more difficult to leverage economies of scale and use
16 environmentally virtuous transport organisations. The impact of new technologies, ser-
17 vices (such as the rise of instant deliveries, 8), and marketplaces, is currently extremely
18 uncertain, and will have to be assessed in the long term.

19 This paper is focused on a specific trend: logistics sprawl. Logistics sprawl refers
20 to the phenomenon observed in many large urban areas (although not all of them) where
21 warehouses and logistic platforms tend to move away from the urban areas, faster than
22 other economic activities or households (9–12). This trend is particularly alarming, as it
23 directly reinforces the impacts of urban logistics, by making vehicles cover longer dis-
24 tances to provide the same service(13). It is also not a fatality: compared to some of the
25 trends quoted above, which essentially stem from technological or organisational inno-
26 vations, and sometimes seem quite inescapable, logistic sprawl is a standard land use
27 planning issue. As such, it is governed by transport economics and urban economics,
28 and it can be addressed by policy instruments such as land use planning and regulation.

29 However, before policy recommendations are suggested, a thorough understanding
30 of the issue is necessary. The objective of this paper is to contribute to this under-
31 standing by the means of a microeconomic model. The model considers commodities
32 delivered in an urban area by vehicles starting from a logistic platform located at the
33 outskirts of the urban area. The location of the logistic platform is assumed to be a trade-
34 off between land rent and transport costs. Particular attention is paid to the modelling
35 of transport costs (14). Indeed, the structure of transport costs results from various
36 operational constraints; several distinct regimes (i.e. types of constraints) are analysed
37 and compared. The sensitivity of the location of the logistic platform to the model's
38 parameters is investigated. The (private) optimum location of the logistic platform is
39 also investigated, with the introduction of a number of externalities.

40 The originality of the paper relies on the detailed representation of the transport
41 cost structure and the distinction and explicit representation of several operational con-
42 straints. This diversity of these constraints illustrates how difficult it can be to measure
43 the overall performance of urban logistics, or lack thereof: simply measuring it with an
44 average loading factor, for example, can be strongly misleading. Economies of scales
45 are identified regarding transport costs: some implications are briefly discussed. The
46 paper also contributes to understanding the drivers of the location of logistic platforms,

1 and confirms the role of land rents (especially land rent gradients) in the process. Fi-
2 nally, it discusses the extend to which land use planning actions can correct some of the
3 market failures of urban logistics.

4 The paper proceeds as follows: Section 2 presents the modelling assumptions, and
5 derives the total cost function, under different sets of assumptions. Section 3 presents
6 and discusses the model's properties. Section 4 concludes the paper.

7 **2 Model presentation**

8 This section begins with a brief presentation of urban logistics, based on the example
9 of the urban area of Paris (Section 2.1). Then, the main modelling assumptions are
10 presented (Section 2.2). Finally, the model is elaborated in Section 2.3.

11 **2.1 A brief description of urban logistics, based on the case of the** 12 **urban area of Paris, France**

13 Before diving into the specifics of the model, it is useful to present a few facts about
14 freight transport operations regarding urban areas. Consider a shipper sending com-
15 modities towards a given receiver (both can be firms or individuals, or households).
16 There are very basically two options to transport those commodities: the first one is
17 direct transport, where the vehicle loads the shipment at the origin, carries it to the des-
18 tination and unloads it (full truckload - FTL), possibly with a few other shipments going
19 from similar origins to similar destinations (partial truckload).

20 The second is massified transport (Less Than Truckload - LTL), where the ship-
21 ment is picked up together with other shipments in the vicinity, regardless of destina-
22 tion, brought to a warehouse, or a cross-docking platform, where it is unloaded, sorted,
23 loaded onto another vehicle, carried toward another cross-docking platform close to the
24 destination area, where it will, again, be unloaded, sorted, and loaded in a vehicle, to
25 be delivered it a certain area, together with other shipments.

26 The first option is adapted for rather large flows of not too time sensitive commodi-
27 ties, whereas the second option is relevant for smaller flows of more time sensitive
28 commodities (consistently with the theory developed in (15), and confirmed empiri-
29 cally in this specific case in (16)).

30 The second organisation is prevalent in urban logistics. Consider the case of the
31 urban area of Paris, France (17,175km², 12.4 million inhabitants). A urban goods
32 movement survey was realised in this area in 2010-2012; it reveals that 38% of the
33 movements (pickups or deliveries) are realised by car or light commercial vehicles,
34 29% by vans, 23% by straight trucks, and only 9% in semi-trailers (17). Parcel deliver-
35 ies are mainly associated with vans and small LCVs, while pallets are more generally
36 delivered by straight trucks (18, 19). Also, many of the movements observed in the
37 survey which were made by semi-trailers are deliveries toward large retail centers or
38 warehouses, which in turn emit movements of smaller vehicles, with an average ratio
39 of three to four outgoing vehicles for one incoming vehicle (17). Finally, it should be
40 noted that the survey is strongly oriented towards B2B flows and therefore misses an
41 unknown share of B2C flows (but estimated to amount to about a third of all movements

1 in 8), which tends to strengthen the above statement again. It is therefore legitimate to
 2 state that the share of LTL transport is overwhelming in the case of the urban area of
 3 Paris, and possibly in other large urban areas as well.

4 2.2 Main modelling assumptions

5 Consider a given large urban area. Given the previous discussion, the focus is brought
 6 on shipments handled in a warehouse inside or at the outskirts of the urban area be-
 7 fore being delivered. Shipments transported in partial or full truckload are disregarded.
 8 Courier activity is ignored as well.

9 By assumption, every shipment delivered in the urban area undergoes the sequence
 10 of operations illustrated in Figure 1. In this figure, the shipment of interest is the small
 11 red block stored in a warehouse (visible at the left-hand side of the picture), ordered by
 12 a given receiver (depicted by a red cross at the right-hand side), in a given urban area
 13 where other shipments will be delivered and picked up. For a delivery, the sequence of
 14 operations is as follows:

- 15 a) the shipment is loaded into a large vehicle (typically a semi-trailer), carried to-
 16 ward a cross-docking platform.
- 17 b) the shipment is unloaded, sorted and loaded in a smaller vehicle.
- 18 c) the smaller vehicle reaches the area where the deliveries and pick-ups will be
 19 made.
- 20 d) the shipment is delivered, during a round where other operations are realised.

21 The distinction between the approach and return movements, on one hand, and
 22 the intermediate movements on the other hand is directly drawn from (20). The gray,
 23 dashed lines illustrate the other vehicles coming to the warehouse or leaving it, from or
 24 towards other places.

Figure 1: Operations sequence

25 Another set of assumptions should be discussed here, regarding the operational con-
 26 straints in urban logistics. By operational constraint, we mean the physical or technical
 27 constraints that limit the operations which can be realised with a given vehicle and/or
 28 a given driver. From this perspective, there are several possibilities, and, to the au-
 29 thor's knowledge, no data to assess the prevalence of each of them. In this paper, the
 30 following regimes are distinguished:

- I) the round's duration must be lower than a certain time limit H , e.g. a driver's workday duration, or half of it if the vehicle has to come back to the origin warehouse in the middle of the day. H is exogenous.
- II) receivers expect a lead time lower than H ; this applies a constraint to the round duration. H is considered exogenous in this paper, although it actually derives from an interaction between the cost of providing a certain lead time, on the supply side, and the willingness to pay for that lead time, on the demand side.
- III) receivers must be delivered during a certain time window of duration H . This case is notably relevant for wholesale trade, where restaurants, bars or retail stores must be delivered in the morning.
- IV) the vehicle has a limited range L . While currently seldom relevant, this constraint may become critical in scenarios where alternative vehicles (such as electric vehicles) are considered, and is worth examining.

H need not be equal under regimes I to III. It should also be noted the model is not relevant for all deliveries with short lead time: while the sequence of operation described in Figure 1 is probably relevant for standard parcel delivery, where all shipments are loaded at a given warehouse, it is completely irrelevant for food ordering or other similar services where couriers carry directly meals from restaurants to customers without consolidation.

Note that volume and weight capacity constraints play an apparently very little role in the paper. They are not explicitly represented, but they are present, in the cost parameters for example. However that capacity is seldom the binding constraint in urban logistics, specifically for small shipments: the binding constraints lie elsewhere.

2.3 The total cost function

The model consists in a cost function which distinguishes two parts: the warehousing cost, and the transport cost. This section details these cost components and presents the resulting total cost function. The calculations are detailed for regime I only, additional details are available on request.

The warehousing cost function Regarding warehousing costs, there is an abundant operations research literature, but given the level of detail required in this paper, and the lack of data, it is of little use in this paper's context. In this paper, the unit warehousing cost denotes the cost of unloading, sorting, handling, and loading a shipment. Based on textbooks such as (21), warehousing typically requires the main following resources: land use, building, human resources, and equipment. Land use cost will directly depend on the location of the warehouse. The warehousing cost is assumed proportional to the amount of operations, and dependent on location. Location is very simply represented by the distance of the warehouse to the operation area (the area where shipments are delivered and picked up), which is assimilated to the city center: this distance is denoted by l . Space is assumed to be continuous: location of highways or other transport infrastructures or the discontinuous and dynamic character of the real estate market are

1 ignored. The city is assumed monocentric and radially symmetric. As a consequence, the
 2 unit warehousing cost per operation is $c_w(l)$, with c_w a decreasing function.

3 **The transport cost function** Operations are realised in sequence during rounds. This
 4 raises a difficult issue: finding the optimal round to deliver a given set of locations is
 5 a classic operations research problem (the Traveling Salesman Problem), known to be
 6 NP-complete. In order to circumvent this difficulty, the approach of (14) is followed.
 7 Consider an area of surface A , where F operations should be realised over the relevant
 8 time period. These F locations are randomly allocated across the area. Let δ denote
 9 the average distance between two consecutive operations: it is inversely proportional
 10 to the square root of the density of operations in the area, up to a constant k .

$$\delta = k\sqrt{\frac{A}{F}}. \quad (1)$$

11 Figure 2 belows illustrates Equation (1). From case (A) to case (B), the number of
 12 operations is multiplied by four ; at the same time, the average intermediate distance is
 halved.

Figure 2: Operations density and intermediate distance.

13 Now, depending on the regime, let us derive the number of operations which can be
 14 realised in one round. Let us focus on regime I . Denote by v_a (resp. v_z) the average
 15 vehicle speed during the approach movement (resp. during intermediate movements),
 16 and denote by h the duration of each operation excluding transport (i.e., precisely, the
 17 time to load, unload, sign papers, etc.) Denote by x the number of operations. The total
 18 round duration, for a given x , and given the sequence operation presented in Section
 19 2.2, is denoted by d , and such that:
 20

$$d = 2\frac{l}{v_a} + x\left(h + \frac{\delta}{v_z}\right). \quad (2)$$

21 The round duration is constrained: $d = H$. As a consequence:

$$x = \frac{H - 2l/v_a}{h + \delta/v_z} \quad (3)$$

22 Two comments can be made about this equation. First, x decreases with l : the
 23 farther the warehouse, the less operations can be done during one round. This is the

1 root of the *value of proximity* for a warehouse in this situation. Second, this requires
 2 that $l < H v_a/2$: the round duration cannot be lower than the time needed to reach the
 3 area and come back.

4 Let H_r denote the in-zone time, i.e. the time actually spent by the vehicle in the
 5 operation area:

$$H_r = H - 2l/v_a. \quad (4)$$

6 Also, let $h_o = h + \delta/v_z$ denote the duration of an operation, including the time re-
 7 quired to travel the intermediate distance between successive operations. Then, Equa-
 8 tion (3) can be rewritten as follows:

$$x = \frac{H_r}{h_o}. \quad (5)$$

9 In order to derive the transport cost function, the distance dependent cost and the
 10 time dependent cost of running a vehicle should be distinguished. The distance depen-
 11 dent cost is assumed to increase linearly with distance, up to a coefficient c_l . It is mainly
 12 related to energy consumption and vehicle wear and tear. The time dependent cost is
 13 assumed to increase linearly with time, up to a coefficient c_h . It is related to the cap-
 14 ital opportunity cost and the wages. The length of a round is $2l + (H_r/h_o)\delta$, and its
 15 duration is H . Therefore, the cost of a round is $(2l + (H_r/h_o)\delta)c_l + Hc_h$.

16 It is now possible to derive the unit transport cost:

$$c_t = (2lc_l + Hc_h) \frac{h_o}{H_r} + \delta c_l. \quad (6)$$

17 With some manipulations, replacing δ with Equation (1), and with $c_R = 2lc_l + Hc_h$:

$$c_t = \frac{c_R}{H_r} h + \left(\frac{1}{v_z} \frac{c_R}{H_r} + c_l \right) k \sqrt{\frac{A}{F}}. \quad (7)$$

18 Note that c_R increases with l , and H_r decreases with l . As a consequence c_t is
 19 an increasing function of the distance of the warehouse to the city center, and doubly
 20 so: first because when l increases, it is more costly to reach the operation area, second
 21 because there is less time to actually proceed to operations in that area.

22 Also, the transport cost upwards the warehouse was not taken into account, for
 23 simplicity. As a matter of fact, if it is assumed to only depend on l , it can be accounted
 24 for by a modification of c_w .

25 **The total cost function** The total unit cost under regime I, which sums the unit ware-
 26 housing cost and the unit transport cost, is:

$$c(l) = c_w(l) + \frac{c_R}{H_r} h + \left(\frac{1}{v_z} \frac{c_R}{H_r} + c_l \right) k \sqrt{\frac{A}{F}}. \quad (8)$$

27 One component of the cost function decreases with l (the farther from the city center,
 28 the lower the warehousing cost), while the other increases with l (the farther from the
 29 city center, the higher the unit transport cost).

Total cost functions under the other regimes Let us first consider the case of regimes *II* and *III*. Under regime *II*, the time constraint is modified: instead of having a constraint on the total round duration, there is a constraint on the maximum lead time: the time span between departure from the warehouse and the last delivery cannot exceed H (picking, packing and handling can be included in the constraint.) Under regime *III*, the constraint is on the time spent in the operation area: the time span between arrival in and departure from the operation area cannot exceed H .

The equations above can be easily generalised to all three regimes. First, the following coefficients are introduced:

$$\begin{cases} \rho^I = 2, \\ \rho^{II} = 1, \\ \rho^{III} = 0. \end{cases} \quad (9)$$

Let $h_a = l/v_a$ define the time to access the operation zone: Then, modify the in zone time H_r given by Equation (4) as follows:

$$H_r = H - \rho h_a. \quad (10)$$

This implies that for $\rho > 0$, distance l cannot be larger than Hv_a/ρ . For $\rho = 0$ there is no such constraint. Also, modify c_R as follows:

$$c_R = 2lc_l + (H + (2 - \rho)h_a)c_h \quad (11)$$

Then, Equations (7) and (8) remain valid. Note that all other things equal, $c_t^I(l) > c_t^{II}(l) > c_t^{III}(l)$, as simple calculations (omitted here) confirm. This behaviour is intuitive: for a given H , the constraint is stronger under regime *I* than under regime *II* (resp. regime *III*), therefore the unit cost is necessarily lower under the latter.

Regime *IV* works differently: a range constraint is considered. The length of the round must be lower than L :

$$2l + x\delta = L. \quad (12)$$

The transport cost function under regime *IV* is:

$$c_t(l) = \left(c_l + \frac{c_h}{v_z}\right)\delta + c_h h + \left(c_l + \frac{c_h}{v_a}\right)\frac{2l\delta}{L - 2l}. \quad (13)$$

Therefore, the total cost function is:

$$c^{IV}(l) = c_w(l) + \left(c_l + \frac{c_h}{v_z}\right)\delta + c_h h + \left(c_l + \frac{c_h}{v_a}\right)\frac{2l\delta}{L - 2l}. \quad (14)$$

Illustration Figure 3 presents the behaviour of the warehousing, transport and total costs under each regime, with the following parameters: access speed $v_a = 40$ km/h (25 mph), in zone speed $v_z = 15$ km/h (9 mph), distance between two operations $\delta = 800$ m (0,5 mile), duration of an operation $h = 0.2$ h, distance dependent cost $c_l = 1.2$ €/km (about \$2,3/mile), time dependent cost $c_h = 20$ €/h (about \$38/mile), and finally a linear gradient of the unit warehousing cost $c'_w = -0.15$ €/km (about

1 \$0.27/mile). Without aiming at realism, it amounts to rounds with twenty to thirty
2 operations, for a unit transport cost between 6 to 10 €(excluding warehousing costs),
3 which are reasonable orders of magnitude for the last stage of transport of relatively
4 small LTL – but larger than parcels – shipments toward a large urban area.

5 The following scenarios are then distinguished: one where the total round duration
6 is limited to eight hours (as an example of regime *I*), one where deliveries need to be
7 faster than two hours (as an example of regime *II*, H was fixed at 1.5h to account for
8 order processing), one where the delivery time window is limited to 4h (as an example
9 of regime *III*) and finally one where the round cannot be longer than 70km (as an
10 example of regime *IV*).

Figure 3: Comparison of cost functions for regimes I-IV

11 Several mechanisms interact in the results which can be observed in Figure 3. In
12 all cases, getting closer to the center saves on transport cost, but the intensity differs.
13 Theoretically, for a given set of parameters, including H , the value of proximity is
14 higher under regime *I*, which is more strongly constrained, than under regimes *II* and
15 *III*. However, H itself plays a very important role, and the smaller it is, the stronger
16 the constraint. This is why the transport cost increases so quickly with distance in the
17 second case, where the delivery lead time is limited to 1.5h, with the consequence that
18 it is optimal to be as close to the city center as possible. In this example, regime *IV*
19 gets to the limit faster than the others.

20 **3 Private optimum, static comparatives, policy impli-** 21 **cations**

22 This section analyses the model's properties. First, the first order conditions of ware-
23 house location optimality are derived (Section 3.1). Then, the influence of the model's
24 parameters on the optimal warehouse location is analysed in Section 3.2. Finally, some

1 policy implications are discussed in Section 3.3.

2 **3.1 Condition of private optimality**

3 The private optimum is the location which minimises the total unit cost function (8).
 4 The social optimum is outside the paper's scope; it is briefly discussed in Section 3.3.
 5 The private optimum can be at the center (e.g. regime *II* in Figure 3), when transport
 6 costs increase so fast that it is optimal to be as close as possible to the operation area;
 7 or it can be optimal to be at the periphery, when land rents stop decreasing. An interior
 8 solution can also be optimal; in that case it is a necessary condition that $dc/dl = 0$.

9 The differential of c for regimes *I* – *III* is:

$$dc = c'_w dl + \frac{dc_R H_r - c_R dH_r}{H_r^2} h + \left(\frac{1}{v_z} \frac{dc_R H_r - c_R dH_r}{H_r^2} \right) \delta. \quad (15)$$

10 By noticing that $dc_R = 2c_l dl + (2 - \rho)c_h dh_a$, $dh_a = dl/v_a$ and $dH_r = -\rho dl/v_a$
 11 and with a few manipulations, the first order condition on the optimality of l for regimes
 12 *I* to *III* is obtained:

$$0 = c'_w + \left(2c_l + (2 - \rho) \frac{c_h}{v_a} \right) \frac{h_o}{H_r} + \rho c_R \frac{h_o}{v_a H_r^2}. \quad (16)$$

13 The first order condition for Regime *IV* is straightforwardly derived from Equation
 14 (14). When distinguishing each regime:

$$\begin{cases} \text{Regime I} & : -c'_w = 2c_l \frac{h_o}{H_r} + 2c_R \frac{h_o}{v_a H_r^2}, \\ \text{Regime II} & : -c'_w = \left(2c_l + \frac{c_h}{v_a} \right) \frac{h_o}{H_r} + c_R \frac{h_o}{v_a H_r^2}, \\ \text{Regime III} & : -c'_w = \left(2c_l + \frac{2c_h}{v_a} \right) \frac{h_o}{H_r}, \\ \text{Regime IV} & : -c'_w = \left(2c_l + \frac{2c_h}{v_a} \right) \frac{L+4l}{(L-2l)^2} \delta \end{cases} \quad (17)$$

15 As is standard in urban economics, at the optimum, the land rent savings which
 16 come from moving one kilometer away from the city center are exactly offset by the
 17 additional transport costs. These costs come from two mechanisms: first, the approach
 18 and return movements are longer, increasing the unit transport cost; second, they take
 19 more time so that less operations can be realised in a round, further increasing the unit
 20 transport cost.

21 **3.2 Comparative statics**

22 The objective is to analyse the influence of each of the model's parameters on the opti-
 23 mal location of the warehouse. To do so, apply the implicit function theorem to Equa-
 24 tions (17). This requires calculating the total differential of each of these equations.

25 First, consider regimes *I* to *III*. Denote by Γ the right-hand side of Equation (16).
 26 Denote by Γ_x the partial differential of Γ with respect to variable x . Then, the total
 27 differential of Γ is:

$$d\Gamma = \Gamma_l dl + \Gamma_{c_l} dc_l + \Gamma_{c_h} dc_h + \Gamma_{v_a} dv_a + \Gamma_{v_z} dv_z + \Gamma_H dH + \Gamma_h dh + \Gamma_\delta d\delta, \quad (18)$$

Then:

$$\Gamma_l = c_w'' + \frac{4c_l\rho H_o}{v_a H_r^2} + 2\frac{(2-\rho)\rho h_o c_h}{v_a^2 H_r^2} + \frac{2\rho^2 c_R h_o}{v_a^2 H_r^3}, \quad (19)$$

$$\Gamma_{c_l} = \frac{2h_o}{H_r} + \frac{2l\rho h_o}{v_a H_r^2}, \quad (20)$$

$$\Gamma_{c_h} = \frac{(2-\rho)h_o}{v_a H_r} + \frac{(H + (2-\rho)h_a)\rho h_o}{v_a H_r^2}, \quad (21)$$

$$\Gamma_{v_a} = -\frac{(2-\rho)c_h h_o}{v_a^2 H_r} - \frac{\rho c_R h_o}{v_a^2 H_r^2} - \frac{2(2-\rho)\rho c_h h_o l}{v_a^3 H_r^2} - \frac{2c_l h_o \rho l}{v_a^2 H_r^2} - \frac{2\rho^2 c_R h_o l}{v_a^3 h_r^3}, \quad (22)$$

$$\Gamma_{v_z} = -\frac{2c_l \delta}{H_r v_z^2} - \frac{(2-\rho)c_h \delta}{v_a H_r v_z^2} - \frac{\rho c_R \delta}{v_a H_r^2 v_z^2}, \quad (23)$$

$$\Gamma_H = \frac{\rho h_o c_h}{v_a H_r^2} - \frac{2c_l h_o}{H_r^2} - \frac{(2-\rho)c_h h_o}{v_a H_r^2} - \frac{2\rho c_R h_o}{v_a H_r^3}, \quad (24)$$

$$\Gamma_h = \frac{2c_l}{H_r} + \frac{(2-\rho)c_h}{v_a H_r} + \frac{\rho c_R}{v_a H_r^2}, \quad (25)$$

$$\Gamma_\delta = \frac{2c_l}{H_r v_z} + \frac{(2-\rho)c_h}{v_a H_r v_z^2} + \frac{\rho c_R}{v_a H_r^2 v_z}. \quad (26)$$

1 The sign of Γ_l depends on the sign of c_w'' . Let us assume that the land rent is convex,
2 or linear; this implies that $\Gamma_l > 0$. The partial differentials of Γ with respect to c_l , c_h ,
3 h and δ are clearly positive. The partial differentials of Γ with respect to v_a and v_z
4 are negative. Some simple calculations can show that the partial differential of Γ with
5 respect to H is negative. By application of the implicit function theorem, provided
6 $\Gamma_l \neq 0$, the variation of l with any parameter x is given by:

$$\frac{dl}{dx} = -\frac{\Gamma_x}{\Gamma_l}. \quad (27)$$

7 It is possible to conclude regarding the influence of the various model's parameters
8 on the distance of the warehouse to the city center:

- 9 - when the unit transport costs c_h or c_l increase, the optimal warehouse distance
10 decreases: the cost increase is partially offset by bringing the warehouse closer
11 to the city center;
- 12 - when the duration of each operation h increases, the optimal warehouse distance
13 decreases.
- 14 - when H increases (i.e. the time constraint on the operations is relaxed), the opti-
15 mal warehouse distance increases. Symmetrically, if H gets small (for example
16 to provide faster deliveries), then the value of proximity increases.
- 17 - when the access or in zone speeds v_a and v_z increase, the optimal warehouse dis-
18 tance increases: better speeds participate in relaxing the operational constraints;
19 being close to the city center is less valuable.

- when the density of operations increase (i.e. when δ decreases), then the optimal warehouse distance *increases*: when the demand is higher, operations are more efficient, proximity is less necessary.

The last point is of particular importance: while logistic sprawl can be and has been explained by many different causes, including land rent changes, one important conclusion of this paper is that changes in demand (especially the strong and sustained increase of the demand for e-commerce) probably contributes to explain the observed dynamics. Note that the expression *logistic sprawl* can refer to a number of distinct spatial dynamics: in this case, we discuss the spreading of warehouses from the city center, but not the spreading or clustering of warehouses relative to each other. The very simplified representation of space in the model makes it unsuitable for the investigation of this more complicated phenomenon.

These conclusions apply to all three regimes, from *I* to *III*. Comparing the elasticities of l with respect to the other parameters is a more involved task: remind that H_r and c_R also depend on ρ . This comparison is outside the paper's scope. Regarding regime *IV*, the results are not detailed. The model's behaviour is rather similar, except that $\Gamma_{v_z} = \Gamma_h = \Gamma_\delta = 0$: the corresponding variables have no influence on the optimum location (under the assumption that the autonomy is truly exogenous). However, even though the signs of the influence of each parameter on l is unchanged, the intensity of the variation will vary. These regimes will not react similarly to given changes in the parameters: urban logistics is a heterogeneous system; and this heterogeneity comes, among other things, from the diversity of constraints under which the agents operate.

Also outside the scope of this paper is an in-depth discussion of the influence of the various model's parameters on the total cost function. Nevertheless, any parameter which has an influence on l has an influence on total costs. More precisely, when a parameter decreases l , it increases the total cost, and conversely. Let us illustrate this point with the case of fast deliveries (Figure 4).

Figure 4: Distance to center and total cost as function of lead time under regime *II*.

1 This figure confirms the discussion above: when H decreases, it is more efficient to
 2 get closer to the city center. However the total cost increases: this is a classic microe-
 3 conomic mechanism where it is possible to adapt to a price increase or to a constraint
 4 strengthening, but not to the point where the cost increase is fully offset. Note that this
 5 discussion suffers from an important limitation: demand is assumed exogenous here.
 6 With endogenous demand and, as it will be seen later, economies of scales, these state-
 7 ments may not hold. In addition, if H decreases, opportunities for massification will
 8 decrease, and δ will increase. This also does limit the conclusions, and warrants further
 9 research.

10 3.3 Some policy implications

11 Urban logistics is a well known source of externalities, as discussed in the introduction.
 12 Standard microeconomic theory recommends that these externalities be internalised.
 13 The main externalities associated with urban logistics are associated with the distances
 14 covered and, to certain extent, to the duration of presence within urban areas as well
 15 (e.g. noise, pollution, congestion generated by illegal parking, etc.) Internalising these
 16 externalities (e.g. through tolls) would amount to increase c_h and c_l . This would de-
 17 crease the optimal warehouse location, getting it closer to the city center.

18 It is possible to take a different perspective: in a second best world, where it can be
 19 very difficult to internalise all externalities, which planning actions could help improve
 20 social welfare? In this case, actions that would help warehouses to locate closer to the
 21 city center would probably be welfare improving. This topic needs further investiga-
 22 tion, and a in-depth analysis of the issue requires endogenous demand. However, the
 23 model contributes to illustrate how planning should be considered as an instrument of
 24 urban logistics policy.

25 Other policy actions can be examined with this type of modelling approach. Con-
 26 sider policies such as enforcing delivery time-windows (forbidding deliveries outside
 27 a certain time window in a certain zone), or supporting off-hour deliveries (22). Under
 28 regime *III*, reducing H is costly; it also causes the optimal distance to decrease. The
 29 warehouse movement can offset part of the cost increase. However, if warehouses can-
 30 not move back towards the city center, then the policy will be very costly. Such policies
 31 are probably worth being accompanied with synergistic land-use planning initiatives.

32 A third policy implication is directly related to the structure of the cost function.
 33 Equation (8) is a unit cost function. Denote by C the total cost function: it is equal to
 34 the unit cost c times the demand F :

$$C = Fc_w(l) + F \frac{c_R}{H_r} h + \left(\frac{1}{v_z} \frac{c_R}{H_r} + c_l \right) k \sqrt{AF} \quad (28)$$

35 Let us calculate the marginal social cost of an additional receiver. According to the
 36 envelop theorem, l can be assumed fixed in the calculation:

$$\frac{\partial C}{\partial F} = c_w(l) + \frac{c_R}{H_r} h + \frac{1}{2} \left(\frac{1}{v_z} \frac{c_R}{H_r} + c_l \right) k \sqrt{\frac{A}{F}}. \quad (29)$$

1 The marginal social cost is lower than the unit cost. Specifically, denote by *mesc*
2 the marginal external social cost:

$$mesc = \frac{\partial C}{\partial F} - c = -\frac{1}{2} \left(\frac{1}{v_z} \frac{c_R}{H_r} + c_l \right) k \sqrt{\frac{A}{F}} < 0. \quad (30)$$

3 When demand increases in a given area, the density of operations increases. There-
4 fore, there are economies of scale, with an impact on cost similar to the Mohring effect
5 in public transport (23), where more passengers induce an increased frequency, to the
6 benefit of all. These economies of scale are also a possible source of economies of ag-
7 glomeration (in (24), the authors find that the sector which aggregates transport, storage
8 and communication exhibits particularly large economies of agglomeration.) For public
9 transport, the Mohring effect is often raised as a motivation for subsidisation. Should
10 urban logistics be subsidised? And how should it be? What are the interaction between
11 this positive externality and the other, negative externalities? This topic warrants a
12 dedicated discussion, which is unfortunately outside this paper’s scope.

13 4 Conclusions

14 The model presented in this paper models the optimal location of a warehouse in an
15 urban area, as the result of a trade off between transport costs and warehouse costs.
16 The model is theoretical and analytical. Close attention is paid to represent the opera-
17 tional constraints of transport. In order to represent the heterogeneity of urban logistics,
18 different constraints are distinguished: constraints on round duration, on lead time, on
19 delivery time window, and on vehicle range.

20 Despite its simplicity, the model yields a number of non trivial implications. First,
21 the role of demand density in the structure of cost is highlighted. In particular, its role
22 as a possible contribution to logistic sprawl is identified. Second, the paper identifies
23 economies of scale in urban logistics, with possibly important consequences in terms of
24 public policy which remain to be fully investigated. Third, the paper briefly addresses
25 how land-use planning aimed at urban logistics can probably be a relevant transport
26 economics policy instrument: in the difficulty to internalise directly many of the exter-
27 nalities of urban freight transport, planning warehouse location can be an indirect way
28 to reach policy objective. Finally, this model is an addition to the modelling toolset for
29 the analysis and assessment of urban public policy. The level of detail in the represen-
30 tation of the transport cost structure allows a detailed analysis of the consequences of a
31 varied range of policies.

32 Several important features lack in the model: endogenous demand, choice of re-
33 ceivers (firms or residents) between distinct channels, market structure, a better repre-
34 sentation of warehousing costs. Additional data about what type of constraint is binding
35 for whom would also be a significant step towards a better knowledge of urban logistics.
36 These limitations are directions for future research.

37 **Acknowledgements** The author would like to thank many colleagues, especially Mar-
38 tin Koning (IFSTTAR), and anonymous reviewers for comments which have proved

1 very helpful in improving the paper. The author remains responsible for the article, its
2 conclusions, and any potential mistake. This article is based on research realised in the
3 framework of the European H2020 CITYLAB research program.

4 **Author contribution statement** The author confirms sole responsibility for the fol-
5 lowing: study conception and design, analysis and interpretation of results, and manuscript
6 preparation. In addition, all the figures in the paper are the author's own elaboration.

7 References

- 8 (1) Taniguchi, E., and Thompson, R. G., *City logistics: Mapping the future*; CRC
9 Press: 2014.
- 10 (2) Macharis, C., and Melo, S., *City distribution and urban freight transport: mul-*
11 *tiple perspectives*; Edward Elgar Publishing: 2011.
- 12 (3) McKinnon, A. (2009). The present and future land requirements of logistical
13 activities. *Land Use Policy* 26, S293–S301.
- 14 (4) Raimbault, N. Gouverner le développement logistique de la métropole: périur-
15 banisation, planification et compétition métropolitaine, le cas du bassin parisien
16 et éclairages étrangers., Ph.D. Thesis, Université Paris-Est, 2014.
- 17 (5) Coulombel, N., Dablanc, L., Gardrat, M., and Koning, M. (2018). The environ-
18 mental social cost of urban road freight: Evidence from the Paris region. *Trans-*
19 *portation Research Part D: Transport and Environment* 63, 514–532.
- 20 (6) Statista Retail e-commerce sales in the United States from 1st quarter 2009
21 to 1st quarter 2018. [https://www.statista.com/statistics/187443/](https://www.statista.com/statistics/187443/quarterly-e-commerce-sales-in-the-us/)
22 [quarterly-e-commerce-sales-in-the-us/](https://www.statista.com/statistics/187443/quarterly-e-commerce-sales-in-the-us/).
- 23 (7) Agatz, N. A., Fleischmann, M., and van Nunen, J. A. (2008). E-fulfillment and
24 multi-channel distribution – A review. *European Journal of Operational Re-*
25 *search* 187, 339–356.
- 26 (8) Dablanc, L., Morganti, E., Arvidsson, N., Woxenius, J., Browne, M., and Saidi,
27 N. (2017). The rise of on-demand 'Instant Deliveries' in European cities. *Supply*
28 *Chain Forum: An International Journal* 18, 203–217.
- 29 (9) Dablanc, L., and Ross, C. (2012). Atlanta: a mega logistics center in the Piedmont
30 Atlantic Megaregion (PAM). *Journal of transport geography* 24, 432–442.
- 31 (10) Dablanc, L., Ogilvie, S., and Goodchild, A. (2014). Logistics sprawl: differen-
32 tial warehousing development patterns in Los Angeles, California, and Seattle,
33 Washington. *Transportation Research Record: Journal of the Transportation Re-*
34 *search Board*, 105–112.
- 35 (11) Sakai, T., Kawamura, K., and Hyodo, T. (2015). Locational dynamics of logistics
36 facilities: Evidence from Tokyo. *Journal of Transport Geography* 46, 10–19.

- 1 (12) Dablanç, L., Liu, Z., Koning, M., Klauenberg, J., de Oliveira, L. K., Blanquart,
2 C., Combes, F., Coulombel, N., Gardrat, M., Heitz, A., et al. Observatory of
3 Strategic Developments Impacting Urban Logistics (2017 version)., IFSTTAR-
4 Institut Français des Sciences et Technologies des Transports, de l'Aménagement
5 et des Réseaux, 2017.
- 6 (13) Andriankaja, D. Le “desserrement logistique”, quelle responsabilité dans l’augment-
7 ation des émissions de CO2 des activités de messagerie., Ph.D. Thesis, IFST-
8 TAR/Université Paris Est, 2014.
- 9 (14) Daganzo, F. F., *Logistics Systems Analysis*, Fourth; Springer: Berlin, 2005.
- 10 (15) Baumol, W. J., and Vinod, H. D. (1970). An Inventory Theoretic Model of Freight
11 Transport Demand. *Management Science* 16, 413–421.
- 12 (16) Combes, F., and Tavasszy, L. A. (2016). Inventory theory, mode choice and net-
13 work structure in freight transport. *European Journal of Transport and Infras-*
14 *tructure Research (EJTIR)*, 16 (1) 2016.
- 15 (17) Serouge, M., Patier, D., Routhier, J.-L., and Toilier, F. Enquête Marchandises en
16 Ville réalisée en Ile-de-France entre 2010 et 2013, Rapport final de convention
17 09 MT CV 46, LET, pp. 126., tech. rep., 2014.
- 18 (18) Beziat, A., Launay, P., and Toilier, F. In *6th Metrans International Urban Freight*
19 *Conference*, Long Beach, CA, USA, 2015.
- 20 (19) Beziat, A. Approche des liens entre transport de marchandises en ville, formes ur-
21 baines et congestion - Le cas de l'Île-de-France., Ph.D. Thesis, IFSTTAR/Université
22 Paris Est, 2017.
- 23 (20) Routhier, J.-L., Segalou, E., and Durand, S. Mesurer l'Impact du Transport de
24 Marchandises en Ville : le Modèle de Simulation FRETURB v1., Report for the
25 French Program *Marchandises en Ville*, 2002.
- 26 (21) Rushton, A., Croucher, P., and Baker, P., *The handbook of logistics and distri-*
27 *bution management: Understanding the supply chain*; Kogan Page Publishers:
28 2014.
- 29 (22) Holguin-Veras, J., Ozbay, K., Kornhauser, A., Brom, M., Iyer, S., Yushimito, W.,
30 Ukkusuri, S., Allen, B., and Silas, M. (2011). Overall impacts of off-hour deliv-
31 ery programs in New York City Metropolitan Area. *Transportation Research*
32 *Record: Journal of the Transportation Research Board*, 68–76.
- 33 (23) Mohring, H. (1972). Optimization and scale economies in urban bus transporta-
34 tion. *The American Economic Review* 62, 591–604.
- 35 (24) Graham, D. J., and Kim, H. Y. (2008). An empirical analytical framework for
36 agglomeration economies. *The Annals of Regional Science* 42, 267–289.