New fourier CGH coding using DMD generated masks for grayscale and color images

Frédéric Zamkotsian, Luca Oggioni, Giorgio Pariani, Patrick Lanzoni, Chiara Bertarelli, Andrea Bianco

► To cite this version:

Frédéric Zamkotsian, Luca Oggioni, Giorgio Pariani, Patrick Lanzoni, Chiara Bertarelli, et al.. New fourier CGH coding using DMD generated masks for grayscale and color images. Advances in Optical and Mechanical Technologies for Telescopes and Instrumentation IV, Dec 2020, Online Only, France. pp.31, 10.1117/12.2562532 . hal-03453570

HAL Id: hal-03453570

<https://hal.science/hal-03453570>

Submitted on 29 Nov 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

New Fourier CGH coding using DMD generated masks for grayscale and color images

Frederic Zamkotsian¹, Luca Oggioni², Giorgio Pariani²,
Patrick Lanzoni¹, Chiara Bertarelli³, Andrea Bianco²

¹ Aix Marseille Université, CNRS, CNES, LAM (Laboratoire d'Astrophysique de Marseille), 13388, Marseille, France

² INAF – Osservatorio Astronomico di Brera, Via Bianchi 46, 23807 Merate, Italy

³ Politecnico di Milano, Dipartimento di Chimica, Materiali e Ingegneria, p.zza L. Da Vinci 32, 20133, Milano, Italy

e-mail: frederic.zamkotsian@lam.fr

ABSTRACT

Computer Generated Holograms (CGHs) are powerful optical elements used in many fields, such as wavefront shaping, quality testing of complex optics and anti-counterfeiting devices. Lee algorithm is the most used to generate binary amplitude Fourier holograms. Grayscale CGHs are known to give a higher reconstruction quality than binary holograms, but they usually require a cumbersome production process. A very simple and straightforward method of manufacturing rewritable grayscale CGHs is here proposed by taking advantage of two key components: a Digital Micro-mirror Device (DMDs) and a photochromic plate. An innovative algorithm, named Island algorithm, able to generate grayscale amplitude Fourier CGHs, is reported and compared with the standard Lee approach, based on 9 levels. A crucial advantage lies on the fact that the increase or decrease of the quantification does not affect the spatial resolution. In other words, the new coding leads to a higher spatial resolution (for a given CGH size) and a reconstructed image with an order of magnitude higher contrast with respect to the classical Lee-coded hologram. In order to show the large potential of our approach, we have investigated the coding of a grayscale image with a 201 levels Island hologram: it shows a much better reconstruction (resolution, fidelity, contrast) thanks to the quantification of the transparency than the Lee algorithm commonly used. By combining 3 grayscale images with RGB filters and adding them, we show the reconstruction of a full color image with high fidelity, high contrast and low noise.

Key words: Computer Generated Hologram, CGH, Fourier coding, programmable CGH, photochromic material, optical testing, wavefront shaping, DMD.

1. INTRODUCTION

Wavefront shaping, complex optics testing, including aspherical and free-form optics or optical instrument alignment techniques will greatly benefit from Computer Generated Holograms (CGHs) [1]. They are classified in two groups:

- 1- phase holograms, which are obtained by recording a phase variation in a material having a modulated refractive index or thickness;
- 2- amplitude holograms, where an intensity pattern is recorded in a material whose transparency can be locally controlled. Phase and amplitude holograms provide the same performances in terms of image reconstruction quality, but different diffraction efficiency. For instance, binary phase holograms, show 40% diffraction efficiency in the first order, whereas efficiency is limited to 10% for binary amplitude holograms [2]. Therefore, amplitude holograms are usually applied in interferometry, which is not intensity limited.

Grayscale amplitude and grayscale phase holograms are known to give a higher reconstruction quality than binary holograms [2], but they require a more complex production process. Specifically, the production of phase grayscale CGHs is complex since a series of masks has to be consecutively aligned very precisely, and a developing step is required after each exposure step to obtain the final hologram.

To our best knowledge, only grayscale phase CGHs have been obtained so far by micro-lithography [3], the uniformity of the material thickness being the main limiting parameter for these components [4]. Concerning amplitude CGHs, they are nowadays produced in chrome on glass by means of lithographic techniques, either mask or maskless (by direct writing) lithography. Due to the binary nature of the chrome developing process, these techniques allow for easily writing binary CGHs, but they cannot provide grayscale CGHs.

We previously demonstrated an original recording technique, which makes use of a programmable mask and a non-threshold photosensitive material, to produce ready to use grayscale CGHs in a one exposure process without requiring any developing step [5,6]. Indeed, a set-up based on a Digital Micro-mirror Device (DMD), which has been originally developed to generate programmable slit masks in multi-object spectrographs [7], is considered. DMDs are programmable devices, composed of millions of micro-mirrors reconfigurable in real time. Actually, DMDs have been extensively used to generate dynamic binary or grayscale holograms [8], by exploiting the fast switching of the mirrors at frequencies higher than the human vision frame rate. The grayscale originates as a dynamic effect and not as a steady state effect. However, the discrete structure of the device induces a high scattering and background noise from the mirrors edges when illuminated with laser light [9], making such holograms useless for interferometry and metrology. Nevertheless, DMDs perfectly reproduce binary masks to be projected with incoherent light on photosensitive plates, thus producing amplitude CGHs. In this work, such plate consists in a photochromic film that can be reversibly converted from an opaque and colored form to a transparent form upon exposure with light of suitable wavelengths [10].

Actually, reversible holograms have been already obtained with photochromic materials [11, 12] and real-time photochromic holograms were shown, by exploiting the fast transition of imidazole dimers [13, 14]. Moreover, photochromic binary CGHs for optical testing have been recently demonstrated [15]. In photochromic materials, a ready to use hologram is generated just after the light exposure, and the reversibility of the photoconversion makes devices rewritable. Even more interesting, the transparency of a photochromic layer can be tuned by the dose of light absorbed, which opens to the development of grayscale patterns [16]. In fact, the DMD set-up allows for easily recording grayscale CGHs in a single exposure process. The lower diffraction efficiency of grayscale amplitude holograms with respect to binary amplitude holograms (6% vs. 10% [2]) is here compensated by a better image reconstruction quality, an easy exposure process and no developing steps, which are the limiting factors in the production of grayscale phase holograms.

Previously, we have successfully recorded the very first amplitude grayscale CGH, in equally spaced levels, so called *stepped CGH*. We recorded up to 1000x1000 pixels CGHs with a contrast greater than 50, using Fresnel coding scheme. Fresnel's CGH are obtained by calculating the inverse Fresnel transform of the original image at a given focus, ranging from 50cm to 2m. The reconstruction of the recorded images with a 632.8nm He-Ne laser beam leads to images with a high fidelity in shape, intensity, size and location. These results reveal the high potential of this method for generating programmable/rewritable grayscale CGHs, which combine DMDs and photochromic substrates. [5,17]

An innovative algorithm, named Island algorithm, able to generate grayscale amplitude Fourier CGHs, has also been reported and compared with the standard Lee approach, based on 9 levels. A crucial advantage lies on the fact that the increase or decrease of the quantification does not affect the spatial resolution. In other words, the new coding leads to a higher spatial resolution (for a given CGH size) and a reconstructed image with an order of magnitude higher contrast with respect to the classical Lee-coded hologram. In order to show the large potential of our approach, a 201 levels Island hologram is designed, produced and reconstructed, pushing the contrast to values higher than 10^4 . These results reveal the high potential of our process as well as our algorithm for generating programmable grayscale CGHs. [6]

In this paper, we report innovative results for Fourier holograms of grayscale objects using our new coding scheme. We show then the ability of this coding algorithm to generate a color image combining 3 grayscale images with Red-Green-Blue (RGB) filters. Realization process as well as writing and reconstruction set-ups are also discussed.

2. FOURIER CGH

Fourier holograms are obtained using algorithms encoding the inverse Fourier transform of the wavefront to be reproduced. These algorithms [18, 19, 20] are operating in a common way. Once the inverse Fourier transform is calculated, the complex information contained in each pixel is encoded in a cell of $W \times H$ pixels, W and H depending on the used algorithm. Lohmann, Lee and Burkhardt algorithms, all generate binary CGH with compactness and quantification of information at different levels. The Lee algorithm is the most widely used and will be considered as a reference for the current work. Only binary Fourier holograms have been produced using these algorithms. The number of pixels of a Fourier hologram is therefore necessarily larger than the number of pixels defining the image. This leads to limiting the resolution and size of images to be encoded. Since these holograms are based on the Fourier transform, it is

necessary to add a lens after the CGH in the reconstruction set-up, for applying the optical Fourier transform to the CGH, and display the image.

2.1 The Lee algorithm

The algorithm proposed by Lee is encoding the real and imaginary parts of the complex Fourier function (Fig. 1a) instead of the phase and amplitude [21]. The binary version of the algorithm, which is the only one developed up to now, foresees a 4x4 elements cell for each pixel and encodes the real and the imaginary part of the complex number in two times two columns (separating the positive and the negative values), leading to 9 quantification levels (8 discrete levels plus the zero position), as shown in the Fig. 1b.

Fig. 1: (a) Complex number to be encoded; (b) correspondent cell of the Lee algorithm; (c) example of a Lee hologram

The only way to increase the number of quantification levels is to increase the size of the cell, 8x8 elements cell for 33 levels, and 16x16 elements cell for 129 levels, increasing then the hologram size. An example of a Lee hologram is provided in Fig. 1c.

2.2 The Lee-compact algorithm

The grayscale approach proposed in this paper opens to new possibilities to increase the hologram information density and hence the reconstruction fidelity against binary holograms of the same size and resolution.

Our first newly proposed algorithm uses the grayscale approach to pop-up the columns of Lee cells, squeezing the information of a quadrant of the complex plane into a single element (Lee-Compact). As shown in Fig. 2b, the cell is composed by 2x2 elements, representing the positive and negative components of the real and imaginary parts of the complex function. Lee-compact algorithm gives better results than the binary Lee algorithm in terms of compactness and quantification levels, but shows small diffraction efficiency since two pixels are intrinsically black.

The number of discrete levels available with this algorithm is infinite, limited by the recording medium to display these levels. This is done without changing the size of the elementary cell.

An example of a Lee-compact hologram is provided in Fig. 2c.

Fig. 2: (a) Complex number to be encoded; (b) correspondent cell of the Lee-compact algorithm; (c) example of a Lee-compact hologram

2.3 The Island algorithm

In order to overcome the limitation due to the two intrinsically black pixels of the Lee-compact algorithm, we introduce a new coding scheme (named Island), where the cell is composed by 2x1 elements corresponding to the real and the imaginary parts of the complex number. An offset is added to obtain positive values only that can be transformed into transparency levels (Fig. 3b). However, we still keep coding the information in a 2x2 elements cell to avoid anamorphism in the reconstructed image.

The number of discrete levels available with this algorithm is also infinite, limited by the recording medium to display these levels. This is done without changing the size of the elementary cell. For example, let's consider a CGH with 129 quantification levels; a 256-elements pixel is required with the Lee-code, while the size of the pixel always relies on a 2x2 element cell with the Island code; this is therefore 64 times more compact than the Lee-code in the case of 129 quantification levels.

An example of an Island hologram is provided in Fig. 3c.

Fig. 3: (a) Complex number to be encoded; (b) correspondent cell of the Island algorithm; (c) example of an Island hologram

3. ISLAND CGH FOR GRAYSCALE IMAGES

Island coding for grayscale images exhibit a much better result with respect to the Lee algorithm. Comparison of simulated reconstructed images with Lee and Island coding is presented in this paragraph.

We chose as object a dunes image including the entire range of graylevels. In both cases, we kept constant the size of the hologram at 512 by 512 pixels. To be consistent, the size of the image to be reconstructed was set to 128 by 128 pixels for the Lee coding, and 256 by 256 pixels for the Island coding. Let's consider 3 cases:

- 1- Lee coding with 9 levels
- 2- Island coding with 9 levels
- 3- Island coding with 201 levels

In Fig. 4a and Fig. 4b are shown the Lee coding 9-levels original image and the simulated reconstructed image. The resulting image is noisy with a low dynamical range for the reconstructed grayscales due to the only 9-levels quantification of the hologram. The binary CGH as well as a detail are in Fig. 4c,d.

In Fig. 5a and Fig. 5b are shown the Island coding 9-levels original image and the simulated reconstructed image. The resulting image is closer to the original, but the dynamical range for the reconstructed grayscales is still limited. The grayscale CGH as well as a detail are in Fig. 5c,d. Note the average value at the mid-gray level for the Island hologram.

In Fig. 6a and Fig. 6b are shown the Island coding 201-levels original image and the simulated reconstructed image. The resulting image is nearly identical with the original, with a full dynamical range for the reconstructed grayscales, thanks to the high number of quantification levels. The contrast of the image is as well maximized. The grayscale CGH as well as a detail are in Fig. 6c,d. Note the average value at the mid-gray level for the Island hologram.

Fig. 4: Lee-coded 9 levels hologram; (a) Original image, (b) reconstructed image, (c) hologram, (d) detail of the hologram.

Fig. 5: Island-coded 9 levels hologram; (a) Original image, (b) reconstructed image, (c) hologram, (d) detail of the hologram.

Fig. 6: Island-coded 201 levels hologram; (a) Original image, (b) reconstructed image, (c) hologram, (d) detail of the hologram.

Simulation of grayscale images with our new Island coding scheme shows a much better reconstruction (resolution, fidelity, contrast) thanks to the quantification of the transparency than the Lee algorithm commonly used.

4. ISLAND CGH FOR COLOR IMAGES

By combining 3 grayscale images with RGB filters and adding them, we are able to generate a full color image. We chose as object a flower (an anemone) image including the entire range of colors. The size of the image is 416 x 312 pixels embedded in a frame of 1024x1024 pixels for a better balance between the frequency and the spatial domain, and the image is located off-axis the frame in order to place the reconstructed image as far as possible from the 0th order signal, increasing the SNR [6]. The hologram size with the Island coding is 2048x2048 pixels.

Let's consider 3 cases:

- 1- Island coding with 2 levels (binary)
- 2- Island coding with 9 levels
- 3- Island coding with 201 levels

In Fig. 7a are shown the 3 RGB original images and the corresponding color image. A detailed image of the center of one flower is also displayed.

In Fig. 7b are shown the Island coding 2-levels RGB simulated reconstructed images and the corresponding simulated reconstructed color image. A detailed image of the center of one flower is also displayed. The resulting image is noisy with a low dynamical range for the reconstructed grayscales due to the only 2-levels quantification of the hologram. The binary CGH (RED channel) as well as a detail are in Fig. 8a.

In Fig. 7c are shown the Island coding 9-levels RGB simulated reconstructed images and the corresponding simulated reconstructed color image. A detailed image of the center of one flower is also displayed. The resulting image is closer to the original, but the dynamical range for the reconstructed colors is still limited. The grayscale CGH (RED channel) as well as a detail are in Fig. 8b. Note the average value at the mid-gray level for the Island hologram.

In Fig. 7d are shown the Island coding 201-levels RGB simulated reconstructed images and the corresponding simulated reconstructed color image. A detailed image of the center of one flower is also displayed. The resulting image is nearly identical with the original, with a full dynamical range for the reconstructed colors, thanks to the high number of quantification levels. The contrast of the image is as well maximized. The grayscale CGH (RED channel) as well as a detail are in Fig. 8c. Note the average value at the mid-gray level for the Island hologram.

Fig. 7: Island-coded RGB simulated reconstructed images and the corresponding simulated reconstructed color image; (a) Original image, (b) 2-levels, (c) 9-levels, (d) 201-levels; A detailed image of the center of one flower is also displayed

Fig. 8: Island-coded RED channel simulated holograms: (a) 2-levels, (b) 9-levels, (c) 201-levels;
A detailed image of the CGH is also displayed

Simulation of a color image with our new Island coding scheme shows a nearly perfect reconstruction (resolution, fidelity, contrast) thanks to the quantification of the transparency than the Lee algorithm commonly used.

5. RECORDING AND RECONSTRUCTION SET-UPS

Two set-ups have been developed for the recording of the calculated CGH and for the reconstruction of the original encoded images.

5.1 Recording set-up

Figure 9 shows our recording set-up, dedicated to the CGH recording on the photosensitive plate. The DMD, controlled by the formatter board [22] is illuminated by a collimated beam from a white source, and redirects the light toward the plate. The beam is illuminating the entire DMD and the light power is homogeneous on the plate. The pattern reproduced by the DMD has to be projected onto the plate as precisely as possible, so the plate is illuminated through an Offner relay with a magnification of 1:1. This relay provides a nearly aberration free beam and has the advantage of being compact.

The unit magnification means that the maximum size of CGH is directly limited by the size of the DMD; the micro-mirrors of the DMD therefore correspond to the “pixels” of the CGH. Finally, a post-CGH imaging system located right after the CGH plate consists of two lenses, a filter around 600 nm and a CCD camera. This system in an afocal assembly allows imaging of the CGH during writing, in situ and in real time. Magnification is tuned by changing properly the pair of lenses, from a value of 1 up to 4.

DMD, CGH and camera planes are then conjugated. Note that DMD plane is a tilted focal plane due to the nature of micro-mirror array: each micro-mirrors tilts out of the array plane by 12° , leading to a global 24° tilted focal plane. This effect is reproduced as well at the post-CGH imaging camera level (the camera plane is tilted by 24°).

The CGH plate is mounted on motorized stages for X,Y and Z directions allowing the writing of holographic plates larger than the original 14mmx14mm FOV given by the DMD, by stitching part of the holograms or different contiguous holograms on the same larger plate; the maximum size is 30x30mm².

Fig. 9: Picture of the set-up dedicated to CGHs recording; it is based on an illumination unit towards the DMD, an imaging optical system based on a 1:1 magnification Offner relay from the DMD plane to the CGH plane, and a post-CGH imaging system.

5.1.1 Mask generator

Digital Micromirror Devices (DMD) from Texas Instruments could act as reconfigurable mask generator. The largest DMD chip developed by TI features 2048 x 1080 mirrors on a $13.68\mu\text{m}$ pitch, where each mirror can be independently switched between an ON ($+12^\circ$) position and an OFF (-12°) position (Fig. 10).

Fig. 10: DMD chip from Texas Instruments (2048 x 1080 micromirrors).

This component has been extensively studied in the framework of an ESA technical assessment of using this DMD component (2048 x 1080 mirrors) for space applications (for example in EUCLID mission). Specialized driving electronics and a cold temperature test set-up have been developed. Our tests reveal that the DMD remains fully operational at -40°C and in vacuum. A 1038 hours life test in space survey conditions (-40°C and vacuum) has been successfully completed. Total Ionizing Dose (TID) radiation tests, thermal cycling (over 500 cycles between room temperature and cold temperature, on a non-operating device) and vibration and shock tests have also been done; no degradation is observed from the optical measurements. **These results do not reveal any concerns regarding the ability of the DMD to meet environmental space requirements [22].**

5.1.2 DMD mask projection

A simple imaging Offner-type layout has been set up, based on two identical spherical concave mirrors and a convex mirror (Fig. 11). Indeed, spherical mirrors belong to the same mother mirror, sharing the same radius and center of curvature. One mirror only could be used instead of two separate ones, helping the alignment of the system. However, mechanical and operational constraints can lead to split these two mirrors. We have preferred two identical spherical mirrors with a diameter of 160mm and a radius of curvature of 438mm. The convex mirror has a 224mm radius of curvature. [23]

Fig. 11: Optical layout of the imaging set-up.

This optical layout will make the system simple and efficient. Additionally it will not suffer from chromatic aberrations. Delivered image quality onto the CGH plane is high enough to not degrade spatial resolution. Typical monochromatic spot diameters are $<20\mu\text{m}$ over the whole FOV for wavelengths between 400nm and 800nm.

5.2 Reconstruction set-up

The reconstruction set-up, shown in Fig. 12, is dedicated to CGH reconstruction.

Fig. 12: Picture of the set-up dedicated to image reconstruction, including a 632.8 nm He-Ne laser, the CGH plane and the camera located at the hologram projection distance (2m in this case) for Fresnel CGHs.

For Fourier holograms, an additional collimating lens is required.

The source is a collimated 632.8 nm He-Ne laser. The camera, placed at the distance z from the plate, is illuminated through the CGH. As described in the next section, the Fresnel holograms are directly calculated from the propagation equations of light, and they are for a given focus. It is thus not necessary to add a lens between the plate and the camera to reconstruct the image, unlike with the Fourier holograms. This is why the source should be rigorously collimated, because a variation in the quality of the collimation can displace the focal plane along the optical axis and change the size of the encoded image.

5.3 Photochromic plates

The photosensitive material is a diarylethene-based polyurethane [24]. Such kind of photochromic substrate contains a large content of photochromic units (i.e. 50% wt. in this work) that turns into a high contrast between the colored and uncolored forms, also for thin films. This layer can be reversibly converted from an opaque and colored form to a transparent form upon exposure with light of suitable wavelengths, around 600nm (Fig. 13). Moreover, the optical quality in terms of transparency and scattering is very good. The photochromic plate is $3\mu\text{m}$ thick and the film is set uniformly to the opaque state by a UV exposure. The conversion under light illumination of the photochromic film has been previously determined by a kinetic model that provides the degree of transparency as function of the film features and illumination conditions [16].

Figure 13: Transmission (Optical Density) of the photochromic material used in the UV-Visible range of the spectrum showing the opaque to the transparent states, according to the illumination amount of the plate

6. RECORDING AND RECONSTRUCTION OF A COLOR CGH

Recording and reconstruction strategies for the color images are dependent from the available photochromic materials. Two different strategies must be applied if the response curves of the Red, Green and Blue materials are spectrally fully separated or not.

In the first case (Fig. 14), each RGB hologram could be treated fully separately. By mixing the 3 materials, we can coat a single plate, and then illuminate sequentially the masks needed for R with a red source, for G with a green source and for B with a blue source, leading to 3 superimposed CGHs on the same plate. For the reconstruction we can light the color-image CGH with 3 LEDs and the color image is reconstructed.

In the second case (Fig. 15), there are overlaps between the transmission curves of the 3 materials, which is the most probable case. Then the strategy described above is not any more possible with a single layer mixing the 3 materials, because while writing an R, G or B hologram, another one is also affected. We propose in that case, to spatially locate each hologram in a different zone of the holographic plate and treat each of them independently, with for example the use of filters in front of each zone. For the reconstruction, the same concept could be used, with a white light source and filters on the R, G and B holograms.

Note that our recording set-up includes a CGH support with motorized stages allowing stitching of the zones on the CGH, leading to a larger hologram and/or locate holograms for the different colors at separated places on the same plate.

Figure 14: Color image recording and reconstruction strategy with spectrally separated photochromic materials

Figure 15: Color image recording and reconstruction strategy with spectrally non-separated photochromic materials

7. CONCLUSION

Computer generated holograms are well suited for optical testing and wavefront shaping. Up to now amplitude holograms have only been recorded in binary format, and our method increases their quality by enabling the realization of stepped holograms with discrete gray levels.

We have proposed a new Fourier CGH coding scheme, called Island algorithm, leading to a quantification exceeding 1000 within a smaller cell size of 2x2 pixels. The reconstruction of the recorded CGH leads to images with a perfect fidelity in shape, intensity and contrast, for any single pixel of the original object. Our proposed code exhibits a much higher resolution, a better compacity and an increased throughput, in comparison with the current Fourier CGHs. Grayscale objects have been simulated with our new coding scheme, and show a much better reconstruction (resolution, fidelity, contrast) than the Lee algorithm commonly used. By combining 3 grayscale images with RGB filters and adding them, we show the reconstruction of a full color image with high fidelity, high contrast and low noise. Recording and reconstruction strategies for the color images have been proposed using our DMD-based set-ups in order to generate the set of masks needed to record the grayscale CGHs.

These results reveal the high potential of this method for generating programmable/rewritable CGHs. The next step will be to code more complex holograms as well as wavefronts containing phase information. We will also use our method to create beam shapers including apodizers, using the same protocol as for stepped CGHs.

ACKNOWLEDGMENTS

This work has been partly funded by the European Union FP7-OPTICON 2 program.

REFERENCES

- [1] C. Pruss, S. Reichelt, H. J. Tiziani and W. Osten, "Computer-generated holograms in interferometric testing," *Opt. Eng.* **43** (11), 2534-2540 (2004)
- [2] Brown, B. R. and Lohmann, A. W., "Computer-generated Binary Holograms," *IBM J. Res. Dev.* (1969)
- [3] Y-T. Lu, C-S. Chu, H-Y. Lin, "Characterization of the gray-scale photolithography with high-resolution gray steps for precise fabrication of diffractive optics," *Opt. Eng.* **43**(11) 2666-2670 (2004)
- [4] N. Luo, Y. Gao, S. He, Y. Rao, "Research on exposure model for DMD-based digital gray-tone mask," *Proc SPIE Vol.* **7657**, 7657 12-1 (2010)
- [5] Romain Alata, Giorgio Pariani, Frederic Zamkotsian, Patrick Lanzoni, Andrea Bianco, Chiara Bertarelli, "Programmable CGH on photochromic plates coded with DMD generated masks", *Optics Express*, Vol. **25**, n° 6, (2017), <https://doi.org/10.1364/OE.25.006945>
- [6] Frederic Zamkotsian, Giorgio Pariani, Romain Alata, Luca Oggioni, Patrick Lanzoni, Chiara Bertarelli, Andrea Bianco, "The island CGH, a new coding scheme: concept and demonstration", *Optics Express*, Vol. 27, Issue 19, pp. 26446-26458, (2019) <https://doi.org/10.1364/OE.27.026446>
- [7] F. Zamkotsian, P. Spano, P. Lanzoni, H. Ramarijaona, M. Moschetti, M. Riva, et al., "BATMAN: a DMD-based Multi-Object Spectrograph on Galileo telescope," in *Proceedings of the SPIE conference on Astronomical Instrumentation 2014*, *Proc. SPIE* **9147**, Montréal, Canada, (June 2014)
- [8] R.S. Nesbitt, S.L. Smith, R.A. Molnar, S.A. Benton, "Holographic recording using a digital micromirror device," *Proc. SPIE* **3637**, Practical Holography XIII, 12 (March 25, 1999); doi:10.1117/12.343767
- [9] Park, M.-C., Lee, B.-R., Son, J.-Y., Chernyshov, O., "Properties of DMDs for holographic displays," *J. Mod. Opt.* **62**(19), 1600–1607 (2015)
- [10] C. Bertarelli, A. Bianco, R. Castagna and G. Pariani, "Photochromism into optics: Opportunities to develop light-triggered optical elements," *Journal of Photochemistry and Photobiology C: Photochemistry Reviews* **12**(2), 106-125 (2011) doi: 10.1016/j.jphotochemrev.2011.05.003
- [11] Nan Xie, Yi Chen, Baoli Yao, Ming Lie, "Photochromic diarylethene for reversible holographic recording," *Materials Science and Engineering: B*, **138**(3), 210-213 (2007)
- [12] Yi Chen, Congming Wang, Meigong Fan, Baoli Yao, Neimule Menke, "Photochromic fulgide for holographic recording," *Optical Materials*, **26**(1), 75-77 (2004)
- [13] Y. Kobayashi and J. Abe, "Real-Time Dynamic Hologram of a 3D Object with Fast Photochromic Molecules," *Adv. Opt. Mater.* **4**(9), 1354–1357 (2016)
- [14] N. Ishii, T. Kato, and J. Abe, "A real-time dynamic holographic material using a fast photochromic molecule" *Sci. Rep.* **2**, 819 (2012)
- [15] G. Pariani, C. Bertarelli, G. Dassa, A. Bianco, G. Zerbi, "Photochromic polyurethanes for rewritable CGHs in optical testing," *Optics Express* **5** (19), 4536-4541 (2011)
- [16] G. Pariani, A. Bianco, R. Castagna and C. Bertarelli, "Kinetics of photochromic conversion at the solid state: Quantum yield of dithienylethene-based films," *Journal of Physical Chemistry A* **115**(44), 12184-12193 (2011) doi: 10.1021/jp207210p
- [17] Romain Alata, Frédéric Zamkotsian, Patrick Lanzoni, Giorgio Pariani, Andrea Bianco, Chiara Bertarelli, "Programmable CGH on photochromic material using DMD generated masks", *Proc. SPIE* **10546**, (2018); <https://doi.org/10.1117/12.2292075>
- [18] A. W. Lohmann and S. Sinizinger, "Graphic codes for computer holography," *Appl. Opt.* **34**, 17 (1995)
- [19] C. B. Burckhardt, "A simplification of Lee's method of generating holograms by computers," *Appl. Opt.* **9**, 1949-1959 (1970)
- [20] C. K. Hsueh and A. A. Sawchuk, "Computer-generated double-phase holograms," *App. Pot.* **17**, 3874-3883 (1978)
- [21] G. Tricoles, "Computer generated holograms: an historical review," *Appl. Opt.* **26**, 4351–60 (1987)
- [22] F. Zamkotsian, P. Lanzoni, E. Grassi, R. Barette, C. Fabron, K. Tangen, L. Valenziano, L. Marchand, L. Duvet "Successful evaluation for space applications of the 2048x1080 DMD," in *Proceedings of the SPIE conference on MOEMS 2011*, *Proc. SPIE* **7932**, San Francisco, USA (2011)
- [23] Frederic Zamkotsian, Patrick Lanzoni, Nicolas Tchoubaklian, Harald Ramarijaona, Manuele Moschetti, Marco Riva, Marc Jaquet, Paolo Spano, William Bon, Mathieu Vachey, Luciano Nicastro, Emilio Molinari, Rosario Cosentino, Adriano Ghedina, Manuel Gonzalez, Walter Boschini, Paolo Di Marcantonio, Igor Coretti, Roberto Cirami, Filippo Zerbi, Luca Valenziano, "BATMAN @ TNG: Instrument integration and performance", in *Proceedings of the SPIE conference on Astronomical Instrumentation 2018*, *Proc. SPIE* **10702**, Austin, USA, (2018), <https://doi.org/10.1117/12.2315222>
- [24] G. Pariani, R. Castagna, G. Dassa, S. Hermes, C. Vailati, A. Bianco and C. Bertarelli, "Diarylethene-based photochromic polyurethanes for multistate optical memories," *Journal of Materials Chemistry* **21**(35), 13223-13231 (2011) doi: 10.1039/c1jm11870f