Measurement of Gravel-Bed Topography: Evaluation Study Applying Statistical Roughness Analysis

Stéphane Bertin, H Friedrich

► To cite this version:

Stéphane Bertin, H Friedrich. Measurement of Gravel-Bed Topography: Evaluation Study Applying Statistical Roughness Analysis. Journal of Hydraulic Engineering, 2014, 140, pp.269 - 279. 10.1061/(asce)hy.1943-7900.0000823 . hal-03470757

HAL Id: hal-03470757

<https://hal.science/hal-03470757>

Submitted on 21 Dec 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Measurement of gravel-bed topography: an evaluation study applying statistical roughness analysis

S. Bertin¹; H. Friedrich²

Abstract

In this two-part study, experiments are conducted to evaluate available topography measurement techniques for gravel-beds in a laboratory flume and to study their suitability for statistical roughness analysis. The available instruments for this study include, (i) an acoustic bed-profiler; (ii) a hand-held laser-scanner; and (iii) two digital consumer cameras forming a stereo-photogrammetric system, and are employed to obtain Digital Elevation Models (DEMs) of water-worked gravel-beds. In the first part of the study, the three measurement techniques are reviewed and their feasibilities for future grain-scale roughness work assessed, based on the obtained elevation datasets. Water-worked gravel-bed topographies are measured with all three available measurement techniques. The analysis of the DEMs concentrates on using Probability Distribution Functions (PDFs) and second-order structure functions of bed elevations. Roughness coefficients are determined and used as a benchmark for comparison of the three measurement techniques. Although, visually, differences in the DEMs obtained with different measurement techniques are observed, the results of the chosen statistical analysis do not disclose the visual differences to the same extent. It is shown that the used stereo-photogrammetric system, although theoretically allowing a fast and high-resolution recording process, lacks behind in accuracy. Thus, the second part of the study identifies and presents steps to improve the quality of the obtained stereo-photogrammetric DEMs. A checklist is

Page 1

¹PhD student, Department of Civil and Environmental Engineering,
The University of Auckland, Private Bag 92019, Auckland, New Zealand
corresponding author E-mail: sber081@aucklanduni.ac.nz

²Lecturer, Department of Civil and Environmental Engineering,
The University of Auckland, Private Bag 92019, Auckland, New Zealand
E-mail: h.friedrich@auckland.ac.nz

provided, highlighting the improvements made in the follow-up study, in order to obtain a high-quality stereo-photogrammetric DEM. The overview will be useful for other researchers to make use of available low-cost and high-quality consumer camera equipment, to set-up their own, non-proprietary stereo-photogrammetric system.

Subject headings: *Topography; Bed roughness; Distance measurement; Photogrammetry.*

INTRODUCTION

Roughness characterization

With recent research advances and technology improvement, statistical analysis of bed elevations in gravel-bed rivers has become crucial to define roughness parameters, quantify armoring effects, and hence to understand the nature of the river flow.

Traditionally, bed-scale roughness parameters used in bedload transport and flow resistance equations are described using percentiles of the Grain Size Distribution (GSD) of the sediment constituting the bed. The intermediate particle axis is chosen as the base value for GSD, despite it is recognized that the short axis is the one protruding into the flow, and is therefore responsible for the bulk of the resistance to the flow (de Jong 1995; Robert 1990).

An equivalent roughness parameter is commonly used, such as Nikuradse's k_s set to $3.5D_{84}$, where D_{84} is the length of the intermediate axis of the sediment particle in the GSD for which 84-% of the particles are smaller (Clifford et al. 1992). GSD characteristics can be determined with techniques such as sieve analysis, Wolman's (1954) or Fehr's (1987) line-by-number sampling procedures or similar methods, which require disturbance of the gravel-bed surface.

Detailed discussions and comparisons of those methods can be found in the work of Bunte

and Abt (2001). 2D image-based automated methods became more popular over the last years (Chang and Chung 2012; Detert and Weitbrecht 2012; Graham et al. 2010; Strom et al. 2010) and allow in-situ recording of GSD characteristics. However, overlapping and buried particles make the use of automated techniques, utilizing photographs, challenging.

The complex arrangements of the particles on the river-bed, such as varied orientations, packing and protrusions also highlight the limitations of using GSD characteristics as a parameter in bedload transport and flow resistance equations. Even the use of a full GSD is not sufficient to fully represent the surface morphology and its effect on the flow field (Nikora et al. 1998; Robert 1988; Robert 1990).

Alternatively, the river-bed surface can be considered as a random field of surface elevations $z(x, y, t)$, where z is the surface height at coordinates x and y at time t . Thus, the bed can be represented as a Digital Elevation Model (DEM). Recent research has shown that high-resolution DEMs, obtained using various topography measurement technologies, allowed the use of statistical tools such as Probability Distribution Functions (PDFs) and second-order 2D structure functions, to understand the structure of water-worked sand-dunes and gravel-beds and quantify roughness parameters (Aberle et al. 2010; Butler et al. 2001; Friedrich 2010; Goring et al. 1999; Nikora et al. 1998; Robert and Richards 1988). The hydraulic roughness can be described as a scale-dependent set of three coefficients, the longitudinal, the transversal and the vertical roughness, with the vertical roughness represented by the standard deviation of bed elevation (Aberle and Nikora 2006; Cooper and Tait 2009; Nikora et al. 1998; Smart et al. 2004). Appropriate measurement technologies are needed to obtain the random field of bed elevations, $z(x, y, t)$, and thus being able to define the various inherent scales of gravel-bed roughness. More attention has to be given to evaluate the measurement techniques that enable such detailed roughness characterization.

Topography measurement techniques

Mainly, three types of remote sensing techniques have been used over the years to obtain DEMs of gravel beds: bed-profilers, laser-scanners and stereo-photogrammetry. Coleman's (1997) laboratory experiments with an acoustic bed-profiler proved that this instrument can be successfully employed to measure submerged topography in a large range of situations. Water depths ranging from 5-mm to 1000-mm were employed, as well as various downstream and transverse sampling distances and adjustable acoustic frequency for different vertical accuracies. The acoustic bed-profiler comprises a sounding probe, which generates ultrasonic waves that reflect off the sediment bed and are received by the probe. The time of passage of sound waves is measured electronically and allows determining the distance of the sediment bed from the probe. Unlike infrared bed-profilers, as in Robert (1988), acoustic bed-profilers allow submerged topography measurement. Flowing water can be employed in some situations, and measurements are theoretically unaffected by suspended sediment of size of the order of the sound wavelength or smaller. Acoustic bed-profilers enable higher spatial resolution than the generally used 10-mm sampling distance with physical profilers (de Jong 1995; Nikora et al. 1998; Smart et al. 2004). However, regardless of the type of bed-profiler, a significant amount of time is required to obtain fine-scale DEMs over a larger area.

A very high horizontal resolution and vertical accuracy can be achieved by using time-of-flight Terrestrial Laser-Scanners (TLSs), also called ground-based LiDAR (light detection and ranging) systems. These scanners find the distance of an object by measuring the round-trip time of a pulse of laser light. Aberle and Nikora (2006), Cooper and Tait (2009) and Goring et al. (1999) conducted bed-elevation measurements in drained laboratory flumes using TLSs. Manufacturer specified vertical accuracies vary from 0.5- μm to 0.1-mm. Heritage and Hetherington (2007), Hodge et al. (2009) and Smart et al. (2004) conducted surveys with

94 TLSs over exposed gravel bars in natural streams. Laser-scanning is the most precise wide-
95 range topography measurement device at the moment. However, TLSs' data requires
96 significant post-processing in the form of filtering to remove systematic errors (Hodge et al.
97 2008). Also, despite the existence of a multitude of laser-scanners, the cost remains high.
98 There is another disadvantage, as some of the TLSs cannot be used for measuring submerged
99 topographies, because of an infrared light pulse absorbed by water (Hodge et al. 2008; Smart
100 et al. 2004).

101 Similarly to human vision, stereo-photogrammetry makes use of two overlapping 2D images
102 to obtain one depth image within the Common Field of View (CFoV) of the two images.
103 Nowadays, commercially available software packages, such as OrthoMAX from Erdas
104 Imagine®, allow high-resolution DEM recording with digital stereo-photogrammetry, from
105 either digital images or digitized film photographs. Those packages are often expensive and
106 limited for specific use. Using OrthoMAX, laboratory-based experiments were carried out by
107 Butler et al. (2001), Brasington and Smart (2003) and Chandler et al. (2001). DEMs of
108 exposed, simulated beds, were plotted onto an adjustable grid, with a sampling distance as
109 small as 1.5-mm. Using ground control points coordinates, Brasington and Smart (2003) and
110 Chandler et al. (2001) assessed surface precision, with standard errors in vertical
111 measurement of 2-mm and 1.1-mm, respectively. Stereo-photogrammetry has the advantage
112 to be relatively easy to set up in both laboratory and field environments, with very quick data
113 acquisition, yet it generally requires special calibration. Field-based applications were carried
114 out by Butler et al. (1998) and Carbonneau et al. (2003), to measure the topography of
115 exposed gravel bars. In addition, Butler et al. (2002) and Westaway et al. (2000; 2001),
116 proved that stereo-photogrammetry can handle through-water measurement, but a rigorous
117 strategy must be employed to assess the quality of the DEMs. Whilst stereo-photogrammetry
118 is to date certainly the most promising technique to remotely sense the dynamic behavior of

gravel-beds at the grain scale, the operational process to obtain DEMs is complex. This generally requires the development of a unique methodology to carefully assess the reliability of the measurements (Butler et al. 1998). Another disadvantage is oblique scanning from two different viewpoints, which causes shadowing behind protruding particles and results in erroneous data in those affected areas.

Objective

Often laboratories have access to one measurement technique for gravel-bed data acquisition. The study's objective is to compare bed-roughness data collected with the above described, most commonly used, three measurement methodologies, which were available for this project. The study is split in two parts, which build upon each other. Initially, a screeded bed was water-worked and once fully developed, the bed was measured with all three available measurement techniques, namely acoustic bed-profiler, laser scanner and stereo-photogrammetry. The water-worked data are used to study the suitability of the DEMs to undertake statistical analysis of the bed roughness and assess the differences in quantitative and qualitative roughness characteristics for the same roughness area, but different measurement methodology. The analysis focuses on the hydraulic roughness, represented by the standard deviation of bed elevations, and bed-elevation Probability Distribution Functions (PDFs) and second-order structure functions (semivariograms) of the DEMs. In order to compare the water-worked roughness characteristics, screeded bed topography, recorded with the acoustic bed-profiler, is assessed.

The second part of the study presents the methodological improvements that were made for the stereo-photogrammetric setup, and how those improvements affect the quality of recorded DEMs.

DATA COLLECTION

The experimental setup

Data collection was undertaken in the Fluid Mechanics Laboratory of The University of Auckland, using a 19-m long sediment-starved tilting flume, with 0.45-m width and 0.5-m depth. For the presented experiments, the slope of the flume bed was set to 0.45. Measurements were obtained on a vertically adjustable test section, located 10-m downstream of the flume inlet, comprising of a fixed bed with a 950-mm long and 450-mm wide recess. The recess was filled with graded, rounded and colored gravel (each class of sediment, except the smallest one was painted with a different color, using white, yellow, green, blue and red). The use of painted gravel particles was necessary for a parallel study on cluster formation and sediment tracking. The sediment had a median size of the intermediate particle axis $D_{50} = 7$ -mm, a minimum sediment size of 0.7-mm, a maximum gravel size of 50-mm and a geometric standard deviation of the grain distribution, calculated as $\sqrt{D_{84}/D_{16}}$, of 2.98. To enable topography measurement, the test section was equipped with a horizontal rack for the acoustic bed-profiler, as well as an overhead mounting bar for stereo-photogrammetry equipment, on which two cameras were mounted (Figure 1). The initial screeded bed was created by placing randomly mixed sediment into the base of the vertically adjustable survey area and the surface was flattened to a thickness of 100-mm, parallel to the flume bed. The topography of the initial manually screeded bed was measured with the acoustic bed-profiler. The gravel-bed was then water-worked and naturally armored over four hours, at a constant flow rate $Q = 66$ -L/s, monitored by a pre-calibrated pressure gauge. The water depth was kept constant at 200-mm, and adjusted using a sharp-edged weir at the downstream end of the flume. A steady uniform flow was maintained throughout the experiment with a Froude number $Fr = 0.58$.

The area used for direct comparison of the three measurement techniques was 0.35-m long and 0.3-m wide (Figure 2). As the laser-scanner could not be used directly at the flume, a metallic tray was submerged into the initially screeded mixture, completely covered by the sediment layer, allowing the careful transportation of the 0.35-m long and 0.3-m wide water-worked gravel-bed sample to the location, where the laser is housed. Whilst water-working, the upper sediment layer eroded downstream. The experiment was stopped just when the tray started to be exposed. Thereafter, the bed topography was measured with the acoustic bed-profiler. The flume was then drained to allow in-air stereo-photogrammetry measurement. Finally, the metallic tray was carefully uncovered and moved to the location of the laser-scanner, to undertake the laser-scanner data collection.

Fig. 1. Flume setup

Acoustic bed-profiler

Measurements of the submerged gravel-beds, at initial screeded and final water-worked stages, were undertaken with a reduced flow rate to avoid suspended sediment that could lead to erroneous data. The acoustic bed-profiler is comprised of a sounding probe, located 100-mm above the sediment bed, mounted on a rack above the flume, traversing the measurement

section in flow direction, and an optical potentiometer of 256 increments per revolution, attached to the hub of a 200-mm diameter wheel, tracking the probe location in the downstream direction. With a sound wave of frequency $f = 2\text{-MHz}$ it provided a theoretical vertical accuracy of 0.37-mm (see Table 1). 2D longitudinal bed-elevation profiles were acquired and subsequently DEMs were obtained with a sampling distance of 2.45-mm downstream (based on the number of increments on the potentiometer and wheel size) and 2.54-mm transverse (0.1-inch on the scale utilized), representing the physical grid over which the measurements were done.

Fig. 2. Gravel bed and measurement window

Laser-scanner

The topography of the final water-worked bed, restricted to the area bounded by the edges of the metallic tray, was measured with an Inition MVT CLS60 hand-held laser-scanner, available in The University of Auckland Automated Systems Laboratory. Because of the short arm of the laser, it could not be used directly above the flume and required the transportation of the gravel-bed sample. Once transported, the sample was scanned vertically from a distance of 100-mm by making several overlapping stripes. The theoretical vertical accuracy is quantified as 0.05-mm (manufacturer specified), and data is recorded on a non-uniform spatial

grid. The merging of the overlapping stripes was operated automatically by the instrument's software, with the process repeated until successful merging was obtained. The laser-scanner has the advantage that both depth and color information are recorded, although color information was not used for this study. Finally, data was saved as an ASCII file and was directly read into MATLAB®. The non-uniform data cloud was transformed to a uniform grid with 1.45-mm sampling distance (Table 1). Measurements took place in non-submerged conditions. However, preliminary tests showed that wet conditions, e.g. with wet particle surfaces, have no detrimental effect on the laser's accuracy (see Table 2).

Stereo-photogrammetry

Stereo-photogrammetric measurements of the exposed water-worked bed were carried out with two Nikon D90 digital consumer cameras, with an 18-mm lens and a 5.5- μ m pixel pitch (12.3-megapixels). The two cameras were attached on a frame 1-m above the flume, mechanically aligned with a 280-mm baseline between the cameras, using a mounting bar. The settings for both cameras were manually adjusted to be identical (shutter speed of 1/3-s, F/22 aperture, ISO 200) and manually focused on the gravel-bed. The Common Field of View (CFoV) of the two cameras, chosen to be larger than the test section, defined the area over which depth information was extracted. Initially, stereo images of the calibration checkerboard were taken in various positions inside the hydraulic flume, covering all degrees of freedom and most of the cameras' CFoV (Zhang 1998). Using MATLAB® and Bouguet and Perona's (1998) camera calibration toolbox, the intrinsic parameters of the two cameras (focal length, principal point, skew among others), and the extrinsic parameters of the stereo setup (translation and rotation between the two cameras) were determined. Radial and tangential lens distortion of the two cameras was modeled using a 6th order polynomial. The calibration data enabled the photographs of the gravel-bed to be rectified to epipolar

geometry, where corresponding points between the left and right images are on the same scan lines, after distortion is removed. From the rectified images of the gravel-bed and the calculated disparity search range, the Symmetric Dynamic Programming Stereo-photogrammetry (SDPS) algorithm allowed getting a map of the bed surface elevations, also called disparity map, within the CFoV (Gimel'farb 2002). A point cloud is extracted, with sampling distance between measured data points representing the pixel size on the gravel-bed images as taken with the Nikon D90s from a distance of 1-m. Finally, the data were transferred to a uniform grid with a sampling distance of 1-mm (Table 1). The best vertical accuracy achievable by the setup in these conditions was calculated as 1-mm.

Improved stereo-photogrammetric setup

The results obtained with stereo-photogrammetry in the first part of the study were not satisfactory, as shown in the 'Results' section. Thus, work was done to obtain better DEMs using photogrammetric means.

The following improvements were made, which can be used as a checklist to obtain high-quality DEMs. Firstly, the measurement section needs to be illuminated as evenly and as best as possible. In addition to placing light sources strategically, any reflection bouncing off the measured object can negatively influence the measurement process. Thus, as a first step, the light sources outside the flume were changed from initially four flood lights to two 1-m long neon lights, which were placed behind a dissipative sheet, resulting in a homogeneous illumination of the measurement area. Secondly, the painted gravels were replaced by natural gravel particles, eliminating any reflection bouncing off the gravel-bed. The third change was to resize the CFoV, by reducing the distance from the cameras to the gravel bed. This change is not responsible in its own for the reduction of streaks and noise in the DEMs, but it led to an enhanced vertical accuracy of 0.34-mm (see Table 1). In addition, the measurement

resolution increased to approximately 30.8-million points/m², equivalent to 0.18-mm pixel size on the gravel-bed surface. Fourthly, a modified checkerboard was used. The checkerboard used previously was made of plastic, and was a cause of light reflection. It did not always allow correct corner recognition during the calibration process leading to inaccurate calibration parameters. Finally, the frame mounting bar holding the cameras was adjusted to allow a faster and more accurate calibration process. The cameras' mounting bar could be rotated at 90°, allowing photographs of the checkerboard to be taken with the checkerboard mounted on a tripod outside the flume.

A simple MATLAB® program was developed to evaluate the accuracy of the calibration step, based on the reprojection error. Using the calibration results (summarized in the projection matrices of the two cameras), the estimated corners of the checkerboard, originally in 3D world coordinates, can be reprojected onto the 2D calibration images. The estimated corners are compared with the actual corners detected with the subpixel corner detection algorithm available with MATLAB®. The reprojection error, in pixel, is defined as the difference between the actual corners and the estimated corners. A decrease in reprojection error shows that the calibration parameters (both intrinsic and extrinsic) are better estimated. In the absence of an external assessment of DEMs quality, an internal assessment of the calibration step was undertaken to contrast two DEMs obtained with stereo-photogrammetry.

Data post-processing

The same data post-processing procedure was applied to all DEMs obtained in the first part of the study. The DEM obtained with the improved stereo-photogrammetric setup (Figure 5), forming the second part of the study, was of high quality, with no spikes observed and the following data post-processing procedure was not needed. Data post-processing consisted of removing measurement spikes and interpolating gaps. Spikes, which were outside the

minimum/ maximum bed elevations, as found with the acoustic bed-profiler $\text{DEM} \pm 2\text{-mm}$, were removed. Minor spikes, due to measurement imprecision and noise, were automatically detected as data points lying outside their four neighbors' elevation, allowing for a $\pm 3\text{-mm}$ threshold. The threshold of 3-mm is specific to the used sediment mixture and was obtained through manual testing. The gaps generated by the removal of spikes were automatically filled by the average elevation of the four neighboring data points.

Before analyzing the DEMs statistically, a detrending algorithm was applied on each DEM. Surface detrending aims to remove larger scale trends than the grain-scale, such as bed slopes, which could obscure DEMs properties and bias grain roughness statistics. This also removes any deviation of the measurement instruments from a parallel positioning to the sediment bed. In accordance with Andreas and Trevino (1997), and Goring et al. (1999), a second-order biquadratic removing filter was applied, as this reduced the variance of the original data series the most. The difference in variance between the original and the detrended signals was significant, and exceeded the square of the measurement resolutions. Finally, all DEMs were normalized to have a mean bed elevation equal to zero, and rotated in order to align the DEMs with the flow direction.

STATISTICAL ROUGHNESS ANALYSIS

Statistical roughness analysis serves as the basis for the comparison of the employed measurement techniques and whether the obtained DEMs (Figure 4) warrant to be used for future studies on gravel-bed roughness characterization. Initially, Probability Distribution Functions (PDFs) were obtained, representing the distribution of surface elevations. Parameters like skewness, kurtosis and standard deviation of surface elevations were extracted from the detrended surfaces. Similar to previous work by Aberle and Nikora (2006),

Cooper and Tait (2009) and Nikora et al. (1998), the vertical roughness height was estimated using the standard deviation of the bed elevation σ_z .

In addition, generalized second-order 2D structure functions were used, defined by Nikora et al. (1998) in discrete form as:

$$D_{G2}(\Delta x, \Delta y) = \frac{1}{(N-n)(M-m)} \sum_{i=0}^{N-n} \sum_{j=0}^{M-m} \{ |z(x_i + n\delta x, y_j + m\delta y) - z(x_i, y_j)| \}^2 \quad (1)$$

where, $\Delta x = n\delta x$ and $\Delta y = m\delta y$; δx and δy are sampling intervals in the longitudinal and transverse directions respectively; $n=1,2,3,\dots,N$ and $m=1,2,3,\dots,M$. N and M are the number of samples in the same two directions. The relationship in Eq.1 is used to represent the generalized 1D second-order structure functions, as well as isopleth maps (contour plots) of the 2D structure functions. To enable a direct comparison between the various measurement techniques, the structure functions were normalized with the ‘saturation level’ $2\sigma_z^2$ and the contours of D_{G2} were plotted as proportions of the saturation level.

The irregular nature of gravel-bed profiles suits the use of generalized structure functions to investigate the fractal properties of the bed surface, which provides information about the inherent scales of roughness present on the gravel-bed surface. A structure function has three regions: a scaling region with uniform slope at small lags, a saturation region at large lags, where the slope is zero, with a transition region in between, where the slope decreases (Butler et al. 2001; Goring et al. 1999; Nikora et al. 1998; Robert and Richards 1988).

At small spatial lags, the scaling region can be fitted by a power function of the form $D(\Delta x) \propto \Delta x^{2H_x}$ (Figure 7a) and $D(\Delta y) \propto \Delta y^{2H_y}$ (Figure 7b). Butler et al. (2001) and Robert (1988) showed that when plotted in log-log scale, the use of a power function allows the determination of the directional Hurst exponents H_x and H_y , representing a basic method to

estimate the fractal dimension of series of data along the downstream and transverse directions, respectively. They also showed that the directional fractal dimensions of series of points, also called Hausdorff dimensions, can be estimated from the slopes of the linear parts of the structure function, using the relation $2 - H$ and can be linked to different roughness scales.

RESULTS

Digital Elevation Models (DEMs)

Both, the initial screeded and final water-worked beds, were measured with the acoustic bed-profiler over the complete recess section (Figure 3). The manually screeded bed (Figure 3a) is composed of grains of different sizes with buried bigger particles. The surface is flat and uniform, with bed elevations between -12.3-mm and 7.2-mm, and sediment randomly distributed. In contrast, the water-worked bed (Figure 3b) presents a heterogeneous surface, with a larger range of bed elevations, of -24.4-mm to 29.7-mm. The surface, composed of coarse grains, with small particles filling the holes between them, presents the evidence of armoring. In Figure 3b, the edges of the metallic tray are clearly visible, defining the region over which the statistical analyses were conducted.

The DEMs of the water-worked bed vary notably (Figure 4). With the acoustic bed-profiler, the surface appears smooth with little noise (Figure 4a). Any visible errors are concentrated on the particles' edges, where major elevation changes occur rapidly. The laser-scanner's DEMs (Figure 4b) are similar to those obtained with the acoustic bed-profiler. Although, theoretically, the higher resolution of the laser scanner should enable the edges of the particles to be more representative, this is not observed, due to measurement noise. The DEM obtained with stereo-photogrammetry (Figure 4c) is of least quality, despite the highest resolution. Not

all of the major gravel particles are well captured. Detailed inspections also show major noise, even after despiking, thus prompting us to investigate the cause of the noise further, which resulted in the methodological changes made on the photogrammetric setup presented in section ‘Improved stereo-photogrammetric setup’. The changes led to a decreased reprojection error. The obtained DEM presented in Figure 5 used calibration results with a standard deviation in reprojection error of 0.2-pixels, compared to the reprojection error for the DEM of Figure 4c with a standard deviation of 1.15-pixels. The measurement noise is correctly suppressed by an improved photogrammetric process, and all particles on the gravel-bed surface are correctly represented. Consequently, the decreased reprojection error results in a visually appealing DEM (Figure 5), plotted on a very fine grid, with 0.2-mm sampling distance.

Fig. 3. Detrended DEMs obtained with the acoustic bed profiler in submerged conditions, after despiking, for (a) the initial screeded bed; (b) the final water-worked bed

Probability Distribution Functions (PDFs)

PDFs were generated to allow a statistical comparison of texture parameters for the various measurement techniques, such as skewness, kurtosis, range of elevations, and the vertical roughness length. In addition, it is a useful tool for comparing initial screeded and final water-worked beds and studying the influence of armoring.

Fig. 4. Detrended DEMs of the water-worked bed, after despiking, focused on the region within the metallic tray, obtained with (a) the acoustic bed profiler; (b) the laser scanner (dry condition); (c) stereophotogrammetry

Fig. 5. DEM of a water-worked bed obtained with the improved stereophotogrammetric setup

In accordance with previous studies, e.g. Aberle and Nikora (2006) and Cooper and Tait (2009), the initial screeded bed is negatively skewed (Figure 6a), whereas the water-worked beds are positively skewed (Figures 6b-c-d), for all three measurement techniques. The PDFs of Figure 6 also visualize the augmentation of geometrical roughness during the armor layer development, i.e. the augmentation of particles of higher elevations with respect to the mean bed level, which protrude into the flow. A larger range of bed elevations is observed for a water-worked bed (Figures 6b-c-d), compared with the narrower range for a screeded bed (Figure 6a). As Table 2 shows, after water-working the initially screeded gravel-bed, the skewness coefficient and the standard deviation of the bed elevation, σ_z , increase, and characterize the coarsening of the gravel-bed surface. No significant change in the kurtosis value was observed.

Fig. 6. PDFs obtained with (a) the acoustic bed profiler over the screeded bed, and over the restricted water-worked bed with (b) the acoustic bed profiler; (c) the laser scanner (dry condition); (d) stereophotogrammetry

For laser-scanner DEMs, similar statistics for the dry and wet surfaces are obtained, indicating a good reproducibility of the results. Although, statistically, the DEM obtained with the initial stereo-photogrammetric setup, results in a reduced skewness and roughness length, the statistics do not vary to the extent, as the visible DEM shortcomings would suggest. The statistics of the DEM obtained with the improved stereo-photogrammetric setup, as obtained in the second part of the study, are not presented, as the studied water-worked gravel-bed is different. Figures 6b-c-d show that the range of bed elevations is similar for all three DEMs, but the distribution of bed elevations in the different ranges varies. The DEM obtained with the acoustic bed-profiler presents the lowest sorting in bed elevations, with the smallest fraction of bed elevations around the zero mean-bed level. Noise present in the DEMs obtained with the laser-scanner and the initial stereo-photogrammetric setup causes more particles to be distributed around the zero-mean and less particles at low and high elevations.

Second-order structure functions

Previous research showed that the value of the Hurst exponent is inversely proportional to the degree of complexity of the gravel-bed surface (Aberle and Nikora 2006; Cooper and Tait 2009; Nikora et al. 1998). For our study, the screeded bed has a smaller Hurst exponent than the water-worked bed, which suggests that the screeded bed surface, with numerous smaller bed elevations, is more complex than the water-worked bed, which comprises a larger range of bed elevations (Figure 7). This correlates well with previous experiments of Aberle and Nikora (2006), where Hurst exponents of the man-made screeded beds are smaller than those of water-worked beds, with Hurst exponents increasing with increasing discharge.

The scaling region of the structure function provides information about the horizontal roughness indices, which can be determined from the slope breakpoint, located at the intersection between the tangent to the scaling region slope and the saturation level

asymptote, in both x and y direction. The horizontal roughness indices (Δx_0 and Δy_0) are larger for water-worked beds, than for screeded beds (Figure 7). The sediment particles on the bed surface coarsen during water-work.

Fig. 7. Generalized second-order structure functions plot in a log-log scale, for (a) $\Delta y = 0$; (b) $\Delta x = 0$

As presented by Aberle and Nikora (2006) and Friedrich (2010), the use of isopleth maps of 2D structure functions provides useful information on the surface forming mechanisms during

the armor layer development. Contour lines at small spatial lags are circular for the screeded bed (Figure 8a), indicating isotropy of the surface structure and a random organization, whereas the contour lines of all water-worked beds are characterized at small spatial lags by an elliptical shape (Figure 8b-c-d). This finding agrees with previous work by Aberle and Nikora (2006), Cooper and Tait (2009) and Goring et al. (1999). Geometrically, the elliptical shape of the contour lines reflects the general elliptical form of the dominant particles and an anisotropic surface structure of the bed. In this study, particles rotate to align their long axis across the flow direction (Figure 8b-c-d), as observed also by Goring et al. (1999).

Fig. 8. Contour lines of structure functions obtained with (a) the acoustic bed profiler over the screeded bed, and over the restricted water-worked bed with (b) the acoustic bed profiler; (c) the laser scanner (dry condition); (d) stereophotogrammetry

DISCUSSION

The three measurement technologies employed in this study, theoretically allow grain-scale elevation measurements of water-worked beds in a laboratory flume. In their work, Lane et al. (1994) estimated that between 4,000 and 10,000-points/m² (equivalent to 10-mm to 16-mm sampling distance) are necessary to survey the morphology of a braided proglacial stream at the grain scale. In the first part of our laboratory study, utilizing sediment with $D_{50} = 7$ -mm, DEMs with resolutions between 160,000 and 1,000,000-points/m² (equivalent to 1-mm to 2.54-mm sampling distance) were obtained. For the 0.35-m long and 0.3-m wide measurement window, this equates to approximately 16,870 data points for DEMs obtained with the acoustic bed-profiler. DEMs with around 49,940 and 105,000 data points were obtained for the laser-scanner and initial stereo-photogrammetric setup, respectively. Our statistical analysis showed that the measurement resolution is not the only key parameter when comparing the quality of the DEMs. The initial stereo-photogrammetric setup had the highest measurement resolution, with statistics showing only a minor deviation from the other DEMs, but visual observation of the DEM showed substantial shortcomings (Figure 4c). Problems were encountered with the reflection of the painted gravel particles, causing inaccuracies in creating the map of the bed surface elevations, and thus resulting in spikes in the DEM. Compared to the other two measurement techniques, stereo-photogrammetry requires a multi-stage recording process (calibration of cameras, creating depth map, extracting point cloud), with errors of various stages accumulating. Calibration inaccuracies for the initial stereo-photogrammetric DEM (Figure 4c), prevented the correct rectification of the gravel-bed stereo pairs to epipolar geometry. With stereo-photogrammetry, the recording time was the quickest of all techniques once the cameras were calibrated, which required 30-minutes (to obtain photographs of the checkerboard and extract the calibration parameters in MATLAB®). Calibration results could then be utilized to rectify all images of the gravel-bed

acquired with the same setup, i.e. when no changes were made on the cameras parameters or the setup geometry.

The laser-scanner is theoretically the most accurate measurement instrument for this study, with a theoretical vertical accuracy of 0.05-mm. Laser scanning enabled a fast survey of the measurement window. However, the size of the latter was restricted by the laser arm. It also required the transportation of the gravel sample to the location of the laser, and required merging of scanned areas, as it was not able to scan the whole measurement window in one scan. Spikes were encountered during the merging process, which had to be removed automatically, but measurement noise remained, reducing the quality of the final DEM.

Finally, the acoustic bed-profiler measured the bed elevation with a theoretical vertical accuracy of 0.37-mm. It was the most straightforward measurement equipment to use and was the only technique in our study that enabled measurement of the submerged gravel-bed. During water-working, sediment of sizes larger than 2-mm were transported in suspension, thus requiring to halt the experiment during measurements, to ensure no suspended sediment particles were picked up by the recording. The recording time was the longest of the three studied techniques, which can be a significant drawback when successive DEMs have to be obtained of evolving processes.

Visually, DEMs obtained with the acoustic bed-profiler and the laser-scanner seemed well suited for statistical roughness analysis, whereas the DEM obtained with the initial stereo-photogrammetric setup showed an obvious lack of topographical accuracy. Following the visual study of the DEMs, the DEMs underwent statistical roughness analysis. The vertical roughness length, as expressed with the standard deviation of bed elevations σ_z , is similar for all DEMs (see Table 2). It was found $\sigma_z = 5.36 \pm 0.4$. As observed visually, the grains' edges were not represented accurately in the DEM obtained with the acoustic bed-profiler,

resulting in flatter gravel tops and thus overestimate the standard deviation of bed elevation. The laser-scanner allowed a good reproducibility of the results when tested over a dry and wet gravel-bed surface, as seen in Table 2.

Statistical results of the PDFs and generalized second-order structure functions, as presented in Figures 6, 7 and 8, show a good agreement for the various DEMs. This indicates that although visible differences in the topography of the DEMs were observed, those measurement differences are less identifiable when DEMs are described statistically.

Our evaluation study highlights that a detailed visual validation of the DEMs is crucial for gravel-bed studies, as significantly different DEMs of the same topography can produce similar roughness statistics. Quantitative validation of DEMs quality can only be made through comparison of obtained bed elevations with a ground truth, which is often practically not feasible, as in our presented study. In our study, the laser-scanner was theoretically the most accurate instrument, but noise in the DEM prevented using the laser-scanner data as a ground truth. Other studies evaluate the error rate of one measurement technique by comparing several records with each other, like it was done in studies employing stereo-photogrammetry (Butler et al. 1998; Carbonneau et al. 2003; Chandler et al. 2001).

The obtained initial stereo-photogrammetric DEM was of inferior quality (Figure 4c) and prompted additional testing to obtain high-quality DEMs, as the literature research showed that low-cost stereo-photogrammetric measurements of gravel-bed topographies will be useful for future studies. In previous hydraulic applications of stereo-photogrammetry, semi-metric cameras were used (Butler et al. 1998; Butler et al. 2001; Butler et al. 2002), in addition to commercial photogrammetric software (Brasington and Smart 2003; Butler et al. 1998; Carbonneau et al. 2003; Chandler et al. 2001; Rapp et al. 2012; Westaway et al. 2001). The calibration technique relied on automatic block-bundle adjustment, or self-calibration

technique. Targets were required, generally a large number, to be arranged on the surface to survey. The 3D locations of the targets are determined with Leica total stations, making for the duplicity of measurement instruments in the experiments and increasing the chance of errors propagating. In addition, targets glued on the riverbed surface disturb the experiment and are not complementary with an otherwise remotely sensed topography.

In our low-cost stereo-photogrammetric setup, we decide to use Zhang calibration technique (Zhang 1998), which requires a planar calibration pattern (called checkerboard) to be photographed in several positions. Although it requires additional time to obtain these images, this calibration technique avoids using ground control points disposed on the riverbed. It is also considered that Zhang calibration will be more suitable for field work, where the areal coverage is larger than inside laboratory flumes, which would mean that more targets are required, compared to a laboratory study. Using ground control points, measured with total stations, has however the advantage that it provides information to assess externally the DEM's quality. With our proposed low-cost stereo-photogrammetric setup, a simple MATLAB® program was prepared to evaluate the accuracy of the calibration step, which was identified as a source of error for the DEMs. The evaluation is based on the reprojection error. Following the checklist provided in section 'Improved stereo-photogrammetric setup' results in a decreased reprojection error, which in turn enables a high-quality DEM to be obtained (Figure 5).

Besides exhibiting the best accuracy qualitatively, the DEM obtained with the improved stereo-photogrammetric setup has a sampling distance of 0.2-mm on the gravel-bed surface, which corresponds to the highest DEM resolution so far obtained for gravel-bed studies, compared to the previous minimum of 1-mm obtained by Cooper and Tait (2009) with TLS and by Carbonneau et al. (2003) with stereo-photogrammetry.

CONCLUSION

A laboratory study to evaluate available measurement techniques to study the hydraulic roughness for gravel beds is presented. The use of an acoustic bed-profiler, a hand-held laser-scanner and stereo-photogrammetry allowed acquisition of DEMs. Analysis techniques, such as determination of the vertical roughness heights, PDFs and generalized second-order structure functions, are used to study the random field of bed elevations, as represented by the DEMs. The advantages and disadvantages of the three measurement techniques in use are discussed, as well as their suitability for obtaining DEMs for statistical roughness analysis.

The results show that all three measurement techniques used for this study are capable of recording DEMs with sampling distances small enough to examine an evolving gravel-bed at the grain scale in laboratory conditions, using a sediment mixture with $D_{50} = 7\text{-mm}$. Statistical analysis resulted in describing vertical as well as horizontal roughness characteristics. Although, visually, differences in the DEMs obtained with different measurement techniques are observed, the results of the chosen statistical analysis do not disclose the visual differences to the same extent.

The accuracy of the DEM obtained with stereo-photogrammetry in the first part of this study is inferior to the DEMs obtained with the other techniques, which did not agree with what is theoretically achievable with a stereo-photogrammetric system. We thus presented changes made in the setup, resulting in the highest gravel-bed DEM resolution obtained with stereo-photogrammetry, 25-million points/m². The result warrants further research into setting up non-proprietary stereo-photogrammetric systems for sediment transport studies. Work is needed to prepare a gravel-bed ground truth to quantitatively validate the DEM's accuracy obtained with the non-proprietary stereo-photogrammetric system. The next step is to employ

and validate the system underwater, and obtain DEMs to study the dynamic behavior of gravel-beds at the grain-scale.

ACKNOWLEDGEMENTS

Photogrammetric application was conducted in collaboration with the Department of Computer Science, The University of Auckland. We would like to thank in particular Patrice Delmas, Alfonso Gastelum Strozzi and Edwin Chan for their valuable input in obtaining the stereo-photogrammetric data. Laser scanning was undertaken with the help of the Department of Mechanical Engineering, The University of Auckland. We would like to thank Katherine Heays, who introduced the first author to the lab environment. The Fluid Mechanics Laboratory technicians Geoff Kirby and Jim Luo helped in conducting the experiments.

REFERENCES

- Aberle, J., and Nikora, V. (2006). "Statistical properties of armored gravel bed surfaces." *Water Resour. Res.*, 42, W11414.
- Aberle, J., Nikora, V., Henning, M., Ettmer, B., and Hentschel, B. (2010). "Statistical characterization of bed roughness due to bed forms: A field study in the Elbe River at Aken, Germany." *Water Resour. Res.*, 46, W03521.
- Andreas, E. L., and Trevino, G. (1997). "Using wavelets to detect trends." *J. Atmos. Ocean. Tech.*, 14(3), 554-564.
- Bouguet, J.-Y., and Perona, P. (1998). "Camera calibration from points and lines in dual-space geometry." *Technical report*, California Institute of Technology, 1-16.
- Brasington, J., and Smart, R. M. A. (2003). "Close range digital photogrammetric analysis of experimental drainage basin evolution." *Earth Surf. Proc. Land.*, 28(3), 231-247.
- Bunte, K., and Abt, S. R. (2001). "Sampling surface and subsurface particle-size distributions In wadable gravel- and cobble-bed streams for analyses in sediment transport, hydraulics, and streambed monitoring." *Gen. Tech. Rep. RMRS-GTR-74*, U.S. Dept. of

570 Agriculture, Forest Service, Rocky Mountain Research Station, Fort Collins, CO, 1-
571 428.

572 Butler, J. B., Lane, S. N., and Chandler, J. H. (1998). "Assessment of DEM quality for
573 characterizing surface roughness using close range digital photogrammetry."
574 *Photogramm. Rec.*, 16(92), 271-291.

575 Butler, J. B., Lane, S. N., and Chandler, J. H. (2001). "Characterization of the structure of
576 river-bed gravels using two-dimensional fractal analysis." *Math. Geol.*, 33(3), 301-
577 330.

578 Butler, J. B., Lane, S. N., Chandler, J. H., and Porfiri, E. (2002). "Through-water close range
579 digital photogrammetry in flume and field environments." *Photogramm. Rec.*, 17(99),
580 419-439.

581 Carbonneau, P. E., Lane, S. N., and Bergeron, N. E. (2003). "Cost-effective non-metric close-
582 range digital photogrammetry and its application to a study of coarse gravel river
583 beds." *Int. J. Remote Sens.*, 24(14), 2837–2854.

584 Chandler, J., Shiono, K., Rameshwaran, P., and Lane, S. (2001). "Measuring flume surfaces
585 for hydraulics research using a Kodak DCS460." *Photogramm. Rec.*, 17(97), 39-61.

586 Chang, F. J., and Chung, C. H. (2012). "Estimation of riverbed grain-size distribution using
587 image-processing techniques." *J. Hydrol.*, 440-441, 102-112.

588 Clifford, N., Robert, A., and Richards, K. (1992). "Estimation of flow resistance in gravel-
589 bedded rivers a physical explanation of the multiplier of roughness length." *Earth*
590 *Surf. Proc. Land.*, 17(2), 111-126.

591 Coleman, S. E. (1997). "Ultrasonic measurement of sediment bed profiles." *Proc.*, 27th
592 *Congress of the International Association for Hydraulic Research*, San Francisco,
593 California, USA, 221-226.

594 Cooper, J. R., and Tait, S. J. (2009). "Water-worked gravel beds in laboratory flumes - a
595 natural analogue?" *Earth Surf. Proc. Land.*, 34(3), 384-397.

596 de Jong, C. (1995). "Temporal and spatial interactions between river bed roughness,
597 geometry, bedload transport and flow hydraulics in mountain streams - examples from
598 Squaw Creek (Montana, USA) and Lainbach/Schmiedlaine (Upper Bavaria,
599 Germany)." Ph.D. thesis, Free University of Berlin, Berlin.

600 Detert, M., and Weitbrecht, V. (2012). "Automatic object detection to analyze the geometry
601 of gravel grains." *Proc., River Flow 2012*, Taylor and Francis Group, San Jose, Costa
602 Rica, 6.

603 Fehr, R. (1987). "Geschiebeanalysen in Gebirgsflüssen; Umrechnung und Vergleich von
604 verschiedenen Analyseverfahren." *Mitteilung Nr. 92 der Versuchsanstalt für*
605 *Wasserbau, Hydrologie und Glaziologie, Eidgenössischen Technischen Hochschule*
606 *Zürich.*

607 Friedrich, H. (2010). "Evaluation of statistical analysis techniques for developing bedforms
608 recorded in 3D." Ph.D. thesis, The University of Auckland, Auckland.

609 Gimel'farb, G. (2002). "Probabilistic regularisation and symmetry in binocular dynamic
610 programming stereo." *Pattern Recogn. Lett.*, 23(4), 431-442.

611 Goring, D. G., Nikora, V. I., and McEwan, I. K. (1999). "Analysis of the texture of gravel-
612 beds using 2-D structure functions." *Proc., I.A.H.R. Symposium on River, Coastal and*
613 *Estuarine Morphodynamics*, Genova, Italy, 111-120.

614 Graham, D. J., Rollet, A. J., Piégay, H., and Rice, S. P. (2010). "Maximizing the accuracy of
615 image-based surface sediment sampling techniques." *Water Resour. Res.*, 46(2), 15.

616 Heritage, G., and Hetherington, D. (2007). "Towards a protocol for laser scanning in fluvial
617 geomorphology." *Earth Surf. Proc. Land.*, 32(1), 66-74.

618 Hodge, R., Brasington, J., and Richards, K. (2008). "In situ characterization of grain-scale
619 fluvial morphology using Terrestrial Laser Scanning." *Earth Surf. Proc. Land.*, 34(7),
620 954-968.

621 Hodge, R., Brasington, J., and Richards, K. (2009). "Analysing laser scanned digital terrain
622 models of gravel bed surfaces: linking morphology to sediment transport processes
623 and hydraulics." *Sedimentology*, 56(7), 2024-2043.

624 Lane, S. N., Richards, K. S., and Chandler, J. H. (1994). "Developments in monitoring and
625 modelling small-scale river bed topography." *Earth Surf. Proc. Land.*, 19(4), 349-368.

626 Nikora, V. I., Goring, D. G., and Biggs, B. J. F. (1998). "On gravel-bed roughness
627 characterization." *Water Resour. Res.*, 34(3), 517-527.

628 Rapp, C., Eder, K., and Stilla, U. (2012). "3D determination of the evolution of a scour hole
629 by photogrammetric means." *Proc., River Flow 2012*, Taylor & Francis Group, San
630 Jose, Costa Rica, 943-950.

631 Robert, A. (1988). "Statistical properties of sediment bed profiles in alluvial channels." *Math.*
632 *Geol.*, 20(3), 205-225.

633 Robert, A. (1990). "Boundary roughness in coarse-grained channels." *Prog. Phys. Geog.*,
634 14(1), 42-70.

- Robert, A., and Richards, K. S. (1988). "On the modelling of sand bedforms using the semivariogram." *Earth Surf. Proc. Land.*, 13(5), 459-473.
- Smart, G., Aberle, J., Duncan, M., and Walsh, J. (2004). "Measurement and analysis of alluvial bed roughness." *J. Hydraul. Res.*, 42(3), 227-237.
- Strom, K. B., Kuhns, R. D., and Lucas, H. J. (2010). "Comparison of automated image-based grain sizing to standard pebble-count methods." *J. Hydraul. Eng.*, 136(8), 461-473.
- Westaway, R. M., Lane, S. N., and Hicks, D. M. (2000). "The development of an automated correction procedure for digital photogrammetry for the study of wide, shallow, gravel-bed rivers." *Earth Surf. Proc. Land.*, 25(2), 209-226.
- Westaway, R. M., Lane, S. N., and Hicks, D. M. (2001). "Remote sensing of clear-water, shallow, gravel-bed rivers using digital photogrammetry." *Photogramm. Eng. Rem. S.*, 67(11), 1271-1281.
- Wolman, M. G. (1954). "A Method of Sampling Coarse River-Bed Material." *Transactions, American Geophysical Union*, 35(6).
- Zhang, Z. (1998). "A Flexible New Technique for Camera Calibration." *IEEE T. Pattern Anal.*, 22(11), 1330-1334.

653

Table 1 Summary of the measurement specifications.

<div>Measurement technique</div> <div>Measurement specifications</div>	Acoustic bed-profiler	Laser-scanner	Stereo-photogrammetric setup (first part)	Improved stereo-photogrammetric setup (second part)
[Downstream x transverse] DEM sampling distance (mm)	2.45 x 2.54	1.45 x 1.45	1 x 1	0.2 x 0.2
Theoretical vertical accuracy (mm)	0.37	0.05	1	0.34

654

655

656

657

658

659

660

661

662

663

664

Table 2 Texture coefficients extracted from bed elevation PDFs and structure functions.

<i>Bed condition</i>	Screeded bed	Water-worked bed			
<i>Measurement technique</i>	Acoustic bed-profiler	Acoustic bed-profiler	Laser-Scanner		Stereo-Photogrammetry
<i>Bed condition</i> <i>Texture coefficients</i>	Submerged	Submerged	Dry surface	Wet surface	Dry surface
Skewness (-)	-0.5	0.81	0.79	0.86	0.5
Kurtosis (-)	4.57	3.8	4.07	4.26	3.58
σ_z (mm)	1.33	5.76	5.32	5.32	5.0
Δx_0 (mm)	6	7.2	9.7	10.1	6.9
Δy_0 (mm)	6.8	8.5	8	8.1	9

665