1 **Assessing intra-bar variations in grain roughness using close-range photogrammetry**

2 **Jane Groom** (jgro800@aucklanduni.ac.nz),

3 **Stéphane Bertin** (s.bertin@ymail.com) and

4 **Heide Friedrich** (h.friedrich@auckland.ac.nz)

5 Department of Civil and Environmental Engineering, University of Auckland, New Zealand.

6

7 **ABSTRACT**

8 Evidence of downstream fining in sediment size along the length of a gravel bar has
9 frequently been observed. However, there is limited quantitative information on the variation
10 of other roughness statistics. Developments in high-resolution topographic data acquisition
11 provide the opportunity for assessing roughness variations along and across a gravel bar,
12 to quantify existing theoretical observations of bar sorting. Here, close-range
13 photogrammetry is used for the first time to assess intra-bar variations in roughness, at 14
14 different locations on a single gravel bar in the Whakatiwai River, New Zealand. An
15 extensive range of roughness parameters are used, including the standard deviation of
16 elevations, skewness, kurtosis, inclination index, and horizontal roughness lengths from
17 second-order structure functions. A reduction with distance down bar was found in all
18 roughness parameters, except skewness, along with a decrease in the variability of the data
19 at the bar tail for all parameters. Lateral variation in roughness parameters was also
20 assessed, showing evidence of an increase in roughness parameters with distance from the
21 water edge. These findings can be used to validate and calibrate existing flow resistance
22 equations and morphodynamic models. General trends in roughness statistics indicate
23 coarser sediment at the bar head and near the river bank. These trends reflect the formative
24 flows and are used to infer sedimentation patterns, which suggest that the gravel bar

undergoes development through lateral accretion. Although complexities in the sedimentation patterns are evident, due to multiple cycles of erosion and deposition, a greater understanding of these patterns is needed for the implementation of successful river management for this river, and others.

Keywords

Grain-roughness; gravel bar; fluvial morphology, close-range photogrammetry, DEM

INTRODUCTION

Fluvial systems demonstrate reach-scale patterns in sedimentation, including downstream fining (i.e., a reduction in grain size) (Sternberg 1875). Although there is less published research on intra-bar variability, variations in sediment characteristics (e.g., size, sorting and packing) across gravel bars contribute to bar morphology and, in turn, channel morphology (Ashworth and Ferguson 1986; Hardy 2006; Rice and Church 2010). The formation of bars occurs from spatial variations in sedimentation, including, but not limited to, lateral accretion and sediment accumulation due to flow convergence, which can result in down bar fining of sediment (Leopold and Wolman 1957; Parker 1975; Nanson 1980; Bluck 1982; Leopold 1992; Ashworth 1996; Bluck 1976; Bridge 2003; Burge 2006). Due to feedbacks between channel morphology, sedimentation and flow properties, the presence of gravel bars can alter flow properties and roughness at different scales, including reach, bar, and grain scale (Church and Jones 1982; Ashworth 1996; Bridge 2003; Church 2006; Raven et al. 2009; Bertoldi et al. 2009).

Roughness, resulting from these sedimentation patterns, is an important aspect within a fluvial system due to its influence on flow properties (including velocity and turbulence), sediment transport, and local ecology (Aberle and Nikora 2006; Hodge et al. 2009a; Baewert et al. 2014; Curran and Waters 2014). Estimations of roughness are important inputs for

49 hydraulic and morphological models, along with models to determine the flow resistance
50 within a channel (Aberle and Smart 2003; Tuijnder and Ribberink 2012).

51 Flow resistance results from forces that act on, and within, a flow to resist motion (Powell
52 2014), with various sources of energy loss in alluvial rivers. To calculate the flow's energy
53 loss, hydraulic parameters such as velocity, depth, slope and boundary shear stress must
54 be predicted or calculated. Generally, there are three flow resistance equations that are
55 used in fluvial research; Darcy-Weisbach, Chezy and Manning equations, which all use
56 roughness coefficients. The determination of these roughness coefficients is crucial for the
57 calculation of flow resistance. However, determining the values of the coefficients is fraught
58 with subjectivity, and thus they are often the main source of error in estimates of discharge
59 and flow resistance (Powell 2014). Choosing the correct equation in flow modelling can be
60 problematic, as an increasing number of modelling software programs calculate flow
61 resistance automatically, without clarifying how it is calculated (Powell 2014). For example,
62 flow modelling packages still use Manning's n as a roughness coefficient, although it has
63 been identified as having many flaws, and there have been calls to move to a more robust
64 alternative roughness coefficient (e.g., quantitative roughness parameters such as the
65 standard deviation of elevations) (Ferguson, 2010; Powell 2014).

66 Roughness is a term that is frequently used in literature, but is rarely explicitly defined, which
67 causes confusion (Smith 2014). Roughness is often used as a synonym for flow resistance,
68 which suggests that roughness is a property of the flow rather than of a surface. Instead,
69 we define grain roughness throughout this manuscript as the microtopography of the
70 surface, resulting from the topography of individual grains; therefore roughness is a property
71 of the surface, with a pronounced effect on flow resistance.

72 Our understanding of bed roughness (i.e., microtopography of the surface) is facilitated by
73 the development of technologies for the acquisition of high-resolution data. This includes (i)

74 aerial photosieving (Carbonneau et al. 2004), which although it can cover a large spatial
75 scale, has been found to overestimate grain size; (ii) laser scanning (Milan et al. 2007;
76 Entwistle and Fuller 2009; Heritage and Milan 2009; Brasington et al. 2012), which is
77 expensive and time consuming; and (iii) structure-from-motion on unmanned aerial systems,
78 which enables for the spatial variability of roughness to be assessed and inputted into
79 morphodynamic models, although noise from reconstructions of up to 10 mm and blurry
80 images are problematic (Vazquez-Tarrio et al. 2017). The technique of close-range
81 photogrammetry (Bertin and Friedrich 2016) uses consumer grade cameras (i.e.,
82 inexpensive), which can provide millimeter accuracy to address these aforementioned
83 issues.

84 An increase in availability of large topographic datasets from these methods has led to an
85 expansion in the literature of information about the grain size of the surface, which is used
86 for calculating bed shear stress and estimating sediment transport (Pearson et al. 2017).
87 Further, these large topographic datasets have resulted in the improved quantification of
88 grain-roughness parameters. This includes bed-elevation moments from digital elevation
89 models (DEMs), such as standard deviation of elevations, skewness, and kurtosis. These
90 improvements signal a shift away from the previous use of roughness coefficients,
91 percentiles of grain size or roughness heights calibrated from flow measurements (Wilcock
92 1996; Smart et al. 2004; Aberle and Nikora 2006).

93 The aim of this paper is to obtain an improved understanding of bar-scale variations in grain-
94 roughness parameters. There is little information regarding the grain-scale variations of
95 surface structure and roughness within gravel surfaces (Bertin and Friedrich 2016). This is
96 despite knowing that these aspects are key influences on flow resistance, sediment
97 transport, and ecohydraulics (Aberle and Nikora 2006; Baewert et al. 2014; Curran and
98 Waters 2014). This paper has three objectives:

- 99 1. To assess grain-roughness variability across the gravel bar, using an extensive range of
100 roughness parameters; although bar-scale sorting is well documented (Rice and Church
101 2010), there is little quantification of this observation. Further, surface roughness of bars is
102 rarely uniformly distributed and its heterogeneity is of great interest (Smith, 2014).
- 103 2. To examine roughness parameters and grain size relationships, as research has
104 investigated the relationship between grain size and the standard deviation of elevations (a
105 common proxy for grain size). The influence of multiple factors including survey error, bed
106 composition (e.g., packing, particle shape, sorting) and scale of roughness has been
107 explored (Pearson et al. 2017), but further work is needed to understand and quantify these
108 factors.
- 109 3. To understand if empirical roughness parameterization can lead to inferences concerning
110 sedimentation patterns, which can provide insights into the physical processes that influence
111 surface morphology (Hodge et al. 2009).

112 **METHODOLOGY**

113 Data collection

114 Data were obtained from the Whakatiwai River; a small gravel-bed stream in the Whakatiwai
115 catchment (~ 1675 ha), which is located in north east North Island, New Zealand (Fig. 1).

116 The stream has limited protection or management schemes (Hauraki Council 2011), apart
117 from stopbanks (levees) upstream and downstream of the gravel bar studied in this
118 investigation. Previously, cyclone Wilma (January 28-29th 2011) resulted in the stream
119 undergoing significant lateral erosion in the stopbanked reaches, with calls from the
120 community for management practices to be put in place. Surrounding areas of the stream
121 mouth have high significance to the local iwi (Māori people), with urupa (burial ground) and
122 waahi tapu (sacred spiritual areas), and thus the local community is concerned with their

123 protection. Recent channel protection works include the insertion of gabion baskets,
124 although these are thought to be of limited effect due to channel movement (Hauraki Council
125 2011).

126 Our field observations at the time of data collection include bank erosion and evidence of
127 animal activity on exposed gravel bars upstream of the study site, due to the surrounding
128 farmland. This study focuses on an exposed gravel bar, located 300 meters upstream from
129 the stream mouth. This gravel bar was chosen due to ease of accessibility with equipment
130 from the road, and because previous field investigations using close-range photogrammetry
131 were also undertaken at this site (Bertin and Friedrich 2016). Upstream areas of the bar
132 were vegetated with clusters of dense pampas grass, and there was a change in elevation
133 towards the water edge, with a slope vegetated by grass. The gravel bar selected for this
134 investigation did not display signs of animal activity or disturbance and was opposite a rock
135 revetment structure (Figs. 1C, 2A, 2B). The bar is not surrounded by accessible farmland,
136 but instead is attached to a densely vegetated bank (Fig. 2). Google Earth images provide
137 an indication to the evolution of this gravel bar over time, with the apparent propagation of
138 the bar downstream (Fig. 2).

139 A 30 meter tape measure was placed along the bar, and care was taken to only walk along
140 this transect in order to not destroy natural sedimentation patterns, and measurement
141 locations were placed either side of the transect, on non-disturbed areas. Measurement
142 locations (Fig. 3), termed patches herein, were partially systematically chosen, covering
143 down bar and lateral patterns, although they were not evenly spaced (due to the deliberate
144 attempt to avoid vegetated areas). Distances between patches were measured with a tape
145 measure in the field, and later verified using a scaled orthophoto of the bar (Fig. 3). The
146 orthophoto of the bar was taken using GoPro cameras at a height of 2 meters above the
147 gravel surface. Subsequently, for analysis, the gravel bar was split into three sections every
148 10 meters down the bar, differentiating between bar head, bar center and bar tail regions

(Fig. 3), similar to the method using in Rice and Church (2010) whom evaluated grain size variability by choosing sites that were representative of dominant textural facies.

At each patch, surface structure and grain size were measured using close-range digital photogrammetry (Fig. 1). Here, two Nikon D5100 cameras with Nikkor 20 mm lenses in tandem (16.4 Mpixel, 23.6 x 15.6 mm² sensor size), were used to take photos of the gravel surface. The cameras were calibrated in the laboratory prior to accessing the field (see analytical methods). Then the camera rig (horizontal metal frame) was kept in a wooden transportation box in order to reduce any movement in the camera set up during travel to the field. This has been found to have minimal disturbance to the (pre-calibrated) cameras and provide adequate results for high-quality DEMs with vertical accuracies, determined with a 3D-printed gravel bed and represented by the mean unsigned error between measurements and true values, of less than 1 mm (Bertin and Friedrich 2016). Once in the field, the camera rig was gently put on top of two tripods, placed ~1 m apart, and screwed securely in place. The cameras were at an approximate height of 75 cm from the gravel surface, as determined from a setup selection in the laboratory. Finally, two laptops were attached by cables to each camera, in order to remotely capture the photographs of the surface. Further details into the field-use of close-range photogrammetry are found in Bertin and Friedrich (2016).

A repeat calibration was completed in the field, as transporting the stereo setup is critical, and this provided the opportunity to determine the suitability of field calibration. Evaluation of the maximum field rectification error provided lower values of 0.47 pixel, compared to 0.88 for the pre-calibrated laboratory calibration. Thereby the decision was made to use the field calibration for analysis, motivated by the smaller rectification error.

Analytical methods

173 Surface grain size (Table I) was subsequently obtained through the software Basegrain®,
174 whereby a single photograph is used to generate a grain-size distribution for the patch
175 (Detert and Weitbrecht 2012; Stähly et al. 2017). The minimum grain size sampled is a
176 function of the pixel size on the gravel, with previous work indicating the need for a least 23
177 pixels for effective grain identification (Graham et al. 2010). With an approximate pixel size
178 of 0.19 mm, this means that grains larger than 4.5 mm were directly accounted for using
179 Basegrain®. As recommended by previous authors, measured grain-size distributions were
180 empirically corrected, with an assumption of 10% fine sediment not accounted for during
181 detection for all patches (as per Ruther et al. 2013). Characteristic grain sizes of the bed-
182 surface material were determined for all patches examined (Table I). The median grain size
183 of the bed-surface material (d_{50}) varies between 15 mm and 25.3 mm, and the coarsest
184 fraction of sediment (d_{90}) ranges between 32.2 mm and 64.4 mm (Table I).

185 Calibration parameters necessary for accurate DEMs with photogrammetry were obtained
186 using images of a chequerboard and Bouquet's (2010) calibration toolbox in Matlab®, which
187 provide both intrinsic (e.g., camera) and extrinsic (e.g., setup) parameters. Based on
188 calibration data, obtained images of the gravel patches were rectified (maximum error < 1
189 pixel), through which corresponding pixels in the two overlapping images are on the same
190 scanline (i.e., same vertical coordinate). Stereo-matching was completed on the rectified
191 images using Gimel'farb's (2002) symmetric dynamic programming stereo algorithm (SDPS)
192 to produce point clouds of elevation data. Point clouds were first interpolated onto regular
193 grids of 0.2 mm spacing, before being interpolated onto a 1 mm spacing grid (i.e. a raster
194 DEM), resulting in less bias when calculating surface metrics in comparison to using non-
195 uniform elevation data (Hodge et al. 2009). Using the mean elevation difference parameter
196 (Hodge et al. 2009b), outliers were identified and replaced using bi-cubic spline interpolation.
197 DEMs were normalized to a mean bed level of zero, and subsequently rotated to align with
198 the flow direction (Hodge et al. 2009). Flow direction was determined by eye in the field,

199 based on channel observations and grain imbrication (Laronne and Carson 1976; Millane et
 200 al. 2006; Bertin and Friedrich 2016). The majority of each patch was vegetation free, and
 201 several overlapping DEMs were merged in order to generate patch sizes of > 1 m in length.
 202 However, in the case of some patches (e.g., bar head site P03, and bar center sites P06
 203 and P07), the presence of vegetation was removed from the patch, resulting in a smaller
 204 DEM, labelled with the letter A. For P03, two DEMs were made, on either side of the
 205 vegetation, and labelled A and B. For these patches, where vegetation was present, the
 206 smaller DEMs were used for analysis.

207 Before surface metric calculation, DEMs were all detrended, first using a bi-linear method
 208 and subsequently using a moving-window method. Bi-linear detrending removes the
 209 influence of riverbed slope or experimental setup misalignments (Bertin and Friedrich,
 210 2016). Moving-window detrending removes large-scale surface distortions larger than the
 211 cluster size for that patch, such as peaks and troughs resulting from bed undulations. As
 212 proposed in Smart et al. (2002), the trend surface corresponding to bed undulations was
 213 estimated over a grid with point spacing $1.25 \times d_{90}$, with the elevation of grid points measured
 214 by averaging DEM data points within a circle of diameter $2.5 \times d_{90}$ centered on the grid point,
 215 and removed from the measured DEMs before analysis. Using a moving-window detrending
 216 method enables the grain topography to be solely considered due to the removal of
 217 bedforms, thereby subsequent roughness parameters determined from DEMs are
 218 representative of grain-scale roughness (i.e., the microtopography of the surface). Analysis
 219 of grain-scale roughness is further suitable due to the size of the patches investigated, as
 220 research has suggested larger patch sizes may be required for thorough analysis of larger
 221 scale bed undulations (Powell et al. 2016).

222 Surface metrics were calculated for each patch to assess variations in surface structure
 223 across the gravel bar. First, standard deviation (σ_z) and skewness (S_k) of bed elevations
 224 were determined from probability distribution functions (Equ. 1) to characterize bed

roughness (Aberle and Nikora 2006). These metrics were chosen to provide an indication of the vertical roughness length (σ_z) and water -working (S_k) (Aberle and Smart 2003; Noss and Lorke 2016; Aberle and Nikora 2006; Coleman et al. 2011). Skewness is a measure of the degree of asymmetry of the probability distribution function. Positive values are indicative of a water-worked, and armored, surface (Coleman et al. 2011; Bertin and Friedrich 2014) because of coarse grains that form the surface, and the fact that the magnitude of surface deviations below the mean is reduced by fine grains filling surface depressions (Nikora et al. 1998; Aberle and Nikora 2006).

$$\sigma_z^2 = \frac{1}{N'} \sum_{i=1}^{N'} (z_i - \langle z_i \rangle)^2 \quad [1]$$

$$S_k = \frac{1}{N' \sigma_z^3} \sum_{i=1}^{N'} (z_i - \langle z_i \rangle)^3$$

where, z represents the bed elevation at location (x,y) in a DEM, N' is the total number of DEM points and $\langle \rangle$ represents the mean value.

Secondly, the inclination index (I_0) in the flow direction was calculated using Equ. 2. Here, the difference between the fraction of positive and negative slopes of particles, is divided by the total number of positive, negative, and zero inclinations at a given lag (of 1 mm), which is equal to the DEM resolution. A positive slope was counted as bed elevations increasing downstream. A threshold value of ± 0.01 was set, so unreliable near-zero slopes were not calculated in the numerator of Equ. 2 (Millane et al. 2006). Particle imbrication can be inferred from positive inclination index values, which indicates a predominance of positive slopes of the grains in the flow direction, reflecting the influence of downstream flow on the bed surface (Laronne and Carson 1976; Millane et al. 2006).

$$I_0 = \frac{n_+ - n_-}{N_s} \quad [2]$$

247 where, n_+ and n_- are the number of positive and negative slopes between successive DEM
 248 points, respectively, and N_s is the total number of slope measurements.

249 The slope and aspect of individual cells of the DEMs (Equ. 3) were analyzed, using a moving
 250 window to calculate the elevations of surrounding cells, in order to provide information on
 251 sediment textures, including any preferential grain imbrication and aspect orientation; this is
 252 possible because the DEM cell size is smaller than the grain size (Hodge et al. 2009). Due
 253 to the alignment of DEMs in the flow direction, those cells with 90° aspects indicate sloping
 254 grains facing downstream and an aspect of 270° indicates sloping grains orientated
 255 upstream. Further details of the calculation of these metrics are provided in the references
 256 cited.

$$257 \quad S = \arctan \sqrt{\left(\frac{dz}{dx}\right)^2 + \left(\frac{dz}{dy}\right)^2}$$

$$258 \quad A = \arctan \left(\frac{dz}{dx} / \frac{dz}{dy} \right) \quad [3]$$

259 where $\frac{dz}{dx}$ and $\frac{dz}{dy}$ are the gradients in the center cell, determined from the elevations of
 260 eight perimeter cells in both the x and y direction.

261 Finally, second-order structure functions (2DSF) were calculated (Equ. 4) to evaluate
 262 changes in elevation correlations at differing lags and directions, which can provide an
 263 indication to surface-forming mechanisms (Nikora et al. 1998; Aberle and Nikora 2006).
 264 Gravel-bed structure functions can be separated into three regions: a scaling region with a
 265 uniform slope at small lags, a saturation region at large lags with a slope of zero, and a
 266 transition region between the two where the slope decreases (Nikora et al. 1998; Hodge et
 267 al. 2009). Small values are indicative of areas of similar elevation, and hence the same grain
 268 (as data is detrended to remove the influence of bedforms), and once values are saturated

they indicate that elevations are no longer correlated. Second-order structure functions are displayed in 2D isopleth maps, which allow for the identification of the length and spatial arrangement of surface layer features (Bertin et al. 2017), and horizontal roughness lengths can be calculated in both the streamwise and cross-stream directions (L_x and L_y). Horizontal roughness lengths L_x and L_y are calculated from the breakpoint in the slope between the scaling region and the saturation region of the 1D structure functions for $\Delta x = 0$ and $\Delta y = 0$, respectively.

$$D_{G2}(\Delta x, \Delta y) = \frac{1}{(N-n)(M-m)} \sum_{i=0}^{N-n} \sum_{j=0}^{M-m} \left\{ z(x_i + n\delta x, y_j + m\delta y) - z(x_i, y_j) \right\}^2 \quad [4]$$

where, $\Delta x = n\delta x$ and $\Delta y = m\delta y$; δx and δy are the sampling intervals (i.e. DEM resolution) in the longitudinal and transverse directions respectively; $n=1,2,3,\dots,N$ and $m=1,2,3,\dots,M$. N and M are the number of DEM points in the same two directions.

RESULTS

Roughness parameters were calculated with both distance down bar and distance from the water edge (Fig. 4), in order to assess down bar and lateral variability in surface structure and grain size.

Whereas there is no simple correlation of roughness parameters with distance down bar and from the water edge (i.e., low R^2 values and significant scatter in the data), there are patterns of a reduction in surface sediment size (both d_{50} and d_{90} fractions of the surface) with distance down bar, compared to an increase with distance from the water edge. There is more scatter in data for d_{90} values due to the wider range in sediment size measured across the patches (as seen in Table I, where values vary from 32 mm to 65 mm). Following the pattern observed in sediment size, the standard deviation of elevations (σ_z) decreases with distance down bar and increases with distance from water edge. These patterns can

292 be seen qualitatively across patch surfaces, in particular a visible reduction in grain size at
 293 the downstream and water edge patches (Fig. 5).

294 In contrast to these patterns, skewness increases with both distance down bar and distance
 295 from the water edge. The majority of patches have positive skewness values, aside from
 296 P02 (bar head), which has a negative skewness ($S_k = -0.0971$).

297 For both the inclination index and horizontal roughness lengths, the pattern follows that of
 298 sediment size and standard deviation of elevations, whereby each roughness parameter
 299 decreases down bar and increases with distance from the water edge. Therefore,
 300 consistencies in patterns of the roughness parameters are evident (Fig. 4), aside from
 301 skewness, which differs from the other roughness parameters.

302 Although there are these patterns in roughness parameters with distance down bar and from
 303 the water edge (Fig. 4), there is significant scatter in the data, largely due to the complex
 304 topography of the gravel surface. This scatter, and with low Pearson's coefficients of
 305 determination (R^2) for the relations, is indicative of spatial variability in roughness statistics
 306 at the bar scale and reflects complex sedimentation patterns at this scale. The coefficients
 307 of determination for those roughness parameters for distance from the water edge are higher
 308 compared to those for distance down bar. This suggests a more robust relationship between
 309 distance and roughness statistics in a lateral direction, which has important implications for
 310 field data collection since such patterns are rarely explored.

311 Further results (Fig. 6) confirm a decrease in the median value of roughness parameters
 312 towards the bar tail for all parameters (e.g., sediment size, σ_z , inclination index and horizontal
 313 roughness lengths), except skewness, which displays an increase with distance down bar.
 314 There are also consistent decreases in the spread of data (variance in roughness statistics)
 315 towards the bar tail.

316 At the downstream end of the bar, median σ_z is 30% lower than the bar head values,
 317 consistent with fine grain sizes comprising the surface, as evident in the trends of reduced
 318 d_{50} , d_{90} and σ_z with distance down bar (Figs. 4 and 6). These patterns are in accordance
 319 with field results from the Fraser River, where a 33% reduction in median grain size from
 320 the bar head to the bar tail was documented (Rice and Church 2010). For our results, the
 321 mean values of the bar head and bar tail were compared using t-tests with a 95% confidence
 322 level, and were found to be statistically different for d_{50} , σ_z and inclination index. There were
 323 significant differences between the bar center and the bar tail for all parameters, except
 324 skewness. All roughness parameters were found to be statistically similar between the bar
 325 head and bar center.

326 The surface slope and aspect are presented as polar plots for all patches and overlain on
 327 an enlarged schematic of the bar (Fig. 7). Flow is assumed to be from left to right in polar
 328 plots (i.e., from 270° to 90°). For all patches, the majority of aspects are upstream (around
 329 270°), particularly on patches upstream of the bar (including P01, P04, P05, P06, and P07).
 330 Patches P08 – P13 (bar center and bar tail) have a higher density of upstream aspects, but
 331 they also have more downstream aspects compared to those patches upstream. These
 332 observations of accentuated particle imbrication at the bar head compared to the bar tail
 333 follow previous results showing a reduction in inclination index at the bar tail (Fig. 6D).
 334 Further, the slopes of DEM cells (assumed to be grains) can be assessed. The highest
 335 slopes observed are about 80° (Fig. 7), and these are predominantly positioned
 336 perpendicular to the flow. Visually, this is shown by shaded areas going further away
 337 towards the circles' edges for 0° and 180° aspect angles (Fig. 7). This is more evident in
 338 patches P09 – P13 (bar center and bar tail) at the downstream end of the bar.

339 Examining the relationship between multiple roughness parameters and grain size provides
 340 a baseline for future studies. For our results, the strongest correlation exists between
 341 roughness lengths in the downstream direction (L_x) and d_{90} (Fig. 8). Roughness parameters,

except skewness, and d_{90} have correlations ranging between $R^2 = 0.47$ and 0.88 . Relationships between roughness parameters and d_{50} also display strong correlations ($R^2 = 0.71 - 0.85$) (Fig. 8). The exception, skewness, shows weak correlation ($R^2 = 0.27$ and $R^2 = 0.21$ for d_{50} and d_{90} respectively). Even with the removal of the one anomalous site (P02, which has a negative skewness) the relationship is still below that of other roughness parameters ($R^2 = 0.35$ and $R^2 < 0.1$ for d_{50} and d_{90} , respectively).

DISCUSSION

Assessing within-bar variability in surface roughness

The assessment of σ_z is an improvement on the former technique of using grain size as a roughness parameter, as gravel beds with similar grain sizes can have contrasting σ_z values (Cooper and Tait 2009; Hodge et al. 2009). The pattern of higher σ_z values (i.e., indication of a rougher surface, Fig. 6B) upstream of the bar, at the bar head, and bar center, partly denotes coarser grains that have accumulated at these sites (Fig. 6A). Our observations of within-bar variability are attributed to varying locations and elevations on the bar. More specifically, field observations and an orthophoto (Fig. 3), indicate that upstream patches are elevated relative to the water line compared to patches at the bar tail, and may therefore be exposed for all but the highest flows, whereas patches at the bar tail are more frequently submerged. The pattern of upstream patches with larger sediment sizes and σ_z is comparable to patterns observed in laboratory studies, and is thought to reflect a coarse armor layer that formed as a result of higher discharges (Aberle and Nikora 2006). Contrasting roughness properties for patches at the bar tail may be due to exposure to more frequent sediment transport events and to submergence during lower flows. Differences in patch elevation on the bar also influence the distribution of bed shear stress during submergence, with higher bed shear stress occurring in areas on the bar top, due to higher velocities and reduced water depths. Previous experimental work showed an increase in

367 surface roughness with shear stress, which is relevant to this study (Aberle and Nikora
368 2006). Further, data from Rice and Church (2010) showed that varying bar elevation
369 determines shear stress distribution across the bar, which in turn determines the sediment
370 size distribution.

371 Whereas the patches at the water edge are more frequently submerged by flows and contain
372 smaller grain sizes, those patches nearer the bank of the river are more stable and have
373 coarser sediment (Fig. 4, higher d_{50} and σ_z). This suggests that these areas only experience
374 high flow events (and are otherwise exposed), which winnow fine sediment and move the
375 coarse sediment infrequently (Leopold and Wolman 1957). For the majority of patches on
376 this bar, skewness values are positive, representing water-working across the bar, except
377 patch P02 at the bar head (Fig. 4), which has a negative skewness value. This patch, located
378 below the change in elevation (i.e., below the bar platform), near vegetation, could explain
379 its singularity. The trend of increasing skewness with distance down bar is the opposite of
380 other roughness parameters (Figs. 4 and 6), with the patches at the bar tail having higher
381 skewness values, suggestive of fewer surface depressions from the deposition of fine
382 sediment in any gaps between coarse sediment during subaqueous transport (Nikora et al.
383 1998; Aberle and Nikora 2006).

384 All patches have positive inclination index values, indicating grain imbrication across the bar
385 (Hodge et al. 2009; Qin and Ng 2012). This is consistent with the findings of Rice and Church
386 (2010), who found that only two out of 87 of their locations displayed no evidence of
387 imbrication. All of their locations were on primary and secondary unit bars, although the
388 locations of the non-imbricated surfaces within the bars were not defined. Here, higher
389 inclination index values at the bar head and near the bank (Figs. 4 and 6) suggest greater
390 imbrication of particles and a higher degree of packing (Cooper and Tait 2009), and
391 therefore sediment is more stable and less readily available for transport. Previous work has
392 related grain imbrication to the movement of the coarse grains on the bed by rolling and

393 sliding (Laronne and Carson 1976), as those grains can stack against each other after
394 meeting with an obstacle, forming imbricated grain structures. In contrast, the bar tail and
395 the water edge have particles that may be more easily repositioned in future flow events due
396 to the surface being poorly organized (Mao et al. 2011). Although inclination index values
397 can provide information with regards to the imbrication of a surface, it is useful to combine
398 this with the analysis of slope and aspect (Fig. 7), as this can determine the slope values of
399 grains (Qin and Ng 2012).

400 Analysis of surface slope and aspect of DEM cells in polar plots (Fig. 7) has been used in
401 only a few gravel-bed river studies to date (Hodge et al. 2009, Qin and Ng, 2012; Bertin and
402 Friedrich 2016). Along with inclination index calculations, this method is more quantitative
403 than previous assessments of imbrication in the field. Imbrication was previously assessed
404 and categorized qualitatively, to extract information regarding the degree of reworking and
405 mobility of grains, with 38% of locations classified as weakly imbricated and 60% of locations
406 classified as strongly or very strongly imbricated (Rice and Church 2010). For all our patch
407 locations (Fig. 7), there is a majority of upstream aspects (i.e., high density of points around
408 270°), which is consistent with our previous observations of grain imbrication in a direction
409 parallel to the flow using the inclination index (Hodge et al. 2009; Qin and Ng 2012). If
410 imbrication is observed in a single direction, this can confirm the assumed flow direction
411 from field observations (Bertin and Friedrich 2016), which in this study is true (Fig.7), where
412 flow was assumed to be from 270 to 90° .

413 Our results quantitatively affirm previous geomorphological results. Although spatial
414 variability within bars is of no surprise, as geomorphologists and sedimentologists frequently
415 gather data from a consistent location (i.e., the bar head) when making inter-bar
416 comparisons of surfaces (Rice and Church 2010), our study emphasizes that a single
417 sample from one exposure cannot represent the whole gravel-bar surface. This has
418 important implications for the development of a standardized sampling approach, and for

the selection of roughness parameters in models, which is difficult due to the displayed complexity (i.e., variability) of roughness at the bar-scale (Rice and Church 2010). Our empirical findings of variations in roughness across a gravel bar can be used to validate and calibrate flow resistance equations and morphodynamic models, including comparisons of model predictions with field data (Rice and Church 2010; Powell 2014).

Examining roughness relationships with grain size

Throughout research, three roughness metrics are commonly used, as summarized in Pearson et al. (2017): (i) roughness height (rh) (Vazquez-Tarrio et al. 2017), which is the difference in height between the top of the particle and the averaged topographic surface (i.e. mean-bed elevation); (ii) twice the standard deviation of elevations (Heritage and Milan 2009); and (iii) root mean square height (RMSH), the standard deviation of heights in a given area for which the average slope has been detrended (Vazquez-Tarrio et al. 2017).

Pearson et al. (2017) summarizes published R^2 values for grain size versus topographic elevation for fluvial systems only, and there is a range between 0.231 and 0.96, although 50% of studies provide a strong relationship that exceeds $R^2 = 0.8$. Vazquez-Tarrio et al. (2017) found moderate to strong correlations for all roughness metrics ($R^2 = 0.45 - 0.90$) between surface roughness and truncated grain size (< 8 mm were removed). The best correlation was with rh -, and the weakest fit with RMSH.

To our knowledge, this is the first time the relationship between the studied roughness parameters (e.g., inclination index or horizontal roughness lengths) and grain size have been investigated (Fig. 8). The data on multiple roughness parameters and d_{50} in this study (Fig. 8) yield R^2 values between 0.71 – 0.85, which lie in the range of published values (Pearson et al. 2017, Vazquez-Tarrio et al. 2017). The one exception is skewness, which has a weak correlation ($R^2 = 0.27$) with grain size. Although skewness cannot be a proxy for grain size, it can contribute to the understanding of a surface (e.g. degree of water-working).

444 Case studies indicate that there are different relationships between surface roughness and
 445 grain size, reflecting different surface textural characteristics (Pearson et al. 2017; Vazquez-
 446 Tarrio et al. 2017). Further, patches with similarities in grain size have distinct roughness
 447 differences due to packing, burial and imbrication (Heritage and Milan 2009; Hodge et al.
 448 2009). There needs to be more data (including that of various roughness parameters) on
 449 differing sediment textures, to determine roughness and grain size relationships.

450 *Inferring sedimentation patterns from roughness parameters*

451 The gravel bar studied in this paper is a channel side bar, or lateral bar, in a non-meandering
 452 section of the channel. Lateral channel bars attach to one bank, in a narrow section of the
 453 channel, and sediment accumulates at both ends of the bar (Church and Jones 1982).

454 Evidence of down bar decreases in sediment size, σ_z , and inclination index (Figs. 4 and 6)
 455 implies down bar fining in sediment. Bar heads are thought to have formed during high flows
 456 (Leopold and Wolman 1957; Bluck 1976), that transport coarser sediment that mantles the
 457 bed. Due to an inability of subsequent lower flows to transport the coarse sediment, it
 458 remains *in situ* (Leopold and Wolman 1957; Bluck 1976; Francalanci et al. 2012). The coarse
 459 sediment becomes the nucleus for bar development, by modifying local flow structures and
 460 creating local turbulence that leads to winnowing of fine sediment. Further, fine sediment is
 461 trapped at the margins of the bar and is moved downstream during a range of flow rates
 462 (Leopold and Wolman 1957; Parker 1975; Nanson 1980; Bluck 1982; Leopold 1992;
 463 Ashworth 1996).

464 From field observations, there is a well defined bar platform across the studied bar (Fig. 3)
 465 with dense vegetation (pampas grass) on top (Blacknell 1982). The junction between a
 466 channel and the bar platform is known as an avalanche face, and these can range between
 467 a few centimeters to a few meters high (Blacknell 1982, Rice et al. 2009). In the case of this
 468 bar, the avalanche face is approximately 1 meter high.

469 Due to the presence of a bar platform, the patches located at higher elevations (i.e., on the
470 bar platform), and away from the water edge are strongly armored, with increased sediment
471 size and σ_z . A tentative correlation between surface elevation (or bar thickness) and surface
472 sediment size has previously been made, and this apparently contributes to deviations in
473 reach-scale downstream fining trends (Rice and Church 2010). In comparison, those
474 patches at the water edge appear to be undergoing multiple erosion and deposition cycles,
475 and sediment accumulates there due to lateral accretion of fine grains (Bluck 1982) (Fig.
476 9A). Downstream of the bar and bar platform, finer sediment is evident (reflected in a
477 decrease in grain size and σ_z in Figs. 4 and 6). Along with lateral accretion, this could be
478 due to the bar tail becoming a shadow zone during high flows (Fig. 9B). This depositional
479 mechanism occurs as fine sediment is transported over the bar platform until subsequent
480 falling flow stages result in the deposition of the sediment at the bar tail (Leopold and
481 Wolman 1957; Burge 2006; Rice and Church 2010). The lateral accretion of sediment is
482 substantiated by field observations of lighter colored sediment located below the bar
483 platform near the water edge (e.g., P02), indicating it has been deposited more recently than
484 the stable, darker sediment on the bar platform. Furthermore, increases in roughness
485 parameters with distance from the water edge (Fig. 4), supports the idea that the bar is
486 undergoing lateral accretion of sediment.

487 The scatter in our data (Fig. 4) suggests that the bar is complex in nature, with secondary
488 sedimentation patterns, supporting observations made from historical images (Fig. 2) that
489 demonstrate downstream propagation of the bar and provide evidence for cycles of erosion
490 and deposition (Rice and Church 2010). Furthermore, sedimentation patterns on this bar
491 may be difficult to interpret due to larger morphological features in the river channel at this
492 location. Directly opposite this bar, is a rock revetment, which was installed *circa* late 2011
493 (Hauraki Council Report 2011). In natural river channels, the deposition of sediment (e.g.,
494 on exposed gravel bars) is compensated for by erosion of the opposite bank, in order for the

495 channel to maintain conveyance (Rice and Church 2010). However, in this case sediment
496 deposition cannot be compensated for directly opposite the bar, which thus influences the
497 flow and natural sedimentation patterns.

498 An improved understanding of the variability in bed roughness is beneficial for modeling
499 purposes, and interpretations of sedimentation patterns and morphology. These are
500 important for successful river restoration procedures and the management of natural
501 systems. The Whakatiwai River studied has at times flooded local communities, and local
502 people have called for effective management to be put in place to protect sacred cultural
503 sites (Hauraki Council 2011). Therefore, developing and improving the understanding of
504 sedimentation patterns can guide management strategies in the future, which is applicable
505 to other locations around the globe.

506 Further, roughness properties can be measured between flow events to provide a signature
507 of erosional and depositional processes (Smith, 2014). Previous research has not
508 established a direct association between changes in grain size and morphological change
509 (Rice and Church 2010; Vazquez-Tarrio et al. 2017). However, we suggest that applying the
510 technique presented in this manuscript multiple times (i.e., following flow events), can aid in
511 the detection of temporal changes in roughness and help to relate changes in roughness to
512 morphological changes. This could involve the installation of GPS markers in order to
513 identify where the patch locations were for repeat surveys.

514 **CONCLUSION**

515 This study investigated intra-bar variability in roughness statistics across a bar at 14 patch
516 locations extending 35 m down bar and 5 m across the bar from the water edge. This
517 extends previous work that focused on grain size and qualitative estimates of parameters
518 such as imbrication. Data were collected using close-range photogrammetry, a technology
519 used for the first time to assess intra-bar variations of surface roughness.

520 Roughness statistics were found to vary across the bar, with evidence of down bar
521 reductions in grain size, changes in standard deviation of elevations, imbrication of particles,
522 variations in horizontal roughness lengths, and an increase in skewness down bar. This
523 paper therefore provides quantification of earlier observations of sorting across a bar. There
524 is a stronger correlation of increased roughness with distance from the water edge. This
525 lateral variation of roughness and sedimentation patterns across gravel bars is infrequently
526 documented, compared to down bar patterns, but is an important consideration for a wide
527 range of fluvial studies, including river restoration. It is also important for choosing a location
528 in the field to measure roughness properties. Relationships between roughness parameters
529 and grain size (d_{50}) were examined and strong correlations ($R^2 = 0.71 - 0.85$) were found in
530 all parameters except skewness. Assessing the relationship between roughness parameters
531 and grain size is timely, as previously no universal relationship has been found, suggesting
532 grain size cannot be used as a proxy for surface roughness.

533 Following on previous photogrammetry and laser-scanning studies, this study infers
534 sedimentation patterns from roughness statistics, with the consideration of wider
535 morphological influences. The trends observed in this study are indications of sediment
536 deposition at the bar tail and water edge, and coarse stable sediment at the bar head and
537 near the banks of the bar; which are consistent with lateral accretion. Inferring sedimentation
538 patterns from these roughness statistics can be difficult due to scatter in the data,
539 highlighting the complexity of surface roughness, which result from several cycles of erosion
540 and deposition. Understanding these sedimentation patterns in the Whakatiwai River, and
541 other rivers, is needed for the successful implementation and monitoring of river
542 management.

543 This paper has highlighted the variability in roughness statistics across a gravel bar and the
544 benefit of using a range of surface metrics to corroborate observations. Future work that
545 would benefit geomorphologists, includes the assessment of roughness parameters at a

546 larger scale (i.e., to include the effect of bedforms), quantification of roughness parameters
547 on multiple bars in different river systems, assessments of roughness over temporal scales,
548 and identifying if a single roughness parameter can be used to represent larger-scale
549 roughness. This would assist in the development of flow resistance, morphodynamic and
550 empirical models.

551 **ACKNOWLEDGEMENTS**

552 We would like to thank Wei Li and Trevor Patrick for assistance in acquiring the data and
553 Wei Li for preparing the orthophoto in Figure 3. The study was partly funded by the Marsden
554 Fund (Grant No. UOA1412), administered by the Royal Society of New Zealand.
555 Anonymous reviews and the insightful feedback from Dr. Paul Myrow are greatly
556 appreciated.

557 REFERENCES

- 558 ABERLE, J., NIKORA, V., HENNING, M., ETTMER, B., AND HENTSCHEL, B., 2010,
 559 Statistical Characterization of Bed Roughness due to Bed Forms: A Field Study in the
 560 Elbe River at Aken, Germany: *Water Resources Research*, v. 46.
- 561 ABERLE, J., AND NIKORA, V., 2006, Statistical Properties of Armored Gravel Bed
 562 Surfaces: *Water Resources Research*, v. 42.
- 563 ABERLE, J., AND SMART, G., 2003, The Influence of Roughness Structure on Flow
 564 Resistance on Steep Slopes: *Journal of Hydraulic Research*, v. 41, p. 259-269.
- 565 ASHWORTH, P. AND FERGUSON, R., 1986, Interrelationships of channel processes,
 566 changes and sediments in a proglacial braided river: *Geografiska Annaler*, v. 68A, p. 361
 567 – 371.
- 568 ASHWORTH, P.J., 1996, Mid-channel bar growth and its relationship to local flow strength
 569 and direction: *Earth Surface Processes and Landforms*, v. 21, p. 103 – 123.
- 570 BAEWERT, H., BIMBÖSE, M., BRYK, A., RASCHER, E., SCHMIDT, K., AND MORCHE,
 571 D., 2014, Roughness determination of coarse grained alpine river bed surfaces using
 572 terrestrial laser scanning data: *Zeitschrift Für Geomorphologie*, v. 58, p. 81 – 95.
- 573 BERTIN, S., AND FRIEDRICH, H., 2014, Measurement of Gravel-Bed Topography:
 574 Evaluation Study Applying Statistical Roughness Analysis: *Journal of Hydraulic*
 575 *Engineering*, v. 140, p. 269-279.
- 576 BERTIN, S., AND FRIEDRICH, H., 2016, Field Application of Close-range Digital
 577 Photogrammetry (CRDP) for Grain-scale Fluvial Morphology Studies: *Earth Surface*
 578 *Processes and Landforms*, v. 41, p. 1358 – 1369.
- 579 BERTIN, S., GROOM, J. AND FRIEDRICH, H., 2017, Isolating roughness scales of gravel-
 580 bed patches: *Water Resources Research*, v. 53, p. 6841 – 6856.

- 581 BERTOLDI, W., ZANONI, L., MIORI, S., REPETTO, R. AND TUBINO, M., 2009, Interaction
 582 between migrating bars and bifurcations in gravel bed rivers: Water Resources Research,
 583 v. 45, p. 1 – 12.
- 584 BLACKNELL, C., 1982, Morphology and surface sedimentary features of point bars in Welsh
 585 gravel-bed rivers: Geological Magazine, v. 119, p. 181 – 192.
- 586 BLUCK, B., 1976, Sedimentation in some Scottish Rivers of Low Sinuosity: Transactions of
 587 the Royal Society of Edinburgh, v. 69, p. 425 – 456.
- 588 BLUCK, B., 1982, Texture of gravel bars in braided streams. In Hey, R., Bathurst, J. and
 589 Thorne, C., 1982, Gravel Bed Rivers: John Wiley and Sons Ltd, Chichester.
- 590 BLUCK, B., 1987, Bed forms and clast size changes in gravel-bed rivers. In Richards, K.,
 591 1987, River Channels: Environment and Process: The Institute of British Geographers
 592 Special Publications Series 17.
- 593 BOUGUET J.-Y., 2010, http://www.vision.caltech.edu/bouquet/calib_doc/
- 594 BRASINGTON, J., VERICAT, D. AND RYCHKOV, I., 2012, Modeling river bed morphology,
 595 roughness and surface sedimentology using high resolution terrestrial laser scanning:
 596 Water Resources Research, v. 48, p. 1 – 18.
- 597 BRIDGE, J., 2003, Rivers and Floodplains: Forms, Processes and Sedimentary Record:
 598 Blackwell Publishing, Oxford.
- 599 BURGE, L., 2006, Stability, morphology and surface grain size patterns of channel
 600 bifurcation in gravel-cobble bedded anabranching rivers: Earth Surface Processes and
 601 Landforms, v. 31, p. 1211 – 1226.
- 602 CARBONNEAU, P., LANE, S. AND BERGERON, N., 2004, Catchment-scale mapping of
 603 surface grain size in gravel bed rivers using airborne digital imagery: Water Resources
 604 Research, v. 40, p. 1 – 11.

- 605 CHURCH, M. AND JONES, D., 1982, Channel bars in gravel-bed rivers. In Hey, R.,
 606 Bathurst, J. and Thorne, C., 1982, Gravel Bed Rivers: John Wiley and Sons Ltd,
 607 Chichester.
- 608 CHURCH, M., 2006, Bed material transport and the morphology of alluvial river channels:
 609 Annual Review of Earth and Planetary Sciences, v. 34, p. 325 – 354.
- 610 COLEMAN, S. E., NIKORA, V. I., AND ABERLE, J., 2011, Interpretation of Alluvial Beds
 611 through Bed-elevation Distribution Moments: Water Resources Research, v. 47.
- 612 COOPER, J. R., AND TAIT, S. J., 2009, Water-worked Gravel Beds in Laboratory Flumes–
 613 a Natural Analogue?: Earth Surface Processes and Landforms, v. 34, p. 384-397.
- 614 CURRAN, J. C., AND WATERS, K. A, 2014, The Importance of Bed Sediment Sand Content
 615 for the Structure of a Static Armor Layer in a Gravel Bed River: Journal of Geophysical
 616 Research: Earth Surface, v. 119, p. 1484-1497.
- 617 DETERT, M., AND WEITBRECHT, V., 2012, Automatic Object Detection to Analyze the
 618 Geometry of Gravel Grains—a Free Stand-Alone Tool: Proceedings of River Flow, 2012,
 619 p. 595-600.
- 620 ENWISTLE, N. AND FULLER, I., 2009, Terrestrial Laser scanning to derive the surface grain
 621 size facies character of gravel bars. In Heritage, G. and Large, A., 2009, Laser Scanning
 622 for the Environmental Sciences: Blackwell Publishing, Sussex.
- 623 FEHR, R., 1987, Geschiebeanalysen in Gebirgsflüssen: Umrechnung Und Vergleich Von
 624 Verschiedenen Analyseverfahren, Versuchsanst. für Wasserbau, Hydrologie u.
 625 Glaziologie.
- 626 FERGUSON, R., 2010, Time to abandon the Manning equation?: Earth Surface Processes
 627 and Landforms, v. 35, p. 1873 - 1876.
- 628 FRANCALANCI, S., SOLARI, L., TOFFOLON, M. AND PARKER, G., 2012, Do alternate
 629 bars affect sediment transport and flow resistance in gravel-bed rivers?: Earth Surface
 630 Processes and Landforms, v. 37, p. 866 – 875.

- 631 GIMEL'FARB, G., 2002, Probabilistic Regularisation and Symmetry in Binocular Dynamic
632 Programming Stereo: Pattern Recog. Lett., v. 23, p. 431-442.
- 633 GRAHAM, D. J., ROLLET, A., PIÉGAY, H., AND RICE, S. P., 2010, Maximizing the
634 Accuracy of Image-based Surface Sediment Sampling Techniques: Water Resources
635 Research, v. 46.
- 636 HARDY, R., 2006, Fluvial geomorphology: Progress in Physical Geography, v. 30, p. 553-
637 567.
- 638 HAURAKI DISTRICT COUNCIL, 2011, Drainage Manager's Report on Kaiaua Issues
639 October 2011. File reference 819 756. Accessed December 2016.
- 640 HERITAGE, G., AND MILAN, D., 2009, Terrestrial Laser Scanning of grain roughness in a
641 gravel bed river: Geomorphology, v. 11, p. 4 – 11.
- 642 HODGE, R., BRASINGTON, J. AND RICHARDS, K., 2009, Analyzing laser-scanned digital
643 terrain models of gravel bed surfaces: linking morphology to sediment transport
644 processes and hydraulics: Sedimentology, v. 56, p. 2024 – 2043.
- 645 HODGE, R., BRASINGTON, J., AND RICHARDS, K., 2009b, In situ characterisation of
646 grain-scale fluvial morphology using Terrestrial Laser Scanning: Earth Surface Processes
647 and Landforms, v. 34, p. 954 – 968.
- 648 IKEDA, S., PARKER, G. AND SAWAI, K., 1981, Bend theory of river meanders. Part 1:
649 Linear Development: Journal of Fluid Mechanics, v.112, p. 363 – 377.
- 650 LARONNE, J., AND CARSON, M., 1976, Interrelationships between Bed Morphology and
651 Bed-material Transport for a Small, Gravel-bed Channel: Sedimentology, v. 23, p. 67-85.
- 652 LEOPOLD, L. AND WOLMAN, M., 1957, River channel patterns: Braided, meandering and
653 straight: Geological Survey Professional Paper.
- 654 LEOPOLD, L., 1992, Sediment size that determines channel morphology. In Billi, P., Hey,
655 R., Thorne, C. and Tacconi, P., 1992, Dynamics of Gravel-Bed Rivers: John Wiley and
656 Sons Ltd.

- 657 LEWIN, J., 1976, Initiation of bed forms and meanders in coarse-grained sediment.
658 Geological Society of America Bulletin, v. 87, p. 281 – 285.
- 659 MAO, L., COOPER, J. AND FROSTICK, L., 2011, Grain size and topographical differences
660 between static and mobile armor layers: Earth Surface Processes and Landforms, v. 26,
661 p. 1321 – 1334.
- 662 MILAN, D., HERITAGE, G., AND HETHERINGTON, D., 2007, Application of a 3D laser
663 scanner in the assessment of erosion and deposition volumes and channel change in a
664 proglacial river: Earth Surface Processes and Landforms, v. 32, p. 1657 – 1674.
- 665 MILLANE, R., WEIR, M., AND SMART, G., 2006, Automated Analysis of Imbrication and
666 Flow Direction in Alluvial Sediments using Laser-Scan Data: Journal of Sedimentary
667 Research, v. 76, p. 1049-1055.
- 668 NANSON, G., 1980, Point bar and floodplain formation of the meandering Beatton River,
669 northeastern British Columbia, Canada: Sedimentology, v. 27, p. 3 – 29.
- 670 NIKORA, V. I., GORING, D. G., AND BIGGS, B. J., 1998, On Gravel-bed Roughness
671 Characterization: Water Resources Research, v. 34, p. 517-527.
- 672 NIKORA, V., AND GORING, D., 2000, Flow Turbulence Over Fixed and Weakly Mobile
673 Gravel Beds: Journal of Hydraulic Engineering, v. 126, p. 679-690.
- 674 NIKORA, V., KOLL, K., MCEWAN, I., MCLEAN, S., AND DITTRICH, A., 2004, Velocity
675 Distribution in the Roughness Layer of Rough-Bed Flows: Journal of Hydraulic
676 Engineering, v. 130, p. 1036-1042.
- 677 NOSS, C., AND LORKE, A., 2016, Roughness, Resistance, and Dispersion: Relationships
678 in Small Streams: Water Resources Research, v. 52, p. 2802-2821.
- 679 PARKER, G., 1975, Chapter 3: Transport of gravel and sediment mixtures: ASCE Manual v.
680 54, p. 1 – 162.

- 681 PEARSON, E., SMITH, M., KLAAR, M. AND BROWN, L., 2017, Can high resolution 3D
682 topographic surveys provide reliable grain size estimates in gravel bed rivers?:
683 Geomorphology, v. 293, p.143 – 155.
- 684 POWELL, M., 2014, Flow resistance in gravel-bed rivers: Progress in research: Earth-
685 Science Reviews, v. 136, p. 301 – 338.
- 686 QIN, J., AND NG, S., 2012, Estimation of Effective Roughness for Water-Worked Gravel
687 Surfaces: Journal of Hydraulic Engineering, v. 138, p. 923-934.
- 688 RAVEN, E., LANE, S., FERGUSON, R. AND BRACKEN, L., 2009, The spatial and temporal
689 patterns of aggradation in a temperate, upland, gravel-bed river: Earth Surface Processes
690 and Landforms, v. 34, p. 1181 – 1197.
- 691 RICE, S., CHURCH, M., WOOLDRIGE, C. AND HICKIN, E., 2009, Morphology and
692 evolution of bars in a wandering gravel-bed river; lower Fraser river, British Columbia,
693 Canada: Sedimentology, v. 56, p. 709 – 736.
- 694 RICE, S. AND CHURCH, M. (2010) Grain-size sorting within river bars in relation to
695 downstream fining along a wandering channel: Sedimentology, v. 57, p. 232 – 251.
- 696 RÜTHER, N., HUBER, S., SPILLER, S., AND ABERLE, J., 2013, Verifying a
697 photogrammetric method to quantify grain size distribution of developed armor layers:
698 Proceedings of 2013 IAHR Congress, Beijing, China.
- 699 SMART, G., ABERLE, J., DUNCAN, M., AND WALSH, J., 2004, Measurement and Analysis
700 of Alluvial Bed Roughness: Journal of Hydraulic Research, v. 42, p. 227-237.
- 701 SMART, G. M., DUNCAN, M. J., AND WALSH, J. M., 2002, Relatively Rough Flow
702 Resistance Equations: Journal of Hydraulic Engineering, v. 128, p. 568-578.
- 703 SMITH, M., 2014, Roughness in the Earth Sciences: Earth-Science Reviews, v. 136, p. 202
704 – 225.

- 705 STÄHLY, S., FRIEDRICH, H., AND DETERT, M., 2017, Size Ratio of Fluvial Grains'
706 Intermediate Axes Assessed by Image Processing and Square-Hole Sieving: Journal of
707 Hydraulic Engineering, v. 143, p. 06017005.
- 708 STERNBERG, H., 1875, Untersuchungen über Längen-und Querprofil geschiebeführender
709 Flüsse: Zeitschrift für Bauwesen, v. 25, p. 483–506.
- 710 TUIJNDER, A. P., AND RIBBERINK, J. S., 2012, Experimental Observation and Modelling
711 of Roughness Variation due to Supply-Limited Sediment Transport in Uni-Directional
712 Flow: Journal of Hydraulic Research, v. 50, p. 506-520.
- 713 VÁZQUEZ-TARRÍO, D., BORNIET, L., LIÉBAULT, F. AND RECKING, A., 2017, Using
714 UAS optical imagery and SfM photogrammetry to characterize the surface grain size of
715 gravel bars in a braided river (Vénénon River, French Alps): Geomorphology, v. 285, p.
716 94 – 105.
- 717 WILCOCK, P., 1996, Estimating local bed shear stress from velocity observations: Water
718 Resources Research, v. 32, p. 3361 - 3366.
- 719 ZHANG, Z., 2000, A Flexible New Technique for Camera Calibration: IEEE Trans. Pattern
720 Anal. Mach. Intell., v. 22, p. 1330-1334.
- 721

722 **FIGURE CAPTIONS**

723

724 **Figure 1.** Whakatiwai catchment, located in the north east of North Island, NZ (a), with study
725 site located near the stream mouth (b). Photo of close-range photogrammetry setup of
726 patches, with a rock revetment visible on the opposite bank of the stream (c).

Figure 2. Images showing the evolution of the bar under investigation from 2015 (A), 2013 (B), 2010 (C) and 2003 (D). The gravel bar is highlighted by dashed black lines, and flow direction is shown by the block black arrow (in 2a), left-to-right of images. These images provide context for the bar, surrounded by farmland and densely vegetated banks. In the 2013 and 2015 images (top row), the addition of the rock revetment can be seen on the opposite bank from the bar. Source: Google Earth.

Figure 3. Schematic of gravel bar, overlaying an orthophoto of the bar, indicating the location of 14 measurement patches, moving down a 30 m transect downstream, and across

737 bar. Black dotted line represents a break in slope and vegetation is represented
 738 schematically across the bar.

739
 740 **Figure 4.** Roughness statistics (including sediment size, standard deviation of elevations,
 741 skewness, inclination index and horizontal roughness lengths) with distance down bar and
 742 distance from the water edge for all 14 patches measured. Circled data points in the top
 743 graphs and associated labels refer to figure labels in Figure 5.

744

745 **Figure 5.** Photographs of grain size at upstream patch P03A (a), away from the water edge
746 P05 (b), downstream P12 (c) and at the water edge P13 (d). All photographs are the same
747 size and taken from the same height above the bed. The grain size data for these patches
748 are circled and labelled in Figure 4.

749

750 **Figure 6.** Boxplots of roughness statistics; (a) d_{50} , (b) σ_z , (c) skewness, (d) inclination index,
 751 (e) horizontal roughness length L_x and (f) horizontal roughness length L_y , for three locations
 752 of the bar (sample size $n = 5$ for bar head, $n = 6$ for bar center and $n = 3$ for bar tail). The
 753 horizontal line in the boxplot represents the median value for each location, the upper and
 754 lower box limits represent the 75 % and 25 % percentiles respectively and whiskers display
 755 the range in values.

756

757 **Figure 7.** Surface slope and aspect polar plots, presented on an enlarged schematic of the
 758 bar (as per Figure 3) to enable location of patch to be identified. Flow is assumed from left
 759 to right (grey arrow). Aspect angle is from 0 to 360° and slope angle is from 0 to 90°, with
 760 high density of points shaded black, and low density of points shaded white. Black dotted
 761 line represents a break in slope and vegetation is represented schematically. Note that the
 762 placement of polar plots is not to scale.

763

764 **Figure 8.** Roughness relationships for standard deviation of elevations, skewness,
 765 inclination index and horizontal roughness lengths with grain size. Circles represent d_{50} grain
 766 size and open triangles represent the d_{90} grain size.

767

768 **Figure 9.** Schematic of sedimentation patterns occurring on this bar. (a) Lateral accretion,
 769 whereby fine sediment is deposited at the edge of the bar and downstream. (b) Down bar
 770 fining due to sediment being transported over the bar platform during high flows and
 771 deposited in the shadow zone during the falling limbs of hydrographs.