Simple method for measuring center of mass work during field running

Authors:

Marine Devise^{1,2}, Jérémy Rossi¹, Nicolas Theveniau², Alain Belli¹

Affiliation:

¹ Univ Lyon, UJM-Saint-Etienne, Laboratoire Interuniversitaire de Biologie de la Motricité, EA 7424, F-42023 Saint-Etienne, France

² CTC, Comité Professionnel de Développement Cuir Chaussure Maroquinerie, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07, France

Corresponding author: Marine Devise

Address: Campus Santé Innovation – 10 Rue de la Marandière – 42270 SAINT-PRIEST-EN-JAREZ – FRANCE

Tel: +334 77 48 15 00

Email: marine.devis@univ-st-etienne.fr

Submission for publication: Short communication

Word count (Introduction through Discussion): 2094

Keywords: total center of mass work, leg stiffness, running

Abstract

The purpose of this study was to propose and validate a new simple method for calculation of center of mass work during field running, in order to avoid the use of costly and inconvenient measurement devices. This method relies on spring-mass model and measurements of average horizontal velocity, and contact and flight times during running. Ten male, recreational subjects ran on a dynamometer treadmill at different velocities ranging from 2.22 to 4.44 m.s⁻¹ during 4 min 30 s for each velocity. Twenty consecutive steps were analyzed after 3 min 30 s. The potential (W_{pot}), forward kinetic (W_{kinf}) and the total center of mass (W_{ext}) work data obtained with this new method were compared with the reference data calculated from ground reaction force measurements. W_{ext} , W_{pot} and W_{kinf} values calculated with the proposed method were respectively $+3.39 \pm 0.77\%$ higher, $-4.14 \pm 0.72\%$ lower and $+7.34 \pm 1.08\%$ higher than values obtained by the reference method. Furthermore, significant linear regressions close to the identity line were obtained between the reference and the proposed method values of works ($r = 0.99$, $p < 0.05$ for W_{ext} ; $r = 0.98$, $p < 0.05$ for W_{pot} ; $r = 0.98$, $p < 0.05$ for W_{kinf}). It was concluded that this new method could provide a good estimate of center of mass work in field running thanks to a few simple mechanical parameters.

Introduction

In sports, the measurement of mechanical power and/or work is often used for research or athlete training and monitoring purposes. As recently mentioned by van der Kruk et al. (2018): “The quantification of mechanical power can provide valuable insight into athlete performance because it is the mechanical principle of the rate at which the athlete does work or transfers energy to complete a movement task”.

The biomechanics and energetics of running have been mainly investigated by means of two integrative mechanical models: the “center of mass model” (CMM) and the “spring-mass model” (SMM). The work done to raise and accelerate the center of mass (COM) at each step was defined as “external work” (W_{ext} , Cavagna, 1975; Fenn, 1930) or center of mass work (van der Kruk et al., 2018) in the literature. The SMM is widely used for describing the stored and released elastic energy in the lower limbs in humans at each step. The SMM is mainly characterized and controlled by the stiffness of the leg (k_{leg}) during contact (McMahon and Cheng, 1990; Farley and González, 1996) in the sense that the SMM represents the bounce of the body on the ground by a single mass mounted on a springy leg.

CMM and SMM biomechanical models have been used in the literature to address the differences in metabolic energy cost among individuals. Indeed, inter-individual variability of the energy cost of running (C_r) have been significantly related to mechanical parameters and more specifically to W_{ext} (Saibene and Minetti, 2003) and k_{leg} (Dalleau et al., 1998). Significant positive correlations between inter- and intra-individual C_r and W_{ext} variations were found by Bourdin et al. (1995) for an homogeneous group of long distance runners and by Lazzer et al. (2014) in ultra-marathon runners. Furthermore, k_{leg} was negatively correlated with inter-individual variability of C_r for middle-distance runners (Dalleau et al., 1998).

Therefore, the measurements of W_{ext} and k_{leg} are important to further investigate the biomechanics of running. In laboratory conditions, W_{ext} can be accurately measured (Cavagna, 1975; Arampatzis et al., 2000; Saibene and Minetti, 2003; Avogadro et al., 2004; Pavei et al., 2017) by using force platforms or instrumented treadmills and motion capture systems. Nowadays, these techniques are still used in order to find any small differences that could discriminate variations among subjects. Using the same measurement devices, k_{leg} was also initially investigated in laboratory conditions (McMahon and Cheng, 1990; Farley and González, 1996). In 2005, Morin et al. proposed and validated a simple method for measurements of k_{leg} , based on measurement of body mass and leg length and on field

measurement of contact time, flight time and average running speed. The contact and flight times as well as average running speed can nowadays be performed by portable and lightweight equipment such as pressure sensors, accelerometers, goniometers or gyroscopes (Norris et al., 2014), or by systems utilizing photocell beams placed on running tracks (Glatthorn et al., 2011). The Morin's method has since been widely used in field conditions (Hobara et al. 2010; Morin et al. 2011a, b).

To the best of our knowledge, there are no simple methods that could monitor W_{ext} in field running conditions and the purpose of the present study was to propose and validate such a method. The proposed method is based on the same measurements as Morin et al. (2005): contact time, flight time, average running speed, leg length and body mass. It was validated during treadmill running by comparing it with the reference W_{ext} computed from ground reaction forces (GRF, Avogadro et al., 2004; Cavagna, 1975).

Materials and methods

Protocol

Ten male subjects (22.5 ± 2.84 years; 75.6 ± 6.05 kg; 1.82 ± 0.06 m; leg length 0.96 ± 0.04 m; mean $\pm$ SD) gave their informed consent to participate in this study. They were all physical education students and experienced in treadmill running. After a standardized 6 min warm-up at 3.33 m.s^{-1} , subjects ran 4 min 30 s on a treadmill at 2.22, 2.78, 3.33, 3.89 and 4.44 m.s^{-1} , in random order, interspersed with at least 5 min rest.

Mechanical parameters were measured by treadmill dynamometer (ADAL 3DC, HEF Techmachine, Andrézieux-Bouthéon, France, for details, see Belli et al. (2001)). Force data were collected after 3 min 30 s. 3D GRF were sampled at 1000 Hz and were filtered using a low-pass fourth-order Butterworth filter with a 50 Hz cut-off. Contact and aerial times were measured from force signals, contact period corresponded to a vertical force higher than 30 N. Measurements were calculated for each cycle (defined by time period from one heel strike to contralateral heel strike) then averaged for twenty consecutive steps to obtain a good estimate of average step values (Belli et al., 1995).

Reference method for measuring W_{ext}

The reference forward kinetic work (W_{kinf}) due to forward acceleration of the body and the reference potential work (W_{pot}) done to raise the COM were calculated from GRF of the foot during each step and computed the speeds and displacement of the COM by simple time-integration of antero-posterior GRF and double time-integration of vertical GRF respectively, according to the method of Avogadro et al. (2004). Assuming that no transfer occurred between kinetic and potential energies in running (Cavagna et al., 1964) and that the medio-lateral work was negligible (Cavagna, 1975), W_{ext} was calculated as:

$$W_{ext} = W_{kinf} + W_{pot} \quad (1)$$

Proposed method for measuring $\hat{W}_{ext}$

In the present method the $\hat{W}_{ext}$ was simply computed as the elastic mechanical energy stored and released by the spring-mass model (e.g. Blickhan and Full, 1993):

$$\hat{W}_{ext} = \frac{1}{2} k_{leg} \Delta L^2 \quad (2)$$

where k_{leg} (in kN.m^{-1}) and ΔL (in m) were calculated according to the method of Morin et al. (2005):

$$k_{leg} = F_{max} \Delta L^{-1} \quad (3) \quad \text{and} \quad \Delta L = L - \sqrt{L^2 - \left(\frac{vt_c}{2}\right)^2} + \Delta y \quad (4)$$

$$\text{with } F_{max} = mg \frac{\pi}{2} \left(\frac{t_f}{t_c} + 1\right) \quad (5) \quad \text{and} \quad \Delta y = \left| -\frac{F_{max} t_c^2}{m \pi^2} + g \frac{t_c^2}{8} \right| \quad (6)$$

Where m is the body mass (in kg), $g = 9.81 \text{ m.s}^{-2}$, v the average running velocity (in m.s^{-1}), L the leg length (in m), t_c and t_f , the contact and the flight times (in s) respectively determined from vertical GRF.

However, in former ΔL computations (equation 4) it is assumed that the average horizontal running velocity during the contact phase (v_{con}) is the same than the average running velocity (v) (e.g. Farley et al. 1993). Because the horizontal velocity is maximal in flight phase and lower in contact phase (Blickhan, 1989; Cavagna, 2006), ΔL was computed using v_{con} in the present study (see appendix):

$$\Delta L' = L - \sqrt{L^2 - \left(\frac{v_{con} t_c}{2}\right)^2} + \Delta y \quad (7)$$

Furthermore, variations of trunk inclination in sagittal plane during the contact phase of running (Thorstensson et al., 1984) induce a backward movement of the COM of the trunk. Therefore, the real horizontal displacement of the COM is lower than the horizontal displacement $v_{con}t_c$ calculated with the SMM (equation 7) that assumes that the COM is always located at the upper end of the leg. This backward movement increases with velocity starting from 2 cm at 2 m.s⁻¹ to 3 cm at 5 m.s⁻¹ at L3 vertebral level (Thorstensson et al., 1984, figure 5) and could induce an increasing overestimation of ΔL with velocity. Taking this phenomenon into account, ΔL was recalculated:

$$\Delta L'' = L - \sqrt{L^2 - \left(\frac{v_{con}t_c - 0.02 - \frac{(v_{con}-2)}{3} \times (0.03-0.02)}{2} \right)^2} + \Delta y \quad (8)$$

From only t_c and t_f measurements $\hat{W}_{pot}$ could also be calculated:

$$\hat{W}_{pot} = mg(\Delta y + \frac{1}{8}gt_f^2) \quad (9)$$

where $\frac{1}{8}gt_f^2$ correspond to the rising of the COM during the flight time (Bosco et al., 1983).

It was then possible to obtain $\hat{W}_{kinf}$ according to equation (1):

$$\hat{W}_{kinf} = \hat{W}_{ext} - \hat{W}_{pot} \quad (10)$$

Statistical analysis

The standard errors of estimate (SEE) of main parameters (W_{ext} , W_{kinf} and W_{pot}) were computed for each subject between values obtained from force plate data at each step and values estimated from model computations:

$$SEE = \sqrt{\frac{\sum (F_{Reference} - F_{Model})^2}{N_{steps} - 2}} \quad (11)$$

Absolute bias was calculated for each subject at each velocity:

$$absolute\ bias = \left| \frac{Model - Reference}{Reference} \right| \times 100 \quad (12)$$

The reference-model relationships were further described by the calculation of the Pearson's correlation coefficient (r). To analyze the reliability of the proposed method in comparison with the reference, the Intraclass correlation coefficient was used (ICC-2,1). Statistical significance

was accepted at $p < 0.05$. All data processing was performed using Matlab 2016b (The MathWorks Inc., Natick, MA).

Results

The values obtained with both the reference and proposed method, absolute reference-proposed bias, Pearson's correlation coefficient and SEE are shown in Table 1. The proposed method overestimated $\hat{W}_{ext}$ and $\hat{W}_{kinf}$, and underestimated $\hat{W}_{pot}$ as compared with the reference method. $\hat{W}_{ext}$ mean bias was 3.39%, ranging from 2.64 to 4.36%. $\hat{W}_{pot}$ and $\hat{W}_{kinf}$ biases were respectively 4.14% (ranging from 2.07 to 7.84%) and 7.34% (ranging from 6.70 to 8.12%).

There were excellent agreements between methods for W_{ext} , W_{pot} and W_{kinf} (ICC = 0.976, $p < 0.001$; ICC = 0.952, $p < 0.01$ and ICC = 0.960, $p < 0.001$ respectively). The values of $\hat{W}_{ext}$, $\hat{W}_{pot}$ and $\hat{W}_{kinf}$ were very close to the reference values measured at each step, with SEE of 0.105, 0.044 and 0.106 J.kg⁻¹.step⁻¹, respectively.

The reference-model linear regressions of mechanical work (figure 1) were highly significant and Pearson's correlation coefficient revealed a very high relationship for W_{ext} , W_{pot} and W_{kinf} ($r = 0.99$, $p < 0.001$; $r = 0.98$, $p < 0.001$; $r = 0.98$, $p < 0.001$ respectively). Nevertheless, there seems to be a tendency of under/over-estimation of the proposed W_{ext} method with respectively lower/higher running speeds.

***** TABLE 1 *****

***** FIGURE 1 *****

Discussion

The purpose of this study was to provide a calculation method of W_{ext} based on simple measurements. When this calculation method was compared to reference measurements a high level of agreement of $\hat{W}_{ext}$ (showed by high ICC) and a very high coefficient correlation ($r = 0.99$, $p < 0.01$) were observed. The same conclusions were reached for $\hat{W}_{pot}$ and $\hat{W}_{kinf}$. Furthermore, the mean biases of the present study (3.39% for W_{ext} , 4.14 % for W_{pot} and 7.34% for W_{kinf}) were comparable to Morin et al. (2005) with bias of 6.05% for k_{leg} during treadmill running (between 3.33 and 6.67 m.s⁻¹). These biases could be explained by the limits inherent

to the spring-mass model, i.e., the human lower limb is not a true linear spring in a physical sense. This point has been widely discussed in the literature (Blickhan, 1989; McMahon and Cheng, 1990; Latash and Zatsiorsky, 1993; Farley and González, 1996).

The values of W_{ext} , W_{pot} and W_{kinf} obtained in the present study are in agreement with the range of values reported in the literature for comparable running velocities (Arampatzis et al., 2000; Avogadro et al., 2004; Bourdin et al., 1995; Cavagna et al., 1964; Dalleau et al., 1998; Fukunaga et al., 1980), up to $2.15 \text{ J.kg}^{-1}.\text{step}^{-1}$ for W_{kin} (at 4.44 m.s^{-1}), from 0.87 to $1.25 \text{ J.kg}^{-1}.\text{step}^{-1}$ for W_{pot} and from 0.33 to $1.13 \text{ J.kg}^{-1}.\text{step}^{-1}$ for W_{kinf} . An increase in W_{ext} and W_{kinf} , and a constant W_{pot} with velocity were also reported in the literature (Cavagna et al., 1964; Avogadro et al., 2004).

It is also important to note that the present method is based on a single body model and thus limited to the calculations of work done by the COM. Minetti (1998) already proposed a method to estimate the “internal work” (W_{int}) produced during field running. This method requires the same type of measurements: running speed, contact and flight times. Both methods could then be combined to obtain both W_{ext} and W_{int} in field conditions. As discussed by van der Kruk et al. (2018) in a recent review, the definition of W_{int} is not consistent. These authors also mentioned that multi-joints models and inverse dynamics could be used to calculate and sum joint powers. However, because there is no standard on whether to allow for energy flow between joints, large discrepancy on total work and power calculations can be found among papers using multi-joint models. In addition, in field conditions the frictional work and power mainly due to air friction cannot be taken into account by either single joint nor multi-joint models, but could be estimated from running velocity (Davies, 1980). The energy cost of overcoming air resistance on a calm day outdoor was calculated to be 2% in marathon (5 m.s^{-1}) up to 7.8% for sprinting (10 m.s^{-1}). Within the velocity range of the present study it represents less than 2% of the total C_r .

Although the present study provides a new mathematical methodology of mechanical work, its extrapolation on overground conditions must be interpreted with caution, since it has not been field tested. Although no fundamental differences exist between mechanics of overground versus treadmill locomotion (van Ingen Schenau, 1980), the wearables used may not be as accurate as the instrumented treadmill to measure horizontal velocity, t_f and t_c . Further investigations are then needed to fully validate this method in field condition.

To sum up, $\widehat{W}_{ext}$ appears to provide consistent calculations of mechanical work production during steps. In future, the present method could be used to monitor $\widehat{W}_{ext}$ changes during long distance field running and with shoes or tracks having different damping and elastic characteristics. Coupled with lightweight and portable tool, such a method could provide mechanical feedback on running techniques during normal trainings and/or competitions.

To our knowledge, this is the first method that could be applied to W_{ext} in field conditions. This new calculation is both a valid and reliable method to estimate W_{ext} thanks to simple parameters and practical for field running.

Acknowledgements

The authors would like to thank the subjects of the present study for their participation and Camille Perrin and Florian Rifino for their contribution during the experiments.

Conflict of Interest

The authors do not have any conflict of interest or personal relationships with other people or organizations that could inappropriately influence this work.

References

- Arampatzis, A., Knicker, A., Metzler, V., Brüggemann, G.P., 2000. Mechanical power in running: a comparison of different approaches. *Journal of Biomechanics*. 33, 457–463.
- Avogadro, P., Chaux, C., Bourdin, M., Dalleau, G., Belli, A., 2004. The use of treadmill ergometers for extensive calculation of external work and leg stiffness during running. *European Journal of Applied Physiology*. 92, 182–185.
- Belli, A., Bui, P., Berger, A., Geyssant, A., Lacour, J.R., 2001. A treadmill ergometer for three-dimensional ground reaction forces measurement during walking. *Journal of Biomechanics*. 34, 105–112.
- Belli, A., Lacour, J.R., Komi, P.V., Candau, R., Denis, C., 1995. Mechanical step variability during treadmill running. *European Journal of Applied Physiology and Occupational Physiology*. 70, 510–517.
- Blickhan, R., 1989. The spring-mass model for running and hopping. *Journal of Biomechanics*. 22, 1217–1227.

244 Blickhan, R., Full, R.J., 1993. Similarity in multilegged locomotion: Bouncing like a monopode.
 245 Journal of Comparative Physiology A. 173, 509–517.

246 Bosco, C., Luhtanen, P., Komi, P.V., 1983. A simple method for measurement of mechanical power in
 247 jumping. European Journal of Applied Physiology and Occupational Physiology. 50, 273–282.

248 Bourdin, M., Belli, A., Arsac, L.M., Bosco, C., Lacour, J.R., 1995. Effect of vertical loading on energy
 249 cost and kinematics of running in trained male subjects. Journal of Applied Physiology. 79,
 250 2078–2085.

251 Cavagna, G.A., 1975. Force platforms as ergometers. Journal of Applied Physiology. 39, 174–179.

252 Cavagna, G.A., 2006. The landing-take-off asymmetry in human running. Journal of Experimental
 253 Biology. 209, 4051–4060.

254 Cavagna, G.A., Saibene, F.P., Margaria, R., 1964. Mechanical work in running. Journal of Applied
 255 Physiology. 19, 249–256.

256 Dalleau, G., Belli, A., Bourdin, M., Lacour, J.R., 1998. The spring-mass model and the energy cost of
 257 treadmill running. European Journal of Applied Physiology. 77, 257–263.

258 Davies, C.T., 1980. Effects of wind assistance and resistance on the forward motion of a runner.
 259 Journal of Applied Physiology. 48, 702–709.

260 Farley, C.T., Glasheen, J., McMahon, T.A., 1993. Running springs: speed and animal size. Journal of
 261 Experimental Biology. 185, 71–86.

262 Farley, C.T., González, O., 1996. Leg stiffness and stride frequency in human running. Journal of
 263 Biomechanics. 29, 181–186.

264 Fenn, W.O., 1930. Work against gravity and work due to velocity changes in running. American
 265 Journal of Physiology-Legacy Content. 93, 433–462.

266 Fukunaga, T., Matsuo, A., Yuasa, K., Fujimatsu, H., Asahina, K., 1980. Effect of running velocity on
 267 external mechanical power output. Ergonomics. 23, 123–136.

268 Glatthorn, J.F., Gouge, S., Nussbaumer, S., Stauffacher, S., Impellizzeri, F.M., Maffiuletti, N.A.,
 269 2011. Validity and reliability of Optojump photoelectric cells for estimating vertical jump
 270 height. Journal of Strength and Conditioning Research. 25, 556–560.

271 Hobara, H., Inoue, K., Gomi, K., Sakamoto, M., Muraoka, T., Iso, S., Kanosue, K., 2010. Continuous
 272 change in spring-mass characteristics during a 400m sprint. Journal of Science and Medicine
 273 in Sport. 13, 256–261.

274 Latash, M.L., Zatsiorsky, V.M., 1993. Joint stiffness: Myth or reality? Human Movement Science. 12,
 275 653–692.

276 Lazzer, S., Taboga, P., Salvadego, D., Rejc, E., Simunic, B., Narici, M.V., Buglione, A., Giovanelli,
 277 N., Antonutto, G., Grassi, B., Pisot, R., di Prampero, P.E., 2014. Factors affecting metabolic
 278 cost of transport during a multi-stage running race. Journal of Experimental Biology. 217,
 279 787–795.

- McMahon, T.A., Cheng, G.C., 1990. The mechanics of running: How does stiffness couple with speed? *Journal of Biomechanics*. 23, 65–78.
- Minetti, A.E., 1998. A model equation for the prediction of mechanical internal work of terrestrial locomotion. *Journal of Biomechanics*. 31, 463–468.
- Morin, J.B., Dalleau, G., Kyröläinen, H., Jeannin, T., Belli, A., 2005. A simple method for measuring stiffness during running. *Journal of Applied Biomechanics*. 21, 167–180.
- Morin, J.B., Samozino, P., Millet, G.Y., 2011a. Changes in running kinematics, kinetics, and spring-mass behavior over a 24-h run. *Medicine & Science in Sports & Exercise*. 43, 829–836.
- Morin, J.B., Tomazin, K., Edouard, P., Millet, G.Y., 2011b. Changes in running mechanics and spring-mass behavior induced by a mountain ultra-marathon race. *Journal of Biomechanics*. 44, 1104–1107.
- Norris, M., Anderson, R., Kenny, I.C., 2014. Method analysis of accelerometers and gyroscopes in running gait: A systematic review. *Proceedings of the Institution of Mechanical Engineers, Part P: Journal of Sports Engineering and Technology*. 228, 3–15.
- Pavei, G., Seminati, E., Storniolo, J.L.L., Peyré-Tartaruga, L.A., 2017. Estimates of Running Ground Reaction Force Parameters from Motion Analysis. *Journal of Applied Biomechanics*. 33, 69–75.
- Saibene, F., Minetti, A.E., 2003. Biomechanical and physiological aspects of legged locomotion in humans. *European Journal of Applied Physiology*. 88, 297–316.
- Thorstensson, A., Nilsson, J., Carlson, H., Zomlefer, M.R., 1984. Trunk movements in human locomotion. *Acta Physiologica Scandinavica*. 121, 9–22.
- van der Kruk, E., van der Helm, F.C.T., Veeger, H.E.J., Schwab, A.L., 2018. Power in sports: A literature review on the application, assumptions, and terminology of mechanical power in sport research. *Journal of Biomechanics*. 79, 1–14.
- van Ingen Schenau, G.J., 1980. Some fundamental aspects of the biomechanics of overground versus treadmill locomotion. *Medicine and Science in Sports and Exercise*. 12, 257–261.

APPENDIX

Computation of average velocity during contact time:

The average running velocity during a complete step (v) is given by:

$$v = \frac{v_f \times t_f + v_{con} \times t_c}{t_c + t_f} = \frac{v_{max} \times t_f + \left(v_{max} - \frac{\Delta v}{2}\right) \times t_c}{t_c + t_f} = v_{max} - \frac{\Delta v \times t_c}{2 \times (t_c + t_f)}$$

where $v_f = v_{max}$ is the maximal velocity during the flight phase, v_{con} is the average velocity during contact and Δv is the change of velocity due to deceleration and corresponding acceleration during contact phase.

It is then possible to establish a relationship between the two unknowns v_{max} and Δv :

$$v_{max} = v + \frac{\Delta v \times t_c}{2 \times (t_c + t_f)} \quad (1')$$

A second relationship between v_{max} and Δv can be drawn from $\hat{W}_{kinf}$ as follow:

$$\hat{W}_{kinf} = \frac{1}{2} m (v_{max}^2 - v_{min}^2) = \frac{1}{2} m (v_{max}^2 - (v_{max} - \Delta v)^2)$$

$$\Leftrightarrow \frac{2\hat{W}_{kinf}}{m} = 2v_{max}\Delta v - \Delta v^2 \quad (2')$$

Combining equations (1') and (2') we get a second degree equation of Δv :

$$\frac{t_f}{t_c + t_f} \Delta v^2 + (-2v\Delta v) + \frac{2\hat{W}_{kinf}}{m} = 0 \quad (3')$$

with two Δv real solutions, using the only solution that gives $\Delta v < v$ it is finally possible to compute v_{con} from equation (1):

$$v_{con} = v_{max} - \frac{\Delta v}{2} \times \frac{t_f}{t_c + t_f} \quad (4')$$

Figure 1

(A)

(B)

(C)

Table 1

Speed (m.s⁻¹)	Reference method (J.kg⁻¹.step⁻¹)	Proposed method (J.kg⁻¹.step⁻¹)	Absolute bias (%)	SEE
<i>W_{ext}</i>				
2.22	1.26 ± 0.10	1.21 ± 0.13	4.09 ± 2.71	0.092
2.78	1.49 ± 0.14	1.48 ± 0.16	2.76 ± 2.07	0.087
3.33	1.70 ± 0.17	1.72 ± 0.20	2.64 ± 1.66	0.095
3.89	1.87 ± 0.20	1.92 ± 0.21	3.10 ± 2.95	0.110
4.44	2.00 ± 0.20	2.07 ± 0.26	4.36 ± 3.63	0.140
<i>W_{pot}</i>				
2.22	0.82 ± 0.09	0.76 ± 0.09	7.84 ± 2.78	0.072
2.78	0.88 ± 0.12	0.84 ± 0.12	5.27 ± 2.69	0.054
3.33	0.91 ± 0.15	0.88 ± 0.15	3.43 ± 2.13	0.041
3.89	0.89 ± 0.17	0.87 ± 0.16	2.07 ± 1.59	0.029
4.44	0.84 ± 0.15	0.83 ± 0.15	2.10 ± 1.12	0.025
<i>W_{kinf}</i>				
2.22	0.44 ± 0.03	0.46 ± 0.04	7.97 ± 5.28	0.072
2.78	0.60 ± 0.04	0.64 ± 0.06	7.02 ± 7.58	0.090
3.33	0.79 ± 0.04	0.84 ± 0.07	6.90 ± 5.78	0.105
3.89	0.99 ± 0.06	1.05 ± 0.06	6.70 ± 5.20	0.117
4.44	1.16 ± 0.07	1.25 ± 0.12	8.12 ± 7.08	0.145