Analytical solution and Bayesian inference for interference pumping tests in fractal dual-porosity media

Mohamed Hayek, Anis Younes, Jabran Zouali, Noura Fajraoui, Marwan Fahs

► To cite this version:

Mohamed Hayek, Anis Younes, Jabran Zouali, Noura Fajraoui, Marwan Fahs. Analytical solution and Bayesian inference for interference pumping tests in fractal dual-porosity media. Computational Geosciences, 2018, 22 (1), pp.413-421. 10.1007/s10596-017-9701-9 . hal-03527143

HAL Id: hal-03527143

<https://hal.science/hal-03527143>

Submitted on 15 Jan 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Distributed under a Creative Commons Attribution| 4.0 International License

Analytical solution and Bayesian inference for interference pumping tests in fractal dual-porosity media

Mohamed Hayek¹, Anis Younes^{*,2,3,4}, Jabran Zouali², Noura Fajraoui⁵, Marwan Fahs²

¹AF-Consult, Groundwater Protection and Waste Disposal, Täferstrasse 26, CH-5405 Baden, Switzerland

²LHyGES, Université de Strasbourg/EOST, CNRS, 1 rue Blessig, 67084 Strasbourg, France

³IRD UMR LISAH, F-92761 Montpellier, France

⁴LMHE, Ecole Nationale d'Ingénieurs de Tunis, Tunisie

⁵Chair of Risk, Safety and Uncertainty Quantification, ETH Zurich, Switzerland

Submitted to *Computational Geosciences*

* Contact person: younes@unistra.fr

21

22 **Abstract**

23 A new analytical solution is developed for interference hydraulic pumping tests in fractured
24 porous media using the dual-porosity concept. Heterogeneous fractured reservoirs are consid-
25 ered with hydrodynamic parameters assumed to follow power-law functions in radial dis-
26 tance. The developed analytical solution is verified by comparison against a finite volume
27 numerical solution. The comparison shows that the numerical solution converges toward the
28 analytical one when the size of the time step decreases. The applicability of the fractal dual-
29 porosity model is then assessed by investigating the identifiability of the parameters from a
30 synthetic interference pumping test with a set of noisy data using Bayesian parameter infer-
31 ence. The results show that if the storage coefficient in the matrix is fixed, the rest of the pa-
32 rameters can be appropriately inferred, otherwise, the identification of the parameters is faced
33 with convergence problems because of equifinality issues.

34 **Keywords:** Fractured porous media, interference pumping test, dual-porosity, fractal media,
35 Bayesian inversion.

36

1 INTRODUCTION

Simulation of interference pumping tests in porous media allows testing different prospective exploitation scenarios at low costs. These tests consist in pumping a well at a controlled flow rate and measuring the water level response (drawdown) in one or more surrounding observation wells. Pumping tests in fractured porous media have been discussed by several authors (see [1-8], among others). Fractured media are often addressed using the dual-porosity model suggested by Barenblatt *et al.* [9]. The main idea of this model is to consider two overlapping continua: (i) the fractures which carry the major part of water to the pumping well and (ii) the low permeability rock matrix which feeds fluid to the fractures. At each point of the domain, water flow between the fractures and matrix are coupled via a linear exchange term proportional to the difference in hydraulic head between the two continua. As stated by De Smedt [8], the simulation of interference pumping tests is often based on numerical models which cannot insure full control of numerical accuracy [10]. Therefore, analytical solutions are highly sought-after because (i) they provide valuable insights into **fundamental physics**, as they are free of numerical errors and (ii), although limited to simplified situations; they allow validation of more complex numerical codes.

In the context of interference pumping tests in fractured porous media, an analytical solution has been developed for homogenous aquifers by De Smedt [8]. Furthermore, Delay et al. [7] developed a numerical solution using the dual-medium approach to describe radial convergent flow in heterogeneous fractal media where power laws in space are used for the hydrodynamic parameters. As a consequence, parameter values decrease with the distance between the pumped well and the observed ones. This type of scaling laws inherits from theoretical works on fractals [11] and has been used by several authors for single porous media ([12-15], among others). Hence, the main objective of this paper is to develop, for the first time, an analytical solution for the mathematical model describing interference pumping tests in heterogeneous

fractal dual media. Applicability of the model is then assessed by investigating identifiability of the different parameters from a synthetic pumping test with a set of noisy data using Statistical Calibration (SC) [16]. The latter means refining the prior distribution of uncertain parameters based on matching simulation outputs with data [17]. In this work, the SC is performed with the DREAM_(ZS) software [16] based on the Markov Chain Monte Carlo process (MCMC). DREAM_(ZS) computes multiple sub-chains in parallel to thoroughly explore the parameter space. Taking the last 25% of individuals of the MCMC (when the chains have converged) yields multiple sets of parameters that adequately fit the model onto observations. These sets can then be used to estimate the updated parameter distributions and therefore the best estimates of the parameters and the associate confidence intervals.

2 MATHEMATICAL MODEL

We assume a horizontal, isotropic, confined and infinite aquifer with a uniform thickness. The pumping well only draws water from the fractures, has a constant rate and fully penetrates the aquifer. Using the dual-porosity concept, the flow in fractured porous media can be described by the following equations [18, 19]:

$$S_f \frac{\partial h_f}{\partial t} = \nabla \cdot (K_f \nabla h_f) + \alpha (h_m - h_f) \quad (1)$$

$$S_m \frac{\partial h_m}{\partial t} = \alpha (h_f - h_m) \quad (2)$$

where indexes m and f refer to the matrix and fracture continua, respectively, $S[L^{-1}]$ is the specific storage, $h[L]$ is the hydraulic head, $K_f[LT^{-1}]$ is the hydraulic conductivity of the fractures, $\alpha[L^{-1}T^{-1}]$ is the exchange rate coefficient between the fractures and the matrix. Following Warren and Root [18], equation (2) assumes pseudo-steady flow in the matrix con-

tinuum (term K_m is removed). Assuming radial symmetry, equations (1) and (2) can be formulated as:

$$S_f(r) \frac{\partial h_f(r,t)}{\partial t} = \frac{1}{r} \frac{\partial}{\partial r} \left[r K_f(r) \frac{\partial h_f(r,t)}{\partial r} \right] + \alpha(r) [h_m(r,t) - h_f(r,t)] \quad (3)$$

$$S_m(r) \frac{\partial h_m(r,t)}{\partial t} = \alpha(r) [h_f(r,t) - h_m(r,t)] \quad (4)$$

where $r[L]$ is the radial coordinate with the center of the pumping well as origin.

The drawdown in an observation well intercepting the fractures can be expressed as follows

$$S_f(r) \frac{\partial H_f(r,t)}{\partial t} = \frac{1}{r} \frac{\partial}{\partial r} \left(r K_f(r) \frac{\partial H_f(r,t)}{\partial r} \right) + \alpha(r) [H_m(r,t) - H_f(r,t)] \quad (5)$$

$$S_m(r) \frac{\partial H_m(r,t)}{\partial t} = \alpha(r) [H_f(r,t) - H_m(r,t)] \quad (6)$$

where $H_f = h_0 - h_f$ and $H_m = h_0 - h_m$ are respectively the drawdown in the fracture and in the rock matrix. Initially, a uniform hydraulic head (h_0) is assumed in both the fracture and matrix continua. Therefore, the drawdowns satisfy the following initial conditions:

$$H_f(r,0) = H_m(r,0) = 0 \quad (7)$$

Far away from the pumping well, the drawdowns are assumed to be zero

$$\lim_{r \rightarrow \infty} H_f(r,t) = \lim_{r \rightarrow \infty} H_m(r,t) = 0 \quad (8)$$

The limit where the radius approaches zero corresponds to the well withdrawal rate

$$\lim_{r \rightarrow 0} \left[-2\pi r B K_f(r) \frac{\partial H_f(r,t)}{\partial r} \right] = Q_0, \quad t > 0 \quad (9)$$

where B is the thickness of the aquifer and Q_0 is the pumping flow rate.

In the sequel, we limit our investigation for the semi-analytical solution of equations (5-9) to the case of a confined reservoir of a fractal structure with a single well in an unbounded me-

dium as described in [7, 12]. Note that more complex fractal approaches have been developed in the case of many wells with variable rates [20] and by considering transient flow from block to fissure and skin between the fissure and the block [21].

In this work, following Delay *et al.* [7], we consider dual porosity media in which the hydrodynamic parameters are power-law functions in space (decreasing functions of the radial distance r between the pumping well and the observed one). Moreover, for sake of simplicity, we assume the same functions for the exchange rate coefficient α and for the storage coefficients S_f and S_m . Hence, the values of the hydraulic parameters vary with respect to radial distance according to the following power-law functions:

$$\begin{aligned} K_f(r) &= K_{f_0} r^{-a}; & S_f(r) &= S_{f_0} r^{-b} \\ S_m(r) &= S_{m_0} r^{-b}; & \alpha(r) &= \alpha_0 r^{-b} \end{aligned} \quad (10)$$

where the power-law exponents a and b are assumed to be positive.

3 ANALYTICAL SOLUTION

3.1 Analytical solution in the Laplace domain

In this section, we follow the strategy developed by De Smedt [8] to derive the analytical solution of the system formed by equations (5)-(10). The solution is derived using the Laplace transform technique with respect to time variable t . The Laplace transform of a time-dependent function y is

$$\bar{y}(p) = L[y(t); t \rightarrow p] = \int_0^{\infty} y(t) e^{-pt} dt \quad (11)$$

Applying the Laplace transform to (5)-(6) and using (10) leads to

$$pS_{f_0} r^{-b} \bar{H}_f(r, p) = \frac{K_{f_0}}{r} \frac{\partial}{\partial r} \left[r^{1-a} \frac{\partial \bar{H}_f(r, p)}{\partial r} \right] + \alpha_0 r^{-b} [\bar{H}_m(r, p) - \bar{H}_f(r, p)] \quad (12)$$

$$pS_{m_0} \bar{H}_m(r, p) = \alpha_0 [\bar{H}_f(r, p) - \bar{H}_m(r, p)] \quad (13)$$

Equation (13) can be rearranged

$$\bar{H}_m(r, p) = \frac{\alpha_0 / S_{m_0}}{p + \alpha_0 / S_{m_0}} \bar{H}_f(r, p) \quad (14)$$

Substituting (14) into (12) yields

$$r^2 \frac{\partial^2 \bar{H}_f}{\partial r^2} + (1-a)r \frac{\partial \bar{H}_f}{\partial r} - \frac{S_{f_0}}{K_{f_0}} \left[p + \frac{(\alpha_0 / S_{f_0}) p}{p + \alpha_0 / S_{m_0}} \right] r^{a-b+2} \bar{H}_f = 0 \quad (15)$$

Equation (15) is a second order ordinary differential equation; its general solution is of the form (cf. Polyanin and Zaitsev [22], page 159, equation (127))

$$\bar{H}_f(r, p) = r^{\frac{a}{2}} \left\{ C_1 J_\nu \left[\frac{2i S_{f_0}^{1/2} r^{n/2}}{n K_{f_0}^{1/2}} \sqrt{A(p)} \right] + C_2 Y_\nu \left[\frac{2i S_{f_0}^{1/2} r^{n/2}}{n K_{f_0}^{1/2}} \sqrt{A(p)} \right] \right\} \quad (16)$$

where $n = a - b + 2$, $\nu = \frac{a}{n}$, $A(p) = p + \frac{(\alpha_0 / S_{f_0}) p}{p + \alpha_0 / S_{m_0}}$, $J_\nu(z)$ and $Y_\nu(z)$ are the Bessel functions

of the first and second kinds, respectively. The parameters C_1 and C_2 are constant that can be calculated using boundary conditions.

In the Laplace domain, the boundary conditions become

$$\lim_{r \rightarrow \infty} \bar{H}_f(r, p) = 0 \quad (17)$$

and

$$\lim_{r \rightarrow 0} \left[-2\pi B K_{f_0} r^{1-a} \frac{\partial \bar{H}_f(r, p)}{\partial r} \right] = \frac{Q_0}{p} \quad (18)$$

The solution of (15), taking into account the boundary conditions (17) and (18) is

$$\bar{H}_f(r, p) = \frac{2r^{\frac{a}{2}}}{n^{1-\nu} \pi \Gamma(1-\nu) B K_{f_0}^{1-\nu/2} S_{f_0}^{\nu/2}} \frac{\bar{Q}(p) K_\nu \left[\frac{2 S_{f_0}^{1/2} r^{n/2}}{n K_{f_0}^{1/2}} \sqrt{p + \frac{(\alpha_0 / S_{f_0}) p}{p + \alpha_0 / S_{m_0}}} \right]}{\left[\sqrt{p + \frac{(\alpha_0 / S_{f_0}) p}{p + \alpha_0 / S_{m_0}}} \right]^\nu} \quad (19)$$

where K_ν is the modified Bessel function of the second kind of order ν . More details about the derivation of the solution (19) are given in the Appendix.

3.2 Analytical solution in the time domain

The solution in the time domain $H_f(r, t)$ is sought using the convolution theorem of the Laplace transform [23]

$$L\left[\int_0^t y(\tau, t-\tau) d\tau; t \rightarrow p\right] = L\{L[y(t_1, t_2); t_2 \rightarrow p]; t_1 \rightarrow p\} \quad (20)$$

Hence, equation (19) is written as

$$\bar{H}_f(r, p) = \bar{H}_f(r; p_1, p_2) = \frac{2Q_0 r^{\frac{a}{2}}}{n^{1-\nu} \pi \Gamma(1-\nu) B K_{f_0}^{1-\nu/2} S_{f_0}^{\nu/2}} \frac{K_\nu \left[\frac{2S_{f_0}^{1/2} r^{n/2}}{nK_{f_0}^{1/2}} \sqrt{p_1 + \frac{(\alpha_0 / S_{f_0}) p_2}{p_2 + \alpha_0 / S_{m_0}}} \right]}{p_2 \left[\sqrt{p_1 + \frac{(\alpha_0 / S_{f_0}) p_2}{p_2 + \alpha_0 / S_{m_0}}} \right]^\nu} \quad (21)$$

where $p_1 = p_2 = p$ but different indexes are used to indicate that the inverse transformation is performed in two steps.

The different indexes used in (21) indicate that the inverse Laplace transform is developed in two steps. In a first step, the inverse Laplace transform with respect to the variable p_1 is expressed as follows

$$L^{-1}[\bar{H}_f(r; p_1, p_2); p_1 \rightarrow t_1] = \frac{n^\nu Q_0 e^{-\frac{S_{f_0} r^n}{2n^2 K_{f_0} t_1}} \cdot W_{\frac{1-\nu}{2}, \frac{\nu}{2}} \left(\frac{S_{f_0} r^n}{n^2 K_{f_0} t_1} \right)}{\pi \Gamma(1-\nu) B K_{f_0}^{\frac{1-\nu}{2}} S_{f_0}^{\frac{\nu}{2}} r^{\frac{2-b}{2}}} \cdot \frac{e^{-\frac{(\alpha_0 / S_{f_0}) t_1 p_2}{p_2 + \alpha_0 / S_{m_0}}}}{p_2} \quad (22)$$

where t_1 is the time variable obtained by the inverse Laplace transform with respect to the variable p_1 and $W_{\kappa, \mu}(z)$ is the Whittaker function (Abramowitz and Stegun [24] p. 505).

In the second step, the inverse Laplace transform with respect to p_2 is obtained using the in-

verse transform of the J -function [25] based on the formula $L^{-1}\left[\frac{1}{p}e^{-\frac{\alpha p}{p+\beta}}; p \rightarrow t\right] = J(\alpha, \beta t)$

which yields

$$\bar{H}_f(r; p_1, p_2) = \frac{n^\nu Q_0 e^{-\frac{S_{f_0} r^n}{2n^2 K_{f_0} t_1}} \cdot t_1^{\frac{\nu-1}{2}} \cdot W_{\frac{1-\nu}{2}, \frac{\nu}{2}}\left(\frac{S_{f_0} r^n}{n^2 K_{f_0} t_1}\right) \cdot J\left(\frac{\alpha_0 t_1}{S_{f_0}}, \frac{\alpha_0 t_2}{S_{m_0}}\right)}{2\pi\Gamma(1-\nu)BK_{f_0}^{\frac{1-\nu}{2}}S_{f_0}^{\frac{1+\nu}{2}}r^{\frac{2-b}{2}}} \quad (23)$$

The Bessel integral J -function is defined as follows [8, 26]

$$J(a, b) = 1 - e^{-b} \int_0^a e^{-\lambda} I_0(2\sqrt{b\lambda}) d\lambda = e^{-a-b} \sum_{n=0}^{\infty} \frac{b^n}{n!} \sum_{m=0}^n \frac{a^m}{m!} \quad (24)$$

In view of (20) and (23), the analytical expression of $H_f(r, t)$ is

$$H_f(r, t) = \frac{n^\nu Q_0}{2\pi\Gamma(1-\nu)BK_{f_0}^{\frac{1-\nu}{2}}S_{f_0}^{\frac{1+\nu}{2}}r^{\frac{2-b}{2}}} \int_0^t \tau^{\frac{\nu-1}{2}} \cdot e^{-\frac{S_{f_0} r^n}{2n^2 K_{f_0} \tau}} \cdot W_{\frac{1-\nu}{2}, \frac{\nu}{2}}\left(\frac{S_{f_0} r^n}{n^2 K_{f_0} \tau}\right) \cdot J\left(\frac{\alpha_0 \tau}{S_{f_0}}, \frac{\alpha_0 (t-\tau)}{S_{m_0}}\right) d\tau \quad (25)$$

A similar expression can be obtained for $H_m(r, t)$ using the convolution theorem of the Laplace transform for equation (14) and using equation (19).

In the case of homogeneous media ($a = b = 0$), we have $W_{\frac{1}{2}, 0}(z) = z^{\frac{1}{2}} e^{-\frac{z}{2}}$ and (25) reduces to

the De Smedt [8] solution:

$$H_f(r, t) = \frac{Q_0}{4\pi BK_{f_0}} \int_0^t \tau^{-1} e^{-\frac{S_{f_0} r^2}{4K_{f_0} \tau}} \cdot J\left(\frac{\alpha_0 \tau}{S_{f_0}}, \frac{\alpha_0 (t-\tau)}{S_{m_0}}\right) d\tau \quad (26)$$

4 COMPARISON TO NUMERICAL SOLUTIONS

We numerically solve two interference pumping tests dealing with homogeneous and fractal dual media. For each test, the numerical solution is compared against the corresponding analytical solution using (25). The numerical solution of the system (5)-(10) is developed using the standard Finite Volume (FV) method. The domain of size $L=10,000m$ is discretized using a uniform spatial discretization of size $\Delta r = 5$ m. A similar solution is obtained using a finer spatial discretization of size $\Delta r = 1$ m which shows the weak sensitivity of the numerical solution to the spatial discretization. The duration of the simulation is 2×10^6 s. Three time step sizes are investigated with $\Delta t = 10^5$ s, $\Delta t = 5 \times 10^4$ s and $\Delta t = 10^4$ s. The pumping flow rate is $Q_0 = 5$ m³/h. The initial head in the aquifer is $h_0 = 100$ m and the aquifer thickness is $B = 100$ m. The specific storage of the fractures and rock matrix are respectively $S_{f_0} = 5 \times 10^{-6}$ m⁻¹ and $S_{m_0} = 10^{-4}$ m⁻¹. The hydraulic conductivity of the fractures is $K_{f_0} = 10^{-4}$ m/s and the rate of exchange between the matrix and the fractures is $\alpha_0 = 5 \times 10^{-11}$ m⁻¹s⁻¹.

Figure 1 depicts the drawdown in both the fracture and matrix at 10m and 100m. The drawdown in the fissure starts at early times because storage of the fissures is immediately effective at the start of the pumping test, while storage of the matrix needs much more time to become noticeable. A flattening of the drawdown curve in the fissure can be observed at intermediate pumping time which is typical for double-porosity behavior because of the transition from fracture to matrix water storage release.

The numerical FV solution is compared to the analytical solution (25) in the case of homogeneous ($a = b = 0$) and fractal ($a = 0.6$ and $b = 0.4$) dual media. The comparison is performed at two observation wells located respectively at distances $r_1 = 10$ m and $r_2 = 100$ m from the pumping well. Significant discrepancies can be observed between analytical and numerical

solutions when the latter is evaluated using a large time step size (Figure 2). The drawdown in the case of fractal dual media is larger than in homogeneous dual media because of the reduction of the hydrodynamic parameters with the distance r from the pumping well. In fact, in the case of fractal dual media, the permeability of the fractures is proportional to $r^{-0.6}$ whereas the exchange rate and the specific storage of both the fractures and the matrix are proportional to $r^{-0.4}$. Thereby, the discrepancy between analytical and numerical solutions (Figure 2) is more pronounced with dual fractal media than with homogeneous dual media. For both homogeneous and fractal dual media, the numerical solution converges toward the analytical solution (25) when the size of the time step decreases (Figure 2). Note that the reduction of the permeability of the fractures with respect to the distance r is also responsible, via the Whittaker function in equation (25), of the delay for the stabilisation of the solution in the fractal case (Figure 2 b) compared to the homogeneous case (Figure 2a).

5 BAYESIAN INVERSION OF A PUMPING TEST IN FRACTAL DUAL MEDIA

In practical applications, most of the hydraulic parameters cannot be measured directly and should be estimated using an inversion procedure. In the case of fractal dual media, the inversion can be challenging because of model equifinality, implying that different parameter combinations can fit the model responses to data. To assess the applicability of the fractal dual porosity model, the identifiability of the parameters of the analytical solution (25) is assessed using a synthetic interference pumping test with a set of noisy data. Parameter identification is performed in a Bayesian framework where the prior knowledge about the parameters and the observed data are merged to define the joint posterior probability distribution function (pdf) of the parameters. In this work, the pdf is performed using the DREAM_(ZS) software [16] based on the Markov Chain Monte Carlo (MCMC) sampler. DREAM_(ZS) generates random sequences of parameter sets that asymptotically converge toward the target joint posterior dis-

tribution [27]. Thus, if the number of runs is sufficiently high, the generated samples allows exploring the entire parameter space of the posterior distribution of the parameters and provides the pairwise parameter correlations and the uncertainty of model predictions.

The Bayes theorem states that the probability density function of the model parameters conditioned onto data can be expressed as:

$$p(\xi | \mathbf{y}_{mes}) \propto p(\mathbf{y}_{mes} | \xi) p(\xi), \quad (27)$$

where $p(\xi | \mathbf{y}_{mes})$ is the likelihood function measuring how well the model fits the observations $\mathbf{y}_{mes}$, and $p(\xi)$ is the prior information about the parameter before the observations are made. In this work, a Gaussian distribution defines the likelihood function because the observations are simulated and corrupted with Gaussian errors. Hence, the parameter posterior distribution is expressed as:

$$p(\xi | \mathbf{y}_{mes}) \propto \sigma_h^{-N_h} \exp\left(-\frac{SS_h(\xi)}{2\sigma_h^2}\right), \quad (28)$$

where $SS_h(\xi)$, are the sums of the squared differences between the observed and modeled drawdowns. For instance, $SS_h(\xi) = \sum_{k=1}^{N_h} \left(h_{mes}^{(k)} - h_{mod}^{(k)}(\xi)\right)^2$, which includes the observed $h_{mes}^{(k)}$ and predicted $h_{mod}^{(k)}$ drawdowns at time t_k for the number of observations N_h .

A synthetic pumping test is generated by running the analytical solution using the reference parameter values given in Table 1 for K_{f_0} , S_{f_0} , α_0 , a and b . As in Fahs *et al.* [28], the storage coefficient in the matrix S_{m_0} is fixed in this study to be 10^{-4} m⁻¹.

Delay *et al* [7] showed that results of calibration improved when several drawdown curves at several locations are inverted at once. In the sequel, the analytical solution is run for a long period of 2×10^7 s to calculate the drawdown at four observation wells located respectively at $r_1 = 1$ m, $r_2 = 10$ m, $r_3 = 100$ m and $r_4 = 500$ m from the pumping well. Four datasets of 2000

values each (corresponding to the drawdown at the observation wells measured each 10^4 s) are used as target responses for model inversion.

Gaussian noise with a standard deviation of 0.01m and a mean of zero was added to the target responses. We assume that all hydraulic parameters have uniform prior distributions over the ranges given in Table 1. As recommended in Vrugt *et al.* [29], we consider that the posterior distribution is stationary if the Gelman and Ruban [30] criterion is less than 1.2 and that the chains are not autocorrelated.

The MCMC method was terminated after 15000 model runs. The convergence was reached at around 10000 model runs.

Figure 3 shows the results of the identification based on the last 25% of individuals of the MCMC sampler (when the chains have converged). The "on-diagonal" plots in these figures display the inferred parameter distributions, whereas the "off-diagonal" plots represent the pairwise correlations in the MCMC sample. If the drawings are independent, non-sloping scatterplots should be observed. However, if a good value of a given parameter is conditioned by the value of another parameter, then their pairwise scatterplot should show a narrow sloping stripe. The results of Figure 3 show that the five parameters K_{f_0} , S_{f_0} , α_0 , a and b are appropriately estimated; they have almost symmetric bell-shaped posterior distributions and have strongly narrowed their prior intervals. The scatter plots in this figure show a moderate correlation between the parameters a and b (a correlation factor of 0.61), a high correlation between the parameters S_{f_0} and b (a correlation factor of 0.79) and a very high correlation between the parameters K_{f_0} and a (a correlation factor of 0.98). The mean and 95% confidence intervals of the samples that adequately fit the model onto observations are reported in Table 2. From this table, we can see that the parameters K_{f_0} , a and b are well identified with respectively a mean value of $0.99 \times 10^{-5} \text{ ms}^{-1}$, 0.299 and 0.2. These values are almost identical to the reference values of Table 1. The uncertainty on these

parameters is small since the 95% confidence intervals are respectively $[0.9-1.1]\times 10^{-5} \text{ ms}^{-1}$, $[0.28-0.32]$ and $[0.17-0.23]$. The parameters S_{f_0} and α_0 are less well identified. Indeed, although their mean values (respectively $5.03\times 10^{-5} \text{ m}^{-1}$ and $3.06\times 10^{-11} \text{ m}^{-1}\text{s}^{-1}$) are very close to the reference values, their posterior uncertainty remains quite large since their confidence intervals are respectively $[3.2-7.6]\times 10^{-5} \text{ m}^{-1}$ and $[2.1-4.5]\times 10^{-11} \text{ m}^{-1}\text{s}^{-1}$. Finally note that the identification procedure does not converge if the storage coefficient in the matrix S_{m_0} is involved in the inversion procedure (not fixed). In that case, the identification of the six parameters K_{f_0} , S_{f_0} , S_{m_0} , α_0 , a and b was not possible. Indeed, in this case, the MCMC algorithm was faced to convergence problem because of **equifinality** issues.

6 CONCLUSION

A new analytical solution for interference hydraulic pumping tests in fractal fractured porous media is developed using the dual-porosity concept and power laws in space for all hydrodynamic parameters. The developed analytical solution is compared to a numerical one obtained with the FV method using different time step sizes. Discrepancies are observed between analytical and numerical solutions when the latter is used with large time steps. These discrepancies are more pronounced with dual fractal media than with homogeneous dual media. When the size of the time step decreases, the numerical solution converges toward the analytical one for both homogeneous and fractal dual media.

The applicability of the fractal dual-porosity model was then assessed by investigating identifiability of the hydraulic parameters from a synthetic interference pumping test with a set of noisy data using the MCMC sampler. The results show that if the storage coefficient in the

288 matrix is fixed, the rest of the parameters can be appropriately identified, whereas conver-
289 gence problems can be encountered if all the hydraulic parameters are to be estimated.

290

291 **Acknowledgements**

292 This work was partially supported by the GdR MoMaS (PACEN/CNRS, ANDRA, BRGM,
293 CEA, EDF, IRSN) France and by the French National Research Agency (ANR) through the
294 program AAP Blanc - SIMI 6 project RESAIN (n°ANR-12-BS06-0010-02).

295

296

297 **Appendix: Derivation of the Analytical Solution in the Laplace Domain**

298

299 Using the boundary condition at infinity (17) and the following asymptotic expansions for

300 large arguments ($|z| \rightarrow \infty$) of J_ν and Y_ν [22], $J_\nu(z) = \sqrt{2/\pi z} \{P(\nu, z) \cos \chi - Q(\nu, z) \sin \chi\}$

301 and $Y_\nu(z) = \sqrt{2/\pi z} \{P(\nu, z) \cos \chi + Q(\nu, z) \sin \chi\}$ for $|\arg z| < \pi$ with $\chi = z - \left(\frac{1}{2}\nu + \frac{1}{4}\right)\pi$,

302 $P(\nu, z) = \sum_{k=0}^{\infty} (-1)^k \frac{(\nu, 2k)}{(2z)^{2k}}$ and $Q(\nu, z) = \sum_{k=0}^{\infty} (-1)^k \frac{(\nu, 2k+1)}{(2z)^{2k+1}}$, equation (16) gives

303 $C_1 + iC_2 = 0$. Therefore, this latter can be written as

$$304 \quad \bar{H}_f(r, p) = C_1 r^{\frac{a}{2}} H_\nu^{(1)} \left[\frac{2iS_{f_0}^{1/2} r^{n/2}}{nK_{f_0}^{1/2}} \sqrt{A(p)} \right] \quad (\text{A.1})$$

305 where $H_\nu^{(1)}$ is the Hankel function of the first kind defined by $H_\nu^{(1)}(z) = J_\nu(z) + iY_\nu(z)$ for

306 any complex number z .

307 The boundary condition at the well (18) is then used to find C_1 . Note that for $\nu > 0$ the

308 Hankel function $H_\nu^{(1)} \sim -\frac{i}{\pi} \Gamma(\nu) \left(\frac{1}{2}z\right)^{-\nu}$ as z approaches zero [22], where Γ is the Gamma

309 function. Using this expansion we can write

$$310 \quad r^{1-a} \frac{\partial H_f(r, t)}{\partial r} \sim \frac{i^{1-\nu} S_{f_0}^{\nu/2} C_1}{2\pi K_{f_0}^{\nu/2}} \left\{ -r^{-a} n^\nu \left[\sqrt{A(p)} \right]^{-\nu} \{a\Gamma(\nu) - n\Gamma(1+\nu)\} + n^{1-\nu} \left[\sqrt{A(p)} \right]^\nu \Gamma(1-\nu) \right\}$$

311 (A.2)

312 as r approaches zero. Using the property of the Gamma function $\Gamma(1+\nu)=\nu\Gamma(\nu)$ for $\nu > 0$,

313 the first term of right hand side of equation (A.2) vanishes since $n\nu=a$. Substituting (A.2)

314 into (18) we get $C_1 = -\frac{\bar{Q}(p)}{i^{1-\nu}n^{1-\nu}\Gamma(1-\nu)BK_{f_0}^{1-\nu/2}S_{f_0}^{\nu/2}\left[\sqrt{A(p)}\right]^\nu}$.

315 Finally, inserting the value of C_1 into (A.1) and using the relationship

316 $K_\nu(z) = \frac{1}{2}\pi i e^{\frac{1}{2}\nu\pi i} H_\nu^{(1)}\left(ze^{\frac{1}{2}\pi i}\right)$ for $-\pi < \arg z \leq \frac{1}{2}\pi$, where K_ν is the modified Bessel func-

317 tion of the second kind of order ν , we get the solution in the Laplace domain as defined by

318 (19).

319

320

321 **REFERENCES**

- 322 [1] Hsieh, P.A.: A brief survey of hydraulic tests in fractured rocks. In Faybishenko B,
323 Witherspoon PA, Benson SM (eds.) Dynamics of fluids in fractured rocks, American
324 Geophysical Union Geophysical Monograph 122:59–66 (2000).
- 325 [2] Kruseman, G.P., de Ridder, N.A.: Analysis and evaluation of pumping test data. Inter-
326 national Institute for Land Reclamation and Improvement Publication, Wageningen
327 (1991).
- 328 [3] Batu, V.: Aquifer Hydraulics: a comprehensive guide to hydrogeologic data analysis.
329 John Wiley & Sons Inc. New York (1998).
- 330 [4] Cheng, A.H.D.: Multilayered aquifer systems fundamentals and applications. Marcel
331 Dekker, New York/Basel (2000).
- 332 [5] Walton, W.C.: Aquifer test modelling. CRC press, Taylor & Francis Group, Boca Raton
333 (2006).
- 334 [6] Nielsen, K.A.: Fractured aquifers formation evaluation by Well Testing. Trafford Pub-
335 lishing, Canada (2007).
- 336 [7] Delay, F., Kaczmaryk, A., Ackerer, P.: Inversion of interference hydraulic pumping
337 tests in both homogeneous and fractal dual media. Adv. in Water Resour. 30(3):314-
338 334. (2007) doi:10.1016/j.advwatres.2006.06.008
- 339 [8] De Smedt, F.: Analytical solution Analytical Solution for Constant-Rate Pumping Test
340 in Fissured Porous Media with Double-Porosity Behaviour. Transp Porous Med.
341 88:479-489 (2011). doi:10.1007/s11242-011-9750-9.
- 342 [9] Barenblatt, G.E., Zheltov, I.P., Kochina, I.N.: Basis concepts in the theory of seepage of
343 homogeneous liquids in fissured rocks. J. Appl. Math. Mech. Engl. Transl. 24(5):1286–
344 1303 (1960). doi:10.1016/0021-8928(60)90107-6.

- 345 [10] Zhan, H., Wen, Z., Gao, G.: An analytical solution of two-dimensional reactive solute
346 transport in an aquifer aquitard system. *Water Resour. Res.* 45, W10501. (2009).
347 doi:10.1029/2008WR007479
- 348 [11] O'Shaughnessy, B., Procaccia, I.: Diffusion in fractals. *Phys Rev A.* ;32:3073 (1985)
349 doi:10.1103/PhysRevA.32.3073
- 350 [12] Acuna, J.A., Yortsos, Y.C.: Application of fractal geometry to the study of networks of
351 fractures and their pressure transient. *Water Resour Res*; 31(3):527–40 (1995). doi:
352 10.1029/94WR02260
- 353 [13] Chang, J., Yortsos, Y.C.: Pressure-transient analysis of fractal reservoirs. *Soc Petrol Eng*
354 J 18710:631–43 (1990) doi:10.2118/18170-PA.
- 355 [14] Delay, F., Porel, G., Bernard, S.: Analytical 2D model to invert hydraulic pumping tests
356 in fractured rocks with fractal behavior. *Geophys Res Lett.* 31(16) (2004).
357 doi:10.1029/2004GL020500.
- 358 [15] Le Borgne, T., Bour, O., de Dreuzay, J.R., Davy, P., Touchard, F.: Equivalent mean flow
359 models for fractured aquifers: insights for a pumping test scaling interpretation. *Water*
360 *Resour Res*;40(3) (2004). doi:10.1029/2003WR002436.
- 361 [16] Laloy, E., Vrugt, J.A.: High-dimensional posterior exploration of hydrologic models
362 using multiple-try DREAM(ZS) and high-performance computing, *Water Resour. Res.*,
363 48 W01526. (2012). doi:10.1029/2011WR010608.
- 364 [17] Campbell, K.: Statistical calibration of computer simulations, *Reliability Engineering*
365 *and System Safety* 91 1358–1363 (2006). doi:10.1016/j.ress.2005.11.032
- 366 [18] Warren, J.E., Root, P.J.: The behavior of naturally fractured reservoirs. *Soc Petrol Eng*
367 3:245–55. (1963). doi:10.2118/426-PA.
- 368 [19] Moench, A.F.: Double-porosity models for a fissured groundwater reservoir with frac-
369 ture skin. *Water Resour. Res.* 20(7):831–846. (1984). doi:10.1029/WR020i007p00831.
- 370 [20] Chang, J., Yortsos, Y. C. A Note On Pressure-Transient Analysis Of Fractal Reservoirs.
371 Society of Petroleum Engineers. (1993). doi:10.2118/25296-PA

- 372 [21] Hamm, S.Y., Bidaux, P. Dual-porosity fractal models for transient flow analysis in fis-
373 sured rocks: *Water Resources Research*, v. 32, no. 9, p. 2733-2745 (1996).
- 374 [22] Polyanin, A.D., Zaitsev, V.F. *Handbook of Exact Solutions for Ordinary Differential*
375 *Equations*, 2nd ed., 787 pp., Chapman and Hall/ CRC, Boca Raton, Fla (2003).
- 376 [23] Sneddon, I.H.: *The Use of Integral Transforms*, McGraw-Hill, New York (1972).
- 377 [24] Abramowitz, M., Stegun, I.A. *Handbook of Mathematical Functions With Formulas,*
378 *Graphs, and Mathematical Tables*, Government Printing Off., Washington, D. C.
379 (1972).
- 380 [25] Goldstein, F.R.S.: On the mathematics of exchange processes in fixed columns I: Math-
381 ematical solutions and asymptotic expansions. *Proc. R. Soc. London* 219: 151-185.
382 (1953).
- 383 [26] De Smedt, F., Wierenga, P.J.: A generalized solution for solute flow in soils with mobile
384 and immobile water. *Water Resour. Res.* 15(5): 1137-1141. (1979). doi:
385 10.1029/WR015i005p01137.
- 386 [27] Gelman, A., Carlin, J.B., Sten, H.S., Rubin, D.B. *Bayesian data analysis* (1997), Chap-
387 mann and Hall, London.
- 388 [28] Fahs, H., Hayek, M., Fahs, M., Younes, A.: An efficient numerical model for hydrody-
389 namic parameterization in 2D fractured dual-porosity media. *Adv. Water Resour.* 63:
390 179-193. (2013). doi: 10.1016/j.advwatres.2013.11.008
- 391 [29] Vrugt, J.A., Gupta, H.V., Bouten, W., Sorooshian, S. A shuffled complex evolution Me-
392 tropolis algorithm for optimization and uncertainty assessment for hydrologic model pa-
393 rameters. *Water Resour. Res.* 39(8):1201 (2003), doi:10.1029/2002WR001642.
- 394 [30] Gelman, A., Rubin, D.B. Inference from iterative simulation using multiple sequences.
395 *Stat. Sci.* 7:457-472 (1992). doi: 10.1214/ss/1177011136
396

397

398

399 **List of Tables**

400 Table 1: Reference values, lower and upper bounds of the parameters for a synthetic pumping
401 test case in fractal dual media.

402 Table 2: Mean values and 95% confidence intervals for the parameters estimated with the
403 MCMC sampler.

404

405

406 **List of Figures**

407 Figure 1: Drawdown versus time curves for a pumping test in homogeneous and fractal dual
408 media.

409 Figure 2: Comparison between analytical and numerical solutions in the case of (i) homoge-
410 neous and (ii) fractal dual media.

411 Figure 3: MCMC solutions of the interference pumping test in fractal dual media. The diago-
412 nal plots represent the inferred posterior probability distribution of model parameters. The off-
413 diagonal scatterplots represent the value of a parameter α versus that of a parameter β in the
414 best solutions inferred by MCMC.

415

416

417

Table 1

Parameters	Lower bounds	Upper bounds	Reference values
K_{f_0} [ms ⁻¹]	5×10^{-7}	5×10^{-4}	1×10^{-5}
S_{f_0} [m ⁻¹]	10^{-6}	10^{-3}	5×10^{-5}
α_0 [m ⁻¹ s ⁻¹]	10^{-12}	10^{-9}	3×10^{-11}
a [-]	0.1	0.5	0.3
b [-]	0.1	0.5	0.2

Table 2

Parameters	Mean	95% Conf. Int.
K_{f_0} [ms ⁻¹]	0.99×10 ⁻⁵	[0.9-1.1]×10 ⁻⁵
S_{f_0} [m ⁻¹]	5.03×10 ⁻⁵	[3.2-7.6]×10 ⁻⁵
α_0 [m ⁻¹ s ⁻¹]	3.06×10 ⁻¹¹	[2.1-4.5]×10 ⁻¹¹
a [-]	0.299	[0.28-0.32]
b [-]	0.2	[0.17-0.23]

Figure 1

Figure 2

Figure 3