An analytical approximation for the I-V characteristic of the MISS device

J. Millán, F. Serra-Mestres, X. Aymerich-Humet

► To cite this version:

J. Millán, F. Serra-Mestres, X. Aymerich-Humet. An analytical approximation for the I-V characteristic of the MISS device. *Revue de Physique Appliquée*, 1982, 17 (7), pp.401-404. 10.1051/rphysap:01982001707040100 . jpa-00245013

HAL Id: jpa-00245013

<https://hal.science/jpa-00245013>

Submitted on 1 Jan 1982

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Classification
Physics Abstracts
73.40Q

An analytical approximation for the I - V characteristic of the MISS device (*) (**)

J. Millán, F. Serra-Mestres and X. Aymerich-Humet

Departamento de Electricidad y Electrónica, Universidad Autónoma de Barcelona, Bellaterra, Barcelona, Spain

(Reçu le 22 septembre 1981, révisé le 29 mars 1982, accepté le 8 avril 1982)

Résumé. — Dans ce travail on obtient une expression analytique valable pour la caractéristique I - V du dispositif MISS. Les équations du mécanisme de commutation tiennent compte de la conduction par effet résonnant à travers l'isolant. On déduit aussi le courant et la tension à la commutation.

Abstract. — A closed-form expression for the I - V characteristic of the MISS device is obtained from the equations that govern the switching mechanism by considering resonant tunnelling conduction through the insulator. Both switching current and voltage are also obtained.

1. Introduction. — The switching mechanism in Metal-Thin SiO_2 -Si (n or p)-Si (p^+ or n^+) (MISS) has been analysed by several authors [1, 2]. The switching in their structures is due to the punch-through mechanism (the depletion layer of the MIS diode goes up to the p-n depletion layer) for low epitaxial doping (N_E), whereas the avalanche is responsible for the switching in case of high N_E . Sarabayrouse [3], Habib [4, 5], Adan [6] and ourselves [7] have set up regenerative models which account qualitatively for the I - V characteristic. In these models current through the insulator is supported by a direct tunnelling conduction. However, experimental results [8, 10] show a current excess that is only explicable if one considers insulator thickness (δ) much smaller than the measured one.

2. Regenerative model formulation with resonant tunnelling conduction. — In order to explain the discrepancy between the observed current and the one deduced from the regenerative models involving direct tunnelling conduction, we have developed a model [11] based on the resonant tunnelling conduction which is supported by traps existing in the insulator at different energy levels.

In the following we describe the equations that govern the switching mechanism, to obtain an analytical expression for the j - V characteristic.

When resonant tunnelling conduction through the insulator is considered, the current densities of electrons and holes can be expressed by [12] :

$$j_n = C_n N_T \exp\left(-\frac{\beta}{2} \chi_n^{1/2} \delta\right) \exp(u_s - u_n) \times \{ \exp(u_M) - 1 \} \quad (1)$$

and

$$j_p = C_p N_T \exp\left(-\frac{\beta}{2} \chi_p^{1/2} \delta\right) \exp(u_n - E_G/kT) \times \exp(\xi_s - u_s) \{ 1 - \exp(-u_M - \xi_s) \} \quad (2)$$

where $C_n(C_p)$ depends on the structure parameters and is practically independent of the bias voltage ($C_n \simeq 9 \times 10^{-12}$ A.cm and $C_p \simeq 5 \times 10^{-12}$ A.cm for $N_E = 5 \times 10^{15}$ cm $^{-3}$ and $\delta = 30$ Å); N_T is the insulator trap density; $\beta = 1.025$ (eV) $^{-1/2}$ (Å) $^{-1}$ and $\chi_{n(p)}$ is the effective barrier for electrons (holes), when the two bands model is considered $\chi_n = 0.80$ eV and $\chi_p = 0.84$ eV. The potentials (normalized to kT/q) are represented in figure 1.

All the electrons, injected into the base (semiconductor epitaxial layer) through the insulator by means of the resonant tunnelling conduction, reach the p-n junction when the recombination process is neglected. The p-n junction, in turn, injects into the base a hole current which is γ times the electron current, γ being the injection factor at the p-n junction. The hole current reaches the SiO_2 -Si interface and flows through the insulator by resonant tunnel. The diffe-

(*) Work performed under the auspices of the « Comisión Asesora Científica y Técnica ».

(**) Communication présentée à l'ESSDERC 1981.

Fig. 1. — Energy diagram of the MISS structure in the high-impedance state.

rence between the metal and hole Fermi levels (E_{FM} and E_{FP}) (see Fig. 1) allows the flow of holes through the SiO_2 layer.

As the applied voltage increases, the electron barrier decreases with it and the electron current which reaches the p-n junction grows. Consequently, the hole current injected from the p-n junction to the SiO_2 -Si interface also grows given rise to a progressively strong inversion of this interface and a lowering of the electron barrier. This mechanism is responsible for the regenerate process [3].

In order to maintain the charge neutrality of the structure a decrease of the base depletion layer is necessary, therefore, voltage across the structure is reduced after switching.

According to this qualitative behaviour of the switching mechanism, the neutrality equation is essential to determine the switching point. When we consider neither electrostatic influence of the surface states nor charges in the insulator, the MIS charge neutrality equation is written as

$$\frac{\delta}{L_D} \frac{\epsilon_s}{\epsilon_i} \frac{u_s}{|u_s|} F(u_s, \xi_s) + u_i = 0 \quad (3)$$

where L_D is the extrinsic Debye's length; $\epsilon_s(\epsilon_i)$ is the semiconductor (insulator) permittivity and $F(u_s, \xi_s)$ represents the F -function for the MIS structure in case of non-equilibrium [13].

The feedback equation is

$$j_p = \gamma j_n \quad (4)$$

and the total current density is expressed by

$$j = j_n + j_p. \quad (5)$$

The expressions of the normalized potentials for the MIS diode (u_M) and for the device (u_A) are deduced from the MISS energy diagram (Fig. 1); their equations are :

$$u_M = u_i + u_n - \psi_{ms} - u_s \quad (6)$$

and

$$u_A = u_M + u_j \quad (7)$$

where $\psi_{ms} = \phi_{ms}/kT = (\phi_m - \chi_s)/kT$ and u_j is the normalized potential across the p-n junction.

3. The j - V characteristic. — From the formulation of the resonant tunnelling model described in the last section, one can deduce an approximated expression of the j - V characteristic.

It is known that, in order to observe the switching mechanism, the structure has to be biased so that the MIS diode be reversed-biased whereas the p-n junction remains forward-biased. In this case u_M and $u_M + \xi_s$ are much greater than unity; therefore, from (1), (2), (4) and (5) we obtain,

$$j = j_{AO} \exp(u_s + u_M) \quad (8)$$

and

$$j = j_{BO} \exp(\xi_s - u_s) \quad (9)$$

where

$$j_{AO} = (1 + \gamma) C_n N_T \exp\left(-\frac{\beta}{2} \chi_n^{1/2} \delta\right) \exp(-u_n) \quad (10)$$

and

$$j_{BO} = \frac{1 + \gamma}{\gamma} C_p N_T \times \exp\left(-\frac{\beta}{2} \chi_p^{1/2} \delta\right) \exp(u_n - E_G/kT) \quad (11)$$

or, according to (6) and (10),

$$j = j_{MO} \exp(u_i) \quad (12)$$

where

$$j_{MO} = (1 + \gamma) C_n N_T \exp\left(-\frac{\beta}{2} \chi_n^{1/2} \delta - \psi_{ms}\right). \quad (13)$$

Hence the SiO_2 -Si interface is depleted or inverted for the range of j we are dealing with, and accordingly, the F -function can be approximated by

$$F(u_s, \xi_s) = \{-u_s + \alpha \exp(\xi_s - u_s)\}^{1/2} \quad (13 \text{ bis})$$

where $\alpha = p_v/n_v$ is the relation between the hole and electron concentrations in the base bulk.

The surface potential expression is obtained from (9), (12) and the neutrality equation (3), yielding

$$u_s = \alpha \frac{j}{j_{BO}} - a \ln^2\left(\frac{j}{j_{MO}}\right) \quad (14)$$

where

$$a = \left(\frac{L_D \epsilon_1}{\delta \epsilon_s} \right)^2. \quad (15)$$

Consequently, substituting the insulator and surface potentials, obtained respectively from (12) and (14), in the device voltage (Eq. 7), the j - V expression is found :

$$u_A = a \ln^2 J + (n+1) \ln J - bJ + c \quad (16)$$

where the normalized current density J is given by

$$J = j/j_{MO} \quad (17)$$

n is the p-n junction ideality factor and

$$b = \gamma \frac{N_v}{N_c} \frac{C_n}{C_p} \exp \left\{ -\frac{\beta}{2} (\chi_n^{1/2} - \chi_p^{1/2}) \delta + u_n - \psi_{ms} \right\} \quad (18)$$

N_c and N_v being respectively the effective densities of states in the conduction and valence bands of the semiconductor and

$$c = u_n - \psi_{ms} + n \ln \frac{j_{MO}}{j_{jo}} \quad (19)$$

j_{jo} being the p-n saturation current density.

For sake of clarity, we remark that the $u_A(j)$ equation is not valid when the SiO_2 -Si interface is degenerated, the degeneration condition being

$$\frac{E_G}{kT} - u_n - \ln \frac{j}{j_{BO}} \leq 0. \quad (20)$$

An example of the j - V characteristic obtained from equation (16) is represented in figure 2.

As a consequence of the j - V characteristic, we can deduce the switching current density. Hence

Fig. 2. — The j - V characteristic according to resonant tunnelling formulation. Structure parameters : $N_E = 2 \times 10^{15} \text{ cm}^{-3}$, $N_T = 10^{18} \text{ cm}^{-3}$, $\phi_{ms} = 0.4 \text{ eV}$ and $\delta = 30 \text{ \AA}$.

$du_A/dj = 0$ at the switching point and, according to (16), the switching current verifies the following equation :

$$M \ln J^s - J^s + N = 0 \quad (21)$$

where J^s is the normalized current density at the switching point. M and N are given by

$$M = \frac{2a}{b} = \frac{kT}{q^2} \frac{\epsilon_i^2}{\epsilon_s \delta^2} \frac{1}{\gamma} \frac{C_p}{C_n N_v} \times \exp \left\{ \frac{\beta}{2} (\chi_n^{1/2} - \chi_p^{1/2}) \delta + \psi_{ms} \right\} \quad (22)$$

and

$$N = \frac{n+1}{b} = \frac{n+1}{\gamma} \frac{C_p}{C_n} \frac{N_E}{N_v} \times \exp \left\{ \frac{\beta}{2} (\chi_n^{1/2} - \chi_p^{1/2}) \delta + \psi_{ms} \right\}. \quad (23)$$

These two coefficients as well as the physical solutions of (21) are always positive. The diagram of figure 3 gives us information about the solutions of (21) in terms of the coefficients M and N .

Obviously we are interested in solutions $J^s > 1$ since the approximation performed on equations (8) and (9) are not longer valid for $J^s < 1$.

Fig. 3. — The solutions of equation (21) as a function of M and N .

The series sum

$$J^s = N + M \ln \{ N + M \ln (N + M \ln \dots) \} \quad (24)$$

is the solution $J_1^s > 1$ of equation (21) when $N > 1$, this value of N being usual within the range of the insulator thickness δ we are dealing with. The sum converges quickly for the values of N and M we are using, resulting in the normalized current density at the switching point.

Once the switching current is obtained from (24), the switching voltage can be deduced from the j - V characteristic of equation (16).

In the framework of this analytical model, the

influence of the structure parameters on the switching behaviour is easily found and, therefore, one can verify the physical mechanisms involved in the device behaviour.

4. Conclusions. — A closed-form expression for the j - V characteristic of the MISS device is obtained from the mathematical formulation of a regenerative model based on the resonant tunnelling conduction through the insulator.

From this j - V expression both switching current and voltage are found. Besides, it allows to determine the influence of the structure parameters on the switching behaviour.

References

- [1] EL-BADRY, A. and SIMMONS, J. G., *Solid State Electron.* **20** (1977) 963.
- [2] SIMMONS, J. G. and EL-BADRY, A., *Solid State Electron.* **20** (1977) 955.
- [3] SARRABAYROUSE, G., Thèse d'Etat (Sciences). Université Paul Sabatier, Toulouse, France (1978).
- [4] HABIB, S. E.-D. and SIMMONS, J. G., *Solid State Electron.* **22** (1979) 181.
- [5] HABIB, S. E.-D. and SIMMONS, J. G., *Solid State Electron.* **23** (1980) 497.
- [6] ADAN, A. and ZOLOGY, I., *Solid State Electron.* **23** (1980) 449.
- [7] MILLÁN, J., SERRA-MESTRES, F. and BUXÓ, J., *Revue Phys. Appl.* **14** (1979) 921.
- [8] CHIK, K. C. and SIMMONS, J. G., *Solid State Electron.* **22** (1979) 589.
- [9] BUXÓ, J., OWEN, A. E., SARRABAYROUSE, G. and SEBAA, J. P., *Revue Phys. Appl.* **13** (1978) 767.
- [10] MILLÁN, J., Ph. Thesis, Universidad Autónoma, Bellaterra Barcelona, Spain (1981).
- [11] MILLÁN, J., SERRA-MESTRES, F. and AYMERICH-HUMET, X., 11th European Solid State Device Research Conference ESSDERC 81, Toulouse, France (1981).
- [12] AYMERICH-HUMET, X. and SERRA-MESTRES, F., *Phys. State Solid (a)* **51** (1979) 583 ; **54** (1979) 655.
- [13] SZE, S. M., *Physics of semiconductor devices* (J. Wiley, New York) 1981.