Test of a recoil ion source at GANIL medium energy facility

A. Gosselin, P. Boduch, D. Hennecart, S. Hicham, X. Husson, D. Lecler, A. Lepoutre, A. Cassimi, J. Grandin

► To cite this version:

A. Gosselin, P. Boduch, D. Hennecart, S. Hicham, X. Husson, et al.. Test of a recoil ion source at GANIL medium energy facility. *Journal de Physique III*, 1994, 4 (9), pp.1765-1777. 10.1051/jp3:1994239 . jpa-00249223

HAL Id: jpa-00249223

<https://hal.science/jpa-00249223>

Submitted on 1 Jan 1994

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Classification

Physics Abstracts

34.50H — 34.70 — 41.80D

Test of a recoil ion source at GANIL medium energy facility

A. Gosselin ⁽¹⁾, P. Boduch ⁽¹⁾, D. Hennecart ⁽¹⁾, S. Hicham ⁽¹⁾, X. Husson ⁽¹⁾,
D. Lecler ⁽¹⁾, A. Lepoutre ⁽¹⁾, A. Cassimi ⁽²⁾ and J. P. Grandin ⁽²⁾

⁽¹⁾ Laboratoire de Spectroscopie Atomique associé au CNRS n 19, ISMRA et Université de Caen, 14050 Caen cedex, France

⁽²⁾ CIRIL, Laboratoire mixte CEA CNRS, B.P. 5133, 14040 Caen cedex, France

(Received 17 February 1993, revised 5 April 1994, accepted 30 May 1994)

Résumé. — Une source d'ions de recul, destinée à la réalisation d'expériences de collisions d'ions multichargés de très basse énergie, a été mise au point et testée sur la SME (Sortie à Moyenne Energie) du GANIL (Grand Accélérateur National d'Ions Lourds). L'efficacité des faisceaux de la SME pour la production d'ions de recul d'argon de hauts états de charge est mise en évidence (plus de 10^4 ions Ar^{15+} obtenus par seconde pour un faisceau d'ions projectiles de 300 nA d'ions Xe^{39+} de 4.7 MeV/A). Il est de plus démontré que les faisceaux produits par cette source peuvent être décélérés jusqu'à des énergies de l'ordre de quelques qeV sans perte importante d'intensité ni de qualité.

Abstract. — A recoil ion source, devoted to the production of very low energy multicharged ion beams which are of interest for charge exchange experiments, has been designed and tested at the SME (medium energy facility) of GANIL (heavy ion accelerator in Caen, France). The efficiency of SME beams for the production of high charge-states of argon recoil ions is demonstrated (more than 10^4 Ar^{15+} ions/s obtained with a 300 nA 4.7 MeV/A Xe^{39+} projectile ion beam). It is shown furthermore that these beams may be decelerated down to energies of some qeV without dramatic loss of intensity and quality.

Introduction.

Experimental results about charge exchange collisions at very low energy between multicharged ions and neutral targets deserve interest, not only from a fundamental point of view, but also for possible applications in the domains of astrophysical and fusion plasmas [1, 2]. Such results are relatively scarce, owing to the fact that production and handling of very low energy multicharged ion beams still constitute an experimental challenge. Concurrently to the method which consists in slowing down ion beams extracted from conventional (ECR or EBIS) electron impact ion sources, recoil ion sources (RIS) have been operated at several heavy ion

accelerators. RIS make use of a swift multicharged heavy ion beam to ionize the atoms or molecules of a gas-target and have been demonstrated to be efficient devices for the production of low energy multicharged ion beams with reasonable energy dispersion [3-7]. A swift multicharged heavy ion reveals indeed to be very efficient for stripping, in a single collision, a large number of electrons from a neutral target atom while imparting only a very small quantity of energy to its nucleus.

The ionization efficiency of accelerated heavy ions lies in the combined effects of their high charge-states and high velocities. The former insures efficient ionization of outer electrons of the target atom while the latter provides the possibility of inner shell ionizations further completed by Auger decay of the resulting excited ion. Low energy accelerators, such as Van de Graaf tandems which deliver ion beams in the MeV/A energy range, have been used successfully for the production of high charge-states of light elements like neon [4]. These accelerators revealed however deceiving for the production of highly charged recoil ions of argon. The velocities of their heavy ion beams are indeed too low to permit efficient hole creation in argon K-shell. Higher energy accelerators have of course been used and have proved, in principle, their efficiency for the production of high charge-state recoil ions for heavier elements. These have been Unilac at Darmstadt [8], Super Hilac at Berkeley [9] or GANIL at Caen [10], promising estimations have also been done concerning SIS-ESR at Darmstadt [11]. Nevertheless, an experimental program for the study of low energy collisions appears to be rather time consuming and hardly compatible with the saturated time schedule of such machines.

At GANIL however, the medium energy facility (SME) provides since 1990 intense beams ranging from ≈ 14 MeV/A argon to ≈ 4 MeV/A uranium ions. These beams are fully dedicated to atomic and solid-state physics and seem furthermore to be very well suited for the stripping of argon atoms. These are the reasons which have motivated our interest for the design of a new RIS adapted to this facility.

We present in this paper a description of the source and the results of tests which were performed at SME. These tests were mainly devoted to the evaluation of available intensities, energy dispersions and optical qualities of the RIS beams. The conditions upon which such beams may be slowed down are analysed in detail.

1. Experimental set-up.

The experimental set-up used (Fig. 1) consists in the RIS itself, completed by a set of detectors which allow the characterization of the extracted beam. The whole set-up, source plus detectors, is placed in a vacuum chamber which can be connected either to the GANIL beam line, or to an electron gun for « off line » test experiments.

1.1 THE RECOIL ION SOURCE. — Production of the recoil ions is performed by sending the projectile beam (parallel to the O_y direction of Fig. 1) through a gas cell from which a weak electric field (parallel to the O_z direction) extracts the recoil ion beam. This beam is then accelerated and focused in order to allow a good charge-state separation by the charge analysis device. The extracting and accelerating electric fields communicate to ions of charge q and mass m , velocities which are proportional to the square root of their q/m ratio. Charge-state analysis is then performed by a Wien-filter (WF) which is a velocity selective device. The charge-state selected ion beam may at last be decelerated to the desired energy value by mean of a retarding electric field.

1.1.1 Production and extraction. — The production of recoil ions takes place in a flat cylindrical differentially pumped gas cell. Two opposite 5 mm diameter holes permit the

Fig. 1. — Scheme of the experimental set-up.

passage of the projectile ion beam along a diameter of the cell, gas feeding and pressure measurements are performed through two different pipes also connected to the cell. The two insulated end caps of the cell, distant of 9 mm, constitute electrodes which, respectively biased to potentials V_1 and V_2 (with $V_1 > V_2$), allow to apply the extracting electric field (a few V/cm). Extraction thus occurs, perpendicularly to the projectile beam direction, at the centre of the cap at potential V_2 , through a 3 mm diameter hole. The quantity $V_1 - V_2$ will hereafter be referred to as « extraction voltage », while the quantity $V_0 = (V_1 + V_2)/2$ will be referred to as « mean acceleration voltage ».

1.1.2 Acceleration and focusing. — Beam acceleration is ensured by a set of five 90 mm diameter 1 mm thick plates. These plates are connected by a chain of resistors which allow to uniformly divide the accelerating voltage V_2 over the acceleration region. Three additional plates, among which the two extremes are grounded while the middle one is biased to a potential V_L , constitute a focusing Einzel-lens. In order to minimize fringing effects, the holes opened through the plates for the passage of the ion beam are covered with 90 % transparency nickel meshes, at each place in the experimental set-up where their position along the beam axis corresponds with a gradient of the electric field (except of course for the Einzel-lens).

1.1.3 Charge-state selection. — The ion beam is submitted in the WF to both an electric field $\mathbf{E}$ and a magnetic field $\mathbf{B}$ (respectively parallel to the Ox and Oy directions). An ion of velocity $\mathbf{v}$ and charge q will then feel, along the electric field direction, a force : $q(E - vB)$ which vanishes for a given velocity, provided that proper values of E and B are chosen. In the present case, the magnetic field is fixed and created by two 97 mm long, 30 mm wide permanent magnets which allow to reach a mean field value of 0.1 T across a 20 mm gap. The electric field is created by two 97 mm long 18 mm wide plates, distant of 30 mm and symmetrically biased to $\pm V_F$ in order to keep the axis of the filter at zero potential. The active length of the WF is limited by two soft iron rings D_1 and D_2 . A slit (2 mm width), parallel to the magnetic field, placed at 30 mm behind the output of the WF, allows to select the desired charge state.

1.1.4 Final energy adjustment. — Final energy adjustment consists in decelerating the charge-state selected beam. This is done over a distance of 50 mm by the mean of a retarding electric field, this field is produced by six plates which are connected by a chain of resistors allowing to uniformly divide the decelerating voltage V_D .

1.2 THE DETECTORS. — Two detectors are used in order to determine the intensity, the size and the divergence of the produced ion beam.

- A Faraday cup, equipped with a biased guard-ring, can be inserted between the output of the WF and the entrance of the decelerating stage, it allows to measure the absolute intensity of the charge-state selected beam before deceleration.

- A position sensitive detector (PSD) [12], made of a set of two microchannel plates (MCP) followed by a resistive anode, allows both to count the ions behind the deceleration stage and to localize their impact with a resolution of the order of 100 μm providing thus the intensity and the shape of the beam. As the distance between this PSD and the output of the ion source may be varied, information can furthermore be obtained on the divergence of the beam.

The ions have of course to be re-accelerated in order to ensure a good efficiency of the MCP detector, two additional plates are used for that purpose.

V_F or V_D voltages may at last be driven by a microcomputer which simultaneously allows to record the counts of the MCP detector.

2. Performances of the RIS.

Accelerator experiments have been preceded by numerical simulations and experimental tests using electrons issued from a 2 keV electron gun as ionizing projectiles. They enabled us to precisely define the ranges of acceleration V_2 and lens V_L voltage values through which proper charge-state selection and transport conditions of the RIS beam may be achieved.

Figure 2 demonstrates the effectiveness of the extraction and charge-state selection devices for high charge-states of argon recoils, as well as the ionization efficiency of a 4.7 MeV/A Xe^{39+} projectile beam.

Tests presented hereafter were performed at GANIL/SME, they have consisted in studying the influence on the intensities, shapes and energy dispersions of the obtained recoil ion beams, of various parameters which are : the pressure of the gas in the production cell, the extraction voltage V_1 - V_2 and the deceleration voltage V_D .

2.1 BEAM INTENSITY.

2.1.1 Influence of gas target pressure. — With increasing gas pressure in the target cell, the probability for producing a recoil ion with a given charge-state is expected to increase, as well as, due to electron capture, the probability for such an ion to have its charge state lowered before being extracted.

Fig. 2. — Number N of MCP detected ions *versus* Wien-filter voltage V_F (projectile beam : 4.7 MeV/A Xe^{39+} $V_1-V_2 = 2$ V, $V_s = 449$ V, $V_L = 465$ V, $V_D = 0$).

A very simple model allows to write the number N_q of extracted ions of charge q , if one neglects the re-population of this charge-state by electron capture from higher charge states :

$$N_q = N_p \cdot \sigma_q^i \cdot n \cdot \ell_1 \cdot (1 - n \cdot \sigma_q^c \cdot \ell_2)$$

where N_p is the number of projectile ions, σ_q^i and σ_q^c are respectively the total effective cross sections : for the production of a recoil ion of charge q and for electronic capture by such a recoil ion from a neutral argon target, ℓ_1 and ℓ_2 are respectively : the useful length of the gas cell along the projectile beam axis and the mean distance along which the recoil ions travel before leaving the cell, and n is the number of target atoms per unit volume in the gas cell. Such a relation describes a parabolic behaviour of N_q as a function of n with a maximum occurring for $\frac{1}{2 \cdot \sigma_q^c \cdot \ell_2}$. It allows at least to expect the existence of a finite optimum pressure

for the production of each beam with a given charge-state.

Figure 3 displays the variations of extracted argon beam intensities *versus* gas pressure into the cell. These intensities have been determined with the Faraday cup for charges $q = 1$ to 8 and with the MCP detector for charges $q = 4$ to 15. Calibration of MCP measurements with regard to Faraday cup measurements has been achieved using the results for charges $q = 4$ to 8 which could be measured with both detectors. Operation of the MCP detector is indeed limited to a maximum pressure in the cell of 4×10^{-3} Torr, beyond which the residual pressure in the experimental chamber ($> 2 \times 10^{-5}$ Torr) gets too high to allow the MCP detector to be switched on. For charge-states $q > 2$, the existence of optimum pressures for recoil ion production is clearly visible. One can notice that, in the frame of this model and in spite of its roughness :

Fig. 3. — Beam intensities N (ions/s) versus gas pressure into the target cell (projectile beam : 300 nA, 4.7 MeV/A Xe^{39+}). Full squares : measurements performed with the Faraday cup, Open circles : measurements performed with the MCP detector.

- the positions of the observed maxima ⁽¹⁾ (in the 10^{-3} - 10^{-2} Torr range) are compatible with realistic values of ℓ_2 (in the cm range) and σ_q^c (in the 10^{-14} - 10^{-15} cm² range) ;
- the shift of the observed maxima towards lower pressures for increasing q values qualitatively reflects, at least up to $q = 8$, the well known increase with q of σ_q^c values.

Figure 3 also allows to emphasize on the efficiency of the 4.7 MeV/A Xe^{39+} beam, which provides more than 10^4 Ar^{15+} ions per second, by comparing it to the efficiency of the 30 MeV Cl^{5+} beam used by the authors of reference [7], who quote 5×10^3 Ar^{6+} per second.

Captures which may occur from the residual gas along the transport path, will have different consequences according to whether they occur in the equipotential region, whether they occur during the extraction-acceleration stage. The ions for which a capture occurs in the equipotential region will constitute a component of lower charge-state in a beam of selected charge-state q , it will be shown further (see Sect. 2.3) that their number remains, in the percent range of the total number of ions in the beam. Ions having captured an electron during the acceleration stage will have different energies depending on the exact place at which the capture occurred, these ions will then be spread over the whole energy spectrum and contribute to a background appearing on spectra similar to the one displayed in figure 2. Such

⁽¹⁾ It is worth in practice to notice that the observed maxima occur for pressures which are fully compatible with satisfying beam transport and MCP operating conditions.

backgrounds have always been negligible, whatever the pressure used in the domain which has been explored, probably due to a fast drop of gas pressure along the recoil ion beam path after the output of the cell. At last, ions of charge $q + 1$ having captured an electron in the extraction region, very close to their production place, will have a charge q and an energy similar to ions directly produced with charge q , except for a slight difference corresponding to the energy gained during the charge exchange collision. Further experiments which will be described elsewhere, have allowed us to observe such ions in a ratio of only a few per cent of the main beam. Such a number of ions is actually too small to significantly perturb the energy dispersion measurements described in section 2.3. It remains however important to keep in mind the existence of such parasitic beams (having the same charge but not exactly the same energy or the same energy but not the same charge as the main beam) even of low intensity, since they can hinder future collision experiments making use of these beams except if convenient experimental procedures are used.

2.1.2 Influence of extraction voltage. — The recoil ion beam intensity has been determined using the Faraday cup, for fixed gas pressure and incident ion flux, as a function of extraction voltage V_1-V_2 . As shown in figure 4 the extraction efficiency, which drops of course for the lowest extraction voltages, remains otherwise almost independent of extraction voltage. Such a behaviour evidences the fact that for a sufficient extraction voltage all the produced ions are extracted from the cell. The slight maxima observed around $V_1-V_2 = 5$ V have already been observed by the authors of reference [7] and attributed by them to residual lens effects occurring, in spite of the presence of a grid at this place, at the passage through the extraction hole of the production cell.

Variations entirely similar to the one displayed in figure 4 have been observed for different gas pressures in the range 10^{-4} – 3×10^{-2} Torr.

Fig. 4. — Beam intensities N (ions/s) versus extraction voltage V_1-V_2 (projectile beam : 300 nA, 4.7 MeV/A Xe^{39+} gas pressure into the cell 10^{-3} Torr).

2.2 DIVERGENCE, EMITTANCE AND BRIGHTNESS OF THE BEAM. — The optical characteristics, divergence, emittance and brightness, of the charge state analysed beam will be considered in this paragraph. They are the one in which we are interested for further experiments making use of this beam and may be estimated using the previously described PSD.

Due in particular to the astigmatic focusing properties of the Wien filter [13], it is actually not possible to obtain a recoil ion beam focused exactly at the same point along z axis in directions parallel to Ox and Oy . Already mentioned preliminary tests, as well as verifications made during the experiment, have shown however that it was possible to find a value of the lens potential for which every recoil ion beam with charge state higher than $q = 3$ could be considered as reasonably focused in both directions somewhere between the output of the WF and the point of closest approach of the detector which is situated at 135 mm from this output. With a mean extraction voltage $V_0 = 450$ V these conditions are for instance obtained for a V_L value of about 470 V.

The observed characteristic dimensions Δx and Δy (fwhm) of recoil ion beams of charge states $q = 5, 10$ and 14 , determined at distances of 135, 235 and 335 mm from the output of the Wien filter, are given in table I. Also given in this table are the divergences $\Delta\theta_x$ and $\Delta\theta_y$ which may be deduced from these values.

Considering Δx and Δy values obtained at 135 mm from the output of the WF as the size of the focused beam ⁽²⁾ and using the determined divergences values, one can deduce upper limits for the normalized transverse emittances defined as :

$$\varepsilon_x = \pi \cdot \Delta x \cdot \Delta\theta_y \cdot V/c \quad \text{and} \quad \varepsilon_y = \pi \cdot \Delta y \cdot \Delta\theta_x \cdot V/c$$

where V is the longitudinal velocity of the recoil ion beam and c the speed of light [1]. The corresponding values are given in table I.

Table I gives at last, according to the characteristic current I (particle-pA) obtained for each charge state (see for instance Fig. 3), lower limits for the emittance normalized brightness :

$$Br = I/\varepsilon_x \cdot \varepsilon_y.$$

Table I. — Dimensions Δ , divergences $\Delta\theta$, emittances ε and brilliances Br of Ar^{5+} , 10^{+} and 14^{+} beams (projectile beam : 4.7 MeV/A Xe^{39+} , $V_1-V_2 = 2$ V, $V_2 = 449$ V, $V_L = 465$ V, $V_D = 0$).

Charge-state q	5^{+}	10^{+}	14^{+}
Δ_x/Δ_y (135 mm) : fwhm mm	$\pm 0.9/\pm 2.1$	$\pm 0.7/\pm 1.7$	$\pm 0.6/\pm 1.9$
Δ_x/Δ_y (235 mm) : fwhm mm	$\pm 1.3/\pm 2.9$	$\pm 1.4/\pm 2.5$	$\pm 1.8/\pm 3$
Δ_x/Δ_y (335 mm) : fwhm mm	$\pm 1.7/\pm 3.6$	$\pm 2.1/\pm 3.2$	$\pm 3/\pm 3.9$
$\Delta\theta_x/\Delta\theta_y$: mrad	$\pm 4/\pm 7.5$	$\pm 7/\pm 7.5$	$\pm 12/\pm 10$
$\varepsilon_x/\varepsilon_y$: π mm mrad	$1.25 \times 10^{-3}/5 \times 10^{-3}$	$2.5 \times 10^{-3}/6 \times 10^{-3}$	$4.5 \times 10^{-3}/10^{-2}$
Br : part. pA/(π mm mrad) ²	1.6×10^4	4.8×10^2	16

⁽²⁾ These values are actually in excess since the different beams are more or less focused in front of this position.

Divergences are observed to increase with charge state, $\Delta\theta_{\perp}$ increasing even more rapidly than $\Delta\theta_{\parallel}$. This is not surprising, the optical characteristics of the beam are indeed expected to evolve with charge-state in different ways along directions parallel to Ox and Oy due to various phenomena such as the anisotropy of recoil velocities (large recoil velocity component in the xOz plan) [1, 14] and the chromaticity of the transport beam line.

2.3 ENERGY DISPERSION, SLOWING DOWN OF THE BEAM. — Slowing down and determining the energy dispersion of the beam are of course tightly bound problems : energy dispersion limits indeed on the one hand the possibility of slowing down the beam, the slowing down procedure provides us on the other hand with a way of determining the energy dispersion.

2.3.1 Intensity of the decelerated beam. — In order to analyse the energy dispersion of the beam, the retarding field method has been used. The principle of the method consists in detecting, for a selected charge-state q , the number of ions reaching the MCP detector as a function of increasing values of the deceleration voltage V_D .

As long as V_D remains smaller than V_0 , the intensity of the decelerated beam does not vary significantly (Fig. 5). For $V_D = V_0$, the number of counts suddenly decreases ⁽³⁾. This decrease corresponds to the repulsion towards the WF of the ions of charge-state q . For values of $V_D > V_0$ the recorded signal (less than 2 % of the initial one in the particular case of Fig. 5) corresponds to the MCP background plus the signal due to ions having decreased their charge state by electron capture during the transport from the end of the acceleration stage.

Fig. 5. — Number of Ar^{9+} recoil ions detected on the MCP detector *versus* deceleration voltage V_D ($V_1 - V_2 = 2$ V, $V_2 = 449$ V).

One observes actually (as it can be seen even more clearly in figure 8) that the decrease of the beam intensity around $V_D = V_0$ has a certain width ΔV_D from which the energy dispersion $q \cdot \Delta V_D$ of the beam can be obtained.

The three components of the observed recoil ion beam energy dispersions are expected to be :

- the energy dispersion introduced by the difference of extraction voltage across the width

⁽³⁾ It is important to notice the fact that the V_D value for which half of the ions are repelled occurs precisely for $V_D = V_0$ (Fig. 5 and Fig. 8) since it attests for the good control which can be kept over the beam energy even for the highest deceleration values.

of the primary beam ΔE_{ext} (with a primary beam width of 3 mm and an extraction field of 3 V/cm for instance, an energy dispersion of ≈ 0.9 qeV is expected) ;

- the instrumental dispersion ΔE_I including the effect of imperfect transport optic conditions and the limited resolution of our energy analysis method ;

- the initial energy dispersion of the recoil ions ΔE_R which, if one neglects the thermal energy of the target atoms, is due to the recoil energy imparted to the ions during the collision in which they are created and increases with increasing recoil ion charge-state [14, 15].

Experimental values of ΔV_D are given in figure 6 for charge-states $q = 1, 10$ and 14 of argon, *versus* the extraction voltage $V_1 - V_2$. ΔV_D presents, for each charge-state, a linear variation which may obviously be attributed to the proportionality of ΔE_{ext} and $V_1 - V_2$. The observed slope, proportional to the diameter of the projectile beam used, depends on q state. Adjustment of the counting rate of the detector is indeed performed by « cutting » into the projectile beam emittance, smaller (resp. higher) beam diameters and thus slopes then correspond to charge-states which are more (resp. less) abundant.

Fig. 6. — Evolution of the width ΔV_D of the deceleration curve *versus* the extraction voltage $V_1 - V_2$, for various charge-states.

For each charge-state, extrapolation of ΔV_D to $V_1 - V_2 = 0$ leads to the determination of $\Delta E_I + \Delta E_R$. Previous experimental results [14] have shown that in the particular case of Ar^{1+} , ΔE_R may be considered as negligible. Extrapolation of ΔV_D to $V_1 - V_2 \approx 0$ for Ar^{1+} then provides an estimation of 1.6 qeV for ΔE_I . If we assume this determination to be valid for any charge-state, we obtain ΔE_R estimations of respectively 0.2 and 1.6 qeV for charges $q = 10$ and 14 .

It does not exist, at our knowledge, experimental determinations of recoil energies which are

directly comparable to these values. However, using on the one hand the recoil energies obtained by Grandin *et al.* [14] with a projectile beam of 27 MeV/A Xe^{52+} ions, using on the other hand the Z_p^2/E_p variation law mentioned by Schlachter [16] for the dependence of recoil energies on projectile charge Z_p and energy E_p , one deduces values of 0.1 and 0.9 qeV for the mean recoil energies of charge-state 10 and 14. These values are perfectly consistent with the ΔE_R values obtained in the present experiment if we consider ΔE_R to be equivalent to twice the mean recoil energy.

2.3.2 Shape of the decelerated beam. — It is worth at this point to wonder about the meaning of the pattern observed on the position sensitive detector for such a decelerated re-accelerated beam (Fig. 1). As in fact the re-acceleration occurs on a distance which represents only 2/5 of the length of the deceleration region, the re-acceleration time represents less than 15 % of the total time which separates the beginning of the deceleration from the detection time. The pattern observed on the PSD may consequently be considered as a close image of the beam at its point of lowest velocity.

Such patterns, obtained for an Ar^{15+} beam with a mean acceleration voltage $V_0 = 450$ V ($V_1 = 451$ V, $V_2 = 449$ V) and six different values of V_D ranging from 0 to 455 V, are displayed in figure 7.

Fig. 7. — Experimental profiles (Ox direction) of a recoil ion beam, the selected charge-state is 15^+ , the mean acceleration voltage $V_0 = 450$ V, the deceleration voltage $V_D = 0$ V (a), 440 V (b), 449 V (c), 449.5 V (d), 450 V (e), 455 V (f).

Figure 8 shows the deceleration curve obtained for the same beams as explained previously. From this deceleration curve a ΔV_D value of 4.5 V is deduced.

The following remarks arise from the simultaneous observation of the patterns of figure 7 and of the corresponding beam intensities in figure 8 :

Fig. 8. — Number of recoil ions detected *versus* deceleration voltage V_D , same beam as for figure 7.

- the beam observed in figure 7f no longer corresponds of course to Ar^{15+} ions but to ions having changed their charge-state by electron capture ; the total number of these ions, once deduced the background count of the MCP, amounts to about 10 % of the selected beam ;
- down to energies of about 10 qeV the recoil ion beam may be slowed down without appreciable loss of intensity and deterioration of shape figures 7a, b ;
- for a more severe slowing down, the observed loss of intensity allows to limit the broadening of the beam as observed from figures 7c, d, e.

The observation of a correct shape of the beam, even for the lowest energies, may be attributed to the particular velocity distribution in the beam which is a consequence of the initial non thermal recoil ion velocity distribution : the last ions to be rejected in the course of the slowing down are indeed those which have the largest velocity components towards the detector and thus small velocity components in directions perpendicular to the recoil ion beam axis.

Conclusion.

We have designed and tested at GANIL/SME a recoil ion source which can deliver very low energy beams of high charge-stage argon ions. The characteristics of these beams are such that their use in low energy charge exchange collision experiments may be immediately considered. These encouraging results are, for a large part, to be attributed to the excellent quality of the projectile ion beams available at GANIL/SME. Improvements which are now being brought to this accelerator will lead to increased intensities for the projectile beams and allow to anticipate even higher performances of our apparatus.

References

- [1] Cocke C. L., Olson R. E., Recoil ions, *Phys. Rep.* **205** (1991) 155-219.
- [2] Tawara H., Phaneuf R. A., Atomic and Molecular Data Requirements for Fusion Plasma Edge Studies, *Comments At. Mol. Phys.* **21** (1988) 177-193.
- [3] Justiniano E., Cocke C. L., Gray T. J., Dubois R. D., Charge transfer and ionization in low-energy $\text{Ar}^{q+} + \text{Ne}$ collisions, *Phys. Rev. A* **24** (1981) 2953-2962.
- [4] Lembo L. J., Danzmann K., Stoller Ch., Meyerhof W. E., Hänsch T. W., Core effects on the polarization of optical Rydberg transitions following electron capture into slow, highly ionized neon recoil ions, *Phys. Rev. A* **37** (1988) 1141-1151.
- [5] Nielsen E. H., Andersen L. H., Barany A., Cederquist H., Heinemeier J., Hvelplund P., Knudsen H., Mc Adam K. B., Sorensen J., Energy-gain spectroscopy of state-selective electron capture for multiply charged Ar recoil ions, *J. Phys. B. At. Mol. Phys.* **18** (1985) 1789-1808.
- [6] Mc Cullough R. W., Wilson S. M. and Gilbody H. B., State-selective capture by slow Ar^{4+} , Ar^{5+} and Ar^{6+} recoil ions in H, H_2 and He, *J. Phys. B. At. Mol. Phys.* **20** (1987) 2031-2055.
- [7] Cederquist H., Biedermann C., Levin J. C., Sellin I. A., Short R. T., Production of highly-charged recoil-ion beams at very low energy, *N.I.M. B* **34** (1988) 243-251.
- [8] Mann R., Total One-Electron Capture Cross Sections for Ar^{q+} and I^{q+} Ions in Slow Collisions on H_2 and He, *Z. Phys. D Atoms Molecular Cluster* **3** (1986) 85-90.
- [9] Mann R., Cocke C. L., Schlachter A. S., Prior M. and Marrus R., Selective Final-State Population in Electron Capture by Low-Energy Highly Charged Projectiles Studied by Energy-Gain Spectroscopy, *Phys. Rev. Lett.* **49** (1982) 1329-1332.
- [10] Hennecart D., Husson X., Leclerc D., Lesteven-Vaïsse I., Grandin J. P., Multiple ionization of rare gases target atoms by 27 MeV/amu Xe^{52+} and 35 MeV/amu Kr^{36+} ions, *Rad. Eff. Def. Solids* **110** (1989) 141-143.
- [11] Ullrich J., Cocke C. L., Kelbch S., Mann R., Richard P., Schmidt-Böcking H., A parasite ion source for bare-ion production on a high-energy heavy-ion accelerator, *J. Phys. B. At. Mol. Phys.* **17** (1984) L 785-790.
- [12] Malic R. A., Improved LEED system using position-sensitive detection, *Rev. Sci. Instrum.* **9** (1988) 1951-1953.
- [13] Seliger R. L., E $\times$ B Mass-Separator Design, *J. Appl. Phys.* **43** (1972) 2352-2357.
- [14] Grandin J. P., Hennecart D., Husson X., Leclerc D., Lesteven-Vaïsse I., Lisfi D., Recoil Energy of Highly Charged Ions Produced in Swift Ion-Atom Collisions as Deduced from Time-of-Flight Measurements, *Europhys. Lett.* **6** (1988) 683-688.
- [15] Ullrich J., Olson R., Schmidt-Böcking H., Schmidt S., Dörner R., Dangendorf V., Berg H., Multiple ionisation and collective electron emission in MeV/u uranium-ion rare gas collisions, *J. Phys. Colloq. France* **50** (1989) C1-29-C1-36.
- [16] Schlachter A. S., Groch W., Müller A., Beyer H. F., Mann R., Olson R. E., Production of highly charged rare-gas recoil ions by 1.4 MeV/amu U^{44+} *Phys. Rev. A* **26** (1982) 1373-1377.

Commission paritaire N 57920

© Les Editions de Physique 1994

Directrice de la Publication Jeanne BERGER

Short Communications saisie, composition **MATHOR5-TEX**
Other Communications saisie MATHOR, composition PHOTOMAT
Impression JOUVE 18, rue Saint-Denis, 75001 PARIS
N° 219706B Dépôt légal Septembre 1994