Sb (P, As OR F) - DOPED SnO_2 FILMS PREPARED BY MOCVD

W. LUO, C. TAN, P. REN and Z. TAN

*Qingdao Institute of Chemical Technology, Center for
Functional Materials Research, 53 Zhengzhou Road, Qingdao,
266042, China*

Abstract Metallorganic chemical vapour deposition (MOCVD) is employed for the growth of Sb(P, As or F) doped thin films of SnO_2 . Using $(\text{CH}_3)_4\text{Sn}$ (TMT) as a tin source, oxygen-argon mixture as the carrier gas and Sb (P, As or F) as dopants, we have obtained four kinds of doped SnO_2 films on different substrates.

These films (thickness 10^2 - $10^3 \text{\AA}$) possess sheet resistances of 30-40 $\Omega/\square$ and transmissivities up to 85-95% in the visible spectral region. The experiments show that the doping causes a change of orientation of SnO_2 crystallites. The films can exhibit a rapid transition from being polycrystalline to becoming amorphous when excess dopant is used.

The structure for the four kinds of doped films and the photoelectrochemical behaviour on silicon single crystals as electrodes are also reported. The experiments show the photoresponse of silicon photocathodes with doped films is larger than that without doping. The silicon electrode coated with the doped film as a heterostructure photocathode for photoelectrolysis of water can increase the potential of hydrogen evolved towards the positive direction.